



cuSPARSE Library

Table of Contents

Chapter 1. Introduction.....	1
1.1. Naming Conventions.....	1
1.2. Asynchronous Execution.....	2
1.3. Static Library support.....	2
Chapter 2. Using the cuSPARSE API.....	4
2.1. Thread Safety.....	4
2.2. Scalar Parameters.....	4
2.3. Parallelism with Streams.....	4
2.4. Compatibility and Versioning.....	5
2.5. Optimization Notes.....	5
Chapter 3. cuSPARSE Indexing and Data Formats.....	6
3.1. Index Base Format.....	6
3.1.1. Vector Formats.....	6
3.1.1.1. Dense Format.....	6
3.1.1.2. Sparse Format.....	6
3.2. Matrix Formats.....	7
3.2.1. Dense Format.....	7
3.2.2. Coordinate Format (COO).....	8
3.2.3. Compressed Sparse Row Format (CSR).....	8
3.2.4. Compressed Sparse Column Format (CSC).....	9
3.2.5. Block Compressed Sparse Row Format (BSR).....	10
3.2.6. Extended BSR Format (BSRX).....	12
Chapter 4. cuSPARSE Types Reference.....	14
4.1. Data types.....	14
4.2. cusparseStatus_t.....	14
4.3. cusparseHandle_t.....	15
4.4. cusparsePointerMode_t.....	16
4.5. cusparseOperation_t.....	16
4.6. cusparseAction_t.....	16
4.7. cusparseDirection_t.....	16
4.8. cusparseMatDescr_t.....	17
4.8.1. cusparseDiagType_t.....	17
4.8.2. cusparseFillMode_t.....	17
4.8.3. cusparseIndexBase_t.....	17
4.8.4. cusparseMatrixType_t.....	18

4.9. cusparseAlgMode_t [DEPRECATED].....	18
4.10. cusparseColorInfo_t.....	18
4.11. cusparseSolvePolicy_t.....	19
4.12. bsrlic02Info_t.....	19
4.13. bsrilu02Info_t.....	19
4.14. bsrrsm2Info_t.....	19
4.15. bsrrsv2Info_t.....	19
4.16. csrgemm2Info_t [DEPRECATED].....	19
4.17. csrlc02Info_t.....	20
4.18. csrlu02Info_t.....	20
4.19. csrrsm2Info_t [DEPRECATED].....	20
4.20. csrrsv2Info_t [DEPRECATED].....	20
Chapter 5. cuSPARSE Management Function Reference.....	21
5.1. cusparseCreate().....	21
5.2. cusparseDestroy().....	21
5.3. cusparseGetErrorName().....	22
5.4. cusparseGetErrorString().....	22
5.5. cusparseGetProperty().....	22
5.6. cusparseGetVersion().....	23
5.7. cusparseGetPointerMode().....	23
5.8. cusparseSetPointerMode().....	23
5.9. cusparseGetStream().....	24
5.10. cusparseSetStream().....	24
Chapter 6. cuSPARSE Logging.....	25
6.1. cusparseLoggerSetCallback().....	26
6.2. cusparseLoggerSetFile().....	26
6.3. cusparseLoggerOpenFile().....	26
6.4. cusparseLoggerSetLevel().....	27
6.5. cusparseLoggerSetMask().....	27
6.6. cublasLtLoggerForceDisable().....	27
Chapter 7. cuSPARSE Helper Function Reference.....	28
7.1. cusparseCreateColorInfo().....	28
7.2. cusparseCreateMatDescr().....	28
7.3. cusparseDestroyColorInfo().....	28
7.4. cusparseDestroyMatDescr().....	29
7.5. cusparseGetMatDiagType().....	29
7.6. cusparseGetMatFillMode().....	29
7.7. cusparseGetMatIndexBase().....	30

7.8. cusparseGetMatType()	30
7.9. cusparseSetMatDiagType()	30
7.10. cusparseSetMatFillMode()	31
7.11. cusparseSetMatIndexBase()	31
7.12. cusparseSetMatType()	31
7.13. cusparseCreateCsrsv2Info() [DEPRECATED]	32
7.14. cusparseDestroyCsrsv2Info() [DEPRECATED]	32
7.15. cusparseCreateCsrs2Info() [DEPRECATED]	32
7.16. cusparseDestroyCsrs2Info() [DEPRECATED]	33
7.17. cusparseCreateCsr2Info()	33
7.18. cusparseDestroyCsr2Info()	33
7.19. cusparseCreateCsrilu2Info()	34
7.20. cusparseDestroyCsrilu2Info()	34
7.21. cusparseCreateBsrsv2Info()	34
7.22. cusparseDestroyBsrsv2Info()	35
7.23. cusparseCreateBsr2Info()	35
7.24. cusparseDestroyBsr2Info()	35
7.25. cusparseCreateBsr2Info()	36
7.26. cusparseDestroyBsr2Info()	36
7.27. cusparseCreateBsrilu2Info()	36
7.28. cusparseDestroyBsrilu2Info()	37
7.29. cusparseCreateCsrsgemm2Info() [DEPRECATED]	37
7.30. cusparseDestroyCsrsgemm2Info() [DEPRECATED]	37
7.31. cusparseCreatePruneInfo()	38
7.32. cusparseDestroyPruneInfo()	38
Chapter 8. cuSPARSE Level 1 Function Reference	39
8.1. cusparse<t>axpyi() [DEPRECATED]	39
8.2. cusparse<t>gthr() [DEPRECATED]	40
8.3. cusparse<t>gthrz() [DEPRECATED]	42
8.4. cusparse<t>roti() [DEPRECATED]	43
8.5. cusparse<t>sctr() [DEPRECATED]	44
Chapter 9. cuSPARSE Level 2 Function Reference	46
9.1. cusparse<t>bsrmv()	46
9.2. cusparse<t>bsrxmv()	49
9.3. cusparse<t>bsrsv2_bufferSize()	53
9.4. cusparse<t>bsrsv2_analysis()	55
9.5. cusparse<t>bsrsv2_solve()	58
9.6. cusparseXbsrsv2_zeroPivot()	62

9.7. <code>cusparseCsrmmvEx()</code> [DEPRECATED].....	63
9.8. <code>cusparse<t>csrsv2_bufferSize()</code> [DEPRECATED].....	65
9.9. <code>cusparse<t>csrsv2_analysis()</code> [DEPRECATED].....	67
9.10. <code>cusparse<t>csrsv2_solve()</code> [DEPRECATED].....	69
9.11. <code>cusparseXcsrsv2_zeroPivot()</code> [DEPRECATED].....	73
9.12. <code>cusparse<t>gemvi()</code>	74
Chapter 10. cuSPARSE Level 3 Function Reference.....	78
10.1. <code>cusparse<t>bsrmm()</code>	78
10.2. <code>cusparse<t>bsrsm2_bufferSize()</code>	82
10.3. <code>cusparse<t>bsrsm2_analysis()</code>	85
10.4. <code>cusparse<t>bsrsm2_solve()</code>	88
10.5. <code>cusparseXbsrsm2_zeroPivot()</code>	91
10.6. <code>cusparse<t>csrsm2_bufferSizeExt()</code> [DEPRECATED].....	92
10.7. <code>cusparse<t>csrsm2_analysis()</code> [DEPRECATED].....	95
10.8. <code>cusparse<t>csrsm2_solve()</code> [DEPRECATED].....	98
10.9. <code>cusparseXcsrsm2_zeroPivot()</code> [DEPRECATED].....	101
10.10. <code>cusparse<t>gemmi()</code> [DEPRECATED].....	102
Chapter 11. cuSPARSE Extra Function Reference.....	105
11.1. <code>cusparse<t>csrgeam2()</code>	105
11.2. <code>cusparse<t>csrsgemm2()</code> [DEPRECATED].....	111
Chapter 12. cuSPARSE Preconditioners Reference.....	119
12.1. Incomplete Cholesky Factorization: level 0.....	119
12.1.1. <code>cusparse<t>csric02_bufferSize()</code>	119
12.1.2. <code>cusparse<t>csric02_analysis()</code>	121
12.1.3. <code>cusparse<t>csric02()</code>	123
12.1.4. <code>cusparseXcsric02_zeroPivot()</code>	127
12.1.5. <code>cusparse<t>bsric02_bufferSize()</code>	128
12.1.6. <code>cusparse<t>bsric02_analysis()</code>	130
12.1.7. <code>cusparse<t>bsric02()</code>	132
12.1.8. <code>cusparseXbsric02_zeroPivot()</code>	137
12.2. Incomplete LU Factorization: level 0.....	137
12.2.1. <code>cusparse<t>csrilu02_numericBoost()</code>	137
12.2.2. <code>cusparse<t>csrilu02_bufferSize()</code>	139
12.2.3. <code>cusparse<t>csrilu02_analysis()</code>	140
12.2.4. <code>cusparse<t>csrilu02()</code>	142
12.2.5. <code>cusparseXcsrilu02_zeroPivot()</code>	146
12.2.6. <code>cusparse<t>bsrilu02_numericBoost()</code>	147
12.2.7. <code>cusparse<t>bsrilu02_bufferSize()</code>	148

12.2.8. <code>cusparse<t>bsrilu02_analysis()</code>	150
12.2.9. <code>cusparse<t>bsrilu02()</code>	153
12.2.10. <code>cusparseXbsrilu02_zeroPivot()</code>	157
12.3. Tridiagonal Solve.....	158
12.3.1. <code>cusparse<t>gtsv2_buffSizeExt()</code>	158
12.3.2. <code>cusparse<t>gtsv2()</code>	160
12.3.3. <code>cusparse<t>gtsv2_nopivot_bufferSizeExt()</code>	162
12.3.4. <code>cusparse<t>gtsv2_nopivot()</code>	163
12.4. Batched Tridiagonal Solve.....	165
12.4.1. <code>cusparse<t>gtsv2StridedBatch_bufferSizeExt()</code>	165
12.4.2. <code>cusparse<t>gtsv2StridedBatch()</code>	167
12.4.3. <code>cusparse<t>gtsvInterleavedBatch()</code>	169
12.5. Batched Pentadiagonal Solve.....	172
12.5.1. <code>cusparse<t>gpsvInterleavedBatch()</code>	172
Chapter 13. cuSPARSE Reorderings Reference.....	177
13.1. <code>cusparse<t>csrColor()</code>	177
Chapter 14. cuSPARSE Format Conversion Reference.....	180
14.1. <code>cusparse<t>bsr2csr()</code>	180
14.2. <code>cusparse<t>gebsr2gebbsc()</code>	183
14.3. <code>cusparse<t>gebsr2gebsr()</code>	186
14.4. <code>cusparse<t>gebsr2csr()</code>	191
14.5. <code>cusparse<t>csr2gebsr()</code>	194
14.6. <code>cusparse<t>coo2csr()</code>	198
14.7. <code>cusparse<t>csc2dense()</code> [DEPRECATED].....	199
14.8. <code>cusparse<t>csr2bsr()</code>	201
14.9. <code>cusparse<t>csr2coo()</code>	204
14.10. <code>cusparseCsr2cscEx2()</code>	205
14.11. <code>cusparse<t>csr2dense()</code> [DEPRECATED].....	207
14.12. <code>cusparse<t>csr2csr_compress()</code>	208
14.13. <code>cusparse<t>dense2csc()</code> [DEPRECATED].....	212
14.14. <code>cusparse<t>dense2csr()</code> [DEPRECATED].....	214
14.15. <code>cusparse<t>nnz()</code>	216
14.16. <code>cusparseCreateIdentityPermutation()</code>	217
14.17. <code>cusparseXcoosort()</code>	218
14.18. <code>cusparseXcsrsort()</code>	219
14.19. <code>cusparseXcscsort()</code>	221
14.20. <code>cusparseXcsru2csr()</code>	223
14.21. <code>cusparseXpruneDense2csr()</code>	228

14.22. <code>cusparseXpruneCsr2csr()</code>	231
14.23. <code>cusparseXpruneDense2csrPercentage()</code>	235
14.24. <code>cusparseXpruneCsr2csrByPercentage()</code>	239
14.25. <code>cusparse<t>nnz_compress()</code>	244
Chapter 15. cuSPARSE Generic API Reference	247
15.1. Generic Types Reference.....	247
15.1.1. <code>cudaDataType_t</code>	247
15.1.2. <code>cusparseFormat_t</code>	248
15.1.3. <code>cusparseOrder_t</code>	248
15.1.4. <code>cusparseIndexType_t</code>	249
15.2. Sparse Vector APIs.....	249
15.2.1. <code>cusparseCreateSpVec()</code>	249
15.2.2. <code>cusparseDestroySpVec()</code>	250
15.2.3. <code>cusparseSpVecGet()</code>	250
15.2.4. <code>cusparseSpVecGetIndexBase()</code>	250
15.2.5. <code>cusparseSpVecGetValues()</code>	251
15.2.6. <code>cusparseSpVecSetValues()</code>	251
15.3. Sparse Matrix APIs.....	251
15.3.1. <code>cusparseCreateCoo()</code>	251
15.3.2. <code>cusparseCreateCooAoS()</code> [DEPRECATED].....	252
15.3.3. <code>cusparseCreateCsr()</code>	253
15.3.4. <code>cusparseCreateCsc()</code>	254
15.3.5. <code>cusparseCreateBlockedEll()</code>	254
15.3.6. <code>cusparseDestroySpMat()</code>	256
15.3.7. <code>cusparseCooGet()</code>	256
15.3.8. <code>cusparseCooAoSGet()</code> [DEPRECATED].....	257
15.3.9. <code>cusparseCsrGet()</code>	257
15.3.10. <code>cusparseCsrSetPointers()</code>	258
15.3.11. <code>cusparseCscSetPointers()</code>	258
15.3.12. <code>cusparseCooSetPointers()</code>	259
15.3.13. <code>cusparseBlockedEllGet()</code>	259
15.3.14. <code>cusparseSpMatGetSize()</code>	260
15.3.15. <code>cusparseSpMatGetFormat()</code>	260
15.3.16. <code>cusparseSpMatGetIndexBase()</code>	261
15.3.17. <code>cusparseSpMatGetValues()</code>	261
15.3.18. <code>cusparseSpMatSetValues()</code>	261
15.3.19. <code>cusparseSpMatGetStridedBatch()</code>	262
15.3.20. <code>cusparseSpMatSetStridedBatch()</code> [DEPRECATED].....	262

15.3.21. cusparseCooSetStridedBatch()	262
15.3.22. cusparseCsrSetStridedBatch()	263
15.3.23. cusparseSpMatGetAttribute()	263
15.3.24. cusparseSpMatSetAttribute()	264
15.4. Dense Vector APIs	265
15.4.1. cusparseCreateDnVec()	265
15.4.2. cusparseDestroyDnVec()	265
15.4.3. cusparseDnVecGet()	265
15.4.4. cusparseDnVecGetValues()	266
15.4.5. cusparseDnVecSetValues()	266
15.5. Dense Matrix APIs	266
15.5.1. cusparseCreateDnMat()	266
15.5.2. cusparseDestroyDnMat()	267
15.5.3. cusparseDnMatGet()	267
15.5.4. cusparseDnMatGetValues()	268
15.5.5. cusparseDnSetValues()	268
15.5.6. cusparseDnMatGetStridedBatch()	268
15.5.7. cusparseDnMatSetStridedBatch()	269
15.6. Generic API Functions	269
15.6.1. cusparseSparseToDense()	269
15.6.2. cusparseDenseToSparse()	271
15.6.3. cusparseAxpby()	273
15.6.4. cusparseGather()	274
15.6.5. cusparseScatter()	275
15.6.6. cusparseRot()	277
15.6.7. cusparseSpVV()	278
15.6.8. cusparseSpMV()	280
15.6.9. cusparseSpSV()	283
15.6.10. cusparseSpMM()	286
15.6.11. cusparseSpMMOp()	293
15.6.12. cusparseSpSM()	295
15.6.13. cusparseConstrainedGeMM() [DEPRECATED]	299
15.6.14. cusparseSDDMM()	299
15.6.15. cusparseSpGEMM()	302
15.6.16. cusparseSpGEMMreuse()	305
Chapter 16. Appendix A: cuSPARSE Fortran Bindings	309
16.1. Fortran Application	310
Chapter 17. Appendix B: Examples of prune	318

17.1. Prune Dense to Sparse.....	318
17.2. Prune Sparse to Sparse.....	322
17.3. Prune Dense to Sparse by Percentage.....	326
17.4. Prune Sparse to Sparse by Percentage.....	330
Chapter 18. Appendix C: Examples of csrsm2.....	335
18.1. Forward Triangular Solver.....	335
Chapter 19. Appendix D: Acknowledgements.....	340
Chapter 20. Bibliography.....	341

List of Figures

Figure 1. Blocked-ELL representation	255
--	-----

Chapter 1. Introduction

The cuSPARSE library contains a set of basic linear algebra subroutines used for handling sparse matrices. The library targets matrices with a number of (structural) zero elements which represent > 95% of the total entries.

Provide Feedback: Math-Libs-Feedback@nvidia.com

It is implemented on top of the NVIDIA® CUDA™ runtime (which is part of the CUDA Toolkit) and is designed to be called from C and C++.

The library routines can be classified into four categories:

- ▶ Level 1: operations between a vector in sparse format and a vector in dense format
- ▶ Level 2: operations between a matrix in sparse format and a vector in dense format
- ▶ Level 3: operations between a matrix in sparse format and a set of vectors in dense format (which can also usually be viewed as a dense tall matrix)
- ▶ Conversion: operations that allow conversion between different matrix formats, and compression of csr matrices.

The cuSPARSE library allows developers to access the computational resources of the NVIDIA graphics processing unit (GPU), although it does not auto-parallelize across multiple GPUs. The cuSPARSE API assumes that input and output data reside in GPU (device) memory, unless it is explicitly indicated otherwise by the string `DevHostPtr` in a function parameter's name.

It is the responsibility of the developer to allocate memory and to copy data between GPU memory and CPU memory using standard CUDA runtime API routines, such as `cudaMalloc()`, `cudaFree()`, `cudaMemcpy()`, and `cudaMemcpyAsync()`.

1.1. Naming Conventions

The cuSPARSE library functions are available for data types `float`, `double`, `cuComplex`, and `cuDoubleComplex`. The sparse Level 1, Level 2, and Level 3 functions follow this naming convention:

```
cusparse<t>[<matrix data format>]<operation>[<output matrix data format>]
```

where `<t>` can be `S`, `D`, `C`, `Z`, or `X`, corresponding to the data types `float`, `double`, `cuComplex`, `cuDoubleComplex`, and the generic type, respectively.

The `<matrix data format>` can be `dense`, `coo`, `csc`, or `csc`, corresponding to the dense, coordinate, compressed sparse row, and compressed sparse column formats, respectively.

Finally, the `<operation>` can be `axpyi`, `gthr`, `gthrz`, `roti`, or `sctr`, corresponding to the Level 1 functions; it also can be `mv` or `sv`, corresponding to the Level 2 functions, as well as `mm` or `sm`, corresponding to the Level 3 functions.

All of the functions have the return type `cusparseStatus_t` and are explained in more detail in the chapters that follow.

1.2. Asynchronous Execution

The cuSPARSE library functions are executed asynchronously with respect to the host and may return control to the application on the host before the result is ready. Developers can use the `cudaDeviceSynchronize()` function to ensure that the execution of a particular cuSPARSE library routine has completed.

A developer can also use the `cudaMemcpy()` routine to copy data from the device to the host and vice versa, using the `cudaMemcpyDeviceToHost` and `cudaMemcpyHostToDevice` parameters, respectively. In this case there is no need to add a call to `cudaDeviceSynchronize()` because the call to `cudaMemcpy()` with the above parameters is blocking and completes only when the results are ready on the host.

1.3. Static Library support

Starting with release 6.5, the cuSPARSE Library is also delivered in a static form as `libcusparse_static.a` on Linux and Mac OSes. The static cuSPARSE library and all other static maths libraries depend on a common thread abstraction layer library called `libcubos.a` on Linux and Mac and `culibos.lib` on Windows.

For example, on linux, to compile a small application using cuSPARSE against the dynamic library, the following command can be used:

```
nvcc myCusparseApp.c -lcusparse -o myCusparseApp
```

Whereas to compile against the static cuSPARSE library, the following command has to be used:

```
nvcc myCusparseApp.c -lcusparse_static -lcubos -o myCusparseApp
```

It is also possible to use the native Host C++ compiler. Depending on the Host Operating system, some additional libraries like `pthread` or `d1` might be needed on the linking line. The following command on Linux is suggested :

```
g++ myCusparseApp.c -lcusparse_static -lcubos -lcudart_static -lpthread -ldl -I <cuda-toolkit-path>/include -L <cuda-toolkit-path>/lib64 -o myCusparseApp
```

Note that in the latter case, the library `cuda` is not needed. The CUDA Runtime will try to open explicitly the `cuda` library if needed. In the case of a system which does not have the CUDA driver installed, this allows the application to gracefully manage this issue and potentially run if a CPU-only path is available.

Chapter 2. Using the cuSPARSE API

This chapter describes how to use the cuSPARSE library API. It is not a reference for the cuSPARSE API data types and functions; that is provided in subsequent chapters.

2.1. Thread Safety

The library is thread safe and its functions can be called from multiple host threads. However, simultaneous read/writes of the same objects (or of the same handle) are not safe. Hence the handle must be private per thread, i.e., only one handle per thread is safe.

2.2. Scalar Parameters

In the cuSPARSE API, the scalar parameters α and β can be passed by reference on the host or the device.

The few functions that return a scalar result, such as `nnz()`, return the resulting value by reference on the host or the device. Even though these functions return immediately, similarly to those that return matrix and vector results, the scalar result is not ready until execution of the routine on the GPU completes. This requires proper synchronization be used when reading the result from the host.

This feature allows the cuSPARSE library functions to execute completely asynchronously using streams, even when α and β are generated by a previous kernel. This situation arises, for example, when the library is used to implement iterative methods for the solution of linear systems and eigenvalue problems [3].

2.3. Parallelism with Streams

If the application performs several small independent computations, or if it makes data transfers in parallel with the computation, CUDA streams can be used to overlap these tasks.

The application can conceptually associate a stream with each task. To achieve the overlap of computation between the tasks, the developer should create CUDA streams using the function `cudaStreamCreate()` and set the stream to be used by each individual cuSPARSE library routine by calling `cusparsesetStream()` just before calling the actual cuSPARSE routine. Then, computations performed in separate streams would be overlapped automatically on the

GPU, when possible. This approach is especially useful when the computation performed by a single task is relatively small and is not enough to fill the GPU with work, or when there is a data transfer that can be performed in parallel with the computation.

When streams are used, we recommend using the new cuSPARSE API with scalar parameters and results passed by reference in the device memory to achieve maximum computational overlap.

Although a developer can create many streams, in practice it is not possible to have more than 16 concurrent kernels executing at the same time.

2.4. Compatibility and Versioning

The cuSPARSE APIs are intended to be backward compatible at the source level with future releases (unless stated otherwise in the release notes of a specific future release). In other words, if a program uses cuSPARSE, it should continue to compile and work correctly with newer versions of cuSPARSE without source code changes. cuSPARSE is not guaranteed to be backward compatible at the binary level. Using different versions of the `cusparse.h` header file and the shared library is not supported. Using different versions of cuSPARSE and the CUDA runtime is not supported. The APIs should be backward compatible at the source level for public functions in most cases

2.5. Optimization Notes

Most of the cuSPARSE routines can be optimized by exploiting *CUDA Graphs capture* and *Hardware Memory Compression* features.

More in details, a single cuSPARSE call or a sequence of calls can be captured by a [CUDA Graph](#) and executed in a second moment. This minimizes kernels launch overhead and allows the CUDA runtime to optimize the whole workflow. A full example of CUDA graphs capture applied to a cuSPARSE routine can be found in [cuSPARSE Library Samples - CUDA Graph](#).

Secondly, the data types and functionalities involved in cuSPARSE are suitable for *Hardware Memory Compression* available in Ampere GPU devices (compute capability 8.0) or above. The feature allows memory compression for data with enough zero bytes without no loss of information. The device memory must be allocation with the [CUDA driver APIs](#). A full example of Hardware Memory Compression applied to a cuSPARSE routine can be found in [cuSPARSE Library Samples - Memory Compression](#).

Chapter 3. cuSPARSE Indexing and Data Formats

The cuSPARSE library supports dense and sparse vector, and dense and sparse matrix formats.

3.1. Index Base Format

The library supports zero- and one-based indexing. The index base is selected through the `cusparseIndexBase_t` type, which is passed as a standalone parameter or as a field in the matrix descriptor `cusparseMatDescr_t` type.

3.1.1. Vector Formats

This section describes dense and sparse vector formats.

3.1.1.1. Dense Format

Dense vectors are represented with a single data array that is stored linearly in memory, such as the following 7×1 dense vector.

```
[1.0 0.0 0.0 2.0 3.0 0.0 4.0]
```

(This vector is referenced again in the next section.)

3.1.1.2. Sparse Format

Sparse vectors are represented with two arrays.

- ▶ The *data array* has the nonzero values from the equivalent array in dense format.
- ▶ The *integer index array* has the positions of the corresponding nonzero values in the equivalent array in dense format.

For example, the dense vector in section 3.2.1 can be stored as a sparse vector with one-based indexing.

$$\begin{bmatrix} 1.0 & 2.0 & 3.0 & 4.0 \\ 1 & 4 & 5 & 7 \end{bmatrix}$$

It can also be stored as a sparse vector with zero-based indexing.

$$\begin{bmatrix} 1.0 & 2.0 & 3.0 & 4.0 \\ 0 & 3 & 4 & 6 \end{bmatrix}$$

In each example, the top row is the data array and the bottom row is the index array, and it is assumed that the indices are provided in increasing order and that each index appears only once.

3.2. Matrix Formats

Dense and several sparse formats for matrices are discussed in this section.

3.2.1. Dense Format

The dense matrix x is assumed to be stored in column-major format in memory and is represented by the following parameters.

m	(integer)	The number of rows in the matrix.
n	(integer)	The number of columns in the matrix.
ldx	(integer)	The leading dimension of x , which must be greater than or equal to m . If ldx is greater than m , then x represents a sub-matrix of a larger matrix stored in memory
x	(pointer)	Points to the data array containing the matrix elements. It is assumed that enough storage is allocated for x to hold all of the matrix elements and that cuSPARSE library functions may access values outside of the sub-matrix, but will never overwrite them.

For example, $m \times n$ dense matrix x with leading dimension ldx can be stored with one-based indexing as shown.

$$\begin{bmatrix} X_{1,1} & X_{1,2} & \cdots & X_{1,n} \\ X_{2,1} & X_{2,2} & \cdots & X_{2,n} \\ \vdots & \vdots & \ddots & \vdots \\ X_{m,1} & X_{m,2} & \cdots & X_{m,n} \\ \vdots & \vdots & \ddots & \vdots \\ X_{ldx,1} & X_{ldx,2} & \cdots & X_{ldx,n} \end{bmatrix}$$

Its elements are arranged linearly in memory in the order below.

$$[X_{1,1} \ X_{2,1} \ \cdots \ X_{m,1} \ \cdots \ X_{ldx,1} \ \cdots \ X_{1,n} \ X_{2,n} \ \cdots \ X_{m,n} \ \cdots \ X_{ldx,n}]$$



Note: This format and notation are similar to those used in the NVIDIA CUDA cuBLAS library.

3.2.2. Coordinate Format (COO)

The $m \times n$ sparse matrix A is represented in COO format by the following parameters.

<code>nnz</code>	(integer)	The number of nonzero elements in the matrix.
<code>cooValA</code>	(pointer)	Points to the data array of length <code>nnz</code> that holds all nonzero values of A in row-major format.
<code>cooRowIndA</code>	(pointer)	Points to the integer array of length <code>nnz</code> that contains the row indices of the corresponding elements in array <code>cooValA</code> .
<code>cooColIndA</code>	(pointer)	Points to the integer array of length <code>nnz</code> that contains the column indices of the corresponding elements in array <code>cooValA</code> .

A sparse matrix in COO format is assumed to be stored in row-major format. Each COO entry consists of a row, column pair. The COO format is assumed to be sorted by row. Both sorted and unsorted column indices are supported.

For example, consider the following 4×5 matrix A .

$$\begin{bmatrix} 1.0 & 4.0 & 0.0 & 0.0 & 0.0 \\ 0.0 & 2.0 & 3.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 0.0 & 7.0 & 8.0 \\ 0.0 & 0.0 & 9.0 & 0.0 & 6.0 \end{bmatrix}$$

It is stored in COO format with zero-based indexing this way.

$$\begin{aligned} \text{cooValA} &= [1.0 \ 4.0 \ 2.0 \ 3.0 \ 5.0 \ 7.0 \ 8.0 \ 9.0 \ 6.0] \\ \text{cooRowIndA} &= [0 \ 0 \ 1 \ 1 \ 2 \ 2 \ 2 \ 3 \ 3] \\ \text{cooColIndA} &= [0 \ 1 \ 1 \ 2 \ 0 \ 3 \ 4 \ 2 \ 4] \end{aligned}$$

In the COO format with one-based indexing, it is stored as shown.

$$\begin{aligned} \text{cooValA} &= [1.0 \ 4.0 \ 2.0 \ 3.0 \ 5.0 \ 7.0 \ 8.0 \ 9.0 \ 6.0] \\ \text{cooRowIndA} &= [1 \ 1 \ 2 \ 2 \ 3 \ 3 \ 3 \ 4 \ 4] \\ \text{cooColIndA} &= [1 \ 2 \ 2 \ 3 \ 1 \ 4 \ 5 \ 3 \ 5] \end{aligned}$$

3.2.3. Compressed Sparse Row Format (CSR)

The only way the CSR differs from the COO format is that the array containing the row indices is compressed in CSR format. The $m \times n$ sparse matrix A is represented in CSR format by the following parameters.

<code>nnz</code>	(integer)	The number of nonzero elements in the matrix.
<code>csrValA</code>	(pointer)	Points to the data array of length <code>nnz</code> that holds all nonzero values of A in row-major format.
<code>csrRowPtrA</code>	(pointer)	Points to the integer array of length $m+1$ that holds indices into the arrays <code>csrColIndA</code> and <code>csrValA</code> . The first m entries of this array contain the indices of the first nonzero element in the i th row for $i=1, \dots, m$, while the last entry contains <code>nnz+csrRowPtrA(0)</code> . In general, <code>csrRowPtrA(0)</code> is 0 or 1 for zero- and one-based indexing, respectively.

<code>csrColIndA</code>	(pointer)	Points to the integer array of length <code>nnz</code> that contains the column indices of the corresponding elements in array <code>csrValA</code> .
-------------------------	-----------	---

Sparse matrices in CSR format are assumed to be stored in row-major CSR format. Both sorted and unsorted column indices are supported.

Consider again the 4×5 matrix A .

$$\begin{bmatrix} 1.0 & 4.0 & 0.0 & 0.0 & 0.0 \\ 0.0 & 2.0 & 3.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 0.0 & 7.0 & 8.0 \\ 0.0 & 0.0 & 9.0 & 0.0 & 6.0 \end{bmatrix}$$

It is stored in CSR format with zero-based indexing as shown.

$$\begin{aligned} \text{csrValA} &= [1.0 \ 4.0 \ 2.0 \ 3.0 \ 5.0 \ 7.0 \ 8.0 \ 9.0 \ 6.0] \\ \text{csrRowPtrA} &= [0 \ 2 \ 4 \ 7 \ 9 \] \\ \text{csrColIndA} &= [0 \ 1 \ 1 \ 2 \ 0 \ 3 \ 4 \ 2 \ 4 \] \end{aligned}$$

This is how it is stored in CSR format with one-based indexing.

$$\begin{aligned} \text{csrValA} &= [1.0 \ 4.0 \ 2.0 \ 3.0 \ 5.0 \ 7.0 \ 8.0 \ 9.0 \ 6.0] \\ \text{csrRowPtrA} &= [1 \ 3 \ 5 \ 8 \ 10 \] \\ \text{csrColIndA} &= [1 \ 2 \ 2 \ 3 \ 1 \ 4 \ 5 \ 3 \ 5 \] \end{aligned}$$

3.2.4. Compressed Sparse Column Format (CSC)

The CSC format is different from the COO format in two ways: the matrix is stored in column-major format, and the array containing the column indices is compressed in CSC format. The $m \times n$ matrix A is represented in CSC format by the following parameters.

<code>nnz</code>	(integer)	The number of nonzero elements in the matrix.
<code>cscValA</code>	(pointer)	Points to the data array of length <code>nnz</code> that holds all nonzero values of A in column-major format.
<code>cscRowIndA</code>	(pointer)	Points to the integer array of length <code>nnz</code> that contains the row indices of the corresponding elements in array <code>cscValA</code> .
<code>cscColPtrA</code>	(pointer)	Points to the integer array of length <code>n+1</code> that holds indices into the arrays <code>cscRowIndA</code> and <code>cscValA</code> . The first <code>n</code> entries of this array contain the indices of the first nonzero element in the i th row for $i=1, \dots, n$, while the last entry contains <code>nnz+cscColPtrA(0)</code> . In general, <code>cscColPtrA(0)</code> is 0 or 1 for zero- and one-based indexing, respectively.



Note: The matrix A in CSR format has exactly the same memory layout as its transpose in CSC format (and vice versa).

For example, consider once again the 4×5 matrix A .

$$\begin{bmatrix} 1.0 & 4.0 & 0.0 & 0.0 & 0.0 \\ 0.0 & 2.0 & 3.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 0.0 & 7.0 & 8.0 \\ 0.0 & 0.0 & 9.0 & 0.0 & 6.0 \end{bmatrix}$$

It is stored in CSC format with zero-based indexing this way.

$$\begin{aligned} \text{cscValA} &= [1.0 \ 5.0 \ 4.0 \ 2.0 \ 3.0 \ 9.0 \ 7.0 \ 8.0 \ 6.0] \\ \text{cscRowIndA} &= [0 \ 2 \ 0 \ 1 \ 1 \ 3 \ 2 \ 2 \ 3] \\ \text{cscColPtrA} &= [0 \ 2 \ 4 \ 6 \ 7 \ 9] \end{aligned}$$

In CSC format with one-based indexing, this is how it is stored.

$$\begin{aligned} \text{cscValA} &= [1.0 \ 5.0 \ 4.0 \ 2.0 \ 3.0 \ 9.0 \ 7.0 \ 8.0 \ 6.0] \\ \text{cscRowIndA} &= [1 \ 3 \ 1 \ 2 \ 2 \ 4 \ 3 \ 3 \ 4] \\ \text{cscColPtrA} &= [1 \ 3 \ 5 \ 7 \ 8 \ 10] \end{aligned}$$

Each pair of row and column indices appears only once.

3.2.5. Block Compressed Sparse Row Format (BSR)

The only difference between the CSR and BSR formats is the format of the storage element. The former stores primitive data types (`single`, `double`, `cuComplex`, and `cuDoubleComplex`) whereas the latter stores a two-dimensional square block of primitive data types. The dimension of the square block is *blockDim*. The $m \times n$ sparse matrix A is equivalent to a block sparse matrix A_b with $mb = \frac{m + blockDim - 1}{blockDim}$ block rows and $nb = \frac{n + blockDim - 1}{blockDim}$ block columns. If m or n is not multiple of *blockDim*, then zeros are filled into A_b .

A is represented in BSR format by the following parameters.

<code>blockDim</code>	(integer)	Block dimension of matrix A .
<code>mb</code>	(integer)	The number of block rows of A .
<code>nb</code>	(integer)	The number of block columns of A .
<code>nnzb</code>	(integer)	The number of nonzero blocks in the matrix.
<code>bsrValA</code>	(pointer)	Points to the data array of length $nnzb * blockDim^2$ that holds all elements of nonzero blocks of A . The block elements are stored in either column-major order or row-major order.
<code>bsrRowPtrA</code>	(pointer)	Points to the integer array of length $mb + 1$ that holds indices into the arrays <code>bsrColIndA</code> and <code>bsrValA</code> . The first mb entries of this array contain the indices of the first nonzero block in the i th block row for $i = 1, \dots, mb$, while the last entry contains $nnzb + \text{bsrRowPtrA}(0)$. In general, <code>bsrRowPtrA(0)</code> is 0 or 1 for zero- and one-based indexing, respectively.
<code>bsrColIndA</code>	(pointer)	Points to the integer array of length $nnzb$ that contains the column indices of the corresponding blocks in array <code>bsrValA</code> .

As with CSR format, (row, column) indices of BSR are stored in row-major order. The index arrays are first sorted by row indices and then within the same row by column indices.

For example, consider again the 4×5 matrix A .

$$\begin{bmatrix} 1.0 & 4.0 & 0.0 & 0.0 & 0.0 \\ 0.0 & 2.0 & 3.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 0.0 & 7.0 & 8.0 \\ 0.0 & 0.0 & 9.0 & 0.0 & 6.0 \end{bmatrix}$$

If *blockDim* is equal to 2, then *mb* is 2, *nb* is 3, and matrix A is split into 2×3 block matrix A_b . The dimension of A_b is 4×6 , slightly bigger than matrix A , so zeros are filled in the last column of A_b . The element-wise view of A_b is this.

$$\begin{bmatrix} 1.0 & 4.0 & 0.0 & 0.0 & 0.0 & 0.0 \\ 0.0 & 2.0 & 3.0 & 0.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 0.0 & 7.0 & 8.0 & 0.0 \\ 0.0 & 0.0 & 9.0 & 0.0 & 6.0 & 0.0 \end{bmatrix}$$

Based on zero-based indexing, the block-wise view of A_b can be represented as follows.

$$A_b = \begin{bmatrix} A_{00} & A_{01} & A_{02} \\ A_{10} & A_{11} & A_{12} \end{bmatrix}$$

The basic element of BSR is a nonzero A_{ij} block, one that contains at least one nonzero element of A . Five of six blocks are nonzero in A_b .

$$A_{00} = \begin{bmatrix} 1 & 4 \\ 0 & 2 \end{bmatrix}, A_{01} = \begin{bmatrix} 0 & 0 \\ 3 & 0 \end{bmatrix}, A_{10} = \begin{bmatrix} 5 & 0 \\ 0 & 0 \end{bmatrix}, A_{11} = \begin{bmatrix} 0 & 7 \\ 9 & 0 \end{bmatrix}, A_{12} = \begin{bmatrix} 8 & 0 \\ 6 & 0 \end{bmatrix}$$

BSR format only stores the information of nonzero blocks, including block indices (i, j) and values A_{ij} . Also row indices are compressed in CSR format.

$$\begin{aligned} \text{bsrValA} &= [A_{00} \ A_{01} \ A_{10} \ A_{11} \ A_{12}] \\ \text{bsrRowPtrA} &= [0 \ 2 \ 5] \\ \text{bsrColIndA} &= [0 \ 1 \ 0 \ 1 \ 2] \end{aligned}$$

There are two ways to arrange the data element of block A_{ij} : row-major order and column-major order. Under column-major order, the physical storage of `bsrValA` is this.

$$\text{bsrValA} = [1 \ 0 \ 4 \ 2 \ | \ 0 \ 3 \ 0 \ 0 \ | \ 5 \ 0 \ 0 \ 0 \ | \ 0 \ 9 \ 7 \ 0 \ | \ 8 \ 6 \ 0 \ 0 \]$$

Under row-major order, the physical storage of `bsrValA` is this.

$$\text{bsrValA} = [1 \ 4 \ 0 \ 2 \ | \ 0 \ 0 \ 3 \ 0 \ | \ 5 \ 0 \ 0 \ 0 \ | \ 0 \ 7 \ 9 \ 0 \ | \ 8 \ 0 \ 6 \ 0 \]$$

Similarly, in BSR format with one-based indexing and column-major order, A can be represented by the following.

$$A_b = \begin{bmatrix} A_{11} & A_{12} & A_{13} \\ A_{21} & A_{22} & A_{23} \end{bmatrix}$$

$$\text{bsrValA} = [1 \ 0 \ 4 \ 2 \ | \ 0 \ 3 \ 0 \ 0 \ | \ 5 \ 0 \ 0 \ 0 \ | \ 0 \ 9 \ 7 \ 0 \ | \ 8 \ 6 \ 0 \ 0 \]$$

```
bsrRowPtrA = [1  3  6]
bsrColIndA = [1  2  1  2  3]
```



Note: The general BSR format has two parameters, `rowBlockDim` and `colBlockDim`. `rowBlockDim` is number of rows within a block and `colBlockDim` is number of columns within a block. If `rowBlockDim=colBlockDim`, general BSR format is the same as BSR format. If `rowBlockDim=colBlockDim=1`, general BSR format is the same as CSR format. The conversion routine `gebsr2gebsr` is used to do conversion among CSR, BSR and general BSR.



Note: In the cuSPARSE Library, the storage format of blocks in BSR format can be column-major or row-major, independently of the base index. However, if the developer uses BSR format from the Math Kernel Library (MKL) and wants to directly interface with the cuSPARSE Library, then `cusparsedirection_t CUSPARSE_DIRECTION_COLUMN` should be used if the base index is one; otherwise, `cusparsedirection_t CUSPARSE_DIRECTION_ROW` should be used.

3.2.6. Extended BSR Format (BSRX)

BSRX is the same as the BSR format, but the array `bsrRowPtrA` is separated into two parts. The first nonzero block of each row is still specified by the array `bsrRowPtrA`, which is the same as in BSR, but the position next to the last nonzero block of each row is specified by the array `bsrEndPtrA`. Briefly, BSRX format is simply like a 4-vector variant of BSR format.

Matrix A is represented in BSRX format by the following parameters.

<code>blockDim</code>	(integer)	Block dimension of matrix A .
<code>mb</code>	(integer)	The number of block rows of A .
<code>nb</code>	(integer)	The number of block columns of A .
<code>nnzb</code>	(integer)	number of nonzero blocks in the matrix A .
<code>bsrValA</code>	(pointer)	Points to the data array of length $nnzb * blockDim^2$ that holds all the elements of the nonzero blocks of A . The block elements are stored in either column-major order or row-major order.
<code>bsrRowPtrA</code>	(pointer)	Points to the integer array of length <code>mb</code> that holds indices into the arrays <code>bsrColIndA</code> and <code>bsrValA</code> ; <code>bsrRowPtrA(i)</code> is the position of the first nonzero block of the i th block row in <code>bsrColIndA</code> and <code>bsrValA</code> .
<code>bsrEndPtrA</code>	(pointer)	Points to the integer array of length <code>mb</code> that holds indices into the arrays <code>bsrColIndA</code> and <code>bsrValA</code> ; <code>bsrRowPtrA(i)</code> is the position next to the last nonzero block of the i th block row in <code>bsrColIndA</code> and <code>bsrValA</code> .
<code>bsrColIndA</code>	(pointer)	Points to the integer array of length <code>nnzb</code> that contains the column indices of the corresponding blocks in array <code>bsrValA</code> .

A simple conversion between BSR and BSRX can be done as follows. Suppose the developer has a 2×3 block sparse matrix A_b represented as shown.

$$A_b = \begin{bmatrix} A_{00} & A_{01} & A_{02} \\ A_{10} & A_{11} & A_{12} \end{bmatrix}$$

Assume it has this BSR format.

$$\begin{aligned}\text{bsrValA of BSR} &= [A_{00} \ A_{01} \ A_{10} \ A_{11} \ A_{12}] \\ \text{bsrRowPtrA of BSR} &= [0 \ 2 \ 5] \\ \text{bsrColIndA of BSR} &= [0 \ 1 \ 0 \ 1 \ 2]\end{aligned}$$

The `bsrRowPtrA` of the BSRX format is simply the first two elements of the `bsrRowPtrA` BSR format. The `bsrEndPtrA` of BSRX format is the last two elements of the `bsrRowPtrA` of BSR format.

$$\begin{aligned}\text{bsrRowPtrA of BSRX} &= [0 \ 2] \\ \text{bsrEndPtrA of BSRX} &= [2 \ 5]\end{aligned}$$

The advantage of the BSRX format is that the developer can specify a submatrix in the original BSR format by modifying `bsrRowPtrA` and `bsrEndPtrA` while keeping `bsrColIndA` and `bsrValA` unchanged.

For example, to create another block matrix $\tilde{A} = \begin{bmatrix} O & O & O \\ O & A_{11} & O \end{bmatrix}$ that is slightly different from A , the developer can keep `bsrColIndA` and `bsrValA`, but reconstruct \tilde{A} by properly setting of `bsrRowPtrA` and `bsrEndPtrA`. The following 4-vector characterizes \tilde{A} .

$$\begin{aligned}\text{bsrValA of } \tilde{A} &= [A_{00} \ A_{01} \ A_{10} \ A_{11} \ A_{12}] \\ \text{bsrColIndA of } \tilde{A} &= [0 \ 1 \ 0 \ 1 \ 2] \\ \text{bsrRowPtrA of } \tilde{A} &= [0 \ 3] \\ \text{bsrEndPtrA of } \tilde{A} &= [0 \ 4]\end{aligned}$$

Chapter 4. cuSPARSE Types Reference

4.1. Data types

The `float`, `double`, `cuComplex`, and `cuDoubleComplex` data types are supported. The first two are standard C data types, while the last two are exported from `cuComplex.h`.

4.2. `cusparseStatus_t`

This data type represents the status returned by the library functions and it can have the following values

Value	Description
<code>CUSPARSE_STATUS_SUCCESS</code>	The operation completed successfully
<code>CUSPARSE_STATUS_NOT_INITIALIZED</code>	<p>The cuSPARSE library was not initialized. This is usually caused by the lack of a prior call, an error in the CUDA Runtime API called by the cuSPARSE routine, or an error in the hardware setup</p> <p>To correct: call <code>cusparseCreate()</code> prior to the function call; and check that the hardware, an appropriate version of the driver, and the cuSPARSE library are correctly installed</p> <p>The error also applies to generic APIs (Generic APIs reference) for indicating a matrix/vector descriptor not initialized</p>
<code>CUSPARSE_STATUS_ALLOC_FAILED</code>	<p>Resource allocation failed inside the cuSPARSE library. This is usually caused by a device memory allocation (<code>cudaMalloc()</code>) or by a host memory allocation failure</p> <p>To correct: prior to the function call, deallocate previously allocated memory as much as possible</p>
<code>CUSPARSE_STATUS_INVALID_VALUE</code>	An unsupported value or parameter was passed to the function (a negative vector size, for example)

Value	Description
	To correct: ensure that all the parameters being passed have valid values
CUSPARSE_STATUS_ARCH_MISMATCH	The function requires a feature absent from the device architecture To correct: compile and run the application on a device with appropriate compute capability
CUSPARSE_STATUS_EXECUTION_FAILED	The GPU program failed to execute. This is often caused by a launch failure of the kernel on the GPU, which can be caused by multiple reasons To correct: check that the hardware, an appropriate version of the driver, and the cuSPARSE library are correctly installed
CUSPARSE_STATUS_INTERNAL_ERROR	An internal cuSPARSE operation failed To correct: check that the hardware, an appropriate version of the driver, and the cuSPARSE library are correctly installed. Also, check that the memory passed as a parameter to the routine is not being deallocated prior to the routine completion
CUSPARSE_STATUS_MATRIX_TYPE_NOT_SUPPORTED	The matrix type is not supported by this function. This is usually caused by passing an invalid matrix descriptor to the function To correct: check that the fields in <code>cusparseMatDescr_t</code> <code>descrA</code> were set correctly
CUSPARSE_STATUS_NOT_SUPPORTED	The operation or data type combination is currently not supported by the function
CUSPARSE_STATUS_INSUFFICIENT_RESOURCES	The resources for the computation, such as GPU global or shared memory, are not sufficient to complete the operation. The error can also indicate that the current computation mode (e.g. bit size of sparse matrix indices) does not allow to handle the given input

4.3. `cusparseHandle_t`

This is a pointer type to an opaque cuSPARSE context, which the user must initialize by calling `cusparseCreate()` prior to calling `cusparseCreate()` any other library function. The handle created and returned by `cusparseCreate()` must be passed to every cuSPARSE function.

4.4. `cusparsePointerMode_t`

This type indicates whether the scalar values are passed by reference on the host or device. It is important to point out that if several scalar values are passed by reference in the function call, all of them will conform to the same single pointer mode. The pointer mode can be set and retrieved using `cusparseSetPointerMode()` and `cusparseGetPointerMode()` routines, respectively.

Value	Meaning
<code>CUSPARSE_POINTER_MODE_HOST</code>	the scalars are passed by reference on the host.
<code>CUSPARSE_POINTER_MODE_DEVICE</code>	the scalars are passed by reference on the device.

4.5. `cusparseOperation_t`

This type indicates which operations need to be performed with the sparse matrix.

Value	Meaning
<code>CUSPARSE_OPERATION_NON_TRANSPOSE</code>	the non-transpose operation is selected.
<code>CUSPARSE_OPERATION_TRANSPOSE</code>	the transpose operation is selected.
<code>CUSPARSE_OPERATION_CONJUGATE_TRANSPOSE</code>	the conjugate transpose operation is selected.

4.6. `cusparseAction_t`

This type indicates whether the operation is performed only on indices or on data and indices.

Value	Meaning
<code>CUSPARSE_ACTION_SYMBOLIC</code>	the operation is performed only on indices.
<code>CUSPARSE_ACTION_NUMERIC</code>	the operation is performed on data and indices.

4.7. `cusparseDirection_t`

This type indicates whether the elements of a dense matrix should be parsed by rows or by columns (assuming column-major storage in memory of the dense matrix) in function `cusparse[S|D|C|Z]nnz`. Besides storage format of blocks in BSR format is also controlled by this type.

Value	Meaning
<code>CUSPARSE_DIRECTION_ROW</code>	the matrix should be parsed by rows.

Value	Meaning
CUSPARSE_DIRECTION_COLUMN	the matrix should be parsed by columns.

4.8. cusparseMatDescr_t

This structure is used to describe the shape and properties of a matrix.

```
typedef struct {
    cusparseMatrixType_t MatrixType;
    cusparseFillMode_t FillMode;
    cusparseDiagType_t DiagType;
    cusparseIndexBase_t IndexBase;
} cusparseMatDescr_t;
```

4.8.1. cusparseDiagType_t

This type indicates if the matrix diagonal entries are unity. The diagonal elements are always assumed to be present, but if CUSPARSE_DIAG_TYPE_UNIT is passed to an API routine, then the routine assumes that all diagonal entries are unity and will not read or modify those entries. Note that in this case the routine assumes the diagonal entries are equal to one, regardless of what those entries are actually set to in memory.

Value	Meaning
CUSPARSE_DIAG_TYPE_NON_UNIT	the matrix diagonal has non-unit elements.
CUSPARSE_DIAG_TYPE_UNIT	the matrix diagonal has unit elements.

4.8.2. cusparseFillMode_t

This type indicates if the lower or upper part of a matrix is stored in sparse storage.

Value	Meaning
CUSPARSE_FILL_MODE_LOWER	the lower triangular part is stored.
CUSPARSE_FILL_MODE_UPPER	the upper triangular part is stored.

4.8.3. cusparseIndexBase_t

This type indicates if the base of the matrix indices is zero or one.

Value	Meaning
CUSPARSE_INDEX_BASE_ZERO	the base index is zero.
CUSPARSE_INDEX_BASE_ONE	the base index is one.

4.8.4. `cusparseMatrixType_t`

This type indicates the type of matrix stored in sparse storage. Notice that for symmetric, Hermitian and triangular matrices only their lower or upper part is assumed to be stored.

The whole idea of matrix type and fill mode is to keep minimum storage for symmetric/ Hermitian matrix, and also to take advantage of symmetric property on SpMV (Sparse Matrix Vector multiplication). To compute $y=A*x$ when A is symmetric and only lower triangular part is stored, two steps are needed. First step is to compute $y=(L+D)*x$ and second step is to compute $y=L^T*x + y$. Given the fact that the transpose operation $y=L^T*x$ is 10x slower than non-transpose version $y=L*x$, the symmetric property does not show up any performance gain. It is better for the user to extend the symmetric matrix to a general matrix and apply $y=A*x$ with matrix type `CUSPARSE_MATRIX_TYPE_GENERAL`.

In general, SpMV, preconditioners (incomplete Cholesky or incomplete LU) and triangular solver are combined together in iterative solvers, for example PCG and GMRES. If the user always uses general matrix (instead of symmetric matrix), there is no need to support other than general matrix in preconditioners. Therefore the new routines, `[bsr|csr]sv2` (triangular solver), `[bsr|csr]ilu02` (incomplete LU) and `[bsr|csr]ic02` (incomplete Cholesky), only support matrix type `CUSPARSE_MATRIX_TYPE_GENERAL`.

Value	Meaning
<code>CUSPARSE_MATRIX_TYPE_GENERAL</code>	the matrix is general.
<code>CUSPARSE_MATRIX_TYPE_SYMMETRIC</code>	the matrix is symmetric.
<code>CUSPARSE_MATRIX_TYPE_HERMITIAN</code>	the matrix is Hermitian.
<code>CUSPARSE_MATRIX_TYPE_TRIANGULAR</code>	the matrix is triangular.

4.9. `cusparseAlgMode_t` [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

This is type for algorithm parameter to `cusparseCsrMvEx()` and `cusparseCsrMvEx_bufferSize()` functions.

Value	Meaning
<code>CUSPARSE_ALG_MERGE_PATH</code>	Use load-balancing algorithm that suits better for irregular nonzero-patterns.

4.10. `cusparseColorInfo_t`

This is a pointer type to an opaque structure holding the information used in `csrColor()`.

4.11. cusparseSolvePolicy_t

This type indicates whether level information is generated and used in `csrsv2`, `csric02`, `csrilu02`, `bsrsv2`, `bsric02` and `bsrilu02`.

Value	Meaning
<code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code>	no level information is generated and used.
<code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code>	generate and use level information.

4.12. bsric02Info_t

This is a pointer type to an opaque structure holding the information used in `bsric02_bufferSize()`, `bsric02_analysis()`, and `bsric02()`.

4.13. bsrilu02Info_t

This is a pointer type to an opaque structure holding the information used in `bsrilu02_bufferSize()`, `bsrilu02_analysis()`, and `bsrilu02()`.

4.14. bsrsm2Info_t

This is a pointer type to an opaque structure holding the information used in `bsrsm2_bufferSize()`, `bsrsm2_analysis()`, and `bsrsm2_solve()`.

4.15. bsrsv2Info_t

This is a pointer type to an opaque structure holding the information used in `bsrsv2_bufferSize()`, `bsrsv2_analysis()`, and `bsrsv2_solve()`.

4.16. csrgemm2Info_t [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

This is a pointer type to an opaque structure holding the information used in `csrgemm2_bufferSizeExt()`, and `csrgemm2()`.

4.17. csric02Info_t

This is a pointer type to an opaque structure holding the information used in `csric02_bufferSize()`, `csric02_analysis()`, and `csric02()`.

4.18. csrilu02Info_t

This is a pointer type to an opaque structure holding the information used in `csrilu02_bufferSize()`, `csrilu02_analysis()`, and `csrilu02()`.

4.19. csrsm2Info_t [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

This is a pointer type to an opaque structure holding the information used in `csrsm2_bufferSize()`, `csrsm2_analysis()`, and `csrsm2_solve()`.

4.20. csrsv2Info_t [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

This is a pointer type to an opaque structure holding the information used in `csrsv2_bufferSize()`, `csrsv2_analysis()`, and `csrsv2_solve()`.

Chapter 5. cuSPARSE Management Function Reference

The cuSPARSE functions for managing the library are described in this section.

5.1. `cusparseCreate()`

```
cusparseStatus_t  
cusparseCreate(cusparseHandle_t *handle)
```

This function initializes the cuSPARSE library and creates a handle on the cuSPARSE context. It must be called before any other cuSPARSE API function is invoked. It allocates hardware resources necessary for accessing the GPU.

Param.	In/out	Meaning
handle	IN	The pointer to the handle to the cuSPARSE context

See [cusparseStatus_t](#) for the description of the return status

5.2. `cusparseDestroy()`

```
cusparseStatus_t  
cusparseDestroy(cusparseHandle_t handle)
```

This function releases CPU-side resources used by the cuSPARSE library. The release of GPU-side resources may be deferred until the application shuts down.

Param.	In/out	Meaning
handle	IN	The handle to the cuSPARSE context

See [cusparseStatus_t](#) for the description of the return status

5.3. `cusparseGetErrorName()`

```
const char*
cusparseGetErrorString(cusparseStatus_t status)
```

The function returns the string representation of an error code enum name. If the error code is not recognized, "unrecognized error code" is returned.

Param.	In/out	Meaning
status	IN	Error code to convert to string
const char*	OUT	Pointer to a NULL-terminated string

5.4. `cusparseGetErrorString()`

```
const char*
cusparseGetErrorString(cusparseStatus_t status)
```

Returns the description string for an error code. If the error code is not recognized, "unrecognized error code" is returned.

Param.	In/out	Meaning
status	IN	Error code to convert to string
const char*	OUT	Pointer to a NULL-terminated string

5.5. `cusparseGetProperty()`

```
cusparseStatus_t
cusparseGetProperty(libraryPropertyType type,
                   int* value)
```

The function returns the value of the requested property. Refer to `libraryPropertyType` for supported types.

Param.	In/out	Meaning
type	IN	Requested property
value	OUT	Value of the requested property

`libraryPropertyType` (defined in `library_types.h`):

Value	Meaning
MAJOR_VERSION	Enumerator to query the major version
MINOR_VERSION	Enumerator to query the minor version

Value	Meaning
PATCH_LEVEL	Number to identify the patch level

See [cusparseStatus_t](#) for the description of the return status

5.6. cusparseGetVersion()

```
cusparseStatus_t
cusparseGetVersion(cusparseHandle_t handle,
                  int* version)
```

This function returns the version number of the cuSPARSE library.

Param.	In/out	Meaning
handle	IN	cuSPARSE handle
version	OUT	The version number of the library

See [cusparseStatus_t](#) for the description of the return status

5.7. cusparseGetPointerMode()

```
cusparseStatus_t
cusparseGetPointerMode(cusparseHandle_t handle,
                      cusparsePointerMode_t *mode)
```

This function obtains the pointer mode used by the cuSPARSE library. Please see the section on the `cusparsePointerMode_t` type for more details.

Param.	In/out	Meaning
handle	IN	The handle to the cuSPARSE context
mode	OUT	One of the enumerated pointer mode types

See [cusparseStatus_t](#) for the description of the return status

5.8. cusparseSetPointerMode()

```
cusparseStatus_t
cusparseSetPointerMode(cusparseHandle_t handle,
                      cusparsePointerMode_t mode)
```

This function sets the pointer mode used by the cuSPARSE library. The *default* is for the values to be passed by reference on the host. Please see the section on the `cublasPointerMode_t` type for more details.

Param.	In/out	Meaning
handle	IN	The handle to the cuSPARSE context
mode	IN	One of the enumerated pointer mode types

See [cusparseStatus_t](#) for the description of the return status

5.9. cusparseGetStream()

```
cusparseStatus_t
cusparseGetStream(cusparseHandle_t handle, cudaStream_t *streamId)
```

This function gets the cuSPARSE library stream, which is being used to execute all calls to the cuSPARSE library functions. If the cuSPARSE library stream is not set, all kernels use the default NULL stream.

Param.	In/out	Meaning
handle	IN	The handle to the cuSPARSE context
streamId	OUT	The stream used by the library

See [cusparseStatus_t](#) for the description of the return status

5.10. cusparseSetStream()

```
cusparseStatus_t
cusparseSetStream(cusparseHandle_t handle, cudaStream_t streamId)
```

This function sets the stream to be used by the cuSPARSE library to execute its routines.

Param.	In/out	Meaning
handle	IN	The handle to the cuSPARSE context
streamId	IN	The stream to be used by the library

See [cusparseStatus_t](#) for the description of the return status

Chapter 6. cuSPARSE Logging

cuSPARSE logging mechanism can be enabled by setting the following environment variables before launching the target application:

`cuSPARSE_LOG_LEVEL=<level>` - while level is one of the following levels:

- ▶ 0 - **Off** - logging is disabled (default)
- ▶ 1 - **Error** - only errors will be logged
- ▶ 2 - **Trace** - API calls that launch CUDA kernels will log their parameters and important information
- ▶ 3 - **Hints** - hints that can potentially improve the application's performance
- ▶ 4 - **Info** - provides general information about the library execution, may contain details about heuristic status
- ▶ 5 - **API Trace** - API calls will log their parameter and important information

`cuSPARSE_LOG_MASK=<mask>` - while mask is a combination of the following masks:

- ▶ 0 - **Off**
- ▶ 1 - **Error**
- ▶ 2 - **Trace**
- ▶ 4 - **Hints**
- ▶ 8 - **Info**
- ▶ 16 - **API Trace**

`cuSPARSE_LOG_FILE=<file_name>` - while file name is a path to a logging file. File name may contain `%i`, that will be replaced with the process id. E.g "`<file_name>_%i.log`". If `cuSPARSE_LOG_FILE` is not defined, the log messages are printed to stdout. Another option is to use the experimental cuSPARSE logging API. See: [`cusparseLoggerSetCallback\(\)`](#), [`cusparseLoggerSetFile\(\)`](#), [`cusparseLoggerOpenFile\(\)`](#), [`cusparseLoggerSetLevel\(\)`](#), [`cusparseLoggerSetMask\(\)`](#), [`cusparseLoggerForceDisable\(\)`](#)

NOTE: The logging mechanism is not available for the legacy APIs

6.1. `cusparseLoggerSetCallback()`

```
cusparseStatus_t
cusparseLoggerSetCallback(cusparseLoggerCallback_t callback)
```

Experimental: The function sets the logging callback function.

Param.	In/out	Meaning
callback	IN	Pointer to a callback function

where `cusparseLoggerCallback_t` has the following signature:

```
void (*cusparseLoggerCallback_t)(int          logLevel,
                                  const char*  functionName,
                                  const char*  message)
```

Param.	In/out	Meaning
logLevel	IN	Selected log level
functionName	IN	The name of the API that logged this message
message	IN	The log message

See [cusparseStatus_t](#) for the description of the return status

6.2. `cusparseLoggerSetFile()`

```
cusparseStatus_t
cusparseLoggerSetFile(FILE* file)
```

Experimental: The function sets the logging output file. Note: once registered using this function call, the provided file handle must not be closed unless the function is called again to switch to a different file handle.

Param.	In/out	Meaning
file	IN	Pointer to an open file. File should have write permission

See [cusparseStatus_t](#) for the description of the return status

6.3. `cusparseLoggerOpenFile()`

```
cusparseStatus_t
cusparseLoggerOpenFile(const char* logFile)
```

Experimental: The function opens a logging output file in the given path.

Param.	In/out	Meaning
logFile	IN	Path of the logging output file

See [cusparseStatus_t](#) for the description of the return status

6.4. cusparseLoggerSetLevel()

```
cusparseStatus_t
cusparseLoggerSetLevel(int level)
```

Experimental: The function sets the value of the logging level. path.

Param.	In/out	Meaning
level	IN	Value of the logging level

See [cusparseStatus_t](#) for the description of the return status

6.5. cusparseLoggerSetMask()

```
cusparseStatus_t
cusparseLoggerSetMask(int mask)
```

Experimental: The function sets the value of the logging mask.

Param.	In/out	Meaning
mask	IN	Value of the logging mask

See [cusparseStatus_t](#) for the description of the return status

6.6. cublasLtLoggerForceDisable()

```
cusparseStatus_t
cublasLtLoggerForceDisable()
```

Experimental: The function disables logging for the entier run.

See [cusparseStatus_t](#) for the description of the return status

Chapter 7. cuSPARSE Helper Function Reference

The cuSPARSE helper functions are described in this section.

7.1. `cusparseCreateColorInfo()`

```
cusparseStatus_t  
cusparseCreateColorInfo(cusparseColorInfo_t* info)
```

This function creates and initializes the `cusparseColorInfo_t` structure to *default* values.

Input

<code>info</code>	the pointer to the <code>cusparseColorInfo_t</code> structure
-------------------	---

See [`cusparseStatus_t`](#) for the description of the return status

7.2. `cusparseCreateMatDescr()`

```
cusparseStatus_t  
cusparseCreateMatDescr(cusparseMatDescr_t *descrA)
```

This function initializes the matrix descriptor. It sets the fields `MatrixType` and `IndexBase` to the *default* values `CUSPARSE_MATRIX_TYPE_GENERAL` and `CUSPARSE_INDEX_BASE_ZERO`, respectively, while leaving other fields uninitialized.

Input

<code>descrA</code>	the pointer to the matrix descriptor.
---------------------	---------------------------------------

See [`cusparseStatus_t`](#) for the description of the return status

7.3. `cusparseDestroyColorInfo()`

```

cusparsesStatus_t
cusparsesDestroyColorInfo(cusparsesColorInfo_t info)

```

This function destroys and releases any memory required by the structure.

Input

info	the pointer to the structure of <code>csrColor()</code>
------	---

See [cusparsesStatus_t](#) for the description of the return status

7.4. cusparsesDestroyMatDescr()

```

cusparsesStatus_t
cusparsesDestroyMatDescr(cusparsesMatDescr_t descrA)

```

This function releases the memory allocated for the matrix descriptor.

Input

descrA	the matrix descriptor.
--------	------------------------

See [cusparsesStatus_t](#) for the description of the return status

7.5. cusparsesGetMatDiagType()

```

cusparsesDiagType_t
cusparsesGetMatDiagType(const cusparsesMatDescr_t descrA)

```

This function returns the `DiagType` field of the matrix descriptor `descrA`.

Input

descrA	the matrix descriptor.
--------	------------------------

Returned

	One of the enumerated <code>diagType</code> types.
--	--

7.6. cusparsesGetMatFillMode()

```

cusparsesFillMode_t
cusparsesGetMatFillMode(const cusparsesMatDescr_t descrA)

```

This function returns the `FillMode` field of the matrix descriptor `descrA`.

Input

descrA	the matrix descriptor.
--------	------------------------

Returned

	One of the enumerated fillMode types.
--	---------------------------------------

7.7. `cusparseGetMatIndexBase()`

```
cusparseIndexBase_t
cusparseGetMatIndexBase(const cusparseMatDescr_t descrA)
```

This function returns the `IndexBase` field of the matrix descriptor `descrA`.

Input

<code>descrA</code>	the matrix descriptor.
---------------------	------------------------

Returned

	One of the enumerated indexBase types.
--	--

7.8. `cusparseGetMatType()`

```
cusparseMatrixType_t
cusparseGetMatType(const cusparseMatDescr_t descrA)
```

This function returns the `MatrixType` field of the matrix descriptor `descrA`.

Input

<code>descrA</code>	the matrix descriptor.
---------------------	------------------------

Returned

	One of the enumerated matrix types.
--	-------------------------------------

7.9. `cusparseSetMatDiagType()`

```
cusparseStatus_t
cusparseSetMatDiagType(cusparseMatDescr_t descrA,
                       cusparseDiagType_t diagType)
```

This function sets the `DiagType` field of the matrix descriptor `descrA`.

Input

<code>diagType</code>	One of the enumerated diagType types.
-----------------------	---------------------------------------

Output

<code>descrA</code>	the matrix descriptor.
---------------------	------------------------

See [`cusparseStatus_t`](#) for the description of the return status

7.10. `cusparseSetMatFillMode()`

```
cusparseStatus_t
cusparseSetMatFillMode(cusparseMatDescr_t descrA,
                      cusparseFillMode_t fillMode)
```

This function sets the `FillMode` field of the matrix descriptor `descrA`.

Input

<code>fillMode</code>	One of the enumerated <code>fillMode</code> types.
-----------------------	--

Output

<code>descrA</code>	the matrix descriptor.
---------------------	------------------------

See [`cusparseStatus_t`](#) for the description of the return status

7.11. `cusparseSetMatIndexBase()`

```
cusparseStatus_t
cusparseSetMatIndexBase(cusparseMatDescr_t descrA,
                       cusparseIndexBase_t base)
```

This function sets the `IndexBase` field of the matrix descriptor `descrA`.

Input

<code>base</code>	One of the enumerated <code>indexBase</code> types.
-------------------	---

Output

<code>descrA</code>	the matrix descriptor.
---------------------	------------------------

See [`cusparseStatus_t`](#) for the description of the return status

7.12. `cusparseSetMatType()`

```
cusparseStatus_t
cusparseSetMatType(cusparseMatDescr_t descrA, cusparseMatrixType_t type)
```

This function sets the `MatrixType` field of the matrix descriptor `descrA`.

Input

<code>type</code>	One of the enumerated matrix types.
-------------------	-------------------------------------

Output

<code>descrA</code>	the matrix descriptor.
---------------------	------------------------

See [cusparseStatus_t](#) for the description of the return status

7.13. cusparseCreateCsrsv2Info() [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseCreateCsrsv2Info(csrsv2Info_t *info);
```

This function creates and initializes the solve and analysis structure of `csrsv2` to *default* values.

Input

info	the pointer to the solve and analysis structure of <code>csrsv2</code> .
------	--

See [cusparseStatus_t](#) for the description of the return status

7.14. cusparseDestroyCsrsv2Info() [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseDestroyCsrsv2Info(csrsv2Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

info	the solve (<code>csrsv2_solve</code>) and analysis (<code>csrsv2_analysis</code>) structure.
------	--

See [cusparseStatus_t](#) for the description of the return status

7.15. cusparseCreateCsrrsm2Info() [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseCreateCsrrsm2Info(csrrsm2Info_t *info);
```

This function creates and initializes the solve and analysis structure of `csrsm2` to *default* values.

Input

<code>info</code>	the pointer to the solve and analysis structure of <code>csrsm2</code> .
-------------------	--

See [`cusparseStatus_t`](#) for the description of the return status

7.16. `cusparseDestroyCsrsm2Info()` [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseDestroyCsrsm2Info(csrsm2Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

<code>info</code>	the solve (<code>csrsm2_solve</code>) and analysis (<code>csrsm2_analysis</code>) structure.
-------------------	--

See [`cusparseStatus_t`](#) for the description of the return status

7.17. `cusparseCreateCsrsm2Info()`

```
cusparseStatus_t
cusparseCreateCsrsm2Info(csrsm2Info_t *info);
```

This function creates and initializes the solve and analysis structure of incomplete Cholesky to *default* values.

Input

<code>info</code>	the pointer to the solve and analysis structure of incomplete Cholesky.
-------------------	---

See [`cusparseStatus_t`](#) for the description of the return status

7.18. `cusparseDestroyCsrsm2Info()`

```
cusparseStatus_t
cusparseDestroyCsrsm2Info(csrsm2Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

info	the solve (<code>csric02_solve</code>) and analysis (<code>csric02_analysis</code>) structure.
------	--

See [`cusparseStatus_t`](#) for the description of the return status

7.19. `cusparseCreateCsrilu02Info()`

```
cusparseStatus_t
cusparseCreateCsrilu02Info(csrilu02Info_t *info);
```

This function creates and initializes the solve and analysis structure of incomplete LU to *default* values.

Input

info	the pointer to the solve and analysis structure of incomplete LU.
------	---

See [`cusparseStatus_t`](#) for the description of the return status

7.20. `cusparseDestroyCsrilu02Info()`

```
cusparseStatus_t
cusparseDestroyCsrilu02Info(csrilu02Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

info	the solve (<code>csrilu02_solve</code>) and analysis (<code>csrilu02_analysis</code>) structure.
------	--

See [`cusparseStatus_t`](#) for the description of the return status

7.21. `cusparseCreateBsrsv2Info()`

```
cusparseStatus_t
cusparseCreateBsrsv2Info(bsrsv2Info_t *info);
```

This function creates and initializes the solve and analysis structure of bsrsv2 to *default* values.

Input

info	the pointer to the solve and analysis structure of bsrsv2.
------	--

See [cusparseStatus_t](#) for the description of the return status

7.22. cusparseDestroyBsrsv2Info()

```
cusparseStatus_t
cusparseDestroyBsrsv2Info (bsrsv2Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

info	the solve (bsrsv2_solve) and analysis (bsrsv2_analysis) structure.
------	--

See [cusparseStatus_t](#) for the description of the return status

7.23. cusparseCreateBsrsm2Info()

```
cusparseStatus_t
cusparseCreateBsrsm2Info (bsrsm2Info_t *info);
```

This function creates and initializes the solve and analysis structure of bsrsm2 to *default* values.

Input

info	the pointer to the solve and analysis structure of bsrsm2.
------	--

See [cusparseStatus_t](#) for the description of the return status

7.24. cusparseDestroyBsrsm2Info()

```
cusparseStatus_t
cusparseDestroyBsrsm2Info (bsrsm2Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

info	the solve (bsrsm2_solve) and analysis (bsrsm2_analysis) structure.
------	--

See [cusparseStatus_t](#) for the description of the return status

7.25. `cusparseCreateBsrict02Info()`

```
cusparseStatus_t
cusparseCreateBsrict02Info(bsrict02Info_t *info);
```

This function creates and initializes the solve and analysis structure of block incomplete Cholesky to *default* values.

Input

<code>info</code>	the pointer to the solve and analysis structure of block incomplete Cholesky.
-------------------	---

See [`cusparseStatus_t`](#) for the description of the return status

7.26. `cusparseDestroyBsrict02Info()`

```
cusparseStatus_t
cusparseDestroyBsrict02Info(bsrict02Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

<code>info</code>	the solve (<code>bsrict02_solve</code>) and analysis (<code>bsrict02_analysis</code>) structure.
-------------------	--

See [`cusparseStatus_t`](#) for the description of the return status

7.27. `cusparseCreateBsrilu02Info()`

```
cusparseStatus_t
cusparseCreateBsrilu02Info(bsrilu02Info_t *info);
```

This function creates and initializes the solve and analysis structure of block incomplete LU to *default* values.

Input

<code>info</code>	the pointer to the solve and analysis structure of block incomplete LU.
-------------------	---

See [`cusparseStatus_t`](#) for the description of the return status

7.28. `cusparseDestroyBsrilu02Info()`

```
cusparseStatus_t
cusparseDestroyBsrilu02Info (bsrilu02Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

info	the solve (<code>bsrilu02_solve</code>) and analysis (<code>bsrilu02_analysis</code>) structure.
------	--

See [`cusparseStatus_t`](#) for the description of the return status

7.29. `cusparseCreateCsrgermm2Info()` [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseCreateCsrgermm2Info (csrgermm2Info_t *info);
```

This function creates and initializes analysis structure of general sparse matrix-matrix multiplication.

Input

info	the pointer to the analysis structure of general sparse matrix-matrix multiplication.
------	---

See [`cusparseStatus_t`](#) for the description of the return status

7.30. `cusparseDestroyCsrgermm2Info()` [DEPRECATED]

[DEPRECATED] *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseDestroyCsrgermm2Info (csrgermm2Info_t info);
```

This function destroys and releases any memory required by the structure.

Input

info	opaque structure of <code>csrgermm2</code> .
------	--

See [cusparseStatus_t](#) for the description of the return status

7.31. cusparseCreatePruneInfo()

```
cusparseStatus_t
cusparseCreatePruneInfo(pruneInfo_t *info);
```

This function creates and initializes structure of `prune` to *default* values.

Input

info	the pointer to the structure of <code>prune</code> .
------	--

See [cusparseStatus_t](#) for the description of the return status

7.32. cusparseDestroyPruneInfo()

```
cusparseStatus_t
cusparseDestroyPruneInfo(pruneInfo_t info);
```

This function destroys and releases any memory required by the structure.

Input

info	the structure of <code>prune</code> .
------	---------------------------------------

See [cusparseStatus_t](#) for the description of the return status

Chapter 8. cuSPARSE Level 1 Function Reference

This chapter describes sparse linear algebra functions that perform operations between dense and sparse vectors.

8.1. `cusparse<t>axpyi()` [DEPRECATED]

[DEPRECATED] use `cusparseAxpby()` instead. *The routine will be removed in the next major release*

```
usparsedStatus_t
cusparseSaxpyi(cusparseHandle_t handle,
              int nnz,
              const float* alpha,
              const float* xVal,
              const int* xInd,
              float* y,
              cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseDaxpyi(cusparseHandle_t handle,
              int nnz,
              const double* alpha,
              const double* xVal,
              const int* xInd,
              double* y,
              cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseCaxpyi(cusparseHandle_t handle,
              int nnz,
              const cuComplex* alpha,
              const cuComplex* xVal,
              const int* xInd,
              cuComplex* y,
              cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseZaxpyi(cusparseHandle_t handle,
              int nnz,
              const cuDoubleComplex* alpha,
              const cuDoubleComplex* xVal,
```

```

const int*          xInd,
cuDoubleComplex*   y,
cusparseIndexBase_t idxBase)

```

This function multiplies the vector x in sparse format by the constant α and adds the result to the vector y in dense format. This operation can be written as

$$y = y + \alpha * x$$

In other words,

```

for i=0 to nnz-1
    y[xInd[i]-idxBase] = y[xInd[i]-idxBase] + alpha*xVal[i]

```

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
nnz	number of elements in vector x .
alpha	<type> scalar used for multiplication.
xVal	<type> vector with nnz nonzero values of vector x .
xInd	integer vector with nnz indices of the nonzero values of vector x .
y	<type> vector in dense format.
idxBase	CUSPARSE_INDEX_BASE_ZERO or CUSPARSE_INDEX_BASE_ONE.

Output

y	<type> updated vector in dense format (that is unchanged if $nnz == 0$).
---	---

See [cusparseStatus_t](#) for the description of the return status

8.2. `cusparse<t>gthr()` [DEPRECATED]

[DEPRECATED] use [cusparseGather\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparseStatus_t
cusparseSgthr(cusparseHandle_t handle,
              int nnz,
              const float* y,
              float* xVal,
              const int* xInd,
              cusparseIndexBase_t idxBase)

```

```

cusparsesStatus_t
cusparsesDgthr(cusparsesHandle_t handle,
              int nnz,
              const double* y,
              double* xVal,
              const int* xInd,
              cusparsesIndexBase_t idxBase)

cusparsesStatus_t
cusparsesCgthr(cusparsesHandle_t handle,
              int nnz,
              const cuComplex* y,
              cuComplex* xVal,
              const int* xInd,
              cusparsesIndexBase_t idxBase)

cusparsesStatus_t
cusparsesZgthr(cusparsesHandle_t handle,
              int nnz,
              const cuDoubleComplex* y,
              cuDoubleComplex* xVal,
              const int* xInd,
              cusparsesIndexBase_t idxBase)

```

This function gathers the elements of the vector `y` listed in the index array `xInd` into the data array `xVal`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>nnz</code>	number of elements in vector <code>x</code> .
<code>y</code>	<type> vector in dense format (of <code>size ≥ max(xInd) - idxBase + 1</code>).
<code>xInd</code>	integer vector with <code>nnz</code> indices of the nonzero values of vector <code>x</code> .
<code>idxBase</code>	CUSPARSE_INDEX_BASE_ZERO or CUSPARSE_INDEX_BASE_ONE.

Output

<code>xVal</code>	<type> vector with <code>nnz</code> nonzero values that were gathered from vector <code>y</code> (that is unchanged if <code>nnz == 0</code>).
-------------------	---

See [cusparsesStatus_t](#) for the description of the return status

8.3. `cusparse<t>gthrz()` [DEPRECATED]

[DEPRECATED] use `cusparseGather()` instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseSgthrz(cusparseHandle_t handle,
              int nnz,
              float* y,
              float* xVal,
              const int* xInd,
              cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseDgthrz(cusparseHandle_t handle,
              int nnz,
              double* y,
              double* xVal,
              const int* xInd,
              cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseCgthrz(cusparseHandle_t handle,
              int nnz,
              cuComplex* y,
              cuComplex* xVal,
              const int* xInd,
              cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseZgthrz(cusparseHandle_t handle,
              int nnz,
              cuDoubleComplex* y,
              cuDoubleComplex* xVal,
              const int* xInd,
              cusparseIndexBase_t idxBase)
```

This function gathers the elements of the vector `y` listed in the index array `xInd` into the data array `xVal`. Also, it zeros out the gathered elements in the vector `y`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>nnz</code>	number of elements in vector <code>x</code> .
<code>y</code>	<type> vector in dense format (of <code>size ≥ max(xInd) - idxBase + 1</code>).

xInd	integer vector with nnz indices of the nonzero values of vector x.
idxBase	CUSPARSE_INDEX_BASE_ZERO or CUSPARSE_INDEX_BASE_ONE.

Output

xVal	<type> vector with nnz nonzero values that were gathered from vector y (that is unchanged if nnz == 0).
y	<type> vector in dense format with elements indexed by xInd set to zero (it is unchanged if nnz == 0).

See [cusparseStatus_t](#) for the description of the return status

8.4. `cusparse<t>roti()` [DEPRECATED]

[DEPRECATED] use [cusparseRot\(\)](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseSroti(cusparseHandle_t handle,
             int nnz,
             float* xVal,
             const int* xInd,
             float* y,
             const float* c,
             const float* s,
             cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseDroti(cusparseHandle_t handle,
             int nnz,
             double* xVal,
             const int* xInd,
             double* y,
             const double* c,
             const double* s,
             cusparseIndexBase_t idxBase)
```

This function applies the Givens rotation matrix

$$G = \begin{pmatrix} c & s \\ -s & c \end{pmatrix}$$

to sparse x and dense y vectors. In other words,

```
for i=0 to nnz-1
    y[xInd[i]-idxBase] = c * y[xInd[i]-idxBase] - s*xVal[i]
    x[i] = c * xVal[i] + s * y[xInd[i]-idxBase]
```

- The routine requires no extra storage

- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
nnz	number of elements in vector x .
xVal	<type> vector with nnz nonzero values of vector x .
xInd	integer vector with nnz indices of the nonzero values of vector x .
y	<type> vector in dense format.
c	cosine element of the rotation matrix.
s	sine element of the rotation matrix.
idxBase	CUSPARSE_INDEX_BASE_ZERO or CUSPARSE_INDEX_BASE_ONE.

Output

xVal	<type> updated vector in sparse format (that is unchanged if $nnz == 0$).
y	<type> updated vector in dense format (that is unchanged if $nnz == 0$).

See [cusparseStatus_t](#) for the description of the return status

8.5. `cusparse<t>sctr()` [DEPRECATED]

[DEPRECATED] use [cusparseScatter\(\)](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseSsctr(cusparseHandle_t handle,
             int nnz,
             const float* xVal,
             const int* xInd,
             float* y,
             cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseDsctr(cusparseHandle_t handle,
             int nnz,
             const double* xVal,
             const int* xInd,
             double* y,
             cusparseIndexBase_t idxBase)

cusparseStatus_t
cusparseCsctr(cusparseHandle_t handle,
             int nnz,
             const cuComplex* xVal,
```

```

        const int*      xInd,
        cuComplex*     y,
        cusparseIndexBase_t idxBase)
cusparseStatus_t
cusparseZsctr(cusparseHandle_t      handle,
             int                    nnz,
             const cuDoubleComplex* xVal,
             const int*             xInd,
             cuDoubleComplex*      y,
             cusparseIndexBase_t    idxBase)

```

This function scatters the elements of the vector x in sparse format into the vector y in dense format. It modifies only the elements of y whose indices are listed in the array $xInd$.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
nnz	number of elements in vector x .
xVal	<type> vector with nnz nonzero values of vector x .
xInd	integer vector with nnz indices of the nonzero values of vector x .
y	<type> dense vector (of size $\geq \max(xInd) - idxBase + 1$).
idxBase	CUSPARSE_INDEX_BASE_ZERO or CUSPARSE_INDEX_BASE_ONE.

Output

y	<type> vector with nnz nonzero values that were scattered from vector x (that is unchanged if $nnz == 0$).
---	---

See [cusparseStatus_t](#) for the description of the return status

Chapter 9. cuSPARSE Level 2 Function Reference

This chapter describes the sparse linear algebra functions that perform operations between sparse matrices and dense vectors.

In particular, the solution of sparse triangular linear systems is implemented in two phases. First, during the analysis phase, the sparse triangular matrix is analyzed to determine the dependencies between its elements by calling the appropriate `csrsv2_analysis()` function. The analysis is specific to the sparsity pattern of the given matrix and to the selected `cusparseOperation_t` type. The information from the analysis phase is stored in the parameter of type `csrsv2Info_t` that has been initialized previously with a call to `cusparseCreateCsrsv2Info()`.

Second, during the solve phase, the given sparse triangular linear system is solved using the information stored in the `csrsv2Info_t` parameter by calling the appropriate `csrsv2_solve()` function. The solve phase may be performed multiple times with different right-hand sides, while the analysis phase needs to be performed only once. This is especially useful when a sparse triangular linear system must be solved for a set of different right-hand sides one at a time, while its coefficient matrix remains the same.

Finally, once all the solves have completed, the opaque data structure pointed to by the `csrsv2Info_t` parameter can be released by calling `cusparseDestroyCsrsv2Info()`

9.1. `cusparse<t>bsrmv()`

```
cusparseStatus_t
cusparseSbsrmv(cusparseHandle_t      handle,
               cusparseDirection_t   dir,
               cusparseOperation_t   trans,
               int                    mb,
               int                    nb,
               int                    nnzb,
               const float*           alpha,
               const cusparseMatDescr_t descr,
               const float*           bsrVal,
               const int*             bsrRowPtr,
               const int*             bsrColInd,
               int                    blockDim,
               const float*           x,
```



```

        const float*
        float*
        beta,
        y)

cusparseStatus_t
cusparseDbsrmv(cusparseHandle_t          handle,
               cusparseDirection_t      dir,
               cusparseOperation_t      trans,
               int                       mb,
               int                       nb,
               int                       nnzb,
               const double*             alpha,
               const cusparseMatDescr_t  descr,
               const double*            bsrVal,
               const int*                bsrRowPtr,
               const int*                bsrColInd,
               int                       blockDim,
               const double*             x,
               const double*            beta,
               double*                   y)

cusparseStatus_t
cusparseCbsrmv(cusparseHandle_t          handle,
               cusparseDirection_t      dir,
               cusparseOperation_t      trans,
               int                       mb,
               int                       nb,
               int                       nnzb,
               const cuComplex*         alpha,
               const cusparseMatDescr_t  descr,
               const cuComplex*         bsrVal,
               const int*                bsrRowPtr,
               const int*                bsrColInd,
               int                       blockDim,
               const cuComplex*         x,
               const cuComplex*         beta,
               cuComplex*                y)

cusparseStatus_t
cusparseZbsrmv(cusparseHandle_t          handle,
               cusparseDirection_t      dir,
               cusparseOperation_t      trans,
               int                       mb,
               int                       nb,
               int                       nnzb,
               const cuDoubleComplex*   alpha,
               const cusparseMatDescr_t  descr,
               const cuDoubleComplex*   bsrVal,
               const int*                bsrRowPtr,
               const int*                bsrColInd,
               int                       blockDim,
               const cuDoubleComplex*   x,
               const cuDoubleComplex*   beta,
               cuDoubleComplex*         y)

```

This function performs the matrix-vector operation

$$y = \alpha * \text{op}(A) * x + \beta * y$$

where A is an $(mb * blockDim) \times (nb * blockDim)$ sparse matrix that is defined in BSR storage format by the three arrays `bsrVal`, `bsrRowPtr`, and `bsrColInd`; x and y are vectors; α and β are scalars; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

`bsrmv()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Several comments on `bsrmv()`:

- ▶ Only `blockDim > 1` is supported
- ▶ Only `CUSPARSE_OPERATION_NON_TRANPOSE` is supported, that is

$$y = \alpha * A * x + \beta * y$$

- ▶ Only `CUSPARSE_MATRIX_TYPE_GENERAL` is supported.
- ▶ The size of vector x should be $(nb * blockDim)$ at least, and the size of vector y should be $(mb * blockDim)$ at least; otherwise, the kernel may return `CUSPARSE_STATUS_EXECUTION_FAILED` because of an out-of-bounds array.

For example, suppose the user has a CSR format and wants to try `bsrmv()`, the following code demonstrates how to use `csr2bsr()` conversion and `bsrmv()` multiplication in single precision.

```
// Suppose that A is m x n sparse matrix represented by CSR format,
// hx is a host vector of size n, and hy is also a host vector of size m.
// m and n are not multiple of blockDim.
// step 1: transform CSR to BSR with column-major order
int base, nnz;
int nzb;
cusparseDirection_t dirA = CUSPARSE_DIRECTION_COLUMN;
int mb = (m + blockDim-1)/blockDim;
int nb = (n + blockDim-1)/blockDim;
cudaMalloc((void**)&bsrRowPtrC, sizeof(int) * (mb+1));
cusparseXcsr2bsrNnz(handle, dirA, m, n,
    descrA, csrRowPtrA, csrColIndA, blockDim,
    descrC, bsrRowPtrC, &nnzb);
cudaMalloc((void**)&bsrColIndC, sizeof(int)*nnzb);
cudaMalloc((void**)&bsrValC, sizeof(float)*(blockDim*blockDim)*nnzb);
cusparseScsr2bsr(handle, dirA, m, n,
    descrA, csrValA, csrRowPtrA, csrColIndA, blockDim,
    descrC, bsrValC, bsrRowPtrC, bsrColIndC);
// step 2: allocate vector x and vector y large enough for bsrmv
cudaMalloc((void**)&x, sizeof(float)*(nb*blockDim));
cudaMalloc((void**)&y, sizeof(float)*(mb*blockDim));
cudaMemcpy(x, hx, sizeof(float)*n, cudaMemcpyHostToDevice);
cudaMemcpy(y, hy, sizeof(float)*m, cudaMemcpyHostToDevice);
// step 3: perform bsrmv
cusparseSbsrmv(handle, dirA, transA, mb, nb, nnzb, &alpha,
    descrC, bsrValC, bsrRowPtrC, bsrColIndC, blockDim, x, &beta, y);
```

Input

handle	handle to the cuSPARSE library context.
dir	storage format of blocks, either CUSPARSE_DIRECTION_ROW or CUSPARSE_DIRECTION_COLUMN.
trans	the operation $op(A)$. Only CUSPARSE_OPERATION_NON_TRANSPOSE is supported.
mb	number of block rows of matrix A .
nb	number of block columns of matrix A .
nnzb	number of nonzero blocks of matrix A .
alpha	<type> scalar used for multiplication.
descr	the descriptor of matrix A . The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL. Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
bsrVal	<type> array of $nnz (= csrRowPtrA(mb) - csrRowPtrA(0))$ nonzero blocks of matrix A .
bsrRowPtr	integer array of $mb + 1$ elements that contains the start of every block row and the end of the last block row plus one.
bsrColInd	integer array of $nnz (= csrRowPtrA(mb) - csrRowPtrA(0))$ column indices of the nonzero blocks of matrix A .
blockDim	block dimension of sparse matrix A , larger than zero.
x	<type> vector of $nb * blockDim$ elements.
beta	<type> scalar used for multiplication. If beta is zero, y does not have to be a valid input.
y	<type> vector of $mb * blockDim$ elements.

Output

y	<type> updated vector.
---	------------------------

See [cusparseStatus_t](#) for the description of the return status

9.2. `cusparse<t>bsrxmv()`

```

cusparseStatus_t
cusparseSbsrxmv(cusparseHandle_t      handle,
                cusparseDirection_t    dir,
                cusparseOperation_t    trans,
                int                     sizeofMask,
                int                     mb,

```

```

        int                nb,
        int                nnzb,
        const float*       alpha,
        const cusparseMatDescr_t descr,
        const float*       bsrVal,
        const int*         bsrMaskPtr,
        const int*         bsrRowPtr,
        const int*         bsrEndPtr,
        const int*         bsrColInd,
        int                blockDim,
        const float*       x,
        const float*       beta,
        float*             y)

cusparseStatus_t
cusparseDbsrxmv(cusparseHandle_t handle,
               cusparseDirection_t dir,
               cusparseOperation_t trans,
               int                sizeofMask,
               int                mb,
               int                nb,
               int                nnzb,
               const double*       alpha,
               const cusparseMatDescr_t descr,
               const double*       bsrVal,
               const int*         bsrMaskPtr,
               const int*         bsrRowPtr,
               const int*         bsrEndPtr,
               const int*         bsrColInd,
               int                blockDim,
               const double*       x,
               const double*       beta,
               double*             y)

cusparseStatus_t
cusparseCbsrxmv(cusparseHandle_t handle,
               cusparseDirection_t dir,
               cusparseOperation_t trans,
               int                sizeofMask,
               int                mb,
               int                nb,
               int                nnzb,
               const cuComplex*    alpha,
               const cusparseMatDescr_t descr,
               const cuComplex*    bsrVal,
               const int*         bsrMaskPtr,
               const int*         bsrRowPtr,
               const int*         bsrEndPtr,
               const int*         bsrColInd,
               int                blockDim,
               const cuComplex*    x,
               const cuComplex*    beta,
               cuComplex*         y)

cusparseStatus_t
cusparseZbsrxmv(cusparseHandle_t handle,
               cusparseDirection_t dir,
               cusparseOperation_t trans,
               int                sizeofMask,
               int                mb,
               int                nb,

```

```

int          nnzb,
const cuDoubleComplex* alpha,
const cusparseMatDescr_t descr,
const cuDoubleComplex* bsrVal,
const int*   bsrMaskPtr,
const int*   bsrRowPtr,
const int*   bsrEndPtr,
const int*   bsrColInd,
int          blockDim,
const cuDoubleComplex* x,
const cuDoubleComplex* beta,
cuDoubleComplex* y)

```

This function performs a `bsrmv` and a mask operation

$$y(\text{mask}) = (\alpha * \text{op}(A) * x + \beta * y)(\text{mask})$$

where A is an $(mb * \text{blockDim}) \times (nb * \text{blockDim})$ sparse matrix that is defined in BSRX storage format by the four arrays `bsrVal`, `bsrRowPtr`, `bsrEndPtr`, and `bsrColInd`; x and y are vectors; α and β are scalars; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

The mask operation is defined by array `bsrMaskPtr` which contains updated block row indices of y . If row i is not specified in `bsrMaskPtr`, then `bsrxmv()` does not touch row block i of A and y .

For example, consider the 2×3 block matrix A :

$$A = \begin{bmatrix} A_{11} & A_{12} & O \\ A_{21} & A_{22} & A_{23} \end{bmatrix}$$

and its one-based BSR format (three vector form) is

$$\begin{aligned} \text{bsrVal} &= [A_{11} \ A_{12} \ A_{21} \ A_{22} \ A_{23}] \\ \text{bsrRowPtr} &= [1 \ 3 \ 6] \\ \text{bsrColInd} &= [1 \ 2 \ 1 \ 2 \ 3] \end{aligned}$$

Suppose we want to do the following `bsrmv` operation on a matrix \bar{A} which is slightly different from A .

$$\begin{bmatrix} y_1 \\ y_2 \end{bmatrix} := \text{alpha} * \left(\bar{A} = \begin{bmatrix} O & O & O \\ O & A_{22} & O \end{bmatrix} \right) * \begin{bmatrix} x_1 \\ x_2 \\ x_3 \end{bmatrix} + \begin{bmatrix} y_1 \\ \text{beta} * y_2 \end{bmatrix}$$

We don't need to create another BSR format for the new matrix \bar{A} , all that we should do is to keep `bsrVal` and `bsrColInd` unchanged, but modify `bsrRowPtr` and add an additional array `bsrEndPtr` which points to the last nonzero elements per row of \bar{A} plus 1.

For example, the following `bsrRowPtr` and `bsrEndPtr` can represent matrix \bar{A} :

$$\begin{aligned} \text{bsrRowPtr} &= [1 \ 4] \\ \text{bsrEndPtr} &= [1 \ 5] \end{aligned}$$

Further we can use a mask operator (specified by array `bsrMaskPtr`) to update particular block row indices of y only because y_1 is never changed. In this case, `bsrMaskPtr = [2]` and `sizeofMask=1`.

The mask operator is equivalent to the following operation:

$$\begin{bmatrix} ? \\ y_2 \end{bmatrix} := \mathit{alpha} * \begin{bmatrix} ? & ? & ? \\ O & A_{22} & O \end{bmatrix} * \begin{bmatrix} x_1 \\ x_2 \\ x_3 \end{bmatrix} + \mathit{beta} * \begin{bmatrix} ? \\ y_2 \end{bmatrix}$$

If a block row is not present in the `bsrMaskPtr`, then no calculation is performed on that row, and the corresponding value in y is unmodified. The question mark "?" is used to indicate row blocks not in `bsrMaskPtr`.

In this case, first row block is not present in `bsrMaskPtr`, so `bsrRowPtr[0]` and `bsrEndPtr[0]` are not touched also.

$$\begin{aligned} \mathit{bsrRowPtr} &= [? \quad 4] \\ \mathit{bsrEndPtr} &= [? \quad 5] \end{aligned}$$

`bsrxmv()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

A couple of comments on `bsrxmv()`:

- ▶ Only `blockDim > 1` is supported
- ▶ Only `CUSPARSE_OPERATION_NON_TRANSPOSE` and `CUSPARSE_MATRIX_TYPE_GENERAL` are supported.
- ▶ Parameters `bsrMaskPtr`, `bsrRowPtr`, `bsrEndPtr` and `bsrColInd` are consistent with base index, either one-based or zero-based. The above example is one-based.

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dir</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>trans</code>	the operation $\mathit{op}(A)$. Only <code>CUSPARSE_OPERATION_NON_TRANSPOSE</code> is supported.
<code>sizeofMask</code>	number of updated block rows of y .
<code>mb</code>	number of block rows of matrix A .
<code>nb</code>	number of block columns of matrix A .
<code>nnzb</code>	number of nonzero blocks of matrix A .
<code>alpha</code>	<type> scalar used for multiplication.

descr	the descriptor of matrix <i>A</i> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
bsrVal	<type> array of <code>nnz</code> nonzero blocks of matrix <i>A</i> .
bsrMaskPtr	integer array of <code>sizeofMask</code> elements that contains the indices corresponding to updated block rows.
bsrRowPtr	integer array of <code>mb</code> elements that contains the start of every block row.
bsrEndPtr	integer array of <code>mb</code> elements that contains the end of the every block row plus one.
bsrColInd	integer array of <code>nnzb</code> column indices of the nonzero blocks of matrix <i>A</i> .
blockDim	block dimension of sparse matrix <i>A</i> , larger than zero.
x	<type> vector of <code>nb * blockDim</code> elements.
beta	<type> scalar used for multiplication. If beta is zero, y does not have to be a valid input.
y	<type> vector of <code>mb * blockDim</code> elements.

See [cusparseStatus_t](#) for the description of the return status

9.3. cusparse<t>bsrsv2_bufferSize()

```

cusparseStatus_t
cusparseSbsrsv2_bufferSize(cusparseHandle_t      handle,
                          cusparseDirection_t   dirA,
                          cusparseOperation_t   transA,
                          int                   mb,
                          int                   nnzb,
                          const cusparseMatDescr_t descrA,
                          float*               bsrValA,
                          const int*           bsrRowPtrA,
                          const int*           bsrColIndA,
                          int                   blockDim,
                          bsrsv2Info_t         info,
                          int*                 pBufferSizeInBytes)

```

```

cusparseStatus_t
cusparseDbsrsv2_bufferSize(cusparseHandle_t      handle,
                          cusparseDirection_t   dirA,
                          cusparseOperation_t   transA,
                          int                   mb,
                          int                   nnzb,
                          const cusparseMatDescr_t descrA,
                          double*              bsrValA,
                          const int*           bsrRowPtrA,
                          const int*           bsrColIndA,

```

```

        int
        bsrsv2Info_t
        int*
        blockDim,
        info,
        pBufferSizeInBytes)

cusparsesStatus_t
cusparsesCbsrsv2_bufferSize(cusparsesHandle_t      handle,
                           cusparsesDirection_t   dirA,
                           cusparsesOperation_t    transA,
                           int                     mb,
                           int                     nnzb,
                           const cusparsesMatDescr_t descrA,
                           cuComplex*             bsrValA,
                           const int*              bsrRowPtrA,
                           const int*              bsrColIndA,
                           int                     blockDim,
                           bsrsv2Info_t           info,
                           int*                    pBufferSizeInBytes)

cusparsesStatus_t
cusparsesZbsrsv2_bufferSize(cusparsesHandle_t      handle,
                            cusparsesDirection_t   dirA,
                            cusparsesOperation_t    transA,
                            int                     mb,
                            int                     nnzb,
                            const cusparsesMatDescr_t descrA,
                            cuDoubleComplex*       bsrValA,
                            const int*              bsrRowPtrA,
                            const int*              bsrColIndA,
                            int                     blockDim,
                            bsrsv2Info_t           info,
                            int*                    pBufferSizeInBytes)

```

This function returns size of the buffer used in `bsrsv2`, a new sparse triangular linear system $\text{op}(A) * y = \alpha x$.

A is an $(mb * \text{blockDim}) \times (mb * \text{blockDim})$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`; x and y are the right-hand-side and the solution vectors; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

Although there are six combinations in terms of parameter `trans` and the upper (lower) triangular part of A , `bsrsv2_bufferSize()` returns the maximum size buffer among these combinations. The buffer size depends on the dimensions `mb`, `blockDim`, and the number of nonzero blocks of the matrix `nnzb`. If the user changes the matrix, it is necessary to call `bsrsv2_bufferSize()` again to have the correct buffer size; otherwise a segmentation fault may occur.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
--------	---

dirA	storage format of blocks, either CUSPARSE_DIRECTION_ROW or CUSPARSE_DIRECTION_COLUMN.
transA	the operation $op(A)$.
mb	number of block rows of matrix A.
nnzb	number of nonzero blocks of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL, while the supported diagonal types are CUSPARSE_DIAG_TYPE_UNIT and CUSPARSE_DIAG_TYPE_NON_UNIT.
bsrValA	<type> array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) nonzero blocks of matrix A.
bsrRowPtrA	integer array of mb + 1 elements that contains the start of every block row and the end of the last block row plus one.
bsrColIndA	integer array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) column indices of the nonzero blocks of matrix A.
blockDim	block dimension of sparse matrix A; must be larger than zero.

Output

info	record of internal states based on different algorithms.
pBufferSizeInBytes	number of bytes of the buffer used in the bsrsv2_analysis() and bsrsv2_solve().

See [cusparseStatus_t](#) for the description of the return status

9.4. cusparse<t>bsrsv2_analysis()

```

cusparseStatus_t
cusparseBsrsv2_analysis(cusparseHandle_t      handle,
                       cusparseDirection_t    dirA,
                       cusparseOperation_t    transA,
                       int                    mb,
                       int                    nnzb,
                       const cusparseMatDescr_t descrA,
                       const float*          bsrValA,
                       const int*           bsrRowPtrA,
                       const int*           bsrColIndA,
                       int                    blockDim,
                       bsrsv2Info_t          info,
                       cusparseSolvePolicy_t policy,
                       void*                 pBuffer)

cusparseStatus_t

```

```

cusparseDbsrsv2_analysis(cusparseHandle_t      handle,
                        cusparseDirection_t    dirA,
                        cusparseOperation_t    transA,
                        int                    mb,
                        int                    nnzb,
                        const cusparseMatDescr_t descrA,
                        const double*         bsrValA,
                        const int*           bsrRowPtrA,
                        const int*           bsrColIndA,
                        int                    blockDim,
                        bsrsv2Info_t         info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

cusparseStatus_t
cusparseDbsrsv2_analysis(cusparseHandle_t      handle,
                        cusparseDirection_t    dirA,
                        cusparseOperation_t    transA,
                        int                    mb,
                        int                    nnzb,
                        const cusparseMatDescr_t descrA,
                        const cuComplex*       bsrValA,
                        const int*           bsrRowPtrA,
                        const int*           bsrColIndA,
                        int                    blockDim,
                        bsrsv2Info_t         info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

cusparseStatus_t
cusparseZbsrsv2_analysis(cusparseHandle_t      handle,
                        cusparseDirection_t    dirA,
                        cusparseOperation_t    transA,
                        int                    mb,
                        int                    nnzb,
                        const cusparseMatDescr_t descrA,
                        const cuDoubleComplex* bsrValA,
                        const int*           bsrRowPtrA,
                        const int*           bsrColIndA,
                        int                    blockDim,
                        bsrsv2Info_t         info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

```

This function performs the analysis phase of `bsrsv2`, a new sparse triangular linear system $\text{op}(A) * y = \alpha x$.

A is an $(mb * \text{blockDim}) \times (mb * \text{blockDim})$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`; x and y are the right-hand side and the solution vectors; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

The block of BSR format is of size `blockDim*blockDim`, stored as column-major or row-major as determined by parameter `dirA`, which is either `CUSPARSE_DIRECTION_COLUMN` or `CUSPARSE_DIRECTION_ROW`. The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, and the fill mode and diagonal type are ignored.

It is expected that this function will be executed only once for a given matrix and a particular operation type.

This function requires a buffer size returned by `bsrsv2_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `bsrsv2_analysis()` reports a structural zero and computes level information, which stored in the opaque structure `info`. The level information can extract more parallelism for a triangular solver. However `bsrsv2_solve()` can be done without level information. To disable level information, the user needs to specify the policy of the triangular solver as `CUSPARSE_SOLVE_POLICY_NO_LEVEL`.

Function `bsrsv2_analysis()` always reports the first structural zero, even when parameter `policy` is `CUSPARSE_SOLVE_POLICY_NO_LEVEL`. No structural zero is reported if `CUSPARSE_DIAG_TYPE_UNIT` is specified, even if block $A(j, j)$ is missing for some j . The user needs to call `cusparseXbsrsv2_zeroPivot()` to know where the structural zero is.

It is the user's choice whether to call `bsrsv2_solve()` if `bsrsv2_analysis()` reports a structural zero. In this case, the user can still call `bsrsv2_solve()`, which will return a numerical zero at the same position as a structural zero. However the result x is meaningless.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dirA</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>transA</code>	the operation $\text{op}(A)$.
<code>mb</code>	number of block rows of matrix A .
<code>nnzb</code>	number of nonzero blocks of matrix A .
<code>descrA</code>	the descriptor of matrix A . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
<code>bsrValA</code>	<type> array of $\text{nnzb} (= \text{bsrRowPtrA}(\text{mb}) - \text{bsrRowPtrA}(0))$ nonzero blocks of matrix A .
<code>bsrRowPtrA</code>	integer array of $\text{mb} + 1$ elements that contains the start of every block row and the end of the last block row plus one.
<code>bsrColIndA</code>	integer array of $\text{nnzb} (= \text{bsrRowPtrA}(\text{mb}) - \text{bsrRowPtrA}(0))$ column indices of the nonzero blocks of matrix A .

blockDim	block dimension of sparse matrix A, larger than zero.
info	structure initialized using <code>cusparseCreateBsrsv2Info()</code> .
policy	the supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
pBuffer	buffer allocated by the user, the size is return by <code>bsrsv2_bufferSize()</code> .

Output

info	structure filled with information collected during the analysis phase (that should be passed to the solve phase unchanged).
------	---

See [cusparseStatus_t](#) for the description of the return status

9.5. `cusparse<t>bsrsv2_solve()`

```

cusparseStatus_t
cusparseSbsrsv2_solve(cusparseHandle_t      handle,
                     cusparseDirection_t   dirA,
                     cusparseOperation_t   transA,
                     int                   mb,
                     int                   nnzb,
                     const float*         alpha,
                     const cusparseMatDescr_t descrA,
                     const float*       bsrValA,
                     const int*         bsrRowPtrA,
                     const int*         bsrColIndA,
                     int                 blockDim,
                     bsrsv2Info_t        info,
                     const float*       x,
                     float*              y,
                     cusparseSolvePolicy_t policy,
                     void*               pBuffer)

cusparseStatus_t
cusparseDbsrsv2_solve(cusparseHandle_t      handle,
                     cusparseDirection_t   dirA,
                     cusparseOperation_t   transA,
                     int                   mb,
                     int                   nnzb,
                     const double*        alpha,
                     const cusparseMatDescr_t descrA,
                     const double*       bsrValA,
                     const int*         bsrRowPtrA,
                     const int*         bsrColIndA,
                     int                 blockDim,
                     bsrsv2Info_t        info,
                     const double*       x,
                     double*             y,
                     cusparseSolvePolicy_t policy,

```

```

        void*                                pBuffer)
cusparseStatus_t
cusparseCbsrsv2_solve(cusparseHandle_t      handle,
                     cusparseDirection_t   dirA,
                     cusparseOperation_t   transA,
                     int                   mb,
                     int                   nnzb,
                     const cuComplex*     alpha,
                     const cusparseMatDescr_t descrA,
                     const cuComplex*     bsrValA,
                     const int*           bsrRowPtrA,
                     const int*           bsrColIndA,
                     int                   blockDim,
                     bsrsv2Info_t         info,
                     const cuComplex*     x,
                     cuComplex*          y,
                     cusparseSolvePolicy_t policy,
                     void*                pBuffer)

cusparseStatus_t
cusparseZbsrsv2_solve(cusparseHandle_t      handle,
                     cusparseDirection_t   dirA,
                     cusparseOperation_t   transA,
                     int                   mb,
                     int                   nnzb,
                     const cuDoubleComplex* alpha,
                     const cusparseMatDescr_t descrA,
                     const cuDoubleComplex* bsrValA,
                     const int*           bsrRowPtrA,
                     const int*           bsrColIndA,
                     int                   blockDim,
                     bsrsv2Info_t         info,
                     const cuDoubleComplex* x,
                     cuDoubleComplex*     y,
                     cusparseSolvePolicy_t policy,
                     void*                pBuffer)

```

This function performs the solve phase of `bsrsv2`, a new sparse triangular linear system $\text{op}(A) * y = \alpha x$.

A is an $(mb * \text{blockDim}) \times (mb * \text{blockDim})$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`; x and y are the right-hand-side and the solution vectors; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

The block in BSR format is of size $\text{blockDim} * \text{blockDim}$, stored as column-major or row-major as determined by parameter `dirA`, which is either `CUSPARSE_DIRECTION_COLUMN` or `CUSPARSE_DIRECTION_ROW`. The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, and the fill mode and diagonal type are ignored. Function `bsrsv02_solve()` can support an arbitrary `blockDim`.

This function may be executed multiple times for a given matrix and a particular operation type.

This function requires a buffer size returned by `bsrsv2_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Although `bsrsv2_solve()` can be done without level information, the user still needs to be aware of consistency. If `bsrsv2_analysis()` is called with policy `CUSPARSE_SOLVE_POLICY_USE_LEVEL`, `bsrsv2_solve()` can be run with or without levels. On the other hand, if `bsrsv2_analysis()` is called with `CUSPARSE_SOLVE_POLICY_NO_LEVEL`, `bsrsv2_solve()` can only accept `CUSPARSE_SOLVE_POLICY_NO_LEVEL`; otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The level information may not improve the performance, but may spend extra time doing analysis. For example, a tridiagonal matrix has no parallelism.

In this case, `CUSPARSE_SOLVE_POLICY_NO_LEVEL` performs better than `CUSPARSE_SOLVE_POLICY_USE_LEVEL`. If the user has an iterative solver, the best approach is to do `bsrsv2_analysis()` with `CUSPARSE_SOLVE_POLICY_USE_LEVEL` once. Then do `bsrsv2_solve()` with `CUSPARSE_SOLVE_POLICY_NO_LEVEL` in the first run, and with `CUSPARSE_SOLVE_POLICY_USE_LEVEL` in the second run, and pick the fastest one to perform the remaining iterations.

Function `bsrsv02_solve()` has the same behavior as `csrsv02_solve()`. That is, `bsr2csr(bsrsv02(A)) = csrsv02(bsr2csr(A))`. The numerical zero of `csrsv02_solve()` means there exists some zero $A(j, j)$. The numerical zero of `bsrsv02_solve()` means there exists some block $A(j, j)$ that is not invertible.

Function `bsrsv2_solve()` reports the first numerical zero, including a structural zero. No numerical zero is reported if `CUSPARSE_DIAG_TYPE_UNIT` is specified, even if $A(j, j)$ is not invertible for some j . The user needs to call `cusparseXbsrsv2_zeroPivot()` to know where the numerical zero is.

The function supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

For example, suppose L is a lower triangular matrix with unit diagonal, then the following code solves $L*y=x$ by level information.

```
// Suppose that L is m x m sparse matrix represented by BSR format,
// The number of block rows/columns is mb, and
// the number of nonzero blocks is nnzb.
// L is lower triangular with unit diagonal.
// Assumption:
// - dimension of matrix L is m(=mb*blockDim),
// - matrix L has nnz(=nnzb*blockDim*blockDim) nonzero elements,
// - handle is already created by cusparseCreate(),
// - (d_bsrRowPtr, d_bsrColInd, d_bsrVal) is BSR of L on device memory,
// - d_x is right hand side vector on device memory.
// - d_y is solution vector on device memory.
// - d_x and d_y are of size m.
cusparseMatDescr_t descr = 0;
bsrsv2Info_t info = 0;
int pBufferSize;
void *pBuffer = 0;
```

```

int structural_zero;
int numerical_zero;
const double alpha = 1.;
const cusparseSolvePolicy_t policy = CUSPARSE_SOLVE_POLICY_USE_LEVEL;
const cusparseOperation_t trans = CUSPARSE_OPERATION_NON_TRANSPOSE;
const cusparseDirection_t dir = CUSPARSE_DIRECTION_COLUMN;

// step 1: create a descriptor which contains
// - matrix L is base-1
// - matrix L is lower triangular
// - matrix L has unit diagonal, specified by parameter CUSPARSE_DIAG_TYPE_UNIT
// (L may not have all diagonal elements.)
cusparseCreateMatDescr(&descr);
cusparseSetMatIndexBase(descr, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatFillMode(descr, CUSPARSE_FILL_MODE_LOWER);
cusparseSetMatDiagType(descr, CUSPARSE_DIAG_TYPE_UNIT);

// step 2: create a empty info structure
cusparseCreateBsrsv2Info(&info);

// step 3: query how much memory used in bsrsv2, and allocate the buffer
cusparseDbstrsv2_bufferSize(handle, dir, trans, mb, nnzb, descr,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, &pBufferSize);

// pBuffer returned by cudaMalloc is automatically aligned to 128 bytes.
cudaMalloc((void**)&pBuffer, pBufferSize);

// step 4: perform analysis
cusparseDbstrsv2_analysis(handle, dir, trans, mb, nnzb, descr,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim,
    info, policy, pBuffer);
// L has unit diagonal, so no structural zero is reported.
status = cusparseXbsrsv2_zeroPivot(handle, info, &structural_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("L(%d,%d) is missing\n", structural_zero, structural_zero);
}

// step 5: solve L*y = x
cusparseDbstrsv2_solve(handle, dir, trans, mb, nnzb, &alpha, descr,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, info,
    d_x, d_y, policy, pBuffer);
// L has unit diagonal, so no numerical zero is reported.
status = cusparseXbsrsv2_zeroPivot(handle, info, &numerical_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("L(%d,%d) is zero\n", numerical_zero, numerical_zero);
}

// step 6: free resources
cudaFree(pBuffer);
cusparseDestroyBsrsv2Info(info);
cusparseDestroyMatDescr(descr);
cusparseDestroy(handle);

```

Input

handle	handle to the cuSPARSE library context.
dirA	storage format of blocks, either CUSPARSE_DIRECTION_ROW or CUSPARSE_DIRECTION_COLUMN.
transA	the operation $op(A)$.
mb	number of block rows and block columns of matrix A.
alpha	<type> scalar used for multiplication.

descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
bsrValA	<type> array of <code>nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0))</code> nonzero blocks of matrix A.
bsrRowPtrA	integer array of <code>mb + 1</code> elements that contains the start of every block row and the end of the last block row plus one.
bsrColIndA	integer array of <code>nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0))</code> column indices of the nonzero blocks of matrix A.
blockDim	block dimension of sparse matrix A, larger than zero.
info	structure with information collected during the analysis phase (that should have been passed to the solve phase unchanged).
x	<type> right-hand-side vector of size m.
policy	the supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
pBuffer	buffer allocated by the user, the size is returned by <code>bsrsv2_bufferSize()</code> .

Output

y	<type> solution vector of size m.
---	-----------------------------------

See [cusparseStatus_t](#) for the description of the return status

9.6. cusparseXbsrsv2_zeroPivot()

```
cusparseStatus_t
cusparseXbsrsv2_zeroPivot(cusparseHandle_t handle,
                          bsrsv2Info_t      info,
                          int*              position)
```

If the returned error code is `CUSPARSE_STATUS_ZERO_PIVOT`, `position=j` means `A(j, j)` is either structural zero or numerical zero (singular block). Otherwise `position=-1`.

The `position` can be 0-based or 1-based, the same as the matrix.

Function `cusparseXbsrsv2_zeroPivot()` is a blocking call. It calls `cudaDeviceSynchronize()` to make sure all previous kernels are done.

The `position` can be in the host memory or device memory. The user can set the proper mode with `cusparseSetPointerMode()`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
info	info contains a structural zero or numerical zero if the user already called <code>bsrsv2_analysis()</code> or <code>bsrsv2_solve()</code> .

Output

position	if no structural or numerical zero, position is -1; otherwise if $A(j, j)$ is missing or $U(j, j)$ is zero, position=j.
----------	---

See [cusparsesStatus_t](#) for the description of the return status

9.7. `cusparsesCsrMvEx()` [DEPRECATED]

[DEPRECATED] use [cusparsesSpMV\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparsesStatus_t
cusparsesCsrMvEx_bufferSize(cusparsesHandle_t      handle,
                           cusparsesAlgMode_t     alg,
                           cusparsesOperation_t   transA,
                           int                    m,
                           int                    n,
                           int                    nnz,
                           const void*           alpha,
                           cudaDataType           alphasType,
                           const cusparsesMatDescr_t descrA,
                           const void*           csrValA,
                           cudaDataType           csrValAtype,
                           const int*             csrRowPtrA,
                           const int*             csrColIndA,
                           const void*           x,
                           cudaDataType           xtype,
                           const void*           beta,
                           cudaDataType           betatype,
                           void*                 y,
                           cudaDataType           ytype,
                           cudaDataType           executiontype,
                           size_t*               bufferSizeInBytes)

cusparsesStatus_t
cusparsesCsrMvEx(cusparsesHandle_t      handle,
                 cusparsesAlgMode_t     alg,
                 cusparsesOperation_t   transA,

```

```

int          m,
int          n,
int          nnz,
const void*  alpha,
cudaDataType alphatype,
const cusparseMatDescr_t descrA,
const void*  csrValA,
cudaDataType csrValAtype,
const int*   csrRowPtrA,
const int*   csrColIndA,
const void*  x,
cudaDataType xtype,
const void*  beta,
cudaDataType betatype,
void*        y,
cudaDataType ytype,
cudaDataType executiontype,
void*        buffer)

```

This function performs the matrix-vector operation

$$y = \alpha * \text{op}(A) * x + \beta * y$$

A is an $m \times n$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`; `x` and `y` are vectors;

The function `cusparseCsrMvEx_bufferSize` returns the size of the workspace needed by `cusparseCsrMvEx`.

The function has the following limitations:

- ▶ All pointers should be aligned with 128 bytes
- ▶ Only `CUSPARSE_OPERATION_NON_TRANSPOSE` operation is supported
- ▶ Only `CUSPARSE_MATRIX_TYPE_GENERAL` matrix type is supported
- ▶ Only `CUSPARSE_INDEX_BASE_ZERO` indexing is supported
- ▶ Half-precision is not supported
- ▶ The minimum GPU architecture supported is SM_53

The function has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input specifically required by `cusparseCsrMvEx`

<code>alg</code>	Algorithm implementation for <code>csmv</code> , see <code>cusparseAlgMode_t</code> for possible values.
<code>alphatype</code>	Data type of <code>alpha</code> .
<code>csrValAtype</code>	Data type of <code>csrValA</code> .

xtype	Data type of x.
betatype	Data type of beta.
ytype	Data type of y.
executiontype	Data type used for computation.
bufferSizeInBytes	Pointer to a size_t variable, which will be assigned with the size of workspace needed by cusparseCsrnvEx.
buffer	Pointer to workspace buffer

See [cusparseStatus_t](#) for the description of the return status

9.8. `cusparse<t>csrsv2_bufferSize()` [DEPRECATED]

[DEPRECATED] use [cusparseSpSV\(\)](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseCsrsv2_bufferSize(cusparseHandle_t      handle,
                        cusparseOperation_t    transA,
                        int                    m,
                        int                    nnz,
                        const cusparseMatDescr_t descrA,
                        float*                 csrValA,
                        const int*             csrRowPtrA,
                        const int*             csrColIndA,
                        csrsv2Info_t          info,
                        int*                   pBufferSizeInBytes)
```

```
cusparseStatus_t
cusparseDcsrsv2_bufferSize(cusparseHandle_t      handle,
                          cusparseOperation_t    transA,
                          int                    m,
                          int                    nnz,
                          const cusparseMatDescr_t descrA,
                          double*                 csrValA,
                          const int*             csrRowPtrA,
                          const int*             csrColIndA,
                          csrsv2Info_t          info,
                          int*                   pBufferSizeInBytes)
```

```
cusparseStatus_t
cusparseCcsrsv2_bufferSize(cusparseHandle_t      handle,
                          cusparseOperation_t    transA,
                          int                    m,
                          int                    nnz,
                          const cusparseMatDescr_t descrA,
                          cuComplex*             csrValA,
                          const int*             csrRowPtrA,
                          const int*             csrColIndA,
                          csrsv2Info_t          info,
                          int*                   pBufferSizeInBytes)
```

```

cusparseStatus_t
cusparseZcsrsv2_bufferSize(cusparseHandle_t      handle,
                          cusparseOperation_t    transA,
                          int                    m,
                          int                    nnz,
                          const cusparseMatDescr_t descrA,
                          cuDoubleComplex*      csrValA,
                          const int*             csrRowPtrA,
                          const int*             csrColIndA,
                          csrsv2Info_t          info,
                          int*                   pBufferSizeInBytes)

```

This function returns the size of the buffer used in `csrsv2`, a new sparse triangular linear system $\text{op}(A) * y = \alpha x$.

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`; x and y are the right-hand-side and the solution vectors; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

Although there are six combinations in terms of the parameter `trans` and the upper (lower) triangular part of A , `csrsv2_bufferSize()` returns the maximum size buffer of these combinations. The buffer size depends on the dimension and the number of nonzero elements of the matrix. If the user changes the matrix, it is necessary to call `csrsv2_bufferSize()` again to have the correct buffer size; otherwise, a segmentation fault may occur.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>transA</code>	the operation $\text{op}(A)$.
<code>m</code>	number of rows of matrix A .
<code>nnz</code>	number of nonzero elements of matrix A .
<code>descrA</code>	the descriptor of matrix A . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
<code>csrValA</code>	<type> array of $\text{nnz} (= \text{csrRowPtrA}(m) - \text{csrRowPtrA}(0))$ nonzero elements of matrix A .
<code>csrRowPtrA</code>	integer array of $m + 1$ elements that contains the start of every row and the end of the last row plus one.

csrColIndA	integer array of nnz (= csrRowPtrA(m) - csrRowPtrA(0)) column indices of the nonzero elements of matrix A.
------------	---

Output

info	record of internal states based on different algorithms.
pBufferSizeInBytes	number of bytes of the buffer used in the csrsv2_analysis and csrsv2_solve.

See [cusparseStatus_t](#) for the description of the return status

9.9. cusparse<t>csrsv2_analysis() [DEPRECATED]

[DEPRECATED] use [cusparseSpSV\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparseStatus_t
cusparseScsrsv2_analysis(cusparseHandle_t      handle,
                        cusparseOperation_t    transA,
                        int                    m,
                        int                    nnz,
                        const cusparseMatDescr_t descrA,
                        const float*          csrValA,
                        const int*            csrRowPtrA,
                        const int*            csrColIndA,
                        csrsv2Info_t          info,
                        cusparseSolvePolicy_t policy,
                        void*                  pBuffer)

cusparseStatus_t
cusparseDcsrsv2_analysis(cusparseHandle_t      handle,
                        cusparseOperation_t    transA,
                        int                    m,
                        int                    nnz,
                        const cusparseMatDescr_t descrA,
                        const double*          csrValA,
                        const int*            csrRowPtrA,
                        const int*            csrColIndA,
                        csrsv2Info_t          info,
                        cusparseSolvePolicy_t policy,
                        void*                  pBuffer)

cusparseStatus_t
cusparseCcsrsv2_analysis(cusparseHandle_t      handle,
                        cusparseOperation_t    transA,
                        int                    m,
                        int                    nnz,
                        const cusparseMatDescr_t descrA,
                        const cuComplex*       csrValA,
                        const int*            csrRowPtrA,
                        const int*            csrColIndA,

```

```

        csrsv2Info_t          info,
        cusparseSolvePolicy_t policy,
        void*                pBuffer)

cusparseStatus_t
cusparseZcsrsv2_analysis(cusparseHandle_t handle,
                        cusparseOperation_t transA,
                        int m,
                        int nnz,
                        const cusparseMatDescr_t descrA,
                        const cuDoubleComplex* csrValA,
                        const int* csrRowPtrA,
                        const int* csrColIndA,
                        csrsv2Info_t info,
                        cusparseSolvePolicy_t policy,
                        void* pBuffer)

```

This function performs the analysis phase of `csrsv2`, a new sparse triangular linear system $\text{op}(A) * y = \alpha x$.

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`; x and y are the right-hand-side and the solution vectors; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

It is expected that this function will be executed only once for a given matrix and a particular operation type.

This function requires a buffer size returned by `csrsv2_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `csrsv2_analysis()` reports a structural zero and computes level information that is stored in opaque structure `info`. The level information can extract more parallelism for a triangular solver. However `csrsv2_solve()` can be done without level information. To disable level information, the user needs to specify the policy of the triangular solver as `CUSPARSE_SOLVE_POLICY_NO_LEVEL`.

Function `csrsv2_analysis()` always reports the first structural zero, even if the policy is `CUSPARSE_SOLVE_POLICY_NO_LEVEL`. No structural zero is reported if `CUSPARSE_DIAG_TYPE_UNIT` is specified, even if $A(j, j)$ is missing for some j . The user needs to call `cusparseXcsrsv2_zeroPivot()` to know where the structural zero is.

It is the user's choice whether to call `csrsv2_solve()` if `csrsv2_analysis()` reports a structural zero. In this case, the user can still call `csrsv2_solve()` which will return a numerical zero in the same position as the structural zero. However the result x is meaningless.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available

- The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
transA	the operation $op(A)$.
m	number of rows of matrix A.
nnz	number of nonzero elements of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
csrValA	<type> array of $nnz (= csrRowPtrA(m) - csrRowPtrA(0))$ nonzero elements of matrix A.
csrRowPtrA	integer array of $m + 1$ elements that contains the start of every row and the end of the last row plus one.
csrColIndA	integer array of $nnz (= csrRowPtrA(m) - csrRowPtrA(0))$ column indices of the nonzero elements of matrix A.
info	structure initialized using <code>cusparseCreateCsrsv2Info()</code> .
policy	The supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
pBuffer	buffer allocated by the user, the size is returned by <code>csrsv2_bufferSize()</code> .

Output

info	structure filled with information collected during the analysis phase (that should be passed to the solve phase unchanged).
------	---

See [cusparseStatus_t](#) for the description of the return status

9.10. `cusparse<t>csrsv2_solve()` [DEPRECATED]

[DEPRECATED] use [cusparseSpSV\(\)](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseCsrsv2_solve(cusparseHandle_t      handle,
                    cusparseOperation_t    transA,
```

```

        int m,
        int nnz,
        const float* alpha,
        const cusparseMatDescr_t descra,
        const float* csrValA,
        const int* csrRowPtrA,
        const int* csrColIndA,
        csrsv2Info_t info,
        const float* x,
        float* Y,
        cusparseSolvePolicy_t policy,
        void* pBuffer)

cusparseStatus_t
cusparseDcsrsv2_solve(cusparseHandle_t handle,
                     cusparseOperation_t transA,
                     int m,
                     int nnz,
                     const double* alpha,
                     const cusparseMatDescr_t descra,
                     const double* csrValA,
                     const int* csrRowPtrA,
                     const int* csrColIndA,
                     csrsv2Info_t info,
                     const double* x,
                     double* Y,
                     cusparseSolvePolicy_t policy,
                     void* pBuffer)

cusparseStatus_t
cusparseCcsrsv2_solve(cusparseHandle_t handle,
                     cusparseOperation_t transA,
                     int m,
                     int nnz,
                     const cuComplex* alpha,
                     const cusparseMatDescr_t descra,
                     const cuComplex* csrValA,
                     const int* csrRowPtrA,
                     const int* csrColIndA,
                     csrsv2Info_t info,
                     const cuComplex* x,
                     cuComplex* Y,
                     cusparseSolvePolicy_t policy,
                     void* pBuffer)

cusparseStatus_t
cusparseZcsrsv2_solve(cusparseHandle_t handle,
                     cusparseOperation_t transA,
                     int m,
                     int nnz,
                     const cuDoubleComplex* alpha,
                     const cusparseMatDescr_t descra,
                     const cuDoubleComplex* csrValA,
                     const int* csrRowPtrA,
                     const int* csrColIndA,
                     csrsv2Info_t info,
                     const cuDoubleComplex* x,
                     cuDoubleComplex* Y,
                     cusparseSolvePolicy_t policy,
                     void* pBuffer)

```


This function performs the solve phase of `csrsv2`, a new sparse triangular linear system $\text{op}(A) * y = \alpha x$.

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`; x and y are the right-hand-side and the solution vectors; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANSPPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANSPPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANSPPOSE} \end{cases}$$

This function may be executed multiple times for a given matrix and a particular operation type.

This function requires the buffer size returned by `csrsv2_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Although `csrsv2_solve()` can be done without level information, the user still needs to be aware of consistency. If `csrsv2_analysis()` is called with policy `CUSPARSE_SOLVE_POLICY_USE_LEVEL`, `csrsv2_solve()` can be run with or without levels. On the contrary, if `csrsv2_analysis()` is called with `CUSPARSE_SOLVE_POLICY_NO_LEVEL`, `csrsv2_solve()` can only accept `CUSPARSE_SOLVE_POLICY_NO_LEVEL`; otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The level information may not improve the performance but spend extra time doing analysis. For example, a tridiagonal matrix has no parallelism. In this case, `CUSPARSE_SOLVE_POLICY_NO_LEVEL` performs better than `CUSPARSE_SOLVE_POLICY_USE_LEVEL`. If the user has an iterative solver, the best approach is to do `csrsv2_analysis()` with `CUSPARSE_SOLVE_POLICY_USE_LEVEL` once. Then do `csrsv2_solve()` with `CUSPARSE_SOLVE_POLICY_NO_LEVEL` in the first run and with `CUSPARSE_SOLVE_POLICY_USE_LEVEL` in the second run, picking faster one to perform the remaining iterations.

Function `csrsv2_solve()` reports the first numerical zero, including a structural zero. If `status` is 0, no numerical zero was found. Furthermore, no numerical zero is reported if `CUSPARSE_DIAG_TYPE_UNIT` is specified, even if $A(j, j)$ is zero for some j . The user needs to call `cusparseXcsrsv2_zeroPivot()` to know where the numerical zero is.

For example, suppose L is a lower triangular matrix with unit diagonal, the following code solves $L*y=x$ by level information.

```
// Suppose that L is m x m sparse matrix represented by CSR format,
// L is lower triangular with unit diagonal.
// Assumption:
// - dimension of matrix L is m,
// - matrix L has nnz number zero elements,
// - handle is already created by cusparseCreate(),
// - (d_csrRowPtr, d_csrColInd, d_csrVal) is CSR of L on device memory,
// - d_x is right hand side vector on device memory,
// - d_y is solution vector on device memory.

cusparseMatDescr_t descr = 0;
csrsv2Info_t info = 0;
int pBufferSize;
void *pBuffer = 0;
int structural_zero;
```

```

int numerical_zero;
const double alpha = 1.;
const cusparseSolvePolicy_t policy = CUSPARSE_SOLVE_POLICY_USE_LEVEL;
const cusparseOperation_t trans = CUSPARSE_OPERATION_NON_TRANSPOSE;

// step 1: create a descriptor which contains
// - matrix L is base-1
// - matrix L is lower triangular
// - matrix L has unit diagonal, specified by parameter CUSPARSE_DIAG_TYPE_UNIT
// (L may not have all diagonal elements.)
cusparseCreateMatDescr(&descr);
cusparseSetMatIndexBase(descr, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatFillMode(descr, CUSPARSE_FILL_MODE_LOWER);
cusparseSetMatDiagType(descr, CUSPARSE_DIAG_TYPE_UNIT);

// step 2: create a empty info structure
cusparseCreateCsrsv2Info(&info);

// step 3: query how much memory used in csrsv2, and allocate the buffer
cusparseDcsrsv2_bufferSize(handle, trans, m, nnz, descr,
    d_csrVal, d_csrRowPtr, d_csrColInd, info, &pBufferSize);
// pBuffer returned by cudaMalloc is automatically aligned to 128 bytes.
cudaMalloc((void**) &pBuffer, pBufferSize);

// step 4: perform analysis
cusparseDcsrsv2_analysis(handle, trans, m, nnz, descr,
    d_csrVal, d_csrRowPtr, d_csrColInd,
    info, policy, pBuffer);
// L has unit diagonal, so no structural zero is reported.
status = cusparseXcsrsv2_zeroPivot(handle, info, &structural_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("L(%d,%d) is missing\n", structural_zero, structural_zero);
}

// step 5: solve L*y = x
cusparseDcsrsv2_solve(handle, trans, m, nnz, &alpha, descr,
    d_csrVal, d_csrRowPtr, d_csrColInd, info,
    d_x, d_y, policy, pBuffer);
// L has unit diagonal, so no numerical zero is reported.
status = cusparseXcsrsv2_zeroPivot(handle, info, &numerical_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("L(%d,%d) is zero\n", numerical_zero, numerical_zero);
}

// step 6: free resources
cudaFree(pBuffer);
cusparseDestroyCsrsv2Info(info);
cusparseDestroyMatDescr(descr);
cusparseDestroy(handle);

```

Remark: `csrsv2_solve()` needs more nonzeros per row to achieve good performance. It would perform better if more than 16 nonzeros per row in average.

The function supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
--------	---

transA	the operation $\text{op}(A)$.
m	number of rows and columns of matrix A.
alpha	<type> scalar used for multiplication.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
csrValA	<type> array of $\text{nnz} (= \text{csrRowPtrA}(m) - \text{csrRowPtrA}(0))$ nonzero elements of matrix A.
csrRowPtrA	integer array of $m + 1$ elements that contains the start of every row and the end of the last row plus one.
csrColIndA	integer array of $\text{nnz} (= \text{csrRowPtrA}(m) - \text{csrRowPtrA}(0))$ column indices of the nonzero elements of matrix A.
info	structure with information collected during the analysis phase (that should have been passed to the solve phase unchanged).
x	<type> right-hand-side vector of size m.
policy	The supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
pBuffer	buffer allocated by the user, the size is return by <code>csrsv2_bufferSize</code> .

Output

y	<type> solution vector of size m.
---	-----------------------------------

See [`cusparseStatus_t`](#) for the description of the return status

9.11. `cusparseXcsrsv2_zeroPivot()` [DEPRECATED]

[DEPRECATED] use [`cusparseSpSV\(\)`](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseXcsrsv2_zeroPivot(cusparseHandle_t handle,
                          csrsv2Info_t      info,
                          int*               position)
```

If the returned error code is `CUSPARSE_STATUS_ZERO_PIVOT`, `position=j` means `A(j, j)` has either a structural zero or a numerical zero. Otherwise `position=-1`.

The `position` can be 0-based or 1-based, the same as the matrix.

Function `cusparseXcsrsv2_zeroPivot()` is a blocking call. It calls `cudaDeviceSynchronize()` to make sure all previous kernels are done.

The `position` can be in the host memory or device memory. The user can set the proper mode with `cusparseSetPointerMode()`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>info</code>	<code>info</code> contains structural zero or numerical zero if the user already called <code>csrsv2_analysis()</code> or <code>csrsv2_solve()</code> .

Output

<code>position</code>	if no structural or numerical zero, <code>position</code> is -1; otherwise, if $A(j, j)$ is missing or $U(j, j)$ is zero, <code>position=j</code> .
-----------------------	---

See [cusparseStatus_t](#) for the description of the return status

9.12. `cusparse<t>gemvi()`

```

cusparseStatus_t
cusparseSgemvi_bufferSize(cusparseHandle_t handle,
                        cusparseOperation_t transA,
                        int m,
                        int n,
                        int nnz,
                        int* pBufferSize)

cusparseStatus_t
cusparseDgemvi_bufferSize(cusparseHandle_t handle,
                        cusparseOperation_t transA,
                        int m,
                        int n,
                        int nnz,
                        int* pBufferSize)

cusparseStatus_t
cusparseCgemvi_bufferSize(cusparseHandle_t handle,
                        cusparseOperation_t transA,
                        int m,
                        int n,
                        int nnz,
                        int* pBufferSize)

```

```

cusparseStatus_t
cusparseZgemvi_bufferSize(cusparseHandle_t handle,
                          cusparseOperation_t transA,
                          int m,
                          int n,
                          int nnz,
                          int* pBufferSize)

```

```

cusparseStatus_t
cusparseSgemvi(cusparseHandle_t handle,
               cusparseOperation_t transA,
               int m,
               int n,
               const float* alpha,
               const float* A,
               int lda,
               int nnz,
               const float* x,
               const int* xInd,
               const float* beta,
               float* y,
               cusparseIndexBase_t idxBase,
               void* pBuffer)

```

```

cusparseStatus_t
cusparseDgemvi(cusparseHandle_t handle,
               cusparseOperation_t transA,
               int m,
               int n,
               const double* alpha,
               const double* A,
               int lda,
               int nnz,
               const double* x,
               const int* xInd,
               const double* beta,
               double* y,
               cusparseIndexBase_t idxBase,
               void* pBuffer)

```

```

cusparseStatus_t
cusparseCgemvi(cusparseHandle_t handle,
               cusparseOperation_t transA,
               int m,
               int n,
               const cuComplex* alpha,
               const cuComplex* A,
               int lda,
               int nnz,
               const cuComplex* x,
               const int* xInd,
               const cuComplex* beta,
               cuComplex* y,
               cusparseIndexBase_t idxBase,
               void* pBuffer)

```

```

cusparseStatus_t
cusparseZgemvi(cusparseHandle_t handle,
               cusparseOperation_t transA,
               int m,

```

```

int n,
const cuDoubleComplex* alpha,
const cuDoubleComplex* A,
int lda,
int nnz,
const cuDoubleComplex* x,
const int* xInd,
const cuDoubleComplex* beta,
cuDoubleComplex* y,
cusparseIndexBase_t idxBase,
void* pBuffer)

```

This function performs the matrix-vector operation

$$y = \alpha * \text{op}(A) * x + \beta * y$$

A is an $m \times n$ dense matrix and a sparse vector x that is defined in a sparse storage format by the two arrays $xVal$, $xInd$ of length nnz , and y is a dense vector; α and β are scalars; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

To simplify the implementation, we have not (yet) optimized the transpose multiple case. We recommend the following for users interested in this case.

1. Convert the matrix from CSR to CSC format using one of the `csr2csc()` functions. Notice that by interchanging the rows and columns of the result you are implicitly transposing the matrix.
2. Call the `gemvi()` function with the `cusparseOperation_t` parameter set to `CUSPARSE_OPERATION_NON_TRANPOSE` and with the interchanged rows and columns of the matrix stored in CSC format. This (implicitly) multiplies the vector by the transpose of the matrix in the original CSR format.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

The function `cusparse<t>gemvi_bufferSize()` returns size of buffer used in `cusparse<t>gemvi()`

Input

handle	handle to the cuSPARSE library context.
trans	the operation $\text{op}(A)$.
m	number of rows of matrix A.
n	number of columns of matrix A.
alpha	<type> scalar used for multiplication.
A	the pointer to dense matrix A.
lda	size of the leading dimension of A.
nnz	number of nonzero elements of vector x.

<code>x</code>	<type> sparse vector of nnz elements of size n if $\text{op}(A) = A$, and size m if $\text{op}(A) = A^T$ or $\text{op}(A) = A^H$
<code>xInd</code>	Indices of non-zero values in <code>x</code>
<code>beta</code>	<type> scalar used for multiplication. If <code>beta</code> is zero, <code>y</code> does not have to be a valid input.
<code>y</code>	<type> dense vector of m elements if $\text{op}(A) = A$, and n elements if $\text{op}(A) = A^T$ or $\text{op}(A) = A^H$
<code>idxBase</code>	0 or 1, for 0 based or 1 based indexing, respectively
<code>pBufferSize</code>	number of elements needed the buffer used in <code>cusparses<t>gemvi()</code> .
<code>pBuffer</code>	working space buffer

Output

<code>y</code>	<type> updated dense vector.
----------------	------------------------------

See [cusparsesStatus_t](#) for the description of the return status

Chapter 10. cuSPARSE Level 3 Function Reference

This chapter describes sparse linear algebra functions that perform operations between sparse and (usually tall) dense matrices.

In particular, the solution of sparse triangular linear systems with multiple right-hand sides is implemented in two phases. First, during the analysis phase, the sparse triangular matrix is analyzed to determine the dependencies between its elements by calling the appropriate `csrsm2_analysis()` function. The analysis is specific to the sparsity pattern of the given matrix and to the selected `cusparseOperation_t` type. The information from the analysis phase is stored in the parameter of type `csrsm2Info_t` that has been initialized previously with a call to `cusparseCreateCsrsm2Info()`.

Second, during the solve phase, the given sparse triangular linear system is solved using the information stored in the `csrsm2Info_t` parameter by calling the appropriate `csrsm2_solve()` function. The solve phase may be performed multiple times with different multiple right-hand sides, while the analysis phase needs to be performed only once. This is especially useful when a sparse triangular linear system must be solved for different sets of multiple right-hand sides one at a time, while its coefficient matrix remains the same.

Finally, once all the solves have completed, the opaque data structure pointed to by the `csrsm2Info_t` parameter can be released by calling `cusparseDestroyCsrsm2Info()`.

10.1. `cusparse<t>bsrmm()`

```
cusparseStatus_t
cusparseSbsrmm(cusparseHandle_t      handle,
               cusparseDirection_t   dirA,
               cusparseOperation_t   transA,
               cusparseOperation_t   transB,
               int                    mb,
               int                    n,
               int                    kb,
               int                    nnzb,
               const float*           alpha,
               const cusparseMatDescr_t descrA,
               const float*           bsrValA,
               const int*             bsrRowPtrA,
               const int*             bsrColIndA,
```



```

        int
        const float*
        int
        const float*
        float*
        int
        blockDim,
        B,
        ldb,
        beta,
        C,
        ldc)

cusparseStatus_t
cusparseDbsrmm(cusparseHandle_t      handle,
               cusparseDirection_t   dirA,
               cusparseOperation_t   transA,
               cusparseOperation_t   transB,
               int                    mb,
               int                    n,
               int                    kb,
               int                    nnzb,
               const double*          alpha,
               const cusparseMatDescr_t descrA,
               const double*          bsrValA,
               const int*             bsrRowPtrA,
               const int*             bsrColIndA,
               int                    blockDim,
               const double*          B,
               int                    ldb,
               const double*          beta,
               double*                C,
               int                    ldc)

cusparseStatus_t
cusparseCbsrmm(cusparseHandle_t      handle,
               cusparseDirection_t   dirA,
               cusparseOperation_t   transA,
               cusparseOperation_t   transB,
               int                    mb,
               int                    n,
               int                    kb,
               int                    nnzb,
               const cuComplex*       alpha,
               const cusparseMatDescr_t descrA,
               const cuComplex*       bsrValA,
               const int*             bsrRowPtrA,
               const int*             bsrColIndA,
               int                    blockDim,
               const cuComplex*       B,
               int                    ldb,
               const cuComplex*       beta,
               cuComplex*             C,
               int                    ldc)

cusparseStatus_t
cusparseZbsrmm(cusparseHandle_t      handle,
               cusparseDirection_t   dirA,
               cusparseOperation_t   transA,
               cusparseOperation_t   transB,
               int                    mb,
               int                    n,
               int                    kb,
               int                    nnzb,
               const cuDoubleComplex* alpha,
               const cusparseMatDescr_t descrA,
               const cuDoubleComplex* bsrValA,

```

```

const int*      bsrRowPtrA,
const int*      bsrColIndA,
int            blockDim,
const cuDoubleComplex* B,
int           ldb,
const cuDoubleComplex* beta,
cuDoubleComplex* C,
int           ldc)

```

This function performs one of the following matrix-matrix operations:

$$C = \alpha * \text{op}(A) * \text{op}(B) + \beta * C$$

A is an $m_b \times k_b$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`; B and C are dense matrices; α and β are scalars; and

$$\text{op}(A) = \begin{cases} A & \text{if transA} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if transA} == \text{CUSPARSE_OPERATION_TRANPOSE (not supported)} \\ A^H & \text{if transA} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE (not supported)} \end{cases}$$

and

$$\text{op}(B) = \begin{cases} B & \text{if transB} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ B^T & \text{if transB} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ B^H & \text{if transB} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE (not supported)} \end{cases}$$

The function has the following limitations:

- ▶ Only `CUSPARSE_MATRIX_TYPE_GENERAL` matrix type is supported
- ▶ Only `blockDim > 1` is supported
- ▶ if `blockDim ≤ 4`, then $\max(m_b)/\max(n) = 524,272$
- ▶ if $4 < \text{blockDim} \leq 8$, then $\max(m_b) = 524,272$, $\max(n) = 262,136$
- ▶ if `blockDim > 8`, then $m < 65,535$ and $\max(n) = 262,136$

The motivation of `transpose(B)` is to improve memory access of matrix B. The computational pattern of $A * \text{transpose}(B)$ with matrix B in column-major order is equivalent to $A * B$ with matrix B in row-major order.

In practice, no operation in an iterative solver or eigenvalue solver uses $A * \text{transpose}(B)$. However, we can perform $A * \text{transpose}(\text{transpose}(B))$ which is the same as $A * B$. For example, suppose A is $m_b \times k_b$, B is $k \times n$ and C is $m \times n$, the following code shows usage of `cusparseDbsrmm()`.

```

// A is mb*kb, B is k*n and C is m*n
const int m = mb*blockSize;
const int k = kb*blockSize;
const int ldb_B = k; // leading dimension of B
const int ldc   = m; // leading dimension of C
// perform C:=alpha*A*B + beta*C
cusparseSetMatType(descrA, CUSPARSE_MATRIX_TYPE_GENERAL);
cusparseDbsrmm(cusparse_handle,
               CUSPARSE_DIRECTION_COLUMN,
               CUSPARSE_OPERATION_NON_TRANPOSE,
               CUSPARSE_OPERATION_NON_TRANPOSE,

```

```

mb, n, kb, nnzb, alpha,
descrA, bsrValA, bsrRowPtrA, bsrColIndA, blockSize,
B, ldb_B,
beta, C, ldc);

```

Instead of using $A*B$, our proposal is to transpose B to B_t by first calling `cublas<t>gem()`, and then to perform $A*\text{transpose}(B_t)$.

```

// step 1: Bt := transpose(B)
const int m = mb*blockSize;
const int k = kb*blockSize;
double *Bt;
const int ldb_Bt = n; // leading dimension of Bt
cudaMalloc((void**)&Bt, sizeof(double)*ldb_Bt*k);
double one = 1.0;
double zero = 0.0;
cublasSetPointerMode(cublas_handle, CUBLAS_POINTER_MODE_HOST);
cublasDgemt(cublas_handle, CUBLAS_OP_T, CUBLAS_OP_T,
            n, k, &one, B, int ldb_B, &zero, Bt, int ldb_Bt);

// step 2: perform C:=alpha*A*transpose(Bt) + beta*C
cusparseDbsrmm(cusparse_handle,
               CUSPARSE_DIRECTION_COLUMN,
               CUSPARSE_OPERATION_NON_TRANSPOSE,
               CUSPARSE_OPERATION_TRANSPOSE,
               mb, n, kb, nnzb, alpha,
               descrA, bsrValA, bsrRowPtrA, bsrColIndA, blockSize,
               Bt, ldb_Bt,
               beta, C, ldc);

```

`bsrmm()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
dir	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
transA	the operation <code>op(A)</code> .
transB	the operation <code>op(B)</code> .
mb	number of block rows of sparse matrix A.
n	number of columns of dense matrix <code>op(B)</code> and A.
kb	number of block columns of sparse matrix A.
nnzb	number of non-zero blocks of sparse matrix A.
alpha	<type> scalar used for multiplication.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are

	CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
bsrValA	<type> array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) nonzero blocks of matrix A.
bsrRowPtrA	integer array of mb + 1 elements that contains the start of every block row and the end of the last block row plus one.
bsrColIndA	integer array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) column indices of the nonzero blocks of matrix A.
blockDim	block dimension of sparse matrix A, larger than zero.
B	array of dimensions (ldb, n) if op(B)=B and (ldb, k) otherwise.
ldb	leading dimension of B. If op(B)=B, it must be at least max(1, k) if op(B) != B, it must be at least max(1, n) .
beta	<type> scalar used for multiplication. If beta is zero, c does not have to be a valid input.
C	array of dimensions (ldc, n).
ldc	leading dimension of C. It must be at least max(1, m) if op(A)=A and at least max(1, k) otherwise.

Output

C	<type> updated array of dimensions (ldc, n).
---	--

See [cusparseStatus_t](#) for the description of the return status

10.2. cusparse<t>bsrsm2_bufferSize()

```

cusparseStatus_t
cusparseSbsrsm2_bufferSize(cusparseHandle_t      handle,
                           cusparseDirection_t   dirA,
                           cusparseOperation_t   transA,
                           cusparseOperation_t   transX,
                           int                   mb,
                           int                   n,
                           int                   nnzb,
                           const cusparseMatDescr_t descrA,
                           float*               bsrSortedValA,
                           const int*           bsrSortedRowPtrA,
                           const int*           bsrSortedColIndA,
                           int                   blockDim,
                           bsrsm2Info_t         info,
                           int*                 pBufferSizeInBytes)

cusparseStatus_t
cusparseDbsrsm2_bufferSize(cusparseHandle_t      handle,

```

```

        cusparseDirection_t      dirA,
        cusparseOperation_t      transA,
        cusparseOperation_t      transX,
        int                       mb,
        int                       n,
        int                       nnzb,
        const cusparseMatDescr_t  descrA,
        double*                   bsrSortedValA,
        const int*                 bsrSortedRowPtrA,
        const int*                 bsrSortedColIndA,
        int                       blockDim,
        bsrsm2Info_t               info,
        int*                       pBufferSizeInBytes)

cusparseStatus_t
cusparseCbsrsm2_bufferSize(cusparseHandle_t      handle,
        cusparseDirection_t      dirA,
        cusparseOperation_t      transA,
        cusparseOperation_t      transX,
        int                       mb,
        int                       n,
        int                       nnzb,
        const cusparseMatDescr_t  descrA,
        cuComplex*                bsrSortedValA,
        const int*                 bsrSortedRowPtrA,
        const int*                 bsrSortedColIndA,
        int                       blockDim,
        bsrsm2Info_t               info,
        int*                       pBufferSizeInBytes)

cusparseStatus_t
cusparseZbsrsm2_bufferSize(cusparseHandle_t      handle,
        cusparseDirection_t      dirA,
        cusparseOperation_t      transA,
        cusparseOperation_t      transX,
        int                       mb,
        int                       n,
        int                       nnzb,
        const cusparseMatDescr_t  descrA,
        cuDoubleComplex*          bsrSortedValA,
        const int*                 bsrSortedRowPtrA,
        const int*                 bsrSortedColIndA,
        int                       blockDim,
        bsrsm2Info_t               info,
        int*                       pBufferSizeInBytes)

```

This function returns size of buffer used in `bsrsm2()`, a new sparse triangular linear system $\text{op}(A) * \text{op}(X) = \alpha \text{op}(B)$.

A is an $(mb * \text{blockDim}) \times (mb * \text{blockDim})$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`; B and X are the right-hand-side and the solution matrices; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

Although there are six combinations in terms of parameter `trans` and the upper (and lower) triangular part of A, `bsrsm2_bufferSize()` returns the maximum size of the buffer among these combinations. The buffer size depends on dimension `mb`, `blockDim` and the

number of nonzeros of the matrix, `nnzb`. If the user changes the matrix, it is necessary to call `bsrsm2_bufferSize()` again to get the correct buffer size, otherwise a segmentation fault may occur.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dirA</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>transA</code>	the operation <code>op(A)</code> .
<code>transX</code>	the operation <code>op(X)</code> .
<code>mb</code>	number of block rows of matrix <code>A</code> .
<code>n</code>	number of columns of matrix <code>op(B)</code> and <code>op(X)</code> .
<code>nnzb</code>	number of nonzero blocks of matrix <code>A</code> .
<code>descrA</code>	the descriptor of matrix <code>A</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
<code>bsrValA</code>	<type> array of <code>nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0))</code> nonzero blocks of matrix <code>A</code> .
<code>bsrRowPtrA</code>	integer array of <code>mb + 1</code> elements that contains the start of every block row and the end of the last block row plus one.
<code>bsrColIndA</code>	integer array of <code>nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0))</code> column indices of the nonzero blocks of matrix <code>A</code> .
<code>blockDim</code>	block dimension of sparse matrix <code>A</code> ; larger than zero.

Output

<code>info</code>	record internal states based on different algorithms.
<code>pBufferSizeInBytes</code>	number of bytes of the buffer used in <code>bsrsm2_analysis()</code> and <code>bsrsm2_solve()</code> .

See [`cusparseStatus_t`](#) for the description of the return status

10.3. cusparse<t>bsrsm2_analysis()

```

cusparseStatus_t
cusparseSbsrsm2_analysis(cusparseHandle_t      handle,
                        cusparseDirection_t    dirA,
                        cusparseOperation_t    transA,
                        cusparseOperation_t    transX,
                        int                    mb,
                        int                    n,
                        int                    nnzb,
                        const cusparseMatDescr_t descrA,
                        const float*          bsrSortedVal,
                        const int*           bsrSortedRowPtr,
                        const int*           bsrSortedColInd,
                        int                    blockDim,
                        bsrsm2Info_t         info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

cusparseStatus_t
cusparseDbsrsm2_analysis(cusparseHandle_t      handle,
                        cusparseDirection_t    dirA,
                        cusparseOperation_t    transA,
                        cusparseOperation_t    transX,
                        int                    mb,
                        int                    n,
                        int                    nnzb,
                        const cusparseMatDescr_t descrA,
                        const double*         bsrSortedVal,
                        const int*           bsrSortedRowPtr,
                        const int*           bsrSortedColInd,
                        int                    blockDim,
                        bsrsm2Info_t         info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

cusparseStatus_t
cusparseCbsrsm2_analysis(cusparseHandle_t      handle,
                        cusparseDirection_t    dirA,
                        cusparseOperation_t    transA,
                        cusparseOperation_t    transX,
                        int                    mb,
                        int                    n,
                        int                    nnzb,
                        const cusparseMatDescr_t descrA,
                        const cuComplex*      bsrSortedVal,
                        const int*           bsrSortedRowPtr,
                        const int*           bsrSortedColInd,
                        int                    blockDim,
                        bsrsm2Info_t         info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

cusparseStatus_t
cusparseZbsrsm2_analysis(cusparseHandle_t      handle,
                        cusparseDirection_t    dirA,
                        cusparseOperation_t    transA,

```

```

    cusparseOperation_t    transX,
    int                    mb,
    int                    n,
    int                    nnzb,
    const cusparseMatDescr_t descrA,
    const cuDoubleComplex* bsrSortedVal,
    const int*             bsrSortedRowPtr,
    const int*             bsrSortedColInd,
    int                    blockDim,
    bsrsm2Info_t          info,
    cusparseSolvePolicy_t policy,
    void*                  pBuffer)

```

This function performs the analysis phase of `bsrsm2()`, a new sparse triangular linear system $\text{op}(A) * \text{op}(X) = \alpha \text{op}(B)$.

A is an $(\text{mb} * \text{blockDim}) \times (\text{mb} * \text{blockDim})$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`; B and X are the right-hand-side and the solution matrices; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

and

$$\text{op}(X) = \begin{cases} X & \text{if transX} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ X^T & \text{if transX} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ X^H & \text{if transX} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE (not supported)} \end{cases}$$

and `op(B)` and `op(X)` are equal.

The block of BSR format is of size `blockDim*blockDim`, stored in column-major or row-major as determined by parameter `dirA`, which is either `CUSPARSE_DIRECTION_ROW` or `CUSPARSE_DIRECTION_COLUMN`. The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, and the fill mode and diagonal type are ignored.

It is expected that this function will be executed only once for a given matrix and a particular operation type.

This function requires the buffer size returned by `bsrsm2_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `bsrsm2_analysis()` reports a structural zero and computes the level information stored in opaque structure `info`. The level information can extract more parallelism during a triangular solver. However `bsrsm2_solve()` can be done without level information. To disable level information, the user needs to specify the policy of the triangular solver as `CUSPARSE_SOLVE_POLICY_NO_LEVEL`.

Function `bsrsm2_analysis()` always reports the first structural zero, even if the parameter `policy` is `CUSPARSE_SOLVE_POLICY_NO_LEVEL`. Besides, no structural zero is reported if `CUSPARSE_DIAG_TYPE_UNIT` is specified, even if block `A(j, j)` is missing for some `j`. The user must call `cusparseXbsrsm2_query_zero_pivot()` to know where the structural zero is.

If `bsrsm2_analysis()` reports a structural zero, the solve will return a numerical zero in the same position as the structural zero but this result `x` is meaningless.

- This function requires temporary extra storage that is allocated internally

- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
dirA	storage format of blocks, either CUSPARSE_DIRECTION_ROW or CUSPARSE_DIRECTION_COLUMN.
transA	the operation $op(A)$.
transX	the operation $op(B)$ and $op(X)$.
mb	number of block rows of matrix A.
n	number of columns of matrix $op(B)$ and $op(X)$.
nnzb	number of non-zero blocks of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL, while the supported diagonal types are CUSPARSE_DIAG_TYPE_UNIT and CUSPARSE_DIAG_TYPE_NON_UNIT.
bsrValA	<type> array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) nonzero blocks of matrix A.
bsrRowPtrA	integer array of mb + 1 elements that contains the start of every block row and the end of the last block row plus one.
bsrColIndA	integer array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) column indices of the nonzero blocks of matrix A.
blockDim	block dimension of sparse matrix A; larger than zero.
info	structure initialized using cusparseCreateBsrsm2Info.
policy	The supported policies are CUSPARSE_SOLVE_POLICY_NO_LEVEL and CUSPARSE_SOLVE_POLICY_USE_LEVEL.
pBuffer	buffer allocated by the user; the size is return by bsrsm2_bufferSize().

Output

info	structure filled with information collected during the analysis phase (that should be passed to the solve phase unchanged).
------	---

See [cusparseStatus_t](#) for the description of the return status

10.4. `cusparse<t>bsrsm2_solve()`

```

cusparseStatus_t
cusparseSbsrsm2_solve(cusparseHandle_t          handle,
                     cusparseDirection_t      dirA,
                     cusparseOperation_t      transA,
                     cusparseOperation_t      transX,
                     int                      mb,
                     int                      n,
                     int                      nnzb,
                     const float*            alpha,
                     const cusparseMatDescr_t descrA,
                     const float*          bsrSortedVal,
                     const int*            bsrSortedRowPtr,
                     const int*            bsrSortedColInd,
                     int                    blockDim,
                     bsrsm2Info_t          info,
                     const float*          B,
                     int                    ldb,
                     float*                X,
                     int                    ldx,
                     cusparseSolvePolicy_t  policy,
                     void*                  pBuffer)

cusparseStatus_t
cusparseDbsrsm2_solve(cusparseHandle_t          handle,
                     cusparseDirection_t      dirA,
                     cusparseOperation_t      transA,
                     cusparseOperation_t      transX,
                     int                      mb,
                     int                      n,
                     int                      nnzb,
                     const double*           alpha,
                     const cusparseMatDescr_t descrA,
                     const double*          bsrSortedVal,
                     const int*            bsrSortedRowPtr,
                     const int*            bsrSortedColInd,
                     int                    blockDim,
                     bsrsm2Info_t          info,
                     const double*          B,
                     int                    ldb,
                     double*                X,
                     int                    ldx,
                     cusparseSolvePolicy_t  policy,
                     void*                  pBuffer)

cusparseStatus_t
cusparseCbsrsm2_solve(cusparseHandle_t          handle,
                     cusparseDirection_t      dirA,
                     cusparseOperation_t      transA,
                     cusparseOperation_t      transX,
                     int                      mb,
                     int                      n,
                     int                      nnzb,
                     const cuComplex*        alpha,
                     const cusparseMatDescr_t descrA,
                     const cuComplex*       bsrSortedVal,

```

```

        const int*          bsrSortedRowPtr,
        const int*          bsrSortedColInd,
        int                 blockDim,
        bsrsm2Info_t        info,
        const cuComplex*    B,
        int                 ldb,
        cuComplex*          X,
        int                 ldx,
        cusparseSolvePolicy_t policy,
        void*                pBuffer)

cusparseStatus_t
cusparseZbsrsm2_solve(cusparseHandle_t        handle,
                     cusparseDirection_t     dirA,
                     cusparseOperation_t     transA,
                     cusparseOperation_t     transX,
                     int                     mb,
                     int                     n,
                     int                     nnzb,
                     const cuDoubleComplex* alpha,
                     const cusparseMatDescr_t descrA,
                     const cuDoubleComplex* bsrSortedVal,
                     const int*              bsrSortedRowPtr,
                     const int*              bsrSortedColInd,
                     int                     blockDim,
                     bsrsm2Info_t           info,
                     const cuDoubleComplex* B,
                     int                     ldb,
                     cuDoubleComplex*       X,
                     int                     ldx,
                     cusparseSolvePolicy_t   policy,
                     void*                   pBuffer)

```

This function performs the solve phase of the solution of a sparse triangular linear system:

$$\text{op}(A) * \text{op}(X) = \alpha * \text{op}(B)$$

A is an $(mb * \text{blockDim}) \times (mb * \text{blockDim})$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`; B and X are the right-hand-side and the solution matrices; α is a scalar, and

$$\text{op}(A) = \begin{cases} A & \text{if transA} == \text{CUSPARSE_OPERATION_NON_TRANSPOSE} \\ A^T & \text{if transA} == \text{CUSPARSE_OPERATION_TRANSPOSE} \\ A^H & \text{if transA} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANSPOSE} \end{cases}$$

and

$$\text{op}(X) = \begin{cases} X & \text{if transX} == \text{CUSPARSE_OPERATION_NON_TRANSPOSE} \\ X^T & \text{if transX} == \text{CUSPARSE_OPERATION_TRANSPOSE} \\ X^H & \text{not supported} \end{cases}$$

Only $\text{op}(A) = A$ is supported.

$\text{op}(B)$ and $\text{op}(X)$ must be performed in the same way. In other words, if $\text{op}(B) = B$, $\text{op}(X) = X$.

The block of BSR format is of size $\text{blockDim} * \text{blockDim}$, stored as column-major or row-major as determined by parameter `dirA`, which is either `CUSPARSE_DIRECTION_ROW` or `CUSPARSE_DIRECTION_COLUMN`. The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, and the fill mode and diagonal type are ignored. Function `bsrsm2_solve()` can support an arbitrary `blockDim`.

This function may be executed multiple times for a given matrix and a particular operation type.

This function requires the buffer size returned by `bsrsm2_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Although `bsrsm2_solve()` can be done without level information, the user still needs to be aware of consistency. If `bsrsm2_analysis()` is called with policy `CUSPARSE_SOLVE_POLICY_USE_LEVEL`, `bsrsm2_solve()` can be run with or without levels. On the other hand, if `bsrsm2_analysis()` is called with `CUSPARSE_SOLVE_POLICY_NO_LEVEL`, `bsrsm2_solve()` can only accept `CUSPARSE_SOLVE_POLICY_NO_LEVEL`; otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `bsrsm02_solve()` has the same behavior as `bsrsv02_solve()`, reporting the first numerical zero, including a structural zero. The user must call `cusparseXbsrsm2_query_zero_pivot()` to know where the numerical zero is.

The motivation of `transpose(x)` is to improve the memory access of matrix `x`. The computational pattern of `transpose(x)` with matrix `x` in column-major order is equivalent to `x` with matrix `x` in row-major order.

In-place is supported and requires that `B` and `x` point to the same memory block, and `ldb=ldx`.

The function supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dirA</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>transA</code>	the operation <code>op(A)</code> .
<code>transX</code>	the operation <code>op(B)</code> and <code>op(X)</code> .
<code>mb</code>	number of block rows of matrix <code>A</code> .
<code>n</code>	number of columns of matrix <code>op(B)</code> and <code>op(X)</code> .
<code>nnzb</code>	number of non-zero blocks of matrix <code>A</code> .
<code>alpha</code>	<type> scalar used for multiplication.
<code>descrA</code>	the descriptor of matrix <code>A</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
<code>bsrValA</code>	<type> array of <code>nnzb</code> ($= \text{bsrRowPtrA}(mb) - \text{bsrRowPtrA}(0)$) non-zero blocks of matrix <code>A</code> .

<code>bsrRowPtrA</code>	integer array of <code>mb + 1</code> elements that contains the start of every block row and the end of the last block row plus one.
<code>bsrColIndA</code>	integer array of <code>nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0))</code> column indices of the nonzero blocks of matrix <code>A</code> .
<code>blockDim</code>	block dimension of sparse matrix <code>A</code> ; larger than zero.
<code>info</code>	structure initialized using <code>cusparseCreateBsrsm2Info()</code> .
<code>B</code>	<type> right-hand-side array.
<code>ldb</code>	leading dimension of <code>B</code> . If <code>op(B)=B</code> , <code>ldb >= (mb*blockDim)</code> ; otherwise, <code>ldb >= n</code> .
<code>ldx</code>	leading dimension of <code>X</code> . If <code>op(X)=X</code> , then <code>ldx >= (mb*blockDim)</code> . otherwise <code>ldx >= n</code> .
<code>policy</code>	the supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
<code>pBuffer</code>	buffer allocated by the user; the size is returned by <code>bsrsm2_bufferSize()</code> .

Output

<code>X</code>	<type> solution array with leading dimensions <code>ldx</code> .
----------------	--

See [cusparseStatus_t](#) for the description of the return status

10.5. cusparseXbsrsm2_zeroPivot()

```
cusparseStatus_t
cusparseXbsrsm2_zeroPivot(cusparseHandle_t handle,
                          bsrsm2Info_t      info,
                          int*               position)
```

If the returned error code is `CUSPARSE_STATUS_ZERO_PIVOT`, `position=j` means `A(j,j)` is either a structural zero or a numerical zero (singular block). Otherwise `position=-1`.

The `position` can be 0-base or 1-base, the same as the matrix.

Function `cusparseXbsrsm2_zeroPivot()` is a blocking call. It calls `cudaDeviceSynchronize()` to make sure all previous kernels are done.

The `position` can be in the host memory or device memory. The user can set the proper mode with `cusparseSetPointerMode()`.

- The routine requires no extra storage

- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
info	info contains a structural zero or a numerical zero if the user already called <code>bsrsm2_analysis()</code> or <code>bsrsm2_solve()</code> .

Output

position	if no structural or numerical zero, position is -1; otherwise, if $A(j, j)$ is missing or $U(j, j)$ is zero, position=j.
----------	--

See [cusparseStatus_t](#) for the description of the return status

10.6. `cusparse<t>csrsm2_bufferSizeExt()` [DEPRECATED]

[[DEPRECATED]] use [cusparseSpSM\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparseStatus_t
cusparseScsrsm2_bufferSizeExt(cusparseHandle_t      handle,
                              int                   algo,
                              cusparseOperation_t   transA,
                              cusparseOperation_t   transB,
                              int                   m,
                              int                   nrhs,
                              int                   nnz,
                              const float*          alpha,
                              const cusparseMatDescr_t descrA,
                              const float*          csrSortedValA,
                              const int*            csrSortedRowPtrA,
                              const int*            csrSortedColIndA,
                              const float*          B,
                              int                   ldb,
                              csrsm2Info_t         info,
                              cusparseSolvePolicy_t policy,
                              size_t*              pBufferSize)

cusparseStatus_t
cusparseDcsrsm2_bufferSizeExt(cusparseHandle_t      handle,
                              int                   algo,
                              cusparseOperation_t   transA,
                              cusparseOperation_t   transB,
                              int                   m,
                              int                   nrhs,
                              int                   nnz,

```

```

        const double*      alpha,
        const cusparseMatDescr_t descrA,
        const double*      csrSortedValA,
        const int*         csrSortedRowPtrA,
        const int*         csrSortedColIndA,
        const double*      B,
        int                 ldb,
        csrsm2Info_t        info,
        cusparseSolvePolicy_t policy,
        size_t*             pBufferSize)

cusparseStatus_t
cusparseCcsrsm2_bufferSizeExt(cusparseHandle_t      handle,
                              int                   algo,
                              cusparseOperation_t   transA,
                              cusparseOperation_t   transB,
                              int                   m,
                              int                   nrhs,
                              int                   nnz,
                              const cuComplex*      alpha,
                              const cusparseMatDescr_t descrA,
                              const cuComplex*      csrSortedValA,
                              const int*            csrSortedRowPtrA,
                              const int*            csrSortedColIndA,
                              const cuComplex*      B,
                              int                   ldb,
                              csrsm2Info_t          info,
                              cusparseSolvePolicy_t policy,
                              size_t*               pBufferSize)

cusparseStatus_t
cusparseZcsrsm2_bufferSizeExt(cusparseHandle_t      handle,
                              int                   algo,
                              cusparseOperation_t   transA,
                              cusparseOperation_t   transB,
                              int                   m,
                              int                   nrhs,
                              int                   nnz,
                              const cuDoubleComplex* alpha,
                              const cusparseMatDescr_t descrA,
                              const cuDoubleComplex* csrSortedValA,
                              const int*            csrSortedRowPtrA,
                              const int*            csrSortedColIndA,
                              const cuDoubleComplex* B,
                              int                   ldb,
                              csrsm2Info_t          info,
                              cusparseSolvePolicy_t policy,
                              size_t*               pBufferSize)

```

This function returns the size of the buffer used in `csrsm2`, a sparse triangular linear system $\text{op}(A) * \text{op}(X) = \alpha \text{op}(B)$.

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`; B and X are the right-hand-side matrix and the solution matrix; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
algo	algo = 0 is non-block version; algo = 1 is block version.
transA	the operation $\text{op}(A)$.
transB	the operation $\text{op}(B)$.
m	number of rows of matrix A.
nrhs	number of columns of right hand side matrix $\text{op}(B)$.
nnz	number of nonzero elements of matrix A.
alpha	<type> scalar used for multiplication.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
csrValA	<type> array of nnz (= <code>csrRowPtrA(m) - csrRowPtrA(0)</code>) nonzero elements of matrix A.
csrRowPtrA	integer array of $m + 1$ elements that contains the start of every row and the end of the last row plus one.
csrColIndA	integer array of nnz (= <code>csrRowPtrA(m) - csrRowPtrA(0)</code>) column indices of the nonzero elements of matrix A.
B	<type> right-hand-side matrix. $\text{op}(B)$ is of size m -by- nrhs .
ldb	leading dimension of B and X.
info	structure with information collected during the analysis phase (that should have been passed to the solve phase unchanged).
policy	The supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .

Output

info	record of internal states based on different algorithms.
pBufferSize	number of bytes of the buffer used in the <code>csrsm2_analysis</code> and <code>csrsm2_solve</code> .

See [cusparseStatus_t](#) for the description of the return status

10.7. `cusparse<t>csrsm2_analysis()` [DEPRECATED]

[DEPRECATED] use [cusparseSpSM\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparseStatus_t
cusparseScsrsm2_analysis(cusparseHandle_t      handle,
                        int                    algo,
                        cusparseOperation_t    transA,
                        cusparseOperation_t    transB,
                        int                    m,
                        int                    nrhs,
                        int                    nnz,
                        const float*          alpha,
                        const cusparseMatDescr_t descrA,
                        const float*          csrSortedValA,
                        const int*           csrSortedRowPtrA,
                        const int*           csrSortedColIndA,
                        const float*          B,
                        int                    ldb,
                        csrsm2Info_t          info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

cusparseStatus_t
cusparseDcsrsm2_analysis(cusparseHandle_t      handle,
                        int                    algo,
                        cusparseOperation_t    transA,
                        cusparseOperation_t    transB,
                        int                    m,
                        int                    nrhs,
                        int                    nnz,
                        const double*         alpha,
                        const cusparseMatDescr_t descrA,
                        const double*         csrSortedValA,
                        const int*           csrSortedRowPtrA,
                        const int*           csrSortedColIndA,
                        const double*         B,
                        int                    ldb,
                        csrsm2Info_t          info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

cusparseStatus_t
cusparseCcsrsm2_analysis(cusparseHandle_t      handle,
                        int                    algo,
                        cusparseOperation_t    transA,
                        cusparseOperation_t    transB,
                        int                    m,
                        int                    nrhs,
                        int                    nnz,
                        const cuComplex*      alpha,
                        const cusparseMatDescr_t descrA,

```

```

        const cuComplex*      csrSortedValA,
        const int*           csrSortedRowPtrA,
        const int*           csrSortedColIndA,
        const cuComplex*     B,
        int                  ldb,
        csrms2Info_t         info,
        cusparseSolvePolicy_t policy,
        void*                 pBuffer)

cusparseStatus_t
cusparseZcsrsm2_analysis(cusparseHandle_t handle,
                        int               algo,
                        cusparseOperation_t transA,
                        cusparseOperation_t transB,
                        int               m,
                        int               nrhs,
                        int               nnz,
                        const cuDoubleComplex* alpha,
                        const cusparseMatDescr_t descrA,
                        const cuDoubleComplex* csrSortedValA,
                        const int*           csrSortedRowPtrA,
                        const int*           csrSortedColIndA,
                        const cuDoubleComplex* B,
                        int                  ldb,
                        csrms2Info_t         info,
                        cusparseSolvePolicy_t policy,
                        void*                 pBuffer)

```

This function performs the analysis phase of `csrsm2`, a sparse triangular linear system $\text{op}(A) * \text{op}(X) = \alpha \text{op}(B)$.

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`; B and x are the right-hand-side matrix and the solution matrix; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if trans} == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if trans} == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if trans} == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

It is expected that this function will be executed only once for a given matrix and a particular operation type.

This function requires a buffer size returned by `csrsm2_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `csrsm2_analysis()` reports a structural zero and computes level information that is stored in opaque structure `info`. The level information can extract more parallelism for a triangular solver. However `csrsm2_solve()` can be done without level information. To disable level information, the user needs to specify the policy of the triangular solver as `CUSPARSE_SOLVE_POLICY_NO_LEVEL`.

Function `csrsm2_analysis()` always reports the first structural zero, even if the policy is `CUSPARSE_SOLVE_POLICY_NO_LEVEL`. No structural zero is reported if `CUSPARSE_DIAG_TYPE_UNIT` is specified, even if $A(j, j)$ is missing for some j . The user needs to call `cusparseXcsrsm2_zeroPivot()` to know where the structural zero is.

It is the user's choice whether to call `csrsm2_solve()` if `csrsm2_analysis()` reports a structural zero. In this case, the user can still call `csrsm2_solve()` which will return a numerical zero in the same position as the structural zero. However the result `x` is meaningless.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>algo</code>	<code>algo = 0</code> is non-block version; <code>algo = 1</code> is block version.
<code>transA</code>	the operation $\text{op}(A)$.
<code>transB</code>	the operation $\text{op}(B)$.
<code>m</code>	number of rows of matrix <code>A</code> .
<code>nrhs</code>	number of columns of matrix $\text{op}(B)$.
<code>nnz</code>	number of nonzero elements of matrix <code>A</code> .
<code>alpha</code>	<type> scalar used for multiplication.
<code>descrA</code>	the descriptor of matrix <code>A</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .
<code>csrValA</code>	<type> array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> nonzero elements of matrix <code>A</code> .
<code>csrRowPtrA</code>	integer array of <code>m + 1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> column indices of the nonzero elements of matrix <code>A</code> .
<code>B</code>	<type> right-hand-side matrix. $\text{op}(B)$ is of size <code>m-by-nrhs</code> .
<code>ldb</code>	leading dimension of <code>B</code> and <code>x</code> .
<code>info</code>	structure initialized using <code>cusparseCreateCsrsv2Info()</code> .
<code>policy</code>	The supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
<code>pBuffer</code>	buffer allocated by the user, the size is returned by <code>csrsm2_bufferSize()</code> .

Output

info	structure filled with information collected during the analysis phase (that should be passed to the solve phase unchanged).
------	---

See [cusparseStatus_t](#) for the description of the return status

10.8. `cusparse<t>csrsm2_solve()` [DEPRECATED]

[DEPRECATED] use [cusparseSpSM\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparseStatus_t
cusparseScsrsm2_solve(cusparseHandle_t      handle,
                     int                    algo,
                     cusparseOperation_t    transA,
                     cusparseOperation_t    transB,
                     int                    m,
                     int                    nrhs,
                     int                    nnz,
                     const float*          alpha,
                     const cusparseMatDescr_t descrA,
                     const float*          csrSortedValA,
                     const int*            csrSortedRowPtrA,
                     const int*            csrSortedColIndA,
                     float*                B,
                     int                    ldb,
                     csrsm2Info_t          info,
                     cusparseSolvePolicy_t policy,
                     void*                  pBuffer)

cusparseStatus_t
cusparseDcsrsm2_solve(cusparseHandle_t      handle,
                     int                    algo,
                     cusparseOperation_t    transA,
                     cusparseOperation_t    transB,
                     int                    m,
                     int                    nrhs,
                     int                    nnz,
                     const double*          alpha,
                     const cusparseMatDescr_t descrA,
                     const double*          csrSortedValA,
                     const int*            csrSortedRowPtrA,
                     const int*            csrSortedColIndA,
                     double*                B,
                     int                    ldb,
                     csrsm2Info_t          info,
                     cusparseSolvePolicy_t policy,
                     void*                  pBuffer)

cusparseStatus_t
cusparseCcsrsm2_solve(cusparseHandle_t      handle,
                     int                    algo,

```

```

        cusparseOperation_t    transA,
        cusparseOperation_t    transB,
        int                    m,
        int                    nrhs,
        int                    nnz,
        const cuComplex*       alpha,
        const cusparseMatDescr_t descrA,
        const cuComplex*       csrSortedValA,
        const int*             csrSortedRowPtrA,
        const int*             csrSortedColIndA,
        cuComplex*             B,
        int                    ldb,
        csrsm2Info_t           info,
        cusparseSolvePolicy_t  policy,
        void*                   pBuffer)

cusparseStatus_t
cusparseZcsrsm2_solve(cusparseHandle_t    handle,
                     int                    algo,
                     cusparseOperation_t    transA,
                     cusparseOperation_t    transB,
                     int                    m,
                     int                    nrhs,
                     int                    nnz,
                     const cuDoubleComplex* alpha,
                     const cusparseMatDescr_t descrA,
                     const cuDoubleComplex* csrSortedValA,
                     const int*             csrSortedRowPtrA,
                     const int*             csrSortedColIndA,
                     cuDoubleComplex*       B,
                     int                    ldb,
                     csrsm2Info_t           info,
                     cusparseSolvePolicy_t  policy,
                     void*                   pBuffer)

```

This function performs the solve phase of `csrsm2`, a sparse triangular linear system $\text{op}(A) * \text{op}(X) = \alpha \text{op}(B)$.

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`; B and X are the right-hand-side matrix and the solution matrix; α is a scalar; and

$$\text{op}(A) = \begin{cases} A & \text{if transA == CUSPARSE_OPERATION_NON_TRANSPOSE} \\ A^T & \text{if transA == CUSPARSE_OPERATION_TRANSPOSE} \\ A^H & \text{if transA == CUSPARSE_OPERATION_CONJUGATE_TRANSPOSE} \end{cases}$$

`transB` acts on both matrix B and matrix X, only `CUSPARSE_OPERATION_NON_TRANSPOSE` and `CUSPARSE_OPERATION_TRANSPOSE`. The operation is in-place, matrix B is overwritten by matrix X.

`ldb` must be not less than `m` if `transB = CUSPARSE_OPERATION_NON_TRANSPOSE`. Otherwise, `ldb` must be not less than `nrhs`.

This function requires the buffer size returned by `csrsm2_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Although `csrsm2_solve()` can be done without level information, the user still needs to be aware of consistency. If `csrsm2_analysis()` is called with `policy`

`CUSPARSE_SOLVE_POLICY_USE_LEVEL`, `csrsm2_solve()` can be run with or without levels. On the contrary, if `csrsm2_analysis()` is called with `CUSPARSE_SOLVE_POLICY_NO_LEVEL`, `csrsm2_solve()` can only accept `CUSPARSE_SOLVE_POLICY_NO_LEVEL`; otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The level information may not improve the performance but spend extra time doing analysis. For example, a tridiagonal matrix has no parallelism. In this case, `CUSPARSE_SOLVE_POLICY_NO_LEVEL` performs better than `CUSPARSE_SOLVE_POLICY_USE_LEVEL`. If the user has an iterative solver, the best approach is to do `csrsm2_analysis()` with `CUSPARSE_SOLVE_POLICY_USE_LEVEL` once. Then do `csrsm2_solve()` with `CUSPARSE_SOLVE_POLICY_NO_LEVEL` in the first run and with `CUSPARSE_SOLVE_POLICY_USE_LEVEL` in the second run, picking faster one to perform the remaining iterations.

Function `csrsm2_solve()` reports the first numerical zero, including a structural zero. If `status` is 0, no numerical zero was found. Furthermore, no numerical zero is reported if `CUSPARSE_DIAG_TYPE_UNIT` is specified, even if $A(j, j)$ is zero for some j . The user needs to call `cusparseXcsrsm2_zeroPivot()` to know where the numerical zero is.

`csrsm2` provides two algorithms specified by the parameter `algo`. `algo=0` is non-block version and `algo=1` is block version. non-block version is memory-bound, limited by bandwidth. block version partitions the matrix into small tiles and applies desne operations. Although it has more flops than non-block version, it may be faster if non-block version already reaches maximum bandwidth..

Appendix section shows an example of `csrsm2`.

The function supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>algo</code>	<code>algo = 0</code> is non-block version; <code>algo = 1</code> is block version.
<code>transA</code>	the operation $\text{op}(A)$.
<code>transB</code>	the operation $\text{op}(B)$.
<code>m</code>	number of rows and columns of matrix A.
<code>nrhs</code>	number of columns of matrix $\text{op}(B)$.
<code>nnz</code>	number of nonzeros of matrix A.
<code>alpha</code>	<type> scalar used for multiplication.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> , while the supported diagonal types are <code>CUSPARSE_DIAG_TYPE_UNIT</code> and <code>CUSPARSE_DIAG_TYPE_NON_UNIT</code> .

csrValA	<type> array of nnz (= csrRowPtrA(m) - csrRowPtrA(0)) nonzero elements of matrix A.
csrRowPtrA	integer array of m + 1 elements that contains the start of every row and the end of the last row plus one.
csrColIndA	integer array of nnz (= csrRowPtrA(m) - csrRowPtrA(0)) column indices of the nonzero elements of matrix A.
B	<type> right-hand-side matrix. op(B) is of size m-by-nrhs.
ldb	leading dimension of B and X.
info	structure with information collected during the analysis phase (that should have been passed to the solve phase unchanged).
policy	The supported policies are CUSPARSE_SOLVE_POLICY_NO_LEVEL and CUSPARSE_SOLVE_POLICY_USE_LEVEL.
pBuffer	buffer allocated by the user, the size is returned by csrsm2_bufferSize.

Output

X	<type> solution matrix, op(X) is of size m-by-nrhs.
---	---

See [cusparseStatus_t](#) for the description of the return status

10.9. cusparseXcsrsm2_zeroPivot() [DEPRECATED]

[DEPRECATED] use [cusparseSpSM\(\)](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseXcsrsm2_zeroPivot(cusparseHandle_t handle,
                          csrsm2Info_t      info,
                          int*               position)
```

If the returned error code is CUSPARSE_STATUS_ZERO_PIVOT, position=j means A(j, j) has either a structural zero or a numerical zero. Otherwise position=-1.

The position can be 0-based or 1-based, the same as the matrix.

Function cusparseXcsrsm2_zeroPivot() is a blocking call. It calls cudaDeviceSynchronize() to make sure all previous kernels are done.

The position can be in the host memory or device memory. The user can set the proper mode with cusparseSetPointerMode().

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
info	info contains structural zero or numerical zero if the user already called <code>csrsm2_analysis()</code> or <code>csrsm2_solve()</code> .

Output

position	if no structural or numerical zero, position is -1; otherwise, if $A(j, j)$ is missing or $U(j, j)$ is zero, position=j.
----------	--

See [cusparsesStatus_t](#) for the description of the return status

10.10. `cusparsesgemmi()` [DEPRECATED]

[DEPRECATED] use [cusparsesSpMM\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparsesStatus_t
cusparsesSgemmi(cusparsesHandle_t handle,
               int m,
               int n,
               int k,
               int nnz,
               const float* alpha,
               const float* A,
               int lda,
               const float* cscValB,
               const int* cscColPtrB,
               const int* cscRowIndB,
               const float* beta,
               float* C,
               int ldc)

cusparsesStatus_t
cusparsesDgemmi(cusparsesHandle_t handle,
               int m,
               int n,
               int k,
               int nnz,
               const double* alpha,
               const double* A,
               int lda,
               const double* cscValB,
               const int* cscColPtrB,

```



```

        const int*      cscRowIndB,
        const double*  beta,
        double*       C,
        int            ldc)

cusparseStatus_t
cusparseCgemmi(cusparseHandle_t handle,
               int            m,
               int            n,
               int            k,
               int            nnz,
               const cuComplex* alpha,
               const cuComplex* A,
               int            lda,
               const cuComplex* cscValB,
               const int*      cscColPtrB,
               const int*      cscRowIndB,
               const cuComplex* beta,
               cuComplex*      C,
               int            ldc)

cusparseStatus_t
cusparseZgemmi(cusparseHandle_t      handle,
               int                    m,
               int                    n,
               int                    k,
               int                    nnz,
               const cuDoubleComplex* alpha,
               const cuDoubleComplex* A,
               int                    lda,
               const cuDoubleComplex* cscValB,
               const int*              cscColPtrB,
               const int*              cscRowIndB,
               const cuDoubleComplex* beta,
               cuDoubleComplex*        C,
               int                    ldc)

```

This function performs the following matrix-matrix operations:

$$C = \alpha * A * B + \beta * C$$

A and C are dense matrices; B is a $k \times n$ sparse matrix that is defined in CSC storage format by the three arrays `cscValB`, `cscColPtrB`, and `cscRowIndB`; α and β are scalars; and

Remark: B is base-0.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
m	number of rows of matrix A.
n	number of columns of matrices B and C.
k	number of columns of matrix A.

nnz	number of nonzero elements of sparse matrix B.
alpha	<type> scalar used for multiplication.
A	array of dimensions (lda, k).
lda	leading dimension of A. It must be at least m
cscValB	<type> array of nnz (= cscColPtrB(k) - cscColPtrB(0)) nonzero elements of matrix B.
cscColPtrB	integer array of k + 1 elements that contains the start of every row and the end of the last row plus one.
cscRowIndB	integer array of nnz (= cscColPtrB(k) - cscColPtrB(0)) column indices of the nonzero elements of matrix B.
beta	<type> scalar used for multiplication. If beta is zero, C does not have to be a valid input.
C	array of dimensions (ldc, n).
ldc	leading dimension of C. It must be at least m

Output

C	<type> updated array of dimensions (ldc, n).
---	--

See [cusparseStatus_t](#) for the description of the return status

Chapter 11. cuSPARSE Extra Function Reference

This chapter describes the extra routines used to manipulate sparse matrices.

11.1. `cusparse<t>csrgeam2()`

```
cusparseStatus_t
cusparseScsrgeam2_bufferSizeExt(cusparseHandle_t      handle,
                                int                    m,
                                int                    n,
                                const float*          alpha,
                                const cusparseMatDescr_t descrA,
                                int                    nnzA,
                                const float*          csrSortedValA,
                                const int*            csrSortedRowPtrA,
                                const int*            csrSortedColIndA,
                                const float*          beta,
                                const cusparseMatDescr_t descrB,
                                int                    nnzB,
                                const float*          csrSortedValB,
                                const int*            csrSortedRowPtrB,
                                const int*            csrSortedColIndB,
                                const cusparseMatDescr_t descrC,
                                const float*          csrSortedValC,
                                const int*            csrSortedRowPtrC,
                                const int*            csrSortedColIndC,
                                size_t*               pBufferSizeInBytes)

cusparseStatus_t
cusparseDcsrgeam2_bufferSizeExt(cusparseHandle_t      handle,
                                int                    m,
                                int                    n,
                                const double*         alpha,
                                const cusparseMatDescr_t descrA,
                                int                    nnzA,
                                const double*         csrSortedValA,
                                const int*            csrSortedRowPtrA,
                                const int*            csrSortedColIndA,
                                const double*         beta,
                                const cusparseMatDescr_t descrB,
                                int                    nnzB,
                                const double*         csrSortedValB,
```

```

        const int*          csrSortedRowPtrB,
        const int*          csrSortedColIndB,
        const cusparseMatDescr_t descrC,
        const double*       csrSortedValC,
        const int*          csrSortedRowPtrC,
        const int*          csrSortedColIndC,
        size_t*             pBufferSizeInBytes)

cusparseStatus_t
cusparseCcsrgeam2_bufferSizeExt(cusparseHandle_t      handle,
                                int                    m,
                                int                    n,
                                const cuComplex*       alpha,
                                const cusparseMatDescr_t descrA,
                                int                    nnzA,
                                const cuComplex*       csrSortedValA,
                                const int*             csrSortedRowPtrA,
                                const int*             csrSortedColIndA,
                                const cuComplex*       beta,
                                const cusparseMatDescr_t descrB,
                                int                    nnzB,
                                const cuComplex*       csrSortedValB,
                                const int*             csrSortedRowPtrB,
                                const int*             csrSortedColIndB,
                                const cusparseMatDescr_t descrC,
                                const cuComplex*       csrSortedValC,
                                const int*             csrSortedRowPtrC,
                                const int*             csrSortedColIndC,
                                size_t*             pBufferSizeInBytes)

cusparseStatus_t
cusparseZcsrgeam2_bufferSizeExt(cusparseHandle_t      handle,
                                int                    m,
                                int                    n,
                                const cuDoubleComplex* alpha,
                                const cusparseMatDescr_t descrA,
                                int                    nnzA,
                                const cuDoubleComplex* csrSortedValA,
                                const int*             csrSortedRowPtrA,
                                const int*             csrSortedColIndA,
                                const cuDoubleComplex* beta,
                                const cusparseMatDescr_t descrB,
                                int                    nnzB,
                                const cuDoubleComplex* csrSortedValB,
                                const int*             csrSortedRowPtrB,
                                const int*             csrSortedColIndB,
                                const cusparseMatDescr_t descrC,
                                const cuDoubleComplex* csrSortedValC,
                                const int*             csrSortedRowPtrC,
                                const int*             csrSortedColIndC,
                                size_t*             pBufferSizeInBytes)

cusparseStatus_t
cusparseXcsrgeam2Nnz(cusparseHandle_t      handle,
                     int                    m,
                     int                    n,
                     const cusparseMatDescr_t descrA,
                     int                    nnzA,
                     const int*             csrSortedRowPtrA,
                     const int*             csrSortedColIndA,
                     const cusparseMatDescr_t descrB,

```

```

int nnzB,
const int* csrSortedRowPtrB,
const int* csrSortedColIndB,
const cusparseMatDescr_t descrC,
int* csrSortedRowPtrC,
int* nnzTotalDevHostPtr,
void* workspace)

```

```

cusparseStatus_t
cusparseScsrgeam2(cusparseHandle_t handle,
int m,
int n,
const float* alpha,
const cusparseMatDescr_t descrA,
int nnzA,
const float* csrSortedValA,
const int* csrSortedRowPtrA,
const int* csrSortedColIndA,
const float* beta,
const cusparseMatDescr_t descrB,
int nnzB,
const float* csrSortedValB,
const int* csrSortedRowPtrB,
const int* csrSortedColIndB,
const cusparseMatDescr_t descrC,
float* csrSortedValC,
int* csrSortedRowPtrC,
int* csrSortedColIndC,
void* pBuffer)

```

```

cusparseStatus_t
cusparseDcsrgeam2(cusparseHandle_t handle,
int m,
int n,
const double* alpha,
const cusparseMatDescr_t descrA,
int nnzA,
const double* csrSortedValA,
const int* csrSortedRowPtrA,
const int* csrSortedColIndA,
const double* beta,
const cusparseMatDescr_t descrB,
int nnzB,
const double* csrSortedValB,
const int* csrSortedRowPtrB,
const int* csrSortedColIndB,
const cusparseMatDescr_t descrC,
double* csrSortedValC,
int* csrSortedRowPtrC,
int* csrSortedColIndC,
void* pBuffer)

```

```

cusparseStatus_t
cusparseCcsrgeam2(cusparseHandle_t handle,
int m,
int n,
const cuComplex* alpha,
const cusparseMatDescr_t descrA,
int nnzA,
const cuComplex* csrSortedValA,

```

```

        const int*          csrSortedRowPtrA,
        const int*          csrSortedColIndA,
        const cuComplex*    beta,
        const cusparseMatDescr_t descrB,
        int                 nnzB,
        const cuComplex*    csrSortedValB,
        const int*          csrSortedRowPtrB,
        const int*          csrSortedColIndB,
        const cusparseMatDescr_t descrC,
        cuComplex*          csrSortedValC,
        int*                csrSortedRowPtrC,
        int*                csrSortedColIndC,
        void*                pBuffer)

cusparseStatus_t
cusparseZcsrgeam2(cusparseHandle_t handle,
                 int m,
                 int n,
                 const cuDoubleComplex* alpha,
                 const cusparseMatDescr_t descrA,
                 int nnzA,
                 const cuDoubleComplex* csrSortedValA,
                 const int* csrSortedRowPtrA,
                 const int* csrSortedColIndA,
                 const cuDoubleComplex* beta,
                 const cusparseMatDescr_t descrB,
                 int nnzB,
                 const cuDoubleComplex* csrSortedValB,
                 const int* csrSortedRowPtrB,
                 const int* csrSortedColIndB,
                 const cusparseMatDescr_t descrC,
                 cuDoubleComplex* csrSortedValC,
                 int* csrSortedRowPtrC,
                 int* csrSortedColIndC,
                 void* pBuffer)

```

This function performs following matrix-matrix operation

$$C = \alpha * A + \beta * B$$

where A, B, and C are $m \times n$ sparse matrices (defined in CSR storage format by the three arrays `csrValA|csrValB|csrValC`, `csrRowPtrA|csrRowPtrB|csrRowPtrC`, and `csrColIndA|csrColIndB|csrColIndC` respectively), and α and β are scalars. Since A and B have different sparsity patterns, cuSPARSE adopts a two-step approach to complete sparse matrix C. In the first step, the user allocates `csrRowPtrC` of $m+1$ elements and uses function `cusparseXcsrgeam2Nnz()` to determine `csrRowPtrC` and the total number of nonzero elements. In the second step, the user gathers `nnzC` (number of nonzero elements of matrix C) from either (`nnzC=*nnzTotalDevHostPtr`) or (`nnzC=csrRowPtrC(m)-csrRowPtrC(0)`) and allocates `csrValC`, `csrColIndC` of `nnzC` elements respectively, then finally calls function `cusparse[S|D|C|Z]csrgeam2()` to complete matrix C.

The general procedure is as follows:

```

int baseC, nnzC;
/* alpha, nnzTotalDevHostPtr points to host memory */
size_t BufferSizeInBytes;
char *buffer = NULL;
int *nnzTotalDevHostPtr = &nnzC;
cusparseSetPointerMode(handle, CUSPARSE_POINTER_MODE_HOST);

```

```

cudaMalloc((void**)&csrRowPtrC, sizeof(int)*(m+1));
/* prepare buffer */
cusparseScsrgeam2_bufferSizeExt(handle, m, n,
    alpha,
    descrA, nnzA,
    csrValA, csrRowPtrA, csrColIndA,
    beta,
    descrB, nnzB,
    csrValB, csrRowPtrB, csrColIndB,
    descrC,
    csrValC, csrRowPtrC, csrColIndC
    &bufferSizeInBytes
);
cudaMalloc((void**)&buffer, sizeof(char)*bufferSizeInBytes);
cusparseXcsrgeam2Nnz(handle, m, n,
    descrA, nnzA, csrRowPtrA, csrColIndA,
    descrB, nnzB, csrRowPtrB, csrColIndB,
    descrC, csrRowPtrC, nnzTotalDevHostPtr,
    buffer);
if (NULL != nnzTotalDevHostPtr){
    nnzC = *nnzTotalDevHostPtr;
}else{
    cudaMemcpy(&nnzC, csrRowPtrC+m, sizeof(int), cudaMemcpyDeviceToHost);
    cudaMemcpy(&baseC, csrRowPtrC, sizeof(int), cudaMemcpyDeviceToHost);
    nnzC -= baseC;
}
cudaMalloc((void**)&csrColIndC, sizeof(int)*nnzC);
cudaMalloc((void**)&csrValC, sizeof(float)*nnzC);
cusparseScsrgeam2(handle, m, n,
    alpha,
    descrA, nnzA,
    csrValA, csrRowPtrA, csrColIndA,
    beta,
    descrB, nnzB,
    csrValB, csrRowPtrB, csrColIndB,
    descrC,
    csrValC, csrRowPtrC, csrColIndC
    buffer);

```

Several comments on `csrgeam2()`:

- ▶ The other three combinations, NT, TN, and TT, are not supported by cuSPARSE. In order to do any one of the three, the user should use the routine `csr2csc()` to convert $A|B$ to $A^T|B^T$.
- ▶ Only `CUSPARSE_MATRIX_TYPE_GENERAL` is supported. If either A or B is symmetric or Hermitian, then the user must extend the matrix to a full one and reconfigure the `MatrixType` field of the descriptor to `CUSPARSE_MATRIX_TYPE_GENERAL`.
- ▶ If the sparsity pattern of matrix C is known, the user can skip the call to function `cusparseXcsrgeam2Nnz()`. For example, suppose that the user has an iterative algorithm which would update A and B iteratively but keep the sparsity patterns. The user can call function `cusparseXcsrgeam2Nnz()` once to set up the sparsity pattern of C, then call function `cusparse[S|D|C|Z]geam()` only for each iteration.
- ▶ The pointers `alpha` and `beta` must be valid.
- ▶ When `alpha` or `beta` is zero, it is not considered a special case by cuSPARSE. The sparsity pattern of C is independent of the value of `alpha` and `beta`. If the user wants $C = 0 \times A + 1 \times B^T$, then `csr2csc()` is better than `csrgeam2()`.

- ▶ `csrgeam2()` is the same as `csrgeam()` except `csrgeam2()` needs explicit buffer where `csrgeam()` allocates the buffer internally.
- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows of sparse matrix <code>A, B, C</code> .
<code>n</code>	number of columns of sparse matrix <code>A, B, C</code> .
<code>alpha</code>	<type> scalar used for multiplication.
<code>descrA</code>	the descriptor of matrix <code>A</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> only.
<code>nnzA</code>	number of nonzero elements of sparse matrix <code>A</code> .
<code>csrValA</code>	<type> array of <code>nnzA (= csrRowPtrA(m) - csrRowPtrA(0))</code> nonzero elements of matrix <code>A</code> .
<code>csrRowPtrA</code>	integer array of <code>m + 1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of <code>nnzA (= csrRowPtrA(m) - csrRowPtrA(0))</code> column indices of the nonzero elements of matrix <code>A</code> .
<code>beta</code>	<type> scalar used for multiplication. If <code>beta</code> is zero, <code>y</code> does not have to be a valid input.
<code>descrB</code>	the descriptor of matrix <code>B</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> only.
<code>nnzB</code>	number of nonzero elements of sparse matrix <code>B</code> .
<code>csrValB</code>	<type> array of <code>nnzB (= csrRowPtrB(m) - csrRowPtrB(0))</code> nonzero elements of matrix <code>B</code> .
<code>csrRowPtrB</code>	integer array of <code>m + 1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndB</code>	integer array of <code>nnzB (= csrRowPtrB(m) - csrRowPtrB(0))</code> column indices of the nonzero elements of matrix <code>B</code> .
<code>descrC</code>	the descriptor of matrix <code>C</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> only.

Output

<code>csrValC</code>	<type> array of <code>nnzC (= csrRowPtrC(m) - csrRowPtrC(0))</code> nonzero elements of matrix <code>C</code> .
----------------------	---

<code>csrRowPtrC</code>	integer array of $m + 1$ elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndC</code>	integer array of $nnzC (= csrRowPtrC(m) - csrRowPtrC(0))$ column indices of the nonzero elements of matrix C .
<code>nnzTotalDevHostPtr</code>	total number of nonzero elements in device or host memory. It is equal to $(csrRowPtrC(m) - csrRowPtrC(0))$.

See [`cusparseStatus_t`](#) for the description of the return status

11.2. `cusparse<t>csrsgemm2()` [DEPRECATED]

[DEPRECATED] use [`cusparseSpGEMM\(\)`](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseScsrsgemm2_bufferSizeExt(cusparseHandle_t      handle,
                                int                    m,
                                int                    n,
                                int                    k,
                                const float*          alpha,
                                const cusparseMatDescr_t descrA,
                                int                    nnzA,
                                const int*            csrRowPtrA,
                                const int*            csrColIndA,
                                const cusparseMatDescr_t descrB,
                                int                    nnzB,
                                const int*            csrRowPtrB,
                                const int*            csrColIndB,
                                const float*          beta,
                                const cusparseMatDescr_t descrD,
                                int                    nnzD,
                                const int*            csrRowPtrD,
                                const int*            csrColIndD,
                                csrgemm2Info_t        info,
                                size_t*               pBufferSizeInBytes)
```

```
cusparseStatus_t
cusparseDcsrsgemm2_bufferSizeExt(cusparseHandle_t      handle,
                                int                    m,
                                int                    n,
                                int                    k,
                                const double*         alpha,
                                const cusparseMatDescr_t descrA,
                                int                    nnzA,
                                const int*            csrRowPtrA,
                                const int*            csrColIndA,
                                const cusparseMatDescr_t descrB,
                                int                    nnzB,
                                const int*            csrRowPtrB,
```

```

        const int*          csrColIndB,
        const double*      beta,
        const cusparseMatDescr_t descrD,
        int                nnzD,
        const int*         csrRowPtrD,
        const int*         csrColIndD,
        csrgemm2Info_t    info,
        size_t*            pBufferSizeInBytes)

cusparseStatus_t
cusparseCcsrgemm2_bufferSizeExt(cusparseHandle_t handle,
                                int m,
                                int n,
                                int k,
                                const cuComplex* alpha,
                                const cusparseMatDescr_t descrA,
                                int nnzA,
                                const int* csrRowPtrA,
                                const int* csrColIndA,
                                const cusparseMatDescr_t descrB,
                                int nnzB,
                                const int* csrRowPtrB,
                                const int* csrColIndB,
                                const cuComplex* beta,
                                const cusparseMatDescr_t descrD,
                                int nnzD,
                                const int* csrRowPtrD,
                                const int* csrColIndD,
                                csrgemm2Info_t info,
                                size_t* pBufferSizeInBytes)

cusparseStatus_t
cusparseZcsrgemm2_bufferSizeExt(cusparseHandle_t handle,
                                int m,
                                int n,
                                int k,
                                const cuDoubleComplex* alpha,
                                const cusparseMatDescr_t descrA,
                                int nnzA,
                                const int* csrRowPtrA,
                                const int* csrColIndA,
                                const cusparseMatDescr_t descrB,
                                int nnzB,
                                const int* csrRowPtrB,
                                const int* csrColIndB,
                                const cuDoubleComplex* beta,
                                const cusparseMatDescr_t descrD,
                                int nnzD,
                                const int* csrRowPtrD,
                                const int* csrColIndD,
                                csrgemm2Info_t info,
                                size_t* pBufferSizeInBytes)

cusparseStatus_t
cusparseXcsrgemm2Nnz(cusparseHandle_t handle,
                     int m,
                     int n,
                     int k,
                     const cusparseMatDescr_t descrA,
                     int nnzA,
                     const int* csrRowPtrA,

```

```

const int*          csrColIndA,
const cusparseMatDescr_t descrB,
int                nnzB,
const int*         csrRowPtrB,
const int*         csrColIndB,
const cusparseMatDescr_t descrD,
int                nnzD,
const int*         csrRowPtrD,
const int*         csrColIndD,
const cusparseMatDescr_t descrC,
int*               csrRowPtrC,
int*               nnzTotalDevHostPtr,
const csrgemm2Info_t info,
void*              pBuffer)

```

```

cusparseStatus_t
cusparseScsrgemm2(cusparseHandle_t handle,
int m,
int n,
int k,
const float* alpha,
const cusparseMatDescr_t descrA,
int nnzA,
const float* csrValA,
const int* csrRowPtrA,
const int* csrColIndA,
const cusparseMatDescr_t descrB,
int nnzB,
const float* csrValB,
const int* csrRowPtrB,
const int* csrColIndB,
const float* beta,
const cusparseMatDescr_t descrD,
int nnzD,
const float* csrValD,
const int* csrRowPtrD,
const int* csrColIndD,
const cusparseMatDescr_t descrC,
float* csrValC,
const int* csrRowPtrC,
int* csrColIndC,
const csrgemm2Info_t info,
void* pBuffer)

```

```

cusparseStatus_t
cusparseDcsrgemm2(cusparseHandle_t handle,
int m,
int n,
int k,
const double* alpha,
const cusparseMatDescr_t descrA,
int nnzA,
const double* csrValA,
const int* csrRowPtrA,
const int* csrColIndA,
const cusparseMatDescr_t descrB,
int nnzB,
const double* csrValB,
const int* csrRowPtrB,
const int* csrColIndB,

```

```

        const double*          beta,
        const cusparseMatDescr_t descrD,
        int                    nnzD,
        const double*          csrValD,
        const int*              csrRowPtrD,
        const int*              csrColIndD,
        const cusparseMatDescr_t descrC,
        double*                 csrValC,
        const int*              csrRowPtrC,
        int*                     csrColIndC,
        const csrgemm2Info_t    info,
        void*                    pBuffer)

cusparseStatus_t
cusparseCcsrgermm2(cusparseHandle_t    handle,
                  int                    m,
                  int                    n,
                  int                    k,
                  const cuComplex*       alpha,
                  const cusparseMatDescr_t descrA,
                  int                    nnzA,
                  const cuComplex*       csrValA,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  const cusparseMatDescr_t descrB,
                  int                    nnzB,
                  const cuComplex*       csrValB,
                  const int*              csrRowPtrB,
                  const int*              csrColIndB,
                  const cuComplex*       beta,
                  const cusparseMatDescr_t descrD,
                  int                    nnzD,
                  const cuComplex*       csrValD,
                  const int*              csrRowPtrD,
                  const int*              csrColIndD,
                  const cusparseMatDescr_t descrC,
                  cuComplex*              csrValC,
                  const int*              csrRowPtrC,
                  int*                     csrColIndC,
                  const csrgemm2Info_t    info,
                  void*                    pBuffer)

cusparseStatus_t
cusparseZcsrgermm2(cusparseHandle_t    handle,
                  int                    m,
                  int                    n,
                  int                    k,
                  const cuDoubleComplex* alpha,
                  const cusparseMatDescr_t descrA,
                  int                    nnzA,
                  const cuDoubleComplex* csrValA,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  const cusparseMatDescr_t descrB,
                  int                    nnzB,
                  const cuDoubleComplex* csrValB,
                  const int*              csrRowPtrB,
                  const int*              csrColIndB,
                  const cuDoubleComplex* beta,
                  const cusparseMatDescr_t descrD,
                  int                    nnzD,

```

```

    const cuDoubleComplex*   csrValD,
    const int*                csrRowPtrD,
    const int*                csrColIndD,
    const cusparseMatDescr_t descrC,
    cuDoubleComplex*         csrValC,
    const int*                csrRowPtrC,
    int*                      csrColIndC,
    const csrgemm2Info_t     info,
    void*                     pBuffer)

```

This function performs following matrix-matrix operation:

$$C = \alpha * A * B + \beta * D$$

where A, B, D and C are $m \times k$, $k \times n$, $m \times n$ and $m \times n$ sparse matrices (defined in CSR storage format by the three arrays `csrValA|csrValB|csrValD|csrValC`, `csrRowPtrA|csrRowPtrB|csrRowPtrD|csrRowPtrC`, and `csrColIndA|csrColIndB|csrColIndD|csrColIndC` respectively).

Note that the new API `cusparseSpGEMM` requires that D must have the same sparsity pattern of C.

The `csrgemm2` uses `alpha` and `beta` to support the following operations:

alpha	beta	operation
NULL	NULL	invalid
NULL	!NULL	C = beta*D, A and B are not used
!NULL	NULL	C = alpha*A*B, D is not used
!NULL	!NULL	C = alpha*A*B + beta*D

The numerical value of `alpha` and `beta` only affects the numerical values of C, not its sparsity pattern. For example, if `alpha` and `beta` are not zero, the sparsity pattern of C is union of A*B and D, independent of numerical value of `alpha` and `beta`.

The following table shows different operations according to the value of m, n and k

m, n, k	operation
m < 0 or n < 0 or k < 0	invalid
m is 0 or n is 0	do nothing
m > 0 and n > 0 and k is 0	invalid if beta is zero; C = beta*D if beta is not zero.
m > 0 and n > 0 and k > 0	C = beta*D if alpha is zero. C = alpha*A*B if beta is zero. C = alpha*A*B + beta*D if alpha and beta are not zero.

This function requires the buffer size returned by `csrgemm2_bufferSizeExt()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The cuSPARSE library adopts a two-step approach to complete sparse matrix. In the first step, the user allocates `csrRowPtrC` of m+1 elements and uses the function

`cusparseXcsrgermm2Nnz()` to determine `csrRowPtrC` and the total number of nonzero elements. In the second step, the user gathers `nnzC` (the number of nonzero elements of matrix `C`) from either `(nnzC=*nnzTotalDevHostPtr)` or `(nnzC=csrRowPtrC(m) - csrRowPtrC(0))` and allocates `csrValC` and `csrColIndC` of `nnzC` elements respectively, then finally calls function `cusparse[S|D|C|Z]csrgermm2()` to evaluate matrix `C`.

The general procedure of $C = -A * B + D$ is as follows:

```
// assume matrices A, B and D are ready.
int baseC, nnzC;
csrgermm2Info_t info = NULL;
size_t bufferSize;
void *buffer = NULL;
// nnzTotalDevHostPtr points to host memory
int *nnzTotalDevHostPtr = &nnzC;
double alpha = -1.0;
double beta = 1.0;
cusparseSetPointerMode(handle, CUSPARSE_POINTER_MODE_HOST);

// step 1: create an opaque structure
cusparseCreateCsrgermm2Info(&info);

// step 2: allocate buffer for csrgermm2Nnz and csrgermm2
cusparseDcsrgermm2_bufferSizeExt(handle, m, n, k, &alpha,
    descrA, nnzA, csrRowPtrA, csrColIndA,
    descrB, nnzB, csrRowPtrB, csrColIndB,
    &beta,
    descrD, nnzD, csrRowPtrD, csrColIndD,
    info,
    &bufferSize);
cudaMalloc(&buffer, bufferSize);

// step 3: compute csrRowPtrC
cudaMalloc((void**)&csrRowPtrC, sizeof(int) * (m+1));
cusparseXcsrgermm2Nnz(handle, m, n, k,
    descrA, nnzA, csrRowPtrA, csrColIndA,
    descrB, nnzB, csrRowPtrB, csrColIndB,
    descrD, nnzD, csrRowPtrD, csrColIndD,
    descrC, csrRowPtrC, nnzTotalDevHostPtr,
    info, buffer);
if (NULL != nnzTotalDevHostPtr){
    nnzC = *nnzTotalDevHostPtr;
}else{
    cudaMemcpy(&nnzC, csrRowPtrC+m, sizeof(int), cudaMemcpyDeviceToHost);
    cudaMemcpy(&baseC, csrRowPtrC, sizeof(int), cudaMemcpyDeviceToHost);
    nnzC -= baseC;
}

// step 4: finish sparsity pattern and value of C
cudaMalloc((void**)&csrColIndC, sizeof(int) * nnzC);
cudaMalloc((void**)&csrValC, sizeof(double) * nnzC);
// Remark: set csrValC to null if only sparsity pattern is required.
cusparseDcsrgermm2(handle, m, n, k, &alpha,
    descrA, nnzA, csrValA, csrRowPtrA, csrColIndA,
    descrB, nnzB, csrValB, csrRowPtrB, csrColIndB,
    &beta,
    descrD, nnzD, csrValD, csrRowPtrD, csrColIndD,
    descrC, csrValC, csrRowPtrC, csrColIndC,
    info, buffer);

// step 5: destroy the opaque structure
cusparseDestroyCsrgermm2Info(info);
```

Several comments on `csrgeam2()`:

- ▶ Only the NN version is supported. For other modes, the user has to transpose A or B explicitly.
- ▶ Only `CUSPARSE_MATRIX_TYPE_GENERAL` is supported. If either A or B is symmetric or Hermitian, the user must extend the matrix to a full one and reconfigure the `MatrixType` field descriptor to `CUSPARSE_MATRIX_TYPE_GENERAL`.
- ▶ if `csrValC` is zero, only sparsity pattern of C is calculated.

The functions `cusparseXcsrgeam2Nnz()` and `cusparse<t>csrgeam2()` supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine does **not** support CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows of sparse matrix A, D and C.
<code>n</code>	number of columns of sparse matrix B, D and C.
<code>k</code>	number of columns/rows of sparse matrix A / B.
<code>alpha</code>	<type> scalar used for multiplication.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> only.
<code>nnzA</code>	number of nonzero elements of sparse matrix A.
<code>csrValA</code>	<type> array of <code>nnzA</code> nonzero elements of matrix A.
<code>csrRowPtrA</code>	integer array of <code>m+1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of <code>nnzA</code> column indices of the nonzero elements of matrix A.
<code>descrB</code>	the descriptor of matrix B. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> only.
<code>nnzB</code>	number of nonzero elements of sparse matrix B.
<code>csrValB</code>	<type> array of <code>nnzB</code> nonzero elements of matrix B.
<code>csrRowPtrB</code>	integer array of <code>k+1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndB</code>	integer array of <code>nnzB</code> column indices of the nonzero elements of matrix B.
<code>descrD</code>	the descriptor of matrix D. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> only.

<code>nnzD</code>	number of nonzero elements of sparse matrix D.
<code>csrValD</code>	<type> array of <code>nnzD</code> nonzero elements of matrix D.
<code>csrRowPtrD</code>	integer array of <code>m+1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndD</code>	integer array of <code>nnzD</code> column indices of the nonzero elements of matrix D.
<code>beta</code>	<type> scalar used for multiplication.
<code>descrC</code>	the descriptor of matrix C. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> only.
<code>info</code>	structure with information used in <code>csrsgemm2Nnz</code> and <code>csrsgemm2</code> .
<code>pBuffer</code>	buffer allocated by the user; the size is returned by <code>csrsgemm2_bufferSizeExt</code> .

Output

<code>csrValC</code>	<type> array of <code>nnzC</code> nonzero elements of matrix C.
<code>csrRowPtrC</code>	integer array of <code>m+1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndC</code>	integer array of <code>nnzC</code> column indices of the nonzero elements of matrix C.
<code>pBufferSizeInBytes</code>	number of bytes of the buffer used in <code>csrsgemm2Nnz</code> and <code>csrsgemm2</code> .
<code>nnzTotalDevHostPtr</code>	total number of nonzero elements in device or host memory. It is equal to <code>(csrRowPtrC(m) - csrRowPtrC(0))</code> .

See [`cusparseStatus_t`](#) for the description of the return status

Chapter 12. cuSPARSE Preconditioners Reference

This chapter describes the routines that implement different preconditioners.

12.1. Incomplete Cholesky Factorization: level 0

Different algorithms for ic0 are discussed in this section.

12.1.1. `cusparse<t>csric02_bufferSize()`

```
cusparseStatus_t
cusparseScsric02_bufferSize(cusparseHandle_t      handle,
                           int                    m,
                           int                    nnz,
                           const cusparseMatDescr_t descrA,
                           float*                csrValA,
                           const int*            csrRowPtrA,
                           const int*            csrColIndA,
                           csric02Info_t        info,
                           int*                  pBufferSizeInBytes)

cusparseStatus_t
cusparseDcsric02_bufferSize(cusparseHandle_t      handle,
                            int                    m,
                            int                    nnz,
                            const cusparseMatDescr_t descrA,
                            double*               csrValA,
                            const int*            csrRowPtrA,
                            const int*            csrColIndA,
                            csric02Info_t        info,
                            int*                  pBufferSizeInBytes)

cusparseStatus_t
cusparseCcsric02_bufferSize(cusparseHandle_t      handle,
                            int                    m,
                            int                    nnz,
                            const cusparseMatDescr_t descrA,
                            cuComplex*           csrValA,
```

```

        const int*
        const int*
        csric02Info_t
        int*
        csrRowPtrA,
        csrColIndA,
        info,
        pBufferSizeInBytes)

cusparsesStatus_t
cusparsesZcsric02_bufferSize(cusparsesHandle_t      handle,
                             int                    m,
                             int                    nnz,
                             const cusparsesMatDescr_t descrA,
                             cuDoubleComplex*      csrValA,
                             const int*            csrRowPtrA,
                             const int*            csrColIndA,
                             csric02Info_t         info,
                             int*                  pBufferSizeInBytes)

```

This function returns size of buffer used in computing the incomplete-Cholesky factorization with 0 fill-in and no pivoting:

$$A \approx LL^H$$

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`.

The buffer size depends on dimension `m` and `nnz`, the number of nonzeros of the matrix. If the user changes the matrix, it is necessary to call `csric02_bufferSize()` again to have the correct buffer size; otherwise, a segmentation fault may occur.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows and columns of matrix A.
<code>nnz</code>	number of nonzeros of matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>csrValA</code>	<type> array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> nonzero elements of matrix A.
<code>csrRowPtrA</code>	integer array of <code>m + 1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> column indices of the nonzero elements of matrix A.

Output

info	record internal states based on different algorithms.
pBufferSizeInBytes	number of bytes of the buffer used in <code>csric02_analysis()</code> and <code>csric02()</code> .

See [`cusparseStatus_t`](#) for the description of the return status

12.1.2. `cusparse<t>csric02_analysis()`

```

cusparseStatus_t
cusparseScsric02_analysis (cusparseHandle_t      handle,
                          int                    m,
                          int                    nnz,
                          const cusparseMatDescr_t descrA,
                          const float*          csrValA,
                          const int*            csrRowPtrA,
                          const int*            csrColIndA,
                          csric02Info_t         info,
                          cusparseSolvePolicy_t policy,
                          void*                  pBuffer)

cusparseStatus_t
cusparseDcsric02_analysis (cusparseHandle_t      handle,
                          int                    m,
                          int                    nnz,
                          const cusparseMatDescr_t descrA,
                          const double*          csrValA,
                          const int*            csrRowPtrA,
                          const int*            csrColIndA,
                          csric02Info_t         info,
                          cusparseSolvePolicy_t policy,
                          void*                  pBuffer)

cusparseStatus_t
cusparseCcsric02_analysis (cusparseHandle_t      handle,
                          int                    m,
                          int                    nnz,
                          const cusparseMatDescr_t descrA,
                          const cuComplex*        csrValA,
                          const int*            csrRowPtrA,
                          const int*            csrColIndA,
                          csric02Info_t         info,
                          cusparseSolvePolicy_t policy,
                          void*                  pBuffer)

cusparseStatus_t
cusparseZcsric02_analysis (cusparseHandle_t      handle,
                          int                    m,
                          int                    nnz,
                          const cusparseMatDescr_t descrA,
                          const cuDoubleComplex* csrValA,
                          const int*            csrRowPtrA,
                          const int*            csrColIndA,
                          csric02Info_t         info,
                          cusparseSolvePolicy_t policy,
                          void*                  pBuffer)

```

This function performs the analysis phase of the incomplete-Cholesky factorization with **0** fill-in and no pivoting:

$$A \approx LL^H$$

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`.

This function requires a buffer size returned by `csric02_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `csric02_analysis()` reports a structural zero and computes level information stored in the opaque structure `info`. The level information can extract more parallelism during incomplete Cholesky factorization. However `csric02()` can be done without level information. To disable level information, the user must specify the policy of `csric02_analysis()` and `csric02()` as `CUSPARSE_SOLVE_POLICY_NO_LEVEL`.

Function `csric02_analysis()` always reports the first structural zero, even if the policy is `CUSPARSE_SOLVE_POLICY_NO_LEVEL`. The user needs to call `cusparseXcsric02_zeroPivot()` to know where the structural zero is.

It is the user's choice whether to call `csric02()` if `csric02_analysis()` reports a structural zero. In this case, the user can still call `csric02()`, which will return a numerical zero at the same position as the structural zero. However the result is meaningless.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows and columns of matrix A.
<code>nnz</code>	number of nonzeros of matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>csrValA</code>	<type> array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> nonzero elements of matrix A.
<code>csrRowPtrA</code>	integer array of <code>m + 1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> column indices of the nonzero elements of matrix A.

info	structure initialized using <code>cusparseCreateCsrlic02Info()</code> .
policy	the supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
pBuffer	buffer allocated by the user; the size is returned by <code>csric02_bufferSize()</code> .

Output

info	number of bytes of the buffer used in <code>csric02_analysis()</code> and <code>csric02()</code> .
------	--

See [cusparseStatus_t](#) for the description of the return status

12.1.3. `cusparse<t>csric02()`

```

cusparseStatus_t
cusparseScsric02(cusparseHandle_t      handle,
                int                    m,
                int                    nnz,
                const cusparseMatDescr_t descrA,
                float*                 csrValA_valM,
                const int*              csrRowPtrA,
                const int*              csrColIndA,
                csric02Info_t          info,
                cusparseSolvePolicy_t  policy,
                void*                  pBuffer)

cusparseStatus_t
cusparseDcsric02(cusparseHandle_t      handle,
                int                    m,
                int                    nnz,
                const cusparseMatDescr_t descrA,
                double*                 csrValA_valM,
                const int*              csrRowPtrA,
                const int*              csrColIndA,
                csric02Info_t          info,
                cusparseSolvePolicy_t  policy,
                void*                  pBuffer)

cusparseStatus_t
cusparseCcsric02(cusparseHandle_t      handle,
                int                    m,
                int                    nnz,
                const cusparseMatDescr_t descrA,
                cuComplex*              csrValA_valM,
                const int*              csrRowPtrA,
                const int*              csrColIndA,
                csric02Info_t          info,
                cusparseSolvePolicy_t  policy,
                void*                  pBuffer)

cusparseStatus_t
cusparseZcsric02(cusparseHandle_t      handle,
                int                    m,

```

```

int nnz,
const cusparseMatDescr_t descrA,
cuDoubleComplex* csrValA_valM,
const int* csrRowPtrA,
const int* csrColIndA,
csric02Info_t info,
cusparseSolvePolicy_t policy,
void* pBuffer)

```

This function performs the solve phase of the computing the incomplete-Cholesky factorization with 0 fill-in and no pivoting:

$$A \approx LL^H$$

This function requires a buffer size returned by `csric02_bufferSize()`. The address of `pBuffer` must be a multiple of 128 bytes. If not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Although `csric02()` can be done without level information, the user still needs to be aware of consistency. If `csric02_analysis()` is called with policy `CUSPARSE_SOLVE_POLICY_USE_LEVEL`, `csric02()` can be run with or without levels. On the other hand, if `csric02_analysis()` is called with `CUSPARSE_SOLVE_POLICY_NO_LEVEL`, `csric02()` can only accept `CUSPARSE_SOLVE_POLICY_NO_LEVEL`; otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `csric02()` reports the first numerical zero, including a structural zero. The user must call `cusparseXcsric02_zeroPivot()` to know where the numerical zero is.

Function `csric02()` only takes the lower triangular part of matrix `A` to perform factorization. The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, the fill mode and diagonal type are ignored, and the strictly upper triangular part is ignored and never touched. It does not matter if `A` is Hermitian or not. In other words, from the point of view of `csric02()` `A` is Hermitian and only the lower triangular part is provided.



Note: In practice, a positive definite matrix may not have incomplete cholesky factorization. To the best of our knowledge, only matrix `M` can guarantee the existence of incomplete cholesky factorization. If `csric02()` failed cholesky factorization and reported a numerical zero, it is possible that incomplete cholesky factorization does not exist.

For example, suppose `A` is a real $m \times m$ matrix, the following code solves the precondition system $M^*y = x$ where `M` is the product of Cholesky factorization `L` and its transpose.

$$M = LL^H$$

```

// Suppose that A is m x m sparse matrix represented by CSR format,
// Assumption:
// - handle is already created by cusparseCreate(),
// - (d_csrRowPtr, d_csrColInd, d_csrVal) is CSR of A on device memory,
// - d_x is right hand side vector on device memory,
// - d_y is solution vector on device memory.
// - d_z is intermediate result on device memory.

cusparseMatDescr_t descr_M = 0;
cusparseMatDescr_t descr_L = 0;
csric02Info_t info_M = 0;
csrsv2Info_t info_L = 0;
csrsv2Info_t info_Lt = 0;

```

```

int pBufferSize_M;
int pBufferSize_L;
int pBufferSize_Lt;
int pBufferSize;
void *pBuffer = 0;
int structural_zero;
int numerical_zero;
const double alpha = 1.;
const cusparseSolvePolicy_t policy_M = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
const cusparseSolvePolicy_t policy_L = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
const cusparseSolvePolicy_t policy_Lt = CUSPARSE_SOLVE_POLICY_USE_LEVEL;
const cusparseOperation_t trans_L = CUSPARSE_OPERATION_NON_TRANSPOSE;
const cusparseOperation_t trans_Lt = CUSPARSE_OPERATION_TRANSPOSE;

// step 1: create a descriptor which contains
// - matrix M is base-1
// - matrix L is base-1
// - matrix L is lower triangular
// - matrix L has non-unit diagonal
cusparseCreateMatDescr(&descr_M);
cusparseSetMatIndexBase(descr_M, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_M, CUSPARSE_MATRIX_TYPE_GENERAL);

cusparseCreateMatDescr(&descr_L);
cusparseSetMatIndexBase(descr_L, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_L, CUSPARSE_MATRIX_TYPE_GENERAL);
cusparseSetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparseSetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 2: create a empty info structure
// we need one info for csric02 and two info's for csrsv2
cusparseCreateCsric02Info(&info_M);
cusparseCreateCsrsv2Info(&info_L);
cusparseCreateCsrsv2Info(&info_Lt);

// step 3: query how much memory used in csric02 and csrsv2, and allocate the buffer
cusparseDcsric02_bufferSize(handle, m, nnz,
    descr_M, d_csrVal, d_csrRowPtr, d_csrColInd, info_M, &bufferSize_M);
cusparseDcsrsv2_bufferSize(handle, trans_L, m, nnz,
    descr_L, d_csrVal, d_csrRowPtr, d_csrColInd, info_L, &pBufferSize_L);
cusparseDcsrsv2_bufferSize(handle, trans_Lt, m, nnz,
    descr_L, d_csrVal, d_csrRowPtr, d_csrColInd, info_Lt, &pBufferSize_Lt);

pBufferSize = max(bufferSize_M, max(pBufferSize_L, pBufferSize_Lt));

// pBuffer returned by cudaMalloc is automatically aligned to 128 bytes.
cudaMalloc((void**) &pBuffer, pBufferSize);

// step 4: perform analysis of incomplete Cholesky on M
//         perform analysis of triangular solve on L
//         perform analysis of triangular solve on L'
// The lower triangular part of M has the same sparsity pattern as L, so
// we can do analysis of csric02 and csrsv2 simultaneously.

cusparseDcsric02_analysis(handle, m, nnz, descr_M,
    d_csrVal, d_csrRowPtr, d_csrColInd, info_M,
    policy_M, pBuffer);
status = cusparseXcsric02_zeroPivot(handle, info_M, &structural_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status) {
    printf("A(%d,%d) is missing\n", structural_zero, structural_zero);
}

cusparseDcsrsv2_analysis(handle, trans_L, m, nnz, descr_L,
    d_csrVal, d_csrRowPtr, d_csrColInd,
    info_L, policy_L, pBuffer);

cusparseDcsrsv2_analysis(handle, trans_Lt, m, nnz, descr_L,

```

```

    d_csrVal, d_csrRowPtr, d_csrColInd,
    info_Lt, policy_Lt, pBuffer);

// step 5: M = L * L'
cusparseDcsric02(handle, m, nnz, descr_M,
    d_csrVal, d_csrRowPtr, d_csrColInd, info_M, policy_M, pBuffer);
status = cusparseXcsric02_zeroPivot(handle, info_M, &numerical_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("L(%d,%d) is zero\n", numerical_zero, numerical_zero);
}

// step 6: solve L*z = x
cusparseDcsrsv2_solve(handle, trans_L, m, nnz, &alpha, descr_L,
    d_csrVal, d_csrRowPtr, d_csrColInd, info_L,
    d_x, d_z, policy_L, pBuffer);

// step 7: solve L'*y = z
cusparseDcsrsv2_solve(handle, trans_Lt, m, nnz, &alpha, descr_L,
    d_csrVal, d_csrRowPtr, d_csrColInd, info_Lt,
    d_z, d_y, policy_Lt, pBuffer);

// step 6: free resources
cudaFree(pBuffer);
cusparseDestroyMatDescr(descr_M);
cusparseDestroyMatDescr(descr_L);
cusparseDestroyCsrinfo02Info(info_M);
cusparseDestroyCsrsv2Info(info_L);
cusparseDestroyCsrsv2Info(info_Lt);
cusparseDestroy(handle);

```

The function supports the following properties if `pBuffer != NULL`

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows and columns of matrix A.
<code>nnz</code>	number of nonzeros of matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>csrValA_valM</code>	<type> array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> nonzero elements of matrix A.
<code>csrRowPtrA</code>	integer array of <code>m + 1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> column indices of the nonzero elements of matrix A.

info	structure with information collected during the analysis phase (that should have been passed to the solve phase unchanged).
policy	the supported policies are CUSPARSE_SOLVE_POLICY_NO_LEVEL and CUSPARSE_SOLVE_POLICY_USE_LEVEL.
pBuffer	buffer allocated by the user; the size is returned by <code>csric02_bufferSize()</code> .

Output

csrValA_valM	<type> matrix containing the incomplete-Cholesky lower triangular factor.
--------------	---

See [cusparsesStatus_t](#) for the description of the return status

12.1.4. `cusparsesXcsric02_zeroPivot()`

```
cusparsesStatus_t
cusparsesXcsric02_zeroPivot(cusparsesHandle_t handle,
                           csric02Info_t info,
                           int* position)
```

If the returned error code is `CUSPARSE_STATUS_ZERO_PIVOT`, `position=j` means `A(j,j)` has either a structural zero or a numerical zero; otherwise, `position=-1`.

The `position` can be 0-based or 1-based, the same as the matrix.

Function `cusparsesXcsric02_zeroPivot()` is a blocking call. It calls `cudaDeviceSynchronize()` to make sure all previous kernels are done.

The `position` can be in the host memory or device memory. The user can set proper mode with `cusparsesSetPointerMode()`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
info	<code>info</code> contains structural zero or numerical zero if the user already called <code>csric02_analysis()</code> or <code>csric02()</code> .

Output

position	if no structural or numerical zero, position is -1; otherwise, if A(j, j) is missing or L(j, j) is zero, position=j.
----------	--

See [cusparseStatus_t](#) for the description of the return status

12.1.5. `cusparse<t>bsric02_bufferSize()`

```

cusparseStatus_t
cusparseSbsric02_bufferSize(cusparseHandle_t      handle,
                           cusparseDirection_t    dirA,
                           int                    mb,
                           int                    nnzb,
                           const cusparseMatDescr_t descrA,
                           float*                 bsrValA,
                           const int*             bsrRowPtrA,
                           const int*             bsrColIndA,
                           int                    blockDim,
                           bsric02Info_t          info,
                           int*                   pBufferSizeInBytes)

cusparseStatus_t
cusparseDbsric02_bufferSize(cusparseHandle_t      handle,
                            cusparseDirection_t    dirA,
                            int                    mb,
                            int                    nnzb,
                            const cusparseMatDescr_t descrA,
                            double*                bsrValA,
                            const int*             bsrRowPtrA,
                            const int*             bsrColIndA,
                            int                    blockDim,
                            bsric02Info_t          info,
                            int*                   pBufferSizeInBytes)

cusparseStatus_t
cusparseCbsric02_bufferSize(cusparseHandle_t      handle,
                            cusparseDirection_t    dirA,
                            int                    mb,
                            int                    nnzb,
                            const cusparseMatDescr_t descrA,
                            cuComplex*             bsrValA,
                            const int*             bsrRowPtrA,
                            const int*             bsrColIndA,
                            int                    blockDim,
                            bsric02Info_t          info,
                            int*                   pBufferSizeInBytes)

cusparseStatus_t
cusparseZbsric02_bufferSize(cusparseHandle_t      handle,
                            cusparseDirection_t    dirA,
                            int                    mb,
                            int                    nnzb,
                            const cusparseMatDescr_t descrA,
                            cuDoubleComplex*       bsrValA,
                            const int*             bsrRowPtrA,
                            const int*             bsrColIndA,
                            int                    blockDim,
                            bsric02Info_t          info,

```

int* pBufferSizeInBytes)

This function returns the size of a buffer used in computing the incomplete-Cholesky factorization with 0 fill-in and no pivoting

$$A \approx LL^H$$

A is an $(mb \times blockDim) \times (mb \times blockDim)$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`.

The buffer size depends on the dimensions of `mb`, `blockDim`, and the number of nonzero blocks of the matrix `nnzb`. If the user changes the matrix, it is necessary to call `bsric02_bufferSize()` again to have the correct buffer size; otherwise, a segmentation fault may occur.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dirA</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>mb</code>	number of block rows and block columns of matrix A.
<code>nnzb</code>	number of nonzero blocks of matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>bsrValA</code>	<type> array of <code>nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0))</code> nonzero blocks of matrix A.
<code>bsrRowPtrA</code>	integer array of <code>mb + 1</code> elements that contains the start of every block row and the end of the last block row plus one.
<code>bsrColIndA</code>	integer array of <code>nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0))</code> column indices of the nonzero blocks of matrix A.
<code>blockDim</code>	block dimension of sparse matrix A, larger than zero.

Output

<code>info</code>	record internal states based on different algorithms.
-------------------	---

<code>pBufferSizeInBytes</code>	number of bytes of the buffer used in <code>bsric02_analysis()</code> and <code>bsric02()</code> .
---------------------------------	--

See [`cusparseStatus_t`](#) for the description of the return status

12.1.6. `cusparse<t>bsric02_analysis()`

```

cusparseStatus_t
cusparseSbsric02_analysis(cusparseHandle_t      handle,
                          cusparseDirection_t  dirA,
                          int                   mb,
                          int                   nnzb,
                          const cusparseMatDescr_t descrA,
                          const float*         bsrValA,
                          const int*           bsrRowPtrA,
                          const int*           bsrColIndA,
                          int                   blockDim,
                          bsric02Info_t        info,
                          cusparseSolvePolicy_t policy,
                          void*                 pBuffer)

cusparseStatus_t
cusparseDbsric02_analysis(cusparseHandle_t      handle,
                          cusparseDirection_t  dirA,
                          int                   mb,
                          int                   nnzb,
                          const cusparseMatDescr_t descrA,
                          const double*        bsrValA,
                          const int*           bsrRowPtrA,
                          const int*           bsrColIndA,
                          int                   blockDim,
                          bsric02Info_t        info,
                          cusparseSolvePolicy_t policy,
                          void*                 pBuffer)

cusparseStatus_t
cusparseCbsric02_analysis(cusparseHandle_t      handle,
                          cusparseDirection_t  dirA,
                          int                   mb,
                          int                   nnzb,
                          const cusparseMatDescr_t descrA,
                          const cuComplex*     bsrValA,
                          const int*           bsrRowPtrA,
                          const int*           bsrColIndA,
                          int                   blockDim,
                          bsric02Info_t        info,
                          cusparseSolvePolicy_t policy,
                          void*                 pBuffer)

cusparseStatus_t
cusparseZbsric02_analysis(cusparseHandle_t      handle,
                          cusparseDirection_t  dirA,
                          int                   mb,
                          int                   nnzb,
                          const cusparseMatDescr_t descrA,
                          const cuDoubleComplex* bsrValA,
                          const int*           bsrRowPtrA,
                          const int*           bsrColIndA,

```

```

int          blockDim,
bsric02Info_t info,
cusparseSolvePolicy_t policy,
void*       pBuffer)

```

This function performs the analysis phase of the incomplete-Cholesky factorization with 0 fill-in and no pivoting

$$A \approx LL^H$$

A is an $(mb \times blockDim) \times (mb \times blockDim)$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`. The block in BSR format is of size $blockDim \times blockDim$, stored as column-major or row-major as determined by parameter `dirA`, which is either `CUSPARSE_DIRECTION_COLUMN` or `CUSPARSE_DIRECTION_ROW`. The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, and the fill mode and diagonal type are ignored.

This function requires a buffer size returned by `bsric02_bufferSize90`. The address of `pBuffer` must be a multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `bsric02_analysis()` reports structural zero and computes level information stored in the opaque structure `info`. The level information can extract more parallelism during incomplete Cholesky factorization. However `bsric02()` can be done without level information. To disable level information, the user needs to specify the parameter `policy` of `bsric02[_analysis|]` as `CUSPARSE_SOLVE_POLICY_NO_LEVEL`.

Function `bsric02_analysis` always reports the first structural zero, even when parameter `policy` is `CUSPARSE_SOLVE_POLICY_NO_LEVEL`. The user must call `cusparseXbsric02_zeroPivot()` to know where the structural zero is.

It is the user's choice whether to call `bsric02()` if `bsric02_analysis()` reports a structural zero. In this case, the user can still call `bsric02()`, which returns a numerical zero in the same position as the structural zero. However the result is meaningless.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dirA</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>mb</code>	number of block rows and block columns of matrix A.
<code>nnzb</code>	number of nonzero blocks of matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> .

	Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
bsrValA	<type> array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) nonzero blocks of matrix A.
bsrRowPtrA	integer array of mb + 1 elements that contains the start of every block row and the end of the last block row plus one.
bsrColIndA	integer array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) column indices of the nonzero blocks of matrix A.
blockDim	block dimension of sparse matrix A; must be larger than zero.
info	structure initialized using cusparseCreateBsrlic02Info().
policy	the supported policies are CUSPARSE_SOLVE_POLICY_NO_LEVEL and CUSPARSE_SOLVE_POLICY_USE_LEVEL.
pBuffer	buffer allocated by the user; the size is returned by bsrlic02_bufferSize().

Output

info	structure filled with information collected during the analysis phase (that should be passed to the solve phase unchanged).
------	---

See [cusparseStatus_t](#) for the description of the return status

12.1.7. cusparse<t>bsrlic02()

```

cusparseStatus_t
cusparseSbsrlic02(cusparseHandle_t      handle,
                  cusparseDirection_t  dirA,
                  int                   mb,
                  int                   nnzb,
                  const cusparseMatDescr_t descrA,
                  float*                bsrValA,
                  const int*            bsrRowPtrA,
                  const int*            bsrColIndA,
                  int                   blockDim,
                  bsrlic02Info_t        info,
                  cusparseSolvePolicy_t policy,
                  void*                 pBuffer)

cusparseStatus_t
cusparseDbsrlic02(cusparseHandle_t      handle,
                  cusparseDirection_t  dirA,
                  int                   mb,
                  int                   nnzb,
                  const cusparseMatDescr_t descrA,
                  double*              bsrValA,

```

```

        const int*          bsrRowPtrA,
        const int*          bsrColIndA,
        int                 blockDim,
        bsrict02Info_t      info,
        cusparseSolvePolicy_t policy,
        void*               pBuffer)

cusparseStatus_t
cusparseCbsric02(cusparseHandle_t      handle,
                 cusparseDirection_t   dirA,
                 int                   mb,
                 int                   nnzb,
                 const cusparseMatDescr_t descrA,
                 cuComplex*            bsrValA,
                 const int*            bsrRowPtrA,
                 const int*            bsrColIndA,
                 int                   blockDim,
                 bsrict02Info_t        info,
                 cusparseSolvePolicy_t policy,
                 void*                 pBuffer)

cusparseStatus_t
cusparseZbsric02(cusparseHandle_t      handle,
                 cusparseDirection_t   dirA,
                 int                   mb,
                 int                   nnzb,
                 const cusparseMatDescr_t descrA,
                 cuDoubleComplex*      bsrValA,
                 const int*            bsrRowPtrA,
                 const int*            bsrColIndA,
                 int                   blockDim,
                 bsrict02Info_t        info,
                 cusparseSolvePolicy_t policy,
                 void*                 pBuffer)

```

This function performs the solve phase of the incomplete-Cholesky factorization with 0 fill-in and no pivoting

$$A \approx LL^H$$

A is an $(mb \times blockDim) \times (mb \times blockDim)$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`. The block in BSR format is of size $blockDim \times blockDim$, stored as column-major or row-major as determined by parameter `dirA`, which is either `CUSPARSE_DIRECTION_COLUMN` or `CUSPARSE_DIRECTION_ROW`. The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, and the fill mode and diagonal type are ignored.

This function requires a buffer size returned by `bsric02_bufferSize()`. The address of `pBuffer` must be a multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Although `bsric02()` can be done without level information, the user must be aware of consistency. If `bsric02_analysis()` is called with policy `CUSPARSE_SOLVE_POLICY_USE_LEVEL`, `bsric02()` can be run with or without levels. On the other hand, if `bsric02_analysis()` is called with `CUSPARSE_SOLVE_POLICY_NO_LEVEL`, `bsric02()` can only accept `CUSPARSE_SOLVE_POLICY_NO_LEVEL`; otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `bsric02()` has the same behavior as `csric02()`. That is, `bsr2csr(bsric02(A)) = csric02(bsr2csr(A))`. The numerical zero of `csric02()` means there exists some zero $L(j, j)$. The numerical zero of `bsric02()` means there exists some block L_j, j that is not invertible.

Function `bsric02` reports the first numerical zero, including a structural zero. The user must call `cusparseXbsric02_zeroPivot()` to know where the numerical zero is.

The `bsric02()` function only takes the lower triangular part of matrix A to perform factorization. The strictly upper triangular part is ignored and never touched. It does not matter if A is Hermitian or not. In other words, from the point of view of `bsric02()`, A is Hermitian and only the lower triangular part is provided. Moreover, the imaginary part of diagonal elements of diagonal blocks is ignored.

For example, suppose A is a real m -by- m matrix, where $m = mb * blockDim$. The following code solves precondition system $M * y = x$, where M is the product of Cholesky factorization L and its transpose.

$$M = LL^H$$

```
// Suppose that A is m x m sparse matrix represented by BSR format,
// The number of block rows/columns is mb, and
// the number of nonzero blocks is nnzb.
// Assumption:
// - handle is already created by cusparseCreate(),
// - (d_bsrRowPtr, d_bsrColInd, d_bsrVal) is BSR of A on device memory,
// - d_x is right hand side vector on device memory,
// - d_y is solution vector on device memory.
// - d_z is intermediate result on device memory.
// - d_x, d_y and d_z are of size m.
cusparseMatDescr_t descr_M = 0;
cusparseMatDescr_t descr_L = 0;
bsric02Info_t info_M = 0;
bsrsv2Info_t info_L = 0;
bsrsv2Info_t info_Lt = 0;
int pBufferSize_M;
int pBufferSize_L;
int pBufferSize_Lt;
int pBufferSize;
void *pBuffer = 0;
int structural_zero;
int numerical_zero;
const double alpha = 1.;
const cusparseSolvePolicy_t policy_M = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
const cusparseSolvePolicy_t policy_L = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
const cusparseSolvePolicy_t policy_Lt = CUSPARSE_SOLVE_POLICY_USE_LEVEL;
const cusparseOperation_t trans_L = CUSPARSE_OPERATION_NON_TRANSPOSE;
const cusparseOperation_t trans_Lt = CUSPARSE_OPERATION_TRANSPOSE;
const cusparseDirection_t dir = CUSPARSE_DIRECTION_COLUMN;

// step 1: create a descriptor which contains
// - matrix M is base-1
// - matrix L is base-1
// - matrix L is lower triangular
// - matrix L has non-unit diagonal
cusparseCreateMatDescr(&descr_M);
cusparseSetMatIndexBase(descr_M, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_M, CUSPARSE_MATRIX_TYPE_GENERAL);

cusparseCreateMatDescr(&descr_L);
cusparseSetMatIndexBase(descr_L, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_L, CUSPARSE_MATRIX_TYPE_GENERAL);
```



```

cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 2: create a empty info structure
// we need one info for bsr02 and two info's for bsrsv2
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);
cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 2: create a empty info structure
// we need one info for bsr02 and two info's for bsrsv2
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);
cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 3: query how much memory used in bsr02 and bsrsv2, and allocate the buffer
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);
cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 4: perform analysis of incomplete Cholesky on M
//         perform analysis of triangular solve on L
//         perform analysis of triangular solve on L'
// The lower triangular part of M has the same sparsity pattern as L, so
// we can do analysis of bsr02 and bsrsv2 simultaneously.

cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);
cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 5: M = L * L'
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);
cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 6: solve L*z = x
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);
cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 7: solve L'*y = z
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);
cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 6: free resources
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);
cusparsesetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparsesetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_NON_UNIT);

```

```

cusparsedestroyBsrsv2Info (info_M);
cusparsedestroyBsrsv2Info (info_L);
cusparsedestroyBsrsv2Info (info_Lt);
cusparsedestroy (handle);

```

The function supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dirA</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>mb</code>	number of block rows and block columns of matrix A.
<code>nnzb</code>	number of nonzero blocks of matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>bsrValA</code>	<type> array of <code>nnzb (= bsrRowPtrA (mb) - bsrRowPtrA (0))</code> nonzero blocks of matrix A.
<code>bsrRowPtrA</code>	integer array of <code>mb + 1</code> elements that contains the start of every block row and the end of the last block row plus one.
<code>bsrColIndA</code>	integer array of <code>nnzb (= bsrRowPtrA (mb) - bsrRowPtrA (0))</code> column indices of the nonzero blocks of matrix A.
<code>blockDim</code>	block dimension of sparse matrix A, larger than zero.
<code>info</code>	structure with information collected during the analysis phase (that should have been passed to the solve phase unchanged).
<code>policy</code>	the supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
<code>pBuffer</code>	buffer allocated by the user, the size is returned by <code>bsrsv2_bufferSize ()</code> .

Output

<code>bsrValA</code>	<type> matrix containing the incomplete-Cholesky lower triangular factor.
----------------------	---

See [cusparseStatus_t](#) for the description of the return status

12.1.8. cusparseXbsric02_zeroPivot()

```
cusparseStatus_t
cusparseXbsric02_zeroPivot(cusparseHandle_t handle,
                           bsrict0Info_t info,
                           int* position)
```

If the returned error code is `CUSPARSE_STATUS_ZERO_PIVOT`, `position=j` means $A(j, j)$ has either a structural zero or a numerical zero (the block is not positive definite). Otherwise `position=-1`.

The `position` can be 0-based or 1-based, the same as the matrix.

Function `cusparseXbsric02_zeroPivot()` is a blocking call. It calls `cudaDeviceSynchronize()` to make sure all previous kernels are done.

The `position` can be in the host memory or device memory. The user can set the proper mode with `cusparseSetPointerMode()`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>info</code>	<code>info</code> contains a structural zero or a numerical zero if the user already called <code>bsric02_analysis()</code> or <code>bsric02()</code> .

Output

<code>position</code>	if no structural or numerical zero, <code>position</code> is -1, otherwise if $A(j, j)$ is missing or $L(j, j)$ is not positive definite, <code>position=j</code> .
-----------------------	---

See [cusparseStatus_t](#) for the description of the return status

12.2. Incomplete LU Factorization: level 0

Different algorithms for `ilu0` are discussed in this section.

12.2.1. cusparse<t>csrilu02_numericBoost()

```
cusparseStatus_t
```

```

cusparseScsrilu02_numericBoost(cusparseHandle_t handle,
                               csrilu02Info_t   info,
                               int               enable_boost,
                               double*          tol,
                               float*           boost_val)

cusparseStatus_t
cusparseDcsrilu02_numericBoost(cusparseHandle_t handle,
                               csrilu02Info_t   info,
                               int               enable_boost,
                               double*          tol,
                               double*          boost_val)

cusparseStatus_t
cusparseCcsrilu02_numericBoost(cusparseHandle_t handle,
                               csrilu02Info_t   info,
                               int               enable_boost,
                               double*          tol,
                               cuComplex*       boost_val)

cusparseStatus_t
cusparseZcsrilu02_numericBoost(cusparseHandle_t handle,
                               csrilu02Info_t   info,
                               int               enable_boost,
                               double*          tol,
                               cuDoubleComplex* boost_val)

```

The user can use a boost value to replace a numerical value in incomplete LU factorization. The `tol` is used to determine a numerical zero, and the `boost_val` is used to replace a numerical zero. The behavior is

if $tol \geq \text{fabs}(A(j,j))$, then $A(j,j) = \text{boost_val}$.

To enable a boost value, the user has to set parameter `enable_boost` to 1 before calling `csrilu02()`. To disable a boost value, the user can call `csrilu02_numericBoost()` again with parameter `enable_boost=0`.

If `enable_boost=0`, `tol` and `boost_val` are ignored.

Both `tol` and `boost_val` can be in the host memory or device memory. The user can set the proper mode with `cusparseSetPointerMode()`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>info</code>	structure initialized using <code>cusparseCreateCsrilu02Info()</code> .
<code>enable_boost</code>	disable boost by <code>enable_boost=0</code> ; otherwise, boost is enabled.
<code>tol</code>	tolerance to determine a numerical zero.
<code>boost_val</code>	boost value to replace a numerical zero.

See [cusparseStatus_t](#) for the description of the return status

12.2.2. `cusparse<t>csrilu02_bufferSize()`

```

cusparseStatus_t
cusparseScsrilu02_bufferSize(cusparseHandle_t      handle,
                             int                  m,
                             int                  nnz,
                             const cusparseMatDescr_t descrA,
                             float*              csrValA,
                             const int*          csrRowPtrA,
                             const int*          csrColIndA,
                             csrilu02Info_t      info,
                             int*                 pBufferSizeInBytes)

cusparseStatus_t
cusparseDcsrilu02_bufferSize(cusparseHandle_t      handle,
                             int                  m,
                             int                  nnz,
                             const cusparseMatDescr_t descrA,
                             double*             csrValA,
                             const int*          csrRowPtrA,
                             const int*          csrColIndA,
                             csrilu02Info_t      info,
                             int*                 pBufferSizeInBytes)

cusparseStatus_t
cusparseCcsrilu02_bufferSize(cusparseHandle_t      handle,
                             int                  m,
                             int                  nnz,
                             const cusparseMatDescr_t descrA,
                             cuComplex*          csrValA,
                             const int*          csrRowPtrA,
                             const int*          csrColIndA,
                             csrilu02Info_t      info,
                             int*                 pBufferSizeInBytes)

cusparseStatus_t
cusparseZcsrilu02_bufferSize(cusparseHandle_t      handle,
                             int                  m,
                             int                  nnz,
                             const cusparseMatDescr_t descrA,
                             cuDoubleComplex*    csrValA,
                             const int*          csrRowPtrA,
                             const int*          csrColIndA,
                             csrilu02Info_t      info,
                             int*                 pBufferSizeInBytes)

```

This function returns size of the buffer used in computing the incomplete-LU factorization with 0 fill-in and no pivoting:

$$A \approx LU$$

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`.

The buffer size depends on the dimension m and nnz , the number of nonzeros of the matrix. If the user changes the matrix, it is necessary to call `csrilu02_bufferSize()` again to have the correct buffer size; otherwise, a segmentation fault may occur.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows and columns of matrix A .
<code>nnz</code>	number of nonzeros of matrix A .
<code>descrA</code>	the descriptor of matrix A . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>csrValA</code>	<type> array of $nnz (= \text{csrRowPtrA}(m) - \text{csrRowPtrA}(0))$ nonzero elements of matrix A .
<code>csrRowPtrA</code>	integer array of $m + 1$ elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of $nnz (= \text{csrRowPtrA}(m) - \text{csrRowPtrA}(0))$ column indices of the nonzero elements of matrix A .

Output

<code>info</code>	record internal states based on different algorithms.
<code>pBufferSizeInBytes</code>	number of bytes of the buffer used in <code>csrilu02_analysis()</code> and <code>csrilu02()</code> .

See [cusparsesStatus_t](#) for the description of the return status

12.2.3. `cusparses<t>csrilu02_analysis()`

```

cusparsesStatus_t
cusparsesScsrilu02_analysis(cusparsesHandle_t      handle,
                           int                    m,
                           int                    nnz,
                           const cusparsesMatDescr_t descrA,
                           const float*          csrValA,
                           const int*           csrRowPtrA,
                           const int*           csrColIndA,
                           cusparsesInfo_t       info,
                           cusparsesSolvePolicy_t policy,
                           void*                pBuffer)

```

```

cusparseStatus_t
cusparseDcsrilu02_analysis(cusparseHandle_t      handle,
                          int                    m,
                          int                    nnz,
                          const cusparseMatDescr_t descrA,
                          const double*         csrValA,
                          const int*            csrRowPtrA,
                          const int*            csrColIndA,
                          csrilu02Info_t        info,
                          cusparseSolvePolicy_t policy,
                          void*                 pBuffer)

cusparseStatus_t
cusparseCcsrilu02_analysis(cusparseHandle_t      handle,
                           int                    m,
                           int                    nnz,
                           const cusparseMatDescr_t descrA,
                           const cuComplex*       csrValA,
                           const int*            csrRowPtrA,
                           const int*            csrColIndA,
                           csrilu02Info_t        info,
                           cusparseSolvePolicy_t policy,
                           void*                 pBuffer)

cusparseStatus_t
cusparseZcsrilu02_analysis(cusparseHandle_t      handle,
                           int                    m,
                           int                    nnz,
                           const cusparseMatDescr_t descrA,
                           const cuDoubleComplex* csrValA,
                           const int*            csrRowPtrA,
                           const int*            csrColIndA,
                           csrilu02Info_t        info,
                           cusparseSolvePolicy_t policy,
                           void*                 pBuffer)

```

This function performs the analysis phase of the incomplete-LU factorization with **0** fill-in and no pivoting:

$$A \approx LU$$

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`.

This function requires the buffer size returned by `csrilu02_bufferSize()`. The address of `pBuffer` must be a multiple of 128 bytes. If not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `csrilu02_analysis()` reports a structural zero and computes level information stored in the opaque structure `info`. The level information can extract more parallelism during incomplete LU factorization; however `csrilu02()` can be done without level information. To disable level information, the user must specify the policy of `csrilu02()` as `CUSPARSE_SOLVE_POLICY_NO_LEVEL`.

It is the user's choice whether to call `csrilu02()` if `csrilu02_analysis()` reports a structural zero. In this case, the user can still call `csrilu02()`, which will return a numerical zero at the same position as the structural zero. However the result is meaningless.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
m	number of rows and columns of matrix A.
nnz	number of nonzeros of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
csrValA	<type> array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> nonzero elements of matrix A.
csrRowPtrA	integer array of <code>m + 1</code> elements that contains the start of every row and the end of the last row plus one.
csrColIndA	integer array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> column indices of the nonzero elements of matrix A.
info	structure initialized using <code>cusparseCreateCsrilu02Info()</code> .
policy	the supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
pBuffer	buffer allocated by the user, the size is returned by <code>csrilu02_bufferSize()</code> .

Output

info	structure filled with information collected during the analysis phase (that should be passed to the solve phase unchanged).
------	---

See [cusparseStatus_t](#) for the description of the return status

12.2.4. `cusparse<t>csrilu02()`

```
cusparseStatus_t
cusparseScsrilu02(cusparseHandle_t      handle,
                  int                    m,
                  int                    nnz,
                  const cusparseMatDescr_t descrA,
                  float*                 csrValA_valM,
```



```

        const int*
        const int*
        csrilu02Info_t
        cusparseSolvePolicy_t
        void*
        csrRowPtrA,
        csrColIndA,
        info,
        policy,
        pBuffer)

cusparseStatus_t
cusparseDcsrilu02(cusparseHandle_t      handle,
                  int                    m,
                  int                    nnz,
                  const cusparseMatDescr_t descrA,
                  double*                 csrValA_valM,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  csrilu02Info_t          info,
                  cusparseSolvePolicy_t   policy,
                  void*                   pBuffer)

cusparseStatus_t
cusparseCcsrilu02(cusparseHandle_t      handle,
                  int                    m,
                  int                    nnz,
                  const cusparseMatDescr_t descrA,
                  cuComplex*              csrValA_valM,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  csrilu02Info_t          info,
                  cusparseSolvePolicy_t   policy,
                  void*                   pBuffer)

cusparseStatus_t
cusparseZcsrilu02(cusparseHandle_t      handle,
                  int                    m,
                  int                    nnz,
                  const cusparseMatDescr_t descrA,
                  cuDoubleComplex*         csrValA_valM,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  csrilu02Info_t          info,
                  cusparseSolvePolicy_t   policy,
                  void*                   pBuffer)

```

This function performs the solve phase of the incomplete-LU factorization with **0** fill-in and no pivoting:

$$A \approx LU$$

A is an $m \times m$ sparse matrix that is defined in CSR storage format by the three arrays `csrValA_valM`, `csrRowPtrA`, and `csrColIndA`.

This function requires a buffer size returned by `csrilu02_bufferSize()`. The address of `pBuffer` must be a multiple of 128 bytes. If not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`. The fill mode and diagonal type are ignored.

Although `csrilu02()` can be done without level information, the user still needs to be aware of consistency. If `csrilu02_analysis()` is called with `policy`

CUSPARSE_SOLVE_POLICY_USE_LEVEL, `csrilu02()` can be run with or without levels. On the other hand, if `csrilu02_analysis()` is called with `CUSPARSE_SOLVE_POLICY_NO_LEVEL`, `csrilu02()` can only accept `CUSPARSE_SOLVE_POLICY_NO_LEVEL`; otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `csrilu02()` reports the first numerical zero, including a structural zero. The user must call `cusparseXcsrilu02_zeroPivot()` to know where the numerical zero is.

For example, suppose A is a real $m \times m$ matrix, the following code solves precondition system $M*y = x$ where M is the product of LU factors L and U .

```
// Suppose that A is m x m sparse matrix represented by CSR format,
// Assumption:
// - handle is already created by cusparseCreate(),
// - (d_csrRowPtr, d_csrColInd, d_csrVal) is CSR of A on device memory,
// - d_x is right hand side vector on device memory,
// - d_y is solution vector on device memory.
// - d_z is intermediate result on device memory.

cusparseMatDescr_t descr_M = 0;
cusparseMatDescr_t descr_L = 0;
cusparseMatDescr_t descr_U = 0;
csrilu02Info_t info_M = 0;
csrsv2Info_t info_L = 0;
csrsv2Info_t info_U = 0;
int pBufferSize_M;
int pBufferSize_L;
int pBufferSize_U;
int pBufferSize;
void *pBuffer = 0;
int structural_zero;
int numerical_zero;
const double alpha = 1.;
const cusparseSolvePolicy_t policy_M = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
const cusparseSolvePolicy_t policy_L = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
const cusparseSolvePolicy_t policy_U = CUSPARSE_SOLVE_POLICY_USE_LEVEL;
const cusparseOperation_t trans_L = CUSPARSE_OPERATION_NON_TRANSPOSE;
const cusparseOperation_t trans_U = CUSPARSE_OPERATION_NON_TRANSPOSE;

// step 1: create a descriptor which contains
// - matrix M is base-1
// - matrix L is base-1
// - matrix L is lower triangular
// - matrix L has unit diagonal
// - matrix U is base-1
// - matrix U is upper triangular
// - matrix U has non-unit diagonal
cusparseCreateMatDescr(&descr_M);
cusparseSetMatIndexBase(descr_M, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_M, CUSPARSE_MATRIX_TYPE_GENERAL);

cusparseCreateMatDescr(&descr_L);
cusparseSetMatIndexBase(descr_L, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_L, CUSPARSE_MATRIX_TYPE_GENERAL);
cusparseSetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparseSetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_UNIT);

cusparseCreateMatDescr(&descr_U);
cusparseSetMatIndexBase(descr_U, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_U, CUSPARSE_MATRIX_TYPE_GENERAL);
cusparseSetMatFillMode(descr_U, CUSPARSE_FILL_MODE_UPPER);
cusparseSetMatDiagType(descr_U, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 2: create a empty info structure
// we need one info for csrilu02 and two info's for csrsv2
```

```

cusparseCreateCsrilu02Info(&info_M);
cusparseCreateCsrsv2Info(&info_L);
cusparseCreateCsrsv2Info(&info_U);

// step 3: query how much memory used in csrilu02 and csrsv2, and allocate the
// buffer
cusparseDcsrilu02_bufferSize(handle, m, nnz,
    descr_M, d_csrVal, d_csrRowPtr, d_csrColInd, info_M, &pBufferSize_M);
cusparseDcsrsv2_bufferSize(handle, trans_L, m, nnz,
    descr_L, d_csrVal, d_csrRowPtr, d_csrColInd, info_L, &pBufferSize_L);
cusparseDcsrsv2_bufferSize(handle, trans_U, m, nnz,
    descr_U, d_csrVal, d_csrRowPtr, d_csrColInd, info_U, &pBufferSize_U);

pBufferSize = max(pBufferSize_M, max(pBufferSize_L, pBufferSize_U));

// pBuffer returned by cudaMalloc is automatically aligned to 128 bytes.
cudaMalloc((void**)&pBuffer, pBufferSize);

// step 4: perform analysis of incomplete Cholesky on M
//         perform analysis of triangular solve on L
//         perform analysis of triangular solve on U
// The lower(upper) triangular part of M has the same sparsity pattern as L(U),
// we can do analysis of csrilu0 and csrsv2 simultaneously.

cusparseDcsrilu02_analysis(handle, m, nnz, descr_M,
    d_csrVal, d_csrRowPtr, d_csrColInd, info_M,
    policy_M, pBuffer);
status = cusparseXcsrilu02_zeroPivot(handle, info_M, &structural_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("A(%d,%d) is missing\n", structural_zero, structural_zero);
}

cusparseDcsrsv2_analysis(handle, trans_L, m, nnz, descr_L,
    d_csrVal, d_csrRowPtr, d_csrColInd,
    info_L, policy_L, pBuffer);

cusparseDcsrsv2_analysis(handle, trans_U, m, nnz, descr_U,
    d_csrVal, d_csrRowPtr, d_csrColInd,
    info_U, policy_U, pBuffer);

// step 5: M = L * U
cusparseDcsrilu02(handle, m, nnz, descr_M,
    d_csrVal, d_csrRowPtr, d_csrColInd, info_M, policy_M, pBuffer);
status = cusparseXcsrilu02_zeroPivot(handle, info_M, &numerical_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("U(%d,%d) is zero\n", numerical_zero, numerical_zero);
}

// step 6: solve L*z = x
cusparseDcsrsv2_solve(handle, trans_L, m, nnz, &alpha, descr_L,
    d_csrVal, d_csrRowPtr, d_csrColInd, info_L,
    d_x, d_z, policy_L, pBuffer);

// step 7: solve U*y = z
cusparseDcsrsv2_solve(handle, trans_U, m, nnz, &alpha, descr_U,
    d_csrVal, d_csrRowPtr, d_csrColInd, info_U,
    d_z, d_y, policy_U, pBuffer);

// step 6: free resources
cudaFree(pBuffer);
cusparseDestroyMatDescr(descr_M);
cusparseDestroyMatDescr(descr_L);
cusparseDestroyMatDescr(descr_U);
cusparseDestroyCsrilu02Info(info_M);
cusparseDestroyCsrsv2Info(info_L);
cusparseDestroyCsrsv2Info(info_U);
cusparseDestroy(handle);

```

The function supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows and columns of matrix A.
<code>nnz</code>	number of nonzeros of matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>csrValA_valM</code>	<type> array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> nonzero elements of matrix A.
<code>csrRowPtrA</code>	integer array of <code>m + 1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> column indices of the nonzero elements of matrix A.
<code>info</code>	structure with information collected during the analysis phase (that should have been passed to the solve phase unchanged).
<code>policy</code>	the supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
<code>pBuffer</code>	buffer allocated by the user; the size is returned by <code>csrilu02_bufferSize()</code> .

Output

<code>csrValA_valM</code>	<type> matrix containing the incomplete-LU lower and upper triangular factors.
---------------------------	--

See [`cusparseStatus_t`](#) for the description of the return status

12.2.5. `cusparseXcsrilu02_zeroPivot()`

```
cusparseStatus_t
cusparseXcsrilu02_zeroPivot(cusparseHandle_t handle,
                           csrilu02Info_t   info,
                           int*              position)
```

If the returned error code is `CUSPARSE_STATUS_ZERO_PIVOT`, `position=j` means $A(j, j)$ has either a structural zero or a numerical zero; otherwise, `position=-1`.

The `position` can be 0-based or 1-based, the same as the matrix.

Function `cusparseXcsrilu02_zeroPivot()` is a blocking call. It calls `cudaDeviceSynchronize()` to make sure all previous kernels are done.

The `position` can be in the host memory or device memory. The user can set proper mode with `cusparseSetPointerMode()`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>info</code>	<code>info</code> contains structural zero or numerical zero if the user already called <code>csrilu02_analysis()</code> or <code>csrilu02()</code> .

Output

<code>position</code>	if no structural or numerical zero, <code>position</code> is -1; otherwise if $A(j, j)$ is missing or $U(j, j)$ is zero, <code>position=j</code> .
-----------------------	--

See [cusparseStatus_t](#) for the description of the return status

12.2.6. `cusparse<t>bsrilu02_numericBoost()`

```
cusparseStatus_t
cusparseSbsrilu02_numericBoost(cusparseHandle_t handle,
                               bsrilu02Info_t   info,
                               int               enable_boost,
                               double*          tol,
                               float*           boost_val)

cusparseStatus_t
cusparseDbsrilu02_numericBoost(cusparseHandle_t handle,
                               bsrilu02Info_t   info,
                               int               enable_boost,
                               double*          tol,
                               double*         boost_val)

cusparseStatus_t
cusparseCbsrilu02_numericBoost(cusparseHandle_t handle,
                               bsrilu02Info_t   info,
                               int               enable_boost,
                               double*          tol,
                               cuComplex*      boost_val)
```

```

cusparsesStatus_t
cusparsesZbsrilu02_numericBoost(cusparsesHandle_t handle,
                                bsrilu02Info_t info,
                                int enable_boost,
                                double* tol,
                                cuDoubleComplex* boost_val)

```

The user can use a boost value to replace a numerical value in incomplete LU factorization. Parameter `tol` is used to determine a numerical zero, and `boost_val` is used to replace a numerical zero. The behavior is as follows:

if `tol >= fabs(A(j,j))`, then reset each diagonal element of block `A(j,j)` by `boost_val`.

To enable a boost value, the user sets parameter `enable_boost` to 1 before calling `bsrilu02()`. To disable the boost value, the user can call `bsrilu02_numericBoost()` with parameter `enable_boost=0`.

If `enable_boost=0`, `tol` and `boost_val` are ignored.

Both `tol` and `boost_val` can be in host memory or device memory. The user can set the proper mode with `cusparsesSetPointerMode()`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>info</code>	structure initialized using <code>cusparsesCreateBsrilu02Info()</code> .
<code>enable_boost</code>	disable boost by setting <code>enable_boost=0</code> . Otherwise, boost is enabled.
<code>tol</code>	tolerance to determine a numerical zero.
<code>boost_val</code>	boost value to replace a numerical zero.

See [cusparsesStatus_t](#) for the description of the return status

12.2.7. `cusparses<t>bsrilu02_bufferSize()`

```

cusparsesStatus_t
cusparsesSbsrilu02_bufferSize(cusparsesHandle_t handle,
                              cusparsesDirection_t dirA,
                              int mb,
                              int nnzb,
                              const cusparsesMatDescr_t descrA,
                              float *bsrValA,
                              const int *bsrRowPtrA,
                              const int *bsrColIndA,
                              int blockDim,
                              bsrilu02Info_t info,
                              int *pBufferSizeInBytes);

```

```

cusparseStatus_t
cusparseDbsrilu02_bufferSize(cusparseHandle_t handle,
                             cusparseDirection_t dirA,
                             int mb,
                             int nnzb,
                             const cusparseMatDescr_t descrA,
                             double *bsrValA,
                             const int *bsrRowPtrA,
                             const int *bsrColIndA,
                             int blockDim,
                             bsrilu02Info_t info,
                             int *pBufferSizeInBytes);

cusparseStatus_t
cusparseCbsrilu02_bufferSize(cusparseHandle_t handle,
                             cusparseDirection_t dirA,
                             int mb,
                             int nnzb,
                             const cusparseMatDescr_t descrA,
                             cuComplex *bsrValA,
                             const int *bsrRowPtrA,
                             const int *bsrColIndA,
                             int blockDim,
                             bsrilu02Info_t info,
                             int *pBufferSizeInBytes);

cusparseStatus_t
cusparseZbsrilu02_bufferSize(cusparseHandle_t handle,
                             cusparseDirection_t dirA,
                             int mb,
                             int nnzb,
                             const cusparseMatDescr_t descrA,
                             cuDoubleComplex *bsrValA,
                             const int *bsrRowPtrA,
                             const int *bsrColIndA,
                             int blockDim,
                             bsrilu02Info_t info,
                             int *pBufferSizeInBytes);

```

This function returns the size of the buffer used in computing the incomplete-LU factorization with 0 fill-in and no pivoting

$$A \approx LU$$

A is an $(mb \cdot blockDim) \times (mb \cdot blockDim)$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`.

The buffer size depends on the dimensions of `mb`, `blockDim`, and the number of nonzero blocks of the matrix `nnzb`. If the user changes the matrix, it is necessary to call `bsrilu02_bufferSize()` again to have the correct buffer size; otherwise, a segmentation fault may occur.

Input

handle	handle to the cuSPARSE library context.
--------	---

dirA	storage format of blocks, either CUSPARSE_DIRECTION_ROW or CUSPARSE_DIRECTION_COLUMN.
mb	number of block rows and columns of matrix A.
nnzb	number of nonzero blocks of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL. Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
bsrValA	<type> array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) nonzero blocks of matrix A.
bsrRowPtrA	integer array of mb + 1 elements that contains the start of every block row and the end of the last block row plus one.
bsrColIndA	integer array of nnzb (= bsrRowPtrA(mb) - bsrRowPtrA(0)) column indices of the nonzero blocks of matrix A.
blockDim	block dimension of sparse matrix A, larger than zero.

Output

info	record internal states based on different algorithms.
pBufferSizeInBytes	number of bytes of the buffer used in bsrilu02_analysis() and bsrilu02().

Status Returned

CUSPARSE_STATUS_SUCCESS	the operation completed successfully.
CUSPARSE_STATUS_NOT_INITIALIZED	the library was not initialized.
CUSPARSE_STATUS_ALLOC_FAILED	the resources could not be allocated.
CUSPARSE_STATUS_INVALID_VALUE	invalid parameters were passed (mb, nnzb<=0), base index is not 0 or 1.
CUSPARSE_STATUS_ARCH_MISMATCH	the device only supports compute capability 2.0 and above.
CUSPARSE_STATUS_INTERNAL_ERROR	an internal operation failed.
CUSPARSE_STATUS_MATRIX_TYPE_NOT_SUPPORTED	the matrix type is not supported.

12.2.8. cusparse<t>bsrilu02_analysis()

```

cusparseStatus_t
cusparseBsrilu02_analysis(cusparseHandle_t      handle,
                          cusparseDirection_t   dirA,
                          int                   mb,
                          int                   nnzb,
                          const cusparseMatDescr_t descrA,

```



```

        float*
        const int*
        const int*
        int
        bsrilu02Info_t
        cusparseSolvePolicy_t
        void*
        bsrValA,
        bsrRowPtrA,
        bsrColIndA,
        blockDim,
        info,
        policy,
        pBuffer)

cusparseStatus_t
cusparseDbsrilu02_analysis(cusparseHandle_t      handle,
                          cusparseDirection_t   dirA,
                          int                   mb,
                          int                   nnzb,
                          const cusparseMatDescr_t descrA,
                          double*              bsrValA,
                          const int*           bsrRowPtrA,
                          const int*           bsrColIndA,
                          int                   blockDim,
                          bsrilu02Info_t       info,
                          cusparseSolvePolicy_t policy,
                          void*                pBuffer)

cusparseStatus_t
cusparseCbsrilu02_analysis(cusparseHandle_t      handle,
                           cusparseDirection_t   dirA,
                           int                   mb,
                           int                   nnzb,
                           const cusparseMatDescr_t descrA,
                           cuComplex*           bsrValA,
                           const int*           bsrRowPtrA,
                           const int*           bsrColIndA,
                           int                   blockDim,
                           bsrilu02Info_t       info,
                           cusparseSolvePolicy_t policy,
                           void*                pBuffer)

cusparseStatus_t
cusparseZbsrilu02_analysis(cusparseHandle_t      handle,
                           cusparseDirection_t   dirA,
                           int                   mb,
                           int                   nnzb,
                           const cusparseMatDescr_t descrA,
                           cuDoubleComplex*     bsrValA,
                           const int*           bsrRowPtrA,
                           const int*           bsrColIndA,
                           int                   blockDim,
                           bsrilu02Info_t       info,
                           cusparseSolvePolicy_t policy,
                           void*                pBuffer)

```

This function performs the analysis phase of the incomplete-LU factorization with 0 fill-in and no pivoting

$$A \approx LU$$

A is an $(mb \times blockDim) \times (mb \times blockDim)$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`. The block in BSR format is of size $blockDim \times blockDim$, stored as column-major or row-major as determined by parameter `dirA`, which is either `CUSPARSE_DIRECTION_COLUMN` or `CUSPARSE_DIRECTION_ROW`. The

matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, and the fill mode and diagonal type are ignored.

This function requires a buffer size returned by `bsrilu02_bufferSize()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `bsrilu02_analysis()` reports a structural zero and computes level information stored in the opaque structure `info`. The level information can extract more parallelism during incomplete LU factorization. However `bsrilu02()` can be done without level information. To disable level information, the user needs to specify the parameter `policy` of `bsrilu02[_analysis|]` as `CUSPARSE_SOLVE_POLICY_NO_LEVEL`.

Function `bsrilu02_analysis()` always reports the first structural zero, even with parameter `policy` is `CUSPARSE_SOLVE_POLICY_NO_LEVEL`. The user must call `cusparseXbsrilu02_zeroPivot()` to know where the structural zero is.

It is the user's choice whether to call `bsrilu02()` if `bsrilu02_analysis()` reports a structural zero. In this case, the user can still call `bsrilu02()`, which will return a numerical zero at the same position as the structural zero. However the result is meaningless.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dirA</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>mb</code>	number of block rows and block columns of matrix A.
<code>nnzb</code>	number of nonzero blocks of matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>bsrValA</code>	<type> array of <code>nnzb</code> ($= \text{bsrRowPtrA}(mb) - \text{bsrRowPtrA}(0)$) nonzero blocks of matrix A.
<code>bsrRowPtrA</code>	integer array of <code>mb + 1</code> elements that contains the start of every block row and the end of the last block row plus one.
<code>bsrColIndA</code>	integer array of <code>nnzb</code> ($= \text{bsrRowPtrA}(mb) - \text{bsrRowPtrA}(0)$) column indices of the nonzero blocks of matrix A.

blockDim	block dimension of sparse matrix A, larger than zero.
info	structure initialized using <code>cusparseCreateBsrilu02Info()</code> .
policy	the supported policies are <code>CUSPARSE_SOLVE_POLICY_NO_LEVEL</code> and <code>CUSPARSE_SOLVE_POLICY_USE_LEVEL</code> .
pBuffer	buffer allocated by the user, the size is returned by <code>bsrilu02_bufferSize()</code> .

Output

info	structure filled with information collected during the analysis phase (that should be passed to the solve phase unchanged).
------	---

See [cusparseStatus_t](#) for the description of the return status

12.2.9. `cusparse<t>bsrilu02()`

```

cusparseStatus_t
cusparseBsrilu02 (cusparseHandle_t      handle,
                  cusparseDirection_t  dirA,
                  int                  mb,
                  int                  nnzb,
                  const cusparseMatDescr_t descry,
                  float*               bsrValA,
                  const int*           bsrRowPtrA,
                  const int*           bsrColIndA,
                  int                  blockDim,
                  bsrilu02Info_t       info,
                  cusparseSolvePolicy_t policy,
                  void*                pBuffer)

cusparseStatus_t
cusparseDbsrilu02 (cusparseHandle_t      handle,
                   cusparseDirection_t  dirA,
                   int                  mb,
                   int                  nnzb,
                   const cusparseMatDescr_t descry,
                   double*              bsrValA,
                   const int*           bsrRowPtrA,
                   const int*           bsrColIndA,
                   int                  blockDim,
                   bsrilu02Info_t       info,
                   cusparseSolvePolicy_t policy,
                   void*                pBuffer)

cusparseStatus_t
cusparseCbsrilu02 (cusparseHandle_t      handle,
                   cusparseDirection_t  dirA,
                   int                  mb,
                   int                  nnzb,
                   const cusparseMatDescr_t descry,
                   cuComplex*          bsrValA,

```

```

        const int*      bsrRowPtrA,
        const int*      bsrColIndA,
        int             blockDim,
        bsrilu02Info_t  info,
        cusparseSolvePolicy_t policy,
        void*           pBuffer)

cusparseStatus_t
cusparseZbsrilu02(cusparseHandle_t handle,
                  cusparseDirection_t dirA,
                  int mb,
                  int nnzb,
                  const cusparseMatDescr_t descry,
                  cuDoubleComplex* bsrValA,
                  const int* bsrRowPtrA,
                  const int* bsrColIndA,
                  int blockDim,
                  bsrilu02Info_t info,
                  cusparseSolvePolicy_t policy,
                  void* pBuffer)

```

This function performs the solve phase of the incomplete-LU factorization with 0 fill-in and no pivoting

$$A \approx LU$$

A is an $(mb \times blockDim) \times (mb \times blockDim)$ sparse matrix that is defined in BSR storage format by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`. The block in BSR format is of size $blockDim \times blockDim$, stored as column-major or row-major determined by parameter `dirA`, which is either `CUSPARSE_DIRECTION_COLUMN` or `CUSPARSE_DIRECTION_ROW`. The matrix type must be `CUSPARSE_MATRIX_TYPE_GENERAL`, and the fill mode and diagonal type are ignored. Function `bsrilu02()` supports an arbitrary `blockDim`.

This function requires a buffer size returned by `bsrilu02_bufferSize()`. The address of `pBuffer` must be a multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Although `bsrilu02()` can be used without level information, the user must be aware of consistency. If `bsrilu02_analysis()` is called with policy `CUSPARSE_SOLVE_POLICY_USE_LEVEL`, `bsrilu02()` can be run with or without levels. On the other hand, if `bsrilu02_analysis()` is called with `CUSPARSE_SOLVE_POLICY_NO_LEVEL`, `bsrilu02()` can only accept `CUSPARSE_SOLVE_POLICY_NO_LEVEL`; otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Function `bsrilu02()` has the same behavior as `csrilu02()`. That is, `bsr2csr(bsrilu02(A)) = csrilu02(bsr2csr(A))`. The numerical zero of `csrilu02()` means there exists some zero $U(j, j)$. The numerical zero of `bsrilu02()` means there exists some block $U(j, j)$ that is not invertible.

Function `bsrilu02` reports the first numerical zero, including a structural zero. The user must call `cusparseXbsrilu02_zeroPivot()` to know where the numerical zero is.

For example, suppose A is a real m-by-m matrix where $m = mb \times blockDim$. The following code solves precondition system $M \cdot y = x$, where M is the product of LU factors L and U.

```
// Suppose that A is m x m sparse matrix represented by BSR format,
```

```

// The number of block rows/columns is mb, and
// the number of nonzero blocks is nnzb.
// Assumption:
// - handle is already created by cusparseCreate(),
// - (d_bsrRowPtr, d_bsrColInd, d_bsrVal) is BSR of A on device memory,
// - d_x is right hand side vector on device memory.
// - d_y is solution vector on device memory.
// - d_z is intermediate result on device memory.
// - d_x, d_y and d_z are of size m.
cusparseMatDescr_t descr_M = 0;
cusparseMatDescr_t descr_L = 0;
cusparseMatDescr_t descr_U = 0;
bsrilu02Info_t info_M = 0;
bsrsv2Info_t info_L = 0;
bsrsv2Info_t info_U = 0;
int pBufferSize_M;
int pBufferSize_L;
int pBufferSize_U;
int pBufferSize;
void *pBuffer = 0;
int structural_zero;
int numerical_zero;
const double alpha = 1.;
const cusparseSolvePolicy_t policy_M = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
const cusparseSolvePolicy_t policy_L = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
const cusparseSolvePolicy_t policy_U = CUSPARSE_SOLVE_POLICY_USE_LEVEL;
const cusparseOperation_t trans_L = CUSPARSE_OPERATION_NON_TRANSPOSE;
const cusparseOperation_t trans_U = CUSPARSE_OPERATION_NON_TRANSPOSE;
const cusparseDirection_t dir = CUSPARSE_DIRECTION_COLUMN;

// step 1: create a descriptor which contains
// - matrix M is base-1
// - matrix L is base-1
// - matrix L is lower triangular
// - matrix L has unit diagonal
// - matrix U is base-1
// - matrix U is upper triangular
// - matrix U has non-unit diagonal
cusparseCreateMatDescr(&descr_M);
cusparseSetMatIndexBase(descr_M, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_M, CUSPARSE_MATRIX_TYPE_GENERAL);

cusparseCreateMatDescr(&descr_L);
cusparseSetMatIndexBase(descr_L, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_L, CUSPARSE_MATRIX_TYPE_GENERAL);
cusparseSetMatFillMode(descr_L, CUSPARSE_FILL_MODE_LOWER);
cusparseSetMatDiagType(descr_L, CUSPARSE_DIAG_TYPE_UNIT);

cusparseCreateMatDescr(&descr_U);
cusparseSetMatIndexBase(descr_U, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descr_U, CUSPARSE_MATRIX_TYPE_GENERAL);
cusparseSetMatFillMode(descr_U, CUSPARSE_FILL_MODE_UPPER);
cusparseSetMatDiagType(descr_U, CUSPARSE_DIAG_TYPE_NON_UNIT);

// step 2: create a empty info structure
// we need one info for bsrilu02 and two info's for bsrsv2
cusparseCreateBsrilu02Info(&info_M);
cusparseCreateBsrsv2Info(&info_L);
cusparseCreateBsrsv2Info(&info_U);

// step 3: query how much memory used in bsrilu02 and bsrsv2, and allocate the
// buffer
cusparseDbsrilu02_bufferSize(handle, dir, mb, nnzb,
    descr_M, d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, info_M, &pBufferSize_M);
cusparseDbsrsv2_bufferSize(handle, dir, trans_L, mb, nnzb,
    descr_L, d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, info_L, &pBufferSize_L);
cusparseDbsrsv2_bufferSize(handle, dir, trans_U, mb, nnzb,

```

```

    descr_U, d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, info_U, &pBufferSize_U);
pBufferSize = max(pBufferSize_M, max(pBufferSize_L, pBufferSize_U));
// pBuffer returned by cudaMalloc is automatically aligned to 128 bytes.
cudaMalloc((void**)&pBuffer, pBufferSize);

// step 4: perform analysis of incomplete LU factorization on M
//           perform analysis of triangular solve on L
//           perform analysis of triangular solve on U
// The lower(upper) triangular part of M has the same sparsity pattern as L(U),
// we can do analysis of bsrilu0 and bsrsv2 simultaneously.

cusparsedbstrilu02_analysis(handle, dir, mb, nnzb, descr_M,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, info_M,
    policy_M, pBuffer);
status = cusparsedbstrilu02_zeroPivot(handle, info_M, &structural_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("A[%d,%d] is missing\n", structural_zero, structural_zero);
}

cusparsedbbsrsv2_analysis(handle, dir, trans_L, mb, nnzb, descr_L,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim,
    info_L, policy_L, pBuffer);

cusparsedbbsrsv2_analysis(handle, dir, trans_U, mb, nnzb, descr_U,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim,
    info_U, policy_U, pBuffer);

// step 5: M = L * U
cusparsedbstrilu02(handle, dir, mb, nnzb, descr_M,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, info_M, policy_M, pBuffer);
status = cusparsedbstrilu02_zeroPivot(handle, info_M, &numerical_zero);
if (CUSPARSE_STATUS_ZERO_PIVOT == status){
    printf("block U[%d,%d] is not invertible\n", numerical_zero, numerical_zero);
}

// step 6: solve L*z = x
cusparsedbbsrsv2_solve(handle, dir, trans_L, mb, nnzb, &alpha, descr_L,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, info_L,
    d_x, d_z, policy_L, pBuffer);

// step 7: solve U*y = z
cusparsedbbsrsv2_solve(handle, dir, trans_U, mb, nnzb, &alpha, descr_U,
    d_bsrVal, d_bsrRowPtr, d_bsrColInd, blockDim, info_U,
    d_z, d_y, policy_U, pBuffer);

// step 6: free resources
cudaFree(pBuffer);
cusparsedestroyMatDescr(descr_M);
cusparsedestroyMatDescr(descr_L);
cusparsedestroyMatDescr(descr_U);
cusparsedestroyBsrilu02Info(info_M);
cusparsedestroyBsrsv2Info(info_L);
cusparsedestroyBsrsv2Info(info_U);
cusparsedestroy(handle);

```

The function supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
dirA	storage format of blocks: either CUSPARSE_DIRECTION_ROW or CUSPARSE_DIRECTION_COLUMN.
mb	number of block rows and block columns of matrix A.
nnzb	number of nonzero blocks of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL. Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
bsrValA	<type> array of nnzb (= bsrRowPtrA (mb) - bsrRowPtrA (0)) nonzero blocks of matrix A.
bsrRowPtrA	integer array of mb + 1 elements that contains the start of every block row and the end of the last block row plus one.
bsrColIndA	integer array of nnzb (= bsrRowPtrA (mb) - bsrRowPtrA (0)) column indices of the nonzero blocks of matrix A.
blockDim	block dimension of sparse matrix A; must be larger than zero.
info	structure with information collected during the analysis phase (that should have been passed to the solve phase unchanged).
policy	the supported policies are CUSPARSE_SOLVE_POLICY_NO_LEVEL and CUSPARSE_SOLVE_POLICY_USE_LEVEL.
pBuffer	buffer allocated by the user; the size is returned by bsrilu02_bufferSize().

Output

bsrValA	<type> matrix containing the incomplete-LU lower and upper triangular factors.
---------	--

See [cusparsesStatus_t](#) for the description of the return status

12.2.10. cusparsesXbsrilu02_zeroPivot()

```

cusparsesStatus_t
cusparsesXbsrilu02_zeroPivot(cusparsesHandle_t handle,
                             bsrilu02Info_t   info,
                             int*              position)

```

If the returned error code is `CUSPARSE_STATUS_ZERO_PIVOT`, `position=j` means $A(j, j)$ has either a structural zero or a numerical zero (the block is not invertible). Otherwise `position=-1`.

The `position` can be 0-based or 1-based, the same as the matrix.

Function `cusparseXbsrilu02_zeroPivot()` is a blocking call. It calls `cudaDeviceSynchronize()` to make sure all previous kernels are done.

The `position` can be in the host memory or device memory. The user can set proper the mode with `cusparseSetPointerMode()`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>info</code>	<code>info</code> contains structural zero or numerical zero if the user already called <code>bsrilu02_analysis()</code> or <code>bsrilu02()</code> .

Output

<code>position</code>	if no structural or numerical zero, <code>position</code> is -1; otherwise if $A(j, j)$ is missing or $U(j, j)$ is not invertible, <code>position=j</code> .
-----------------------	--

See [cusparseStatus_t](#) for the description of the return status

12.3. Tridiagonal Solve

Different algorithms for tridiagonal solve are discussed in this section.

12.3.1. `cusparse<t>gtsv2_bufferSizeExt()`

```
cusparseStatus_t
cusparseSgtsv2_bufferSizeExt(cusparseHandle_t handle,
                             int m,
                             int n,
                             const float* dl,
                             const float* d,
                             const float* du,
                             const float* B,
                             int ldb,
                             size_t* bufferSizeInBytes)
cusparseStatus_t
```



```

cusparseDgtsv2_bufferSizeExt(cusparseHandle_t handle,
                             int m,
                             int n,
                             const double* dl,
                             const double* d,
                             const double* du,
                             const double* B,
                             int ldb,
                             size_t* bufferSizeInBytes)

cusparseStatus_t
cusparseCgtsv2_bufferSizeExt(cusparseHandle_t handle,
                             int m,
                             int n,
                             const cuComplex* dl,
                             const cuComplex* d,
                             const cuComplex* du,
                             const cuComplex* B,
                             int ldb,
                             size_t* bufferSizeInBytes)

cusparseStatus_t
cusparseZgtsv2_bufferSizeExt(cusparseHandle_t handle,
                             int m,
                             int n,
                             const cuDoubleComplex* dl,
                             const cuDoubleComplex* d,
                             const cuDoubleComplex* du,
                             const cuDoubleComplex* B,
                             int ldb,
                             size_t* bufferSizeInBytes)

```

This function returns the size of the buffer used in `gtsv2` which computes the solution of a tridiagonal linear system with multiple right-hand sides.

$$A * X = B$$

The coefficient matrix `A` of each of these tri-diagonal linear system is defined with three vectors corresponding to its lower (`dl`), main (`d`), and upper (`du`) matrix diagonals; the right-hand sides are stored in the dense matrix `B`. Notice that solution `x` overwrites right-hand-side matrix `B` on exit.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	the size of the linear system (must be ≥ 3).
<code>n</code>	number of right-hand sides, columns of matrix <code>B</code> .
<code>dl</code>	<type> dense array containing the lower diagonal of the tri-diagonal linear system. The first element of each lower diagonal must be zero.

d	<type> dense array containing the main diagonal of the tri-diagonal linear system.
du	<type> dense array containing the upper diagonal of the tri-diagonal linear system. The last element of each upper diagonal must be zero.
B	<type> dense right-hand-side array of dimensions (ldb, n).
ldb	leading dimension of B (that is $\geq \max(1, m)$).

Output

pBufferSizeInBytes	number of bytes of the buffer used in the <code>gtsv2</code> .
--------------------	--

See [cusparseStatus_t](#) for the description of the return status

12.3.2. `cusparse<t>gtsv2()`

```

cusparseStatus_t
cusparseSgtsv2(cusparseHandle_t handle,
               int m,
               int n,
               const float* dl,
               const float* d,
               const float* du,
               float* B,
               int ldb,
               void pBuffer)

cusparseStatus_t
cusparseDgtsv2(cusparseHandle_t handle,
               int m,
               int n,
               const double* dl,
               const double* d,
               const double* du,
               double* B,
               int ldb,
               void pBuffer)

cusparseStatus_t
cusparseCgtsv2(cusparseHandle_t handle,
               int m,
               int n,
               const cuComplex* dl,
               const cuComplex* d,
               const cuComplex* du,
               cuComplex* B,
               int ldb,
               void pBuffer)

cusparseStatus_t
cusparseZgtsv2(cusparseHandle_t handle,
               int m,
               int n,
               const cuDoubleComplex* dl,
               const cuDoubleComplex* d,

```

```

const cuDoubleComplex* du,
cuDoubleComplex*      B,
int                    ldb,
void                   pBuffer)

```

This function computes the solution of a tridiagonal linear system with multiple right-hand sides:

$$A * X = B$$

The coefficient matrix A of each of these tri-diagonal linear system is defined with three vectors corresponding to its lower (d_l), main (d), and upper (d_u) matrix diagonals; the right-hand sides are stored in the dense matrix B . Notice that solution x overwrites right-hand-side matrix B on exit.

Assuming A is of size m and base-1, d_l , d and d_u are defined by the following formula:

$d_l(i) := A(i, i-1)$ for $i=1, 2, \dots, m$

The first element of d_l is out-of-bound ($d_l(1) := A(1, 0)$), so $d_l(1) = 0$.

$d(i) = A(i, i)$ for $i=1, 2, \dots, m$

$d_u(i) = A(i, i+1)$ for $i=1, 2, \dots, m$

The last element of d_u is out-of-bound ($d_u(m) := A(m, m+1)$), so $d_u(m) = 0$.

The routine does perform pivoting, which usually results in more accurate and more stable results than `cusparse<t>gtsv_nopivot()` or `cusparse<t>gtsv2_nopivot()` at the expense of some execution time.

This function requires a buffer size returned by `gtsv2_bufferSizeExt()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
m	the size of the linear system (must be ≥ 3).
n	number of right-hand sides, columns of matrix B .
d_l	<type> dense array containing the lower diagonal of the tri-diagonal linear system. The first element of each lower diagonal must be zero.
d	<type> dense array containing the main diagonal of the tri-diagonal linear system.
d_u	<type> dense array containing the upper diagonal of the tri-diagonal linear system. The last element of each upper diagonal must be zero.

B	<type> dense right-hand-side array of dimensions (ldb, n).
ldb	leading dimension of B (that is $\geq \max(1, m)$).
pBuffer	buffer allocated by the user, the size is return by gtsv2_bufferSizeExt.

Output

B	<type> dense solution array of dimensions (ldb, n).
---	---

See [cusparseStatus_t](#) for the description of the return status

12.3.3. cusparse<t>gtsv2_nopivot_bufferSizeExt()

```
cusparseStatus_t
cusparseSgtsv2_nopivot_bufferSizeExt (cusparseHandle_t handle,
                                     int                m,
                                     int                n,
                                     const float*       dl,
                                     const float*       d,
                                     const float*       du,
                                     const float*       B,
                                     int                ldb,
                                     size_t*            bufferSizeInBytes)
```

```
cusparseStatus_t
cusparseDgtsv2_nopivot_bufferSizeExt (cusparseHandle_t handle,
                                     int                m,
                                     int                n,
                                     const double*      dl,
                                     const double*      d,
                                     const double*      du,
                                     const double*      B,
                                     int                ldb,
                                     size_t*            bufferSizeInBytes)
```

```
cusparseStatus_t
cusparseCgtsv2_nopivot_bufferSizeExt (cusparseHandle_t handle,
                                     int                m,
                                     int                n,
                                     const cuComplex*   dl,
                                     const cuComplex*   d,
                                     const cuComplex*   du,
                                     const cuComplex*   B,
                                     int                ldb,
                                     size_t*            bufferSizeInBytes)
```

```
cusparseStatus_t
cusparseZgtsv2_nopivot_bufferSizeExt (cusparseHandle_t handle,
                                     int                m,
                                     int                n,
                                     const cuDoubleComplex* dl,
                                     const cuDoubleComplex* d,
                                     const cuDoubleComplex* du,
                                     const cuDoubleComplex* B,
                                     size_t*            bufferSizeInBytes)
```

```

                                int          ldb,
                                size_t*
bufferSizeInBytes)

```

This function returns the size of the buffer used in `gtsv2_nopivot` which computes the solution of a tridiagonal linear system with multiple right-hand sides.

$$A * X = B$$

The coefficient matrix **A** of each of these tri-diagonal linear system is defined with three vectors corresponding to its lower (**a1**), main (**d**), and upper (**du**) matrix diagonals; the right-hand sides are stored in the dense matrix **B**. Notice that solution **x** overwrites right-hand-side matrix **B** on exit.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
m	the size of the linear system (must be ≥ 3).
n	number of right-hand sides, columns of matrix B .
d1	<type> dense array containing the lower diagonal of the tri-diagonal linear system. The first element of each lower diagonal must be zero.
d	<type> dense array containing the main diagonal of the tri-diagonal linear system.
du	<type> dense array containing the upper diagonal of the tri-diagonal linear system. The last element of each upper diagonal must be zero.
B	<type> dense right-hand-side array of dimensions (<code>ldb</code> , <code>n</code>).
ldb	leading dimension of B . (that is $\geq \max(1, m)$).

Output

pBufferSizeInBytes	number of bytes of the buffer used in the <code>gtsv2_nopivot</code> .
--------------------	--

See [cusparsesStatus_t](#) for the description of the return status

12.3.4. `cusparses<t>gtsv2_nopivot()`

```

cusparsesStatus_t
cusparsesSgtsv2_nopivot(cusparsesHandle_t handle,
                        int          m,
                        int          n,
                        const float* d1,

```

```

        const float*    d,
        const float*    du,
        float*          B,
        int             ldb,
        void*           pBuffer)

cusparseStatus_t
cusparseDgtsv2_nopivot (cusparseHandle_t handle,
                       int             m,
                       int             n,
                       const double*   dl,
                       const double*   d,
                       const double*   du,
                       double*         B,
                       int             ldb,
                       void*           pBuffer)

cusparseStatus_t
cusparseCgtsv2_nopivot (cusparseHandle_t handle,
                       int             m,
                       int             n,
                       const cuComplex* dl,
                       const cuComplex* d,
                       const cuComplex* du,
                       cuComplex*      B,
                       int             ldb,
                       void*           pBuffer)

cusparseStatus_t
cusparseZgtsv2_nopivot (cusparseHandle_t handle,
                       int             m,
                       int             n,
                       const cuDoubleComplex* dl,
                       const cuDoubleComplex* d,
                       const cuDoubleComplex* du,
                       cuDoubleComplex* B,
                       int             ldb,
                       void*           pBuffer)

```

This function computes the solution of a tridiagonal linear system with multiple right-hand sides:

$$A * X = B$$

The coefficient matrix A of each of these tri-diagonal linear system is defined with three vectors corresponding to its lower (dl), main (d), and upper (du) matrix diagonals; the right-hand sides are stored in the dense matrix B . Notice that solution x overwrites right-hand-side matrix B on exit.

The routine does not perform any pivoting and uses a combination of the Cyclic Reduction (CR) and the Parallel Cyclic Reduction (PCR) algorithms to find the solution. It achieves better performance when m is a power of 2.

This function requires a buffer size returned by `gtsv2_nopivot_bufferSizeExt()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

- ▶ The routine requires no extra storage

- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
m	the size of the linear system (must be ≥ 3).
n	number of right-hand sides, columns of matrix B.
dl	<type> dense array containing the lower diagonal of the tri-diagonal linear system. The first element of each lower diagonal must be zero.
d	<type> dense array containing the main diagonal of the tri-diagonal linear system.
du	<type> dense array containing the upper diagonal of the tri-diagonal linear system. The last element of each upper diagonal must be zero.
B	<type> dense right-hand-side array of dimensions (ldb, n).
ldb	leading dimension of B. (that is $\geq \max(1, m)$).
pBuffer	buffer allocated by the user, the size is return by gtsv2_nopivot_bufferSizeExt.

Output

B	<type> dense solution array of dimensions (ldb, n).
---	---

See [cusparsesStatus_t](#) for the description of the return status

12.4. Batched Tridiagonal Solve

Different algorithms for batched tridiagonal solve are discussed in this section.

12.4.1. `cusparses<t>gtsv2StridedBatch_bufferSizeExt()`

```

cusparsesStatus_t
cusparsesSgtsv2StridedBatch_bufferSizeExt(cusparsesHandle_t handle,
                                           int m,
                                           const float* dl,
                                           const float* d,
                                           const float* du,
                                           const float* x,
                                           int batchSize,
                                           int batchStride,
                                           size_t* bufferSizeInBytes)

cusparsesStatus_t
cusparsesDgtsv2StridedBatch_bufferSizeExt(cusparsesHandle_t handle,
                                           int m,

```

```

        const double* dl,
        const double* d,
        const double* du,
        const double* x,
        int batchCount,
        int batchStride,
        size_t* bufferSizeInBytes)

cusparsesStatus_t
cusparsesCgtsv2StridedBatch_bufferSizeExt (cusparsesHandle_t handle,
        int m,
        const cuComplex* dl,
        const cuComplex* d,
        const cuComplex* du,
        const cuComplex* x,
        int batchCount,
        int batchStride,
        size_t* bufferSizeInBytes)

cusparsesStatus_t
cusparsesZgtsv2StridedBatch_bufferSizeExt (cusparsesHandle_t handle,
        int m,
        const cuDoubleComplex* dl,
        const cuDoubleComplex* d,
        const cuDoubleComplex* du,
        const cuDoubleComplex* x,
        int batchCount,
        int batchStride,
        size_t* bufferSizeInBytes)

```

This function returns the size of the buffer used in `gtsv2StridedBatch` which computes the solution of multiple tridiagonal linear systems for $i=0,\dots,\text{batchCount}$:

$$A^{(i)} * y^{(i)} = x^{(i)}$$

The coefficient matrix A of each of these tri-diagonal linear system is defined with three vectors corresponding to its lower (`dl`), main (`d`), and upper (`du`) matrix diagonals; the right-hand sides are stored in the dense matrix `x`. Notice that solution `y` overwrites right-hand-side matrix `x` on exit. The different matrices are assumed to be of the same size and are stored with a fixed `batchStride` in memory.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>n</code>	the size of the linear system (must be ≥ 3).
<code>dl</code>	<type> dense array containing the lower diagonal of the tri-diagonal linear system. The lower diagonal $dl^{(i)}$ that corresponds to the i^{th} linear system starts at location <code>dl+batchStride<i>i</i></code> in

	memory. Also, the first element of each lower diagonal must be zero.
d	<type> dense array containing the main diagonal of the tri-diagonal linear system. The main diagonal $d^{(i)}$ that corresponds to the i^{th} linear system starts at location $d + \text{batchStride} \times i$ in memory.
du	<type> dense array containing the upper diagonal of the tri-diagonal linear system. The upper diagonal $du^{(i)}$ that corresponds to the i^{th} linear system starts at location $du + \text{batchStride} \times i$ in memory. Also, the last element of each upper diagonal must be zero.
x	<type> dense array that contains the right-hand-side of the tri-diagonal linear system. The right-hand-side $x^{(i)}$ that corresponds to the i^{th} linear system starts at location $x + \text{batchStride} \times i$ in memory.
batchCount	number of systems to solve.
batchStride	stride (number of elements) that separates the vectors of every system (must be at least m).

Output

pBufferSizeInBytes	number of bytes of the buffer used in the <code>gtsv2StridedBatch</code> .
--------------------	--

See [`cusparseStatus_t`](#) for the description of the return status

12.4.2. `cusparse<t>gtsv2StridedBatch()`

```

cusparseStatus_t
cusparseSgtsv2StridedBatch(cusparseHandle_t handle,
                           int m,
                           const float* dl,
                           const float* d,
                           const float* du,
                           float* x,
                           int batchCount,
                           int batchStride,
                           void* pBuffer)

cusparseStatus_t
cusparseDgtsv2StridedBatch(cusparseHandle_t handle,
                           int m,
                           const double* dl,
                           const double* d,
                           const double* du,
                           double* x,
                           int batchCount,
                           int batchStride,
                           void* pBuffer)

```

```

cusparsesStatus_t
cusparsesCgtsv2StridedBatch(cusparsesHandle_t handle,
                           int m,
                           const cuComplex* dl,
                           const cuComplex* d,
                           const cuComplex* du,
                           cuComplex* x,
                           int batchCount,
                           int batchStride,
                           void* pBuffer)

cusparsesStatus_t
cusparsesZgtsv2StridedBatch(cusparsesHandle_t handle,
                           int m,
                           const cuDoubleComplex* dl,
                           const cuDoubleComplex* d,
                           const cuDoubleComplex* du,
                           cuDoubleComplex* x,
                           int batchCount,
                           int batchStride,
                           void* pBuffer)

```

This function computes the solution of multiple tridiagonal linear systems for $i=0, \dots, \text{batchCount}$:

$$A^{(i)} * y^{(i)} = x^{(i)}$$

The coefficient matrix A of each of these tri-diagonal linear system is defined with three vectors corresponding to its lower ($d1$), main (d), and upper (du) matrix diagonals; the right-hand sides are stored in the dense matrix x . Notice that solution y overwrites right-hand-side matrix x on exit. The different matrices are assumed to be of the same size and are stored with a fixed `batchStride` in memory.

The routine does not perform any pivoting and uses a combination of the Cyclic Reduction (CR) and the Parallel Cyclic Reduction (PCR) algorithms to find the solution. It achieves better performance when m is a power of 2.

This function requires a buffer size returned by `gtsv2StridedBatch_bufferSizeExt()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>n</code>	the size of the linear system (must be ≥ 3).
<code>d1</code>	<type> dense array containing the lower diagonal of the tri-diagonal linear system. The lower diagonal $d1^{(i)}$ that corresponds to the i^{th} linear system starts at location <code>d1+batchStride<i>i</i></code> in

	memory. Also, the first element of each lower diagonal must be zero.
d	<type> dense array containing the main diagonal of the tri-diagonal linear system. The main diagonal $d^{(i)}$ that corresponds to the i^{th} linear system starts at location $d+\text{batchStride}\times i$ in memory.
du	<type> dense array containing the upper diagonal of the tri-diagonal linear system. The upper diagonal $du^{(i)}$ that corresponds to the i^{th} linear system starts at location $du+\text{batchStride}\times i$ in memory. Also, the last element of each upper diagonal must be zero.
x	<type> dense array that contains the right-hand-side of the tri-diagonal linear system. The right-hand-side $x^{(i)}$ that corresponds to the i^{th} linear system starts at location $x+\text{batchStride}\times i$ in memory.
batchCount	number of systems to solve.
batchStride	stride (number of elements) that separates the vectors of every system (must be at least n).
pBuffer	buffer allocated by the user, the size is return by <code>gtsv2StridedBatch_bufferSizeExt</code> .

Output

x	<type> dense array that contains the solution of the tri-diagonal linear system. The solution $x^{(i)}$ that corresponds to the i^{th} linear system starts at location $x+\text{batchStride}\times i$ in memory.
---	--

See [cusparseStatus_t](#) for the description of the return status

12.4.3. `cusparse<t>gtsvInterleavedBatch()`

```

cusparseStatus_t
cusparseSgtsvInterleavedBatch_bufferSizeExt(cusparseHandle_t handle,
                                             int                algo,
                                             int                m,
                                             const float*       dl,
                                             const float*       d,
                                             const float*       du,
                                             const float*       x,
                                             int                batchCount,
                                             size_t*            pBufferSizeInBytes)

cusparseStatus_t
cusparseDgtsvInterleavedBatch_bufferSizeExt(cusparseHandle_t handle,
                                             int                algo,
                                             int                m,

```

```

        const double* dl,
        const double* d,
        const double* du,
        const double* x,
        int batchCount,
        size_t*
    pBufferSizeInBytes)

cusparsesStatus_t
cusparsesCgtsvInterleavedBatch_bufferSizeExt(cusparsesHandle_t handle,
        int algo,
        int m,
        const cuComplex* dl,
        const cuComplex* d,
        const cuComplex* du,
        const cuComplex* x,
        int batchCount,
        size_t*
    pBufferSizeInBytes)

cusparsesStatus_t
cusparsesZgtsvInterleavedBatch_bufferSizeExt(cusparsesHandle_t handle,
        int algo,
        int m,
        const cuDoubleComplex* dl,
        const cuDoubleComplex* d,
        const cuDoubleComplex* du,
        const cuDoubleComplex* x,
        int
    batchCount,
        size_t*
    pBufferSizeInBytes)

```

```

cusparsesStatus_t
cusparsesSgtsvInterleavedBatch(cusparsesHandle_t handle,
        int algo,
        int m,
        float* dl,
        float* d,
        float* du,
        float* x,
        int batchCount,
        void* pBuffer)

cusparsesStatus_t
cusparsesDgtsvInterleavedBatch(cusparsesHandle_t handle,
        int algo,
        int m,
        double* dl,
        double* d,
        double* du,
        double* x,
        int batchCount,
        void* pBuffer)

cusparsesStatus_t
cusparsesCgtsvInterleavedBatch(cusparsesHandle_t handle,
        int algo,
        int m,
        cuComplex* dl,

```

```

                                cuComplex*    d,
                                cuComplex*    du,
                                cuComplex*    x,
                                int           batchCount,
                                void*        pBuffer)

cusparseStatus_t
cusparseZgtsvInterleavedBatch(cusparseHandle_t handle,
                              int             algo,
                              int            m,
                              cuDoubleComplex* dl,
                              cuDoubleComplex* d,
                              cuDoubleComplex* du,
                              cuDoubleComplex* x,
                              int            batchCount,
                              void*        pBuffer)

```

This function computes the solution of multiple tridiagonal linear systems for $i=0, \dots, \text{batchCount}$:

$$A^{(i)} * x^{(i)} = b^{(i)}$$

The coefficient matrix A of each of these tri-diagonal linear system is defined with three vectors corresponding to its lower $\{d_l\}$, main $\{d\}$, and upper $\{d_u\}$ matrix diagonals; the right-hand sides are stored in the dense matrix B . Notice that solution x overwrites right-hand-side matrix B on exit.

Assuming A is of size m and base-1, d_l , d and d_u are defined by the following formula:

$d_l(i) := A(i, i-1)$ for $i=1, 2, \dots, m$

The first element of d_l is out-of-bound ($d_l(1) := A(1, 0)$), so $d_l(1) = 0$.

$d(i) = A(i, i)$ for $i=1, 2, \dots, m$

$d_u(i) = A(i, i+1)$ for $i=1, 2, \dots, m$

The last element of d_u is out-of-bound ($d_u(m) := A(m, m+1)$), so $d_u(m) = 0$.

The data layout is different from `gtsvStridedBatch` which aggregates all matrices one after another. Instead, `gtsvInterleavedBatch` gathers different matrices of the same element in a continuous manner. If d_l is regarded as a 2-D array of size m -by- batchCount , $d_l(:, j)$ to store j -th matrix. `gtsvStridedBatch` uses column-major while `gtsvInterleavedBatch` uses row-major.

The routine provides three different algorithms, selected by parameter `algo`. The first algorithm is `cuThomas` provided by Barcelona Supercomputing Center. The second algorithm is LU with partial pivoting and last algorithm is QR. From stability perspective, `cuThomas` is not numerically stable because it does not have pivoting. LU with partial pivoting and QR are stable. From performance perspective, LU with partial pivoting and QR is about 10% to 20% slower than `cuThomas`.

This function requires a buffer size returned by `gtsvInterleavedBatch_bufferSizeExt()`. The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

If the user prepares aggregate format, one can use `cublasXgeam` to get interleaved format. However such transformation takes time comparable to solver itself. To reach best performance, the user must prepare interleaved format explicitly.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>algo</code>	<code>algo = 0</code> : cuThomas (unstable algorithm); <code>algo = 1</code> : LU with pivoting (stable algorithm); <code>algo = 2</code> : QR (stable algorithm)
<code>m</code>	the size of the linear system.
<code>dl</code>	<type> dense array containing the lower diagonal of the tri-diagonal linear system. The first element of each lower diagonal must be zero.
<code>d</code>	<type> dense array containing the main diagonal of the tri-diagonal linear system.
<code>du</code>	<type> dense array containing the upper diagonal of the tri-diagonal linear system. The last element of each upper diagonal must be zero.
<code>x</code>	<type> dense right-hand-side array of dimensions (<code>batchCount</code> , <code>n</code>).
<code>pBuffer</code>	buffer allocated by the user, the size is return by <code>gtsvInterleavedBatch_bufferSizeExt</code> .

Output

<code>x</code>	<type> dense solution array of dimensions (<code>batchCount</code> , <code>n</code>).
----------------	---

See [`cusparseStatus_t`](#) for the description of the return status

12.5. Batched Pentadiagonal Solve

Different algorithms for batched pentadiagonal solve are discussed in this section.

12.5.1. `cusparse<t>gpsvInterleavedBatch()`

```
cusparseStatus_t
cusparseSgpsvInterleavedBatch_bufferSizeExt(cusparseHandle_t handle,
                                             int             algo,
                                             int             m,
```

```

        const float*   ds,
        const float*   dl,
        const float*   d,
        const float*   du,
        const float*   dw,
        const float*   x,
        int             batchCount,
        size_t*
    pBufferSizeInBytes)

cusparseStatus_t
cusparseDgpsvInterleavedBatch_bufferSizeExt(cusparseHandle_t handle,
        int             algo,
        int             m,
        const double*   ds,
        const double*   dl,
        const double*   d,
        const double*   du,
        const double*   dw,
        const double*   x,
        int             batchCount,
        size_t*
    pBufferSizeInBytes)

cusparseStatus_t
cusparseCgpsvInterleavedBatch_bufferSizeExt(cusparseHandle_t handle,
        int             algo,
        int             m,
        const cuComplex* ds,
        const cuComplex* dl,
        const cuComplex* d,
        const cuComplex* du,
        const cuComplex* dw,
        const cuComplex* x,
        int             batchCount,
        size_t*
    pBufferSizeInBytes)

cusparseStatus_t
cusparseZgpsvInterleavedBatch_bufferSizeExt(cusparseHandle_t handle,
        int             algo,
        int             m,
        const cuDoubleComplex* ds,
        const cuDoubleComplex* dl,
        const cuDoubleComplex* d,
        const cuDoubleComplex* du,
        const cuDoubleComplex* dw,
        const cuDoubleComplex* x,
        int
    batchCount,
        size_t*
    pBufferSizeInBytes)

```

```

cusparseStatus_t
cusparseSgpsvInterleavedBatch(cusparseHandle_t handle,
        int             algo,
        int             m,
        float*          ds,
        float*          dl,
        float*          d,

```

```

        float*      du,
        float*      dw,
        float*      x,
        int         batchCount,
        void*       pBuffer)

cusparseStatus_t
cusparseDgpsvInterleavedBatch(cusparseHandle_t handle,
        int         algo,
        int         m,
        double*     ds,
        double*     dl,
        double*     d,
        double*     du,
        double*     dw,
        double*     x,
        int         batchCount,
        void*       pBuffer)

cusparseStatus_t
cusparseCgpsvInterleavedBatch(cusparseHandle_t handle,
        int         algo,
        int         m,
        cuComplex*  ds,
        cuComplex*  dl,
        cuComplex*  d,
        cuComplex*  du,
        cuComplex*  dw,
        cuComplex*  x,
        int         batchCount,
        void*       pBuffer)

cusparseStatus_t
cusparseZgpsvInterleavedBatch(cusparseHandle_t handle,
        int         algo,
        int         m,
        cuDoubleComplex* ds,
        cuDoubleComplex* dl,
        cuDoubleComplex* d,
        cuDoubleComplex* du,
        cuDoubleComplex* dw,
        cuDoubleComplex* x,
        int         batchCount,
        void*       pBuffer)

```

This function computes the solution of multiple penta-diagonal linear systems for $i=0, \dots, \text{batchCount}$:

$$A^{(i)} * x^{(i)} = b^{(i)}$$

The coefficient matrix A of each of these penta-diagonal linear system is defined with five vectors corresponding to its lower [ds , dl], main [d], and upper [du , dw] matrix diagonals; the right-hand sides are stored in the dense matrix B . Notice that solution x overwrites right-hand-side matrix B on exit.

Assuming A is of size m and base-1, ds , dl , d , du and dw are defined by the following formula:

$$ds(i) := A(i, i-2) \text{ for } i=1, 2, \dots, m$$

The first two elements of ds is out-of-bound ($ds(1) := A(1, -1)$, $ds(2) := A(2, 0)$), so $ds(1) = 0$ and $ds(2) = 0$.

$dl(i) := A(i, i-1)$ for $i=1, 2, \dots, m$

The first element of dl is out-of-bound ($dl(1) := A(1, 0)$), so $dl(1) = 0$.

$d(i) = A(i, i)$ for $i=1, 2, \dots, m$

$du(i) = A(i, i+1)$ for $i=1, 2, \dots, m$

The last element of du is out-of-bound ($du(m) := A(m, m+1)$), so $du(m) = 0$.

$dw(i) = A(i, i+2)$ for $i=1, 2, \dots, m$

The last two elements of dw is out-of-bound ($dw(m-1) := A(m-1, m+1)$, $dw(m) := A(m, m+2)$), so $dw(m-1) = 0$ and $dw(m) = 0$.

The data layout is the same as `gtsvStridedBatch`.

The routine is numerically stable because it uses QR to solve the linear system.

This function requires a buffer size returned by `gpsvInterleavedBatch_bufferSizeExt()`.

The address of `pBuffer` must be multiple of 128 bytes. If it is not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The function supports the following properties if `pBuffer != NULL`

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>algo</code>	only support <code>algo = 0</code> (QR)
<code>m</code>	the size of the linear system.
<code>ds</code>	<type> dense array containing the lower diagonal (distance 2 to the diagonal) of the penta-diagonal linear system. The first two elements must be zero.
<code>dl</code>	<type> dense array containing the lower diagonal (distance 1 to the diagonal) of the penta-diagonal linear system. The first element must be zero.
<code>d</code>	<type> dense array containing the main diagonal of the penta-diagonal linear system.
<code>du</code>	<type> dense array containing the upper diagonal (distance 1 to the diagonal) of the penta-diagonal linear system. The last element must be zero.
<code>dw</code>	<type> dense array containing the upper diagonal (distance 2 to the diagonal) of the penta-diagonal linear system. The last two elements must be zero.

<code>x</code>	<type> dense right-hand-side array of dimensions (batchCount, n).
<code>pBuffer</code>	buffer allocated by the user, the size is return by <code>gpsvInterleavedBatch_bufferSizeExt</code> .

Output

<code>x</code>	<type> dense solution array of dimensions (batchCount, n).
----------------	--

See [`cusparseStatus_t`](#) for the description of the return status

Please visit [cuSPARSE Library Samples - `cusparseSgpsvInterleavedBatch`](#) for a code example.

Chapter 13. cuSPARSE Reorderings Reference

This chapter describes the reordering routines used to manipulate sparse matrices.

13.1. `cusparse<t>csrcolor()`

```
cusparseStatus_t
cusparseScsrColor(cusparseHandle_t      handle,
                  int                    m,
                  int                    nnz,
                  const cusparseMatDescr_t descrA,
                  const float*           csrValA,
                  const int*             csrRowPtrA,
                  const int*             csrColIndA,
                  const float*           fractionToColor,
                  int*                   ncolors,
                  int*                   coloring,
                  int*                   reordering,
                  cusparseColorInfo_t    info)

cusparseStatus_t
cusparseDcsrColor(cusparseHandle_t      handle,
                  int                    m,
                  int                    nnz,
                  const cusparseMatDescr_t descrA,
                  const double*          csrValA,
                  const int*             csrRowPtrA,
                  const int*             csrColIndA,
                  const double*          fractionToColor,
                  int*                   ncolors,
                  int*                   coloring,
                  int*                   reordering,
                  cusparseColorInfo_t    info)

cusparseStatus_t
cusparseCcsrColor(cusparseHandle_t      handle,
                  int                    m,
                  int                    nnz,
                  const cusparseMatDescr_t descrA,
                  const cuComplex*       csrValA,
                  const int*             csrRowPtrA,
                  const int*             csrColIndA,
```

```

        const cuComplex*      fractionToColor,
        int*                  ncolors,
        int*                  coloring,
        int*                  reordering,
        cusparseColorInfo_t  info)

cusparseStatus_t
cusparseZcsrcoLor (cusparseHandle_t      handle,
                  int                    m,
                  int                    nnz,
                  const cusparseMatDescr_t descrA,
                  const cuDoubleComplex* csrValA,
                  const int*             csrRowPtrA,
                  const int*             csrColIndA,
                  const cuDoubleComplex* fractionToColor,
                  int*                   ncolors,
                  int*                   coloring,
                  int*                   reordering,
                  cusparseColorInfo_t    info)

```

This function performs the coloring of the adjacency graph associated with the matrix A stored in CSR format. The coloring is an assignment of colors (integer numbers) to nodes, such that neighboring nodes have distinct colors. An approximate coloring algorithm is used in this routine, and is stopped when a certain percentage of nodes has been colored. The rest of the nodes are assigned distinct colors (an increasing sequence of integers numbers, starting from the last integer used previously). The last two auxiliary routines can be used to extract the resulting number of colors, their assignment and the associated reordering. The reordering is such that nodes that have been assigned the same color are reordered to be next to each other.

The matrix A passed to this routine, must be stored as a general matrix and have a symmetric sparsity pattern. If the matrix is nonsymmetric the user should pass $A+A^T$ as a parameter to this routine.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
m	number of rows of matrix A.
nnz	number of nonzero elements of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
csrValA	<type> array of nnz (= <code>csrRowPtrA(m) - csrRowPtrA(0)</code>) nonzero elements of matrix A.

<code>csrRowPtrA</code>	integer array of $m+1$ elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of $nnz (= csrRowPtrA(m) - csrRowPtrA(0))$ column indices of the nonzero elements of matrix A .
<code>fractionToColor</code>	fraction of nodes to be colored, which should be in the interval $[0.0, 1.0]$, for example 0.8 implies that 80 percent of nodes will be colored.
<code>info</code>	structure with information to be passed to the coloring.

Output

<code>ncolors</code>	The number of distinct colors used (at most the size of the matrix, but likely much smaller).
<code>coloring</code>	The resulting coloring permutation
<code>reordering</code>	The resulting reordering permutation (untouched if NULL)

See [`cusparseStatus_t`](#) for the description of the return status

Chapter 14. cuSPARSE Format Conversion Reference

This chapter describes the conversion routines between different sparse and dense storage formats.

`coosort`, `csrsort`, `cscsort`, and `csru2csr` are sorting routines without `malloc` inside, the following table estimates the buffer size

routine	buffer size	maximum problem size if buffer is limited by 2GB
<code>coosort</code>	> 16*n bytes	125M
<code>csrsort</code> or <code>cscsort</code>	> 20*n bytes	100M
<code>csru2csr</code>	'd' > 28*n bytes ; 'z' > 36*n bytes	71M for 'd' and 55M for 'z'

14.1. `cusparse<t>bsr2csr()`

```
cusparseStatus_t
cusparseSbsr2csr(cusparseHandle_t      handle,
                 cusparseDirection_t   dir,
                 int                    mb,
                 int                    nb,
                 const cusparseMatDescr_t descrA,
                 const float*           bsrValA,
                 const int*             bsrRowPtrA,
                 const int*             bsrColIndA,
                 int                    blockDim,
                 const cusparseMatDescr_t descrC,
                 float*                 csrValC,
                 int*                   csrRowPtrC,
                 int*                   csrColIndC)

cusparseStatus_t
cusparseDbsr2csr(cusparseHandle_t      handle,
                 cusparseDirection_t   dir,
                 int                    mb,
                 int                    nb,
                 const cusparseMatDescr_t descrA,
                 const double*          bsrValA,
```

```

        const int*          bsrRowPtrA,
        const int*          bsrColIndA,
        int                 blockDim,
        const cusparseMatDescr_t descrC,
        double*             csrValC,
        int*                csrRowPtrC,
        int*                csrColIndC)

cusparseStatus_t
cusparseCbsr2csr(cusparseHandle_t handle,
                 cusparseDirection_t dir,
                 int mb,
                 int nb,
                 const cusparseMatDescr_t descrA,
                 const cuComplex* bsrValA,
                 const int* bsrRowPtrA,
                 const int* bsrColIndA,
                 int blockDim,
                 const cusparseMatDescr_t descrC,
                 cuComplex* csrValC,
                 int* csrRowPtrC,
                 int* csrColIndC)

cusparseStatus_t
cusparseZbsr2csr(cusparseHandle_t handle,
                 cusparseDirection_t dir,
                 int mb,
                 int nb,
                 const cusparseMatDescr_t descrA,
                 const cuDoubleComplex* bsrValA,
                 const int* bsrRowPtrA,
                 const int* bsrColIndA,
                 int blockDim,
                 const cusparseMatDescr_t descrC,
                 cuDoubleComplex* csrValC,
                 int* csrRowPtrC,
                 int* csrColIndC)

```

This function converts a sparse matrix in BSR format that is defined by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA`) into a sparse matrix in CSR format that is defined by arrays `csrValC`, `csrRowPtrC`, and `csrColIndC`.

Let $m (=mb * blockDim)$ be the number of rows of A and $n (=nb * blockDim)$ be number of columns of A , then A and C are $m * n$ sparse matrices. The BSR format of A contains $nnzb (=bsrRowPtrA[mb] - bsrRowPtrA[0])$ nonzero blocks, whereas the sparse matrix A contains $nnz (=nnzb * blockDim * blockDim)$ elements. The user must allocate enough space for arrays `csrRowPtrC`, `csrColIndC`, and `csrValC`. The requirements are as follows:

`csrRowPtrC` of $m+1$ elements

`csrValC` of nnz elements

`csrColIndC` of nnz elements

The general procedure is as follows:

```

// Given BSR format (bsrRowPtrA, bsrColIndA, bsrValA) and
// blocks of BSR format are stored in column-major order.
cusparseDirection_t dir = CUSPARSE_DIRECTION_COLUMN;
int m = mb * blockDim;
int nnzb = bsrRowPtrA[mb] - bsrRowPtrA[0]; // number of blocks

```

```

int nnz = nnzb * blockDim * blockDim; // number of elements
cudaMalloc((void**)&csrRowPtrC, sizeof(int) * (m+1));
cudaMalloc((void**)&csrColIndC, sizeof(int) * nnz);
cudaMalloc((void**)&csrValC, sizeof(float) * nnz);
cusparsesbsr2csr(handle, dir, mb, nb,
    descrA,
    bsrValA, bsrRowPtrA, bsrColIndA,
    blockDim,
    descrC,
    csrValC, csrRowPtrC, csrColIndC);

```

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if `blockDim != 1` or the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if `blockDim != 1` or the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dir</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>mb</code>	number of block rows of sparse matrix A.
<code>nb</code>	number of block columns of sparse matrix A.
<code>descrA</code>	the descriptor of matrix A.
<code>bsrValA</code>	<type> array of <code>nnzb*blockDim*blockDim</code> nonzero elements of matrix A.
<code>bsrRowPtrA</code>	integer array of <code>mb+1</code> elements that contains the start of every block row and the end of the last block row plus one of matrix A.
<code>bsrColIndA</code>	integer array of <code>nnzb</code> column indices of the nonzero blocks of matrix A.
<code>blockDim</code>	block dimension of sparse matrix A.
<code>descrC</code>	the descriptor of matrix c.

Output

<code>csrValC</code>	<type> array of <code>nnz (=csrRowPtrC[m] - csrRowPtrC[0])</code> nonzero elements of matrix c.
<code>csrRowPtrC</code>	integer array of <code>m+1</code> elements that contains the start of every row and the end of the last row plus one of matrix c.
<code>csrColIndC</code>	integer array of <code>nnz</code> column indices of the nonzero elements of matrix c.

See [cusparsesbsr2csr](#) for the description of the return status

14.2. `cusparse<t>gebsr2gebsc()`

```

cusparseStatus_t
cusparseSgebsr2gebsc_bufferSize(cusparseHandle_t handle,
                                int mb,
                                int nb,
                                int nnzb,
                                const float* bsrVal,
                                const int* bsrRowPtr,
                                const int* bsrColInd,
                                int rowBlockDim,
                                int colBlockDim,
                                int* pBufferSize)

cusparseStatus_t
cusparseDgebsr2gebsc_bufferSize(cusparseHandle_t handle,
                                int mb,
                                int nb,
                                int nnzb,
                                const double* bsrVal,
                                const int* bsrRowPtr,
                                const int* bsrColInd,
                                int rowBlockDim,
                                int colBlockDim,
                                int* pBufferSize)

cusparseStatus_t
cusparseCgebsr2gebsc_bufferSize(cusparseHandle_t handle,
                                int mb,
                                int nb,
                                int nnzb,
                                const cuComplex* bsrVal,
                                const int* bsrRowPtr,
                                const int* bsrColInd,
                                int rowBlockDim,
                                int colBlockDim,
                                int* pBufferSize)

cusparseStatus_t
cusparseZgebsr2gebsc_bufferSize(cusparseHandle_t handle,
                                int mb,
                                int nb,
                                int nnzb,
                                const cuDoubleComplex* bsrVal,
                                const int* bsrRowPtr,
                                const int* bsrColInd,
                                int rowBlockDim,
                                int colBlockDim,
                                int* pBufferSize)

cusparseStatus_t
cusparseSgebsr2gebsc(cusparseHandle_t handle,
                      int mb,
                      int nb,
                      int nnzb,

```

```

        const float*      bsrVal,
        const int*       bsrRowPtr,
        const int*       bsrColInd,
        int              rowBlockDim,
        int              colBlockDim,
        float*          bscVal,
        int*            bscRowInd,
        int*            bscColPtr,
        cusparseAction_t copyValues,
        cusparseIndexBase_t baseIdx,
        void*           pBuffer)

cusparseStatus_t
cusparseDgebsr2gebsc (cusparseHandle_t handle,
                    int mb,
                    int nb,
                    int nnzb,
                    const double* bsrVal,
                    const int* bsrRowPtr,
                    const int* bsrColInd,
                    int rowBlockDim,
                    int colBlockDim,
                    double* bscVal,
                    int* bscRowInd,
                    int* bscColPtr,
                    cusparseAction_t copyValues,
                    cusparseIndexBase_t baseIdx,
                    void* pBuffer)

cusparseStatus_t
cusparseCgebsr2gebsc (cusparseHandle_t handle,
                    int mb,
                    int nb,
                    int nnzb,
                    const cuComplex* bsrVal,
                    const int* bsrRowPtr,
                    const int* bsrColInd,
                    int rowBlockDim,
                    int colBlockDim,
                    cuComplex* bscVal,
                    int* bscRowInd,
                    int* bscColPtr,
                    cusparseAction_t copyValues,
                    cusparseIndexBase_t baseIdx,
                    void* pBuffer)

cusparseStatus_t
cusparseZgebsr2gebsc (cusparseHandle_t handle,
                    int mb,
                    int nb,
                    int nnzb,
                    const cuDoubleComplex* bsrVal,
                    const int* bsrRowPtr,
                    const int* bsrColInd,
                    int rowBlockDim,
                    int colBlockDim,
                    cuDoubleComplex* bscVal,
                    int* bscRowInd,
                    int* bscColPtr,
                    cusparseAction_t copyValues,
                    cusparseIndexBase_t baseIdx,
                    void* pBuffer)

```


bscRowInd	integer array of nnzb row indices of the non-zero blocks of matrix A.
bscColPtr	integer array of nb+1 elements that contains the start of every block column and the end of the last block column plus one.

See [cusparseStatus_t](#) for the description of the return status

14.3. cusparse<t>gebsr2gebsr()

```

cusparseStatus_t
cusparseSgebsr2gebsr_bufferSize(cusparseHandle_t      handle,
                                cusparseDirection_t   dir,
                                int                    mb,
                                int                    nb,
                                int                    nnzb,
                                const cusparseMatDescr_t descrA,
                                const float*           bsrValA,
                                const int*            bsrRowPtrA,
                                const int*            bsrColIndA,
                                int                    rowBlockDimA,
                                int                    colBlockDimA,
                                int                    rowBlockDimC,
                                int                    colBlockDimC,
                                int*                  pBufferSize)

cusparseStatus_t
cusparseDgebsr2gebsr_bufferSize(cusparseHandle_t      handle,
                                cusparseDirection_t   dir,
                                int                    mb,
                                int                    nb,
                                int                    nnzb,
                                const cusparseMatDescr_t descrA,
                                const double*          bsrValA,
                                const int*            bsrRowPtrA,
                                const int*            bsrColIndA,
                                int                    rowBlockDimA,
                                int                    colBlockDimA,
                                int                    rowBlockDimC,
                                int                    colBlockDimC,
                                int*                  pBufferSize)

cusparseStatus_t
cusparseCgebsr2gebsr_bufferSize(cusparseHandle_t      handle,
                                cusparseDirection_t   dir,
                                int                    mb,
                                int                    nb,
                                int                    nnzb,
                                const cusparseMatDescr_t descrA,
                                const cuComplex*       bsrValA,
                                const int*            bsrRowPtrA,
                                const int*            bsrColIndA,
                                int                    rowBlockDimA,
                                int                    colBlockDimA,
                                int                    rowBlockDimC,
                                int                    colBlockDimC,
                                int*                  pBufferSize)

```

```

                                int*                                pBufferSize)
cusparseStatus_t
cusparseZgebsr2gebsr_bufferSize(cusparseHandle_t                handle,
                                cusparseDirection_t            dir,
                                int                             mb,
                                int                             nb,
                                int                             nnzb,
                                const cusparseMatDescr_t        descrA,
                                const cuDoubleComplex*         bsrValA,
                                const int*                     bsrRowPtrA,
                                const int*                     bsrColIndA,
                                int                             rowBlockDimA,
                                int                             colBlockDimA,
                                int                             rowBlockDimC,
                                int                             colBlockDimC,
                                int*                             pBufferSize)

```

```

cusparseStatus_t
cusparseXgebsr2gebsrNnz(cusparseHandle_t                handle,
                        cusparseDirection_t            dir,
                        int                             mb,
                        int                             nb,
                        int                             nnzb,
                        const cusparseMatDescr_t        descrA,
                        const int*                     bsrRowPtrA,
                        const int*                     bsrColIndA,
                        int                             rowBlockDimA,
                        int                             colBlockDimA,
                        const cusparseMatDescr_t        descrC,
                        int*                             bsrRowPtrC,
                        int                             rowBlockDimC,
                        int                             colBlockDimC,
                        int*                             nnzTotalDevHostPtr,
                        void*                             pBuffer)

```

```

cusparseStatus_t
cusparseSgebsr2gebsr(cusparseHandle_t                handle,
                     cusparseDirection_t            dir,
                     int                             mb,
                     int                             nb,
                     int                             nnzb,
                     const cusparseMatDescr_t        descrA,
                     const float*                   bsrValA,
                     const int*                     bsrRowPtrA,
                     const int*                     bsrColIndA,
                     int                             rowBlockDimA,
                     int                             colBlockDimA,
                     const cusparseMatDescr_t        descrC,
                     float*                           bsrValC,
                     int*                             bsrRowPtrC,
                     int*                             bsrColIndC,
                     int                             rowBlockDimC,
                     int                             colBlockDimC,
                     void*                             pBuffer)

```

```

cusparseStatus_t
cusparseDgebsr2gebsr(cusparseHandle_t                handle,
                     cusparseDirection_t            dir,
                     int                             mb,

```

```

        int                nb,
        int                nnzb,
        const cusparseMatDescr_t descrA,
        const double*      bsrValA,
        const int*         bsrRowPtrA,
        const int*         bsrColIndA,
        int                rowBlockDimA,
        int                colBlockDimA,
        const cusparseMatDescr_t descrC,
        double*            bsrValC,
        int*               bsrRowPtrC,
        int*               bsrColIndC,
        int                rowBlockDimC,
        int                colBlockDimC,
        void*              pBuffer)

cusparseStatus_t
cusparseCgebsr2gebsr(cusparseHandle_t      handle,
                    cusparseDirection_t    dir,
                    int                    mb,
                    int                    nb,
                    int                    nnzb,
                    const cusparseMatDescr_t descrA,
                    const cuComplex*      bsrValA,
                    const int*            bsrRowPtrA,
                    const int*            bsrColIndA,
                    int                    rowBlockDimA,
                    int                    colBlockDimA,
                    const cusparseMatDescr_t descrC,
                    cuComplex*            bsrValC,
                    int*                  bsrRowPtrC,
                    int*                  bsrColIndC,
                    int                    rowBlockDimC,
                    int                    colBlockDimC,
                    void*                  pBuffer)

cusparseStatus_t
cusparseZgebsr2gebsr(cusparseHandle_t      handle,
                    cusparseDirection_t    dir,
                    int                    mb,
                    int                    nb,
                    int                    nnzb,
                    const cusparseMatDescr_t descrA,
                    const cuDoubleComplex* bsrValA,
                    const int*            bsrRowPtrA,
                    const int*            bsrColIndA,
                    int                    rowBlockDimA,
                    int                    colBlockDimA,
                    const cusparseMatDescr_t descrC,
                    cuDoubleComplex*      bsrValC,
                    int*                  bsrRowPtrC,
                    int*                  bsrColIndC,
                    int                    rowBlockDimC,
                    int                    colBlockDimC,
                    void*                  pBuffer)

```

This function converts a sparse matrix in general BSR format that is defined by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA` into a sparse matrix in another general BSR format that is defined by arrays `bsrValC`, `bsrRowPtrC`, and `bsrColIndC`.

If `rowBlockDimA=1` and `colBlockDimA=1`, `cusparse[S|D|C|Z]gebsr2gebsr()` is the same as `cusparse[S|D|C|Z]csr2gebsr()`.

If `rowBlockDimC=1` and `colBlockDimC=1`, `cusparse[S|D|C|Z]gebsr2gebsr()` is the same as `cusparse[S|D|C|Z]gebsr2csr()`.

A is an $m \times n$ sparse matrix where $m (=mb \times \text{rowBlockDim})$ is the number of rows of A, and $n (=nb \times \text{colBlockDim})$ is the number of columns of A. The general BSR format of A contains $\text{nnzb} (= \text{bsrRowPtrA}[mb] - \text{bsrRowPtrA}[0])$ nonzero blocks. The matrix c is also general BSR format with a different block size, $\text{rowBlockDimC} \times \text{colBlockDimC}$. If m is not a multiple of `rowBlockDimC`, or n is not a multiple of `colBlockDimC`, zeros are filled in. The number of block rows of C is $m_c (= (m + \text{rowBlockDimC} - 1) / \text{rowBlockDimC})$. The number of block rows of c is $n_c (= (n + \text{colBlockDimC} - 1) / \text{colBlockDimC})$. The number of nonzero blocks of c is `nnzc`.

The implementation adopts a two-step approach to do the conversion. First, the user allocates `bsrRowPtrC` of $m_c + 1$ elements and uses function `cusparseXgebsr2gebsrNnz()` to determine the number of nonzero block columns per block row of matrix c. Second, the user gathers `nnzc` (number of non-zero block columns of matrix c) from either $(\text{nnzc} = * \text{nnzTotalDevHostPtr})$ or $(\text{nnzc} = \text{bsrRowPtrC}[m_c] - \text{bsrRowPtrC}[0])$ and allocates `bsrValC` of $\text{nnzc} \times \text{rowBlockDimC} \times \text{colBlockDimC}$ elements and `bsrColIndC` of `nnzc` integers. Finally the function `cusparse[S|D|C|Z]gebsr2gebsr()` is called to complete the conversion.

The user must call `gebsr2gebsr_bufferSize()` to know the size of the buffer required by `gebsr2gebsr()`, allocate the buffer, and pass the buffer pointer to `gebsr2gebsr()`.

The general procedure is as follows:

```
// Given general BSR format (bsrRowPtrA, bsrColIndA, bsrValA) and
// blocks of BSR format are stored in column-major order.
cusparseDirection_t dir = CUSPARSE_DIRECTION_COLUMN;
int base, nnzc;
int m = mb*rowBlockDimA;
int n = nb*colBlockDimA;
int mc = (m+rowBlockDimC-1)/rowBlockDimC;
int nc = (n+colBlockDimC-1)/colBlockDimC;
int bufferSize;
void *pBuffer;
cusparseSgebsr2gebsr_bufferSize(handle, dir, mb, nb, nnzb,
    descrA, bsrValA, bsrRowPtrA, bsrColIndA,
    rowBlockDimA, colBlockDimA,
    rowBlockDimC, colBlockDimC,
    &bufferSize);
cudaMalloc((void**)&pBuffer, bufferSize);
cudaMalloc((void**)&bsrRowPtrC, sizeof(int)*(mc+1));
// nnzTotalDevHostPtr points to host memory
int *nnzTotalDevHostPtr = &nnzc;
cusparseXgebsr2gebsrNnz(handle, dir, mb, nb, nnzb,
    descrA, bsrRowPtrA, bsrColIndA,
    rowBlockDimA, colBlockDimA,
    descrC, bsrRowPtrC,
    rowBlockDimC, colBlockDimC,
    nnzTotalDevHostPtr,
    pBuffer);
if (NULL != nnzTotalDevHostPtr){
    nnzc = *nnzTotalDevHostPtr;
}else{
    cudaMemcpy(&nnzc, bsrRowPtrC+mc, sizeof(int), cudaMemcpyDeviceToHost);
    cudaMemcpy(&base, bsrRowPtrC, sizeof(int), cudaMemcpyDeviceToHost);
    nnzc -= base;
}
cudaMalloc((void**)&bsrColIndC, sizeof(int)*nnzc);
```

```

cudaMalloc((void**)&bsrValC, sizeof(float)*(rowBlockDimC*colBlockDimC)*nnzb);
cusparseSgebsr2gebsr(handle, dir, mb, nb, nnzb,
    descrA, bsrValA, bsrRowPtrA, bsrColIndA,
    rowBlockDimA, colBlockDimA,
    descrC, bsrValC, bsrRowPtrC, bsrColIndC,
    rowBlockDimC, colBlockDimC,
    pBuffer);

```

- ▶ The routines require no extra storage if `pBuffer != NULL`
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routines do **not** support CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
dir	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
mb	number of block rows of sparse matrix A.
nb	number of block columns of sparse matrix A.
nnzb	number of nonzero blocks of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
bsrValA	<type> array of <code>nnzb*rowBlockDimA*colBlockDimA</code> non-zero elements of matrix A.
bsrRowPtrA	integer array of <code>mb+1</code> elements that contains the start of every block row and the end of the last block row plus one of matrix A.
bsrColIndA	integer array of <code>nnzb</code> column indices of the non-zero blocks of matrix A.
rowBlockDimA	number of rows within a block of A.
colBlockDimA	number of columns within a block of A.
descrC	the descriptor of matrix C. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
rowBlockDimC	number of rows within a block of C.
colBlockDimC	number of columns within a block of C.
pBufferSize	host pointer containing number of bytes of the buffer used in <code>gebsr2gebsr()</code> .
pBuffer	buffer allocated by the user; the size is return by <code>gebsr2gebsr_bufferSize()</code> .

Output

bsrValC	<type> array of nnzc*rowBlockDimC*colBlockDimC non-zero elements of matrix c.
bsrRowPtrC	integer array of mc+1 elements that contains the start of every block row and the end of the last block row plus one of matrix c.
bsrColIndC	integer array of nnzc block column indices of the nonzero blocks of matrix c.
nnzTotalDevHostPtr	total number of nonzero blocks of c. *nnzTotalDevHostPtr is the same as bsrRowPtrC[mc]-bsrRowPtrC[0].

See [cusparseStatus_t](#) for the description of the return status

14.4. `cusparse<t>gebsr2csr()`

```

cusparseStatus_t
cusparseSgebsr2csr(cusparseHandle_t      handle,
                  cusparseDirection_t    dir,
                  int                    mb,
                  int                    nb,
                  const cusparseMatDescr_t descrA,
                  const float*           bsrValA,
                  const int*             bsrRowPtrA,
                  const int*             bsrColIndA,
                  int                    rowBlockDim,
                  int                    colBlockDim,
                  const cusparseMatDescr_t descrC,
                  float*                 csrValC,
                  int*                   csrRowPtrC,
                  int*                   csrColIndC)

cusparseStatus_t
cusparseDgebsr2csr(cusparseHandle_t      handle,
                  cusparseDirection_t    dir,
                  int                    mb,
                  int                    nb,
                  const cusparseMatDescr_t descrA,
                  const double*          bsrValA,
                  const int*             bsrRowPtrA,
                  const int*             bsrColIndA,
                  int                    rowBlockDim,
                  int                    colBlockDim,
                  const cusparseMatDescr_t descrC,
                  double*                csrValC,
                  int*                   csrRowPtrC,
                  int*                   csrColIndC)

cusparseStatus_t
cusparseCgebsr2csr(cusparseHandle_t      handle,
                  cusparseDirection_t    dir,
                  int                    mb,

```

```

        int
        const cusparseMatDescr_t descrA,
        const cuComplex*
        const int*
        const int*
        int
        int
        const cusparseMatDescr_t descrC,
        cuComplex*
        int*
        int*
        nb,
        descrA,
        bsrValA,
        bsrRowPtrA,
        bsrColIndA,
        rowBlockDim,
        colBlockDim,
        descrC,
        csrValC,
        csrRowPtrC,
        csrColIndC)

cusparseStatus_t
cusparseZgebsr2csr(cusparseHandle_t handle,
                  cusparseDirection_t dir,
                  int mb,
                  int nb,
                  const cusparseMatDescr_t descrA,
                  const cuDoubleComplex* bsrValA,
                  const int* bsrRowPtrA,
                  const int* bsrColIndA,
                  int rowBlockDim,
                  int colBlockDim,
                  const cusparseMatDescr_t descrC,
                  cuDoubleComplex* csrValC,
                  int* csrRowPtrC,
                  int* csrColIndC)

```

This function converts a sparse matrix in general BSR format that is defined by the three arrays `bsrValA`, `bsrRowPtrA`, and `bsrColIndA` into a sparse matrix in CSR format that is defined by arrays `csrValC`, `csrRowPtrC`, and `csrColIndC`.

Let $m (=mb * rowBlockDim)$ be number of rows of A and $n (=nb * colBlockDim)$ be number of columns of A , then A and C are $m * n$ sparse matrices. The general BSR format of A contains $nnzb (=bsrRowPtrA[mb] - bsrRowPtrA[0])$ non-zero blocks, whereas sparse matrix A contains $nnz (=nnzb * rowBlockDim * colBlockDim)$ elements. The user must allocate enough space for arrays `csrRowPtrC`, `csrColIndC`, and `csrValC`. The requirements are as follows:

`csrRowPtrC` of $m+1$ elements

`csrValC` of nnz elements

`csrColIndC` of nnz elements

The general procedure is as follows:

```

// Given general BSR format (bsrRowPtrA, bsrColIndA, bsrValA) and
// blocks of BSR format are stored in column-major order.
cusparseDirection_t dir = CUSPARSE_DIRECTION_COLUMN;
int m = mb * rowBlockDim;
int n = nb * colBlockDim;
int nnzb = bsrRowPtrA[mb] - bsrRowPtrA[0]; // number of blocks
int nnz = nnzb * rowBlockDim * colBlockDim; // number of elements
cudaMalloc((void**)&csrRowPtrC, sizeof(int) * (m+1));
cudaMalloc((void**)&csrColIndC, sizeof(int) * nnz);
cudaMalloc((void**)&csrValC, sizeof(float) * nnz);
cusparseSgebsr2csr(handle, dir, mb, nb,
                  descrA,
                  bsrValA, bsrRowPtrA, bsrColIndA,
                  rowBlockDim, colBlockDim,
                  descrC,
                  csrValC, csrRowPtrC, csrColIndC);

```

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
dir	storage format of blocks, either CUSPARSE_DIRECTION_ROW or CUSPARSE_DIRECTION_COLUMN.
mb	number of block rows of sparse matrix A.
nb	number of block columns of sparse matrix A.
descrA	the descriptor of matrix A. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL. Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
bsrValA	<type> array of nnzb*rowBlockDim*colBlockDim non-zero elements of matrix A.
bsrRowPtrA	integer array of mb+1 elements that contains the start of every block row and the end of the last block row plus one of matrix A.
bsrColIndA	integer array of nnzb column indices of the non-zero blocks of matrix A.
rowBlockDim	number of rows within a block of A.
colBlockDim	number of columns within a block of A.
descrC	the descriptor of matrix C. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL. Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.

Output

csrValC	<type> array of nnz non-zero elements of matrix C.
csrRowPtrC	integer array of m+1 elements that contains the start of every row and the end of the last row plus one of matrix C.
csrColIndC	integer array of nnz column indices of the non-zero elements of matrix C.

See [cusparsesStatus_t](#) for the description of the return status

14.5. `cusparse<t>csr2gebsr()`

```
cusparseStatus_t
cusparseScsr2gebsr_bufferSize(cusparseHandle_t      handle,
                              cusparseDirection_t   dir,
                              int                   m,
                              int                   n,
                              const cusparseMatDescr_t descrA,
                              const float*          csrValA,
                              const int*            csrRowPtrA,
                              const int*            csrColIndA,
                              int                   rowBlockDim,
                              int                   colBlockDim,
                              int*                  pBufferSize)
```

```
cusparseStatus_t
cusparseDcsr2gebsr_bufferSize(cusparseHandle_t      handle,
                              cusparseDirection_t   dir,
                              int                   m,
                              int                   n,
                              const cusparseMatDescr_t descrA,
                              const double*          csrValA,
                              const int*            csrRowPtrA,
                              const int*            csrColIndA,
                              int                   rowBlockDim,
                              int                   colBlockDim,
                              int*                  pBufferSize)
```

```
cusparseStatus_t
cusparseCcsr2gebsr_bufferSize(cusparseHandle_t      handle,
                              cusparseDirection_t   dir,
                              int                   m,
                              int                   n,
                              const cusparseMatDescr_t descrA,
                              const cuComplex*       csrValA,
                              const int*            csrRowPtrA,
                              const int*            csrColIndA,
                              int                   rowBlockDim,
                              int                   colBlockDim,
                              int*                  pBufferSize)
```

```
cusparseStatus_t
cusparseZcsr2gebsr_bufferSize(cusparseHandle_t      handle,
                              cusparseDirection_t   dir,
                              int                   m,
                              int                   n,
                              const cusparseMatDescr_t descrA,
                              const cuDoubleComplex* csrValA,
                              const int*            csrRowPtrA,
                              const int*            csrColIndA,
                              int                   rowBlockDim,
                              int                   colBlockDim,
                              int*                  pBufferSize)
```

```
cusparseStatus_t
```

```

cusparseXcsr2gebsrNnz(cusparseHandle_t      handle,
                     cusparseDirection_t    dir,
                     int                    m,
                     int                    n,
                     const cusparseMatDescr_t descrA,
                     const int*             csrRowPtrA,
                     const int*             csrColIndA,
                     const cusparseMatDescr_t descrC,
                     int*                   bsrRowPtrC,
                     int                    rowBlockDim,
                     int                    colBlockDim,
                     int*                   nnzTotalDevHostPtr,
                     void*                   pBuffer)

```

```

cusparseStatus_t
cusparseScsr2gebsr(cusparseHandle_t      handle,
                   cusparseDirection_t    dir,
                   int                    m,
                   int                    n,
                   const cusparseMatDescr_t descrA,
                   const float*            csrValA,
                   const int*              csrRowPtrA,
                   const int*              csrColIndA,
                   const cusparseMatDescr_t descrC,
                   float*                   bsrValC,
                   int*                     bsrRowPtrC,
                   int*                     bsrColIndC,
                   int                      rowBlockDim,
                   int                      colBlockDim,
                   void*                     pBuffer)

```

```

cusparseStatus_t
cusparseDcsr2gebsr(cusparseHandle_t      handle,
                   cusparseDirection_t    dir,
                   int                    m,
                   int                    n,
                   const cusparseMatDescr_t descrA,
                   const double*           csrValA,
                   const int*              csrRowPtrA,
                   const int*              csrColIndA,
                   const cusparseMatDescr_t descrC,
                   double*                  bsrValC,
                   int*                     bsrRowPtrC,
                   int*                     bsrColIndC,
                   int                      rowBlockDim,
                   int                      colBlockDim,
                   void*                     pBuffer)

```

```

cusparseStatus_t
cusparseCcsr2gebsr(cusparseHandle_t      handle,
                   cusparseDirection_t    dir,
                   int                    m,
                   int                    n,
                   const cusparseMatDescr_t descrA,
                   const cuComplex*        csrValA,
                   const int*              csrRowPtrA,
                   const int*              csrColIndA,
                   const cusparseMatDescr_t descrC,
                   cuComplex*              bsrValC,
                   int*                     bsrRowPtrC,
                   int*                     bsrColIndC,

```

```

        int                rowBlockDim,
        int                colBlockDim,
        void*              pBuffer)

cusparseStatus_t
cusparseZcsr2gebsr(cusparseHandle_t      handle,
                  cusparseDirection_t    dir,
                  int                    m,
                  int                    n,
                  const cusparseMatDescr_t descrA,
                  const cuDoubleComplex* csrValA,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  const cusparseMatDescr_t descrC,
                  cuDoubleComplex*        bsrValC,
                  int*                    bsrRowPtrC,
                  int*                    bsrColIndC,
                  int                    rowBlockDim,
                  int                    colBlockDim,
                  void*                    pBuffer)

```

This function converts a sparse matrix A in CSR format (that is defined by arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`) into a sparse matrix C in general BSR format (that is defined by the three arrays `bsrValC`, `bsrRowPtrC`, and `bsrColIndC`).

The matrix A is a $m \times n$ sparse matrix and matrix C is a $(mb \times \text{rowBlockDim}) \times (nb \times \text{colBlockDim})$ sparse matrix, where $mb = (m + \text{rowBlockDim} - 1) / \text{rowBlockDim}$ is the number of block rows of C, and $nb = (n + \text{colBlockDim} - 1) / \text{colBlockDim}$ is the number of block columns of C.

The block of C is of size $\text{rowBlockDim} \times \text{colBlockDim}$. If m is not multiple of rowBlockDim or n is not multiple of colBlockDim , zeros are filled in.

The implementation adopts a two-step approach to do the conversion. First, the user allocates `bsrRowPtrC` of $mb+1$ elements and uses function `cusparseXcsr2gebsrNnz()` to determine the number of nonzero block columns per block row. Second, the user gathers `nnzb` (number of nonzero block columns of matrix C) from either ($\text{nnzb} = * \text{nnzTotalDevHostPtr}$) or ($\text{nnzb} = \text{bsrRowPtrC}[mb] - \text{bsrRowPtrC}[0]$) and allocates `bsrValC` of $\text{nnzb} \times \text{rowBlockDim} \times \text{colBlockDim}$ elements and `bsrColIndC` of nnzb integers. Finally function `cusparse[S|D|C|Z]csr2gebsr()` is called to complete the conversion.

The user must obtain the size of the buffer required by `csr2gebsr()` by calling `csr2gebsr_bufferSize()`, allocate the buffer, and pass the buffer pointer to `csr2gebsr()`.

The general procedure is as follows:

```

// Given CSR format (csrRowPtrA, csrColIndA, csrValA) and
// blocks of BSR format are stored in column-major order.
cusparseDirection_t dir = CUSPARSE_DIRECTION_COLUMN;
int base, nnzb;
int mb = (m + rowBlockDim-1)/rowBlockDim;
int nb = (n + colBlockDim-1)/colBlockDim;
int bufferSize;
void *pBuffer;
cusparseScsr2gebsr_bufferSize(handle, dir, m, n,
                              descrA, csrValA, csrRowPtrA, csrColIndA,
                              rowBlockDim, colBlockDim,
                              &bufferSize);
cudaMalloc((void**)&pBuffer, bufferSize);
cudaMalloc((void**)&bsrRowPtrC, sizeof(int) * (mb+1));
// nnzTotalDevHostPtr points to host memory

```

```

int *nnzTotalDevHostPtr = &nnzb;
cusparsExcsr2gebsrNnz(handle, dir, m, n,
    descrA, csrRowPtrA, csrColIndA,
    descrC, bsrRowPtrC, rowBlockDim, colBlockDim,
    nnzTotalDevHostPtr,
    pBuffer);
if (NULL != nnzTotalDevHostPtr){
    nnzb = *nnzTotalDevHostPtr;
}else{
    cudaMemcpy(&nnzb, bsrRowPtrC+mb, sizeof(int), cudaMemcpyDeviceToHost);
    cudaMemcpy(&base, bsrRowPtrC, sizeof(int), cudaMemcpyDeviceToHost);
    nnzb -= base;
}
cudaMalloc((void**)&bsrColIndC, sizeof(int)*nnzb);
cudaMalloc((void**)&bsrValC, sizeof(float)*(rowBlockDim*colBlockDim)*nnzb);
cusparsScsr2gebsr(handle, dir, m, n,
    descrA,
    csrValA, csrRowPtrA, csrColIndA,
    descrC,
    bsrValC, bsrRowPtrC, bsrColIndC,
    rowBlockDim, colBlockDim,
    pBuffer);

```

The routine `cusparsExcsr2gebsrNnz()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

The routine `cuspars<t>csr2gebsr()` has the following properties:

- ▶ The routine requires no extra storage if `pBuffer != NULL`
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dir</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>m</code>	number of rows of sparse matrix A.
<code>n</code>	number of columns of sparse matrix A.
<code>descrA</code>	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>csrValA</code>	<type> array of <code>nnz</code> nonzero elements of matrix A.

<code>csrRowPtrA</code>	integer array of $m+1$ elements that contains the start of every row and the end of the last row plus one of matrix A.
<code>csrColIndA</code>	integer array of nnz column indices of the nonzero elements of matrix A.
<code>descrC</code>	the descriptor of matrix C. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>rowBlockDim</code>	number of rows within a block of C.
<code>colBlockDim</code>	number of columns within a block of C.
<code>pBuffer</code>	buffer allocated by the user, the size is return by <code>csr2gebsr_bufferSize()</code> .

Output

<code>bsrValC</code>	<type> array of $nnzb * rowBlockDim * colBlockDim$ nonzero elements of matrix C.
<code>bsrRowPtrC</code>	integer array of $mb+1$ elements that contains the start of every block row and the end of the last block row plus one of matrix C.
<code>bsrColIndC</code>	integer array of $nnzb$ column indices of the nonzero blocks of matrix C.
<code>nnzTotalDevHostPtr</code>	total number of nonzero blocks of matrix C. Pointer <code>nnzTotalDevHostPtr</code> can point to a device memory or host memory.

See [cusparseStatus_t](#) for the description of the return status

14.6. `cusparse<t>coo2csr()`

```
cusparseStatus_t
cusparseXcoo2csr(cusparseHandle_t handle,
                 const int* cooRowInd,
                 int nnz,
                 int m,
                 int* csrRowPtr,
                 cusparseIndexBase_t idxBase)
```

This function converts the array containing the uncompressed row indices (corresponding to COO format) into an array of compressed row pointers (corresponding to CSR format).

It can also be used to convert the array containing the uncompressed column indices (corresponding to COO format) into an array of column pointers (corresponding to CSC format).

- The routine requires no extra storage

- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
cooRowInd	integer array of nnz uncompressed row indices.
nnz	number of non-zeros of the sparse matrix (that is also the length of array cooRowInd).
m	number of rows of matrix A.
idxBase	CUSPARSE_INDEX_BASE_ZERO or CUSPARSE_INDEX_BASE_ONE.

Output

csrRowPtr	integer array of m+1 elements that contains the start of every row and the end of the last row plus one.
-----------	--

See [cusparseStatus_t](#) for the description of the return status

14.7. `cusparse<t>csc2dense()` [DEPRECATED]

[DEPRECATED] use [cusparseSparse2Dense\(\)](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseScsc2dense(cusparseHandle_t      handle,
                  int                    m,
                  int                    n,
                  const cusparseMatDescr_t descrA,
                  const float*           cscValA,
                  const int*             cscRowIndA,
                  const int*             cscColPtrA,
                  float*                 A,
                  int                    lda)
```

```
cusparseStatus_t
cusparseDcsc2dense(cusparseHandle_t      handle,
                  int                    m,
                  int                    n,
                  const cusparseMatDescr_t descrA,
                  const double*          cscValA,
                  const int*             cscRowIndA,
                  const int*             cscColPtrA,
                  double*                 A,
                  int                    lda)
```

```
cusparseStatus_t
cusparseCcsc2dense(cusparseHandle_t      handle,
```

```

        int m,
        int n,
        const cusparseMatDescr_t descrA,
        const cuComplex* cscValA,
        const int* cscRowIndA,
        const int* cscColPtrA,
        cuComplex* A,
        int lda)

cusparseStatus_t
cusparseZcsc2dense(cusparseHandle_t handle,
        int m,
        int n,
        const cusparseMatDescr_t descrA,
        const cuDoubleComplex* cscValA,
        const int* cscRowIndA,
        const int* cscColPtrA,
        cuDoubleComplex* A,
        int lda)

```

This function converts the sparse matrix in CSC format that is defined by the three arrays `cscValA`, `cscColPtrA`, and `cscRowIndA` into the matrix `A` in dense format. The dense matrix `A` is filled in with the values of the sparse matrix and with zeros elsewhere.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
m	number of rows of matrix A.
n	number of columns of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
cscValA	<type> array of <code>nnz (= cscColPtrA(m) - cscColPtrA(0))</code> nonzero elements of matrix A.
cscRowIndA	integer array of <code>nnz (= cscColPtrA(m) - cscColPtrA(0))</code> row indices of the nonzero elements of matrix A.
cscColPtrA	integer array of <code>n+1</code> elements that contains the start of every row and the end of the last column plus one.
lda	leading dimension of dense array A.

Output

A	array of dimensions <code>(lda, n)</code> that is filled in with the values of the sparse matrix.
---	---

See [cusparsesStatus_t](#) for the description of the return status

14.8. `cusparses<t>csr2bsr()`

```

cusparsesStatus_t
cusparsesXcsr2bsrNnz(cusparsesHandle_t      handle,
                    cusparsesDirection_t   dir,
                    int                     m,
                    int                     n,
                    const cusparsesMatDescr_t descrA,
                    const int*              csrRowPtrA,
                    const int*              csrColIndA,
                    int                     blockDim,
                    const cusparsesMatDescr_t descrC,
                    int*                    bsrRowPtrC,
                    int*                    nnzTotalDevHostPtr)

```

```

cusparsesStatus_t
cusparsesScsr2bsr(cusparsesHandle_t      handle,
                  cusparsesDirection_t   dir,
                  int                     m,
                  int                     n,
                  const cusparsesMatDescr_t descrA,
                  const float*            csrValA,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  int                     blockDim,
                  const cusparsesMatDescr_t descrC,
                  float*                  bsrValC,
                  int*                    bsrRowPtrC,
                  int*                    bsrColIndC)

```

```

cusparsesStatus_t
cusparsesDcsr2bsr(cusparsesHandle_t      handle,
                  cusparsesDirection_t   dir,
                  int                     m,
                  int                     n,
                  const cusparsesMatDescr_t descrA,
                  const double*           csrValA,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  int                     blockDim,
                  const cusparsesMatDescr_t descrC,
                  double*                 bsrValC,
                  int*                    bsrRowPtrC,
                  int*                    bsrColIndC)

```

```

cusparsesStatus_t
cusparsesCcsr2bsr(cusparsesHandle_t      handle,
                  cusparsesDirection_t   dir,
                  int                     m,
                  int                     n,
                  const cusparsesMatDescr_t descrA,
                  const cuComplex*        csrValA,
                  const int*              csrRowPtrA,
                  const int*              csrColIndA,
                  int                     blockDim,

```

```

        const cusparseMatDescr_t descrC,
        cuComplex*                bsrValC,
        int*                       bsrRowPtrC,
        int*                       bsrColIndC)

cusparseStatus_t
cusparseZcsr2bsr(cusparseHandle_t    handle,
                 cusparseDirection_t dir,
                 int                  m,
                 int                  n,
                 const cusparseMatDescr_t descrA,
                 const cuDoubleComplex* csrValA,
                 const int*             csrRowPtrA,
                 const int*             csrColIndA,
                 int                    blockDim,
                 const cusparseMatDescr_t descrC,
                 cuDoubleComplex*      bsrValC,
                 int*                   bsrRowPtrC,
                 int*                   bsrColIndC)

```

This function converts a sparse matrix in CSR format that is defined by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA` into a sparse matrix in BSR format that is defined by arrays `bsrValC`, `bsrRowPtrC`, and `bsrColIndC`.

A is an $m \times n$ sparse matrix. The BSR format of A has `mb` block rows, `nb` block columns, and `nnzb` nonzero blocks, where $mb = (m + \text{blockDim} - 1) / \text{blockDim}$ and $nb = (n + \text{blockDim} - 1) / \text{blockDim}$.

If `m` or `n` is not multiple of `blockDim`, zeros are filled in.

The conversion in cuSPARSE entails a two-step approach. First, the user allocates `bsrRowPtrC` of `mb+1` elements and uses function `cusparseXcsr2bsrNnz()` to determine the number of nonzero block columns per block row. Second, the user gathers `nnzb` (number of non-zero block columns of matrix c) from either ($nnzb = *nnzTotalDevHostPtr$) or ($nnzb = \text{bsrRowPtrC}[mb] - \text{bsrRowPtrC}[0]$) and allocates `bsrValC` of `nnzb * blockDim * blockDim` elements and `bsrColIndC` of `nnzb` elements. Finally function `cusparse[S|D|C|Z]csr2bsr90` is called to complete the conversion.

The general procedure is as follows:

```

// Given CSR format (csrRowPtrA, csrColIndA, csrValA) and
// blocks of BSR format are stored in column-major order.
cusparseDirection_t dir = CUSPARSE_DIRECTION_COLUMN;
int base, nnzb;
int mb = (m + blockDim-1)/blockDim;
cudaMalloc((void**)&bsrRowPtrC, sizeof(int) * (mb+1));
// nnzTotalDevHostPtr points to host memory
int *nnzTotalDevHostPtr = &nnzb;
cusparseXcsr2bsrNnz(handle, dir, m, n,
                   descrA, csrRowPtrA, csrColIndA,
                   blockDim,
                   descrC, bsrRowPtrC,
                   nnzTotalDevHostPtr);
if (NULL != nnzTotalDevHostPtr){
    nnzb = *nnzTotalDevHostPtr;
}else{
    cudaMemcpy(&nnzb, bsrRowPtrC+mb, sizeof(int), cudaMemcpyDeviceToHost);
    cudaMemcpy(&base, bsrRowPtrC, sizeof(int), cudaMemcpyDeviceToHost);
    nnzb -= base;
}
cudaMalloc((void**)&bsrColIndC, sizeof(int) * nnzb);

```

```

cudaMalloc((void**) &bsrValC, sizeof(float) * (blockDim * blockDim) * nnzb);
cusparsescsr2bsr(handle, dir, m, n,
                 descrA,
                 csrValA, csrRowPtrA, csrColIndA,
                 blockDim,
                 descrC,
                 bsrValC, bsrRowPtrC, bsrColIndC);

```

The routine `cusparsescsr2bsr()` has the following properties:

- ▶ This function requires temporary extra storage that is allocated internally if `blockDim > 16`
- ▶ The routine support asynchronous execution if `blockDim != 1` and the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if `blockDim != 1` or the Stream Ordered Memory Allocator is available

The routine `cusparsescsr2bsrNnz()` has the following properties:

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine support asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>dir</code>	storage format of blocks, either <code>CUSPARSE_DIRECTION_ROW</code> or <code>CUSPARSE_DIRECTION_COLUMN</code> .
<code>m</code>	number of rows of sparse matrix A.
<code>n</code>	number of columns of sparse matrix A.
<code>descrA</code>	the descriptor of matrix A.
<code>csrValA</code>	<type> array of <code>nnz (=csrRowPtrA[m] - csrRowPtrA[0])</code> non-zero elements of matrix A.
<code>csrRowPtrA</code>	integer array of <code>m+1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	integer array of <code>nnz</code> column indices of the non-zero elements of matrix A.
<code>blockDim</code>	block dimension of sparse matrix A. The range of <code>blockDim</code> is between 1 and <code>min(m, n)</code> .
<code>descrC</code>	the descriptor of matrix C.

Output

<code>bsrValC</code>	<type> array of <code>nnzb * blockDim * blockDim</code> nonzero elements of matrix C.
----------------------	---

<code>bsrRowPtrC</code>	integer array of <code>mb+1</code> elements that contains the start of every block row and the end of the last block row plus one of matrix <code>C</code> .
<code>bsrColIndC</code>	integer array of <code>nnzb</code> column indices of the non-zero blocks of matrix <code>C</code> .
<code>nnzTotalDevHostPtr</code>	total number of nonzero elements in device or host memory. It is equal to <code>(bsrRowPtrC[mb] - bsrRowPtrC[0])</code> .

See [`cusparseStatus_t`](#) for the description of the return status

14.9. `cusparse<t>csr2coo()`

```
cusparseStatus_t
cusparseXcsr2coo(cusparseHandle_t handle,
                 const int*      csrRowPtr,
                 int              nnz,
                 int              m,
                 int*             cooRowInd,
                 cusparseIndexBase_t idxBase)
```

This function converts the array containing the compressed row pointers (corresponding to CSR format) into an array of uncompressed row indices (corresponding to COO format).

It can also be used to convert the array containing the compressed column indices (corresponding to CSC format) into an array of uncompressed column indices (corresponding to COO format).

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>csrRowPtr</code>	integer array of <code>m+1</code> elements that contains the start of every row and the end of the last row plus one.
<code>nnz</code>	number of nonzeros of the sparse matrix (that is also the length of array <code>cooRowInd</code>).
<code>m</code>	number of rows of matrix <code>A</code> .
<code>idxBase</code>	<code>CUSPARSE_INDEX_BASE_ZERO</code> or <code>CUSPARSE_INDEX_BASE_ONE</code> .

Output

<code>cooRowInd</code>	integer array of <code>nnz</code> uncompressed row indices.
------------------------	---

See [cusparseStatus_t](#) for the description of the return status

14.10. cusparseCsr2cscEx2()

```
cusparseStatus_t
cusparseCsr2cscEx2_bufferSize(cusparseHandle_t    handle,
                              int                m,
                              int                n,
                              int                nnz,
                              const void*       csrVal,
                              const int*        csrRowPtr,
                              const int*        csrColInd,
                              void*            cscVal,
                              int*             cscColPtr,
                              int*             cscRowInd,
                              cudaDataType     valType,
                              cusparseAction_t  copyValues,
                              cusparseIndexBase_t idxBase,
                              cusparseCsr2CscAlg_t alg,
                              size_t*          bufferSize)
```

```
cusparseStatus_t
cusparseCsr2cscEx2(cusparseHandle_t    handle,
                  int                m,
                  int                n,
                  int                nnz,
                  const void*       csrVal,
                  const int*        csrRowPtr,
                  const int*        csrColInd,
                  void*            cscVal,
                  int*             cscColPtr,
                  int*             cscRowInd,
                  cudaDataType     valType,
                  cusparseAction_t  copyValues,
                  cusparseIndexBase_t idxBase,
                  cusparseCsr2CscAlg_t alg,
                  void*            buffer)
```

This function converts a sparse matrix in CSR format (that is defined by the three arrays `csrVal`, `csrRowPtr`, and `csrColInd`) into a sparse matrix in CSC format (that is defined by arrays `cscVal`, `cscRowInd`, and `cscColPtr`). The resulting matrix can also be seen as the transpose of the original sparse matrix. Notice that this routine can also be used to convert a matrix in CSC format into a matrix in CSR format.

For alg `CUSPARSE_CSR2CSC_ALG1`: it requires extra storage proportional to the number of nonzero values `nnz`. It provides in output always the same matrix.

For alg `CUSPARSE_CSR2CSC_ALG2`: it requires extra storage proportional to the number of rows `m`. It does not ensure always the same ordering of CSC column indices and values. Also, it provides better performance than `CUSPARSE_CSR2CSC_ALG1` for regular matrices.

It is executed asynchronously with respect to the host, and it may return control to the application on the host before the result is ready.

The function `cusparseCsr2cscEx2_bufferSize()` returns the size of the workspace needed by `cusparseCsr2cscEx2()`. User needs to allocate a buffer of this size and give that buffer to `cusparseCsr2cscEx2()` as an argument.

If `nnz == 0`, then `csrColInd`, `csrVal`, `cscVal`, and `cscRowInd` could have `NULL` value. In this case, `cscColPtr` is set to `idxBase` for all values.

If `m == 0` or `n == 0`, the pointers are not checked and the routine returns `CUSPARSE_STATUS_SUCCESS`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine does **not** support CUDA graph capture

Input

<code>handle</code>	handle to the cuSPARSE library context
<code>m</code>	number of rows of the CSR input matrix; number of columns of the CSC output matrix
<code>n</code>	number of columns of the CSR input matrix; number of rows of the CSC output matrix
<code>nnz</code>	number of nonzero elements of the CSR and CSC matrices
<code>csrVal</code>	value array of size <code>nnz</code> of the CSR matrix; of same type as <code>valType</code>
<code>csrRowPtr</code>	integer array of size <code>m + 1</code> that contains the CSR row offsets
<code>csrColInd</code>	integer array of size <code>nnz</code> that contains the CSR column indices
<code>cscVal</code>	value array of size <code>nnz</code> of the CSC matrix; of same type as <code>valType</code>
<code>cscColPtr</code>	integer array of size <code>n + 1</code> that contains the CSC column offsets
<code>cscRowInd</code>	integer array of size <code>nnz</code> that contains the CSC row indices
<code>valType</code>	value type for both CSR and CSC matrices
<code>copyValues</code>	<code>CUSPARSE_ACTION_SYMBOLIC</code> or <code>CUSPARSE_ACTION_NUMERIC</code>
<code>idxBase</code>	Index base <code>CUSPARSE_INDEX_BASE_ZERO</code> or <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>alg</code>	algorithm implementation. see <code>cusparseCsr2CscAlg_t</code> for possible values.
<code>bufferSize</code>	number of bytes of workspace needed by <code>cusparseCsr2cscEx2()</code>
<code>buffer</code>	pointer to workspace buffer

See [cusparseStatus_t](#) for the description of the return status

14.11. `cusparse<t>csr2dense()` [DEPRECATED]

[DEPRECATED] use `cusparseSparse2Dense()` instead. *The routine will be removed in the next major release*

```

cusparseStatus_t
cusparseScsr2dense(cusparseHandle_t      handle,
                  int                    m,
                  int                    n,
                  const cusparseMatDescr_t descrA,
                  const float*           csrValA,
                  const int*             csrRowPtrA,
                  const int*             csrColIndA,
                  float*                 A,
                  int                    lda)

cusparseStatus_t
cusparseDcsr2dense(cusparseHandle_t      handle,
                  int                    m,
                  int                    n,
                  const cusparseMatDescr_t descrA,
                  const double*          csrValA,
                  const int*             csrRowPtrA,
                  const int*             csrColIndA,
                  double*                A,
                  int                    lda)

cusparseStatus_t
cusparseCcsr2dense(cusparseHandle_t      handle,
                  int                    m,
                  int                    n,
                  const cusparseMatDescr_t descrA,
                  const cuComplex*       csrValA,
                  const int*             csrRowPtrA,
                  const int*             csrColIndA,
                  cuComplex*            A,
                  int                    lda)

cusparseStatus_t
cusparseZcsr2dense(cusparseHandle_t      handle,
                  int                    m,
                  int                    n,
                  const cusparseMatDescr_t descrA,
                  const cuDoubleComplex* csrValA,
                  const int*             csrRowPtrA,
                  const int*             csrColIndA,
                  cuDoubleComplex*      A,
                  int                    lda)

```

This function converts the sparse matrix in CSR format (that is defined by the three arrays `csrValA`, `csrRowPtrA`, and `csrColIndA`) into the matrix `A` in dense format. The dense matrix `A` is filled in with the values of the sparse matrix and with zeros elsewhere.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

handle	handle to the cuSPARSE library context.
m	number of rows of matrix <i>A</i> .
n	number of columns of matrix <i>A</i> .
descrA	the descriptor of matrix <i>A</i> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
csrValA	<type> array of nnz (= <code>csrRowPtrA(m) - csrRowPtrA(0)</code>) nonzero elements of matrix <i>A</i> .
csrRowPtrA	integer array of m+1 elements that contains the start of every row and the end of the last row plus one.
csrColIndA	integer array of nnz (= <code>csrRowPtrA(m) - csrRowPtrA(0)</code>) column indices of the nonzero elements of matrix <i>A</i> .
lda	leading dimension of array matrixA.

Output

A	array of dimensions (lda, n) that is filled in with the values of the sparse matrix.
---	--

See [cusparsesStatus_t](#) for the description of the return status

14.12. `cusparses<t>csr2csr_compress()`

```

cusparsesStatus_t
cusparsesScsr2csr_compress(cusparsesHandle_t      handle,
                           int                    m,
                           int                    n,
                           const cusparsesMatDescr_t descrA,
                           const float*          csrValA,
                           const int*            csrColIndA,
                           const int*            csrRowPtrA,
                           int                    nnzA,
                           const int*            nnzPerRow,
                           float*               csrValC,
                           int*                  csrColIndC,
                           int*                  csrRowPtrC,
                           float                 tol)
cusparsesStatus_t

```

```

cusparseDcsr2csr_compress(cusparseHandle_t      handle,
                        int                     m,
                        int                     n,
                        const cusparseMatDescr_t descrA,
                        const double*          csrValA,
                        const int*             csrColIndA,
                        const int*             csrRowPtrA,
                        int                     nnzA,
                        const int*             nnzPerRow,
                        double*                csrValC,
                        int*                   csrColIndC,
                        int*                   csrRowPtrC,
                        double                  tol)

cusparseStatus_t
cusparseCcsr2csr_compress(cusparseHandle_t      handle,
                        int                     m,
                        int                     n,
                        const cusparseMatDescr_t descrA,
                        const cuComplex*        csrValA,
                        const int*             csrColIndA,
                        const int*             csrRowPtrA,
                        int                     nnzA,
                        const int*             nnzPerRow,
                        cuComplex*             csrValC,
                        int*                   csrColIndC,
                        int*                   csrRowPtrC,
                        cuComplex              tol)

cusparseStatus_t
cusparseZcsr2csr_compress(cusparseHandle_t      handle,
                        int                     m,
                        int                     n,
                        const cusparseMatDescr_t descrA,
                        const cuDoubleComplex* csrValA,
                        const int*             csrColIndA,
                        const int*             csrRowPtrA,
                        int                     nnzA,
                        const int*             nnzPerRow,
                        cuDoubleComplex*       csrValC,
                        int*                   csrColIndC,
                        int*                   csrRowPtrC,
                        cuDoubleComplex         tol)

```

This function compresses the sparse matrix in CSR format into compressed CSR format. Given a sparse matrix A and a non-negative value threshold, the function returns a sparse matrix C, defined by

$$C(i,j) = A(i,j) \quad \text{if } |A(i,j)| > |\text{threshold}|$$

The implementation adopts a two-step approach to do the conversion. First, the user allocates `csrRowPtrC` of `m+1` elements and uses function `cusparse<t>nnz_compress()` to determine `nnzPerRow` (the number of nonzeros columns per row) and `nnzC` (the total number of nonzeros). Second, the user allocates `csrValC` of `nnzC` elements and `csrColIndC` of `nnzC` integers. Finally function `cusparse<t>csr2csr_compress()` is called to complete the conversion.

- This function requires temporary extra storage that is allocated internally

- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
m	number of rows of matrix A .
n	number of columns of matrix A .
descrA	the descriptor of matrix A . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
csrValA	<type> array of $nnz (= csrRowPtrA(m) - csrRowPtrA(0))$ elements of matrix A .
csrColIndA	integer array of $nnz (= csrRowPtrA(m) - csrRowPtrA(0))$ column indices of the elements of matrix A .
csrRowPtrA	integer array of $m+1$ elements that contains the start of every row and the end of the last row plus one.
nnzA	number of nonzero elements in matrix A .
nnzPerRow	this array contains the number of elements kept in the compressed matrix, by row.
tol	on input, this contains the non-negative tolerance value used for compression. Any values in matrix A less than or equal to this value will be dropped during compression.

Output

csrValC	on output, this array contains the typed values of elements kept in the compressed matrix. Size = $nnzC$.
csrColIndC	on output, this integer array contains the column indices of elements kept in the compressed matrix. Size = $nnzC$.
csrRowPtrC	on output, this integer array contains the row pointers for elements kept in the compressed matrix. Size = $m+1$

See [`cusparseStatus_t`](#) for the description of the return status

The following is a sample code to show how to use this API.

```
#include <stdio.h>
#include <sys/time.h>
#include <cusparse.h>
```

```

#define ERR_NE(X,Y) do { if ((X) != (Y)) { \
    fprintf(stderr,"Error in %s at %s:%d\n",__func__,__FILE__,__LINE__); \
    exit(-1);}} while(0)
#define CUDA_CALL(X) ERR_NE((X),cudaSuccess)
#define CUSPARSE_CALL(X) ERR_NE((X),CUSPARSE_STATUS_SUCCESS)
int main(){
    int m = 6, n = 5;
    cusparseHandle_t handle;
    CUSPARSE_CALL( cusparseCreate(&handle) );
    cusparseMatDescr_t descrX;
    CUSPARSE_CALL( cusparseCreateMatDescr(&descrX) );
    // Initialize sparse matrix
    float *X;
    CUDA_CALL( cudaMallocManaged( &X, sizeof(float) * m * n ));
    memset( X, 0, sizeof(float) * m * n );
    X[0 + 0*m] = 1.0; X[0 + 1*m] = 3.0;
    X[1 + 1*m] = -4.0; X[1 + 2*m] = 5.0;
    X[2 + 0*m] = 2.0; X[2 + 3*m] = 7.0; X[2 + 4*m] = 8.0;
    X[3 + 2*m] = 6.0; X[3 + 4*m] = 9.0;
    X[4 + 3*m] = 3.5; X[4 + 4*m] = 5.5;
    X[5 + 0*m] = 6.5; X[5 + 2*m] = -9.9;
    // Initialize total_nnz, and nnzPerRowX for cusparseSdense2csr()
    int total_nnz = 13;
    int *nnzPerRowX;
    CUDA_CALL( cudaMallocManaged( &nnzPerRowX, sizeof(int) * m ));
    nnzPerRowX[0] = 2; nnzPerRowX[1] = 2; nnzPerRowX[2] = 3;
    nnzPerRowX[3] = 2; nnzPerRowX[4] = 2; nnzPerRowX[5] = 2;

    float *csrValX;
    int *csrRowPtrX;
    int *csrColIndX;
    CUDA_CALL( cudaMallocManaged( &csrValX, sizeof(float) * total_nnz ));
    CUDA_CALL( cudaMallocManaged( &csrRowPtrX, sizeof(int) * (m+1) ));
    CUDA_CALL( cudaMallocManaged( &csrColIndX, sizeof(int) * total_nnz ));

```

Before calling this API, call two APIs to prepare the input.

```

/** Call cusparseSdense2csr to generate CSR format as the inputs for
cusparseScsr2csr_compress */
CUSPARSE_CALL( cusparseSdense2csr( handle, m, n, descrX, X,
    m, nnzPerRowX, csrValX,
    csrRowPtrX, csrColIndX ));

float tol = 3.5;
int *nnzPerRowY;
int *testNNZTotal;
CUDA_CALL( cudaMallocManaged( &nnzPerRowY, sizeof(int) * m ));
CUDA_CALL( cudaMallocManaged( &testNNZTotal, sizeof(int) ));
memset( nnzPerRowY, 0, sizeof(int) * m );
// cusparseSnnz_compress generates nnzPerRowY and testNNZTotal
CUSPARSE_CALL( cusparseSnnz_compress( handle, m, descrX, csrValX,
    csrRowPtrX, nnzPerRowY,
    testNNZTotal, tol ));

float *csrValY;
int *csrRowPtrY;
int *csrColIndY;
CUDA_CALL( cudaMallocManaged( &csrValY, sizeof(float) * (*testNNZTotal) ));
CUDA_CALL( cudaMallocManaged( &csrRowPtrY, sizeof(int) * (m+1) ));
CUDA_CALL( cudaMallocManaged( &csrColIndY, sizeof(int) * (*testNNZTotal) ));

CUSPARSE_CALL( cusparseScsr2csr_compress( handle, m, n, descrX, csrValX,
    csrColIndX, csrRowPtrX,
    total_nnz, nnzPerRowY,

```

```

        csrValY, csrColIndY,
        csrRowPtrY, tol));

/* Expect results
nnzPerRowY:  0 2 2 2 1 2
csrValY:    -4 5 7 8 6 9 5.5 6.5 -9.9
csrColIndY:  1 2 3 4 2 4 4 0 2
csrRowPtrY:  0 0 2 4 6 7 9
*/
cudaFree(X);
cusparsityDestroy(handle);
cudaFree(nnzPerRowX);
cudaFree(csrValX);
cudaFree(csrRowPtrX);
cudaFree(csrColIndX);
cudaFree(csrValY);
cudaFree(nnzPerRowY);
cudaFree(testNNZTotal);
cudaFree(csrRowPtrY);
cudaFree(csrColIndY);
return 0;
}

```

14.13. `cusparsity<t>dense2csc()` [DEPRECATED]

[DEPRECATED] use [`cusparsityDense2Sparse\(\)`](#) instead. *The routine will be removed in the next major release*

```

cusparsityStatus_t
cusparsitySdense2csc(cusparsityHandle_t      handle,
                    int                     m,
                    int                     n,
                    const cusparsityMatDescr_t descrA,
                    const float*           A,
                    int                     lda,
                    const int*             nnzPerCol,
                    float*                 cscValA,
                    int*                   cscRowIndA,
                    int*                   cscColPtrA)

cusparsityStatus_t
cusparsityDdense2csc(cusparsityHandle_t      handle,
                    int                     m,
                    int                     n,
                    const cusparsityMatDescr_t descrA,
                    const double*           A,
                    int                     lda,
                    const int*             nnzPerCol,
                    double*                 cscValA,
                    int*                   cscRowIndA,
                    int*                   cscColPtrA)

cusparsityStatus_t
cusparsityCdense2csc(cusparsityHandle_t      handle,
                    int                     m,
                    int                     n,
                    const cusparsityMatDescr_t descrA,

```

```

        const cuComplex*      A,
        int                  lda,
        const int*           nnzPerCol,
        cuComplex*          cscValA,
        int*                 cscRowIndA,
        int*                 cscColPtrA)

cusparsesStatus_t
cusparsesZdense2csc (cusparsesHandle_t      handle,
                    int                    m,
                    int                    n,
                    const cusparsesMatDescr_t descrA,
                    const cuDoubleComplex* A,
                    int                    lda,
                    const int*             nnzPerCol,
                    cuDoubleComplex*      cscValA,
                    int*                 cscRowIndA,
                    int*                 cscColPtrA)

```

This function converts the matrix `A` in dense format into a sparse matrix in CSC format. All the parameters are assumed to have been pre-allocated by the user, and the arrays are filled in based on `nnzPerCol`, which can be precomputed with `cusparses<t>nnz()`.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows of matrix <code>A</code> .
<code>n</code>	number of columns of matrix <code>A</code> .
<code>descrA</code>	the descriptor of matrix <code>A</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>A</code>	array of dimensions <code>(lda, n)</code> .
<code>lda</code>	leading dimension of dense array <code>A</code> .
<code>nnzPerCol</code>	array of size <code>n</code> containing the number of nonzero elements per column.

Output

<code>cscValA</code>	<type> array of <code>nnz (= cscRowPtrA(m) - cscRowPtrA(0))</code> nonzero elements of matrix <code>A</code> . It is only filled in if <code>copyValues</code> is set to <code>CUSPARSE_ACTION_NUMERIC</code> .
----------------------	---

cscRowIndA	integer array of nnz (= cscRowPtrA(m) - cscRowPtrA(0)) row indices of the nonzero elements of matrix A.
cscColPtrA	integer array of n+1 elements that contains the start of every column and the end of the last column plus one.

See [cusparsesStatus_t](#) for the description of the return status

14.14. `cusparses<t>dense2csr()` [DEPRECATED]

[DEPRECATED] use [cusparsesDense2Sparse\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparsesStatus_t
cusparsesSdense2csr(cusparsesHandle_t      handle,
                   int                    m,
                   int                    n,
                   const cusparsesMatDescr_t descrA,
                   const float*           A,
                   int                    lda,
                   const int*             nnzPerRow,
                   float*                 csrValA,
                   int*                   csrRowPtrA,
                   int*                   csrColIndA)

cusparsesStatus_t
cusparsesDdense2csr(cusparsesHandle_t      handle,
                   int                    m,
                   int                    n,
                   const cusparsesMatDescr_t descrA,
                   const double*          A,
                   int                    lda,
                   const int*             nnzPerRow,
                   double*                 csrValA,
                   int*                   csrRowPtrA,
                   int*                   csrColIndA)

cusparsesStatus_t
cusparsesCdense2csr(cusparsesHandle_t      handle,
                   int                    m,
                   int                    n,
                   const cusparsesMatDescr_t descrA,
                   const cuComplex*       A,
                   int                    lda,
                   const int*             nnzPerRow,
                   cuComplex*             csrValA,
                   int*                   csrRowPtrA,
                   int*                   csrColIndA)

cusparsesStatus_t
cusparsesZdense2csr(cusparsesHandle_t      handle,
                   int                    m,

```



```

int n,
const cusparseMatDescr_t descrA,
const cuDoubleComplex* A,
int lda,
const int* nnzPerRow,
cuDoubleComplex* csrValA,
int* csrRowPtrA,
int* csrColIndA)

```

This function converts the matrix `A` in dense format into a sparse matrix in CSR format. All the parameters are assumed to have been pre-allocated by the user and the arrays are filled in based on `nnzPerRow`, which can be pre-computed with `cusparse<t>nnz()`.

This function requires no extra storage. It is executed asynchronously with respect to the host and may return control to the application on the host before the result is ready.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

<code>handle</code>	handle to the cuSPARSE library context.
<code>m</code>	number of rows of matrix <code>A</code> .
<code>n</code>	number of columns of matrix <code>A</code> .
<code>descrA</code>	the descriptor of matrix <code>A</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>A</code>	array of dimensions <code>(lda, n)</code> .
<code>lda</code>	leading dimension of dense array <code>A</code> .
<code>nnzPerRow</code>	array of size <code>n</code> containing the number of non-zero elements per row.

Output

<code>csrValA</code>	<type> array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> nonzero elements of matrix <code>A</code> .
<code>csrRowPtrA</code>	integer array of <code>m+1</code> elements that contains the start of every column and the end of the last column plus one.
<code>csrColIndA</code>	integer array of <code>nnz (= csrRowPtrA(m) - csrRowPtrA(0))</code> column indices of the non-zero elements of matrix <code>A</code> .

See [cusparseStatus_t](#) for the description of the return status

14.15. `cusparse<t>nnz()`

```

cusparseStatus_t
cusparseSnnz(cusparseHandle_t      handle,
             cusparseDirection_t   dirA,
             int                    m,
             int                    n,
             const cusparseMatDescr_t descrA,
             const float*           A,
             int                    lda,
             int*                   nnzPerRowColumn,
             int*                   nnzTotalDevHostPtr)

cusparseStatus_t
cusparseDnnz(cusparseHandle_t      handle,
             cusparseDirection_t   dirA,
             int                    m,
             int                    n,
             const cusparseMatDescr_t descrA,
             const double*          A,
             int                    lda,
             int*                   nnzPerRowColumn,
             int*                   nnzTotalDevHostPtr)

cusparseStatus_t
cusparseCnnz(cusparseHandle_t      handle,
             cusparseDirection_t   dirA,
             int                    m,
             int                    n,
             const cusparseMatDescr_t descrA,
             const cuComplex*       A,
             int                    lda,
             int*                   nnzPerRowColumn,
             int*                   nnzTotalDevHostPtr)

cusparseStatus_t
cusparseZnnz(cusparseHandle_t      handle,
             cusparseDirection_t   dirA,
             int                    m,
             int                    n,
             const cusparseMatDescr_t descrA,
             const cuDoubleComplex* A,
             int                    lda,
             int*                   nnzPerRowColumn,
             int*                   nnzTotalDevHostPtr)

```

This function computes the number of nonzero elements per row or column and the total number of nonzero elements in a dense matrix.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available

- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
dirA	direction that specifies whether to count nonzero elements by <code>CUSPARSE_DIRECTION_ROW</code> or by <code>CUSPARSE_DIRECTION_COLUMN</code> .
m	number of rows of matrix A.
n	number of columns of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
A	array of dimensions (lda, n) .
lda	leading dimension of dense array A.

Output

nnzPerRowColumn	array of size m or n containing the number of nonzero elements per row or column, respectively.
nnzTotalDevHostPtr	total number of nonzero elements in device or host memory.

See [`cusparseStatus_t`](#) for the description of the return status

14.16. `cusparseCreateIdentityPermutation()`

```
cusparseStatus_t
cusparseCreateIdentityPermutation(cusparseHandle_t handle,
                                int n,
                                int* p);
```

This function creates an identity map. The output parameter `p` represents such map by `p = 0:1:(n-1)`.

This function is typically used with `coosort`, `csrsort`, `cscsort`.

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

parameter	device or host	description
-----------	----------------	-------------

handle	host	handle to the cuSPARSE library context.
n	host	size of the map.

Output

parameter	device or host	description
p	device	integer array of dimensions n.

See [cusparseStatus_t](#) for the description of the return status

14.17. cusparseXcoosort()

```
cusparseStatus_t
cusparseXcoosort_bufferSizeExt(cusparseHandle_t handle,
                               int m,
                               int n,
                               int nnz,
                               const int* cooRows,
                               const int* cooCols,
                               size_t* pBufferSizeInBytes)
```

```
cusparseStatus_t
cusparseXcoosortByRow(cusparseHandle_t handle,
                     int m,
                     int n,
                     int nnz,
                     int* cooRows,
                     int* cooCols,
                     int* P,
                     void* pBuffer)
```

```
cusparseStatus_t
cusparseXcoosortByColumn(cusparseHandle_t handle,
                         int m,
                         int n,
                         int nnz,
                         int* cooRows,
                         int* cooCols,
                         int* P,
                         void* pBuffer);
```

This function sorts COO format. The sorting is in-place. Also the user can sort by row or sort by column.

A is an $m \times n$ sparse matrix that is defined in COO storage format by the three arrays `cooVals`, `cooRows`, and `cooCols`.

There is no assumption for the base index of the matrix. `coosort` uses stable sort on signed integer, so the value of `cooRows` or `cooCols` can be negative.

This function `coosort()` requires buffer size returned by `coosort_bufferSizeExt()`. The address of `pBuffer` must be multiple of 128 bytes. If not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The parameter `P` is both input and output. If the user wants to compute sorted `cooVal`, `P` must be set as `0:1:(nnz-1)` before `coosort()`, and after `coosort()`, new sorted value array satisfies `cooVal_sorted = cooVal(P)`.

Remark: the dimension `m` and `n` are not used. If the user does not know the value of `m` or `n`, just passes a value positive. This usually happens if the user only reads a COO array first and needs to decide the dimension `m` or `n` later.

- ▶ The routine requires no extra storage if `pBuffer != NULL`
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

parameter	device or host	description
<code>handle</code>	host	handle to the cuSPARSE library context.
<code>m</code>	host	number of rows of matrix <code>A</code> .
<code>n</code>	host	number of columns of matrix <code>A</code> .
<code>nnz</code>	host	number of nonzero elements of matrix <code>A</code> .
<code>cooRows</code>	device	integer array of <code>nnz</code> unsorted row indices of <code>A</code> .
<code>cooCols</code>	device	integer array of <code>nnz</code> unsorted column indices of <code>A</code> .
<code>P</code>	device	integer array of <code>nnz</code> unsorted map indices. To construct <code>cooVal</code> , the user has to set <code>P=0:1:(nnz-1)</code> .
<code>pBuffer</code>	device	buffer allocated by the user; the size is returned by <code>coosort_bufferSizeExt()</code> .

Output

parameter	device or host	description
<code>cooRows</code>	device	integer array of <code>nnz</code> sorted row indices of <code>A</code> .
<code>cooCols</code>	device	integer array of <code>nnz</code> sorted column indices of <code>A</code> .
<code>P</code>	device	integer array of <code>nnz</code> sorted map indices.
<code>pBufferSizeInBytes</code>	host	number of bytes of the buffer.

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseXcoosortByRow](#) for a code example.

14.18. cusparseXcsrsort()

```
cusparseStatus_t
cusparseXcsrsort_bufferSizeExt(cusparseHandle_t handle,
                               int m,
```

```

int n,
int nnz,
const int* csrRowPtr,
const int* csrColInd,
size_t* pBufferSizeInBytes)

```

```

cusparsesort(cusparsesortHandle_t handle,
             int m,
             int n,
             int nnz,
             const cusparseMatDescr_t descrA,
             const int* csrRowPtr,
             int* csrColInd,
             int* P,
             void* pBuffer)

```

This function sorts CSR format. The stable sorting is in-place.

The matrix type is regarded as `CUSPARSE_MATRIX_TYPE_GENERAL` implicitly. In other words, any symmetric property is ignored.

This function `csrsort()` requires buffer size returned by `csrsort_bufferSizeExt()`. The address of `pBuffer` must be multiple of 128 bytes. If not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The parameter `P` is both input and output. If the user wants to compute sorted `csrVal`, `P` must be set as `0:1:(nnz-1)` before `csrsort()`, and after `csrsort()`, new sorted value array satisfies `csrVal_sorted = csrVal(P)`.

The general procedure is as follows:

```

// A is a 3x3 sparse matrix, base-0
//   | 1 2 3 |
// A = | 4 5 6 |
//   | 7 8 9 |
const int m = 3;
const int n = 3;
const int nnz = 9;
csrRowPtr[m+1] = { 0, 3, 6, 9}; // on device
csrColInd[nnz] = { 2, 1, 0, 0, 2, 1, 1, 2, 0}; // on device
csrVal[nnz] = { 3, 2, 1, 4, 6, 5, 8, 9, 7}; // on device
size_t pBufferSizeInBytes = 0;
void *pBuffer = NULL;
int *P = NULL;

// step 1: allocate buffer
cusparsesort_bufferSizeExt(handle, m, n, nnz, csrRowPtr, csrColInd,
    &pBufferSizeInBytes);
cudaMalloc( &pBuffer, sizeof(char)* pBufferSizeInBytes);

// step 2: setup permutation vector P to identity
cudaMalloc( (void*)&P, sizeof(int)*nnz);
cusparsesort_createIdentityPermutation(handle, nnz, P);

// step 3: sort CSR format
cusparsesort(handle, m, n, nnz, descrA, csrRowPtr, csrColInd, P, pBuffer);

// step 4: gather sorted csrVal
cusparsesort_dgthr(handle, nnz, csrVal, csrVal_sorted, P, CUSPARSE_INDEX_BASE_ZERO);

```

- ▶ The routine requires no extra storage if `pBuffer != NULL`
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

parameter	device or host	description
<code>handle</code>	host	handle to the cuSPARSE library context.
<code>m</code>	host	number of rows of matrix A.
<code>n</code>	host	number of columns of matrix A.
<code>nnz</code>	host	number of nonzero elements of matrix A.
<code>csrRowsPtr</code>	device	integer array of <code>m+1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColInd</code>	device	integer array of <code>nnz</code> unsorted column indices of A.
<code>P</code>	device	integer array of <code>nnz</code> unsorted map indices. To construct <code>csrVal</code> , the user has to set <code>P=0:1:(nnz-1)</code> .
<code>pBuffer</code>	device	buffer allocated by the user; the size is returned by <code>csrsort_bufferSizeExt()</code> .

Output

parameter	device or host	description
<code>csrColInd</code>	device	integer array of <code>nnz</code> sorted column indices of A.
<code>P</code>	device	integer array of <code>nnz</code> sorted map indices.
<code>pBufferSizeInBytes</code>	host	number of bytes of the buffer.

See [`cusparseStatus_t`](#) for the description of the return status

14.19. `cusparseXcscsort()`

```
cusparseStatus_t
cusparseXcscsort_bufferSizeExt(cusparseHandle_t handle,
                               int m,
                               int n,
                               int nnz,
                               const int* cscColPtr,
                               const int* cscRowInd,
                               size_t* pBufferSizeInBytes)
```

```
cusparseStatus_t
cusparseXcscsort(cusparseHandle_t handle,
                 int m,
                 int n,
                 int nnz,
```

```

const cusparseMatDescr_t descrA,
const int*                cscColPtr,
int*                      cscRowInd,
int*                      P,
void*                     pBuffer)

```

This function sorts CSC format. The stable sorting is in-place.

The matrix type is regarded as `CUSPARSE_MATRIX_TYPE_GENERAL` implicitly. In other words, any symmetric property is ignored.

This function `cscsort()` requires buffer size returned by `cscsort_bufferSizeExt()`. The address of `pBuffer` must be multiple of 128 bytes. If not, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

The parameter `P` is both input and output. If the user wants to compute sorted `cscVal`, `P` must be set as `0:1:(nnz-1)` before `cscsort()`, and after `cscsort()`, new sorted value array satisfies `cscVal_sorted = cscVal(P)`.

The general procedure is as follows:

```

// A is a 3x3 sparse matrix, base-0
//   | 1 2 |
// A = | 4 0 |
//   | 0 8 |
const int m = 3;
const int n = 2;
const int nnz = 4;
cscColPtr[n+1] = { 0, 2, 4}; // on device
cscRowInd[nnz] = { 1, 0, 2, 0}; // on device
cscVal[nnz]    = { 4.0, 1.0, 8.0, 2.0 }; // on device
size_t pBufferSizeInBytes = 0;
void *pBuffer = NULL;
int *P = NULL;

// step 1: allocate buffer
cusparseXcscsort_bufferSizeExt(handle, m, n, nnz, cscColPtr, cscRowInd,
&pBufferSizeInBytes);
cudaMalloc(&pBuffer, sizeof(char)* pBufferSizeInBytes);

// step 2: setup permutation vector P to identity
cudaMalloc( (void**)&P, sizeof(int)*nnz);
cusparseCreateIdentityPermutation(handle, nnz, P);

// step 3: sort CSC format
cusparseXcscsort(handle, m, n, nnz, descrA, cscColPtr, cscRowInd, P, pBuffer);

// step 4: gather sorted cscVal
cusparseDgthr(handle, nnz, cscVal, cscVal_sorted, P, CUSPARSE_INDEX_BASE_ZERO);

```

- ▶ The routine requires no extra storage if `pBuffer != NULL`
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

parameter	device or host	description
handle	host	handle to the cuSPARSE library context.
m	host	number of rows of matrix A.
n	host	number of columns of matrix A.
nnz	host	number of nonzero elements of matrix A.
cscColPtr	device	integer array of n+1 elements that contains the start of every column and the end of the last column plus one.
cscRowInd	device	integer array of nnz unsorted row indices of A.
P	device	integer array of nnz unsorted map indices. To construct cscVal, the user has to set P=0:1:(nnz-1).
pBuffer	device	buffer allocated by the user; the size is returned by cscsort_bufferSizeExt().

Output

parameter	device or host	description
cscRowInd	device	integer array of nnz sorted row indices of A.
P	device	integer array of nnz sorted map indices.
pBufferSizeInBytes	host	number of bytes of the buffer.

See [cusparsesStatus_t](#) for the description of the return status

14.20. cusparsesXcsru2csr()

```

cusparsesStatus_t
cusparsesCreateCsru2csrInfo(csru2csrInfo_t *info);

cusparsesStatus_t
cusparsesDestroyCsru2csrInfo(csru2csrInfo_t info);

cusparsesStatus_t
cusparsesScsru2csr_bufferSizeExt(cusparsesHandle_t handle,
                                int m,
                                int n,
                                int nnz,
                                float* csrVal,
                                const int* csrRowPtr,
                                int* csrColInd,
                                csru2csrInfo_t info,
                                size_t* pBufferSizeInBytes)

cusparsesStatus_t
cusparsesDcsru2csr_bufferSizeExt(cusparsesHandle_t handle,
                                 int m,
                                 int n,
                                 int nnz,
                                 double* csrVal,
                                 const int* csrRowPtr,
                                 int* csrColInd,
                                 csru2csrInfo_t info,

```

```

                                size_t*           pBufferSizeInBytes)
cusparseStatus_t
cusparseCcsru2csr_bufferSizeExt(cusparseHandle_t handle,
                                int               m,
                                int               n,
                                int               nnz,
                                cuComplex*      csrVal,
                                const int*      csrRowPtr,
                                int*            csrColInd,
                                csru2csrInfo_t  info,
                                size_t*         pBufferSizeInBytes)

cusparseStatus_t
cusparseZcsru2csr_bufferSizeExt(cusparseHandle_t handle,
                                int               m,
                                int               n,
                                int               nnz,
                                cuDoubleComplex* csrVal,
                                const int*      csrRowPtr,
                                int*            csrColInd,
                                csru2csrInfo_t  info,
                                size_t*         pBufferSizeInBytes)

```

```

cusparseStatus_t
cusparseScsru2csr(cusparseHandle_t handle,
                  int               m,
                  int               n,
                  int               nnz,
                  const cusparseMatDescr_t descrA,
                  float*            csrVal,
                  const int*      csrRowPtr,
                  int*            csrColInd,
                  csru2csrInfo_t  info,
                  void*            pBuffer)

```

```

cusparseStatus_t
cusparseDcsru2csr(cusparseHandle_t handle,
                  int               m,
                  int               n,
                  int               nnz,
                  const cusparseMatDescr_t descrA,
                  double*          csrVal,
                  const int*      csrRowPtr,
                  int*            csrColInd,
                  csru2csrInfo_t  info,
                  void*            pBuffer)

```

```

cusparseStatus_t
cusparseCcsru2csr(cusparseHandle_t handle,
                  int               m,
                  int               n,
                  int               nnz,
                  const cusparseMatDescr_t descrA,
                  cuComplex*      csrVal,
                  const int*      csrRowPtr,
                  int*            csrColInd,
                  csru2csrInfo_t  info,
                  void*            pBuffer)

```

```

cusparsesStatus_t
cusparsesZcsru2csr (cusparsesHandle_t      handle,
                   int                    m,
                   int                    n,
                   int                    nnz,
                   const cusparsesMatDescr_t descrA,
                   cuDoubleComplex*      csrVal,
                   const int*             csrRowPtr,
                   int*                   csrColInd,
                   csru2csrInfo_t        info,
                   void*                   pBuffer)

```

```

cusparsesStatus_t
cusparsesScsr2csru (cusparsesHandle_t      handle,
                   int                    m,
                   int                    n,
                   int                    nnz,
                   const cusparsesMatDescr_t descrA,
                   float*                 csrVal,
                   const int*             csrRowPtr,
                   int*                   csrColInd,
                   csru2csrInfo_t        info,
                   void*                   pBuffer)

```

```

cusparsesStatus_t
cusparsesDcsr2csru (cusparsesHandle_t      handle,
                   int                    m,
                   int                    n,
                   int                    nnz,
                   const cusparsesMatDescr_t descrA,
                   double*                csrVal,
                   const int*             csrRowPtr,
                   int*                   csrColInd,
                   csru2csrInfo_t        info,
                   void*                   pBuffer)

```

```

cusparsesStatus_t
cusparsesCcsr2csru (cusparsesHandle_t      handle,
                   int                    m,
                   int                    n,
                   int                    nnz,
                   const cusparsesMatDescr_t descrA,
                   cuComplex*            csrVal,
                   const int*             csrRowPtr,
                   int*                   csrColInd,
                   csru2csrInfo_t        info,
                   void*                   pBuffer)

```

```

cusparsesStatus_t
cusparsesZcsr2csru (cusparsesHandle_t      handle,
                   int                    m,
                   int                    n,
                   int                    nnz,
                   const cusparsesMatDescr_t descrA,
                   cuDoubleComplex*      csrVal,
                   const int*             csrRowPtr,
                   int*                   csrColInd,
                   csru2csrInfo_t        info,
                   void*                   pBuffer)

```

This function transfers unsorted CSR format to CSR format, and vice versa. The operation is in-place.

This function is a wrapper of `csrsort` and `gather`. The usecase is the following scenario.

If the user has a matrix `A` of CSR format which is unsorted, and implements his own code (which can be CPU or GPU kernel) based on this special order (for example, diagonal first, then lower triangle, then upper triangle), and wants to convert it to CSR format when calling CUSPARSE library, and then convert it back when doing something else on his/her kernel. For example, suppose the user wants to solve a linear system $Ax=b$ by the following iterative scheme

$$x^{(k+1)} = x^{(k)} + L^{(-1)} * (b - Ax^{(k)})$$

The code heavily uses SpMv and triangular solve. Assume that the user has an in-house design of SpMV (Sparse Matrix-Vector multiplication) based on special order of `A`. However the user wants to use CUSPARSE library for triangular solver. Then the following code can work.

```

do
    step 1: compute residual vector           r = b - A x(k) by
step 2: B := sort(A), and L is lower triangular part of B
        (only sort A once and keep the permutation vector)
    step 3: solve                             z = L(-1) * ( b
step 4: add correction                       x(k+1) = x(k) + z
    step 5: A := unsort(B)
        (use permutation vector to get back the unsorted CSR)
until convergence

```

The requirements of step 2 and step 5 are

1. In-place operation.
2. The permutation vector `P` is hidden in an opaque structure.
3. No `cudaMalloc` inside the conversion routine. Instead, the user has to provide the buffer explicitly.
4. The conversion between unsorted CSR and sorted CSR may needs several times, but the function only generates the permutation vector `P` once.
5. The function is based on `csrsort`, `gather` and `scatter` operations.

The operation is called `csru2csr`, which means unsorted CSR to sorted CSR. Also we provide the inverse operation, called `csr2csru`.

In order to keep the permutation vector invisible, we need an opaque structure called `csru2csrInfo`. Then two functions (`cusparsesCreateCsru2csrInfo`, `cusparsesDestroyCsru2csrInfo`) are used to initialize and to destroy the opaque structure.

`cusparses[S|D|C|Z]csru2csr_bufferSizeExt` returns the size of the buffer. The permutation vector `P` is also allcated inside `csru2csrInfo`. The lifetime of the permutation vector is the same as the lifetime of `csru2csrInfo`.

`cusparse[S|D|C|Z]csru2csr` performs forward transformation from unsorted CSR to sorted CSR. First call uses `csrsort` to generate the permutation vector `p`, and subsequent call uses `p` to do transformation.

`cusparse[S|D|C|Z]csr2csru` performs backward transformation from sorted CSR to unsorted CSR. `p` is used to get unsorted form back.

The routine `cusparse<t>csru2csr()` has the following properties:

- ▶ The routine requires no extra storage if `pBuffer != NULL`
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

The routine `cusparse<t>csr2csru()` has the following properties if `pBuffer != NULL`:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

The following tables describe parameters of `csr2csru_bufferSizeExt` and `csr2csru`.

Input

parameter	device or host	description
<code>handle</code>	host	handle to the cuSPARSE library context.
<code>m</code>	host	number of rows of matrix <code>A</code> .
<code>n</code>	host	number of columns of matrix <code>A</code> .
<code>nnz</code>	host	number of nonzero elements of matrix <code>A</code> .
<code>descrA</code>	host	the descriptor of matrix <code>A</code> . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>csrVal</code>	device	<type> array of <code>nnz</code> unsorted nonzero elements of matrix <code>A</code> .
<code>csrRowsPtr</code>	device	integer array of <code>m+1</code> elements that contains the start of every row and the end of the last row plus one.
<code>csrColInd</code>	device	integer array of <code>nnz</code> unsorted column indices of <code>A</code> .
<code>info</code>	host	opaque structure initialized using <code>cusparseCreateCsru2csrInfo()</code> .
<code>pBuffer</code>	device	buffer allocated by the user; the size is returned by <code>csru2csr_bufferSizeExt()</code> .

Output

parameter	device or host	description
-----------	----------------	-------------

csrVal	device	<type> array of nnz sorted nonzero elements of matrix A.
csrColInd	device	integer array of nnz sorted column indices of A.
pBufferSizeInBytes	host	number of bytes of the buffer.

See [cusparseStatus_t](#) for the description of the return status

14.21. cusparseXpruneDense2csr()

```

cusparseStatus_t
cusparseHpruneDense2csr_bufferSizeExt (cusparseHandle_t      handle,
                                       int                    m,
                                       int                    n,
                                       const __half*         A,
                                       int                    lda,
                                       const __half*         threshold,
                                       const cusparseMatDescr_t descrC,
                                       const __half*         csrValC,
                                       const int*            csrRowPtrC,
                                       const int*            csrColIndC,
                                       size_t*               size_t*)
pBufferSizeInBytes)

cusparseStatus_t
cusparseSpruneDense2csr_bufferSizeExt (cusparseHandle_t      handle,
                                       int                    m,
                                       int                    n,
                                       const float*          A,
                                       int                    lda,
                                       const float*          threshold,
                                       const cusparseMatDescr_t descrC,
                                       const float*          csrValC,
                                       const int*            csrRowPtrC,
                                       const int*            csrColIndC,
                                       size_t*               size_t*)
pBufferSizeInBytes)

cusparseStatus_t
cusparseDpruneDense2csr_bufferSizeExt (cusparseHandle_t      handle,
                                       int                    m,
                                       int                    n,
                                       const double*         A,
                                       int                    lda,
                                       const double*         threshold,
                                       const cusparseMatDescr_t descrC,
                                       const double*         csrValC,
                                       const int*            csrRowPtrC,
                                       const int*            csrColIndC,
                                       size_t*               size_t*)
pBufferSizeInBytes)

cusparseStatus_t
cusparseHpruneDense2csrNnz (cusparseHandle_t      handle,
                           int                    m,

```

```

        int n,
        const __half* A,
        int lda,
        const __half* threshold,
        const cusparseMatDescr_t descrC,
        int* csrRowPtrC,
        int* nnzTotalDevHostPtr,
        void* pBuffer)

cusparseStatus_t
cusparseSpruneDense2csrNnz (cusparseHandle_t handle,
        int m,
        int n,
        const float* A,
        int lda,
        const float* threshold,
        const cusparseMatDescr_t descrC,
        int* csrRowPtrC,
        int* nnzTotalDevHostPtr,
        void* pBuffer)

cusparseStatus_t
cusparseDpruneDense2csrNnz (cusparseHandle_t handle,
        int m,
        int n,
        const double* A,
        int lda,
        const double* threshold,
        const cusparseMatDescr_t descrC,
        int* csrRowPtrC,
        int* nnzTotalDevHostPtr,
        void* pBuffer)

```

```

cusparseStatus_t
cusparseHpruneDense2csr (cusparseHandle_t handle,
        int m,
        int n,
        const __half* A,
        int lda,
        const __half* threshold,
        const cusparseMatDescr_t descrC,
        __half* csrValC,
        const int* csrRowPtrC,
        int* csrColIndC,
        void* pBuffer)

cusparseStatus_t
cusparseSpruneDense2csr (cusparseHandle_t handle,
        int m,
        int n,
        const float* A,
        int lda,
        const float* threshold,
        const cusparseMatDescr_t descrC,
        float* csrValC,
        const int* csrRowPtrC,
        int* csrColIndC,
        void* pBuffer)

cusparseStatus_t

```

```

cusparseDpruneDense2csr(cusparseHandle_t      handle,
                       int                   m,
                       int                   n,
                       const double*        A,
                       int                   lda,
                       const double*        threshold,
                       const cusparseMatDescr_t descrC,
                       double*              csrValC,
                       const int*           csrRowPtrC,
                       int*                 csrColIndC,
                       void*                pBuffer)

```

This function prunes a dense matrix to a sparse matrix with CSR format.

Given a dense matrix *A* and a non-negative value *threshold*, the function returns a sparse matrix *C*, defined by

$$C(i,j) = A(i,j) \quad \text{if } |A(i,j)| > \text{threshold}$$

The implementation adopts a two-step approach to do the conversion. First, the user allocates *csrRowPtrC* of *m*+1 elements and uses function `pruneDense2csrNnz()` to determine the number of nonzeros columns per row. Second, the user gathers *nnzC* (number of nonzeros of matrix *C*) from either (`nnzC=*nnzTotalDevHostPtr`) or (`nnzC=csrRowPtrC[m]-csrRowPtrC[0]`) and allocates *csrValC* of *nnzC* elements and *csrColIndC* of *nnzC* integers. Finally function `pruneDense2csr()` is called to complete the conversion.

The user must obtain the size of the buffer required by `pruneDense2csr()` by calling `pruneDense2csr_bufferSizeExt()`, allocate the buffer, and pass the buffer pointer to `pruneDense2csr()`.

Appendix section provides a simple example of `pruneDense2csr()`.

The routine `cusparse<t>pruneDense2csrNnz()` has the following properties:

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

The routine `cusparse<t>DpruneDense2csr()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

parameter	device or host	description
<code>handle</code>	host	handle to the cuSPARSE library context.
<code>m</code>	host	number of rows of matrix <i>A</i> .
<code>n</code>	host	number of columns of matrix <i>A</i> .

A	device	array of dimension (lda, n).
lda	device	leading dimension of A. It must be at least max(1, m).
threshold	host or device	a value to drop the entries of A. threshold can point to a device memory or host memory.
descrC	host	the descriptor of matrix c. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL, Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
pBuffer	device	buffer allocated by the user; the size is returned by pruneDense2csr_bufferSizeExt().

Output

parameter	device or host	description
nnzTotalDevHostPtr	device or host	total number of nonzero of matrix c. nnzTotalDevHostPtr can point to a device memory or host memory.
csrValC	device	<type> array of nnzC nonzero elements of matrix c.
csrRowsPtrC	device	integer array of m+1 elements that contains the start of every row and the end of the last row plus one.
csrColIndC	device	integer array of nnzC column indices of c.
pBufferSizeInBytes	host	number of bytes of the buffer.

See [cusparseStatus_t](#) for the description of the return status

14.22. cusparseXpruneCsr2csr()

```

cusparseStatus_t
cusparseHpruneCsr2csr_bufferSizeExt(cusparseHandle_t      handle,
                                     int                    m,
                                     int                    n,
                                     int                    nnzA,
                                     const cusparseMatDescr_t descrA,
                                     const __half*         csrValA,
                                     const int*            csrRowPtrA,
                                     const int*            csrColIndA,
                                     const __half*         threshold,
                                     const cusparseMatDescr_t descrC,
                                     const __half*         csrValC,
                                     const int*            csrRowPtrC,
                                     const int*            csrColIndC,
                                     size_t*               pBuffer)

cusparseStatus_t
cusparseSpruneCsr2csr_bufferSizeExt(cusparseHandle_t      handle,
                                     int                    m,
                                     int                    n,
                                     int                    nnzA,
                                     const cusparseMatDescr_t descrA,

```

```

        const float*      csrValA,
        const int*       csrRowPtrA,
        const int*       csrColIndA,
        const float*     threshold,
        const cusparseMatDescr_t descrC,
        const float*     csrValC,
        const int*       csrRowPtrC,
        const int*       csrColIndC,
        size_t*
    pBufferSizeInBytes)

cusparseStatus_t
cusparseDpruneCsr2csr_bufferSizeExt(cusparseHandle_t      handle,
        int m,
        int n,
        int nnzA,
        const cusparseMatDescr_t descrA,
        const double* csrValA,
        const int* csrRowPtrA,
        const int* csrColIndA,
        const double* threshold,
        const cusparseMatDescr_t descrC,
        const double* csrValC,
        const int* csrRowPtrC,
        const int* csrColIndC,
        size_t*
    pBufferSizeInBytes)

```

```

cusparseStatus_t
cusparseHpruneCsr2csrNnz(cusparseHandle_t      handle,
        int m,
        int n,
        int nnzA,
        const cusparseMatDescr_t descrA,
        const __half* csrValA,
        const int* csrRowPtrA,
        const int* csrColIndA,
        const __half* threshold,
        const cusparseMatDescr_t descrC,
        int* csrRowPtrC,
        int* nnzTotalDevHostPtr,
        void* pBuffer)

cusparseStatus_t
cusparseSpruneCsr2csrNnz(cusparseHandle_t      handle,
        int m,
        int n,
        int nnzA,
        const cusparseMatDescr_t descrA,
        const float* csrValA,
        const int* csrRowPtrA,
        const int* csrColIndA,
        const float* threshold,
        const cusparseMatDescr_t descrC,
        int* csrRowPtrC,
        int* nnzTotalDevHostPtr,
        void* pBuffer)

cusparseStatus_t
cusparseDpruneCsr2csrNnz(cusparseHandle_t      handle,

```

```

int m,
int n,
int nnzA,
const cusparseMatDescr_t descrA,
const double* csrValA,
const int* csrRowPtrA,
const int* csrColIndA,
const double* threshold,
const cusparseMatDescr_t descrC,
int* csrRowPtrC,
int* nnzTotalDevHostPtr,
void* pBuffer)

```

```

cusparseStatus_t
cusparseHpruneCsr2csr(cusparseHandle_t handle,
int m,
int n,
int nnzA,
const cusparseMatDescr_t descrA,
const __half* csrValA,
const int* csrRowPtrA,
const int* csrColIndA,
const __half* threshold,
const cusparseMatDescr_t descrC,
__half* csrValC,
const int* csrRowPtrC,
int* csrColIndC,
void* pBuffer)

```

```

cusparseStatus_t
cusparseSpruneCsr2csr(cusparseHandle_t handle,
int m,
int n,
int nnzA,
const cusparseMatDescr_t descrA,
const float* csrValA,
const int* csrRowPtrA,
const int* csrColIndA,
const float* threshold,
const cusparseMatDescr_t descrC,
float* csrValC,
const int* csrRowPtrC,
int* csrColIndC,
void* pBuffer)

```

```

cusparseStatus_t
cusparseDpruneCsr2csr(cusparseHandle_t handle,
int m,
int n,
int nnzA,
const cusparseMatDescr_t descrA,
const double* csrValA,
const int* csrRowPtrA,
const int* csrColIndA,
const double* threshold,
const cusparseMatDescr_t descrC,
double* csrValC,
const int* csrRowPtrC,
int* csrColIndC,
void* pBuffer)

```

This function prunes a sparse matrix to a sparse matrix with CSR format.

Given a sparse matrix A and a non-negative value `threshold`, the function returns a sparse matrix C , defined by

$$C(i,j) = A(i,j) \quad \text{if } |A(i,j)| > \text{threshold}$$

The implementation adopts a two-step approach to do the conversion. First, the user allocates `csrRowPtrC` of $m+1$ elements and uses function `pruneCsr2csrNnz()` to determine the number of nonzeros columns per row. Second, the user gathers `nnzC` (number of nonzeros of matrix C) from either `(nnzC=*nnzTotalDevHostPtr)` or `(nnzC=csrRowPtrC[m]-csrRowPtrC[0])` and allocates `csrValC` of `nnzC` elements and `csrColIndC` of `nnzC` integers. Finally function `pruneCsr2csr()` is called to complete the conversion.

The user must obtain the size of the buffer required by `pruneCsr2csr()` by calling `pruneCsr2csr_bufferSizeExt()`, allocate the buffer, and pass the buffer pointer to `pruneCsr2csr()`.

Appendix section provides a simple example of `pruneCsr2csr()`.

The routine `cusparse<t>pruneCsr2csrNnz()` has the following properties:

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

The routine `cusparse<t>pruneCsr2csr()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

parameter	device or host	description
<code>handle</code>	host	handle to the cuSPARSE library context.
<code>m</code>	host	number of rows of matrix A .
<code>n</code>	host	number of columns of matrix A .
<code>nnzA</code>	host	number of nonzeros of matrix A .
<code>descrA</code>	host	the descriptor of matrix A . The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>csrValA</code>	device	<type> array of <code>nnzA</code> nonzero elements of matrix A .
<code>csrRowsPtrA</code>	device	integer array of $m+1$ elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndA</code>	device	integer array of <code>nnzA</code> column indices of A .

threshold	host or device	a value to drop the entries of A. threshold can point to a device memory or host memory.
descrC	host	the descriptor of matrix c. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL, Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
pBuffer	device	buffer allocated by the user; the size is returned by pruneCsr2csr_bufferSizeExt().

Output

parameter	device or host	description
nnzTotalDevHostPtr	device or host	total number of nonzero of matrix c. nnzTotalDevHostPtr can point to a device memory or host memory.
csrValC	device	<type> array of nnzC nonzero elements of matrix c.
csrRowsPtrC	device	integer array of m+1 elements that contains the start of every row and the end of the last row plus one.
csrColIndC	device	integer array of nnzC column indices of c.
pBufferSizeInBytes	host	number of bytes of the buffer.

See [cusparseStatus_t](#) for the description of the return status

14.23. cusparseXpruneDense2csrPercentage()

```

cusparseStatus_t
cusparseHpruneDense2csrByPercentage_bufferSizeExt(cusparseHandle_t
  handle,
                                                    int
  m,
                                                    int
  n,
                                                    const __half*
  A,
                                                    int
  lda,
                                                    float
  percentage,
                                                    const cusparseMatDescr_t
  descrC,
                                                    const __half*
  csrValC,
                                                    const int*
  csrRowPtrC,
                                                    const int*
  csrColIndC,
                                                    pruneInfo_t
  info,
                                                    size_t*
  pBufferSizeInBytes)

```

```

cusparseStatus_t
cusparseSpruneDense2csrByPercentage_bufferSizeExt(cusparseHandle_t
  handle,
                                                    int
  m,
                                                    int
  n,
                                                    const float*
  A,
                                                    int
  lda,
                                                    float
  percentage,
                                                    const cusparseMatDescr_t
  descrC,
                                                    const float*
  csrValC,
                                                    const int*
  csrRowPtrC,
                                                    const int*
  csrColIndC,
                                                    pruneInfo_t
  info,
                                                    size_t*
  pBufferSizeInBytes)

```

```

cusparseStatus_t
cusparseDpruneDense2csrByPercentage_bufferSizeExt(cusparseHandle_t
  handle,
                                                    int
  m,
                                                    int
  n,
                                                    const double*
  A,
                                                    int
  lda,
                                                    float
  percentage,
                                                    const cusparseMatDescr_t
  descrC,
                                                    const double*
  csrValC,
                                                    const int*
  csrRowPtrC,
                                                    const int*
  csrColIndC,
                                                    pruneInfo_t
  info,
                                                    size_t*
  pBufferSizeInBytes)

```

```

cusparseStatus_t
cusparseHpruneDense2csrNnzByPercentage(cusparseHandle_t      handle,
                                        int                    m,
                                        int                    n,
                                        const __half*         A,
                                        int                    lda,
                                        float                  percentage,
                                        const cusparseMatDescr_t descrC,

```



```

                                void*                                pBuffer)
cusparseStatus_t
cusparseDpruneDense2csrByPercentage(cusparseHandle_t    handle,
                                int                    m,
                                int                    n,
                                const double*         A,
                                int                    lda,
                                float                 percentage,
                                const cusparseMatDescr_t descrC,
                                double*              csrValC,
                                const int*            csrRowPtrC,
                                int*                 csrColIndC,
                                pruneInfo_t          info,
                                void*                 pBuffer)

```

This function prunes a dense matrix to a sparse matrix by percentage.

Given a dense matrix A and a non-negative value `percentage`, the function computes sparse matrix C by the following three steps:

Step 1: sort absolute value of A in ascending order.

$$\text{key} := \text{sort}(|A|)$$

Step 2: choose threshold by the parameter `percentage`

$$\begin{aligned} \text{pos} &= \text{ceil}(m*n*(\text{percentage}/100)) - 1 \\ \text{pos} &= \min(\text{pos}, m*n-1) \\ \text{pos} &= \max(\text{pos}, 0) \\ \text{threshold} &= \text{key}[\text{pos}] \end{aligned}$$

Step 3: call `pruneDense2csr()` by with the parameter `threshold`.

The implementation adopts a two-step approach to do the conversion. First, the user allocates `csrRowPtrC` of $m+1$ elements and uses function `pruneDense2csrNnzByPercentage()` to determine the number of nonzeros columns per row. Second, the user gathers `nnzC` (number of nonzeros of matrix C) from either `(nnzC=*nnzTotalDevHostPtr)` or `(nnzC=csrRowPtrC[m]-csrRowPtrC[0])` and allocates `csrValC` of `nnzC` elements and `csrColIndC` of `nnzC` integers. Finally function `pruneDense2csrByPercentage()` is called to complete the conversion.

The user must obtain the size of the buffer required by `pruneDense2csrByPercentage()` by calling `pruneDense2csrByPercentage_bufferSizeExt()`, allocate the buffer, and pass the buffer pointer to `pruneDense2csrByPercentage()`.

Remark 1: the value of `percentage` must be not greater than 100. Otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Remark 2: the zeros of A are not ignored. All entries are sorted, including zeros. This is different from `pruneCsr2csrByPercentage()`

Appendix section provides a simple example of `pruneDense2csrNnzByPercentage()`.

The routine `cusparse<t>pruneDense2csrNnzByPercentage()` has the following properties:

- ▶ This function requires temporary extra storage that is allocated internally

- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

The routine `cusparse<t>pruneDense2csrByPercentage()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

parameter	device or host	description
<code>handle</code>	host	handle to the cuSPARSE library context.
<code>m</code>	host	number of rows of matrix A.
<code>n</code>	host	number of columns of matrix A.
<code>A</code>	device	array of dimension (lda, n) .
<code>lda</code>	device	leading dimension of A. It must be at least $\max(1, m)$.
<code>percentage</code>	host	percentage ≤ 100 and percentage ≥ 0
<code>descrC</code>	host	the descriptor of matrix C. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
<code>pBuffer</code>	device	buffer allocated by the user; the size is returned by <code>pruneDense2csrByPercentage_bufferSizeExt()</code> .

Output

parameter	device or host	description
<code>nnzTotalDevHostPtr</code>	device or host	total number of nonzero of matrix C. <code>nnzTotalDevHostPtr</code> can point to a device memory or host memory.
<code>csrValC</code>	device	<type> array of <code>nnzC</code> nonzero elements of matrix C.
<code>csrRowsPtrC</code>	device	integer array of $m+1$ elements that contains the start of every row and the end of the last row plus one.
<code>csrColIndC</code>	device	integer array of <code>nnzC</code> column indices of C.
<code>pBufferSizeInBytes</code>	host	number of bytes of the buffer.

See [cusparseStatus_t](#) for the description of the return status

14.24. `cusparseXpruneCsr2csrByPercentage()`

`cusparseStatus_t`

```

cusparseHpruneCsr2csrByPercentage_bufferSizeExt (cusparseHandle_t
handle,
                                                    int                m,
                                                    int                n,
                                                    int
nnzA,
descrA,
const cusparseMatDescr_t
csrValA,
const __half*
csrRowPtrA,
const int*
csrColIndA,
float
percentage,
const cusparseMatDescr_t
descrC,
const __half*
csrValC,
const int*
csrRowPtrC,
const int*
csrColIndC,
pruneInfo_t
info,
size_t*
pBufferSizeInBytes)
cusparseStatus_t
cusparseSpruneCsr2csrByPercentage_bufferSizeExt (cusparseHandle_t
handle,
                                                    int                m,
                                                    int                n,
                                                    int
nnzA,
descrA,
const cusparseMatDescr_t
csrValA,
const float*
csrRowPtrA,
const int*
csrColIndA,
float
percentage,
const cusparseMatDescr_t
descrC,
const float*
csrValC,
const int*
csrRowPtrC,
const int*
csrColIndC,
pruneInfo_t
info,
size_t*
pBufferSizeInBytes)
cusparseStatus_t

```

```

cusparseDpruneCsr2csrByPercentage_bufferSizeExt(cusparseHandle_t
handle,
                                                int           m,
                                                int           n,
                                                int
nnzA,
                                                const cusparseMatDescr_t
descrA,
                                                const double*
csrValA,
                                                const int*
csrRowPtrA,
                                                const int*
csrColIndA,
                                                float
percentage,
                                                const cusparseMatDescr_t
descrC,
                                                const double*
csrValC,
                                                const int*
csrRowPtrC,
                                                const int*
csrColIndC,
                                                pruneInfo_t
info,
                                                size_t*
pBufferSizeInBytes)

```

```

cusparseStatus_t
cusparseHpruneCsr2csrNnzByPercentage(cusparseHandle_t handle,
int m,
int n,
int nnzA,
const cusparseMatDescr_t descrA,
const __half* csrValA,
const int* csrRowPtrA,
const int* csrColIndA,
float percentage,
const cusparseMatDescr_t descrC,
int* csrRowPtrC,
int*
nnzTotalDevHostPtr,
pruneInfo_t info,
void* pBuffer)

```

```

cusparseStatus_t
cusparseSpruneCsr2csrNnzByPercentage(cusparseHandle_t handle,
int m,
int n,
int nnzA,
const cusparseMatDescr_t descrA,
const float* csrValA,
const int* csrRowPtrA,
const int* csrColIndA,
float percentage,
const cusparseMatDescr_t descrC,
int* csrRowPtrC,
int*
nnzTotalDevHostPtr,

```

```

                                pruneInfo_t      info,
                                void*             pBuffer)

cusparsesStatus_t
cusparsesDpruneCsr2csrNnzByPercentage (cusparsesHandle_t      handle,
                                        int                    m,
                                        int                    n,
                                        int                    nnzA,
                                        const cusparsesMatDescr_t descrA,
                                        const double*         csrValA,
                                        const int*            csrRowPtrA,
                                        const int*            csrColIndA,
                                        float                 percentage,
                                        const cusparsesMatDescr_t descrC,
                                        int*                  csrRowPtrC,
                                        int*                  csrColIndC,
                                        nnzTotalDevHostPtr,
                                pruneInfo_t      info,
                                void*             pBuffer)

```

```

cusparsesStatus_t
cusparsesHpruneCsr2csrByPercentage (cusparsesHandle_t      handle,
                                        int                    m,
                                        int                    n,
                                        int                    nnzA,
                                        const cusparsesMatDescr_t descrA,
                                        const __half*         csrValA,
                                        const int*            csrRowPtrA,
                                        const int*            csrColIndA,
                                        float                 percentage,
                                        const cusparsesMatDescr_t descrC,
                                        __half*              csrValC,
                                        const int*            csrRowPtrC,
                                        const int*            csrColIndC,
                                        pruneInfo_t          info,
                                        void*                 pBuffer)

```

```

cusparsesStatus_t
cusparsesSpruneCsr2csrByPercentage (cusparsesHandle_t      handle,
                                        int                    m,
                                        int                    n,
                                        int                    nnzA,
                                        const cusparsesMatDescr_t descrA,
                                        const float*          csrValA,
                                        const int*            csrRowPtrA,
                                        const int*            csrColIndA,
                                        float                 percentage,
                                        const cusparsesMatDescr_t descrC,
                                        float*               csrValC,
                                        const int*            csrRowPtrC,
                                        const int*            csrColIndC,
                                        pruneInfo_t          info,
                                        void*                 pBuffer)

```

```

cusparsesStatus_t
cusparsesDpruneCsr2csrByPercentage (cusparsesHandle_t      handle,
                                        int                    m,
                                        int                    n,
                                        int                    nnzA,
                                        const cusparsesMatDescr_t descrA,

```

```

const double*      csrValA,
const int*         csrRowPtrA,
const int*         csrColIndA,
float              percentage,
const cusparseMatDescr_t descrC,
double*           csrValC,
const int*         csrRowPtrC,
int*              csrColIndC,
pruneInfo_t       info,
void*              pBuffer)

```

This function prunes a sparse matrix to a sparse matrix by percentage.

Given a sparse matrix *A* and a non-negative value *percentage*, the function computes sparse matrix *C* by the following three steps:

Step 1: sort absolute value of *A* in ascending order.

```
key := sort( |csrValA| )
```

Step 2: choose threshold by the parameter *percentage*

```

pos = ceil(nnzA*(percentage/100)) - 1
pos = min(pos, nnzA-1)
pos = max(pos, 0)
threshold = key[pos]

```

Step 3: call `pruneCsr2csr()` by with the parameter *threshold*.

The implementation adopts a two-step approach to do the conversion. First, the user allocates `csrRowPtrC` of *m*+1 elements and uses function `pruneCsr2csrNnzByPercentage()` to determine the number of nonzeros columns per row. Second, the user gathers `nnzC` (number of nonzeros of matrix *C*) from either (`nnzC=*nnzTotalDevHostPtr`) or (`nnzC=csrRowPtrC[m]-csrRowPtrC[0]`) and allocates `csrValC` of `nnzC` elements and `csrColIndC` of `nnzC` integers. Finally function `pruneCsr2csrByPercentage()` is called to complete the conversion.

The user must obtain the size of the buffer required by `pruneCsr2csrByPercentage()` by calling `pruneCsr2csrByPercentage_bufferSizeExt()`, allocate the buffer, and pass the buffer pointer to `pruneCsr2csrByPercentage()`.

Remark 1: the value of *percentage* must be not greater than 100. Otherwise, `CUSPARSE_STATUS_INVALID_VALUE` is returned.

Appendix section provides a simple example of `pruneCsr2csrByPercentage()`.

The routine `cusparse<t>pruneCsr2csrNnzByPercentage()` has the following properties:

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

The routine `cusparse<t>pruneCsr2csrByPercentage()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports CUDA graph capture

Input

parameter	device or host	description
handle	host	handle to the cuSPARSE library context.
m	host	number of rows of matrix A.
n	host	number of columns of matrix A.
nnzA	host	number of nonzeros of matrix A.
descrA	host	the descriptor of matrix A. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL, Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
csrValA	device	<type> array of nnzA nonzero elements of matrix A.
csrRowsPtrA	device	integer array of m+1 elements that contains the start of every row and the end of the last row plus one.
csrColIndA	device	integer array of nnzA column indices of A.
percentage	host	percentage <=100 and percentage >= 0
descrC	host	the descriptor of matrix C. The supported matrix type is CUSPARSE_MATRIX_TYPE_GENERAL, Also, the supported index bases are CUSPARSE_INDEX_BASE_ZERO and CUSPARSE_INDEX_BASE_ONE.
pBuffer	device	buffer allocated by the user; the size is returned by <code>pruneCsr2csrByPercentage_bufferSizeExt()</code> .

Output

parameter	device or host	description
nnzTotalDevHostPtr	device or host	total number of nonzero of matrix C. nnzTotalDevHostPtr can point to a device memory or host memory.
csrValC	device	<type> array of nnzC nonzero elements of matrix C.
csrRowsPtrC	device	integer array of m+1 elements that contains the start of every row and the end of the last row plus one.
csrColIndC	device	integer array of nnzC column indices of C.
pBufferSizeInBytes	host	number of bytes of the buffer.

See [cusparsesStatus_t](#) for the description of the return status

14.25. `cusparses<t>nnz_compress()`

```

cusparseStatus_t
cusparseSnnz_compress(cusparseHandle_t      handle,
                     int                    m,
                     const cusparseMatDescr_t descr,
                     const float*          csrValA,
                     const int*           csrRowPtrA,
                     int*                  nnzPerRow,
                     int*                  nnzC,
                     float                  tol)

cusparseStatus_t
cusparseDnnz_compress(cusparseHandle_t      handle,
                     int                    m,
                     const cusparseMatDescr_t descr,
                     const double*         csrValA,
                     const int*           csrRowPtrA,
                     int*                  nnzPerRow,
                     int*                  nnzC,
                     double                 tol)

cusparseStatus_t
cusparseCnnz_compress(cusparseHandle_t      handle,
                     int                    m,
                     const cusparseMatDescr_t descr,
                     const cuComplex*      csrValA,
                     const int*           csrRowPtrA,
                     int*                  nnzPerRow,
                     int*                  nnzC,
                     cuComplex             tol)

cusparseStatus_t
cusparseZnnz_compress(cusparseHandle_t      handle,
                     int                    m,
                     const cusparseMatDescr_t descr,
                     const cuDoubleComplex* csrValA,
                     const int*           csrRowPtrA,
                     int*                  nnzPerRow,
                     int*                  nnzC,
                     cuDoubleComplex       tol)

```

This function is the step one to convert from csr format to compressed csr format.

Given a sparse matrix A and a non-negative value threshold, the function returns nnzPerRow(the number of nonzeros columns per row) and nnzC(the total number of nonzeros) of a sparse matrix C, defined by

$$C(i,j) = A(i,j) \quad \text{if } |A(i,j)| > \text{threshold}$$

A key assumption for the cuComplex and cuDoubleComplex case is that this tolerance is given as the real part. For example $\text{tol} = 1e-8 + 0*i$ and we extract `cureal`, that is the x component of this struct.

- ▶ This function requires temporary extra storage that is allocated internally
- ▶ The routine supports asynchronous execution if the Stream Ordered Memory Allocator is available
- ▶ The routine supports CUDA graph capture if the Stream Ordered Memory Allocator is available

Input

handle	handle to the cuSPARSE library context.
m	number of rows of matrix A.
descrA	the descriptor of matrix A. The supported matrix type is <code>CUSPARSE_MATRIX_TYPE_GENERAL</code> . Also, the supported index bases are <code>CUSPARSE_INDEX_BASE_ZERO</code> and <code>CUSPARSE_INDEX_BASE_ONE</code> .
csrValA	csr noncompressed values array
csrRowPtrA	the corresponding input noncompressed row pointer.
tol	non-negative tolerance to determine if a number less than or equal to it.

Output

nnzPerRow	this array contains the number of elements whose absolute values are greater than tol per row.
nnzC	host/device pointer of the total number of elements whose absolute values are greater than tol.

See [`cusparseStatus_t`](#) for the description of the return status

Chapter 15. cuSPARSE Generic API Reference

The cuSPARSE Generic APIs allow computing the most common sparse linear algebra operations, such as sparse matrix-vector (SpMV) and sparse matrix-matrix multiplication (SpMM), in a flexible way. The new APIs have the following capabilities and features:

- ▶ Set matrix data layouts, number of batches, and storage formats (for example, CSR, COO, and so on)
- ▶ Set input/output/compute data types. This also allows mixed data-type computation
- ▶ Set types of sparse matrix indices
- ▶ Choose the algorithm for the computation
- ▶ Provide external device memory for internal operations
- ▶ Provide extensive consistency checks across input matrices and vectors for a given routine. This includes the validation of matrix sizes, data types, layout, allowed operations, etc.

15.1. Generic Types Reference

The cuSPARSE generic type references are described in this section.

15.1.1. `cudaDataType_t`

The section describes the types shared by multiple CUDA Libraries and defined in the header file `library_types.h`. The `cudaDataType` type is an enumerator to specify the data precision. It is used when the data reference does not carry the type itself (e.g. `void*`). For example, it is used in the routine `cusparseSpMM()`.

Value	Meaning	Data Type	Header
<code>CUDA_R_16F</code>	The data type is 16-bit IEEE-754 floating-point	<code>__half</code>	<code>cuda_fp16.h</code>
<code>CUDA_C_16F</code>	The data type is 16-bit complex IEEE-754 floating-point	<code>__half2</code>	<code>cuda_fp16.h</code>
<code>CUDA_R_16BF</code>	The data type is 16-bit bfloat floating-point	<code>__nv_bfloat16</code>	<code>cuda_bf16.h</code>

Value	Meaning	Data Type	Header
CUDA_C_16BF	The data type is 16-bit complex bfloat floating-point	<code>__nv_bfloat162</code>	<code>cuda_bf16.h</code>
CUDA_R_32F	The data type is 32-bit IEEE-754 floating-point	<code>float</code>	
CUDA_C_32F	The data type is 32-bit complex IEEE-754 floating-point	<code>cuComplex</code>	<code>cuComplex.h</code>
CUDA_R_64F	The data type is 64-bit IEEE-754 floating-point	<code>double</code>	
CUDA_C_64F	The data type is 64-bit complex IEEE-754 floating-point	<code>cuDoubleComplex</code>	<code>cuComplex.h</code>
CUDA_R_8I	The data type is 8-bit integer	<code>int8_t</code>	<code>stdint.h</code>
CUDA_R_32I	The data type is 32-bit integer	<code>int32_t</code>	<code>stdint.h</code>

IMPORTANT: The Generic API routines allow all data types reported in the respective section of the documentation only on GPU architectures with *native* support for them. If a specific GPU model does not provide *native* support for a given data type, the routine returns `CUSPARSE_STATUS_ARCH_MISMATCH` error.

Unsupported data types and Compute Capability (CC):

- ▶ `__half` on GPUs with `cc < 53` (e.g. Kepler)
- ▶ `__nv_bfloat16` on GPUs with `cc < 80` (e.g. Kepler, Maxwell, Pascal, Volta, Turing)

see <https://developer.nvidia.com/cuda-gpus>

15.1.2. `cusparseFormat_t`

This type indicates the format of the sparse matrix.

Value	Meaning
<code>CUSPARSE_FORMAT_COO</code>	The matrix is stored in Coordinate (COO) format organized in <i>Structure of Arrays (SoA)</i> layout
<code>CUSPARSE_FORMAT_COO_AOS</code>	The matrix is stored in Coordinate (COO) format organized in <i>Array of Structures (SoA)</i> layout
<code>CUSPARSE_FORMAT_CSR</code>	The matrix is stored in Compressed Sparse Row (CSR) format
<code>CUSPARSE_FORMAT_CSC</code>	The matrix is stored in Compressed Sparse Column (CSC) format
<code>CUSPARSE_FORMAT_BLOCKED_ELL</code>	The matrix is stored in Blocked-Ellpack (Blocked-ELL) format

15.1.3. `cusparseOrder_t`

This type indicates the memory layout of a dense matrix.

Value	Meaning
<code>CUSPARSE_ORDER_ROW</code>	The matrix is stored in row-major

Value	Meaning
CUSPARSE_ORDER_COL	The matrix is stored in column-major

15.1.4. `cusparseIndexType_t`

This type indicates the index type for representing the sparse matrix indices.

Value	Meaning
CUSPARSE_INDEX_16U	16-bit unsigned integer [1, 65535]
CUSPARSE_INDEX_32I	32-bit signed integer [1, 2 ³¹ - 1]
CUSPARSE_INDEX_64I	64-bit signed integer [1, 2 ⁶³ - 1]

15.2. Sparse Vector APIs

The cuSPARSE helper functions for sparse vector descriptor are described in this section.

15.2.1. `cusparseCreateSpVec()`

```
cusparseStatus_t
cusparseCreateSpVec(cusparseSpVecDescr_t* spVecDescr,
                   int64_t size,
                   int64_t nnz,
                   void* indices,
                   void* values,
                   cusparseIndexType_t idxType,
                   cusparseIndexBase_t idxBase,
                   cudaDataType valueType)
```

This function initializes the sparse matrix descriptor `spVecDescr`.

Param.	Memory	In/out	Meaning
<code>spVecDescr</code>	HOST	OUT	Sparse vector descriptor
<code>size</code>	HOST	IN	Size of the sparse vector
<code>nnz</code>	HOST	IN	Number of non-zero entries of the sparse vector
<code>indices</code>	DEVICE	IN	Indices of the sparse vector. Array of size <code>nnz</code>
<code>values</code>	DEVICE	IN	Values of the sparse vector. Array of size <code>nnz</code>
<code>idxType</code>	HOST	IN	Enumerator specifying the data type of <code>indices</code>
<code>idxBase</code>	HOST	IN	Enumerator specifying the the base index of <code>indices</code>
<code>valueType</code>	HOST	IN	Enumerator specifying the datatype of <code>values</code>

NOTE: it is safe to cast away constness (`const_cast`) for input pointers if the descriptor will not be used as an output parameter of a routine (e.g. conversion functions).

See [`cusparseStatus_t`](#) for the description of the return status

15.2.2. `cusparseDestroySpVec()`

```
cusparseStatus_t
cusparseDestroySpVec (cusparseSpVecDescr_t spVecDescr)
```

This function releases the host memory allocated for the sparse vector descriptor `spVecDescr`.

Param.	Memory	In/out	Meaning
<code>spVecDescr</code>	HOST	IN	Sparse vector descriptor

See [`cusparseStatus_t`](#) for the description of the return status

15.2.3. `cusparseSpVecGet()`

```
cusparseStatus_t
cusparseSpVecGet (cusparseSpVecDescr_t spVecDescr,
                 int64_t* size,
                 int64_t* nnz,
                 void** indices,
                 void** values,
                 cusparseIndexType_t* idxType,
                 cusparseIndexBase_t* idxBase,
                 cudaDataType* valueType)
```

This function returns the fields of the sparse vector descriptor `spVecDescr`.

Param.	Memory	In/out	Meaning
<code>spVecDescr</code>	HOST	IN	Sparse vector descriptor
<code>size</code>	HOST	OUT	Size of the sparse vector
<code>nnz</code>	HOST	OUT	Number of non-zero entries of the sparse vector
<code>indices</code>	DEVICE	OUT	Indices of the sparse vector. Array of size <code>nnz</code>
<code>values</code>	DEVICE	OUT	Values of the sparse vector. Array of size <code>nnz</code>
<code>idxType</code>	HOST	OUT	Enumerator specifying the data type of <code>indices</code>
<code>idxBase</code>	HOST	OUT	Enumerator specifying the the base index of <code>indices</code>
<code>valueType</code>	HOST	OUT	Enumerator specifying the datatype of <code>values</code>

See [`cusparseStatus_t`](#) for the description of the return status

15.2.4. `cusparseSpVecGetIndexBase()`

```
cusparseStatus_t
cusparseSpVecGetIndexBase (cusparseSpVecDescr_t spVecDescr,
                          cusparseIndexBase_t* idxBase)
```

This function returns the `idxBase` field of the sparse vector descriptor `spVecDescr`.

Param.	Memory	In/out	Meaning
spVecDescr	HOST	IN	Sparse vector descriptor
idxBase	HOST	OUT	Enumerator specifying the the base index of indices

See [cusparseStatus_t](#) for the description of the return status

15.2.5. cusparseSpVecGetValues()

```
cusparseStatus_t
cusparseSpVecGetValues(cusparseSpVecDescr_t spVecDescr,
                      void**                values)
```

This function returns the `values` field of the sparse vector descriptor `spVecDescr`.

Param.	Memory	In/out	Meaning
spVecDescr	HOST	IN	Sparse vector descriptor
values	DEVICE	OUT	Values of the sparse vector. Array of size <code>nnz</code>

See [cusparseStatus_t](#) for the description of the return status

15.2.6. cusparseSpVecSetValues()

```
cusparseStatus_t
cusparseSpVecSetValues(cusparseSpVecDescr_t spVecDescr,
                      void*                values)
```

This function set the `values` field of the sparse vector descriptor `spVecDescr`.

Param.	Memory	In/out	Meaning
spVecDescr	HOST	IN	Sparse vector descriptor
values	DEVICE	IN	Values of the sparse vector. Array of size <code>nnz</code>

See [cusparseStatus_t](#) for the description of the return status

15.3. Sparse Matrix APIs

The cuSPARSE helper functions for sparse matrix descriptor are described in this section.

15.3.1. cusparseCreateCoo()

```
cusparseStatus_t
cusparseCreateCoo(cusparseSpMatDescr_t* spMatDescr,
                 int64_t                rows,
                 int64_t                cols,
                 int64_t                nnz,
                 void*                  cooRowInd,
```

```

void*
void*
cusparseIndexType_t
cusparseIndexBase_t
cudaDataType

cooColInd,
cooValues,
cooIdxType,
idxBase,
valueType)

```

This function initializes the sparse matrix descriptor `spMatDescr` in the COO format (Structure of Arrays layout).

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	OUT	Sparse matrix descriptor
<code>rows</code>	HOST	IN	Number of rows of the sparse matrix
<code>cols</code>	HOST	IN	Number of columns of the sparse matrix
<code>nnz</code>	HOST	IN	Number of non-zero entries of the sparse matrix
<code>cooRowInd</code>	DEVICE	IN	Row indices of the sparse matrix. Array of size <code>nnz</code>
<code>cooColInd</code>	DEVICE	IN	Column indices of the sparse matrix. Array of size <code>nnz</code>
<code>cooValues</code>	DEVICE	IN	Values of the sparse matrix. Array of size <code>nnz</code>
<code>cooIdxType</code>	HOST	IN	Data type of <code>cooRowInd</code> and <code>cooColInd</code>
<code>idxBase</code>	HOST	IN	Base index of <code>cooRowInd</code> and <code>cooColInd</code>
<code>valueType</code>	HOST	IN	Datatype of <code>cooValues</code>

NOTE: it is safe to cast away constness (`const_cast`) for input pointers if the descriptor will not be used as an output parameter of a routine (e.g. conversion functions).

See [cusparseStatus_t](#) for the description of the return status

15.3.2. `cusparseCreateCooAoS()` [DEPRECATED]

```

cusparseStatus_t
cusparseCreateCooAoS(cusparseSpMatDescr_t* spMatDescr,
                    int64_t rows,
                    int64_t cols,
                    int64_t nnz,
                    void* cooInd,
                    void* cooValues,
                    cusparseIndexType_t cooIdxType,
                    cusparseIndexBase_t idxBase,
                    cudaDataType valueType)

```

This function initializes the sparse matrix descriptor `spMatDescr` in the COO format (Array of Structures layout).

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	OUT	Sparse matrix descriptor
<code>rows</code>	HOST	IN	Number of rows of the sparse matrix
<code>cols</code>	HOST	IN	Number of columns of the sparse matrix
<code>nnz</code>	HOST	IN	Number of non-zero entries of the sparse matrix

Param.	Memory	In/out	Meaning
cooInd	DEVICE	IN	<Row, Column> indices of the sparse matrix. Array of size nnz
cooValues	DEVICE	IN	Values of the sparse matrix. Array of size nnz
cooIdxType	HOST	IN	Data type of cooInd
idxBase	HOST	IN	Base index of cooInd
valueType	HOST	IN	Datatype of cooValues

See [cusparseStatus_t](#) for the description of the return status

15.3.3. cusparseCreateCsr()

```

cusparseStatus_t
cusparseCreateCsr(cusparseSpMatDescr_t* spMatDescr,
                 int64_t rows,
                 int64_t cols,
                 int64_t nnz,
                 void* csrRowOffsets,
                 void* csrColInd,
                 void* csrValues,
                 cusparseIndexType_t csrRowOffsetsType,
                 cusparseIndexType_t csrColIndType,
                 cusparseIndexBase_t idxBase,
                 cudaDataType valueType)

```

This function initializes the sparse matrix descriptor `spMatDescr` in the CSR format.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	OUT	Sparse matrix descriptor
rows	HOST	IN	Number of rows of the sparse matrix
cols	HOST	IN	Number of columns of the sparse matrix
nnz	HOST	IN	Number of non-zero entries of the sparse matrix
csrRowOffsets	DEVICE	IN	Row offsets of the sparse matrix. Array of size rows + 1
csrColInd	DEVICE	IN	Column indices of the sparse matrix. Array of size nnz
csrValues	DEVICE	IN	Values of the sparse matrix. Array of size nnz
csrRowOffsetsType	HOST	IN	Data type of csrRowOffsets
csrColIndType	HOST	IN	Data type of csrColInd
idxBase	HOST	IN	Base index of csrRowOffsets and csrColInd
valueType	HOST	IN	Datatype of csrValues

NOTE: it is safe to cast away constness (`const_cast`) for input pointers if the descriptor will not be used as an output parameter of a routine (e.g. conversion functions).

See [cusparseStatus_t](#) for the description of the return status

15.3.4. `cusparseCreateCsc()`

```

cusparseStatus_t
cusparseCreateCsc(cusparseSpMatDescr_t* spMatDescr,
                  int64_t rows,
                  int64_t cols,
                  int64_t nnz,
                  void* cscColOffsets,
                  void* cscRowInd,
                  void* cscValues,
                  cusparseIndexType_t cscColOffsetsType,
                  cusparseIndexType_t cscRowIndType,
                  cusparseIndexBase_t idxBase,
                  cudaDataType valueType)

```

This function initializes the sparse matrix descriptor `spMatDescr` in the CSC format.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	OUT	Sparse matrix descriptor
<code>rows</code>	HOST	IN	Number of rows of the sparse matrix
<code>cols</code>	HOST	IN	Number of columns of the sparse matrix
<code>nnz</code>	HOST	IN	Number of non-zero entries of the sparse matrix
<code>cscColOffsets</code>	DEVICE	IN	Column offsets of the sparse matrix. Array of size <code>cols + 1</code>
<code>cscRowInd</code>	DEVICE	IN	Row indices of the sparse matrix. Array of size <code>nnz</code>
<code>cscValues</code>	DEVICE	IN	Values of the sparse matrix. Array of size <code>nnz</code>
<code>cscColOffsetsType</code>	HOST	IN	Data type of <code>cscColOffsets</code>
<code>cscRowIndType</code>	HOST	IN	Data type of <code>cscRowInd</code>
<code>idxBase</code>	HOST	IN	Base index of <code>cscColOffsets</code> and <code>cscRowInd</code>
<code>valueType</code>	HOST	IN	Datatype of <code>cscValues</code>

NOTE: it is safe to cast away constness (`const_cast`) for input pointers if the descriptor will not be used as an output parameter of a routine (e.g. conversion functions).

See [`cusparseStatus_t`](#) for the description of the return status

15.3.5. `cusparseCreateBlockedEll()`

```

cusparseStatus_t
cusparseCreateBlockedEll(cusparseSpMatDescr_t* spMatDescr,
                        int64_t rows,
                        int64_t cols,
                        int64_t ellBlockSize,
                        int64_t ellCols,
                        void* ellColInd,
                        void* ellValue,
                        cusparseIndexType_t ellIdxType,

```


cusparseIndexBase_t idxBase,
 cudaDataType valueType)


This function initializes the sparse matrix descriptor `spMatDescr` for the Blocked-Ellpack (ELL) format.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	OUT	Sparse matrix descriptor
<code>rows</code>	HOST	IN	Number of rows of the sparse matrix
<code>cols</code>	HOST	IN	Number of columns of the sparse matrix
<code>ellBlockSize</code>	HOST	IN	Size of the ELL-Block
<code>ellCols</code>	HOST	IN	Actual number of columns of the Blocked-Ellpack format (<code>ellValue</code> columns)
<code>ellColInd</code>	DEVICE	IN	Blocked-ELL Column indices. Array of size $[\text{ellCols} / \text{ellBlockSize}][\text{rows} / \text{ellBlockSize}]$
<code>ellValue</code>	DEVICE	IN	Values of the sparse matrix. Array of size <code>rows * ellCols</code>
<code>ellIdxType</code>	HOST	IN	Data type of <code>ellColInd</code>
<code>idxBase</code>	HOST	IN	Base index of <code>ellColInd</code>
<code>valueType</code>	HOST	IN	Datatype of <code>ellValue</code>

Blocked-ELL Column indices (`ellColInd`) are in the range $[0, \text{cols} / \text{ellBlockSize} - 1]$. The array can contain `-1` values for indicating empty blocks.

NOTE: it is safe to cast away constness (`const_cast`) for input pointers if the descriptor will not be used as an output parameter of a routine (e.g. conversion functions).

Figure 1. Blocked-ELL representation



See [cusparseStatus_t](#) for the description of the return status

15.3.6. `cusparseDestroySpMat()`

```
cusparseStatus_t
cusparseDestroySpMat(cusparseSpMatDescr_t spMatDescr)
```

This function releases the host memory allocated for the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor

See [`cusparseStatus_t`](#) for the description of the return status

15.3.7. `cusparseCooGet()`

```
cusparseStatus_t
cusparseCooGet(cusparseSpMatDescr_t spMatDescr,
               int64_t* rows,
               int64_t* cols,
               int64_t* nnz,
               void** cooRowInd,
               void** cooColInd,
               void** cooValues,
               cusparseIndexType_t* idxType,
               cusparseIndexBase_t* idxBase,
               cudaDataType* valueType)
```

This function returns the fields of the sparse matrix descriptor `spMatDescr` stored in COO format (Array of Structures layout).

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor
<code>rows</code>	HOST	OUT	Number of rows of the sparse matrix
<code>cols</code>	HOST	OUT	Number of columns of the sparse matrix
<code>nnz</code>	HOST	OUT	Number of non-zero entries of the sparse matrix
<code>cooRowInd</code>	DEVICE	OUT	Row indices of the sparse matrix. Array of size <code>nnz</code>
<code>cooColInd</code>	DEVICE	OUT	Column indices of the sparse matrix. Array of size <code>nnz</code>
<code>cooValues</code>	DEVICE	OUT	Values of the sparse matrix. Array of size <code>nnz</code>
<code>cooIdxType</code>	HOST	OUT	Data type of <code>cooRowInd</code> and <code>cooColInd</code>
<code>idxBase</code>	HOST	OUT	Base index of <code>cooRowInd</code> and <code>cooColInd</code>
<code>valueType</code>	HOST	OUT	Datatype of <code>cooValues</code>

See [`cusparseStatus_t`](#) for the description of the return status

15.3.8. `cusparseCooAoSGet()` [DEPRECATED]

```
cusparseStatus_t
cusparseCooAoSGet(cusparseSpMatDescr_t spMatDescr,
                  int64_t* rows,
                  int64_t* cols,
                  int64_t* nnz,
                  void** cooInd,
                  void** cooValues,
                  cusparseIndexType_t* idxType,
                  cusparseIndexBase_t* idxBase,
                  cudaDataType* valueType)
```

This function returns the fields of the sparse matrix descriptor `spMatDescr` stored in COO format (Structure of Arrays layout).

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor
<code>rows</code>	HOST	OUT	Number of rows of the sparse matrix
<code>cols</code>	HOST	OUT	Number of columns of the sparse matrix
<code>nnz</code>	HOST	OUT	Number of non-zero entries of the sparse matrix
<code>cooInd</code>	DEVICE	OUT	<Row, Column> indices of the sparse matrix. Array of size <code>nnz</code>
<code>cooValues</code>	DEVICE	OUT	Values of the sparse matrix. Array of size <code>nnz</code>
<code>cooIdxType</code>	HOST	OUT	Data type of <code>cooInd</code>
<code>idxBase</code>	HOST	OUT	Base index of <code>cooInd</code>
<code>valueType</code>	HOST	OUT	Datatype of <code>cooValues</code>

See [`cusparseStatus_t`](#) for the description of the return status

15.3.9. `cusparseCsrGet()`

```
cusparseStatus_t
cusparseCsrGet(cusparseSpMatDescr_t spMatDescr,
               int64_t* rows,
               int64_t* cols,
               int64_t* nnz,
               void** csrRowOffsets,
               void** csrColInd,
               void** csrValues,
               cusparseIndexType_t* csrRowOffsetsType,
               cusparseIndexType_t* csrColIndType,
               cusparseIndexBase_t* idxBase,
               cudaDataType* valueType)
```

This function returns the fields of the sparse matrix descriptor `spMatDescr` stored in CSR format.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor
<code>rows</code>	HOST	OUT	Number of rows of the sparse matrix
<code>cols</code>	HOST	OUT	Number of columns of the sparse matrix
<code>nnz</code>	HOST	OUT	Number of non-zero entries of the sparse matrix
<code>csrRowOffsets</code>	DEVICE	OUT	Row offsets of the sparse matrix. Array of size <code>rows + 1</code>
<code>csrColInd</code>	DEVICE	OUT	Column indices of the sparse matrix. Array of size <code>nnz</code>
<code>csrValues</code>	DEVICE	OUT	Values of the sparse matrix. Array of size <code>nnz</code>
<code>csrRowOffsetsType</code>	HOST	OUT	Data type of <code>csrRowOffsets</code>
<code>csrColIndType</code>	HOST	OUT	Data type of <code>csrColInd</code>
<code>idxBase</code>	HOST	OUT	Base index of <code>csrRowOffsets</code> and <code>csrColInd</code>
<code>valueType</code>	HOST	OUT	Datatype of <code>csrValues</code>

See [`cusparseStatus_t`](#) for the description of the return status

15.3.10. `cusparseCsrSetPointers()`

```
cusparseStatus_t
cusparseCsrSetPointers(cusparseSpMatDescr_t spMatDescr,
                      void* csrRowOffsets,
                      void* csrColInd,
                      void* csrValues)
```

This function sets the pointers of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor
<code>csrRowOffsets</code>	DEVICE	IN	Row offsets of the sparse matrix. Array of size <code>rows + 1</code>
<code>csrColInd</code>	DEVICE	IN	Column indices of the sparse matrix. Array of size <code>nnz</code>
<code>csrValues</code>	DEVICE	IN	Values of the sparse matrix. Array of size <code>nnz</code>

See [`cusparseStatus_t`](#) for the description of the return status

15.3.11. `cusparseCscSetPointers()`

```
cusparseStatus_t
cusparseCscSetPointers(cusparseSpMatDescr_t spMatDescr,
                      void* cscColOffsets,
                      void* cscRowInd,
                      void* cscValues)
```

This function sets the pointers of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor
<code>cscColOffsets</code>	DEVICE	IN	Col offsets of the sparse matrix. Array of size <code>cols + 1</code>
<code>cscRowInd</code>	DEVICE	IN	Row indices of the sparse matrix. Array of size <code>nnz</code>
<code>cscValues</code>	DEVICE	IN	Values of the sparse matrix. Array of size <code>nnz</code>

See [`cusparseStatus_t`](#) for the description of the return status

15.3.12. `cusparseCooSetPointers()`

```
cusparseStatus_t
cusparseCooSetPointers(cusparseSpMatDescr_t spMatDescr,
                      void*                cooRows,
                      void*                cooColumns,
                      void*                cooValues)
```

This function sets the pointers of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor
<code>cooRows</code>	DEVICE	IN	Row indices of the sparse matrix. Array of size <code>nnz</code>
<code>cooColumns</code>	DEVICE	IN	Column indices of the sparse matrix. Array of size <code>nnz</code>
<code>cooValues</code>	DEVICE	IN	Values of the sparse matrix. Array of size <code>nnz</code>

See [`cusparseStatus_t`](#) for the description of the return status

15.3.13. `cusparseBlockedEllGet()`

```
cusparseStatus_t
cusparseBlockedEllGet(cusparseSpMatDescr_t spMatDescr,
                    int64_t*              rows,
                    int64_t*              cols,
                    int64_t*              ellBlockSize,
                    int64_t*              ellCols,
                    void**                ellColInd,
                    void**                ellValue,
                    cusparseIndexType_t*  ellIdxType,
                    cusparseIndexBase_t*  idxBase,
                    cudaDataType*         valueType)
```

This function returns the fields of the sparse matrix descriptor `spMatDescr` stored in Blocked-Ellpack (ELL) format.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
rows	HOST	OUT	Number of rows of the sparse matrix
cols	HOST	OUT	Number of columns of the sparse matrix
ellBlockSize	HOST	OUT	Size of the ELL-Block
ellCols	HOST	OUT	Actual number of columns of the Blocked-Ellpack format
ellColInd	DEVICE	OUT	Column indices for the ELL-Block. Array of size $[\text{cols} / \text{ellBlockSize}][\text{rows} / \text{ellBlockSize}]$
ellValue	DEVICE	OUT	Values of the sparse matrix. Array of size $\text{rows} * \text{ellCols}$
ellIdxType	HOST	OUT	Data type of ellColInd
idxBase	HOST	OUT	Base index of ellColInd
valueType	HOST	OUT	Datatype of ellValue

See [cusparseStatus_t](#) for the description of the return status

15.3.14. cusparseSpMatGetSize()

```
cusparseStatus_t
cusparseSpMatGetSize(cusparseSpMatDescr_t spMatDescr,
                    int64_t* rows,
                    int64_t* cols,
                    int64_t* nnz)
```

This function returns the sizes of the sparse matrix spMatDescr.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
rows	HOST	OUT	Number of rows of the sparse matrix
cols	HOST	OUT	Number of columns of the sparse matrix
nnz	HOST	OUT	Number of non-zero entries of the sparse matrix

See [cusparseStatus_t](#) for the description of the return status

15.3.15. cusparseSpMatGetFormat()

```
cusparseStatus_t
cusparseSpMatGetFormat(cusparseSpMatDescr_t spMatDescr,
                      cusparseFormat_t* format)
```

This function returns the format field of the sparse matrix descriptor spMatDescr.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
format	HOST	OUT	Storage format of the sparse matrix

See [cusparseStatus_t](#) for the description of the return status

15.3.16. cusparseSpMatGetIndexBase()

```
cusparseStatus_t
cusparseSpMatGetIndexBase(cusparseSpMatDescr_t spMatDescr,
                          cusparseIndexBase_t* idxBase)
```

This function returns the `idxBase` field of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
idxBase	HOST	OUT	Base index of the sparse matrix

See [cusparseStatus_t](#) for the description of the return status

15.3.17. cusparseSpMatGetValues()

```
cusparseStatus_t
cusparseSpMatGetValues(cusparseSpMatDescr_t spMatDescr,
                       void** values)
```

This function returns the `values` field of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
values	DEVICE	OUT	Values of the sparse matrix. Array of size <code>nnz</code>

See [cusparseStatus_t](#) for the description of the return status

15.3.18. cusparseSpMatSetValues()

```
cusparseStatus_t
cusparseSpMatSetValues(cusparseSpMatDescr_t spMatDescr,
                       void* values)
```

This function sets the `values` field of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
values	DEVICE	IN	Values of the sparse matrix. Array of size nnz

See [cusparseStatus_t](#) for the description of the return status

15.3.19. cusparseSpMatGetStridedBatch()

```
cusparseStatus_t
cusparseSpMatGetStridedBatch(cusparseSpMatDescr_t spMatDescr,
                             int* batchCount)
```

This function returns the `batchCount` field of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
batchCount	HOST	OUT	Number of batches of the sparse matrix

See [cusparseStatus_t](#) for the description of the return status

15.3.20. cusparseSpMatSetStridedBatch() [DEPRECATED]

[[DEPRECATED]] use [_cusparseSpMatSetCsrStridedBatch\(\)](#), [cusparseSpMatSetCooStridedBatch\(\)](#) instead. *The routine will be removed in the next major release*

```
cusparseStatus_t
cusparseSpMatSetStridedBatch(cusparseSpMatDescr_t spMatDescr,
                             int batchCount)
```

This function sets the `batchCount` field of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
batchCount	HOST	IN	Number of batches of the sparse matrix

See [cusparseStatus_t](#) for the description of the return status

15.3.21. cusparseCooSetStridedBatch()


```

cusparseStatus_t
cusparseCooSetStridedBatch(cusparseSpMatDescr_t spMatDescr,
                           int batchCount,
                           int64_t batchStride)

```

This function sets the `batchCount` and the `batchStride` fields of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor
<code>batchCount</code>	HOST	IN	Number of batches of the sparse matrix
<code>batchStride</code>	HOST	IN	address offset between consecutive batches

See [cusparseStatus_t](#) for the description of the return status

15.3.22. cusparseCsrSetStridedBatch()

```

cusparseStatus_t
cusparseCsrSetStridedBatch(cusparseSpMatDescr_t spMatDescr,
                           int batchCount,
                           int64_t offsetsBatchStride,
                           int64_t columnsValuesBatchStride)

```

This function sets the `batchCount` and the `batchStride` fields of the sparse matrix descriptor `spMatDescr`.

Param.	Memory	In/out	Meaning
<code>spMatDescr</code>	HOST	IN	Sparse matrix descriptor
<code>batchCount</code>	HOST	IN	Number of batches of the sparse matrix
<code>offsetsBatchStride</code>	HOST	IN	Address offset between consecutive batches for the row offset array
<code>columnsValuesBatchStride</code>	HOST	IN	Address offset between consecutive batches for the column and value arrays

See [cusparseStatus_t](#) for the description of the return status

15.3.23. cusparseSpMatGetAttribute()

```

cusparseStatus_t
cusparseSpMatGetAttribute(cusparseSpMatDescr_t spMatDescr,
                          cusparseSpMatAttribute_t attribute,
                          void* data,
                          size_t dataSize)

```

The function gets the attributes of the sparse matrix descriptor `spMatDescr`

Param.	Memory	In/out	Meaning
spMatDescr	HOST	IN	Sparse matrix descriptor
attribute	HOST	IN	Attribute enumerator
data	HOST	OUT	Attribute value
dataSize	HOST	IN	Size of the attribute in bytes for safety

Attribute	Meaning	Possible Values
CUSPARSE_SPMAT_FILL_MODE	Indicates if the lower or upper part of a matrix is stored in sparse storage	CUSPARSE_FILL_MODE_LOWER CUSPARSE_FILL_MODE_UPPER
CUSPARSE_SPMAT_DIAG_TYPE	Indicates if the matrix diagonal entries are unity	CUSPARSE_DIAG_TYPE_NON_UNIT CUSPARSE_DIAG_TYPE_UNIT

See [cusparseStatus_t](#) for the description of the return status

15.3.24. cusparseSpMatSetAttribute()

```
cusparseStatus_t
cusparseSpMatSetAttribute(cusparseSpMatDescr_t spMatDescr,
                          cusparseSpMatAttribute_t attribute,
                          const void* data,
                          size_t dataSize)
```

The function sets the attributes of the sparse matrix descriptor `spMatDescr`

Param.	Memory	In/out	Meaning
spMatDescr	HOST	OUT	Sparse matrix descriptor
attribute	HOST	IN	Attribute enumerator
data	HOST	IN	Attribute value
dataSize	HOST	IN	Size of the attribute in bytes for safety

Attribute	Meaning	Possible Values
CUSPARSE_SPMAT_FILL_MODE	Indicates if the lower or upper part of a matrix is stored in sparse storage	CUSPARSE_FILL_MODE_LOWER CUSPARSE_FILL_MODE_UPPER
CUSPARSE_SPMAT_DIAG_TYPE	Indicates if the matrix diagonal entries are unity	CUSPARSE_DIAG_TYPE_NON_UNIT CUSPARSE_DIAG_TYPE_UNIT

See [cusparseStatus_t](#) for the description of the return status

15.4. Dense Vector APIs

The cuSPARSE helper functions for dense vector descriptor are described in this section.

15.4.1. `cusparseCreateDnVec()`

```
cusparseStatus_t
cusparseCreateDnVec (cusparseDnVecDescr_t* dnVecDescr,
                    int64_t size,
                    void* values,
                    cudaDataType valueType)
```

This function initializes the dense vector descriptor `dnVecDescr`.

Param.	Memory	In/out	Meaning
<code>dnVecDescr</code>	HOST	OUT	Dense vector descriptor
<code>size</code>	HOST	IN	Size of the dense vector
<code>values</code>	DEVICE	IN	Values of the dense vector. Array of size <code>size</code>
<code>valueType</code>	HOST	IN	Enumerator specifying the datatype of <code>values</code>

NOTE: it is safe to cast away constness (`const_cast`) for input pointers if the descriptor will not be used as an output parameter of a routine (e.g. conversion functions).

See [`cusparseStatus_t`](#) for the description of the return status

15.4.2. `cusparseDestroyDnVec()`

```
cusparseStatus_t
cusparseDestroyDnVec (cusparseDnVecDescr_t dnVecDescr)
```

This function releases the host memory allocated for the dense vector descriptor `dnVecDescr`.

Param.	Memory	In/out	Meaning
<code>dnVecDescr</code>	HOST	IN	Dense vector descriptor

See [`cusparseStatus_t`](#) for the description of the return status

15.4.3. `cusparseDnVecGet()`

```
cusparseStatus_t
cusparseDnVecGet (cusparseDnVecDescr_t dnVecDescr,
                 int64_t* size,
                 void** values,
                 cudaDataType* valueType)
```

This function returns the fields of the dense vector descriptor `dnVecDescr`.

Param.	Memory	In/out	Meaning
dnVecDescr	HOST	IN	Dense vector descriptor
size	HOST	OUT	Size of the dense vector
values	DEVICE	OUT	Values of the dense vector. Array of size nnz
valueType	HOST	OUT	Enumerator specifying the datatype of values

See [cusparseStatus_t](#) for the description of the return status

15.4.4. cusparseDnVecGetValues()

```
cusparseStatus_t
cusparseDnVecGetValues(cusparseDnVecDescr_t dnVecDescr,
                      void** values)
```

This function returns the `values` field of the dense vector descriptor `dnVecDescr`.

Param.	Memory	In/out	Meaning
dnVecDescr	HOST	IN	Dense vector descriptor
values	DEVICE	OUT	Values of the dense vector

See [cusparseStatus_t](#) for the description of the return status

15.4.5. cusparseDnVecSetValues()

```
cusparseStatus_t
cusparseDnVecSetValues(cusparseDnVecDescr_t dnVecDescr,
                      void* values)
```

This function set the `values` field of the dense vector descriptor `dnVecDescr`.

Param.	Memory	In/out	Meaning
dnVecDescr	HOST	IN	Dense vector descriptor
values	DEVICE	IN	Values of the dense vector. Array of size size

The possible error values returned by this function and their meanings are listed below :

See [cusparseStatus_t](#) for the description of the return status

15.5. Dense Matrix APIs

The cuSPARSE helper functions for dense matrix descriptor are described in this section.

15.5.1. cusparseCreateDnMat()

```
cusparseStatus_t
```

```

cusparseCreateDnMat (cusparseDnMatDescr_t* dnMatDescr,
                    int64_t                rows,
                    int64_t                cols,
                    int64_t                ld,
                    void*                  values,
                    cudaDataType           valueType,
                    cusparseOrder_t        order)

```

The function initializes the dense matrix descriptor `dnMatDescr`.

Param.	Memory	In/out	Meaning
<code>dnMatDescr</code>	HOST	OUT	Dense matrix descriptor
<code>rows</code>	HOST	IN	Number of rows of the dense matrix
<code>cols</code>	HOST	IN	Number of columns of the dense matrix
<code>ld</code>	HOST	IN	Leading dimension of the dense matrix
<code>values</code>	DEVICE	IN	Values of the dense matrix. Array of size <code>size</code>
<code>valueType</code>	HOST	IN	Enumerator specifying the datatype of <code>values</code>
<code>order</code>	HOST	IN	Enumerator specifying the memory layout of the dense matrix

NOTE: it is safe to cast away constness (`const_cast`) for input pointers if the descriptor will not be used as an output parameter of a routine (e.g. conversion functions).

See [cusparseStatus_t](#) for the description of the return status

15.5.2. cusparseDestroyDnMat()

```

cusparseStatus_t
cusparseDestroyDnMat (cusparseDnMatDescr_t dnMatDescr)

```

This function releases the host memory allocated for the dense matrix descriptor `dnMatDescr`.

Param.	Memory	In/out	Meaning
<code>dnMatDescr</code>	HOST	IN	Dense matrix descriptor

See [cusparseStatus_t](#) for the description of the return status

15.5.3. cusparseDnMatGet()

```

cusparseStatus_t
cusparseDnMatGet (cusparseDnMatDescr_t dnMatDescr,
                  int64_t*              rows,
                  int64_t*              cols,
                  int64_t*              ld,
                  void**                 values,
                  cudaDataType*          type,
                  cusparseOrder_t*       order)

```

This function returns the fields of the dense matrix descriptor `dnMatDescr`.

Param.	Memory	In/out	Meaning
dnMatDescr	HOST	IN	Dense matrix descriptor
rows	HOST	OUT	Number of rows of the dense matrix
cols	HOST	OUT	Number of columns of the dense matrix
ld	HOST	OUT	Leading dimension of the dense matrix
values	DEVICE	OUT	Values of the dense matrix. Array of size <code>ld * cols</code>
valueType	HOST	OUT	Enumerator specifying the datatype of <code>values</code>
order	HOST	OUT	Enumerator specifying the memory layout of the dense matrix

See [cusparseStatus_t](#) for the description of the return status

15.5.4. cusparseDnMatGetValues()

```
cusparseStatus_t
cusparseDnMatGetValues(cusparseDnMatDescr_t dnMatDescr,
                      void** values)
```

This function returns the `values` field of the dense matrix descriptor `dnMatDescr`.

Param.	Memory	In/out	Meaning
dnMatDescr	HOST	IN	Dense matrix descriptor
values	DEVICE	OUT	Values of the dense matrix. Array of size <code>ld * cols</code>

See [cusparseStatus_t](#) for the description of the return status

15.5.5. cusparseDnSetValues()

```
cusparseStatus_t
cusparseDnMatSetValues(cusparseDnMatDescr_t dnMatDescr,
                      void* values)
```

This function sets the `values` field of the dense matrix descriptor `dnMatDescr`.

Param.	Memory	In/out	Meaning
dnMatDescr	HOST	IN	Dense matrix descriptor
values	DEVICE	IN	Values of the dense matrix. Array of size <code>ld * cols</code>

See [cusparseStatus_t](#) for the description of the return status

15.5.6. cusparseDnMatGetStridedBatch()

```
cusparseStatus_t
cusparseDnMatGetStridedBatch(cusparseDnMatDescr_t dnMatDescr,
                             int* batchCount,
```

```
int64_t* batchStride)
```

The function returns the number of batches and the batch stride of the dense matrix descriptor `dnMatDescr`.

Param.	Memory	In/out	Meaning
<code>dnMatDescr</code>	HOST	IN	Dense matrix descriptor
<code>batchCount</code>	HOST	OUT	Number of batches of the dense matrix
<code>batchStride</code>	HOST	OUT	Address offset between a matrix and the next one in the batch

See [`cusparseStatus_t`](#) for the description of the return status

15.5.7. `cusparseDnMatSetStridedBatch()`

```
cusparseStatus_t
cusparseDnMatSetStridedBatch(cusparseDnMatDescr_t dnMatDescr,
                             int batchCount,
                             int64_t batchStride)
```

The function sets the number of batches and the batch stride of the dense matrix descriptor `dnMatDescr`.

Param.	Memory	In/out	Meaning
<code>dnMatDescr</code>	HOST	IN	Dense matrix descriptor
<code>batchCount</code>	HOST	IN	Number of batches of the dense matrix
<code>batchStride</code>	HOST	IN	Address offset between a matrix and the next one in the batch. $\text{batchStride} \geq \text{ld} * \text{cols}$ if the matrix uses column-major layout, $\text{batchStride} \geq \text{ld} * \text{rows}$ otherwise

See [`cusparseStatus_t`](#) for the description of the return status

15.6. Generic API Functions

15.6.1. `cusparseSparseToDense()`

```
cusparseStatus_t
cusparseSparseToDense_bufferSize(cusparseHandle_t handle,
                                 cusparseSpMatDescr_t matA,
                                 cusparseDnMatDescr_t matB,
                                 cusparseSparseToDenseAlg_t alg,
                                 size_t* bufferSize)
```

```
cusparseStatus_t
cusparseSparseToDense(cusparseHandle_t handle,
```

```

    cusparseSpMatDescr_t    matA,
    cusparseDnMatDescr_t   matB,
    cusparseSparseToDenseAlg_t alg,
    void*                   buffer)

```

The function converts the sparse matrix `matA` in CSR, CSC, or COO format into its dense representation `matB`. Blocked-ELL is not currently supported.

The function `cusparseSparseToDense_bufferSize()` returns the size of the workspace needed by `cusparseSparseToDense()`

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>matA</code>	HOST	IN	Sparse matrix A
<code>matB</code>	HOST	OUT	Dense matrix B
<code>alg</code>	HOST	IN	Algorithm for the computation
<code>bufferSize</code>	HOST	OUT	Number of bytes of workspace needed by <code>cusparseSparseToDense()</code>
<code>buffer</code>	DEVICE	IN	Pointer to workspace buffer

`cusparseSparseToDense()` supports the following index type for representing the sparse matrix `matA`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

`cusparseSparseToDense()` supports the following data types:

A/B
<code>CUDA_R_16F</code>
<code>CUDA_R_16BF</code>
<code>CUDA_R_32F</code>
<code>CUDA_R_64F</code>
<code>CUDA_C_16F</code>
<code>CUDA_C_16BF</code>
<code>CUDA_C_32F</code>
<code>CUDA_C_64F</code>

`cusparseSparse2Dense()` supports the following algorithm:

Algorithm	Notes
<code>CUSPARSE_SPARSETODENSE_ALG_DEFAULT</code>	Default algorithm

`cusparseSparseToDense()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution

- ▶ Provides deterministic (bit-wise) results for each run

`cusparseSparseToDense()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseSparseToDense](#) for a code example.

15.6.2. `cusparseDenseToSparse()`

```
cusparseStatus_t
cusparseDenseToSparse_bufferSize(cusparseHandle_t      handle,
                                  cusparseDnMatDescr_t  matA,
                                  cusparseSpMatDescr_t  matB,
                                  cusparseDenseToSparseAlg_t alg,
                                  size_t*               bufferSize)
```

```
cusparseStatus_t
cusparseDenseToSparse_analysis(cusparseHandle_t      handle,
                                cusparseDnMatDescr_t  matA,
                                cusparseSpMatDescr_t  matB,
                                cusparseDenseToSparseAlg_t alg,
                                void*                 buffer)
```

```
cusparseStatus_t
cusparseDenseToSparse_convert(cusparseHandle_t      handle,
                               cusparseDnMatDescr_t  matA,
                               cusparseSpMatDescr_t  matB,
                               cusparseDenseToSparseAlg_t alg,
                               void*                 buffer)
```

The function converts the dense matrix `matA` into a sparse matrix `matB` in CSR, CSC, COO, or Blocked-ELL format.

The function `cusparseDenseToSparse_bufferSize()` returns the size of the workspace needed by `cusparseDenseToSparse_analysis()`.

The function `cusparseDenseToSparse_analysis()` updates the number of non-zero elements in the sparse matrix descriptor `matB`. The user is responsible to allocate the memory required by the sparse matrix:

- ▶ Row/Column indices and value arrays for CSC and CSR respectively
- ▶ Row, column, value arrays for COO
- ▶ Column (`e11ColInd`), value (`e11Value`) arrays for Blocked-ELL

Finally, we call `cusparseDenseToSparse_convert()` for filling the arrays allocated in the previous step.

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>matA</code>	HOST	IN	Dense matrix A
<code>matB</code>	HOST	OUT	Sparse matrix B
<code>alg</code>	HOST	IN	Algorithm for the computation
<code>bufferSize</code>	HOST	OUT	Number of bytes of workspace needed by <code>cusparseDenseToSparse_analysis()</code>
<code>buffer</code>	DEVICE	IN	Pointer to workspace buffer

`cusparseDenseToSparse()` supports the following index type for representing the sparse vector `matB`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

`cusparseDenseToSparse()` supports the following data types:

A/B
<code>CUDA_R_16F</code>
<code>CUDA_R_16BF</code>
<code>CUDA_R_32F</code>
<code>CUDA_R_64F</code>
<code>CUDA_C_16F</code>
<code>CUDA_C_16BF</code>
<code>CUDA_C_32F</code>
<code>CUDA_C_64F</code>

`cusparseDense2Sparse()` supports the following algorithm:

Algorithm	Notes
<code>CUSPARSE_DENSETOSPARSE_ALG_DEFAULT</code>	Default algorithm

`cusparseDenseToSparse()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ Provides deterministic (bit-wise) results for each run

`cusparseDenseToSparse()` supports the following [optimizations](#):

- ▶ The routine supports does **not** support CUDA graph capture for CSR, CSC, COO formats
- ▶ Hardware Memory Compression

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseDenseToSparse \(CSR\)](#) and [cuSPARSE Library Samples - cusparseDenseToSparse \(Blocked-ELL\)](#) for code examples.

15.6.3. cusparseAxpby()

```
cusparseStatus_t
cusparseAxpby(cusparseHandle_t    handle,
              const void*         alpha,
              cusparseSpVecDescr_t vecX,
              const void*         beta,
              cusparseDnVecDescr_t vecY)
```

The function computes the sum of a sparse vector `vecX` and a dense vector `vecY`

$$Y = \alpha X + \beta Y$$

In other words,

```
for i=0 to n-1
    Y[i] = beta * Y[i]
for i=0 to nnz-1
    Y[X_indices[i]] += alpha * X_values[i]
```

Param.	Memory	In/out	Meaning
handle	HOST	IN	Handle to the cuSPARSE library context
alpha	HOST or DEVICE	IN	α scalar used for multiplication of compute type
vecX	HOST	IN	Sparse vector x
beta	HOST or DEVICE	IN	β scalar used for multiplication of compute type
vecY	HOST	IN/OUT	Dense vector y

`cusparseAxpby` supports the following index type for representing the sparse vector `vecX`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

`cusparseAxpby` supports the following data types:

Uniform-precision computation:

x/y/compute
CUDA_R_32F
CUDA_R_64F
CUDA_C_32F
CUDA_C_64F

Mixed-precision computation:

x/y	compute
CUDA_R_16F	CUDA_R_32F
CUDA_R_16BF	
CUDA_C_16F	CUDA_C_32F
CUDA_C_16BF	

cusparseAxpby() has the following constraints:

- ▶ The arrays representing the sparse vector `vecX` must be aligned to 16 bytes

cusparseAxpby() has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ Provides deterministic (bit-wise) results for each run if the the sparse vector `vecX` indices are distinct

cusparseAxpby() supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseAxpby](#) for a code example.

15.6.4. cusparseGather()

```
cusparseStatus_t
cusparseGather(cusparseHandle_t    handle,
               cusparseDnVecDescr_t vecY,
               cusparseSpVecDescr_t vecX)
```

The function gathers the elements of the dense vector `vecY` into the sparse vector `vecX`

In other words,

```
for i=0 to nnz-1
    X_values[i] = Y[X_indices[i]]
```

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>vecX</code>	HOST	OUT	Sparse vector x
<code>vecY</code>	HOST	IN	Dense vector Y

`cusparseGather` supports the following index type for representing the sparse vector `vecX`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

`cusparseGather` supports the following data types:

x/y
CUDA_R_16F
CUDA_R_16BF
CUDA_R_32F
CUDA_R_64F
CUDA_C_16F
CUDA_C_16BF
CUDA_C_32F
CUDA_C_64F

`cusparseGather()` has the following constraints:

- ▶ The arrays representing the sparse vector `vecX` must be aligned to 16 bytes

`cusparseGather()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ Provides deterministic (bit-wise) results for each run if the the sparse vector `vecX` indices are distinct

`cusparseGather()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [`cusparseStatus_t`](#) for the description of the return status

Please visit [cuSPARSE Library Samples - `cusparseGather`](#) for a code example.

15.6.5. `cusparseScatter()`

```
cusparseStatus_t
cusparseScatter(cusparseHandle_t    handle,
                cusparseSpVecDescr_t vecX,
                cusparseDnVecDescr_t vecY)
```

The function scatters the elements of the sparse vector `vecX` into the dense vector `vecY`

In other words,

```
for i=0 to nnz-1
    Y[X_indices[i]] = X_values[i]
```

Param.	Memory	In/out	Meaning
handle	HOST	IN	Handle to the cuSPARSE library context
vecX	HOST	IN	Sparse vector x
vecY	HOST	OUT	Dense vector y

`cusparseScatter` supports the following index type for representing the sparse vector `vecX`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

`cusparseScatter` supports the following data types:

x/y
<code>CUDA_R_16F</code>
<code>CUDA_R_16BF</code>
<code>CUDA_R_32F</code>
<code>CUDA_R_64F</code>
<code>CUDA_C_16F</code>
<code>CUDA_C_16BF</code>
<code>CUDA_C_32F</code>
<code>CUDA_C_64F</code>

`cusparseScatter()` has the following constraints:

- ▶ The arrays representing the sparse vector `vecX` must be aligned to 16 bytes

`cusparseScatter()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ Provides deterministic (bit-wise) results for each run if the the sparse vector `vecX` indices are distinct

`cusparseScatter()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [`cusparseStatus_t`](#) for the description of the return status

Please visit [cuSPARSE Library Samples - `cusparseScatter`](#) for a code example.

15.6.6. `cusparseRot()`

```
cusparseStatus_t
cusparseRot(cusparseHandle_t handle,
            const void* c_coeff,
            const void* s_coeff,
            cusparseSpVecDescr_t vecX,
            cusparseDnVecDescr_t vecY)
```

The function computes the Givens rotation matrix

$$G = \begin{bmatrix} c & s \\ -s & c \end{bmatrix}$$

to a sparse `vecX` and a dense vector `vecY`

In other words,

```
for i=0 to nnz-1
    Y[X_indices[i]] = c * Y[X_indices[i]] - s * X_values[i]
    X_values[i]     = c * X_values[i] + s * Y[X_indices[i]]
```

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>c_coeff</code>	HOST or DEVICE	IN	cosine element of the rotation matrix
<code>vecX</code>	HOST	IN/OUT	Sparse vector <code>x</code>
<code>s_coeff</code>	HOST or DEVICE	IN	sine element of the rotation matrix
<code>vecY</code>	HOST	IN/OUT	Dense vector <code>Y</code>

`cusparseRot` supports the following index type for representing the sparse vector `vecX`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

`cusparseRot` supports the following data types:

Uniform-precision computation:

x/y/compute
<code>CUDA_R_32F</code>
<code>CUDA_R_64F</code>
<code>CUDA_C_32F</code>
<code>CUDA_C_64F</code>

Mixed-precision computation:

x/y	compute
CUDA_R_16F	CUDA_R_32F
CUDA_R_16BF	
CUDA_C_16F	CUDA_C_32F
CUDA_C_16BF	

`cusparseRot()` has the following constraints:

- ▶ The arrays representing the sparse vector `vecX` must be aligned to 16 bytes

`cusparseRot()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ Provides deterministic (bit-wise) results for each run if the the sparse vector `vecX` indices are distinct

`cusparseRot()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseRot](#) for a code example.

15.6.7. `cusparseSpVV()`

```
cusparseStatus_t
cusparseSpVV_bufferSize(cusparseHandle_t    handle,
                        cusparseOperation_t  opX,
                        cusparseSpVecDescr_t vecX,
                        cusparseDnVecDescr_t vecY,
                        void*                result,
                        cudaDataType         computeType,
                        size_t*              bufferSize)
```

```
cusparseStatus_t
cusparseSpVV(cusparseHandle_t    handle,
             cusparseOperation_t  opX,
             cusparseSpVecDescr_t vecX,
             cusparseDnVecDescr_t vecY,
             void*                result,
             cudaDataType         computeType,
             void*                externalBuffer)
```

The function computes the inner dot product of a sparse vector `vecX` and a dense vector `vecY`

$$result = \mathbf{X}' \cdot \mathbf{Y}$$

In other words,

```
result = 0;
for i=0 to nnz-1
    result += X_values[i] * Y[X_indices[i]]
```

$$\text{op}(X) = \begin{cases} X & \text{if op}(X) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ \overline{X} & \text{if op}(X) == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

The function `cusparseSpVV_bufferSize()` returns the size of the workspace needed by `cusparseSpVV()`

Param.	Memory	In/out	Meaning
handle	HOST	IN	Handle to the cuSPARSE library context
opX	HOST	IN	Operation <code>op(X)</code> that is non-transpose or conjugate transpose
vecX	HOST	IN	Sparse vector <code>x</code>
vecY	HOST	IN	Dense vector <code>y</code>
result	HOST or DEVICE	OUT	The resulting dot product
computeType	HOST	IN	Datatype in which the computation is executed
bufferSize	HOST	OUT	Number of bytes of workspace needed by <code>cusparseSpVV</code>
externalBuffer	DEVICE	IN	Pointer to a workspace buffer of at least <code>bufferSize</code> bytes

`cusparseSpVV` supports the following index type for representing the sparse vector `vecX`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

The data types combinations currently supported for `cusparseSpVV` are listed below:

Uniform-precision computation:

x/y/computeType
CUDA_R_32F
CUDA_R_64F
CUDA_C_32F
CUDA_C_64F

Mixed-precision computation:

x/y	computeType/result
CUDA_R_8I	CUDA_R_32I
CUDA_R_8I	CUDA_R_32F
CUDA_R_16F	
CUDA_R_16BF	

x/y	computeType/result
CUDA_C_16F	CUDA_C_32F
CUDA_C_16BF	

`cusparseSpVV()` has the following constraints:

- ▶ The arrays representing the sparse vector `vecX` must be aligned to 16 bytes

`cusparseSpVV()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ Provides deterministic (bit-wise) results for each run if the the sparse vector `vecX` indices are distinct

`cusparseSpVV()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseSpVV](#) for a code example.

15.6.8. `cusparseSpMV()`

```
cusparseStatus_t
cusparseSpMV_bufferSize(cusparseHandle_t    handle,
                        cusparseOperation_t opA,
                        const void*         alpha,
                        cusparseSpMatDescr_t matA,
                        cusparseDnVecDescr_t vecX,
                        const void*         beta,
                        cusparseDnVecDescr_t vecY,
                        cudaDataType         computeType,
                        cusparseSpMValg_t    alg,
                        size_t*              bufferSize)
```

```
cusparseStatus_t
cusparseSpMV(cusparseHandle_t    handle,
             cusparseOperation_t opA,
             const void*         alpha,
             cusparseSpMatDescr_t matA,
             cusparseDnVecDescr_t vecX,
             const void*         beta,
             cusparseDnVecDescr_t vecY,
             cudaDataType         computeType,
             cusparseSpMValg_t    alg,
             void*                externalBuffer)
```

This function performs the multiplication of a sparse matrix `matA` and a dense vector `vecX`

$$Y = \alpha op(A) \cdot X + \beta Y$$

where

- ▶ `op(A)` is a sparse matrix of size $m \times k$
- ▶ `x` is a dense vector of size k
- ▶ `y` is a dense vector of size m
- ▶ α and β are scalars

Also, for matrix `A`

$$op(A) = \begin{cases} A & \text{if } op(A) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if } op(A) == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if } op(A) == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

The function `cusparseSpMV_bufferSize()` returns the size of the workspace needed by `cusparseSpMV()`

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>opA</code>	HOST	IN	Operation <code>op(A)</code>
<code>alpha</code>	HOST or DEVICE	IN	α scalar used for multiplication of type <code>computeType</code>
<code>matA</code>	HOST	IN	Sparse matrix <code>A</code>
<code>vecX</code>	HOST	IN	Dense vector <code>x</code>
<code>beta</code>	HOST or DEVICE	IN	β scalar used for multiplication of type <code>computeType</code>
<code>vecY</code>	HOST	IN/OUT	Dense vector <code>y</code>
<code>computeType</code>	HOST	IN	Datatype in which the computation is executed
<code>alg</code>	HOST	IN	Algorithm for the computation
<code>bufferSize</code>	HOST	OUT	Number of bytes of workspace needed by <code>cusparseSpMV</code>
<code>externalBuffer</code>	DEVICE	IN	Pointer to a workspace buffer of at least <code>bufferSize</code> bytes

The sparse matrix formats currently supported are listed below:

- ▶ `CUSPARSE_FORMAT_COO`
- ▶ `CUSPARSE_FORMAT_COO_AOS` [deprecated]
- ▶ `CUSPARSE_FORMAT_CSR`
- ▶ `CUSPARSE_FORMAT_CSC`

cusparseSpMV supports the following index type for representing the sparse matrix matA:

- ▶ 32-bit indices (CUSPARSE_INDEX_32I)
- ▶ 64-bit indices (CUSPARSE_INDEX_64I)

cusparseSpMV supports the following data types:

Uniform-precision computation:

A/x/ y/computeType
CUDA_R_32F
CUDA_R_64F
CUDA_C_32F
CUDA_C_64F

Mixed-precision computation:

A/x	y	computeType
CUDA_R_8I	CUDA_R_32I	CUDA_R_32I
CUDA_R_8I	CUDA_R_32F	CUDA_R_32F
CUDA_R_16F		
CUDA_R_16BF		
CUDA_R_16F		
CUDA_R_16BF	CUDA_R_16F	
CUDA_R_16BF	CUDA_R_16BF	
CUDA_C_32F	CUDA_C_32F	CUDA_C_32F
CUDA_C_16F	CUDA_C_16F	
CUDA_C_16BF	CUDA_C_16BF	

Mixed Regular/Complex computation:

A	x/y/computeType
CUDA_R_32F	CUDA_C_32F
CUDA_R_64F	CUDA_C_64F

NOTE: CUDA_R_16F, CUDA_R_16BF, CUDA_C_16F, and CUDA_C_16BF data types always imply mixed-precision computation.

cusparseSpMV () supports the following algorithms:

[D]: Deprecated

Algorithm	Notes
CUSPARSE_MV_ALG_DEFAULT [D]	Default algorithm for any sparse matrix format
CUSPARSE_SPMV_ALG_DEFAULT	

Algorithm	Notes
CUSPARSE_COOMV_ALG [D] CUSPARSE_SPMV_COO_ALG1	Default algorithm for COO sparse matrix format. May produce slightly different results during different runs with the same input parameters
CUSPARSE_SPMV_COO_ALG2	Provides deterministic (bit-wise) results for each run. If <code>opA != CUSPARSE_OPERATION_NON_TRANSPOSE</code> , it is identical to CUSPARSE_SPMV_COO_ALG1
CUSPARSE_CSRMV_ALG1 [D] CUSPARSE_SPMV_CSR_ALG1	Default algorithm for CSR/CSC sparse matrix format. May produce slightly different results during different runs with the same input parameters
CUSPARSE_CSRMV_ALG2 [D] CUSPARSE_SPMV_CSR_ALG2	Provides deterministic (bit-wise) results for each run. If <code>opA != CUSPARSE_OPERATION_NON_TRANSPOSE</code> , it is identical to CUSPARSE_SPMV_COO_ALG1

Performance notes:

- ▶ CUSPARSE_SPMV_COO_ALG1 and CUSPARSE_SPMV_CSR_ALG1 provide higher performance than CUSPARSE_SPMV_COO_ALG2 and CUSPARSE_SPMV_CSR_ALG2.
- ▶ In general, `opA == CUSPARSE_OPERATION_NON_TRANSPOSE` is 3x faster than `opA != CUSPARSE_OPERATION_NON_TRANSPOSE`.

`cusparseSpMV()` has the following properties:

- ▶ The routine requires extra storage for CSR/CSC format (all algorithms) and for COO format with CUSPARSE_SPMV_COO_ALG2 algorithm.
- ▶ Provides deterministic (bit-wise) results for each run only for CUSPARSE_SPMV_COO_ALG2 and CUSPARSE_SPMV_CSR_ALG2 algorithms, and `opA == CUSPARSE_OPERATION_NON_TRANSPOSE`.
- ▶ The routine supports asynchronous execution.

`cusparseSpMV()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseSpMV CSR](#) and [cusparseSpMV COO](#) for a code example.

15.6.9. cusparseSpSV()

```
cusparseStatus_t
cusparseSpSV_createDescr(cusparseSpSVDscr_t* spsvDescr);
cusparseStatus_t
```

```
cusparseSpSV_destroyDescr(cusparseSpSVDescr_t spsvDescr);
```

```
cusparseStatus_t
cusparseSpSV_bufferSize(cusparseHandle_t    handle,
                        cusparseOperation_t  opA,
                        const void*         alpha,
                        cusparseSpMatDescr_t matA,
                        cusparseDnVecDescr_t vecX,
                        cusparseDnVecDescr_t vecY,
                        cudaDataType        computeType,
                        cusparseSpSVALg_t    alg,
                        cusparseSpSVDescr_t spsvDescr,
                        size_t*             bufferSize)
```

```
cusparseStatus_t
cusparseSpSV_analysis(cusparseHandle_t    handle,
                      cusparseOperation_t  opA,
                      const void*         alpha,
                      cusparseSpMatDescr_t matA,
                      cusparseDnVecDescr_t vecX,
                      cusparseDnVecDescr_t vecY,
                      cudaDataType        computeType,
                      cusparseSpSVALg_t    alg,
                      cusparseSpSVDescr_t spsvDescr,
                      void*               externalBuffer)
```

```
cusparseStatus_t
cusparseSpSV_solve(cusparseHandle_t    handle,
                   cusparseOperation_t  opA,
                   const void*         alpha,
                   cusparseSpMatDescr_t matA,
                   cusparseDnVecDescr_t vecX,
                   cusparseDnVecDescr_t vecY,
                   cudaDataType        computeType,
                   cusparseSpSVALg_t    alg,
                   cusparseSpSVDescr_t spsvDescr)
```

The function solves a system of linear equations whose coefficients are represented in a sparse triangular matrix:

$$op(\mathbf{A}) \cdot \mathbf{Y} = \alpha \mathbf{X}$$

where

- ▶ $op(\mathbf{A})$ is a sparse square matrix of size $m \times m$
- ▶ \mathbf{x} is a dense vector of size m
- ▶ \mathbf{y} is a dense vector of size m
- ▶ α is a scalar

Also, for matrix \mathbf{A}

$$\text{op}(A) = \begin{cases} A & \text{if } \text{op}(A) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if } \text{op}(A) == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if } \text{op}(A) == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

The function `cusparseSpSV_bufferSize()` returns the size of the workspace needed by `cusparseSpSV_analysis()` and `cusparseSpSV_solve()`. The function `cusparseSpSV_analysis()` performs the analysis phase, while `cusparseSpSV_solve()` executes the solve phase for a sparse triangular linear system. The opaque data structure `spsvDescr` is used to share information among all functions.

The routine supports arbitrary sparsity for the input matrix, but only the upper or lower triangular part is taken into account in the computation.

NOTE: all parameters must be consistent across `cusparseSpSV` API calls and the matrix descriptions must not be modified between `cusparseSpSV_analysis()` and `cusparseSpSV_solve()`

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>opA</code>	HOST	IN	Operation <code>op(A)</code>
<code>alpha</code>	HOST or DEVICE	IN	α scalar used for multiplication of type <code>computeType</code>
<code>matA</code>	HOST	IN	Sparse matrix <code>A</code>
<code>vecX</code>	HOST	IN	Dense vector <code>x</code>
<code>vecY</code>	HOST	IN/OUT	Dense vector <code>y</code>
<code>computeType</code>	HOST	IN	Datatype in which the computation is executed
<code>alg</code>	HOST	IN	Algorithm for the computation
<code>bufferSize</code>	HOST	OUT	Number of bytes of workspace needed by <code>cusparseSpSV_analysis()</code> and <code>cusparseSpSV_solve()</code>
<code>externalBuffer</code>	DEVICE	IN	Pointer to a workspace buffer of at least <code>bufferSize</code> bytes. It is used by <code>cusparseSpSV_analysis</code> and <code>cusparseSpSV_solve()</code>
<code>spsvDescr</code>	HOST	IN/OUT	Opaque descriptor for storing internal data used across the three steps

The sparse matrix formats currently supported are listed below:

- ▶ `CUSPARSE_FORMAT_CSR`
- ▶ `CUSPARSE_FORMAT_COO`

The `cusparseSpSV()` supports the following shapes and properties:

- ▶ `CUSPARSE_FILL_MODE_LOWER` and `CUSPARSE_FILL_MODE_UPPER` fill modes
- ▶ `CUSPARSE_DIAG_TYPE_NON_UNIT` and `CUSPARSE_DIAG_TYPE_UNIT` diagonal types

The fill mode and diagonal type can be set by [`cusparseSpMatSetAttribute\(\)`](#)

`cusparseSpSV()` supports the following index type for representing the sparse matrix `matA`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

`cusparseSpSV()` supports the following data types:

Uniform-precision computation:

A/x/ y/computeType
<code>CUDA_R_32F</code>
<code>CUDA_R_64F</code>
<code>CUDA_C_32F</code>
<code>CUDA_C_64F</code>

`cusparseSpSV()` supports the following algorithms:

Algorithm	Notes
<code>CUSPARSE_SPSV_ALG_DEFAULT</code>	Default algorithm

`cusparseSpSV()` has the following properties:

- ▶ The routine requires extra storage for the analysis phase which is proportional to number of non-zero entries of the sparse matrix
- ▶ Provides deterministic (bit-wise) results for each run for the solving phase `cusparseSpSV_solve()`
- ▶ The routine supports asynchronous execution

`cusparseSpSV()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [`cusparseStatus_t`](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseSpSV CSR](#) and [cuSPARSE Library Samples - cusparseSpSV COO](#) for code examples.

15.6.10. `cusparseSpMM()`

```
cusparseStatus_t
cusparseSpMM_bufferSize(cusparseHandle_t    handle,
                        cusparseOperation_t opA,
                        cusparseOperation_t opB,
                        const void*         alpha,
                        cusparseSpMatDescr_t matA,
                        cusparseDnMatDescr_t matB,
                        const void*         beta,
```



```

    cusparseDnMatDescr_t matC,
    cudaDataType         computeType,
    cusparseSpMMAlg_t   alg,
    size_t*              bufferSize)

```

```

cusparseStatus_t
cusparseSpMM_preprocess(cusparseHandle_t   handle,
                        cusparseOperation_t opA,
                        cusparseOperation_t opB,
                        const void*        alpha,
                        cusparseSpMatDescr_t matA,
                        cusparseDnMatDescr_t matB,
                        const void*        beta,
                        cusparseDnMatDescr_t matC,
                        cudaDataType        computeType,
                        cusparseSpMMAlg_t   alg,
                        void*              externalBuffer)

```

```

cusparseStatus_t
cusparseSpMM(cusparseHandle_t   handle,
              cusparseOperation_t opA,
              cusparseOperation_t opB,
              const void*        alpha,
              cusparseSpMatDescr_t matA,
              cusparseDnMatDescr_t matB,
              const void*        beta,
              cusparseDnMatDescr_t matC,
              cudaDataType        computeType,
              cusparseSpMMAlg_t   alg,
              void*              externalBuffer)

```

The function performs the multiplication of a sparse matrix `matA` and a dense matrix `matB`

$$\mathbf{C} = \alpha \mathbf{op(A)} \cdot \mathbf{op(B)} + \beta \mathbf{C}$$

where

- ▶ `op(A)` is a sparse matrix of size $m \times k$
- ▶ `op(B)` is a dense matrix of size $k \times n$
- ▶ `C` is a dense matrix of size $m \times n$
- ▶ α and β are scalars

The routine can be also used to perform the multiplication of a dense matrix and a sparse matrix by switching the dense matrices layout:

$$\begin{aligned} \mathbf{C}_C &= \mathbf{B}_C \cdot \mathbf{A} + \beta \mathbf{C}_C \longrightarrow \\ \mathbf{C}_R &= \mathbf{A}^T \cdot \mathbf{B}_R + \beta \mathbf{C}_R \end{aligned}$$

where \mathbf{B}_C , \mathbf{C}_C indicate column-major layout, while \mathbf{B}_R , \mathbf{C}_R refer to row-major layout

Also, for matrix `A` and `B`

$$\text{op}(A) = \begin{cases} A & \text{if } \text{op}(A) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if } \text{op}(A) == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if } \text{op}(A) == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

$$\text{op}(B) = \begin{cases} B & \text{if } \text{op}(B) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ B^T & \text{if } \text{op}(B) == \text{CUSPARSE_OPERATION_TRANPOSE} \\ B^H & \text{if } \text{op}(B) == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

When using the (conjugate) transpose of the sparse matrix A , this routine may produce slightly different results during different runs with the same input parameters.

The function `cusparseSpMM_bufferSize()` returns the size of the workspace needed by `cusparseSpMM()`

The function `cusparseSpMM_preprocess()` can be called before `cusparseSpMM` to speedup the actual computation. It is useful when `cusparseSpMM` is called multiple times with the same sparsity pattern (`matA`). The values of the matrices (`matA`, `matB`, `matC`) can change arbitrarily. It provides performance advantages is used with `CUSPARSE_SPMM_CSR_ALG1` or `CUSPARSE_SPMM_CSR_ALG3`. For all other formats and algorithms have no effect.

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>opA</code>	HOST	IN	Operation $\text{op}(A)$
<code>opB</code>	HOST	IN	Operation $\text{op}(B)$
<code>alpha</code>	HOST or DEVICE	IN	α scalar used for multiplication of type <code>computeType</code>
<code>matA</code>	HOST	IN	Sparse matrix A
<code>matB</code>	HOST	IN	Dense matrix B
<code>beta</code>	HOST or DEVICE	IN	β scalar used for multiplication of type <code>computeType</code>
<code>matC</code>	HOST	IN/OUT	Dense matrix c
<code>computeType</code>	HOST	IN	Datatype in which the computation is executed
<code>alg</code>	HOST	IN	Algorithm for the computation
<code>bufferSize</code>	HOST	OUT	Number of bytes of workspace needed by <code>cusparseSpMM</code>
<code>externalBuffer</code>	DEVICE	IN	Pointer to workspace buffer of at least <code>bufferSize</code> bytes

`cusparseSpMM` supports the following sparse matrix formats:

- ▶ `CUSPARSE_FORMAT_COO`
- ▶ `CUSPARSE_FORMAT_CSR`
- ▶ `CUSPARSE_FORMAT_CSC`
- ▶ `CUSPARSE_FORMAT_BLOCKED_ELL`

(1) COO/CSR/CSC FORMATS

cusparseSpMM supports the following index type for representing the sparse matrix matA:

- ▶ 32-bit indices (CUSPARSE_INDEX_32I)
- ▶ 64-bit indices (CUSPARSE_INDEX_64I) except for CUSPARSE_SPMM_COO_ALG2 and CUSPARSE_SPMM_COO_ALG3

cusparseSpMM supports the following data types:

Uniform-precision computation:

A/B/ C/computeType
CUDA_R_32F
CUDA_R_64F
CUDA_C_32F
CUDA_C_64F

Mixed-precision computation:

A/B	C	computeType
CUDA_R_8I	CUDA_R_32I	CUDA_R_32I
CUDA_R_8I	CUDA_R_32F	CUDA_R_32F
CUDA_R_16F		
CUDA_R_16BF		
CUDA_R_16F		
CUDA_R_16BF	CUDA_R_16BF	CUDA_C_32F
CUDA_C_16F	CUDA_C_16F	
CUDA_C_16BF	CUDA_C_16BF	
CUDA_C_16BF	CUDA_C_16BF	

NOTE: CUDA_R_16F, CUDA_R_16BF, CUDA_C_16F, and CUDA_C_16BF data types always imply mixed-precision computation.

cusparseSpMM supports the following algorithms:

[D]: deprecated

Algorithm	Notes
CUSPARSE_MM_ALG_DEFAULT [D]	Default algorithm for any sparse matrix format
CUSPARSE_SPMM_ALG_DEFAULT	Algorithm 1 for COO sparse matrix format
CUSPARSE_COOMM_ALG1 [D]	▶ May provide better performance for small number of nnz
CUSPARSE_SPMM_COO_ALG1	▶ Provide the best performance with column-major layout
	▶ It supports batched computation

Algorithm	Notes
	<ul style="list-style-type: none"> ▶ May produce slightly different results during different runs with the same input parameters
<p>CUSPARSE_COOMM_ALG2 [D] CUSPARSE_SPMM_COO_ALG2</p>	<p>Algorithm 2 for COO sparse matrix format</p> <ul style="list-style-type: none"> ▶ It provides deterministic result ▶ In general, slower than Algorithm 1 ▶ It supports batched computation ▶ It requires additional memory ▶ It supports only column-major layout ▶ It does not support CUDA_R_16BF, CUDA_C_16F, and CUDA_C_16BF data types
<p>CUSPARSE_COOMM_ALG3 [D] CUSPARSE_SPMM_COO_ALG3</p>	<p>Algorithm 3 for COO sparse matrix format</p> <ul style="list-style-type: none"> ▶ May provide better performance for large number of nnz ▶ It supports only column-major layout ▶ May produce slightly different results during different runs with the same input parameters ▶ It does not support CUDA_R_16BF, CUDA_C_16F, and CUDA_C_16BF data types
<p>CUSPARSE_COOMM_ALG4 [D] CUSPARSE_SPMM_COO_ALG4</p>	<p>Algorithm 4 for COO sparse matrix format</p> <ul style="list-style-type: none"> ▶ Provide the best performance with row-major layout ▶ It supports batched computation ▶ May produce slightly different results during different runs with the same input parameters
<p>CUSPARSE_CSRMM_ALG1 [D] CUSPARSE_SPMM_CSR_ALG1</p>	<p>Algorithm 1 for CSR/CSC sparse matrix format</p> <ul style="list-style-type: none"> ▶ Provide the best performance with column-major layout ▶ It supports batched computation ▶ It requires additional memory ▶ May produce slightly different results during different runs with the same input parameters
<p>CUSPARSE_SPMM_CSR_ALG2</p>	<p>Algorithm 2 for CSR/CSC sparse matrix format</p> <ul style="list-style-type: none"> ▶ Provide the best performance with row-major layout ▶ It supports batched computation ▶ It requires additional memory

Algorithm	Notes
	<ul style="list-style-type: none"> ▶ May produce slightly different results during different runs with the same input parameters
CUSPARSE_SPMM_CSR_ALG3	<p>Algorithm 3 for CSR/CSC sparse matrix format</p> <ul style="list-style-type: none"> ▶ It provides deterministic result ▶ It requires additional memory ▶ It supports only <code>opA == CUSPARSE_OPERATION_NON_TRANSPOSE</code> (fallback to <code>CUSPARSE_SPMM_CSR_ALG2</code>) ▶ It does not support <code>CUDA_C_16F</code> and <code>CUDA_C_16BF</code> data types

Performance notes:

- ▶ Row-major layout provides higher performance than column-major
- ▶ `CUSPARSE_SPMM_COO_ALG4` and `CUSPARSE_SPMM_CSR_ALG2` should be used with row-major layout, while `CUSPARSE_SPMM_COO_ALG1`, `CUSPARSE_SPMM_COO_ALG2`, and `CUSPARSE_SPMM_COO_ALG3`, and `CUSPARSE_SPMM_CSR_ALG1` with column-major layout
- ▶ For `beta != 1`, the output matrix is scaled before the actual computation
- ▶ For `n == 1`, the routine uses `cusparseSpMV()` as fallback

`cusparseSpMM()` with `CUSPARSE_SPMM_COO_ALG1`, `CUSPARSE_SPMM_COO_ALG4`, `CUSPARSE_SPMM_CSR_ALG1`, and `CUSPARSE_SPMM_CSR_ALG2` support the following batch modes:

- ▶ $C_i = A \cdot B_i$
- ▶ $C_i = A_i \cdot B$
- ▶ $C_i = A_i \cdot B_i$

The number of batches and their strides can be set by using `cusparseCooSetStridedBatch`, `cusparseCsrSetStridedBatch`, and `cusparseDnMatSetStridedBatch`.

`cusparseSpMM()` has the following properties:

- ▶ The routine requires no extra storage for `CUSPARSE_SPMM_COO_ALG1`, `CUSPARSE_SPMM_COO_ALG3`, `CUSPARSE_SPMM_COO_ALG4`
- ▶ The routine supports asynchronous execution
- ▶ Provides deterministic (bit-wise) results for each run only for `CUSPARSE_SPMM_COO_ALG2` and `CUSPARSE_SPMM_CSR_ALG3` algorithms, and `opA == CUSPARSE_OPERATION_NON_TRANSPOSE`

`cusparseSpMM()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

Please visit [cuSPARSE Library Samples - cusparseSpMM CSR](#) and [cusparseSpMM COO](#) for a code example. For batched computation please visit [cusparseSpMM CSR Batched](#) and [cusparseSpMM COO Batched](#).

(2) BLOCKED-ELLPACK FORMAT

cusparseSpMM supports the following data types for CUSPARSE_FORMAT_BLOCKED_ELL format and the following GPU architectures for exploiting NVIDIA Tensor Cores:

A/B	C	computeType	opB	Compute Capability
CUDA_R_16F	CUDA_R_16F	CUDA_R_16F	N, T	≥ 70
CUDA_R_16F	CUDA_R_16F	CUDA_R_32F	N, T	≥ 70
CUDA_R_16F	CUDA_R_32F	CUDA_R_32F	N, T	≥ 70
CUDA_R_8I	CUDA_R_8I	CUDA_R_32I	N	≥ 75
CUDA_R_16BF	CUDA_R_16BF	CUDA_R_32F	N, T	≥ 80
CUDA_R_16BF	CUDA_R_32F	CUDA_R_32F	N, T	≥ 80
CUDA_R_32F	CUDA_R_32F	CUDA_R_32F	N, T	≥ 80
CUDA_R_64F	CUDA_R_64F	CUDA_R_64F	N, T	≥ 80

cusparseSpMM supports the following algorithms with CUSPARSE_FORMAT_BLOCKED_ELL format:

[D]: deprecated

Algorithm	Notes
CUSPARSE_MM_ALG_DEFAULT [D]	Default algorithm for any sparse matrix format
CUSPARSE_SPMM_ALG_DEFAULT	Default algorithm for Sparse-Matrix-Matrix
CUSPARSE_SPMM_BLOCKED_ELL_ALG_DEFAULT	Default algorithm for Blocked-ELL format

Performance notes:

- ▶ Blocked-ELL SpMM provides the best performance with Power-of-2 Block-Sizes
- ▶ Large Block-Sizes (e.g. ≥ 64) provide the best performance

The function has the following limitations:

- ▶ The pointer mode must be equal to CUSPARSE_POINTER_MODE_HOST
- ▶ Only opA == CUSPARSE_OPERATION_NON_TRANSPOSE is supported
- ▶ opB == CUSPARSE_OPERATION_CONJUGATE_TRANSPOSE is not supported

Please visit [cuSPARSE Library Samples - cusparseSpMM Blocked-ELL](#) for a code example.

See [cusparseStatus_t](#) for the description of the return status

15.6.11. cusparseSpMMOp()

```

cusparseStatus_t CUSPARSEAPI
cusparseSpMMOp_createPlan(cusparseHandle_t      handle,
                          cusparseSpMMOpPlan_t* plan,
                          cusparseOperation_t   opA,
                          cusparseOperation_t   opB,
                          cusparseSpMatDescr_t  matA,
                          cusparseDnMatDescr_t  matB,
                          cusparseDnMatDescr_t  matC,
                          cudaDataType          computeType,
                          cusparseSpMMOpAlg_t   alg,
                          const void*          addOperationNvvmBuffer,
                          size_t               addOperationBufferSize,
                          const void*          mulOperationNvvmBuffer,
                          size_t               mulOperationBufferSize,
                          const void*          epilogueNvvmBuffer,
                          size_t               epilogueBufferSize,
                          size_t*             SpMMWorkspaceSize)

cusparseStatus_t
cusparseSpMMOp_destroyPlan(cusparseSpMMOpPlan_t plan)

```

```

cusparseStatus_t
cusparseSpMMOp(cusparseSpMMOpPlan_t plan,
               void*                  externalBuffer)

```

NOTE 1: The routine requires CUDA driver $\geq 495.XX$ (CUDA 11.5).

NOTE 2: NVRTC is not currently available on Arm64 Android platforms

Experimental: The function performs the multiplication of a sparse matrix `matA` and a dense matrix `matB` with custom operators

$$C_{ij} = \text{epilogue}\left(\sum_k^{\oplus} \text{op}(A_{ik}) \otimes \text{op}(B_{kj}), C_{ij}\right)$$

where

- ▶ `op(A)` is a sparse matrix of size $m \times k$
- ▶ `op(B)` is a dense matrix of size $k \times n$
- ▶ `c` is a dense matrix of size $m \times n$
- ▶ \oplus , \otimes , and `epilogue` are custom **add**, **mul**, and **epilogue** operators respectively

Also, for matrix `A` and `B`

$$\text{op}(A) = \begin{cases} A & \text{if op}(A) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if op}(A) == \text{CUSPARSE_OPERATION_TRANPOSE} \end{cases}$$

$$\text{op}(B) = \begin{cases} B & \text{if op}(B) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ B^T & \text{if op}(B) == \text{CUSPARSE_OPERATION_TRANPOSE} \end{cases}$$

Only `opA == CUSPARSE_OPERATION_NON_TRANSPOSE` and `opB == CUSPARSE_OPERATION_NON_TRANSPOSE` is currently supported

The function `cusparseSpMMOp_createPlan()` returns the size of the workspace and the compiled kernel needed by `cusparseSpMMOp()`

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>opA</code>	HOST	IN	Operation <code>op</code> (A)
<code>opB</code>	HOST	IN	Operation <code>op</code> (B)
<code>matA</code>	HOST	IN	Sparse matrix A
<code>matB</code>	HOST	IN	Dense matrix B
<code>matC</code>	HOST	IN/OUT	Dense matrix C
<code>computeType</code>	HOST	IN	Datatype in which the computation is executed
<code>alg</code>	HOST	IN	Algorithm for the computation
<code>addOperationNvvmBuffer</code>	HOST	IN	Pointer to the NVVM buffer containing the custom add operator
<code>addOperationBufferSize</code>	HOST	IN	Size in bytes of <code>addOperationNvvmBuffer</code>
<code>mulOperationNvvmBuffer</code>	HOST	IN	Pointer to the NVVM buffer containing the custom mul operator
<code>mulOperationBufferSize</code>	HOST	IN	Size in bytes of <code>mulOperationNvvmBuffer</code>
<code>epilogueNvvmBuffer</code>	HOST	IN	Pointer to the NVVM buffer containing the custom epilogue operator
<code>epilogueBufferSize</code>	HOST	IN	Size in bytes of <code>epilogueNvvmBuffer</code>
<code>SpMMWorkspaceSize</code>	HOST	OUT	Number of bytes of workspace needed by <code>cusparseSpMMOp</code>

The operators must have the following signature and return type

```
__device__ <computetype> add_op(<computetype> value1, <computetype> value2);
__device__ <computetype> mul_op(<computetype> value1, <computetype> value2);
__device__ <computetype> epilogue(<computetype> value1, <computetype>
value2);
```

`<computetype>` is one of `float`, `double`, `cuComplex`, `cuDoubleComplex`, or `int`,

`cusparseSpMMOp` supports the following sparse matrix formats:

- ▶ `CUSPARSE_FORMAT_CSR`

`cusparseSpMMOp` supports the following index type for representing the sparse matrix `matA`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

`cusparseSpMMOp` supports the following data types:

Uniform-precision computation:

A/B/ C/computeType
CUDA_R_32F
CUDA_R_64F
CUDA_C_32F
CUDA_C_64F

Mixed-precision computation:

A/B	C	computeType
CUDA_R_8I	CUDA_R_32I	CUDA_R_32I
CUDA_R_8I	CUDA_R_32F	CUDA_R_32F
CUDA_R_16F		
CUDA_R_16BF		
CUDA_R_16F		
CUDA_R_16BF		
CUDA_R_16BF	CUDA_R_16BF	

`cusparseSpMMOp` supports the following algorithms:

Algorithm	Notes
CUSPARSE_SPMM_OP_ALG_Default	Default algorithm for any sparse matrix format

Performance notes:

- ▶ Row-major layout provides higher performance than column-major.

`cusparseSpMMOp()` has the following properties:

- ▶ The routine requires extra storage
- ▶ The routine supports asynchronous execution
- ▶ Provides deterministic (bit-wise) results for each run

`cusparseSpMMOp()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

Please visit [cuSPARSE Library Samples - cusparseSpMMOp](#)

See [cusparseStatus_t](#) for the description of the return status

15.6.12. `cusparseSpSM()`

```

cusparseStatus_t
cusparseSpSM_createDescr(cusparseSpSMDescr_t* spsmDescr);

cusparseStatus_t
cusparseSpSM_destroyDescr(cusparseSpSMDescr_t spsmDescr);

```

```

cusparseStatus_t
cusparseSpSM_bufferSize(cusparseHandle_t    handle,
                        cusparseOperation_t  opA,
                        cusparseOperation_t  opB,
                        const void*         alpha,
                        cusparseSpMatDescr_t matA,
                        cusparseDnMatDescr_t matB,
                        cusparseDnMatDescr_t matC,
                        cudaDataType        computeType,
                        cusparseSpSMAlg_t    alg,
                        cusparseSpSMDescr_t spsmDescr,
                        size_t*             bufferSize)

```

```

cusparseStatus_t
cusparseSpSM_analysis(cusparseHandle_t    handle,
                     cusparseOperation_t  opA,
                     cusparseOperation_t  opB,
                     const void*         alpha,
                     cusparseSpMatDescr_t matA,
                     cusparseDnMatDescr_t matB,
                     cusparseDnMatDescr_t matC,
                     cudaDataType        computeType,
                     cusparseSpSMAlg_t    alg,
                     cusparseSpSMDescr_t spsmDescr,
                     void*               externalBuffer)

```

```

cusparseStatus_t
cusparseSpSM_solve(cusparseHandle_t    handle,
                  cusparseOperation_t  opA,
                  cusparseOperation_t  opB,
                  const void*         alpha,
                  cusparseSpMatDescr_t matA,
                  cusparseDnMatDescr_t matB,
                  cusparseDnMatDescr_t matC,
                  cudaDataType        computeType,
                  cusparseSpSMAlg_t    alg,
                  cusparseSpSMDescr_t spsmDescr)

```

The function solves a system of linear equations whose coefficients are represented in a sparse triangular matrix:

$$op(A) \cdot C = \alpha op(B)$$

where

- ▶ $op(A)$ is a sparse square matrix of size $m \times m$
- ▶ $op(B)$ is a dense matrix of size $m \times n$
- ▶ C is a dense matrix of size $m \times n$

- α is a scalar

Also, for matrix A

$$\text{op}(A) = \begin{cases} A & \text{if op}(A) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ A^T & \text{if op}(A) == \text{CUSPARSE_OPERATION_TRANPOSE} \\ A^H & \text{if op}(A) == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

$$\text{op}(B) = \begin{cases} B & \text{if op}(B) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ B^T & \text{if op}(B) == \text{CUSPARSE_OPERATION_TRANPOSE} \end{cases}$$

The function `cusparseSpSM_bufferSize()` returns the size of the workspace needed by `cusparseSpSM_analysis()` and `cusparseSpSM_solve()`. The function `cusparseSpSM_analysis()` performs the analysis phase, while `cusparseSpSM_solve()` executes the solve phase for a sparse triangular linear system. The opaque data structure `spsmDescr` is used to share information among all functions.

The routine supports arbitrary sparsity for the input matrix, but only the upper or lower triangular part is taken into account in the computation.

`cusparseSpSM_bufferSize()` requires a buffer size for the analysis phase which is proportional to number of non-zero entries of the sparse matrix

The `externalBuffer` is stored into `spsmDescr` and used by `cusparseSpSM_solve()`. For this reason, the device memory buffer must be deallocated only after `cusparseSpSM_solve()`

NOTE: all parameters must be consistent across `cusparseSpSM` API calls and the matrix descriptions must not be modified between `cusparseSpSM_analysis()` and `cusparseSpSM_solve()`

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>opA</code>	HOST	IN	Operation <code>op(A)</code>
<code>opB</code>	HOST	IN	Operation <code>op(B)</code>
<code>alpha</code>	HOST or DEVICE	IN	α scalar used for multiplication of type <code>computeType</code>
<code>matA</code>	HOST	IN	Sparse matrix A
<code>matB</code>	HOST	IN	Dense matrix B
<code>matC</code>	HOST	IN/OUT	Dense matrix c
<code>computeType</code>	HOST	IN	Datatype in which the computation is executed
<code>alg</code>	HOST	IN	Algorithm for the computation
<code>bufferSize</code>	HOST	OUT	Number of bytes of workspace needed by <code>cusparseSpSM_analysis()</code> and <code>cusparseSpSM_solve()</code>
<code>externalBuffer</code>	DEVICE	IN	Pointer to a workspace buffer of at least <code>bufferSize</code> bytes. It is used by <code>cusparseSpSM_analysis</code> and <code>cusparseSpSM_solve()</code>

Param.	Memory	In/out	Meaning
spsmDescr	HOST	IN/OUT	Opaque descriptor for storing internal data used across the three steps

The sparse matrix formats currently supported are listed below:

- ▶ CUSPARSE_FORMAT_CSR
- ▶ CUSPARSE_FORMAT_COO

The `cusparseSpSM()` supports the following shapes and properties:

- ▶ CUSPARSE_FILL_MODE_LOWER and CUSPARSE_FILL_MODE_UPPER fill modes
- ▶ CUSPARSE_DIAG_TYPE_NON_UNIT and CUSPARSE_DIAG_TYPE_UNIT diagonal types

The fill mode and diagonal type can be set by `_cusparseSpMatSetAttribute()`

`cusparseSpSM()` supports the following index type for representing the sparse matrix `matA`:

- ▶ 32-bit indices (CUSPARSE_INDEX_32I)
- ▶ 64-bit indices (CUSPARSE_INDEX_64I)

`cusparseSpSM()` supports the following data types:

Uniform-precision computation:

A/B/ C/computeType
CUDA_R_32F
CUDA_R_64F
CUDA_C_32F
CUDA_C_64F

`cusparseSpSM()` supports the following algorithms:

Algorithm	Notes
CUSPARSE_SPSM_ALG_DEFAULT	Default algorithm

`cusparseSpSM()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ Provides deterministic (bit-wise) results for each run for the solving phase `cusparseSpSM_solve()`
- ▶ The routine supports asynchronous execution

`cusparseSpSM()` supports the following optimizations:

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See `cusparseStatus_t` for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseSpSM CSR](#) and [cuSPARSE Library Samples - cusparseSpSM COO](#) for code examples.

15.6.13. cusparseConstrainedGeMM() [DEPRECATED]

[DEPRECATED] use [cusparseSDDMM\(\)](#) instead. *The routine will be removed in the next major release*

```

cusparseStatus_t
cusparseConstrainedGeMM(cusparseHandle_t      handle,
                        cusparseOperation_t   opA,
                        cusparseOperation_t   opB,
                        const void*           alpha,
                        cusparseDnMatDescr_t  matA,
                        cusparseDnMatDescr_t  matB,
                        const void*           beta,
                        cusparseSpMatDescr_t   matC,
                        cudaDataType          computeType,
                        void*                  externalBuffer)

cusparseStatus_t
cusparseConstrainedGeMM_bufferSize(cusparseHandle_t      handle,
                                   cusparseOperation_t   opA,
                                   cusparseOperation_t   opB,
                                   const void*           alpha,
                                   cusparseDnMatDescr_t  matA,
                                   cusparseDnMatDescr_t  matB,
                                   const void*           beta,
                                   cusparseSpMatDescr_t  matC,
                                   cudaDataType          computeType,
                                   size_t*               bufferSize)

```

The function has the same behavior of [cusparseSDDMM\(\)](#).

15.6.14. cusparseSDDMM()

```

cusparseStatus_t
cusparseSDDMM_bufferSize(cusparseHandle_t      handle,
                          cusparseOperation_t   opA,
                          cusparseOperation_t   opB,
                          const void*           alpha,
                          cusparseDnMatDescr_t  matA,
                          cusparseDnMatDescr_t  matB,
                          const void*           beta,
                          cusparseSpMatDescr_t  matC,
                          cudaDataType          computeType,
                          cusparseSDDMMAlg_t    alg,
                          size_t*               bufferSize)

```

```

cusparseStatus_t
cusparseSDDMM_preprocess(cusparseHandle_t      handle,

```

```

    cusparseOperation_t  opA,
    cusparseOperation_t  opB,
    const void*          alpha,
    cusparseDnMatDescr_t matA,
    cusparseDnMatDescr_t matB,
    const void*          beta,
    cusparseSpMatDescr_t matC,
    cudaDataType         computeType,
    cusparseSDDMMAlg_t   alg,
    void*                externalBuffer)

```

```

cusparseStatus_t
cusparseSDDMM(cusparseHandle_t  handle,
              cusparseOperation_t opA,
              cusparseOperation_t opB,
              const void*        alpha,
              cusparseDnMatDescr_t matA,
              cusparseDnMatDescr_t matB,
              const void*        beta,
              cusparseSpMatDescr_t matC,
              cudaDataType        computeType,
              cusparseSDDMMAlg_t  alg,
              void*              externalBuffer)

```

This function performs the multiplication of `matA` and `matB`, followed by an element-wise multiplication with the sparsity pattern of `matC`. Formally, it performs the following operation:

$$\mathbf{C} = \alpha(\text{op}(\mathbf{A}) \cdot \text{op}(\mathbf{B})) \circ \text{spy}(\mathbf{C}) + \beta \mathbf{C}$$

where

- ▶ `op(A)` is a dense matrix of size $m \times k$
- ▶ `op(B)` is a dense matrix of size $k \times n$
- ▶ `c` is a sparse matrix of size $m \times n$
- ▶ α and β are scalars
- ▶ \circ denotes the Hadamard (entry-wise) matrix product, and `spy(C)` is the sparsity pattern matrix of `c` defined as:

$$\text{spy}(\mathbf{C})_{ij} = \begin{cases} 0 & \text{if } \mathbf{C}_{ij} = 0 \\ 1 & \text{otherwise} \end{cases}$$

Also, for matrix `A` and `B`

$$\text{op}(\mathbf{A}) = \begin{cases} \mathbf{A} & \text{if } \text{op}(\mathbf{A}) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ \mathbf{A}^T & \text{if } \text{op}(\mathbf{A}) == \text{CUSPARSE_OPERATION_TRANPOSE} \\ \mathbf{A}^H & \text{if } \text{op}(\mathbf{A}) == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

$$\text{op}(\mathbf{B}) = \begin{cases} \mathbf{B} & \text{if } \text{op}(\mathbf{B}) == \text{CUSPARSE_OPERATION_NON_TRANPOSE} \\ \mathbf{B}^T & \text{if } \text{op}(\mathbf{B}) == \text{CUSPARSE_OPERATION_TRANPOSE} \\ \mathbf{B}^H & \text{if } \text{op}(\mathbf{B}) == \text{CUSPARSE_OPERATION_CONJUGATE_TRANPOSE} \end{cases}$$

CUSPARSE_OPERATION_CONJUGATE_TRANSPOSE is currently not supported.

The function `cusparseSDDMM_bufferSize()` returns the size of the workspace needed by `cusparseSDDMM` or `cusparseSDDMM_preprocess`.

The function `cusparseSDDMM_preprocess()` can be called before `cusparseSDDMM` to speedup the actual computation. It is useful when `cusparseSDDMM` is called multiple times with the same sparsity pattern (`matC`). The values of the dense matrices (`matA`, `matB`) can change arbitrarily.

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>opA</code>	HOST	IN	Operation <code>op</code> (A)
<code>opB</code>	HOST	IN	Operation <code>op</code> (B)
<code>alpha</code>	HOST or DEVICE	IN	α scalar used for multiplication of type <code>computeType</code>
<code>matA</code>	HOST	IN	Dense matrix <code>matA</code>
<code>matB</code>	HOST	IN	Dense matrix <code>matB</code>
<code>beta</code>	HOST or DEVICE	IN	β scalar used for multiplication of type <code>computeType</code>
<code>matC</code>	HOST	IN/OUT	Sparse matrix <code>matC</code>
<code>computeType</code>	HOST	IN	Datatype in which the computation is executed
<code>alg</code>	HOST	IN	Algorithm for the computation
<code>bufferSize</code>	HOST	OUT	Number of bytes of workspace needed by <code>cusparseSDDMM</code>
<code>externalBuffer</code>	DEVICE	IN	Pointer to a workspace buffer of at least <code>bufferSize</code> bytes

Currently supported sparse matrix formats:

- ▶ `CUSPARSE_FORMAT_CSR`

`cusparseSpSV()` supports the following index type for representing the sparse matrix `matA`:

- ▶ 32-bit indices (`CUSPARSE_INDEX_32I`)
- ▶ 64-bit indices (`CUSPARSE_INDEX_64I`)

The data types combinations currently supported for `cusparseSDDMM` are listed below :

Uniform-precision computation:

A/x/ y/computeType
CUDA_R_32F
CUDA_R_64F
CUDA_C_32F
CUDA_C_64F

`cusparseSpSV()` supports the following algorithms:

Algorithm	Notes
CUSPARSE_SDDMM_ALG_DEFAULT	Default algorithm

`cusparseSDDMM()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ Provides deterministic (bit-wise) results for each run
- ▶ The routine supports asynchronous execution

`cusparseSDDMM()` supports the following [optimizations](#):

- ▶ CUDA graph capture
- ▶ Hardware Memory Compression

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseSDDMM](#) for a code example.

15.6.15. `cusparseSpGEMM()`

```
cusparseStatus_t
cusparseSpGEMM_createDescr(cusparseSpGEMMDescr_t* descr)
```

```
cusparseStatus_t
cusparseSpGEMM_destroyDescr(cusparseSpGEMMDescr_t descr)
```

```
cusparseStatus_t
cusparseSpGEMM_workEstimation(cusparseHandle_t      handle,
                               cusparseOperation_t  opA,
                               cusparseOperation_t  opB,
                               const void*          alpha,
                               cusparseSpMatDescr_t  matA,
                               cusparseSpMatDescr_t  matB,
                               const void*          beta,
                               cusparseSpMatDescr_t  matC,
                               cudaDataType          computeType,
                               cusparseSpGEMMAlg_t   alg,
                               cusparseSpGEMMDescr_t spgemmDescr,
                               size_t*              bufferSize1,
                               void*                 externalBuffer1)
```

```
cusparseStatus_t
cusparseSpGEMM_compute(cusparseHandle_t      handle,
                       cusparseOperation_t  opA,
                       cusparseOperation_t  opB,
                       const void*          alpha,
                       cusparseSpMatDescr_t  matA,
                       cusparseSpMatDescr_t  matB,
                       const void*          beta,
                       cusparseSpMatDescr_t  matC,
                       cudaDataType          computeType,
```



```

        cusparseSpGEMMAlg_t    alg,
        cusparseSpGEMMDescr_t spgemmDescr,
        void*                  externalBuffer1,
        size_t*                bufferSize2,
        void*                  externalBuffer2)

cusparseStatus_t
cusparseSpGEMM_copy (cusparseHandle_t    handle,
                    cusparseOperation_t  opA,
                    cusparseOperation_t  opB,
                    const void*          alpha,
                    cusparseSpMatDescr_t matA,
                    cusparseSpMatDescr_t matB,
                    const void*          beta,
                    cusparseSpMatDescr_t matC,
                    cudaDataType         computeType,
                    cusparseSpGEMMAlg_t  alg,
                    cusparseSpGEMMDescr_t spgemmDescr)

```

This function performs the multiplication of two sparse matrices `matA` and `matB`

$$C = \alpha op(A) \cdot op(B) + \beta C$$

where α and β are scalars.

The functions `cusparseSpGEMM_workEstimation()` and `cusparseSpGEMM_compute()` are used for both determining the buffer size and performing the actual computation

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>opA</code>	HOST	IN	Operation <code>op</code> (A)
<code>opB</code>	HOST	IN	Operation <code>op</code> (B)
<code>alpha</code>	HOST or DEVICE	IN	α scalar used for multiplication
<code>matA</code>	HOST	IN	Sparse matrix A
<code>matB</code>	HOST	IN	Sparse matrix B
<code>beta</code>	HOST or DEVICE	IN	β scalar used for multiplication
<code>matC</code>	HOST	IN/OUT	Sparse matrix c
<code>computeType</code>	HOST	IN	Enumerator specifying the datatype in which the computation is executed
<code>alg</code>	HOST	IN	Enumerator specifying the algorithm for the computation
<code>spgemmDescr</code>	HOST	IN/OUT	Opaque descriptor for storing internal data used across the three steps
<code>bufferSize1</code>	HOST	IN/OUT	Number of bytes of workspace requested by <code>cusparseSpGEMM_workEstimation</code>
<code>bufferSize2</code>	HOST	IN/OUT	Number of bytes of workspace requested by <code>cusparseSpGEMM_compute</code>

Param.	Memory	In/out	Meaning
externalBuffer	DEVICE	IN	Pointer to workspace buffer needed by <code>cusparseSpGEMM_workEstimation</code> and <code>cusparseSpGEMM_compute</code>
externalBuffer	DEVICE	IN	Pointer to workspace buffer needed by <code>cusparseSpGEMM_compute</code> and <code>cusparseSpGEMM_copy</code>

MEMORY REQUIREMENT: the first invocation of `cusparseSpGEMM_compute` provides an *upper bound* of the memory required for the computation that is generally several times larger of the actual memory used. The user can provide an arbitrary buffer size `bufferSize2` in the second invocation. If it is not sufficient, the routine will return `CUSPARSE_STATUS_INSUFFICIENT_RESOURCES` status.

Currently, the function has the following limitations:

- ▶ Only 32-bit indices `CUSPARSE_INDEX_32I` is supported
- ▶ Only CSR format `CUSPARSE_FORMAT_CSR` is supported
- ▶ Only `opA`, `opB` equal to `CUSPARSE_OPERATION_NON_TRANSPOSE` are supported

The data types combinations currently supported for `cusparseSpGEMM` are listed below :

Uniform-precision computation:

A/B/C/computeType
CUDA_R_16F
CUDA_R_16BF
CUDA_R_32F
CUDA_R_64F
CUDA_C_16F
CUDA_C_16BF
CUDA_C_32F
CUDA_C_64F

`cusparseSpGEMM` routine runs for the following algorithm:

Algorithm	Notes
<code>CUSPARSE_SPGEMM_DEFAULT</code>	Default algorithm. Provides deterministic (bit-wise) results for each run

`cusparseSpGEMM()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports does **not** support CUDA graph capture

`cusparseSpGEMM()` supports the following [optimizations](#):

- ▶ Hardware Memory Compression

See [cusparseStatus_t](#) for the description of the return status

Please visit [cuSPARSE Library Samples - cusparseSpGEMM](#) for a code example.

15.6.16. cusparseSpGEMMreuse()

```
cusparseStatus_t
cusparseSpGEMM_createDescr(cusparseSpGEMMDescr_t* descr)
```

```
cusparseStatus_t
cusparseSpGEMM_destroyDescr(cusparseSpGEMMDescr_t descr)
```

```
cusparseStatus_t
cusparseSpGEMMreuse_workEstimation(cusparseHandle_t      handle,
                                     cusparseOperation_t  opA,
                                     cusparseOperation_t  opB,
                                     cusparseSpMatDescr_t matA,
                                     cusparseSpMatDescr_t matB,
                                     cusparseSpMatDescr_t matC,
                                     cusparseSpGEMMAlg_t  alg,
                                     cusparseSpGEMMDescr_t spgemmDescr,
                                     size_t*               bufferSize1,
                                     void*                externalBuffer1)
```

```
cusparseStatus_t
cusparseSpGEMMreuse_nnz(cusparseHandle_t      handle,
                         cusparseOperation_t  opA,
                         cusparseOperation_t  opB,
                         cusparseSpMatDescr_t matA,
                         cusparseSpMatDescr_t matB,
                         cusparseSpMatDescr_t matC,
                         cusparseSpGEMMAlg_t  alg,
                         cusparseSpGEMMDescr_t spgemmDescr,
                         size_t*               bufferSize2,
                         void*                externalBuffer2,
                         size_t*               bufferSize3,
                         void*                externalBuffer3,
                         size_t*               bufferSize4,
                         void*                externalBuffer4)
```

```
cusparseStatus_t CUSPARSEAPI
cusparseSpGEMMreuse_copy(cusparseHandle_t      handle,
                          cusparseOperation_t  opA,
                          cusparseOperation_t  opB,
                          cusparseSpMatDescr_t matA,
                          cusparseSpMatDescr_t matB,
                          cusparseSpMatDescr_t matC,
                          cusparseSpGEMMAlg_t  alg,
                          cusparseSpGEMMDescr_t spgemmDescr,
                          size_t*               bufferSize5,
                          void*                externalBuffer5)
```

```
cusparseStatus_t CUSPARSEAPI
cusparseSpGEMMreuse_compute(cusparseHandle_t      handle,
                             cusparseOperation_t  opA,
                             cusparseOperation_t  opB,
```

```

const void*      alpha,
cusparseSpMatDescr_t matA,
cusparseSpMatDescr_t matB,
const void*      beta,
cusparseSpMatDescr_t matC,
cudaDataType     computeType,
cusparseSpGEMMAlg_t alg,
cusparseSpGEMMDescr_t spgemmDescr)

```

This function performs the multiplication of two sparse matrices `matA` and `matB` where the structure of the output matrix `matC` can be reused for multiple computations with different values.

$$C' = \alpha op(A) \cdot op(B) + \beta C$$

where α and β are scalars.

The functions `cusparseSpGEMMreuse_workEstimation()`, `cusparseSpGEMMreuse_nnz()`, and `cusparseSpGEMMreuse_copy()` are used for determining the buffer size and performing the actual computation.

Param.	Memory	In/out	Meaning
<code>handle</code>	HOST	IN	Handle to the cuSPARSE library context
<code>opA</code>	HOST	IN	Operation <code>op</code> (A)
<code>opB</code>	HOST	IN	Operation <code>op</code> (B)
<code>alpha</code>	HOST or DEVICE	IN	α scalar used for multiplication
<code>matA</code>	HOST	IN	Sparse matrix A
<code>matB</code>	HOST	IN	Sparse matrix B
<code>beta</code>	HOST or DEVICE	IN	β scalar used for multiplication
<code>matC</code>	HOST	IN/OUT	Sparse matrix c
<code>computeType</code>	HOST	IN	Enumerator specifying the datatype in which the computation is executed
<code>alg</code>	HOST	IN	Enumerator specifying the algorithm for the computation
<code>spgemmDescr</code>	HOST	IN/OUT	Opaque descriptor for storing internal data used across the three steps
<code>bufferSize1</code>	HOST	IN/OUT	Number of bytes of workspace requested by <code>cusparseSpGEMMreuse_workEstimation</code>
<code>bufferSize2</code> <code>bufferSize3</code> <code>bufferSize4</code>	HOST	IN/OUT	Number of bytes of workspace requested by <code>cusparseSpGEMMreuse_nnz</code>
<code>bufferSize5</code>	HOST	IN/OUT	Number of bytes of workspace requested by <code>cusparseSpGEMMreuse_copy</code>
<code>externalBuffer</code>	DEVICE	IN	Pointer to workspace buffer needed by <code>cusparseSpGEMMreuse_workEstimation</code> and <code>cusparseSpGEMMreuse_nnz</code>

Param.	Memory	In/out	Meaning
externalBuffer1	DEVICE	IN	Pointer to workspace buffer needed by <code>cusparseSpGEMMreuse_nnz</code>
externalBuffer2	DEVICE	IN	Pointer to workspace buffer needed by <code>cusparseSpGEMMreuse_nnz</code> and <code>cusparseSpGEMMreuse_copy</code>
externalBuffer3	DEVICE	IN	Pointer to workspace buffer needed by <code>cusparseSpGEMMreuse_nnz</code> and <code>cusparseSpGEMMreuse_compute</code>
externalBuffer4	DEVICE	IN	Pointer to workspace buffer needed by <code>cusparseSpGEMMreuse_copy</code> and <code>cusparseSpGEMMreuse_compute</code>

MEMORY REQUIREMENT: `cusparseSpGEMMreuse` requires to keep in memory all intermediate products to reuse the structure of the output matrix. On the other hand, the number of intermediate products is orders of magnitude higher than the number of non-zero entries in general. In order to minimize the memory requirements, the routine uses multiple buffers that can be deallocated after they are no more needed. If the number of intermediate product exceeds $2^{31}-1$, the routine will return `CUSPARSE_STATUS_INSUFFICIENT_RESOURCES` status.

Currently, the function has the following limitations:

- ▶ Only 32-bit indices `CUSPARSE_INDEX_32I` is supported
- ▶ Only CSR format `CUSPARSE_FORMAT_CSR` is supported
- ▶ Only `opA`, `opB` equal to `CUSPARSE_OPERATION_NON_TRANSPOSE` are supported

The data types combinations currently supported for `cusparseSpGEMMreuse` are listed below :

Uniform-precision computation:

A/B/C/computeType
CUDA_R_32F
CUDA_R_64F
CUDA_C_16F
CUDA_C_16BF
CUDA_C_32F
CUDA_C_64F

Mixed-precision computation:

A/B	C	computeType
CUDA_R_16F	CUDA_R_16F	CUDA_R_32F
CUDA_R_16BF	CUDA_R_16BF	CUDA_R_32F

`cusparseSpGEMMreuse` routine runs for the following algorithm:

Algorithm	Notes
CUSPARSE_SPGEMM_DEFAULT CUSPARSE_SPGEMM_CSR_ALG_NONDETERMINISTIC	Default algorithm. Provides deterministic (bit-wise) structure for the output matrix for each run, while value computation is not deterministic
CUSPARSE_SPGEMM_CSR_ALG_DETERMINISTIC	Provides deterministic (bit-wise) structure for the output matrix and value computation for each run

`cusparseSpGEMMreuse()` has the following properties:

- ▶ The routine requires no extra storage
- ▶ The routine supports asynchronous execution
- ▶ The routine supports does **not** support CUDA graph capture

`cusparseSpGEMMreuse()` supports the following [optimizations](#):

- ▶ Hardware Memory Compression

See [`cusparseStatus_t`](#) for the description of the return status

Please visit [cuSPARSE Library Samples - `cusparseSpGEMMreuse`](#) for a code example.

Chapter 16. Appendix A: cuSPARSE Fortran Bindings

The cuSPARSE library is implemented using the C-based CUDA toolchain, and it thus provides a C-style API that makes interfacing to applications written in C or C++ trivial. There are also many applications implemented in Fortran that would benefit from using cuSPARSE, and therefore a cuSPARSE Fortran interface has been developed.

Unfortunately, Fortran-to-C calling conventions are not standardized and differ by platform and toolchain. In particular, differences may exist in the following areas:

- Symbol names (capitalization, name decoration)

- Argument passing (by value or reference)

- Passing of pointer arguments (size of the pointer)

To provide maximum flexibility in addressing those differences, the cuSPARSE Fortran interface is provided in the form of wrapper functions, which are written in C and are located in the file `cusparse_fortran.c`. This file also contains a few additional wrapper functions (for `cudaMalloc()`, `cudaMemset`, and so on) that can be used to allocate memory on the GPU.

The cuSPARSE Fortran wrapper code is provided as an example only and needs to be compiled into an application for it to call the cuSPARSE API functions. Providing this source code allows users to make any changes necessary for a particular platform and toolchain.

The cuSPARSE Fortran wrapper code has been used to demonstrate interoperability with the compilers g95 0.91 (on 32-bit and 64-bit Linux) and g95 0.92 (on 32-bit and 64-bit Mac OS X). In order to use other compilers, users have to make any changes to the wrapper code that may be required.

The direct wrappers, intended for production code, substitute device pointers for vector and matrix arguments in all cuSPARSE functions. To use these interfaces, existing applications need to be modified slightly to allocate and deallocate data structures in GPU memory space (using `CUDA_MALLOC()` and `CUDA_FREE()`) and to copy data between GPU and CPU memory spaces (using the `CUDA_MEMCPY()` routines). The sample wrappers provided in `cusparse_fortran.c` map device pointers to the OS-dependent type `size_t`, which is 32 bits wide on 32-bit platforms and 64 bits wide on a 64-bit platforms.

One approach to dealing with index arithmetic on device pointers in Fortran code is to use C-style macros and to use the C preprocessor to expand them. On Linux and Mac OS X, preprocessing can be done by using the option `'-cpp'` with g95 or gfortran. The function

GET_SHIFTED_ADDRESS(), provided with the cuSPARSE Fortran wrappers, can also be used, as shown in example B.

Example B shows the the C++ of example A implemented in Fortran 77 on the host. This example should be compiled with ARCH_64 defined as 1 on a 64-bit OS system and as undefined on a 32-bit OS system. For example, on g95 or gfortran, it can be done directly on the command line using the option `-cpp -DARCH_64=1`.

16.1. Fortran Application

```

c      #define ARCH_64 0
c      #define ARCH_64 1

      program cusparse_fortran_example
      implicit none
      integer cuda_malloc
      external cuda_free
      integer cuda_memcpy_c2fort_int
      integer cuda_memcpy_c2fort_real
      integer cuda_memcpy_fort2c_int
      integer cuda_memcpy_fort2c_real
      integer cuda_memset
      integer cusparse_create
      external cusparse_destroy
      integer cusparse_get_version
      integer cusparse_create_mat_descr
      external cusparse_destroy_mat_descr
      integer cusparse_set_mat_type
      integer cusparse_get_mat_type
      integer cusparse_get_mat_fill_mode
      integer cusparse_get_mat_diag_type
      integer cusparse_set_mat_index_base
      integer cusparse_get_mat_index_base
      integer cusparse_xcoo2csr
      integer cusparse_dsctr
      integer cusparse_dcsmv
      integer cusparse_dcsmm
      external get_shifted_address
#if ARCH_64
      integer*8 handle
      integer*8 descrA
      integer*8 cooRowIndex
      integer*8 cooColIndex
      integer*8 cooVal
      integer*8 xInd
      integer*8 xVal
      integer*8 y
      integer*8 z
      integer*8 csrRowPtr
      integer*8 ynp1
#else
      integer*4 handle
      integer*4 descrA
      integer*4 cooRowIndex
      integer*4 cooColIndex
      integer*4 cooVal
      integer*4 xInd
      integer*4 xVal
      integer*4 y
      integer*4 z
      integer*4 csrRowPtr
      integer*4 ynp1

```



```

#endif
integer status
integer cudaStat1,cudaStat2,cudaStat3
integer cudaStat4,cudaStat5,cudaStat6
integer n, nnz, nnz_vector
parameter (n=4, nnz=9, nnz_vector=3)
integer cooRowIndexHostPtr(nnz)
integer cooColIndexHostPtr(nnz)
real*8 cooValHostPtr(nnz)
integer xIndHostPtr(nnz_vector)
real*8 xValHostPtr(nnz_vector)
real*8 yHostPtr(2*n)
real*8 zHostPtr(2*(n+1))
integer i, j
integer version, mtype, fmode, dtype, ibase
real*8 dzero,dtwo,dthree,dfive
real*8 epsilon

write(*,*) "testing fortran example"

c predefined constants (need to be careful with them)
dzero = 0.0
dtwo = 2.0
dthree= 3.0
dfive = 5.0
c create the following sparse test matrix in COO format
c (notice one-based indexing)
c |1.0 2.0 3.0|
c | 4.0 |
c |5.0 6.0 7.0|
c | 8.0 9.0|
cooRowIndexHostPtr(1)=1
cooColIndexHostPtr(1)=1
cooValHostPtr(1) =1.0
cooRowIndexHostPtr(2)=1
cooColIndexHostPtr(2)=3
cooValHostPtr(2) =2.0
cooRowIndexHostPtr(3)=1
cooColIndexHostPtr(3)=4
cooValHostPtr(3) =3.0
cooRowIndexHostPtr(4)=2
cooColIndexHostPtr(4)=2
cooValHostPtr(4) =4.0
cooRowIndexHostPtr(5)=3
cooColIndexHostPtr(5)=1
cooValHostPtr(5) =5.0
cooRowIndexHostPtr(6)=3
cooColIndexHostPtr(6)=3
cooValHostPtr(6) =6.0
cooRowIndexHostPtr(7)=3
cooColIndexHostPtr(7)=4
cooValHostPtr(7) =7.0
cooRowIndexHostPtr(8)=4
cooColIndexHostPtr(8)=2
cooValHostPtr(8) =8.0
cooRowIndexHostPtr(9)=4
cooColIndexHostPtr(9)=4
cooValHostPtr(9) =9.0
c print the matrix
write(*,*) "Input data:"
do i=1,nnz
write(*,*) "cooRowIndexHostPtr[" ,i,"]=" ,cooRowIndexHostPtr(i)
write(*,*) "cooColIndexHostPtr[" ,i,"]=" ,cooColIndexHostPtr(i)
write(*,*) "cooValHostPtr[" , i,"]=" ,cooValHostPtr(i)
enddo

```

```

c      create a sparse and dense vector
c      xVal= [100.0 200.0 400.0]      (sparse)
c      xInd= [0      1      3      ]
c      y   = [10.0 20.0 30.0 40.0 | 50.0 60.0 70.0 80.0] (dense)
c      (notice one-based indexing)
      yHostPtr(1) = 10.0
      yHostPtr(2) = 20.0
      yHostPtr(3) = 30.0
      yHostPtr(4) = 40.0
      yHostPtr(5) = 50.0
      yHostPtr(6) = 60.0
      yHostPtr(7) = 70.0
      yHostPtr(8) = 80.0
      xIndHostPtr(1)=1
      xValHostPtr(1)=100.0
      xIndHostPtr(2)=2
      xValHostPtr(2)=200.0
      xIndHostPtr(3)=4
      xValHostPtr(3)=400.0
c      print the vectors
      do j=1,2
        do i=1,n
          write(*,*) "yHostPtr[" ,i ,",",j ,"]=" ,yHostPtr(i+n*(j-1))
        enddo
      enddo
      do i=1,nnz_vector
        write(*,*) "xIndHostPtr[" ,i ,"]=" ,xIndHostPtr(i)
        write(*,*) "xValHostPtr[" ,i ,"]=" ,xValHostPtr(i)
      enddo

c      allocate GPU memory and copy the matrix and vectors into it
c      cudaSuccess=0
c      cudaMemcpyHostToDevice=1
      cudaStat1 = cuda_malloc(cooRowIndex,nnz*4)
      cudaStat2 = cuda_malloc(cooColIndex,nnz*4)
      cudaStat3 = cuda_malloc(cooVal,      nnz*8)
      cudaStat4 = cuda_malloc(y,          2*n*8)
      cudaStat5 = cuda_malloc(xInd,nnz_vector*4)
      cudaStat6 = cuda_malloc(xVal,nnz_vector*8)
      if ((cudaStat1 /= 0) .OR.
$      (cudaStat2 /= 0) .OR.
$      (cudaStat3 /= 0) .OR.
$      (cudaStat4 /= 0) .OR.
$      (cudaStat5 /= 0) .OR.
$      (cudaStat6 /= 0)) then
        write(*,*) "Device malloc failed"
        write(*,*) "cudaStat1=",cudaStat1
        write(*,*) "cudaStat2=",cudaStat2
        write(*,*) "cudaStat3=",cudaStat3
        write(*,*) "cudaStat4=",cudaStat4
        write(*,*) "cudaStat5=",cudaStat5
        write(*,*) "cudaStat6=",cudaStat6
        stop 2
      endif
      cudaStat1 = cuda_memcpy_fort2c_int(cooRowIndex,cooRowIndexHostPtr,
$                                     nnz*4,1)
      cudaStat2 = cuda_memcpy_fort2c_int(cooColIndex,cooColIndexHostPtr,
$                                     nnz*4,1)
      cudaStat3 = cuda_memcpy_fort2c_real(cooVal,      cooValHostPtr,
$                                     nnz*8,1)
      cudaStat4 = cuda_memcpy_fort2c_real(y,          yHostPtr,
$                                     2*n*8,1)
      cudaStat5 = cuda_memcpy_fort2c_int(xInd,          xIndHostPtr,
$                                     nnz_vector*4,1)
      cudaStat6 = cuda_memcpy_fort2c_real(xVal,          xValHostPtr,
$                                     nnz_vector*8,1)
      if ((cudaStat1 /= 0) .OR.

```

```

$   (cudaStat2 /= 0) .OR.
$   (cudaStat3 /= 0) .OR.
$   (cudaStat4 /= 0) .OR.
$   (cudaStat5 /= 0) .OR.
$   (cudaStat6 /= 0) then
    write(*,*) "Memcpy from Host to Device failed"
    write(*,*) "cudaStat1=",cudaStat1
    write(*,*) "cudaStat2=",cudaStat2
    write(*,*) "cudaStat3=",cudaStat3
    write(*,*) "cudaStat4=",cudaStat4
    write(*,*) "cudaStat5=",cudaStat5
    write(*,*) "cudaStat6=",cudaStat6
    call cuda_free(cooRowIndex)
    call cuda_free(cooColIndex)
    call cuda_free(cooVal)
    call cuda_free(xInd)
    call cuda_free(xVal)
    call cuda_free(y)
    stop 1
endif

c   initialize cusparse library
c   CUSPARSE_STATUS_SUCCESS=0
status = cusparse_create(handle)
if (status /= 0) then
    write(*,*) "CUSPARSE Library initialization failed"
    call cuda_free(cooRowIndex)
    call cuda_free(cooColIndex)
    call cuda_free(cooVal)
    call cuda_free(xInd)
    call cuda_free(xVal)
    call cuda_free(y)
    stop 1
endif

c   get version
c   CUSPARSE_STATUS_SUCCESS=0
status = cusparse_get_version(handle,version)
if (status /= 0) then
    write(*,*) "CUSPARSE Library initialization failed"
    call cuda_free(cooRowIndex)
    call cuda_free(cooColIndex)
    call cuda_free(cooVal)
    call cuda_free(xInd)
    call cuda_free(xVal)
    call cuda_free(y)
    call cusparse_destroy(handle)
    stop 1
endif
write(*,*) "CUSPARSE Library version",version

c   create and setup the matrix descriptor
c   CUSPARSE_STATUS_SUCCESS=0
c   CUSPARSE_MATRIX_TYPE_GENERAL=0
c   CUSPARSE_INDEX_BASE_ONE=1
status= cusparse_create_mat_descr(descrA)
if (status /= 0) then
    write(*,*) "Creating matrix descriptor failed"
    call cuda_free(cooRowIndex)
    call cuda_free(cooColIndex)
    call cuda_free(cooVal)
    call cuda_free(xInd)
    call cuda_free(xVal)
    call cuda_free(y)
    call cusparse_destroy(handle)
    stop 1
endif
status = cusparse_set_mat_type(descrA,0)

```

```

      status = cusparse_set_mat_index_base(descrA,1)
c      print the matrix descriptor
      mtype = cusparse_get_mat_type(descrA)
      fmode = cusparse_get_mat_fill_mode(descrA)
      dtype = cusparse_get_mat_diag_type(descrA)
      ibase = cusparse_get_mat_index_base(descrA)
      write (*,*) "matrix descriptor:"
      write (*,*) "t=",mtype,"m=",fmode,"d=",dtype,"b=",ibase

c      exercise conversion routines (convert matrix from COO 2 CSR format)
c      cudaSuccess=0
c      CUSPARSE_STATUS_SUCCESS=0
c      CUSPARSE_INDEX_BASE_ONE=1
c      cudaStat1 = cuda_malloc(csrRowPtr, (n+1)*4)
      if (cudaStat1 /= 0) then
        call cuda_free(cooRowIndex)
        call cuda_free(cooColIndex)
        call cuda_free(cooVal)
        call cuda_free(xInd)
        call cuda_free(xVal)
        call cuda_free(y)
        call cusparse_destroy_mat_descr(descrA)
        call cusparse_destroy(handle)
        write(*,*) "Device malloc failed (csrRowPtr)"
        stop 2
      endif
      status= cusparse_xcoo2csr(handle,cooRowIndex,nnz,n,
$          csrRowPtr,1)
      if (status /= 0) then
        call cuda_free(cooRowIndex)
        call cuda_free(cooColIndex)
        call cuda_free(cooVal)
        call cuda_free(xInd)
        call cuda_free(xVal)
        call cuda_free(y)
        call cuda_free(csrRowPtr)
        call cusparse_destroy_mat_descr(descrA)
        call cusparse_destroy(handle)
        write(*,*) "Conversion from COO to CSR format failed"
        stop 1
      endif
c      csrRowPtr = [0 3 4 7 9]

c      exercise Level 1 routines (scatter vector elements)
c      CUSPARSE_STATUS_SUCCESS=0
c      CUSPARSE_INDEX_BASE ONE=1
      call get_shifted_address(y,n*8,ynp1)
      status= cusparse_dsctr(handle, nnz_vector, xVal, xInd,
$          ynp1, 1)
      if (status /= 0) then
        call cuda_free(cooRowIndex)
        call cuda_free(cooColIndex)
        call cuda_free(cooVal)
        call cuda_free(xInd)
        call cuda_free(xVal)
        call cuda_free(y)
        call cuda_free(csrRowPtr)
        call cusparse_destroy_mat_descr(descrA)
        call cusparse_destroy(handle)
        write(*,*) "Scatter from sparse to dense vector failed"
        stop 1
      endif
c      y = [10 20 30 40 | 100 200 70 400]

c      exercise Level 2 routines (csrvm)
c      CUSPARSE_STATUS_SUCCESS=0
c      CUSPARSE_OPERATION_NON_TRANSPOSE=0

```

```

status= cusparsv_dcsrmmv(handle, 0, n, n, nnz, dtwo,
$          descrA, cooVal, csrRowPtr, cooColIndex,
$          y, dthree, ynpl)
if (status /= 0) then
  call cuda_free(cooRowIndex)
  call cuda_free(cooColIndex)
  call cuda_free(cooVal)
  call cuda_free(xInd)
  call cuda_free(xVal)
  call cuda_free(y)
  call cuda_free(csrRowPtr)
  call cusparsv_destroy_mat_descr(descrA)
  call cusparsv_destroy(handle)
  write(*,*) "Matrix-vector multiplication failed"
  stop 1
endif

c   print intermediate results (y)
c   y = [10 20 30 40 | 680 760 1230 2240]
c   cudaSuccess=0
c   cudaMemcpyDeviceToHost=2
c   cudaStat1 = cuda_memcpy_c2fort_real(yHostPtr, y, 2*n*8, 2)
if (cudaStat1 /= 0) then
  call cuda_free(cooRowIndex)
  call cuda_free(cooColIndex)
  call cuda_free(cooVal)
  call cuda_free(xInd)
  call cuda_free(xVal)
  call cuda_free(y)
  call cuda_free(csrRowPtr)
  call cusparsv_destroy_mat_descr(descrA)
  call cusparsv_destroy(handle)
  write(*,*) "Memcpy from Device to Host failed"
  stop 1
endif
write(*,*) "Intermediate results:"
do j=1,2
  do i=1,n
    write(*,*) "yHostPtr["i","j"]="",yHostPtr(i+n*(j-1))
  enddo
enddo

c   exercise Level 3 routines (csrmm)
c   cudaSuccess=0
c   CUSPARSE_STATUS_SUCCESS=0
c   CUSPARSE_OPERATION_NON_TRANSPOSE=0
c   cudaStat1 = cuda_malloc(z, 2*(n+1)*8)
if (cudaStat1 /= 0) then
  call cuda_free(cooRowIndex)
  call cuda_free(cooColIndex)
  call cuda_free(cooVal)
  call cuda_free(xInd)
  call cuda_free(xVal)
  call cuda_free(y)
  call cuda_free(csrRowPtr)
  call cusparsv_destroy_mat_descr(descrA)
  call cusparsv_destroy(handle)
  write(*,*) "Device malloc failed (z)"
  stop 2
endif
cudaStat1 = cuda_memset(z, 0, 2*(n+1)*8)
if (cudaStat1 /= 0) then
  call cuda_free(cooRowIndex)
  call cuda_free(cooColIndex)
  call cuda_free(cooVal)
  call cuda_free(xInd)
  call cuda_free(xVal)

```

```

        call cuda_free(y)
        call cuda_free(z)
        call cuda_free(csrRowPtr)
        call cusparse_destroy_mat_descr(descrA)
        call cusparse_destroy(handle)
        write(*,*) "Memset on Device failed"
        stop 1
    endif
    status= cusparse_dcsrmm(handle, 0, n, 2, n, nnz, dfive,
$           descrA, cooVal, csrRowPtr, cooColIndex,
$           y, n, dzero, z, n+1)
    if (status /= 0) then
        call cuda_free(cooRowIndex)
        call cuda_free(cooColIndex)
        call cuda_free(cooVal)
        call cuda_free(xInd)
        call cuda_free(xVal)
        call cuda_free(y)
        call cuda_free(z)
        call cuda_free(csrRowPtr)
        call cusparse_destroy_mat_descr(descrA)
        call cusparse_destroy(handle)
        write(*,*) "Matrix-matrix multiplication failed"
        stop 1
    endif

c    print final results (z)
c    cudaSuccess=0
c    cudaMemcpyDeviceToHost=2
c    cudaStat1 = cuda_memcpy_c2fort_real(zHostPtr, z, 2*(n+1)*8, 2)
    if (cudaStat1 /= 0) then
        call cuda_free(cooRowIndex)
        call cuda_free(cooColIndex)
        call cuda_free(cooVal)
        call cuda_free(xInd)
        call cuda_free(xVal)
        call cuda_free(y)
        call cuda_free(z)
        call cuda_free(csrRowPtr)
        call cusparse_destroy_mat_descr(descrA)
        call cusparse_destroy(handle)
        write(*,*) "Memcpy from Device to Host failed"
        stop 1
    endif
c    z = [950 400 2550 2600 0 | 49300 15200 132300 131200 0]
    write(*,*) "Final results:"
    do j=1,2
        do i=1,n+1
            write(*,*) "z[" ,i, ", ",j, "]=", zHostPtr(i+(n+1)*(j-1))
        enddo
    enddo

c    check the results
    epsilon = 0.000000000000001
    if ((DABS(zHostPtr(1) - 950.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(2) - 400.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(3) - 2550.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(4) - 2600.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(5) - 0.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(6) - 49300.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(7) - 15200.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(8) - 132300.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(9) - 131200.0) .GT. epsilon) .OR.
$      (DABS(zHostPtr(10) - 0.0) .GT. epsilon) .OR.
$      (DABS(yHostPtr(1) - 10.0) .GT. epsilon) .OR.
$      (DABS(yHostPtr(2) - 20.0) .GT. epsilon) .OR.
$      (DABS(yHostPtr(3) - 30.0) .GT. epsilon) .OR.

```

```

$ (DABS(yHostPtr(4) - 40.0) .GT. epsilon) .OR.
$ (DABS(yHostPtr(5) - 680.0) .GT. epsilon) .OR.
$ (DABS(yHostPtr(6) - 760.0) .GT. epsilon) .OR.
$ (DABS(yHostPtr(7) - 1230.0) .GT. epsilon) .OR.
$ (DABS(yHostPtr(8) - 2240.0) .GT. epsilon) then
  write(*,*) "fortran example test FAILED"
else
  write(*,*) "fortran example test PASSED"
endif

c  deallocate GPU memory and exit
   call cuda_free(cooRowIndex)
   call cuda_free(cooColIndex)
   call cuda_free(cooVal)
   call cuda_free(xInd)
   call cuda_free(xVal)
   call cuda_free(y)
   call cuda_free(z)
   call cuda_free(csrRowPtr)
   call cusparse_destroy_mat_descr(descrA)
   call cusparse_destroy(handle)

   stop 0
end

```

Chapter 17. Appendix B: Examples of prune

17.1. Prune Dense to Sparse

This section provides a simple example in the C programming language of pruning a dense matrix to a sparse matrix of CSR format.

A is a 4x4 dense matrix,

$$A = \begin{pmatrix} 1.0 & 0.0 & 2.0 & -3.0 \\ 0.0 & 4.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 6.0 & 7.0 \\ 0.0 & 8.0 & 0.0 & 9.0 \end{pmatrix}$$

```
/*
 * How to compile (assume cuda is installed at /usr/local/cuda/)
 * nvcc -c -I/usr/local/cuda/include prunedense_example.cpp
 * g++ -o prunedense_example.cpp prunedense_example.o -L/usr/local/cuda/lib64 -
lcusparse -lcudart
 */
#include <stdio.h>
#include <stdlib.h>
#include <assert.h>
#include <cuda_runtime.h>
#include <cusparse.h>

void printMatrix(int m, int n, const float*A, int lda, const char* name)
{
    for(int row = 0 ; row < m ; row++){
        for(int col = 0 ; col < n ; col++){
            float Areg = A[row + col*lda];
            printf("%s(%d,%d) = %f\n", name, row+1, col+1, Areg);
        }
    }
}

void printCsr(
    int m,
    int n,
    int nnz,
    const cusparseMatDescr_t descrA,
    const float *csrValA,
    const int *csrRowPtrA,
    const int *csrColIndA,
```



```

    const char* name)
{
    const int base = (cusparseGetMatIndexBase(descrA) != CUSPARSE_INDEX_BASE_ONE)?
0:1 ;

    printf("matrix %s is %d-by-%d, nnz=%d, base=%d\n", name, m, n, nnz, base);
    for(int row = 0 ; row < m ; row++){
        const int start = csrRowPtrA[row ] - base;
        const int end   = csrRowPtrA[row+1] - base;
        for(int colidx = start ; colidx < end ; colidx++){
            const int col = csrColIndA[colidx] - base;
            const float Areg = csrValA[colidx];
            printf("%s(%d,%d) = %f\n", name, row+1, col+1, Areg);
        }
    }
}

int main(int argc, char*argv[])
{
    cusparseHandle_t handle = NULL;
    cudaStream_t stream = NULL;
    cusparseMatDescr_t descrC = NULL;

```

```

    cusparseStatus_t status = CUSPARSE_STATUS_SUCCESS;
    cudaError_t cudaStat1 = cudaSuccess;
    cudaError_t cudaStat2 = cudaSuccess;
    cudaError_t cudaStat3 = cudaSuccess;
    cudaError_t cudaStat4 = cudaSuccess;
    cudaError_t cudaStat5 = cudaSuccess;
    const int m = 4;
    const int n = 4;
    const int lda = m;
/*
 *      |   1   0   2   -3 |
 *      |   0   4   0   0  |
 *  A = |   5   0   6   7  |
 *      |   0   8   0   9  |
 *
 */
    const float A[lda*n] = {1, 0, 5, 0, 0, 4, 0, 8, 2, 0, 6, 0, -3, 0, 7, 9};
    int* csrRowPtrC = NULL;
    int* csrColIndC = NULL;
    float* csrValC = NULL;

    float *d_A = NULL;
    int *d_csrRowPtrC = NULL;
    int *d_csrColIndC = NULL;
    float *d_csrValC = NULL;

    size_t lworkInBytes = 0;
    char *d_work = NULL;

    int nnzC = 0;

    float threshold = 4.1; /* remove Aij <= 4.1 */
    // float threshold = 0; /* remove zeros */

    printf("example of pruneDense2csr \n");

    printf("prune |A(i,j)| <= threshold \n");
    printf("threshold = %E \n", threshold);

    printMatrix(m, n, A, lda, "A");

```

```

/* step 1: create cusparse handle, bind a stream */
cudaStat1 = cudaStreamCreateWithFlags(&stream, cudaStreamNonBlocking);
assert(cudaSuccess == cudaStat1);

status = cusparseCreate(&handle);
assert(CUSPARSE_STATUS_SUCCESS == status);

status = cusparseSetStream(handle, stream);
assert(CUSPARSE_STATUS_SUCCESS == status);

/* step 2: configuration of matrix C */
status = cusparseCreateMatDescr(&descrC);
assert(CUSPARSE_STATUS_SUCCESS == status);

cusparseSetMatIndexBase(descrC, CUSPARSE_INDEX_BASE_ZERO);
cusparseSetMatType(descrC, CUSPARSE_MATRIX_TYPE_GENERAL);

cudaStat1 = cudaMalloc((void**) &d_A, sizeof(float)*lda*n);
cudaStat2 = cudaMalloc((void**) &d_csrRowPtrC, sizeof(int)*(m+1));
assert(cudaSuccess == cudaStat1);
assert(cudaSuccess == cudaStat2);

/* step 3: query workspace */
cudaStat1 = cudaMemcpy(d_A, A, sizeof(float)*lda*n, cudaMemcpyHostToDevice);
assert(cudaSuccess == cudaStat1);

status = cusparseSpruneDense2csr_bufferSizeExt(
    handle,
    m,
    n,
    d_A,
    lda,
    &threshold,
    descrC,
    d_csrValC,
    d_csrRowPtrC,
    d_csrColIndC,
    &lworkInBytes);
assert(CUSPARSE_STATUS_SUCCESS == status);

printf("lworkInBytes (prune) = %lld \n", (long long)lworkInBytes);

if (NULL != d_work) { cudaFree(d_work); }
cudaStat1 = cudaMalloc((void**) &d_work, lworkInBytes);
assert(cudaSuccess == cudaStat1);

/* step 4: compute csrRowPtrC and nnzC */
status = cusparseSpruneDense2csrNnz(
    handle,
    m,
    n,
    d_A,
    lda,
    &threshold,
    descrC,
    d_csrRowPtrC,
    &nnzC, /* host */
    d_work);
assert(CUSPARSE_STATUS_SUCCESS == status);
cudaStat1 = cudaDeviceSynchronize();
assert(cudaSuccess == cudaStat1);

```

```

printf("nnzC = %d\n", nnzC);
if (0 == nnzC){
    printf("C is empty \n");
    return 0;
}

```

```

/* step 5: compute csrColIndC and csrValC */
cudaStat1 = cudaMalloc ((void**)&d_csrColIndC, sizeof(int ) * nnzC );
cudaStat2 = cudaMalloc ((void**)&d_csrValC , sizeof(float) * nnzC );
assert(cudaSuccess == cudaStat1);
assert(cudaSuccess == cudaStat2);

status = cusparseSpruneDense2csr(
    handle,
    m,
    n,
    d_A,
    lda,
    &threshold,
    descrC,
    d_csrValC,
    d_csrRowPtrC,
    d_csrColIndC,
    d_work);
assert(CUSPARSE_STATUS_SUCCESS == status);
cudaStat1 = cudaDeviceSynchronize();
assert(cudaSuccess == cudaStat1);

/* step 6: output C */
csrRowPtrC = (int* )malloc(sizeof(int )*(m+1));
csrColIndC = (int* )malloc(sizeof(int )*nnzC);
csrValC = (float*)malloc(sizeof(float)*nnzC);
assert( NULL != csrRowPtrC);
assert( NULL != csrColIndC);
assert( NULL != csrValC);

    cudaStat1 = cudaMemcpy(csrRowPtrC, d_csrRowPtrC, sizeof(int )*(m+1),
cudaMemcpyDeviceToHost);
    cudaStat2 = cudaMemcpy(csrColIndC, d_csrColIndC, sizeof(int )*nnzC ,
cudaMemcpyDeviceToHost);
    cudaStat3 = cudaMemcpy(csrValC , d_csrValC , sizeof(float)*nnzC ,
cudaMemcpyDeviceToHost);
    assert(cudaSuccess == cudaStat1);
    assert(cudaSuccess == cudaStat2);
    assert(cudaSuccess == cudaStat3);

    printCsr(m, n, nnzC, descrC, csrValC, csrRowPtrC, csrColIndC, "C");

/* free resources */
if (d_A ) cudaFree(d_A);
if (d_csrRowPtrC ) cudaFree(d_csrRowPtrC);
if (d_csrColIndC ) cudaFree(d_csrColIndC);
if (d_csrValC ) cudaFree(d_csrValC);

if (csrRowPtrC ) free(csrRowPtrC);
if (csrColIndC ) free(csrColIndC);
if (csrValC ) free(csrValC);

if (handle ) cusparseDestroy(handle);
if (stream ) cudaStreamDestroy(stream);
if (descrC ) cusparseDestroyMatDescr(descrC);

cudaDeviceReset();
return 0;
}

```

17.2. Prune Sparse to Sparse

This section provides a simple example in the C programming language of pruning a sparse matrix to a sparse matrix of CSR format.

A is a 4x4 sparse matrix,

$$A = \begin{pmatrix} 1.0 & 0.0 & 2.0 & -3.0 \\ 0.0 & 4.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 6.0 & 7.0 \\ 0.0 & 8.0 & 0.0 & 9.0 \end{pmatrix}$$

```

/*
 * How to compile (assume cuda is installed at /usr/local/cuda/)
 *   nvcc -c -I/usr/local/cuda/include prunecsr_example.cpp
 *   g++ -o prunecsr_example.cpp prunecsr_example.o -L/usr/local/cuda/lib64 -
 *   lcusparses -lcudart
 */
#include <stdio.h>
#include <stdlib.h>
#include <assert.h>
#include <cuda_runtime.h>
#include <cusparses.h>

void printCsr(
    int m,
    int n,
    int nnz,
    const cusparsesMatDescr_t descrA,
    const float *csrValA,
    const int *csrRowPtrA,
    const int *csrColIndA,
    const char* name)
{
    const int base = (cusparsesGetMatIndexBase(descrA) != CUSPARSE_INDEX_BASE_ONE)?
    0:1 ;

    printf("matrix %s is %d-by-%d, nnz=%d, base=%d, output base-1\n", name, m, n,
    nnz, base);
    for(int row = 0 ; row < m ; row++){
        const int start = csrRowPtrA[row ] - base;
        const int end   = csrRowPtrA[row+1] - base;
        for(int colidx = start ; colidx < end ; colidx++){
            const int col = csrColIndA[colidx] - base;
            const float Areg = csrValA[colidx];
            printf("%s(%d,%d) = %f\n", name, row+1, col+1, Areg);
        }
    }
}

int main(int argc, char*argv[])
{
    cusparsesHandle_t handle = NULL;
    cudaStream_t stream = NULL;
    cusparsesMatDescr_t descrA = NULL;
    cusparsesMatDescr_t descrC = NULL;

    cusparsesStatus_t status = CUSPARSE_STATUS_SUCCESS;
    cudaError_t cudaStat1 = cudaSuccess;
    const int m = 4;

```

```

const int n = 4;
const int nnzA = 9;
/*
 *      |   1   0   2   -3 |
 *      |   0   4   0   0 |
 *  A = |   5   0   6   7 |
 *      |   0   8   0   9 |
 *
 */

```

```

const int csrRowPtrA[m+1] = { 1, 4, 5, 8, 10};
const int csrColIndA[nnzA] = { 1, 3, 4, 2, 1, 3, 4, 2, 4};
const float csrValA[nnzA] = {1, 2, -3, 4, 5, 6, 7, 8, 9};

int* csrRowPtrC = NULL;
int* csrColIndC = NULL;
float* csrValC = NULL;

int *d_csrRowPtrA = NULL;
int *d_csrColIndA = NULL;
float *d_csrValA = NULL;

int *d_csrRowPtrC = NULL;
int *d_csrColIndC = NULL;
float *d_csrValC = NULL;

size_t lworkInBytes = 0;
char *d_work = NULL;

int nnzC = 0;

float threshold = 4.1; /* remove Aij <= 4.1 */
// float threshold = 0; /* remove zeros */

printf("example of pruneCsr2csr \n");

printf("prune |A(i,j)| <= threshold \n");
printf("threshold = %E \n", threshold);

/* step 1: create cusparse handle, bind a stream */
cudaStat1 = cudaStreamCreateWithFlags(&stream, cudaStreamNonBlocking);
assert(cudaSuccess == cudaStat1);

status = cusparseCreate(&handle);
assert(CUSPARSE_STATUS_SUCCESS == status);

status = cusparseSetStream(handle, stream);
assert(CUSPARSE_STATUS_SUCCESS == status);

/* step 2: configuration of matrix A and C */
status = cusparseCreateMatDescr(&descrA);
assert(CUSPARSE_STATUS_SUCCESS == status);
/* A is base-1 */
cusparseSetMatIndexBase(descrA, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descrA, CUSPARSE_MATRIX_TYPE_GENERAL );

status = cusparseCreateMatDescr(&descrC);
assert(CUSPARSE_STATUS_SUCCESS == status);
/* C is base-0 */
cusparseSetMatIndexBase(descrC, CUSPARSE_INDEX_BASE_ZERO);
cusparseSetMatType(descrC, CUSPARSE_MATRIX_TYPE_GENERAL );

printCsr(m, n, nnzA, descrA, csrValA, csrRowPtrA, csrColIndA, "A");

```

```

    cudaStat1 = cudaMalloc ((void*)&d_csrRowPtrA, sizeof(int)*(m+1) );
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMalloc ((void*)&d_csrColIndA, sizeof(int)*nnzA );
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMalloc ((void*)&d_csrValA , sizeof(float)*nnzA );
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMalloc ((void*)&d_csrRowPtrC, sizeof(int)*(m+1) );
    assert(cudaSuccess == cudaStat1);

    cudaStat1 = cudaMemcpy(d_csrRowPtrA, csrRowPtrA, sizeof(int)*(m+1),
        cudaMemcpyHostToDevice);
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMemcpy(d_csrColIndA, csrColIndA, sizeof(int)*nnzA,
        cudaMemcpyHostToDevice);
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMemcpy(d_csrValA , csrValA , sizeof(float)*nnzA,
        cudaMemcpyHostToDevice);
    assert(cudaSuccess == cudaStat1);

/* step 3: query workspace */
    status = cusparseSpruneCsr2csr_bufferSizeExt(
        handle,
        m,
        n,
        nnzA,
        descrA,
        d_csrValA,
        d_csrRowPtrA,
        d_csrColIndA,
        &threshold,
        descrC,
        d_csrValC,
        d_csrRowPtrC,
        d_csrColIndC,
        &lworkInBytes);
    assert(CUSPARSE_STATUS_SUCCESS == status);

    printf("lworkInBytes (prune) = %lld \n", (long long)lworkInBytes);

    if (NULL != d_work) { cudaFree(d_work); }
    cudaStat1 = cudaMalloc((void*)&d_work, lworkInBytes);
    assert(cudaSuccess == cudaStat1);

/* step 4: compute csrRowPtrC and nnzC */
    status = cusparseSpruneCsr2csrNnz(
        handle,
        m,
        n,
        nnzA,
        descrA,
        d_csrValA,
        d_csrRowPtrA,
        d_csrColIndA,
        &threshold,
        descrC,
        d_csrRowPtrC,
        &nnzC, /* host */
        d_work);
    assert(CUSPARSE_STATUS_SUCCESS == status);
    cudaStat1 = cudaDeviceSynchronize();
    assert(cudaSuccess == cudaStat1);

```

```

printf("nnzC = %d\n", nnzC);
if (0 == nnzC){
    printf("C is empty \n");
    return 0;
}
/* step 5: compute csrColIndC and csrValC */
cudaStat1 = cudaMalloc ((void**)&d_csrColIndC, sizeof(int ) * nnzC );
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMalloc ((void**)&d_csrValC , sizeof(float) * nnzC );
assert(cudaSuccess == cudaStat1);

status = cusparseSpruneCsr2csr(
    handle,
    m,
    n,
    nnzA,
    descrA,
    d_csrValA,
    d_csrRowPtrA,
    d_csrColIndA,
    &threshold,
    descrC,
    d_csrValC,
    d_csrRowPtrC,
    d_csrColIndC,
    d_work);
assert(CUSPARSE_STATUS_SUCCESS == status);
cudaStat1 = cudaDeviceSynchronize();
assert(cudaSuccess == cudaStat1);

/* step 6: output C */
csrRowPtrC = (int* )malloc(sizeof(int )*(m+1));
csrColIndC = (int* )malloc(sizeof(int )*nnzC);
csrValC = (float*)malloc(sizeof(float)*nnzC);
assert( NULL != csrRowPtrC);
assert( NULL != csrColIndC);
assert( NULL != csrValC);
cudaStat1 = cudaMemcpy(csrRowPtrC, d_csrRowPtrC, sizeof(int )*(m+1),
    cudaMemcpyDeviceToHost);
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMemcpy(csrColIndC, d_csrColIndC, sizeof(int )*nnzC ,
    cudaMemcpyDeviceToHost);
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMemcpy(csrValC , d_csrValC , sizeof(float)*nnzC ,
    cudaMemcpyDeviceToHost);
assert(cudaSuccess == cudaStat1);
printCsr(m, n, nnzC, descrC, csrValC, csrRowPtrC, csrColIndC, "C");
/* free resources */
if (d_csrRowPtrA ) cudaFree(d_csrRowPtrA);
if (d_csrColIndA ) cudaFree(d_csrColIndA);
if (d_csrValA ) cudaFree(d_csrValA);
if (d_csrRowPtrC ) cudaFree(d_csrRowPtrC);
if (d_csrColIndC ) cudaFree(d_csrColIndC);
if (d_csrValC ) cudaFree(d_csrValC);
if (csrRowPtrC ) free(csrRowPtrC);
if (csrColIndC ) free(csrColIndC);
if (csrValC ) free(csrValC);
if (handle ) cusparseDestroy(handle);
if (stream ) cudaStreamDestroy(stream);
if (descrA ) cusparseDestroyMatDescr(descrA);
if (descrC ) cusparseDestroyMatDescr(descrC);
cudaDeviceReset();
return 0;
}

```

17.3. Prune Dense to Sparse by Percentage

This section provides a simple example in the C programming language of pruning a dense matrix to a sparse matrix by percentage.

A is a 4x4 dense matrix,

$$A = \begin{pmatrix} 1.0 & 0.0 & 2.0 & -3.0 \\ 0.0 & 4.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 6.0 & 7.0 \\ 0.0 & 8.0 & 0.0 & 9.0 \end{pmatrix}$$

The percentage is 50, which means to prune 50 percent of the dense matrix. The matrix has 16 elements, so 8 out of 16 must be pruned out. Therefore 7 zeros are pruned out, and value 1.0 is also out because it is the smallest among 9 nonzero elements.

```

/*
 * How to compile (assume cuda is installed at /usr/local/cuda/)
 * nvcc -c -I/usr/local/cuda/include prunedense2csrbyP.cpp
 * g++ -o prunedense2csrbyP.cpp prunedense2csrbyP.o -L/usr/local/cuda/lib64 -
 * lcusparse -lcudart
 */
#include <stdio.h>
#include <stdlib.h>
#include <assert.h>
#include <cuda_runtime.h>
#include <cusparse.h>

void printMatrix(int m, int n, const float*A, int lda, const char* name)
{
    for(int row = 0 ; row < m ; row++){
        for(int col = 0 ; col < n ; col++){
            float Areg = A[row + col*lda];
            printf("%s(%d,%d) = %f\n", name, row+1, col+1, Areg);
        }
    }
}

void printCsr(
    int m,
    int n,
    int nnz,
    const cusparseMatDescr_t descrA,
    const float *csrValA,
    const int *csrRowPtrA,
    const int *csrColIndA,
    const char* name)
{
    const int base = (cusparseGetMatIndexBase(descrA) != CUSPARSE_INDEX_BASE_ONE)?
    0:1 ;

    printf("matrix %s is %d-by-%d, nnz=%d, base=%d, output base-1\n", name, m, n,
    nnz, base);
    for(int row = 0 ; row < m ; row++){
        const int start = csrRowPtrA[row ] - base;
        const int end   = csrRowPtrA[row+1] - base;
        for(int colidx = start ; colidx < end ; colidx++){

```



```

        const int col = csrColIndA[colidx] - base;
        const float Areg = csrValA[colidx];
        printf("%s(%d,%d) = %f\n", name, row+1, col+1, Areg);
    }
}
}

int main(int argc, char*argv[])
{
    cusparseHandle_t handle = NULL;
    cudaStream_t stream = NULL;
    cusparseMatDescr_t descrC = NULL;
    pruneInfo_t info = NULL;

    cusparseStatus_t status = CUSPARSE_STATUS_SUCCESS;
    cudaError_t cudaStat1 = cudaSuccess;
    cudaError_t cudaStat2 = cudaSuccess;
    cudaError_t cudaStat3 = cudaSuccess;
    cudaError_t cudaStat4 = cudaSuccess;
    cudaError_t cudaStat5 = cudaSuccess;
    const int m = 4;
    const int n = 4;
    const int lda = m;

/*
 *      |   1   0   2   -3 |
 *      |   0   4   0   0 |
 *  A = |   5   0   6   7 |
 *      |   0   8   0   9 |
 *
 */
    const float A[lda*n] = {1, 0, 5, 0, 0, 4, 0, 8, 2, 0, 6, 0, -3, 0, 7, 9};
    int* csrRowPtrC = NULL;
    int* csrColIndC = NULL;
    float* csrValC = NULL;

    float *d_A = NULL;
    int *d_csrRowPtrC = NULL;
    int *d_csrColIndC = NULL;
    float *d_csrValC = NULL;

    size_t lworkInBytes = 0;
    char *d_work = NULL;

    int nnzC = 0;

    float percentage = 50; /* 50% of nnz */

    printf("example of pruneDense2csrByPercentage \n");

    printf("prune out %.1f percentage of A \n", percentage);

    printMatrix(m, n, A, lda, "A");

/* step 1: create cusparse handle, bind a stream */
    cudaStat1 = cudaStreamCreateWithFlags(&stream, cudaStreamNonBlocking);
    assert(cudaStat1 == cudaSuccess);

    status = cusparseCreate(&handle);
    assert(CUSPARSE_STATUS_SUCCESS == status);

    status = cusparseSetStream(handle, stream);
    assert(CUSPARSE_STATUS_SUCCESS == status);

    status = cusparseCreatePruneInfo(&info);

```

```

assert(CUSPARSE_STATUS_SUCCESS == status);

/* step 2: configuration of matrix C */
status = cusparseCreateMatDescr(&descrC);
assert(CUSPARSE_STATUS_SUCCESS == status);

cusparseSetMatIndexBase(descrC, CUSPARSE_INDEX_BASE_ZERO);
cusparseSetMatType(descrC, CUSPARSE_MATRIX_TYPE_GENERAL );

cudaStat1 = cudaMalloc ((void**)&d_A          , sizeof(float)*lda*n );
cudaStat2 = cudaMalloc ((void**)&d_csrRowPtrC, sizeof(int)*(m+1) );
assert(cudaSuccess == cudaStat1);
assert(cudaSuccess == cudaStat2);

cudaStat1 = cudaMemcpy(d_A, A, sizeof(float)*lda*n, cudaMemcpyHostToDevice);
assert(cudaSuccess == cudaStat1);

```

```

/* step 3: query workspace */
status = cusparseSpruneDense2csrByPercentage_bufferSizeExt(
    handle,
    m,
    n,
    d_A,
    lda,
    percentage,
    descrC,
    d_csrValC,
    d_csrRowPtrC,
    d_csrColIndC,
    info,
    &lworkInBytes);
assert(CUSPARSE_STATUS_SUCCESS == status);

printf("lworkInBytes = %lld \n", (long long)lworkInBytes);

if (NULL != d_work) { cudaFree(d_work); }
cudaStat1 = cudaMalloc((void**)&d_work, lworkInBytes);
assert(cudaSuccess == cudaStat1);

/* step 4: compute csrRowPtrC and nnzC */
status = cusparseSpruneDense2csrNnzByPercentage(
    handle,
    m,
    n,
    d_A,
    lda,
    percentage,
    descrC,
    d_csrRowPtrC,
    &nnzC, /* host */
    info,
    d_work);
assert(CUSPARSE_STATUS_SUCCESS == status);
cudaStat1 = cudaDeviceSynchronize();
assert(cudaSuccess == cudaStat1);

printf("nnzC = %d\n", nnzC);
if (0 == nnzC){
    printf("C is empty \n");
    return 0;
}

/* step 5: compute csrColIndC and csrValC */
cudaStat1 = cudaMalloc ((void**)&d_csrColIndC, sizeof(int) * nnzC );
cudaStat2 = cudaMalloc ((void**)&d_csrValC   , sizeof(float) * nnzC );

```

```
assert(cudaSuccess == cudaStat1);
assert(cudaSuccess == cudaStat2);
```

```

status = cusparseSpruneDense2csrByPercentage(
    handle,
    m,
    n,
    d_A,
    lda,
    percentage,
    descrC,
    d_csrValC,
    d_csrRowPtrC,
    d_csrColIndC,
    info,
    d_work);
assert(CUSPARSE_STATUS_SUCCESS == status);
cudaStat1 = cudaDeviceSynchronize();
assert(cudaSuccess == cudaStat1);

/* step 7: output C */
csrRowPtrC = (int*) malloc(sizeof(int) * (m+1));
csrColIndC = (int*) malloc(sizeof(int) * nnzC);
csrValC     = (float*) malloc(sizeof(float) * nnzC);
assert( NULL != csrRowPtrC);
assert( NULL != csrColIndC);
assert( NULL != csrValC);

    cudaStat1 = cudaMemcpy(csrRowPtrC, d_csrRowPtrC, sizeof(int) * (m+1),
cudaMemcpyDeviceToHost);
    cudaStat2 = cudaMemcpy(csrColIndC, d_csrColIndC, sizeof(int) * nnzC ,
cudaMemcpyDeviceToHost);
    cudaStat3 = cudaMemcpy(csrValC , d_csrValC , sizeof(float) * nnzC ,
cudaMemcpyDeviceToHost);
assert(cudaSuccess == cudaStat1);
assert(cudaSuccess == cudaStat2);
assert(cudaSuccess == cudaStat3);

    printCsr(m, n, nnzC, descrC, csrValC, csrRowPtrC, csrColIndC, "C");

/* free resources */
if (d_A ) cudaFree(d_A);
if (d_csrRowPtrC) cudaFree(d_csrRowPtrC);
if (d_csrColIndC) cudaFree(d_csrColIndC);
if (d_csrValC ) cudaFree(d_csrValC);

if (csrRowPtrC ) free(csrRowPtrC);
if (csrColIndC ) free(csrColIndC);
if (csrValC ) free(csrValC);

if (handle ) cusparseDestroy(handle);
if (stream ) cudaStreamDestroy(stream);
if (descrC ) cusparseDestroyMatDescr(descrC);
if (info ) cusparseDestroyPruneInfo(info);

    cudaDeviceReset();

    return 0;
}

```

17.4. Prune Sparse to Sparse by Percentage

This section provides a simple example in the C programming language of pruning a sparse matrix to a sparse matrix by percentage.

A is a 4x4 sparse matrix,

$$A = \begin{pmatrix} 1.0 & 0.0 & 2.0 & -3.0 \\ 0.0 & 4.0 & 0.0 & 0.0 \\ 5.0 & 0.0 & 6.0 & 7.0 \\ 0.0 & 8.0 & 0.0 & 9.0 \end{pmatrix}$$

The percentage is 20, which means to prune 20 percent of the nonzeros. The sparse matrix has 9 nonzero elements, so 1.4 elements must be pruned out. The function removes 1.0 and 2.0 which are first two smallest numbers of nonzeros.

```

/*
 * How to compile (assume cuda is installed at /usr/local/cuda/)
 *   nvcc -c -I/usr/local/cuda/include prunedcsr2csrByP.cpp
 *   g++ -o prunedcsr2csrByP prunedcsr2csrByP.o -L/usr/local/cuda/lib64 -lcusparse
 *   -lcudart
 */
#include <stdio.h>
#include <stdlib.h>
#include <assert.h>
#include <cuda_runtime.h>
#include <cusparse.h>

void printCsr(
    int m,
    int n,
    int nnz,
    const cusparseMatDescr_t descrA,
    const float *csrValA,
    const int *csrRowPtrA,
    const int *csrColIndA,
    const char* name)
{
    const int base = (cusparseGetMatIndexBase(descrA) != CUSPARSE_INDEX_BASE_ONE)?
    0:1 ;

    printf("matrix %s is %d-by-%d, nnz=%d, base=%d, output base-1\n", name, m, n,
    nnz, base);
    for(int row = 0 ; row < m ; row++){
        const int start = csrRowPtrA[row ] - base;
        const int end   = csrRowPtrA[row+1] - base;
        for(int colidx = start ; colidx < end ; colidx++){
            const int col = csrColIndA[colidx] - base;
            const float Areg = csrValA[colidx];
            printf("%s(%d,%d) = %f\n", name, row+1, col+1, Areg);
        }
    }
}

int main(int argc, char*argv[])
{
    cusparseHandle_t handle = NULL;

```

```

cudaStream_t stream = NULL;
cusparseMatDescr_t descrA = NULL;
cusparseMatDescr_t descrC = NULL;
pruneInfo_t info = NULL;

cusparseStatus_t status = CUSPARSE_STATUS_SUCCESS;
cudaError_t cudaStat1 = cudaSuccess;
const int m = 4;
const int n = 4;
const int nnzA = 9;
/*
 *      |   1   0   2   -3 |
 *      |   0   4   0   0 |
 *  A = |   5   0   6   7 |
 *      |   0   8   0   9 |
 *
 */

```

```

const int csrRowPtrA[m+1] = { 1, 4, 5, 8, 10};
const int csrColIndA[nnzA] = { 1, 3, 4, 2, 1, 3, 4, 2, 4};
const float csrValA[nnzA] = {1, 2, -3, 4, 5, 6, 7, 8, 9};

int* csrRowPtrC = NULL;
int* csrColIndC = NULL;
float* csrValC = NULL;

int *d_csrRowPtrA = NULL;
int *d_csrColIndA = NULL;
float *d_csrValA = NULL;

int *d_csrRowPtrC = NULL;
int *d_csrColIndC = NULL;
float *d_csrValC = NULL;

size_t lworkInBytes = 0;
char *d_work = NULL;

int nnzC = 0;

float percentage = 20; /* remove 20% of nonzeros */

printf("example of pruneCsr2csrByPercentage \n");

printf("prune %.1f percent of nonzeros \n", percentage);

/* step 1: create cusparse handle, bind a stream */
cudaStat1 = cudaStreamCreateWithFlags(&stream, cudaStreamNonBlocking);
assert(cudaSuccess == cudaStat1);

status = cusparseCreate(&handle);
assert(CUSPARSE_STATUS_SUCCESS == status);

status = cusparseSetStream(handle, stream);
assert(CUSPARSE_STATUS_SUCCESS == status);

status = cusparseCreatePruneInfo(&info);
assert(CUSPARSE_STATUS_SUCCESS == status);

/* step 2: configuration of matrix C */
status = cusparseCreateMatDescr(&descrA);
assert(CUSPARSE_STATUS_SUCCESS == status);
/* A is base-1 */
cusparseSetMatIndexBase(descrA, CUSPARSE_INDEX_BASE_ONE);
cusparseSetMatType(descrA, CUSPARSE_MATRIX_TYPE_GENERAL);

```

```

    status = cusparseCreateMatDescr(&descrC);
    assert(CUSPARSE_STATUS_SUCCESS == status);
/* C is base-0 */
    cusparseSetMatIndexBase(descrC,CUSPARSE_INDEX_BASE_ZERO);
    cusparseSetMatType(descrC, CUSPARSE_MATRIX_TYPE_GENERAL );

    printCsr(m, n, nnzA, descrA, csrValA, csrRowPtrA, csrColIndA, "A");

```

```

    cudaStat1 = cudaMalloc ((void*)&d_csrRowPtrA, sizeof(int)*(m+1) );
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMalloc ((void*)&d_csrColIndA, sizeof(int)*nnzA );
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMalloc ((void*)&d_csrValA , sizeof(float)*nnzA );
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMalloc ((void*)&d_csrRowPtrC, sizeof(int)*(m+1) );
    assert(cudaSuccess == cudaStat1);

    cudaStat1 = cudaMemcpy(d_csrRowPtrA, csrRowPtrA, sizeof(int)*(m+1),
        cudaMemcpyHostToDevice);
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMemcpy(d_csrColIndA, csrColIndA, sizeof(int)*nnzA,
        cudaMemcpyHostToDevice);
    assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMemcpy(d_csrValA , csrValA , sizeof(float)*nnzA,
        cudaMemcpyHostToDevice);
    assert(cudaSuccess == cudaStat1);

/* step 3: query workspace */
    status = cusparseSpruneCsr2csrByPercentage_bufferSizeExt(
        handle,
        m,
        n,
        nnzA,
        descrA,
        d_csrValA,
        d_csrRowPtrA,
        d_csrColIndA,
        percentage,
        descrC,
        d_csrValC,
        d_csrRowPtrC,
        d_csrColIndC,
        info,
        &lworkInBytes);
    assert(CUSPARSE_STATUS_SUCCESS == status);

    printf("lworkInBytes = %lld \n", (long long)lworkInBytes);

    if (NULL != d_work) { cudaFree(d_work); }
    cudaStat1 = cudaMalloc((void*)&d_work, lworkInBytes);
    assert(cudaSuccess == cudaStat1);

/* step 4: compute csrRowPtrC and nnzC */
    status = cusparseSpruneCsr2csrNnzByPercentage(
        handle,
        m,
        n,
        nnzA,
        descrA,
        d_csrValA,
        d_csrRowPtrA,
        d_csrColIndA,
        percentage,

```

```

    descrC,
    d_csrRowPtrC,
    &nnzC, /* host */
    info,
    d_work);

assert(CUSPARSE_STATUS_SUCCESS == status);
cudaStat1 = cudaDeviceSynchronize();
assert(cudaSuccess == cudaStat1);

printf("nnzC = %d\n", nnzC);
if (0 == nnzC ) {
    printf("C is empty \n");
    return 0;
}

/* step 5: compute csrColIndC and csrValC */
cudaStat1 = cudaMalloc ((void**)&d_csrColIndC, sizeof(int ) * nnzC );
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMalloc ((void**)&d_csrValC , sizeof(float) * nnzC );
assert(cudaSuccess == cudaStat1);

status = cusparseSpruneCsr2csrByPercentage(
    handle,
    m,
    n,
    nnzA,
    descrA,
    d_csrValA,
    d_csrRowPtrA,
    d_csrColIndA,
    percentage,
    descrC,
    d_csrValC,
    d_csrRowPtrC,
    d_csrColIndC,
    info,
    d_work);
assert(CUSPARSE_STATUS_SUCCESS == status);
cudaStat1 = cudaDeviceSynchronize();
assert(cudaSuccess == cudaStat1);

/* step 6: output C */
csrRowPtrC = (int* )malloc(sizeof(int )*(m+1));
csrColIndC = (int* )malloc(sizeof(int )*nnzC);
csrValC = (float*)malloc(sizeof(float)*nnzC);
assert( NULL != csrRowPtrC);
assert( NULL != csrColIndC);
assert( NULL != csrValC);

    cudaStat1 = cudaMemcpy(csrRowPtrC, d_csrRowPtrC, sizeof(int )*(m+1),
cudaMemcpyDeviceToHost);
assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMemcpy(csrColIndC, d_csrColIndC, sizeof(int )*nnzC ,
cudaMemcpyDeviceToHost);
assert(cudaSuccess == cudaStat1);
    cudaStat1 = cudaMemcpy(csrValC , d_csrValC , sizeof(float)*nnzC ,
cudaMemcpyDeviceToHost);
assert(cudaSuccess == cudaStat1);

    printCsr(m, n, nnzC, descrC, csrValC, csrRowPtrC, csrColIndC, "C");

```

```
/* free resources */
if (d_csrRowPtrA) cudaFree(d_csrRowPtrA);
if (d_csrColIndA) cudaFree(d_csrColIndA);
if (d_csrValA) cudaFree(d_csrValA);
if (d_csrRowPtrC) cudaFree(d_csrRowPtrC);
if (d_csrColIndC) cudaFree(d_csrColIndC);
if (d_csrValC) cudaFree(d_csrValC);

if (csrRowPtrC) free(csrRowPtrC);
if (csrColIndC) free(csrColIndC);
if (csrValC) free(csrValC);

if (handle) cusparseDestroy(handle);
if (stream) cudaStreamDestroy(stream);
if (descrA) cusparseDestroyMatDescr(descrA);
if (descrC) cusparseDestroyMatDescr(descrC);
if (info) cusparseDestroyPruneInfo(info);

cudaDeviceReset();

return 0;
}
```

Chapter 18. Appendix C: Examples of csrms2

18.1. Forward Triangular Solver

This section provides a simple example in the C programming language of csrms2.

The example solves a lower triangular system with 2 right hand side vectors.

```
/*
 * How to compile (assume cuda is installed at /usr/local/cuda/)
 *   nvcc -c -I/usr/local/cuda/include csrms2.cpp
 *   g++ -o csrm2 csrms2.o -L/usr/local/cuda/lib64 -lcusparse -lcudart
 */
#include <stdio.h>
#include <stdlib.h>
#include <assert.h>
#include <cuda_runtime.h>
#include <cusparse.h>

/* compute | b - A*x|_inf */
void residaul_eval(
    int n,
    const cusparseMatDescr_t descrA,
    const float *csrVal,
    const int *csrRowPtr,
    const int *csrColInd,
    const float *b,
    const float *x,
    float *r_nrminf_ptr)
{
    const int base = (cusparseGetMatIndexBase(descrA) != CUSPARSE_INDEX_BASE_ONE)?
0:1 ;
    const int lower = (CUSPARSE_FILL_MODE_LOWER == cusparseGetMatFillMode(descrA))?
1:0;
    const int unit = (CUSPARSE_DIAG_TYPE_UNIT == cusparseGetMatDiagType(descrA))?
1:0;

    float r_nrminf = 0;
    for(int row = 0 ; row < n ; row++){
        const int start = csrRowPtr[row] - base;
        const int end = csrRowPtr[row+1] - base;
        float dot = 0;
        for(int colidx = start ; colidx < end; colidx++){
            const int col = csrColInd[colidx] - base;
            float Aij = csrVal[colidx];
            float xj = x[col];
```

```

        if ( (row == col) && unit ){
            Aij = 1.0;
        }
        int valid = (row >= col) && lower ||
                    (row <= col) && !lower ;
        if ( valid ){
            dot += Aij*xj;
        }
    }
    float ri = b[row] - dot;
    r_nrminf = (r_nrminf > fabs(ri)) ? r_nrminf : fabs(ri);
}
*r_nrminf_ptr = r_nrminf;
}

int main(int argc, char*argv[])
{
    cusparseHandle_t handle = NULL;
    cudaStream_t stream = NULL;
    cusparseMatDescr_t descrA = NULL;
    csrsm2Info_t info = NULL;

```

```

    cusparseStatus_t status = CUSPARSE_STATUS_SUCCESS;
    cudaError_t cudaStat1 = cudaSuccess;
    const int nrhs = 2;
    const int n = 4;
    const int nnzA = 9;
    const cusparseSolvePolicy_t policy = CUSPARSE_SOLVE_POLICY_NO_LEVEL;
    const float h_one = 1.0;
/*
*      |   1   0   2   -3 |
*      |   0   4   0   0 |
*  A = |   5   0   6   7 |
*      |   0   8   0   9 |
*
*  Regard A as a lower triangle matrix L with non-unit diagonal.
*  Given  B = | 1 5 |, X = L \ B = | 1           5           |
*           | 2 6 |,              | 0.5         1.5         |
*           | 3 7 |,              | -0.3333     -3           |
*           | 4 8 |,              | 0           -0.4444     |
*/
    const int csrRowPtrA[n+1] = { 1, 4, 5, 8, 10};
    const int csrColIndA[nnzA] = { 1, 3, 4, 2, 1, 3, 4, 2, 4};
    const float csrValA[nnzA] = {1, 2, -3, 4, 5, 6, 7, 8, 9};
    const float B[n*nrhs] = {1,2,3,4,5,6,7,8};
    float X[n*nrhs];

    int *d_csrRowPtrA = NULL;
    int *d_csrColIndA = NULL;
    float *d_csrValA = NULL;
    float *d_B = NULL;

    size_t lworkInBytes = 0;
    char *d_work = NULL;

    const int algo = 0; /* non-block version */

    printf("example of csrsm2 \n");

/* step 1: create cusparse handle, bind a stream */
    cudaStat1 = cudaStreamCreateWithFlags(&stream, cudaStreamNonBlocking);
    assert(cudaSuccess == cudaStat1);

    status = cusparseCreate(&handle);

```

```

assert(CUSPARSE_STATUS_SUCCESS == status);

status = cusparseSetStream(handle, stream);
assert(CUSPARSE_STATUS_SUCCESS == status);

status = cusparseCreateCsrsm2Info(&info);
assert(CUSPARSE_STATUS_SUCCESS == status);

/* step 2: configuration of matrix A */
status = cusparseCreateMatDescr(&descrA);
assert(CUSPARSE_STATUS_SUCCESS == status);
/* A is base-1 */
cusparseSetMatIndexBase(descrA, CUSPARSE_INDEX_BASE_ONE);

cusparseSetMatType(descrA, CUSPARSE_MATRIX_TYPE_GENERAL);
/* A is lower triangle */
cusparseSetMatFillMode(descrA, CUSPARSE_FILL_MODE_LOWER);
/* A has non unit diagonal */
cusparseSetMatDiagType(descrA, CUSPARSE_DIAG_TYPE_NON_UNIT);

cudaStat1 = cudaMalloc ((void**)&d_csrRowPtrA, sizeof(int)*(n+1) );
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMalloc ((void**)&d_csrColIndA, sizeof(int)*nnzA );
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMalloc ((void**)&d_csrValA, sizeof(float)*nnzA );
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMalloc ((void**)&d_B, sizeof(float)*n*nrhs );
assert(cudaSuccess == cudaStat1);

cudaStat1 = cudaMemcpy(d_csrRowPtrA, csrRowPtrA, sizeof(int)*(n+1),
cudaMemcpyHostToDevice);
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMemcpy(d_csrColIndA, csrColIndA, sizeof(int)*nnzA,
cudaMemcpyHostToDevice);
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMemcpy(d_csrValA, csrValA, sizeof(float)*nnzA,
cudaMemcpyHostToDevice);
assert(cudaSuccess == cudaStat1);
cudaStat1 = cudaMemcpy(d_B, B, sizeof(float)*n*nrhs,
cudaMemcpyHostToDevice);
assert(cudaSuccess == cudaStat1);

/* step 3: query workspace */
status = cusparseScsrsm2_bufferSizeExt(
    handle,
    algo,
    CUSPARSE_OPERATION_NON_TRANSPOSE, /* transA */
    CUSPARSE_OPERATION_NON_TRANSPOSE, /* transB */
    n,
    nrhs,
    nnzA,
    &h_one,
    descrA,
    d_csrValA,
    d_csrRowPtrA,
    d_csrColIndA,
    d_B,
    n, /* ldb */
    info,
    policy,
    &lworkInBytes);
assert(CUSPARSE_STATUS_SUCCESS == status);

printf("lworkInBytes = %lld \n", (long long)lworkInBytes);

```

```

if (NULL != d_work) { cudaFree(d_work); }
cudaStat1 = cudaMalloc((void**)&d_work, lworkInBytes);
assert(cudaSuccess == cudaStat1);

/* step 4: analysis */
status = cusparseScsrsm2_analysis(
    handle,
    algo,
    CUSPARSE_OPERATION_NON_TRANSPOSE, /* transA */
    CUSPARSE_OPERATION_NON_TRANSPOSE, /* transB */
    n,
    nrhs,
    nnzA,
    &h_one,
    descrA,
    d_csrValA,
    d_csrRowPtrA,
    d_csrColIndA,
    d_B,
    n, /* ldb */
    info,
    policy,
    d_work);
assert(CUSPARSE_STATUS_SUCCESS == status);

/* step 5: solve L * X = B */
status = cusparseScsrsm2_solve(
    handle,
    algo,
    CUSPARSE_OPERATION_NON_TRANSPOSE, /* transA */
    CUSPARSE_OPERATION_NON_TRANSPOSE, /* transB */
    n,
    nrhs,
    nnzA,
    &h_one,
    descrA,
    d_csrValA,
    d_csrRowPtrA,
    d_csrColIndA,
    d_B,
    n, /* ldb */
    info,
    policy,
    d_work);
assert(CUSPARSE_STATUS_SUCCESS == status);
cudaStat1 = cudaDeviceSynchronize();
assert(cudaSuccess == cudaStat1);

/* step 6: measure residual B - A*X */
cudaStat1 = cudaMemcpy(X, d_B, sizeof(float)*n*nrhs, cudaMemcpyDeviceToHost);
assert(cudaSuccess == cudaStat1);
cudaDeviceSynchronize();

printf("==== x1 = inv(A)*b1 \n");
for(int j = 0 ; j < n; j++){
    printf("x1[%d] = %f\n", j, X[j]);
}
float r1_nrminf;
residual_eval(
    n,
    descrA,
    csrValA,
    csrRowPtrA,
    csrColIndA,
    B,

```

```

        X,
        &r1_nrminf
    );
    printf("|b1 - A*x1| = %E\n", r1_nrminf);

    printf("==== x2 = inv(A)*b2 \n");
    for(int j = 0 ; j < n; j++){
        printf("x2[%d] = %f\n", j, X[n+j]);
    }
    float r2_nrminf;
    residaul_eval(
        n,
        descrA,
        csrValA,
        csrRowPtrA,
        csrColIndA,
        B+n,
        X+n,
        &r2_nrminf
    );
    printf("|b2 - A*x2| = %E\n", r2_nrminf);

```

```

/* free resources */
if (d_csrRowPtrA ) cudaFree(d_csrRowPtrA);
if (d_csrColIndA ) cudaFree(d_csrColIndA);
if (d_csrValA    ) cudaFree(d_csrValA);
if (d_B         ) cudaFree(d_B);

if (handle      ) cusparseDestroy(handle);
if (stream      ) cudaStreamDestroy(stream);
if (descrA      ) cusparseDestroyMatDescr(descrA);
if (info        ) cusparseDestroyCsrsm2Info(info);

cudaDeviceReset();

return 0;
}

```

Chapter 19. Appendix D: Acknowledgements

NVIDIA would like to thank the following individuals and institutions for their contributions:

- ▶ The `cusparse<tsv>` implementation is derived from a version developed by Li-Wen Chang from the University of Illinois.
- ▶ The `cusparse<tsv>InterleavedBatch` adopts `cuThomasBatch` developed by Pedro Valero-Lara and Ivan Martínez-Pérez from Barcelona Supercomputing Center and BSC/UPC NVIDIA GPU Center of Excellence.
- ▶ This product includes `{fmt}` - A modern formatting library <https://fmt.dev> Copyright (c) 2012 - present, Victor Zverovich.

Chapter 20. Bibliography

- [1] N. Bell and M. Garland, "[Implementing Sparse Matrix-Vector Multiplication on Throughput-Oriented Processors](#)", Supercomputing, 2009.
- [2] R. Grimes, D. Kincaid, and D. Young, "ITPACK 2.0 User's Guide", Technical Report CNA-150, Center for Numerical Analysis, University of Texas, 1979.
- [3] M. Naumov, "[Incomplete-LU and Cholesky Preconditioned Iterative Methods Using cuSPARSE and cuBLAS](#)", Technical Report and White Paper, 2011.
- [4] Pedro Valero-Lara, Ivan Martínez-Pérez, Raül Sirvent, Xavier Martorell, and Antonio J. Peña. NVIDIA GPUs Scalability to Solve Multiple (Batch) Tridiagonal Systems. Implementation of cuThomasBatch. In Parallel Processing and Applied Mathematics - 12th International Conference (PPAM), 2017.

Notice

This document is provided for information purposes only and shall not be regarded as a warranty of a certain functionality, condition, or quality of a product. NVIDIA Corporation ("NVIDIA") makes no representations or warranties, expressed or implied, as to the accuracy or completeness of the information contained in this document and assumes no responsibility for any errors contained herein. NVIDIA shall have no liability for the consequences or use of such information or for any infringement of patents or other rights of third parties that may result from its use. This document is not a commitment to develop, release, or deliver any Material (defined below), code, or functionality.

NVIDIA reserves the right to make corrections, modifications, enhancements, improvements, and any other changes to this document, at any time without notice.

Customer should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

NVIDIA products are sold subject to the NVIDIA standard terms and conditions of sale supplied at the time of order acknowledgement, unless otherwise agreed in an individual sales agreement signed by authorized representatives of NVIDIA and customer ("Terms of Sale"). NVIDIA hereby expressly objects to applying any customer general terms and conditions with regards to the purchase of the NVIDIA product referenced in this document. No contractual obligations are formed either directly or indirectly by this document.

OpenCL

OpenCL is a trademark of Apple Inc. used under license to the Khronos Group Inc.

Trademarks

NVIDIA and the NVIDIA logo are trademarks or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

© 2007-2022 NVIDIA Corporation & affiliates. All rights reserved.