



Release Notes

Release 12.5

NVIDIA Corporation

Jun 04, 2024

Contents

1	CUDA Toolkit Major Component Versions	3
2	New Features	9
2.1	General CUDA	9
2.2	CUDA Compilers	9
2.3	CUDA Developer Tools	9
3	Known Issues and Limitations	11
4	Deprecated or Dropped Features	13
4.1	Deprecated or Dropped Architectures	13
4.2	Deprecated Operating Systems	13
4.3	Deprecated Toolchains	13
4.4	CUDA Tools	14
5	CUDA Libraries	15
5.1	cuBLAS Library	15
5.1.1	cuBLAS: Release 12.5	15
5.1.2	cuBLAS: Release 12.4 Update 1	15
5.1.3	cuBLAS: Release 12.4	16
5.1.4	cuBLAS: Release 12.3 Update 1	17
5.1.5	cuBLAS: Release 12.3	17
5.1.6	cuBLAS: Release 12.2 Update 2	18
5.1.7	cuBLAS: Release 12.2	18
5.1.8	cuBLAS: Release 12.1 Update 1	18
5.1.9	cuBLAS: Release 12.0 Update 1	19
5.1.10	cuBLAS: Release 12.0	19
5.2	cuFFT Library	20
5.2.1	cuFFT: Release 12.5	20
5.2.2	cuFFT: Release 12.4 Update 1	20
5.2.3	cuFFT: Release 12.4	20
5.2.4	cuFFT: Release 12.3 Update 1	21
5.2.5	cuFFT: Release 12.3	21
5.2.6	cuFFT: Release 12.2	21
5.2.7	cuFFT: Release 12.1 Update 1	22
5.2.8	cuFFT: Release 12.1	22
5.2.9	cuFFT: Release 12.0 Update 1	22
5.2.10	cuFFT: Release 12.0	23
5.3	cuSOLVER Library	23
5.3.1	cuSOLVER: Release 12.5	23
5.3.2	cuSOLVER: Release 12.4 Update 1	24
5.3.3	cuSOLVER: Release 12.4	24
5.3.4	cuSOLVER: Release 12.2 Update 2	24
5.3.5	cuSOLVER: Release 12.2	25

5.4	cuSPARSE Library	25
5.4.1	cuSPARSE: Release 12.5	25
5.4.2	cuSPARSE: Release 12.4	25
5.4.3	cuSPARSE: Release 12.3 Update 1	26
5.4.4	cuSPARSE: Release 12.3	26
5.4.5	cuSPARSE: Release 12.2 Update 1	26
5.4.6	cuSPARSE: Release 12.1 Update 1	27
5.4.7	cuSPARSE: Release 12.0 Update 1	27
5.4.8	cuSPARSE: Release 12.0	27
5.5	Math Library	28
5.5.1	CUDA Math: Release 12.5	28
5.5.2	CUDA Math: Release 12.4	28
5.5.3	CUDA Math: Release 12.3	28
5.5.4	CUDA Math: Release 12.2	29
5.5.5	CUDA Math: Release 12.1	30
5.5.6	CUDA Math: Release 12.0	30
5.6	NVIDIA Performance Primitives (NPP)	30
5.6.1	NPP: Release 12.4	30
5.6.2	NPP: Release 12.0	30
5.7	nvJPEG Library	31
5.7.1	nvJPEG: Release 12.4	31
5.7.2	nvJPEG: Release 12.3 Update 1	31
5.7.3	nvJPEG: Release 12.2	31
5.7.4	nvJPEG: Release 12.0	31
6	Notices	33
6.1	Notice	33
6.2	OpenCL	34
6.3	Trademarks	34

NVIDIA CUDA Toolkit Release Notes

The Release Notes for the CUDA Toolkit.

The release notes for the NVIDIA® CUDA® Toolkit can be found online at <https://docs.nvidia.com/cuda/cuda-toolkit-release-notes/index.html>.

Note: The release notes have been reorganized into two major sections: the general CUDA release notes, and the CUDA libraries release notes including historical information for 12.x releases.

Chapter 1. CUDA Toolkit Major Component Versions

CUDA Components

Starting with CUDA 11, the various components in the toolkit are versioned independently.

For CUDA 12.5, the table below indicates the versions:

Table 1: CUDA 12.5 Component Versions

Component Name		Version Information	Supported Architectures	Supported Platforms
CUDA C++ Core Compute Libraries	Thrust	2.4.0	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows
	CUB	2.4.0		
	libcudpp	2.4.0		
	Cooperative Groups	12.5.x		
CUDA Compatibility		12.5.36033601	aarch64-jetson	Linux
CUDA Runtime (cudart)		12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
cuobjdump		12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows
CUPTI		12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA cuxxfilt (demangler)		12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows
CUDA Demo Suite		12.5.39	x86_64	Linux, Windows
CUDA GDB		12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, WSL

continues on next page

Table 1 – continued from previous page

Component Name	Version Information	Supported Architectures	Supported Platforms
CUDA Nsight Eclipse Plugin	12.5.39	x86_64	Linux
CUDA NVCC	12.5.40	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA nvdiasm	12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows
CUDA NVML Headers	12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA nvprof	12.5.39	x86_64	Linux, Windows
CUDA nvprune	12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA NVRTC	12.5.40	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
NVTX	12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA NVVP	12.5.39	x86_64,	Linux, Windows
CUDA OpenCL	12.5.39	x86_64	Linux, Windows
CUDA Profiler API	12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA Compute Sanitizer API	12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA cuBLAS	12.5.2.13	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
cuDLA	12.5.39	aarch64-jetson	Linux
CUDA cuFFT	11.2.3.18	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA cuFile	1.10.0.4	x86_64, arm64-sbsa, aarch64-jetson	Linux

continues on next page

Table 1 – continued from previous page

Component Name	Version Information	Supported Architectures	Supported Platforms
CUDA cuRAND	10.3.6.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA cuSOLVER	11.6.2.40	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA cuSPARSE	12.4.1.18	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA NPP	12.3.0.116	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA nvFatbin	12.5.39	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA nvJitLink	12.5.40	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
CUDA nvJPEG	12.3.2.38	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL
Nsight Compute	2024.2.0.16	x86_64, arm64-sbsa, aarch64-jetson	Linux, Windows, WSL (Windows 11)
Nsight Systems	2024.2.3.38	x86_64, arm64-sbsa,	Linux, Windows, WSL
Nsight Visual Studio Edition (VSE)	2024.2.0.24102	x86_64 (Windows)	Windows
nvidia_fs ¹	2.20.5	x86_64, arm64-sbsa, aarch64-jetson	Linux
Visual Studio Integration	12.5.39	x86_64 (Windows)	Windows
NVIDIA Linux Driver	555.42.02	x86_64, arm64-sbsa	Linux
NVIDIA Windows Driver	555.85	x86_64 (Windows)	Windows, WSL

CUDA Driver

Running a CUDA application requires the system with at least one CUDA capable GPU and a driver that is compatible with the CUDA Toolkit. See [Table 3](#). For more information various GPU

¹ Only available on select Linux distros

products that are CUDA capable, visit <https://developer.nvidia.com/cuda-gpus>.

Each release of the CUDA Toolkit requires a minimum version of the CUDA driver. The CUDA driver is backward compatible, meaning that applications compiled against a particular version of the CUDA will continue to work on subsequent (later) driver releases.

More information on compatibility can be found at <https://docs.nvidia.com/cuda/cuda-c-best-practices-guide/index.html#cuda-compatibility-and-upgrades>.

Note: Starting with CUDA 11.0, the toolkit components are individually versioned, and the toolkit itself is versioned as shown in the table below.

The minimum required driver version for CUDA minor version compatibility is shown below. CUDA minor version compatibility is described in detail in <https://docs.nvidia.com/deploy/cuda-compatibility/index.html>

Table 2: CUDA Toolkit and Minimum Required Driver Version for CUDA Minor Version Compatibility

CUDA Toolkit	Minimum Required Driver Version for CUDA Minor Version Compatibility*	
	Linux x86_64 Driver Version	Windows x86_64 Driver Version
CUDA 12.x	>=525.60.13	>=528.33
CUDA 11.8.x CUDA 11.7.x CUDA 11.6.x CUDA 11.5.x CUDA 11.4.x CUDA 11.3.x CUDA 11.2.x CUDA 11.1.x	>=450.80.02	>=452.39
CUDA 11.0 (11.0.3)	>=450.36.06**	>=451.22**

* Using a Minimum Required Version that is **different** from Toolkit Driver Version could be allowed in compatibility mode – please read the CUDA Compatibility Guide for details.

** CUDA 11.0 was released with an earlier driver version, but by upgrading to Tesla Recommended Drivers 450.80.02 (Linux) / 452.39 (Windows), minor version compatibility is possible across the CUDA 11.x family of toolkits.

The version of the development NVIDIA GPU Driver packaged in each CUDA Toolkit release is shown below.

Table 3: CUDA Toolkit and Corresponding Driver Versions

CUDA Toolkit	Toolkit Driver Version	
	Linux x86_64 Driver Version	Windows x86_64 Driver Version
CUDA 12.5 GA	>=555.42.02	>=555.85
CUDA 12.4 Update 1	>=550.54.15	>=551.78
CUDA 12.4 GA	>=550.54.14	>=551.61
CUDA 12.3 Update 1	>=545.23.08	>=546.12
CUDA 12.3 GA	>=545.23.06	>=545.84
CUDA 12.2 Update 2	>=535.104.05	>=537.13

continues on next page

Table 3 – continued from previous page

CUDA Toolkit	Toolkit Driver Version	
CUDA 12.2 Update 1	>=535.86.09	>=536.67
CUDA 12.2 GA	>=535.54.03	>=536.25
CUDA 12.1 Update 1	>=530.30.02	>=531.14
CUDA 12.1 GA	>=530.30.02	>=531.14
CUDA 12.0 Update 1	>=525.85.12	>=528.33
CUDA 12.0 GA	>=525.60.13	>=527.41
CUDA 11.8 GA	>=520.61.05	>=520.06
CUDA 11.7 Update 1	>=515.48.07	>=516.31
CUDA 11.7 GA	>=515.43.04	>=516.01
CUDA 11.6 Update 2	>=510.47.03	>=511.65
CUDA 11.6 Update 1	>=510.47.03	>=511.65
CUDA 11.6 GA	>=510.39.01	>=511.23
CUDA 11.5 Update 2	>=495.29.05	>=496.13
CUDA 11.5 Update 1	>=495.29.05	>=496.13
CUDA 11.5 GA	>=495.29.05	>=496.04
CUDA 11.4 Update 4	>=470.82.01	>=472.50
CUDA 11.4 Update 3	>=470.82.01	>=472.50
CUDA 11.4 Update 2	>=470.57.02	>=471.41
CUDA 11.4 Update 1	>=470.57.02	>=471.41
CUDA 11.4.0 GA	>=470.42.01	>=471.11
CUDA 11.3.1 Update 1	>=465.19.01	>=465.89
CUDA 11.3.0 GA	>=465.19.01	>=465.89
CUDA 11.2.2 Update 2	>=460.32.03	>=461.33
CUDA 11.2.1 Update 1	>=460.32.03	>=461.09
CUDA 11.2.0 GA	>=460.27.03	>=460.82
CUDA 11.1.1 Update 1	>=455.32	>=456.81
CUDA 11.1 GA	>=455.23	>=456.38
CUDA 11.0.3 Update 1	>= 450.51.06	>= 451.82
CUDA 11.0.2 GA	>= 450.51.05	>= 451.48
CUDA 11.0.1 RC	>= 450.36.06	>= 451.22
CUDA 10.2.89	>= 440.33	>= 441.22

continues on next page

Table 3 – continued from previous page

CUDA Toolkit	Toolkit Driver Version	
CUDA 10.1 (10.1.105 general release, and updates)	>= 418.39	>= 418.96
CUDA 10.0.130	>= 410.48	>= 411.31
CUDA 9.2 (9.2.148 Update 1)	>= 396.37	>= 398.26
CUDA 9.2 (9.2.88)	>= 396.26	>= 397.44
CUDA 9.1 (9.1.85)	>= 390.46	>= 391.29
CUDA 9.0 (9.0.76)	>= 384.81	>= 385.54
CUDA 8.0 (8.0.61 GA2)	>= 375.26	>= 376.51
CUDA 8.0 (8.0.44)	>= 367.48	>= 369.30
CUDA 7.5 (7.5.16)	>= 352.31	>= 353.66
CUDA 7.0 (7.0.28)	>= 346.46	>= 347.62

For convenience, the NVIDIA driver is installed as part of the CUDA Toolkit installation. Note that this driver is for development purposes and is not recommended for use in production with Tesla GPUs.

For running CUDA applications in production with Tesla GPUs, it is recommended to download the latest driver for Tesla GPUs from the NVIDIA driver downloads site at <https://www.nvidia.com/drivers>.

During the installation of the CUDA Toolkit, the installation of the NVIDIA driver may be skipped on Windows (when using the interactive or silent installation) or on Linux (by using meta packages).

For more information on customizing the install process on Windows, see <https://docs.nvidia.com/cuda/cuda-installation-guide-microsoft-windows/index.html#install-cuda-software>.

For meta packages on Linux, see <https://docs.nvidia.com/cuda/cuda-installation-guide-linux/index.html#package-manager-metas>.

Chapter 2. New Features

This section lists new general CUDA and CUDA compilers features.

2.1. General CUDA

- ▶ In an upcoming CUDA release the NVIDIA Open GPU kernel module flavor will be the default and recommended installation option. End-users with Maxwell, Pascal, or Volta GPUs may need to take action to install the NVIDIA proprietary kernel modules.
- ▶ MPS (Multi-process service) is now supported on L4T and embedded-Linux Tegra platforms. More details can be found [here](#).

2.2. CUDA Compilers

- ▶ For changes to PTX, refer to <https://docs.nvidia.com/cuda/parallel-thread-execution/#ptx-isa-version-8-5>.

2.3. CUDA Developer Tools

- ▶ For changes to nvprof and Visual Profiler, see the [changelog](#).
- ▶ For new features, improvements, and bug fixes in Nsight Systems, see the [changelog](#).
- ▶ For new features, improvements, and bug fixes in Nsight Visual Studio Edition, see the [changelog](#).
- ▶ For new features, improvements, and bug fixes in CUPTI, see the [changelog](#).
- ▶ For new features, improvements, and bug fixes in Nsight Compute, see the [changelog](#).
- ▶ For new features, improvements, and bug fixes in Compute Sanitizer, see the [changelog](#).
- ▶ For new features, improvements, and bug fixes in CUDA-GDB, see the [changelog](#).

Chapter 3. Known Issues and Limitations

- ▶ Runfile will not be supported for Amazon Linux 2023.
- ▶ Confidential Computing is not supported on CUDA 12.5. Please continue to use CUDA 12.4 and drivers r550.xx to use these features.
- ▶ Launching Cooperative Group kernels with MPS is not supported on Tegra platforms.

Chapter 4. Deprecated or Dropped Features

Features deprecated in the current release of the CUDA software still work in the current release, but their documentation may have been removed, and they will become officially unsupported in a future release. We recommend that developers employ alternative solutions to these features in their software.

4.1. Deprecated or Dropped Architectures

- ▶ NVIDIA CUDA support for the PowerPC architecture is removed in CUDA 12.5.

4.2. Deprecated Operating Systems

- ▶ NVIDIA CUDA support for Red Hat Enterprise Linux 7 and CentOS 7 is removed in CUDA 12.5.
- ▶ CUDA 12.5 is the last release to support Debian 10.
- ▶ Support for Microsoft Windows 10 21H2 and Microsoft Windows 10 21H2 (SV1) is deprecated.

4.3. Deprecated Toolchains

CUDA Toolkit 12.4 deprecated support for the following host compilers:

- ▶ Microsoft Visual C/C++ (MSVC) 2017
- ▶ All GCC versions prior to GCC 7.3

4.4. CUDA Tools

- ▶ Support for the macOS host client of CUDA-GDB is deprecated. It will be dropped in an upcoming release.

Chapter 5. CUDA Libraries

This section covers CUDA Libraries release notes for 12.x releases.

- ▶ CUDA Math Libraries toolchain uses C++11 features, and a C++11-compatible standard library (libstdc++ >= 20150422) is required on the host.

5.1. cuBLAS Library

5.1.1. cuBLAS: Release 12.5

▶ New Features

- ▶ cuBLAS adds an experimental API to support mixed precision grouped batched GEMMs. This enables grouped batched GEMMs with FP16 or BF16 inputs/outputs with the FP32 compute type. Refer to [cublasGemmGroupedBatchedEx](#) for more details.

▶ Known Issues

- ▶ `cublasLtMatmul` ignores inputs to `CUBLASLT_MATMUL_DESC_D_SCALE_POINTER` and `CUBLASLT_MATMUL_DESC_EPILOGUE_AUX_SCALE_POINTER` if the elements of the respective matrix are not of FP8 types.

▶ Resolved Issues

- ▶ `cublasLtMatmul` ignored the mismatch between the provided scale type and the implied by the documentation, assuming the latter. For instance, an unsupported configuration of `cublasLtMatmul` with the scale type being FP32 and all other types being FP16 would run with the implicit assumption that the scale type is FP16 and produce incorrect results.

5.1.2. cuBLAS: Release 12.4 Update 1

▶ Known Issues

- ▶ Setting a cuBLAS handle stream to `cudaStreamPerThread` and setting the workspace via `cublasSetWorkspace` will cause any subsequent `cublasSetWorkspace` calls to fail. This will be fixed in an upcoming release.
- ▶ `cublasLtMatmul` ignores mismatches between the provided scale type and the scale type implied by the documentation and assumes the latter. For example, an unsupported configuration of `cublasLtMatmul` with the scale type being FP32 and all other types being

FP16 would run with the implicit assumption that the scale type is FP16 which can produce incorrect results. This will be fixed in an upcoming release.

► **Resolved Issues**

- `cublasLtMatmul` ignored the `CUBLASLT_MATMUL_DESC_AMAX_D_POINTER` for unsupported configurations instead of returning an error. In particular, computing absolute maximum of D is currently supported only for FP8 Matmul when the output data type is also FP8 (`CUDA_R_8F_E4M3` or `CUDA_R_8F_E5M2`).
- Reduced host-side overheads for some of the cuBLASLt APIs: `cublasLtMatmul()`, `cublasLtMatmulAlgoCheck()`, and `cublasLtMatmulAlgoGetHeuristic()`. The issue was introduced in CUDA Toolkit 12.4.
- `cublasLtMatmul()` and `cublasLtMatmulAlgoGetHeuristic()` could have resulted in floating point exceptions (FPE) on some Hopper-based GPUs, including Multi-Instance GPU (MIG). The issue was introduced in cuBLAS 11.8.

5.1.3. cuBLAS: Release 12.4

► **New Features**

- cuBLAS adds experimental APIs to support grouped batched GEMM for single precision and double precision. Single precision also supports the math mode, `CUBLAS_TF32_TENSOR_OP_MATH`. Grouped batch mode allows you to concurrently solve GEMMs of different dimensions (m, n, k), leading dimensions (lda, ldb, ldc), transpositions (transa, transb), and scaling factors (alpha, beta). Please see [gemmGroupedBatched](#) for more details.

► **Known Issues**

- When the current context has been created using `cuGreenCtxCreate()`, cuBLAS does not properly detect the number of SMs available. The user may provide the corrected SM count to cuBLAS using an API such as `cublasSetSmCountTarget()`.
- BLAS level 2 and 3 functions might not treat alpha in a BLAS compliant manner when alpha is zero and the pointer mode is set to `CUBLAS_POINTER_MODE_DEVICE`. This is the same known issue documented in cuBLAS 12.3 Update 1.
- `cublasLtMatmul` with K equals 1 and epilogue `CUBLASLT_EPILOGUE_D{RELU, GELU}_BGRAD` could out-of-bound access the workspace. The issue exists since cuBLAS 11.3 Update 1.
- `cublasLtMatmul` with K equals 1 and epilogue `CUBLASLT_EPILOGUE_D{RELU, GELU}` could produce illegal memory access if no workspace is provided. The issue exists since cuBLAS 11.6.
- When captured in CUDA Graph stream capture, cuBLAS routines can create [memory nodes](#) through the use of stream-ordered allocation APIs, `cudaMallocAsync` and `cudaFreeAsync`. However, as there is currently no support for memory nodes in [child graphs](#) or graphs launched [from the device](#), attempts to capture cuBLAS routines in such scenarios may fail. To avoid this issue, use the `cublasSetWorkspace()` function to provide user-owned workspace memory.

5.1.4. cuBLAS: Release 12.3 Update 1

► New Features

- Improved performance of heuristics cache for workloads that have a high eviction rate.

► Known Issues

- BLAS level 2 and 3 functions might not treat alpha in a BLAS compliant manner when alpha is zero and the pointer mode is set to `CUBLAS_POINTER_MODE_DEVICE`. The expected behavior is that the corresponding computations would be skipped. You may encounter the following issues: (1) `HER{2,X,K,2K}` may zero the imaginary part on the diagonal elements of the output matrix; and (2) `HER{2,X,K,2K}`, `SYR{2,X,K,2K}` and others may produce NaN resulting from performing computation on matrices A and B which would otherwise be skipped. If strict compliance with BLAS is required, the user may manually check for alpha value before invoking the functions or switch to `CUBLAS_POINTER_MODE_HOST`.

► Resolved Issues

- `cuBLASLt` matmul operations might have computed the output incorrectly under the following conditions: the data type of matrices A and B is FP8, the data type of matrices C and D is FP32, FP16, or BF16, the beta value is 1.0, the C and D matrices are the same, the epilogue contains GELU activation function.
- When an application compiled with `cuBLASLt` from CUDA Toolkit 12.2 update 1 or earlier runs with `cuBLASLt` from CUDA Toolkit 12.2 update 2 or CUDA Toolkit 12.3, matrix multiply descriptors initialized using `cublasLtMatmulDescInit()` sometimes did not respect attribute changes using `cublasLtMatmulDescSetAttribute()`.
- Fixed creation of `cuBLAS` or `cuBLASLt` handles on Hopper GPUs under the Multi-Process Service (MPS).
- `cublasLtMatmul` with K equals 1 and epilogue `CUBLASLT_EPILOGUE_BGRAD{A, B}` might have returned incorrect results for the bias gradient.

5.1.5. cuBLAS: Release 12.3

► New Features

- Improved performance on NVIDIA L40S Ada GPUs.

► Known Issues

- `cuBLASLt` matmul operations may compute the output incorrectly under the following conditions: the data type of matrices A and B is FP8, the data type of matrices C and D is FP32, FP16, or BF16, the beta value is 1.0, the C and D matrices are the same, the epilogue contains GELU activation function.
- When an application compiled with `cuBLASLt` from CUDA Toolkit 12.2 update 1 or earlier runs with `cuBLASLt` from CUDA Toolkit 12.2 update 2 or later, matrix multiply descriptors initialized using `cublasLtMatmulDescInit()` may not respect attribute changes using `cublasLtMatmulDescSetAttribute()`. To workaround this issue, create the matrix multiply descriptor using `cublasLtMatmulDescCreate()` instead of `cublasLtMatmulDescInit()`. This will be fixed in an upcoming release.

5.1.6. cuBLAS: Release 12.2 Update 2

► New Features

- cuBLASLt will now attempt to decompose problems that cannot be run by a single gemm kernel. It does this by partitioning the problem into smaller chunks and executing the gemm kernel multiple times. This improves functional coverage for very large m, n, or batch size cases and makes the transition from the cuBLAS API to the cuBLASLt API more reliable.

► Known Issues

- cuBLASLt matmul operations may compute the output incorrectly under the following conditions: the data type of matrices A and B is FP8, the data type of matrices C and D is FP32, FP16, or BF16, the beta value is 1.0, the C and D matrices are the same, the epilogue contains GELU activation function.

5.1.7. cuBLAS: Release 12.2

► Known Issues

- cuBLAS initialization fails on Hopper architecture GPUs when MPS is in use with `CUDA_MPS_ACTIVE_THREAD_PERCENTAGE` set to a value less than 100%. There is currently no workaround for this issue.
- Some Hopper kernels produce incorrect results for batched matmuls with `CUBLASLT_EPILOGUE_RELU_BIAS` or `CUBLASLT_EPILOGUE_GELU_BIAS` and a non-zero `CUBLASLT_MATMUL_DESC_BIAS_BATCH_STRIDE`. The kernels apply the first batch's bias vector to all batches. This will be fixed in a future release.

5.1.8. cuBLAS: Release 12.1 Update 1

► New Features

- Support for FP8 on NVIDIA Ada GPUs.
- Improved performance on NVIDIA L4 Ada GPUs.
- Introduced an API that instructs the cuBLASLt library to not use some CPU instructions. This is useful in some rare cases where certain CPU instructions used by cuBLASLt heuristics negatively impact CPU performance. Refer to <https://docs.nvidia.com/cuda/cublas/index.html#disabling-cpu-instructions>.

► Known Issues

- When creating a matrix layout using the `cublasLtMatrixLayoutCreate()` function, the object pointed at by `cublasLtMatrixLayout_t` is smaller than `cublasLtMatrixLayoutOpaque_t` (but enough to hold the internal structure). As a result, the object should not be dereferenced or copied explicitly, as this might lead to out of bound accesses. If one needs to serialize the layout or copy it, it is recommended to manually allocate an object of size `sizeof(cublasLtMatrixLayoutOpaque_t)` bytes, and initialize it using `cublasLtMatrixLayoutInit()` function. The same applies to `cublasLtMatmulDesc_t` and `cublasLtMatrixTransformDesc_t`. The issue will be fixed in future releases by ensuring that `cublasLtMatrixLayoutCreate()` allocates at least `sizeof(cublasLtMatrixLayoutOpaque_t)` bytes.

5.1.9. cuBLAS: Release 12.0 Update 1

► New Features

- Improved performance on NVIDIA H100 SXM and NVIDIA H100 PCIe GPUs.

► Known Issues

- For optimal performance on NVIDIA Hopper architecture, cuBLAS needs to allocate a bigger internal workspace (64 MiB) than on the previous architectures (8 MiB). In the current and previous releases, cuBLAS allocates 256 MiB. This will be addressed in a future release. A possible workaround is to set the CUBLAS_WORKSPACE_CONFIG environment variable to :32768:2 when running cuBLAS on NVIDIA Hopper architecture.

► Resolved Issues

- Reduced cuBLAS host-side overheads caused by not using the cublasLt heuristics cache. This began in the CUDA Toolkit 12.0 release.
- Added forward compatible single precision complex GEMM that does not require workspace.

5.1.10. cuBLAS: Release 12.0

► New Features

- `cublasLtMatmul` now supports FP8 with a non-zero beta.
- Added `int64` APIs to enable larger problem sizes; refer to [64-bit integer interface](#).
- Added more Hopper-specific kernels for `cublasLtMatmul` with epilogues:
 - `CUBLASLT_EPILOGUE_BGRAD{A, B}`
 - `CUBLASLT_EPILOGUE_{RELU, GELU}_AUX`
 - `CUBLASLT_EPILOGUE_D{RELU, GELU}`
- Improved Hopper performance on `arm64-sbsa` by adding Hopper kernels that were previously supported only on the `x86_64` architecture for Windows and Linux.

► Known Issues

- There are no forward compatible kernels for single precision complex gemms that do not require workspace. Support will be added in a later release.

► Resolved Issues

- Fixed an issue on NVIDIA Ampere architecture and newer GPUs where `cublasLtMatmul` with epilogue `CUBLASLT_EPILOGUE_BGRAD{A, B}` and a nontrivial reduction scheme (that is, not `CUBLASLT_REDUCTION_SCHEME_NONE`) could return incorrect results for the bias gradient.
- `cublasLtMatmul` for `gemv`-like cases (that is, `m` or `n` equals 1) might ignore bias with the `CUBLASLT_EPILOGUE_RELU_BIAS` and `CUBLASLT_EPILOGUE_BIAS` epilogues.

Deprecations

- Disallow including `cublas.h` and `cublas_v2.h` in the same translation unit.
- Removed:

- ▶ `CUBLAS_MATMUL_STAGES_16x80` and `CUBLAS_MATMUL_STAGES_64x80` from `cublasLtMatmulStages_t`. No kernels utilize these stages anymore.
- ▶ `cublasLt3mMode_t`, `CUBLASLT_MATMUL_PREF_MATH_MODE_MASK`, and `CUBLASLT_MATMUL_PREF_GAUSSIAN_MODE_MASK` from `cublasLtMatmulPreferenceAttributes_t`. Instead, use the corresponding flags from `cublasLtNumericalImplFlags_t`.
- ▶ `CUBLASLT_MATMUL_PREF_POINTER_MODE_MASK`, `CUBLASLT_MATMUL_PREF_EPILOGUE_MASK`, and `CUBLASLT_MATMUL_PREF_SM_COUNT_TARGET` from `cublasLtMatmulPreferenceAttributes_t`. The corresponding parameters are taken directly from `cublasLtMatmulDesc_t`.
- ▶ `CUBLASLT_POINTER_MODE_MASK_NO_FILTERING` from `cublasLtPointerModeMask_t`. This mask was only applicable to `CUBLASLT_MATMUL_PREF_MATH_MODE_MASK` which was removed.

5.2. cuFFT Library

5.2.1. cuFFT: Release 12.5

▶ New Features

- ▶ Added [Just-In-Time Link-Time Optimized \(JIT LTO\) kernels](#) for improved performance in R2C and C2R FFTs for many sizes.
 - ▶ We recommend testing your R2C / C2R use cases with and without JIT LTO kernels and comparing the resulting performance. You can enable JIT LTO kernels using the [per-plan properties](#) cuFFT API.

5.2.2. cuFFT: Release 12.4 Update 1

▶ Resolved Issues

- ▶ A routine from the [cuFFT LTO EA library](#) was added by mistake to the cuFFT Advanced API header (`cufftXt.h`) in CUDA 12.4. This routine has now been removed from the header.

5.2.3. cuFFT: Release 12.4

▶ New Features

- ▶ Added [Just-In-Time Link-Time Optimized \(JIT LTO\) kernels](#) for improved performance in FFTs with 64-bit indexing.
- ▶ Added [per-plan properties](#) to the cuFFT API. These new routines can be leveraged to give users more control over the behavior of cuFFT. Currently they can be used to enable JIT LTO kernels for 64-bit FFTs.
- ▶ Improved accuracy for certain single-precision (fp32) FFT cases, especially involving FFTs for larger sizes.

► Known Issues

- A routine from the cuFFT LTO EA library was added by mistake to the cuFFT Advanced API header (`cufftXt.h`). This routine is not supported by cuFFT, and will be removed from the header in a future release.

► Resolved Issues

- Fixed an issue that could cause overwriting of user data when performing out-of-place real-to-complex (R2C) transforms with user-specified output strides (i.e. using the `ostride` component of the [Advanced Data Layout API](#)).
- Fixed inconsistent behavior between `libcufftw` and `FFTW` when both `inembed` and `onembed` are `nullptr` / `NULL`. From now on, as in `FFTW`, passing `nullptr` / `NULL` as `inembed` / `onembed` parameter is equivalent to passing `n`, that is, the logical size for that dimension.

5.2.4. cuFFT: Release 12.3 Update 1

► Known Issues

- Executing a real-to-complex (R2C) or complex-to-real (C2R) plan in a context different to the one used to create the plan could cause undefined behavior. This issue will be fixed in an upcoming release of cuFFT.

► Resolved Issues

- Complex-to-complex (C2C) execution functions (`cufftExec` and similar) now properly error-out in case of error during kernel launch, for example due to a missing CUDA context.

5.2.5. cuFFT: Release 12.3

► New Features

- Callback kernels are more relaxed in terms of resource usage, and will use fewer registers.
- Improved accuracy for double precision prime and composite FFT sizes with factors larger than 127.
- Slightly improved planning times for some FFT sizes.

5.2.6. cuFFT: Release 12.2

► New Features

- `cufftSetStream` can be used in multi-GPU plans with a stream from any GPU context, instead of from the primary context of the first GPU listed in `cufftXtSetGPUs`.
- Improved performance of 1000+ of FFTs of sizes ranging from 62 to 16380. The improved performance spans hundreds of single precision and double precision cases for FFTs with contiguous data layout, across multiple GPU architectures (from Maxwell to Hopper GPUs) via PTX JIT.
- Reduced the size of the static libraries when compared to cuFFT in the 12.1 release.

► Resolved Issues

- ▶ cuFFT no longer exhibits a race condition when threads simultaneously create and access plans with more than 1023 plans alive.
- ▶ cuFFT no longer exhibits a race condition when multiple threads call `cufftXtSetGPUs` concurrently.

5.2.7. cuFFT: Release 12.1 Update 1

▶ **Known Issues**

- ▶ cuFFT exhibits a race condition when one thread calls `cufftCreate` (or `cufftDestroy`) and another thread calls any API (except `cufftCreate` or `cufftDestroy`), and when the total number of plans alive exceeds 1023.
- ▶ cuFFT exhibits a race condition when multiple threads call `cufftXtSetGPUs` concurrently on different plans.

5.2.8. cuFFT: Release 12.1

▶ **New Features**

- ▶ Improved performance on Hopper GPUs for hundreds of FFTs of sizes ranging from 14 to 28800. The improved performance spans over 542 cases across single and double precision for FFTs with contiguous data layout.

▶ **Known Issues**

- ▶ Starting from CUDA 11.8, CUDA Graphs are no longer supported for callback routines that load data in out-of-place mode transforms. An upcoming release will update the cuFFT callback implementation, removing this limitation. cuFFT deprecated callback functionality based on separate compiled device code in cuFFT 11.4.

▶ **Resolved Issues**

- ▶ cuFFT no longer produces errors with compute-sanitizer at program exit if the CUDA context used at plan creation was destroyed prior to program exit.

5.2.9. cuFFT: Release 12.0 Update 1

▶ **Resolved Issues**

- ▶ Scratch space requirements for multi-GPU, single-batch, 1D FFTs were reduced.

5.2.10. cuFFT: Release 12.0

► New Features

- PTX JIT kernel compilation allowed the addition of many new accelerated cases for Maxwell, Pascal, Volta and Turing architectures.

► Known Issues

- cuFFT plan generation time increases due to PTX JIT compiling. Refer to [Plan Initialization Time](#).

► Resolved Issues

- cuFFT plans had an unintentional small memory overhead (of a few kB) per plan. This is resolved.

5.3. cuSOLVER Library

5.3.1. cuSOLVER: Release 12.5

► New Features

- Performance improvements of `cusolverDnXgesvd` and `cusolverDn<t>gesvd` if `jobu != 'N'` or `jobvt != 'N'`.
- Performance improvements of `cusolverDnXgesvdp` if `jobz = CUSOLVER_EIG_MODE_NOVECTOR`.

► Known Issues

- With CUDA Toolkit 12.4 Update 1, values `ldt > k` in calls of `cusolverDnXlarft` can result in out-of-bound memory accesses on `bufferOnDevice`. As a workaround it is possible to allocate a larger device workspace buffer of size `workspaceInBytesOnDevice=ALIGN_32((ldt*k + n*k)*sizeofCudaDataType(dataTypeT))`, with

```
auto ALIGN_32= [](int64_t val) {
    return ((val + 31)/32)*32;
};
```

and

```
auto sizeofCudaDataType= [](cudaDataType dt) {
    if (dt == CUDA_R_32F) return sizeof(float);
    if (dt == CUDA_R_64F) return sizeof(double);
    if (dt == CUDA_C_32F) return sizeof(cuComplex);
    if (dt == CUDA_C_64F) return sizeof(cuDoubleComplex);
};
```

5.3.2. cuSOLVER: Release 12.4 Update 1

► New Features

- The performance of `cusolverDnXlarft` has been improved. For large matrices, the speedup might exceed 100x. The performance on H100 is now consistently better than on A100. The change in `cusolverDnXlarft` also results in a modest speedup in `cusolverDn<t>ormqr`, `cusolverDn<t>ormtr`, and `cusolverDnXsyevd`.
- The performance of `cusolverDnXgesvd` when singular vectors are sought has been improved. The job configuration that computes both left and right singular vectors is up to 1.5x faster.

► Resolved Issues

- `cusolverDnXtrtri_bufferSize` now returns the correct workspace size in bytes.

► Deprecations

- Using long-deprecated `cusolverDnPotrf`, `cusolverDnPotrs`, `cusolverDnGeqrf`, `cusolverDnGetrf`, `cusolverDnGetrs`, `cusolverDnSyevd`, `cusolverDnSyevdx`, `cusolverDnGesvd`, and their accompanying `bufferSize` functions will result in a deprecation warning. The warning can be turned off by using the `-DDISABLE_CUSOLVER_DEPRECATED` flag while compiling; however, users should use `cusolverDnXpotrf`, `cusolverDnXpotrs`, `cusolverDnXgeqrf`, `cusolverDnXgetrf`, `cusolverDnXgetrs`, `cusolverDnXsyevd`, `cusolverDnXsyevdx`, `cusolverDnXgesvd`, and the corresponding `bufferSize` functions instead.

5.3.3. cuSOLVER: Release 12.4

► New Features

- `cusolverDnXlarft` and `cusolverDnXlarft_bufferSize` APIs were introduced. `cusolverDnXlarft` forms the triangular factor of a real block reflector, while `cusolverDnXlarft_bufferSize` returns its required workspace sizes in bytes.

► Known Issues

- `cusolverDnXtrtri_bufferSize`` returns an incorrect required device workspace size. As a workaround the returned size can be multiplied by the size of the data type (for example, 8 bytes if matrix A is of type double) to obtain the correct workspace size.

5.3.4. cuSOLVER: Release 12.2 Update 2

► Resolved Issues

- Fixed an issue with `cusolverDn<t>gesvd()`, `cusolverDnGesvd()`, and `cusolverDnXgesvd()`, which could cause wrong results for matrices larger than 18918 if `jobu` or `jobvt` was unequal to 'N'.

5.3.5. cuSOLVER: Release 12.2

► New Features

- A new API to ensure deterministic results or allow non-deterministic results for improved performance. See `cusolverDnSetDeterministicMode()` and `cusolverDnGetDeterministicMode()`. Affected functions are: `cusolverDn<t>geqrf()`, `cusolverDn<t>syevd()`, `cusolverDn<t>syevdx()`, `cusolverDn<t>gesvdj()`, `cusolverDnXgeqrf()`, `cusolverDnXsyevd()`, `cusolverDnXsyevdx()`, `cusolverDnXgesvdr()`, and `cusolverDnXgesvdp()`.

► Known Issues

- Concurrent executions of `cusolverDn<t>getrf()` or `cusolverDnXgetrf()` in different non-blocking CUDA streams on the same device might result in a deadlock.

5.4. cuSPARSE Library

5.4.1. cuSPARSE: Release 12.5

► New Features

- Added support for mixed input types in SpMV: single precision input matrix, double precision input vector, double precision output vector.

► Resolved Issues

- `cusparseSpMV()` introduces invalid memory accesses when the output vector is not aligned to 16 bytes.

5.4.2. cuSPARSE: Release 12.4

► New Features

- Added the preprocessing step for sparse matrix-vector multiplication `cusparseSpMV_preprocess()`.
- Added support for mixed real and complex types for `cusparseSpMM()`.
- Added a new API `cusparseSpSM_updateMatrix()` to update the sparse matrix between the analysis and solving phase of `cusparseSpSM()`.

► Known Issues

- `cusparseSpMV()` introduces invalid memory accesses when the output vector is not aligned to 16 bytes.

► Resolved Issues

- `cusparseSpVV()` provided incorrect results when the sparse vector has many non-zeros.

5.4.3. cuSPARSE: Release 12.3 Update 1

► New Features

- Added support for block sizes of 64 and 128 in `cusparseSDDMM()`.
- Added a preprocessing step `cusparseSDDMM_preprocess()` for BSR `cusparseSDDMM()` that helps improve performance of the main computing stage.

5.4.4. cuSPARSE: Release 12.3

► New Features

- The `cusparseSpSV_bufferSize()` and `cusparseSpSV_analysis()` routines now accept NULL pointers for the dense vector.
- The `cusparseSpSM_bufferSize()` and `cusparseSpSM_analysis()` routines now accept dense matrix descriptors with NULL pointer for values.

► Known Issues

- The `cusparseSpSV_analysis()` and `cusparseSpSM_analysis()` routines are blocking calls/not asynchronous.
- Wrong results can occur for `cusparseSpSV()` using sliced ELLPACK format and transpose/transpose conjugate operation on matrix A.

► Resolved Issues

- `cusparseSpSV()` provided indeterministic results in some cases.
- Fixed an issue that caused `cusparseSpSV_analysis()` to hang sometimes in a multi-thread environment.
- Fixed an issue with `cusparseSpSV()` and `cusparseSpSV()` that sometimes yielded wrong output when the output vector/matrix or input matrix contained NaN.

5.4.5. cuSPARSE: Release 12.2 Update 1

► New Features

- The library now provides the opportunity to dump sparse matrices to files during the creation of the descriptor for debugging purposes. See logging API <https://docs.nvidia.com/cuda/cusparse/index.html#cusparse-logging-api>.

► Resolved Issues

- Removed `CUSPARSE_SPMM_CSR_ALG3` fallback to avoid confusion in the algorithm selection process.
- Clarified the supported operations for `cusparseSDDMM()`.
- `cusparseCreateConstSlicedEll()` now uses const pointers.
- Fixed wrong results in rare edge cases of `cusparseCsr2CscEx2()` with base 1 indexing.
- `cusparseSpSM_bufferSize()` could ask slightly less memory than needed.

- ▶ `cusparseSpMV()` now checks the validity of the buffer pointer only when it is strictly needed.
- ▶ **Deprecations**
 - ▶ Several legacy APIs have been officially deprecated. A compile-time warning has been added to all of them.

5.4.6. cuSPARSE: Release 12.1 Update 1

- ▶ **New Features**
 - ▶ Introduced Block Sparse Row (BSR) sparse matrix storage for the Generic APIs with support for SDDMM routine (`cusparseSDDMM`).
 - ▶ Introduced Sliced Ellpack (SELL) sparse matrix storage format for the Generic APIs with support for sparse matrix-vector multiplication (`cusparseSpMV`) and triangular solver with a single right-hand side (`cusparseSpSV`).
 - ▶ Added a new API call (`cusparseSpSV_updateMatrix`) to update matrix values and/or the matrix diagonal in the sparse triangular solver with a single right-hand side after the analysis step.

5.4.7. cuSPARSE: Release 12.0 Update 1

- ▶ **New Features**
 - ▶ `cusparseSDDMM()` now supports mixed precision computation.
 - ▶ Improved `cusparseSpMM()` alg2 mixed-precision performance on some matrices on NVIDIA Ampere architecture GPUs.
 - ▶ Improved `cusparseSpMV()` performance with a new load balancing algorithm.
 - ▶ `cusparseSpSV()` and `cusparseSpSM()` now support in-place computation, namely the output and input vectors/matrices have the same memory address.
- ▶ **Resolved Issues**
 - ▶ `cusparseSpSM()` could produce wrong results if the leading dimension (ld) of the RHS matrix is greater than the number of columns/rows.

5.4.8. cuSPARSE: Release 12.0

- ▶ **New Features**
 - ▶ JIT LTO functionalities (`cusparseSpMMOp()`) switched from driver to `nvJitLto` library. Starting from CUDA 12.0 the user needs to link to `libnvJitLto.so`, see [cuSPARSE documentation](#). JIT LTO performance has also been improved for `cusparseSpMMOpPlan()`.
 - ▶ Introduced const descriptors for the Generic APIs, for example, `cusparseConstSpVecGet()`. Now the Generic APIs interface clearly declares when a descriptor and its data are modified by the cuSPARSE functions.

- ▶ Added two new algorithms to `cusparseSpGEMM()` with lower memory utilization. The first algorithm computes a strict bound on the number of intermediate product, while the second one allows partitioning the computation in chunks.
- ▶ Added `int8_t` support to `cusparseGather()`, `cusparseScatter()`, and `cusparseCsr2cscEx2()`.
- ▶ Improved `cusparseSpSV()` performance for both the analysis and the solving phases.
- ▶ Improved `cusparseSpSM()` performance for both the analysis and the solving phases.
- ▶ Improved `cusparseSDDMM()` performance and added support for batch computation.
- ▶ Improved `cusparseCsr2cscEx2()` performance.
- ▶ **Resolved Issues**
 - ▶ `cusparseSpSV()` and `cusparseSpSM()` could produce wrong results.
 - ▶ `cusparseDnMatGetStridedBatch()` did not accept `batchStride == 0`.
- ▶ **Deprecations**
 - ▶ Removed deprecated CUDA 11.x APIs, enumerators, and descriptors.

5.5. Math Library

5.5.1. CUDA Math: Release 12.5

- ▶ **Known Issues**
 - ▶ As a result of ongoing testing we updated the interval bounds in which double precision `lgamma()` function may experience greater than the documented 4 ulp accuracy loss. New interval shall read (-23.0001; -2.2637). This finding is applicable to CUDA 12.5 and all previous versions.

5.5.2. CUDA Math: Release 12.4

- ▶ **Resolved Issues**
 - ▶ Host-specific code in `cuda_fp16/bf16` headers is now free from type-punning and shall work correctly in the presence of optimizations based on strict-aliasing rules.

5.5.3. CUDA Math: Release 12.3

- ▶ **New Features**
 - ▶ Performance of SIMD Integer CUDA Math APIs was improved.
- ▶ **Resolved Issues**

- ▶ The `__hisinf()` Math APIs from `cuda_fp16.h` and `cuda_bf16.h` headers were silently producing wrong results if compiled with the `-std=c++20` compiler option because of an underlying `nvcc` compiler issue, resolved in version 12.3.

▶ Known Issues

- ▶ Users of `cuda_fp16.h` and `cuda_bf16.h` headers are advised to disable host compilers strict aliasing rules based optimizations (e.g. pass `-fno-strict-aliasing` to host GCC compiler) as these may interfere with the type-punning idioms used in the `__half`, `__half2`, `__nv_bfloat16`, `__nv_bfloat162` types implementations and expose the user program to undefined behavior. Note, the headers suppress GCC diagnostics through: `#pragma GCC diagnostic ignored -Wstrict-aliasing`. This behavior may improve in future versions of the headers.

5.5.4. CUDA Math: Release 12.2

▶ New Features

- ▶ CUDA Math APIs for `__half` and `__nv_bfloat16` types received usability improvements, including host side `<emulated>` support for many of the arithmetic operations and conversions.
- ▶ `__half` and `__nv_bfloat16` types have implicit conversions to/from integral types, which are now available with host compilers by default. These may cause build issues due to ambiguous overloads resolution. Users are advised to update their code to select proper overloads. To opt-out user may want to define the following macros (these macros will be removed in the future CUDA release):
 - ▶ `__CUDA_FP16_DISABLE_IMPLICIT_INTEGER_CONVERTS_FOR_HOST_COMPILERS__`
 - ▶ `__CUDA_BF16_DISABLE_IMPLICIT_INTEGER_CONVERTS_FOR_HOST_COMPILERS__`

▶ Resolved Issues

- ▶ During ongoing testing, NVIDIA identified that due to an algorithm error the results of 64-bit floating-point division in default round-to-nearest-even mode could produce spurious overflow to infinity. NVIDIA recommends that all developers requiring strict IEEE754 compliance update to CUDA Toolkit 12.2 or newer. The affected algorithm was present in both offline compilation as well as just-in-time (JIT) compilation. As JIT compilation is handled by the driver, NVIDIA recommends updating to driver version greater than or equal to R535 (R536 on Windows) when IEEE754 compliance is required and when using JIT. This is a software algorithm fix and is not tied to specific hardware.
- ▶ Updated the observed worst case error bounds for single precision intrinsic functions `__expf()`, `__exp10f()` and double precision functions `asinh()`, `acosh()`.

5.5.5. CUDA Math: Release 12.1

▶ New Features

- ▶ Performance and accuracy improvements in `atanf`, `acosf`, `asinf`, `sinpif`, `cospif`, `powf`, `erff`, and `tgammaf`.

5.5.6. CUDA Math: Release 12.0

▶ New Features

- ▶ Introduced new integer/fp16/bf16 CUDA Math APIs to help expose performance benefits of new DPX instructions. Refer to <https://docs.nvidia.com/cuda/cuda-math-api/index.html>.

▶ Known Issues

- ▶ Double precision inputs that cause the double precision division algorithm in the default 'round to nearest even mode' produce spurious overflow: an infinite result is delivered where `DBL_MAX 0x7FEF_FFFF_FFFF_FFFF` is expected. Affected CUDA Math APIs: `__ddiv_rn()`. Affected CUDA language operation: double precision / operation in the device code.

▶ Deprecations

- ▶ All previously deprecated undocumented APIs are removed from CUDA 12.0.

5.6. NVIDIA Performance Primitives (NPP)

5.6.1. NPP: Release 12.4

▶ New Features

- ▶ Enhanced large file support with `size_t`.

5.6.2. NPP: Release 12.0

▶ Deprecations

- ▶ Deprecating non-CTX API support from next release.

▶ Resolved Issues

- ▶ A performance issue with the NPP `ResizeSqrPixel` API is now fixed and shows improved performance.

5.7. nvJPEG Library

5.7.1. nvJPEG: Release 12.4

► New Features

- IDCT performance optimizations for single image CUDA decode.
- Zero Copy behavior has been changed: Setting `NVJPEG_FLAGS_REduced_MEMORY_DECODE_ZERO_COPY` flag will no longer enable `NVJPEG_FLAGS_REduced_MEMORY_DECODE`.

5.7.2. nvJPEG: Release 12.3 Update 1

► New Features

- New APIs: `nvjpegBufferPinnedResize` and `nvjpegBufferDeviceResize` which can be used to resize pinned and device buffers before using them.

5.7.3. nvJPEG: Release 12.2

► New Features

- Added support for JPEG Lossless decode (process 14, FO prediction).
- nvJPEG is now supported on L4T.

5.7.4. nvJPEG: Release 12.0

► New Features

- Improved the GPU Memory optimisation for the nvJPEG codec.

► Resolved Issues

- An issue that causes runtime failures when `nvJPEGDecMultipleInstances` was tested with a large number of threads is resolved.
- An issue with CMYK four component color conversion is now resolved.

► Known Issues

- Backend `NVJPEG_BACKEND_GPU_HYBRID` - Unable to handle bistreams with extra scans lengths.

► Deprecations

- The reuse of Huffman table in Encoder (`nvjpegEncoderParamsCopyHuffmanTables`).

Chapter 6. Notices

6.1. Notice

This document is provided for information purposes only and shall not be regarded as a warranty of a certain functionality, condition, or quality of a product. NVIDIA Corporation (“NVIDIA”) makes no representations or warranties, expressed or implied, as to the accuracy or completeness of the information contained in this document and assumes no responsibility for any errors contained herein. NVIDIA shall have no liability for the consequences or use of such information or for any infringement of patents or other rights of third parties that may result from its use. This document is not a commitment to develop, release, or deliver any Material (defined below), code, or functionality.

NVIDIA reserves the right to make corrections, modifications, enhancements, improvements, and any other changes to this document, at any time without notice.

Customer should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

NVIDIA products are sold subject to the NVIDIA standard terms and conditions of sale supplied at the time of order acknowledgement, unless otherwise agreed in an individual sales agreement signed by authorized representatives of NVIDIA and customer (“Terms of Sale”). NVIDIA hereby expressly objects to applying any customer general terms and conditions with regards to the purchase of the NVIDIA product referenced in this document. No contractual obligations are formed either directly or indirectly by this document.

NVIDIA products are not designed, authorized, or warranted to be suitable for use in medical, military, aircraft, space, or life support equipment, nor in applications where failure or malfunction of the NVIDIA product can reasonably be expected to result in personal injury, death, or property or environmental damage. NVIDIA accepts no liability for inclusion and/or use of NVIDIA products in such equipment or applications and therefore such inclusion and/or use is at customer’s own risk.

NVIDIA makes no representation or warranty that products based on this document will be suitable for any specified use. Testing of all parameters of each product is not necessarily performed by NVIDIA. It is customer’s sole responsibility to evaluate and determine the applicability of any information contained in this document, ensure the product is suitable and fit for the application planned by customer, and perform the necessary testing for the application in order to avoid a default of the application or the product. Weaknesses in customer’s product designs may affect the quality and reliability of the NVIDIA product and may result in additional or different conditions and/or requirements beyond those contained in this document. NVIDIA accepts no liability related to any default, damage, costs, or problem which may be based on or attributable to: (i) the use of the NVIDIA product in any manner that is contrary to this document or (ii) customer product designs.

No license, either expressed or implied, is granted under any NVIDIA patent right, copyright, or other NVIDIA intellectual property right under this document. Information published by NVIDIA regarding third-party products or services does not constitute a license from NVIDIA to use such products or

services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property rights of the third party, or a license from NVIDIA under the patents or other intellectual property rights of NVIDIA.

Reproduction of information in this document is permissible only if approved in advance by NVIDIA in writing, reproduced without alteration and in full compliance with all applicable export laws and regulations, and accompanied by all associated conditions, limitations, and notices.

THIS DOCUMENT AND ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE. TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL NVIDIA BE LIABLE FOR ANY DAMAGES, INCLUDING WITHOUT LIMITATION ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF ANY USE OF THIS DOCUMENT, EVEN IF NVIDIA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Notwithstanding any damages that customer might incur for any reason whatsoever, NVIDIA's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms of Sale for the product.

6.2. OpenCL

OpenCL is a trademark of Apple Inc. used under license to the Khronos Group Inc.

6.3. Trademarks

NVIDIA and the NVIDIA logo are trademarks or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

©2007-2024, NVIDIA Corporation & affiliates. All rights reserved