

NVIDIA Performance Primitives (NPP)
Version 8.0

January 28, 2016

Contents

1	NVIDIA Performance Primitives	1
1.1	What is NPP?	2
1.2	Documentation	2
1.3	Technical Specifications	3
1.4	Files	3
1.4.1	Header Files	3
1.4.2	Library Files	3
1.5	Supported NVIDIA Hardware	4
2	General API Conventions	5
2.1	Memory Management	6
2.1.1	Scratch Buffer and Host Pointer	6
2.2	Function Naming	7
2.3	Integer Result Scaling	7
2.4	Rounding Modes	8
2.4.1	Rounding Mode Parameter	8
3	Signal-Processing Specific API Conventions	9
3.1	Signal Data	10
3.1.1	Parameter Names for Signal Data	10
3.1.1.1	Source Signal Pointer	10
3.1.1.2	Destination Signal Pointer	10
3.1.1.3	In-Place Signal Pointer	10
3.1.2	Signal Data Alignment Requirements	11
3.1.3	Signal Data Related Error Codes	11
3.2	Signal Length	11
3.2.1	Length Related Error Codes	11
4	Imaging-Processing Specific API Conventions	13

4.1	Function Naming	14
4.2	Image Data	14
4.2.1	Line Step	15
4.2.2	Parameter Names for Image Data	15
4.2.2.1	Passing Source-Image Data	15
4.2.2.2	Passing Destination-Image Data	16
4.2.2.3	Passing In-Place Image Data	18
4.2.2.4	Passing Mask-Image Data	18
4.2.2.5	Passing Channel-of-Interest Data	18
4.2.3	Image Data Alignment Requirements	18
4.2.4	Image Data Related Error Codes	19
4.3	Region-of-Interest (ROI)	19
4.3.1	ROI Related Error Codes	19
4.4	Masked Operation	20
4.5	Channel-of-Interest API	20
4.5.1	Select-Channel Source-Image Pointer	20
4.5.2	Select-Channel Source-Image	20
4.5.3	Select-Channel Destination-Image Pointer	20
4.6	Source-Image Sampling	21
4.6.1	Point-Wise Operations	21
4.6.2	Neighborhood Operations	21
4.6.2.1	Mask-Size Parameter	21
4.6.2.2	Anchor-Point Parameter	22
4.6.2.3	Sampling Beyond Image Boundaries	22
5	Module Index	23
5.1	Modules	23
6	Data Structure Index	25
6.1	Data Structures	25
7	Module Documentation	27
7.1	NPP Core	27
7.1.1	Detailed Description	28
7.1.2	Function Documentation	28
7.1.2.1	nppGetGpuComputeCapability	28
7.1.2.2	nppGetGpuDeviceProperties	28
7.1.2.3	nppGetGpuName	28

7.1.2.4	nppGetGpuNumSMs	28
7.1.2.5	nppGetLibVersion	29
7.1.2.6	nppGetMaxThreadsPerBlock	29
7.1.2.7	nppGetMaxThreadsPerSM	29
7.1.2.8	nppGetStream	29
7.1.2.9	nppGetStreamMaxThreadsPerSM	29
7.1.2.10	nppGetStreamNumSMs	29
7.1.2.11	nppSetStream	30
7.2	NPP Type Definitions and Constants	31
7.2.1	Define Documentation	37
7.2.1.1	NPP_MAX_16S	37
7.2.1.2	NPP_MAX_16U	37
7.2.1.3	NPP_MAX_32S	37
7.2.1.4	NPP_MAX_32U	37
7.2.1.5	NPP_MAX_64S	37
7.2.1.6	NPP_MAX_64U	37
7.2.1.7	NPP_MAX_8S	37
7.2.1.8	NPP_MAX_8U	37
7.2.1.9	NPP_MAXABS_32F	37
7.2.1.10	NPP_MAXABS_64F	37
7.2.1.11	NPP_MIN_16S	38
7.2.1.12	NPP_MIN_16U	38
7.2.1.13	NPP_MIN_32S	38
7.2.1.14	NPP_MIN_32U	38
7.2.1.15	NPP_MIN_64S	38
7.2.1.16	NPP_MIN_64U	38
7.2.1.17	NPP_MIN_8S	38
7.2.1.18	NPP_MIN_8U	38
7.2.1.19	NPP_MINABS_32F	38
7.2.1.20	NPP_MINABS_64F	38
7.2.2	Enumeration Type Documentation	38
7.2.2.1	NppCmpOp	38
7.2.2.2	NppGpuComputeCapability	39
7.2.2.3	NppHintAlgorithm	39
7.2.2.4	NppiAlphaOp	39
7.2.2.5	NppiAxis	40

7.2.2.6	NppiBayerGridPosition	40
7.2.2.7	NppiBorderType	40
7.2.2.8	NppiDifferentialKernel	40
7.2.2.9	NppiHuffmanTableType	41
7.2.2.10	NppiInterpolationMode	41
7.2.2.11	NppiMaskSize	41
7.2.2.12	NppiNorm	42
7.2.2.13	NppRoundMode	42
7.2.2.14	NppStatus	43
7.2.2.15	NppsZCType	45
7.3	Basic NPP Data Types	46
7.3.1	Typedef Documentation	47
7.3.1.1	Npp16s	47
7.3.1.2	Npp16u	47
7.3.1.3	Npp32f	47
7.3.1.4	Npp32fc	47
7.3.1.5	Npp32s	47
7.3.1.6	Npp32sc	48
7.3.1.7	Npp32u	48
7.3.1.8	Npp32uc	48
7.3.1.9	Npp64f	48
7.3.1.10	Npp64fc	48
7.3.1.11	Npp64s	48
7.3.1.12	Npp64sc	48
7.3.1.13	Npp64u	48
7.3.1.14	Npp8s	48
7.3.1.15	Npp8u	48
7.3.2	Function Documentation	48
7.3.2.1	__align__	48
7.3.2.2	__align__	49
7.3.3	Variable Documentation	49
7.3.3.1	Npp16sc	49
7.3.3.2	Npp16uc	49
7.3.3.3	Npp8uc	49
7.4	Geometry Transforms	50
7.4.1	Detailed Description	50

7.4.2	Geometric Transform API Specifics	50
7.4.2.1	Geometric Transforms and ROIs	50
7.4.2.2	Pixel Interpolation	51
7.5	ResizeSqrPixel	52
7.5.1	Detailed Description	55
7.5.2	Error Codes	56
7.5.3	Function Documentation	56
7.5.3.1	nppiGetResizeRect	56
7.5.3.2	nppiResizeAdvancedGetBufferHostSize_8u_C1R	56
7.5.3.3	nppiResizeSqrPixel_16s_AC4R	57
7.5.3.4	nppiResizeSqrPixel_16s_C1R	57
7.5.3.5	nppiResizeSqrPixel_16s_C3R	58
7.5.3.6	nppiResizeSqrPixel_16s_C4R	58
7.5.3.7	nppiResizeSqrPixel_16s_P3R	59
7.5.3.8	nppiResizeSqrPixel_16s_P4R	59
7.5.3.9	nppiResizeSqrPixel_16u_AC4R	60
7.5.3.10	nppiResizeSqrPixel_16u_C1R	60
7.5.3.11	nppiResizeSqrPixel_16u_C3R	61
7.5.3.12	nppiResizeSqrPixel_16u_C4R	61
7.5.3.13	nppiResizeSqrPixel_16u_P3R	62
7.5.3.14	nppiResizeSqrPixel_16u_P4R	62
7.5.3.15	nppiResizeSqrPixel_32f_AC4R	63
7.5.3.16	nppiResizeSqrPixel_32f_C1R	64
7.5.3.17	nppiResizeSqrPixel_32f_C3R	64
7.5.3.18	nppiResizeSqrPixel_32f_C4R	65
7.5.3.19	nppiResizeSqrPixel_32f_P3R	65
7.5.3.20	nppiResizeSqrPixel_32f_P4R	66
7.5.3.21	nppiResizeSqrPixel_64f_AC4R	66
7.5.3.22	nppiResizeSqrPixel_64f_C1R	67
7.5.3.23	nppiResizeSqrPixel_64f_C3R	67
7.5.3.24	nppiResizeSqrPixel_64f_C4R	68
7.5.3.25	nppiResizeSqrPixel_64f_P3R	68
7.5.3.26	nppiResizeSqrPixel_64f_P4R	69
7.5.3.27	nppiResizeSqrPixel_8u_AC4R	69
7.5.3.28	nppiResizeSqrPixel_8u_C1R	70
7.5.3.29	nppiResizeSqrPixel_8u_C1R_Advanced	70

7.5.3.30	<code>nppiResizeSqrPixel_8u_C3R</code>	71
7.5.3.31	<code>nppiResizeSqrPixel_8u_C4R</code>	71
7.5.3.32	<code>nppiResizeSqrPixel_8u_P3R</code>	72
7.5.3.33	<code>nppiResizeSqrPixel_8u_P4R</code>	72
7.6	Resize	74
7.6.1	Detailed Description	75
7.6.2	Error Codes	76
7.6.3	Function Documentation	76
7.6.3.1	<code>nppiResize_16u_AC4R</code>	76
7.6.3.2	<code>nppiResize_16u_C1R</code>	77
7.6.3.3	<code>nppiResize_16u_C3R</code>	77
7.6.3.4	<code>nppiResize_16u_C4R</code>	78
7.6.3.5	<code>nppiResize_16u_P3R</code>	78
7.6.3.6	<code>nppiResize_16u_P4R</code>	79
7.6.3.7	<code>nppiResize_32f_AC4R</code>	79
7.6.3.8	<code>nppiResize_32f_C1R</code>	80
7.6.3.9	<code>nppiResize_32f_C3R</code>	80
7.6.3.10	<code>nppiResize_32f_C4R</code>	81
7.6.3.11	<code>nppiResize_32f_P3R</code>	81
7.6.3.12	<code>nppiResize_32f_P4R</code>	82
7.6.3.13	<code>nppiResize_8u_AC4R</code>	82
7.6.3.14	<code>nppiResize_8u_C1R</code>	83
7.6.3.15	<code>nppiResize_8u_C3R</code>	83
7.6.3.16	<code>nppiResize_8u_C4R</code>	84
7.6.3.17	<code>nppiResize_8u_P3R</code>	84
7.6.3.18	<code>nppiResize_8u_P4R</code>	85
7.7	Remap	86
7.7.1	Detailed Description	89
7.7.2	Error Codes	89
7.7.3	Function Documentation	89
7.7.3.1	<code>nppiRemap_16s_AC4R</code>	89
7.7.3.2	<code>nppiRemap_16s_C1R</code>	90
7.7.3.3	<code>nppiRemap_16s_C3R</code>	91
7.7.3.4	<code>nppiRemap_16s_C4R</code>	91
7.7.3.5	<code>nppiRemap_16s_P3R</code>	92
7.7.3.6	<code>nppiRemap_16s_P4R</code>	92

7.7.3.7	nppiRemap_16u_AC4R	93
7.7.3.8	nppiRemap_16u_C1R	94
7.7.3.9	nppiRemap_16u_C3R	94
7.7.3.10	nppiRemap_16u_C4R	95
7.7.3.11	nppiRemap_16u_P3R	95
7.7.3.12	nppiRemap_16u_P4R	96
7.7.3.13	nppiRemap_32f_AC4R	97
7.7.3.14	nppiRemap_32f_C1R	97
7.7.3.15	nppiRemap_32f_C3R	98
7.7.3.16	nppiRemap_32f_C4R	98
7.7.3.17	nppiRemap_32f_P3R	99
7.7.3.18	nppiRemap_32f_P4R	99
7.7.3.19	nppiRemap_64f_AC4R	100
7.7.3.20	nppiRemap_64f_C1R	101
7.7.3.21	nppiRemap_64f_C3R	101
7.7.3.22	nppiRemap_64f_C4R	102
7.7.3.23	nppiRemap_64f_P3R	102
7.7.3.24	nppiRemap_64f_P4R	103
7.7.3.25	nppiRemap_8u_AC4R	104
7.7.3.26	nppiRemap_8u_C1R	104
7.7.3.27	nppiRemap_8u_C3R	105
7.7.3.28	nppiRemap_8u_C4R	105
7.7.3.29	nppiRemap_8u_P3R	106
7.7.3.30	nppiRemap_8u_P4R	106
7.8	Rotate	108
7.8.1	Detailed Description	109
7.8.2	Rotate Error Codes	109
7.8.3	Function Documentation	109
7.8.3.1	nppiGetRotateBound	109
7.8.3.2	nppiGetRotateQuad	110
7.8.3.3	nppiRotate_16u_AC4R	110
7.8.3.4	nppiRotate_16u_C1R	111
7.8.3.5	nppiRotate_16u_C3R	111
7.8.3.6	nppiRotate_16u_C4R	112
7.8.3.7	nppiRotate_32f_AC4R	112
7.8.3.8	nppiRotate_32f_C1R	113

7.8.3.9	nppiRotate_32f_C3R	113
7.8.3.10	nppiRotate_32f_C4R	114
7.8.3.11	nppiRotate_8u_AC4R	114
7.8.3.12	nppiRotate_8u_C1R	115
7.8.3.13	nppiRotate_8u_C3R	115
7.8.3.14	nppiRotate_8u_C4R	116
7.9	Mirror	117
7.9.1	Detailed Description	120
7.9.2	Mirror Error Codes	120
7.9.3	Function Documentation	120
7.9.3.1	nppiMirror_16s_AC4IR	120
7.9.3.2	nppiMirror_16s_AC4R	120
7.9.3.3	nppiMirror_16s_C1IR	121
7.9.3.4	nppiMirror_16s_C1R	121
7.9.3.5	nppiMirror_16s_C3IR	121
7.9.3.6	nppiMirror_16s_C3R	122
7.9.3.7	nppiMirror_16s_C4IR	122
7.9.3.8	nppiMirror_16s_C4R	122
7.9.3.9	nppiMirror_16u_AC4IR	123
7.9.3.10	nppiMirror_16u_AC4R	123
7.9.3.11	nppiMirror_16u_C1IR	124
7.9.3.12	nppiMirror_16u_C1R	124
7.9.3.13	nppiMirror_16u_C3IR	124
7.9.3.14	nppiMirror_16u_C3R	125
7.9.3.15	nppiMirror_16u_C4IR	125
7.9.3.16	nppiMirror_16u_C4R	125
7.9.3.17	nppiMirror_32f_AC4IR	126
7.9.3.18	nppiMirror_32f_AC4R	126
7.9.3.19	nppiMirror_32f_C1IR	126
7.9.3.20	nppiMirror_32f_C1R	127
7.9.3.21	nppiMirror_32f_C3IR	127
7.9.3.22	nppiMirror_32f_C3R	127
7.9.3.23	nppiMirror_32f_C4IR	128
7.9.3.24	nppiMirror_32f_C4R	128
7.9.3.25	nppiMirror_32s_AC4IR	128
7.9.3.26	nppiMirror_32s_AC4R	129

7.9.3.27	nppiMirror_32s_C1IR	129
7.9.3.28	nppiMirror_32s_C1R	129
7.9.3.29	nppiMirror_32s_C3IR	130
7.9.3.30	nppiMirror_32s_C3R	130
7.9.3.31	nppiMirror_32s_C4IR	130
7.9.3.32	nppiMirror_32s_C4R	131
7.9.3.33	nppiMirror_8u_AC4IR	131
7.9.3.34	nppiMirror_8u_AC4R	131
7.9.3.35	nppiMirror_8u_C1IR	132
7.9.3.36	nppiMirror_8u_C1R	132
7.9.3.37	nppiMirror_8u_C3IR	132
7.9.3.38	nppiMirror_8u_C3R	133
7.9.3.39	nppiMirror_8u_C4IR	133
7.9.3.40	nppiMirror_8u_C4R	133
7.10	Affine Transforms	134
7.10.1	Detailed Description	143
7.10.2	Affine Transform Error Codes	143
7.10.3	Function Documentation	143
7.10.3.1	nppiGetAffineBound	143
7.10.3.2	nppiGetAffineQuad	143
7.10.3.3	nppiGetAffineTransform	144
7.10.3.4	nppiWarpAffine_16u_AC4R	145
7.10.3.5	nppiWarpAffine_16u_C1R	145
7.10.3.6	nppiWarpAffine_16u_C3R	146
7.10.3.7	nppiWarpAffine_16u_C4R	146
7.10.3.8	nppiWarpAffine_16u_P3R	147
7.10.3.9	nppiWarpAffine_16u_P4R	147
7.10.3.10	nppiWarpAffine_32f_AC4R	148
7.10.3.11	nppiWarpAffine_32f_C1R	148
7.10.3.12	nppiWarpAffine_32f_C3R	149
7.10.3.13	nppiWarpAffine_32f_C4R	149
7.10.3.14	nppiWarpAffine_32f_P3R	150
7.10.3.15	nppiWarpAffine_32f_P4R	150
7.10.3.16	nppiWarpAffine_32s_AC4R	151
7.10.3.17	nppiWarpAffine_32s_C1R	151
7.10.3.18	nppiWarpAffine_32s_C3R	152

7.10.3.19	nppiWarpAffine_32s_C4R	152
7.10.3.20	nppiWarpAffine_32s_P3R	153
7.10.3.21	nppiWarpAffine_32s_P4R	153
7.10.3.22	nppiWarpAffine_64f_AC4R	154
7.10.3.23	nppiWarpAffine_64f_C1R	154
7.10.3.24	nppiWarpAffine_64f_C3R	155
7.10.3.25	nppiWarpAffine_64f_C4R	155
7.10.3.26	nppiWarpAffine_64f_P3R	156
7.10.3.27	nppiWarpAffine_64f_P4R	156
7.10.3.28	nppiWarpAffine_8u_AC4R	157
7.10.3.29	nppiWarpAffine_8u_C1R	157
7.10.3.30	nppiWarpAffine_8u_C3R	158
7.10.3.31	nppiWarpAffine_8u_C4R	158
7.10.3.32	nppiWarpAffine_8u_P3R	159
7.10.3.33	nppiWarpAffine_8u_P4R	159
7.10.3.34	nppiWarpAffineBack_16u_AC4R	160
7.10.3.35	nppiWarpAffineBack_16u_C1R	160
7.10.3.36	nppiWarpAffineBack_16u_C3R	161
7.10.3.37	nppiWarpAffineBack_16u_C4R	161
7.10.3.38	nppiWarpAffineBack_16u_P3R	162
7.10.3.39	nppiWarpAffineBack_16u_P4R	162
7.10.3.40	nppiWarpAffineBack_32f_AC4R	163
7.10.3.41	nppiWarpAffineBack_32f_C1R	163
7.10.3.42	nppiWarpAffineBack_32f_C3R	164
7.10.3.43	nppiWarpAffineBack_32f_C4R	164
7.10.3.44	nppiWarpAffineBack_32f_P3R	165
7.10.3.45	nppiWarpAffineBack_32f_P4R	165
7.10.3.46	nppiWarpAffineBack_32s_AC4R	166
7.10.3.47	nppiWarpAffineBack_32s_C1R	166
7.10.3.48	nppiWarpAffineBack_32s_C3R	167
7.10.3.49	nppiWarpAffineBack_32s_C4R	167
7.10.3.50	nppiWarpAffineBack_32s_P3R	168
7.10.3.51	nppiWarpAffineBack_32s_P4R	168
7.10.3.52	nppiWarpAffineBack_8u_AC4R	169
7.10.3.53	nppiWarpAffineBack_8u_C1R	169
7.10.3.54	nppiWarpAffineBack_8u_C3R	170

7.10.3.55	nppiWarpAffineBack_8u_C4R	170
7.10.3.56	nppiWarpAffineBack_8u_P3R	171
7.10.3.57	nppiWarpAffineBack_8u_P4R	171
7.10.3.58	nppiWarpAffineQuad_16u_AC4R	172
7.10.3.59	nppiWarpAffineQuad_16u_C1R	172
7.10.3.60	nppiWarpAffineQuad_16u_C3R	173
7.10.3.61	nppiWarpAffineQuad_16u_C4R	173
7.10.3.62	nppiWarpAffineQuad_16u_P3R	174
7.10.3.63	nppiWarpAffineQuad_16u_P4R	174
7.10.3.64	nppiWarpAffineQuad_32f_AC4R	175
7.10.3.65	nppiWarpAffineQuad_32f_C1R	175
7.10.3.66	nppiWarpAffineQuad_32f_C3R	176
7.10.3.67	nppiWarpAffineQuad_32f_C4R	176
7.10.3.68	nppiWarpAffineQuad_32f_P3R	177
7.10.3.69	nppiWarpAffineQuad_32f_P4R	177
7.10.3.70	nppiWarpAffineQuad_32s_AC4R	178
7.10.3.71	nppiWarpAffineQuad_32s_C1R	178
7.10.3.72	nppiWarpAffineQuad_32s_C3R	179
7.10.3.73	nppiWarpAffineQuad_32s_C4R	179
7.10.3.74	nppiWarpAffineQuad_32s_P3R	180
7.10.3.75	nppiWarpAffineQuad_32s_P4R	180
7.10.3.76	nppiWarpAffineQuad_8u_AC4R	181
7.10.3.77	nppiWarpAffineQuad_8u_C1R	181
7.10.3.78	nppiWarpAffineQuad_8u_C3R	182
7.10.3.79	nppiWarpAffineQuad_8u_C4R	182
7.10.3.80	nppiWarpAffineQuad_8u_P3R	183
7.10.3.81	nppiWarpAffineQuad_8u_P4R	183
7.11	Perspective Transform	184
7.11.1	Detailed Description	192
7.11.2	Perspective Transform Error Codes	192
7.11.3	Function Documentation	192
7.11.3.1	nppiGetPerspectiveBound	192
7.11.3.2	nppiGetPerspectiveQuad	193
7.11.3.3	nppiGetPerspectiveTransform	193
7.11.3.4	nppiWarpPerspective_16u_AC4R	193
7.11.3.5	nppiWarpPerspective_16u_C1R	194

7.11.3.6	nppiWarpPerspective_16u_C3R	194
7.11.3.7	nppiWarpPerspective_16u_C4R	195
7.11.3.8	nppiWarpPerspective_16u_P3R	195
7.11.3.9	nppiWarpPerspective_16u_P4R	196
7.11.3.10	nppiWarpPerspective_32f_AC4R	196
7.11.3.11	nppiWarpPerspective_32f_C1R	197
7.11.3.12	nppiWarpPerspective_32f_C3R	197
7.11.3.13	nppiWarpPerspective_32f_C4R	198
7.11.3.14	nppiWarpPerspective_32f_P3R	198
7.11.3.15	nppiWarpPerspective_32f_P4R	199
7.11.3.16	nppiWarpPerspective_32s_AC4R	199
7.11.3.17	nppiWarpPerspective_32s_C1R	200
7.11.3.18	nppiWarpPerspective_32s_C3R	200
7.11.3.19	nppiWarpPerspective_32s_C4R	201
7.11.3.20	nppiWarpPerspective_32s_P3R	201
7.11.3.21	nppiWarpPerspective_32s_P4R	202
7.11.3.22	nppiWarpPerspective_8u_AC4R	202
7.11.3.23	nppiWarpPerspective_8u_C1R	203
7.11.3.24	nppiWarpPerspective_8u_C3R	203
7.11.3.25	nppiWarpPerspective_8u_C4R	204
7.11.3.26	nppiWarpPerspective_8u_P3R	204
7.11.3.27	nppiWarpPerspective_8u_P4R	205
7.11.3.28	nppiWarpPerspectiveBack_16u_AC4R	205
7.11.3.29	nppiWarpPerspectiveBack_16u_C1R	206
7.11.3.30	nppiWarpPerspectiveBack_16u_C3R	206
7.11.3.31	nppiWarpPerspectiveBack_16u_C4R	207
7.11.3.32	nppiWarpPerspectiveBack_16u_P3R	207
7.11.3.33	nppiWarpPerspectiveBack_16u_P4R	208
7.11.3.34	nppiWarpPerspectiveBack_32f_AC4R	208
7.11.3.35	nppiWarpPerspectiveBack_32f_C1R	209
7.11.3.36	nppiWarpPerspectiveBack_32f_C3R	209
7.11.3.37	nppiWarpPerspectiveBack_32f_C4R	210
7.11.3.38	nppiWarpPerspectiveBack_32f_P3R	210
7.11.3.39	nppiWarpPerspectiveBack_32f_P4R	211
7.11.3.40	nppiWarpPerspectiveBack_32s_AC4R	211
7.11.3.41	nppiWarpPerspectiveBack_32s_C1R	212

7.11.3.42 nppiWarpPerspectiveBack_32s_C3R	212
7.11.3.43 nppiWarpPerspectiveBack_32s_C4R	213
7.11.3.44 nppiWarpPerspectiveBack_32s_P3R	213
7.11.3.45 nppiWarpPerspectiveBack_32s_P4R	214
7.11.3.46 nppiWarpPerspectiveBack_8u_AC4R	214
7.11.3.47 nppiWarpPerspectiveBack_8u_C1R	215
7.11.3.48 nppiWarpPerspectiveBack_8u_C3R	215
7.11.3.49 nppiWarpPerspectiveBack_8u_C4R	216
7.11.3.50 nppiWarpPerspectiveBack_8u_P3R	216
7.11.3.51 nppiWarpPerspectiveBack_8u_P4R	217
7.11.3.52 nppiWarpPerspectiveQuad_16u_AC4R	217
7.11.3.53 nppiWarpPerspectiveQuad_16u_C1R	218
7.11.3.54 nppiWarpPerspectiveQuad_16u_C3R	218
7.11.3.55 nppiWarpPerspectiveQuad_16u_C4R	219
7.11.3.56 nppiWarpPerspectiveQuad_16u_P3R	219
7.11.3.57 nppiWarpPerspectiveQuad_16u_P4R	220
7.11.3.58 nppiWarpPerspectiveQuad_32f_AC4R	220
7.11.3.59 nppiWarpPerspectiveQuad_32f_C1R	221
7.11.3.60 nppiWarpPerspectiveQuad_32f_C3R	221
7.11.3.61 nppiWarpPerspectiveQuad_32f_C4R	222
7.11.3.62 nppiWarpPerspectiveQuad_32f_P3R	222
7.11.3.63 nppiWarpPerspectiveQuad_32f_P4R	223
7.11.3.64 nppiWarpPerspectiveQuad_32s_AC4R	223
7.11.3.65 nppiWarpPerspectiveQuad_32s_C1R	224
7.11.3.66 nppiWarpPerspectiveQuad_32s_C3R	224
7.11.3.67 nppiWarpPerspectiveQuad_32s_C4R	225
7.11.3.68 nppiWarpPerspectiveQuad_32s_P3R	225
7.11.3.69 nppiWarpPerspectiveQuad_32s_P4R	226
7.11.3.70 nppiWarpPerspectiveQuad_8u_AC4R	226
7.11.3.71 nppiWarpPerspectiveQuad_8u_C1R	227
7.11.3.72 nppiWarpPerspectiveQuad_8u_C3R	227
7.11.3.73 nppiWarpPerspectiveQuad_8u_C4R	228
7.11.3.74 nppiWarpPerspectiveQuad_8u_P3R	228
7.11.3.75 nppiWarpPerspectiveQuad_8u_P4R	229
8 Data Structure Documentation	231
8.1 NPP_ALIGN_16 Struct Reference	231

8.1.1	Detailed Description	231
8.1.2	Field Documentation	231
8.1.2.1	im	231
8.1.2.2	im	232
8.1.2.3	re	232
8.1.2.4	re	232
8.2	NPP_ALIGN_8 Struct Reference	233
8.2.1	Detailed Description	233
8.2.2	Field Documentation	233
8.2.2.1	im	233
8.2.2.2	im	233
8.2.2.3	im	233
8.2.2.4	re	234
8.2.2.5	re	234
8.2.2.6	re	234
8.3	NppiHaarBuffer Struct Reference	235
8.3.1	Field Documentation	235
8.3.1.1	haarBuffer	235
8.3.1.2	haarBufferSize	235
8.4	NppiHaarClassifier_32f Struct Reference	236
8.4.1	Field Documentation	236
8.4.1.1	classifiers	236
8.4.1.2	classifierSize	236
8.4.1.3	classifierStep	236
8.4.1.4	counterDevice	236
8.4.1.5	numClassifiers	236
8.5	NppiPoint Struct Reference	237
8.5.1	Detailed Description	237
8.5.2	Field Documentation	237
8.5.2.1	x	237
8.5.2.2	y	237
8.6	NppiRect Struct Reference	238
8.6.1	Detailed Description	238
8.6.2	Field Documentation	238
8.6.2.1	height	238
8.6.2.2	width	238

8.6.2.3	x	238
8.6.2.4	y	238
8.7	NppiSize Struct Reference	239
8.7.1	Detailed Description	239
8.7.2	Field Documentation	239
8.7.2.1	height	239
8.7.2.2	width	239
8.8	NppLibraryVersion Struct Reference	240
8.8.1	Field Documentation	240
8.8.1.1	build	240
8.8.1.2	major	240
8.8.1.3	minor	240

Chapter 1

NVIDIA Performance Primitives

Note: Starting with release 6.5, NPP is also provided as a static library (`libnppc_static.a`, `libnppi_static.a`, and `libnpps_static.a`) on Linux, Android, and Mac OSes in addition to being provided as a shared library. The static NPP libraries depend on a common thread abstraction layer library called `cuLIBOS` (`libculibos.a`) that is now distributed as part of the toolkit. Consequently, `cuLIBOS` must be provided to the linker when the static library is being linked against. The `libnppi` library is becoming quite large so to minimize library loading and CUDA runtime startup times it is recommended to use the static library(s) whenever possible. To improve loading and runtime performance when using dynamic libraries NPP 8.0 now includes the full set of `nppi` sub-libraries in addition to the full sized `nppi` library itself. Linking to only the sub-libraries that contain functions that your application uses can significantly improve load time and runtime startup performance. Some `nppi` functions make calls to other `nppi` and/or `npps` functions internally so you may need to link to a few extra libraries depending on what function calls your application makes. The `nppi` sub-libraries are split into sections corresponding to the way that `nppi` header files are split. There are also static versions of each of the new sub-libraries. The full sized `nppi` library will be deprecated in the next CUDA release. This list of sub-libraries is as follows:

```
nppial arithmetic and logical operation functions in nppi_arithmetic_and_logical_operations.h
nppicc color conversion and sampling functions in nppi_color_conversion.h
nppicom JPEG compression and decompression functions in nppi_compression_functions.h
nppidei data exchange and initialization functions in nppi_data_exchange_and_initialization.h
nppif filtering and computer vision functions in nppi_filter_functions.h
nppig geometry transformation functions found in nppi_geometry_transforms.h
nppim morphological operation functions found in nppi_morphological_operations.h
nppist statistics and linear transform in nppi_statistics_functions.h and nppi_linear_transforms.h
nppisu memory support functions in nppi_support_functions.h
nppitc threshold and compare operation functions in nppi_threshold_and_compare_operations.h
```

For example, on Linux, to compile a small application `foo` using NPP against the dynamic library, the following command can be used:

```
nvcc foo.c -lnppi -o foo
```

Whereas to compile against the static NPP library, the following command has to be used:

```
nvcc foo.c -lnppi_static -lculibos -o foo
```

It is also possible to use the native host C++ compiler. Depending on the host operating system, some additional libraries like `pthread` or `dl` might be needed on the linking line. The following command on Linux is suggested:

```
g++ foo.c -lnppi_static -lculibos -lcudart_static -lpthread -ldl
-I <cuda-toolkit-path>/include -L <cuda-toolkit-path>/lib64 -o foo
```

NPP is a stateless API, as of NPP 6.5 the ONLY state that NPP remembers between function calls is the current stream ID, i.e. the stream ID that was set in the most recent `nppSetStream` call. The default stream ID is 0. If an application intends to use NPP with multiple streams then it is the responsibility of the application to call `nppSetStream` whenever it wishes to change stream IDs. Several NPP functions may call other NPP functions internally to complete their functionality. For this reason it is recommended that `cudaDeviceSynchronize` be called before making an `nppSetStream` call to change to a new stream ID. This will insure that any internal function calls that have not yet occurred will be completed using the current stream ID before it changes to a new ID. Calling `cudaDeviceSynchronize` frequently call kill performance so minimizing the frequency of these calls is critical for good performance. It is not necessary to call `cudaDeviceSynchronize` for stream management while the same stream ID is used for multiple NPP calls. All NPP functions should be thread safe except for the following functions:

```
nppiGraphcut_32s8u - this function has been deprecated in NPP 8.0
nppiGraphcut_32f8u - this function has been deprecated in NPP 8.0
nppiGraphcut8_32s8u - this function has been deprecated in NPP 8.0
nppiGraphcut8_32f8u - this function has been deprecated in NPP 8.0
nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R
nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R
```

As of NPP version 5.0 and beyond a few parameters for a few pre-5.0 existing image LUT functions have changed from host memory pointers to device memory pointers. Your application will fail (crash or report an error) if you use these functions with host memory pointers. The functions are the `nppiLUT_Linear_8u_xxx` functions.

Also, pre-5.0 function `nppiMeanStdDev8uC1RGetBufferHostSize` has been renamed `nppiMeanStdDevGetBufferHostSize_8u_C1R`.

1.1 What is NPP?

NVIDIA NPP is a library of functions for performing CUDA accelerated processing. The initial set of functionality in the library focuses on imaging and video processing and is widely applicable for developers in these areas. NPP will evolve over time to encompass more of the compute heavy tasks in a variety of problem domains. The NPP library is written to maximize flexibility, while maintaining high performance.

NPP can be used in one of two ways:

- A stand-alone library for adding GPU acceleration to an application with minimal effort. Using this route allows developers to add GPU acceleration to their applications in a matter of hours.
- A cooperative library for interoperating with a developer's GPU code efficiently.

Either route allows developers to harness the massive compute resources of NVIDIA GPUs, while simultaneously reducing development times.

1.2 Documentation

- [General API Conventions](#)

- [Signal-Processing Specific API Conventions](#)
- [Imaging-Processing Specific API Conventions](#)

1.3 Technical Specifications

Supported Platforms:

- Microsoft Windows 7, 8, and 10 (64-bit and 32-bit)
- Microsoft Windows Vista (64-bit and 32-bit)
- Linux (Centos, Ubuntu, and several others) (64-bit and 32-bit)
- Mac OS X (64-bit)
- Android on Arm (32-bit and 64-bit)

1.4 Files

NPP is comprised of the following files:

1.4.1 Header Files

- [nppdefs.h](#)
- [nppcore.h](#)
- [nppi.h](#)
- [npps.h](#)
- [nppversion.h](#)
- [npp.h](#)

All these header files are located in the CUDA Toolkit's

```
/include/
```

directory.

1.4.2 Library Files

Starting with Version 5.5 NPP's functionality is now split up into 3 distinct libraries:

- A core library (NPPC) containing basic functionality from the `npp.h` header files as well as functionality shared by the other two libraries.
- The image processing library NPPI. Any functions from the `nppi.h` header file (or the various header files named "nppi_XXX.h") are bundled into the NPPI library.

- The signal processing library NPPS. Any function from the npps.h header file (or the various header files named "npps_xxx.h" are bundled into the NPPS library.

On the Windows platform the NPP stub libraries are found in the CUDA Toolkit's library directory:

```
/lib/nppc.lib
```

```
/lib/nppi.lib
```

```
/lib/npps.lib
```

The matching DLLs are located in the CUDA Toolkit's binary directory. Example

```
/bin/nppi64_55_<build_no>.dll // Dynamic image-processing library for 64-bit Windows.
```

On Linux and Mac platforms the dynamic libraries are located in the lib directory

```
/lib/libnppc32.so.5.5.<build_no> // NPP 32-bit dynamic core library for Linux
```

```
/lib/libnpps32.5.5.dylib // NPP 32-bit dynamic signal processing library for Mac
```

1.5 Supported NVIDIA Hardware

NPP runs on all CUDA capable NVIDIA hardware. For details please see http://www.nvidia.com/object/cuda_learn_products.html

Chapter 2

General API Conventions

2.1 Memory Management

The design of all the NPP functions follows the same guidelines as other NVIDIA CUDA libraries like cuFFT and cuBLAS. That is that all pointer arguments in those APIs are device pointers.

This convention enables the individual developer to make smart choices about memory management that minimize the number of memory transfers. It also allows the user the maximum flexibility regarding which of the various memory transfer mechanisms offered by the CUDA runtime is used, e.g. synchronous or asynchronous memory transfers, zero-copy and pinned memory, etc.

The most basic steps involved in using NPP for processing data is as follows:

1. Transfer input data from the host to device using

```
cudaMemcpy(...)
```

2. Process data using one or several NPP functions or custom CUDA kernels

3. Transfer the result data from the device to the host using

```
cudaMemcpy(...)
```

2.1.1 Scratch Buffer and Host Pointer

Some primitives of NPP require additional device memory buffers (scratch buffers) for calculations, e.g. signal and image reductions (Sum, Max, Min, MinMax, etc.). In order to give the NPP user maximum control regarding memory allocations and performance, it is the user's responsibility to allocate and delete those temporary buffers. For one this has the benefit that the library will not allocate memory unbeknownst to the user. It also allows developers who invoke the same primitive repeatedly to allocate the scratch only once, improving performance and potential device-memory fragmentation.

Scratch-buffer memory is unstructured and may be passed to the primitive in uninitialized form. This allows for reuse of the same scratch buffers with any primitive require scratch memory, as long as it is sufficiently sized.

The minimum scratch-buffer size for a given primitive (e.g. `nppsSum_32f()`) can be obtained by a companion function (e.g. `nppsSumGetBufferSize_32f()`). The buffer size is returned via a host pointer as allocation of the scratch-buffer is performed via CUDA runtime host code.

An example to invoke signal sum primitive and allocate and free the necessary scratch memory:

```
// pSrc, pSum, pDeviceBuffer are all device pointers.
Npp32f * pSrc;
Npp32f * pSum;
Npp8u * pDeviceBuffer;
int nLength = 1024;

// Allocate the device memroy.
cudaMalloc((void **)&pSrc, sizeof(Npp32f) * nLength);
nppsSet_32f(1.0f, pSrc, nLength);
cudaMalloc((void **)&pSum, sizeof(Npp32f) * 1);

// Compute the appropriate size of the scratch-memory buffer
int nBufferSize;
nppsSumGetBufferSize_32f(nLength, &nBufferSize);
// Allocate the scratch buffer
cudaMalloc((void **)&pDeviceBuffer, nBufferSize);

// Call the primitive with the scratch buffer
```



```
nppsSum_32f(pSrc, nLength, pSum, pDeviceBuffer);
Npp32f nSumHost;
cudaMemcpy(&nSumHost, pSum, sizeof(Npp32f) * 1, cudaMemcpyDeviceToHost);
printf("sum = %f\n", nSumHost); // nSumHost = 1024.0f;

// Free the device memory
cudaFree(pSrc);
cudaFree(pDeviceBuffer);
cudaFree(pSum);
```

2.2 Function Naming

Since NPP is a C API and therefore does not allow for function overloading for different data-types the NPP naming convention addresses the need to differentiate between different flavors of the same algorithm or primitive function but for various data types. This disambiguation of different flavors of a primitive is done via a suffix containing data type and other disambiguating information.

In addition to the flavor suffix, all NPP functions are prefixed with by the letters "npp". Primitives belonging to NPP's image-processing module add the letter "i" to the npp prefix, i.e. are prefixed by "nppi". Similarly signal-processing primitives are prefixed with "npps".

The general naming scheme is:

```
npp<module info><PrimitiveName>_<data-type info>[_<additional flavor info>](<parameter list>)
```

The data-type information uses the same names as the [Basic NPP Data Types](#). For example the data-type information "8u" would imply that the primitive operates on [Npp8u](#) data.

If a primitive consumes different type data from what it produces, both types will be listed in the order of consumed to produced data type.

Details about the "additional flavor information" is provided for each of the NPP modules, since each problem domain uses different flavor information suffixes.

2.3 Integer Result Scaling

NPP signal processing and imaging primitives often operate on integer data. This integer data is usually a fixed point fractional representation of some physical magnitude (e.g. luminance). Because of this fixed-point nature of the representation many numerical operations (e.g. addition or multiplication) tend to produce results exceeding the original fixed-point range if treated as regular integers.

In cases where the results exceed the original range, these functions clamp the result values back to the valid range. E.g. the maximum positive value for a 16-bit unsigned integer is 32767. A multiplication operation of $4 * 10000 = 40000$ would exceed this range. The result would be clamped to be 32767.

To avoid the level of lost information due to clamping most integer primitives allow for result scaling. Primitives with result scaling have the "Sfs" suffix in their name and provide a parameter "nScaleFactor" that controls the amount of scaling. Before the results of an operation are clamped to the valid output-data range by multiplying them with $2^{-nScaleFactor}$.

Example: The primitive `nppsSqr_8u_Sfs()` computes the square of 8-bit unsigned sample values in a signal (1D array of values). The maximum value of a 8-bit value is 255. The square of $255^2 = 65025$ which would be clamped to 255 if no result scaling is performed. In order to map the maximum value of 255 to 255 in the result, one would specify an integer result scaling factor of 8, i.e. multiply each result with $2^{-8} = \frac{1}{2^8} = \frac{1}{256}$. The final result for a signal value of 255 being squared and scaled would be:

$$255^2 \cdot 2^{-8} = 254.00390625$$

which would be rounded to a final result of 254.

A medium gray value of 128 would result in

$$128^2 * 2^{-8} = 64$$

2.4 Rounding Modes

Many NPP functions require converting floating-point values to integers. The [NppRoundMode](#) enum lists NPP's supported rounding modes. Not all primitives in NPP that perform rounding as part of their functionality allow the user to specify the round-mode used. Instead they use NPP's default rounding mode, which is [NPP_RND_FINANCIAL](#).

2.4.1 Rounding Mode Parameter

A subset of NPP functions performing rounding as part of their functionality do allow the user to specify which rounding mode is used through a parameter of the [NppRoundMode](#) type.

Chapter 3

Signal-Processing Specific API Conventions

3.1 Signal Data

Signal data is passed to and from NPPS primitives via a pointer to the signal's data type.

The general idea behind this fairly low-level way of passing signal data is ease-of-adoption into existing software projects:

- Passing the data pointer rather than a higher-level signal struct allows for easy adoption by not requiring a specific signal representation (that could include total signal size offset, or other additional information). This avoids awkward packing and unpacking of signal data from the host application to an NPP specific signal representation.

3.1.1 Parameter Names for Signal Data

There are three general cases of image-data passing throughout NPP detailed in the following sections.

Those are signals consumed by the algorithm.

3.1.1.1 Source Signal Pointer

The source signal data is generally passed via a pointer named

```
pSrc
```

The source signal pointer is generally defined constant, enforcing that the primitive does not change any image data pointed to by that pointer. E.g.

```
nppsPrimitive_32s(const Npp32s * pSrc, ...)
```

In case the primitive consumes multiple signals as inputs the source pointers are numbered like this:

```
pSrc1, pSrc2, ...
```

3.1.1.2 Destination Signal Pointer

The destination signal data is generally passed via a pointer named

```
pDst
```

In case the primitive consumes multiple signals as inputs the source pointers are numbered like this:

```
pDst1, pDst2, ...
```

3.1.1.3 In-Place Signal Pointer

In the case of in-place processing, source and destination are served by the same pointer and thus pointers to in-place signal data are called:

```
pSrcDst
```

3.1.2 Signal Data Alignment Requirements

NPP requires signal sample data to be naturally aligned, i.e. any pointer

```
NppType * p;
```

to a sample in a signal needs to fulfill:

```
assert(p % sizeof(p) == 0);
```

3.1.3 Signal Data Related Error Codes

All NPPI primitives operating on signal data validate the signal-data pointer for proper alignment and test that the point is not null.

Failed validation results in one of the following error codes being returned and the primitive not being executed:

- [NPP_NULL_POINTER_ERROR](#) is returned if the image-data pointer is 0 (NULL).
- [NPP_ALIGNMENT_ERROR](#) if the signal-data pointer address is not a multiple of the signal's data-type size.

3.2 Signal Length

The vast majority of NPPS functions take a

```
nLength
```

parameter that tells the primitive how many of the signal's samples starting from the given data pointer are to be processed.

3.2.1 Length Related Error Codes

All NPPS primitives taking a length parameter validate this input.

Failed validation results in the following error code being returned and the primitive not being executed:

- [NPP_SIZE_ERROR](#) is returned if the length is negative.

Chapter 4

Imaging-Processing Specific API Conventions

4.1 Function Naming

Image processing related functions use a number of suffixes to indicate various different flavors of a primitive beyond just different data types. The flavor suffix uses the following abbreviations:

- "A" if the image is a 4 channel image this indicates the result alpha channel is not affected by the primitive.
- "Cn" the image consists of n channel packed pixels, where n can be 1, 2, 3 or 4.
- "Pn" the image consists of n separate image planes, where n can be 1, 2, 3 or 4.
- "C" (following the channel information) indicates that the primitive only operates on one of the color channels, the "channel-of-interest". All other output channels are not affected by the primitive.
- "I" indicates that the primitive works "in-place". In this case the image-data pointer is usually named "pSrcDst" to indicate that the image data serves as source and destination at the same time.
- "M" indicates "masked operation". These types of primitives have an additional "mask image" as input. Each pixel in the destination image corresponds to a pixel in the mask image. Only pixels with a corresponding non-zero mask pixel are being processed.
- "R" indicates the primitive operates only on a rectangular "region-of-interest" or "ROI". All ROI primitives take an additional input parameter of type [NppiSize](#), which specifies the width and height of the rectangular region that the primitive should process. For details on how primitives operate on ROIs see: [Region-of-Interest \(ROI\)](#).
- "Sfs" indicates the result values are processed by fixed scaling and saturation before they're written out.

The suffixes above always appear in alphabetical order. E.g. a 4 channel primitive not affecting the alpha channel with masked operation, in place and with scaling/saturation and ROI would have the postfix: "AC4IMRSfs".

4.2 Image Data

Image data is passed to and from NPPI primitives via a pair of parameters:

1. A pointer to the image's underlying data type.
2. A line step in bytes (also sometimes called line stride).

The general idea behind this fairly low-level way of passing image data is ease-of-adoption into existing software projects:

- Passing a raw pointer to the underlying pixel data type, rather than structured (by color) channel pixel data allows usage of the function in a wide variety of situations avoiding risky type cast or expensive image data copies.
- Passing the data pointer and line step individually rather than a higher- level image struct again allows for easy adoption by not requiring a specific image representation and thus avoiding awkward packing and unpacking of image data from the host application to an NPP specific image representation.

4.2.1 Line Step

The line step (also called "line stride" or "row step") allows lines of oddly sized images to start on well-aligned addresses by adding a number of unused bytes at the ends of the lines. This type of line padding has been common practice in digital image processing for a long time and is not particular to GPU image processing.

The line step is the number of bytes in a line **including the padding**. An other way to interpret this number is to say that it is the number of bytes between the first pixel of successive rows in the image, or generally the number of bytes between two neighboring pixels in any column of pixels.

The general reason for the existence of the line step it is that uniformly aligned rows of pixel enable optimizations of memory-access patterns.

Even though all functions in NPP will work with arbitrarily aligned images, best performance can only be achieved with well aligned image data. Any image data allocated with the NPP image allocators or the 2D memory allocators in the CUDA runtime, is well aligned.

Particularly on older CUDA capable GPUs it is likely that the performance decrease for misaligned data is substantial (orders of magnitude).

All image data passed to NPPI primitives requires a line step to be provided. It is important to keep in mind that this line step is always specified in terms of bytes, not pixels.

4.2.2 Parameter Names for Image Data

There are three general cases of image-data passing throughout NPP detailed in the following sections.

4.2.2.1 Passing Source-Image Data

Those are images consumed by the algorithm.

4.2.2.1.1 Source-Image Pointer

The source image data is generally passed via a pointer named

```
pSrc
```

The source image pointer is generally defined constant, enforcing that the primitive does not change any image data pointed to by that pointer. E.g.

```
nppiPrimitive_32s_C1R(const Npp32s * pSrc, ...)
```

In case the primitive consumes multiple images as inputs the source pointers are numbered like this:

```
pSrc1, pSrc2, ...
```

4.2.2.1.2 Source-Planar-Image Pointer Array

The planar source image data is generally passed via an array of pointers named

```
pSrc[]
```

The planar source image pointer array is generally defined a constant array of constant pointers, enforcing that the primitive does not change any image data pointed to by those pointers. E.g.

```
nppiPrimitive_8u_P3R(const Npp8u * const pSrc[3], ...)
```

Each pointer in the array points to a different image plane.

4.2.2.1.3 Source-Planar-Image Pointer

The multiple plane source image data is passed via a set of pointers named

```
pSrc1, pSrc2, ...
```

The planar source image pointer is generally defined as one of a set of constant pointers with each pointer pointing to a different input image plane.

4.2.2.1.4 Source-Image Line Step

The source image line step is the number of bytes between successive rows in the image. The source image line step parameter is

```
nSrcStep
```

or in the case of multiple source images

```
nSrcStep1, nSrcStep2, ...
```

4.2.2.1.5 Source-Planar-Image Line Step Array

The source planar image line step array is an array where each element of the array contains the number of bytes between successive rows for a particular plane in the input image. The source planar image line step array parameter is

```
rSrcStep[]
```

4.2.2.1.6 Source-Planar-Image Line Step

The source planar image line step is the number of bytes between successive rows in a particular plane of the multiplane input image. The source planar image line step parameter is

```
nSrcStep1, nSrcStep2, ...
```

4.2.2.2 Passing Destination-Image Data

Those are images produced by the algorithm.

4.2.2.2.1 Destination-Image Pointer

The destination image data is generally passed via a pointer named

```
pDst
```

In case the primitive generates multiple images as outputs the destination pointers are numbered like this:

```
pDst1, pDst2, ...
```

4.2.2.2.2 Destination-Planar-Image Pointer Array

The planar destination image data pointers are generally passed via an array of pointers named

```
pDst[]
```

Each pointer in the array points to a different image plane.

4.2.2.2.3 Destination-Planar-Image Pointer

The destination planar image data is generally passed via a pointer to each plane of a multiplane output image named

```
pDst1, pDst2, ...
```

4.2.2.2.4 Destination-Image Line Step

The destination image line step parameter is

```
nDstStep
```

or in the case of multiple destination images

```
nDstStep1, nDstStep2, ...
```

4.2.2.2.5 Destination-Planar-Image Line Step Array

The destination planar image line step array is an array where each element of the array contains the number of bytes between successive rows for a particular plane in the output image. The destination planar image line step array parameter is

```
rDstStep[]
```

4.2.2.2.6 Destination-Planar-Image Line Step

The destination planar image line step is the number of bytes between successive rows for a particular plane in a multiplane output image. The destination planar image line step parameter is

```
nDstStep1, nDstStep2, ...
```

4.2.2.3 Passing In-Place Image Data

4.2.2.3.1 In-Place Image Pointer

In the case of in-place processing, source and destination are served by the same pointer and thus pointers to in-place image data are called:

```
pSrcDst
```

4.2.2.3.2 In-Place-Image Line Step

The in-place line step parameter is

```
nSrcDstStep
```

4.2.2.4 Passing Mask-Image Data

Some image processing primitives have variants supporting [Masked Operation](#).

4.2.2.4.1 Mask-Image Pointer

The mask-image data is generally passed via a pointer named

```
pMask
```

4.2.2.4.2 Mask-Image Line Step

The mask-image line step parameter is

```
nMaskStep
```

4.2.2.5 Passing Channel-of-Interest Data

Some image processing primitives support [Channel-of-Interest API](#).

4.2.2.5.1 Channel_of_Interest Number

The channel-of-interest data is generally an integer (either 1, 2, or 3):

```
nCOI
```

4.2.3 Image Data Alignment Requirements

NPP requires pixel data to adhere to certain alignment constraints: For 2 and 4 channel images the following alignment requirement holds: `data_pointer % (#channels * sizeof(channel type)) == 0`. E.g. a 4 channel image with underlying type [Npp8u](#) (8-bit unsigned) would require all pixels to fall on addresses that are multiples of 4 (4 channels * 1 byte size).

As a logical consequence of all pixels being aligned to their natural size the image line steps of 2 and 4 channel images also need to be multiples of the pixel size.

1 and 3 channel images only require that pixel pointers are aligned to the underlying data type, i.e. `pData % sizeof(data type) == 0`. And consequentially line steps are also held to this requirement.

4.2.4 Image Data Related Error Codes

All NPPI primitives operating on image data validate the image-data pointer for proper alignment and test that the point is not null. They also validate the line stride for proper alignment and guard against the step being less or equal to 0. Failed validation results in one of the following error codes being returned and the primitive not being executed:

- `NPP_STEP_ERROR` is returned if the data step is 0 or negative.
- `NPP_NOT_EVEN_STEP_ERROR` is returned if the line step is not a multiple of the pixel size for 2 and 4 channel images.
- `NPP_NULL_POINTER_ERROR` is returned if the image-data pointer is 0 (NULL).
- `NPP_ALIGNMENT_ERROR` if the image-data pointer address is not a multiple of the pixel size for 2 and 4 channel images.

4.3 Region-of-Interest (ROI)

In practice processing a rectangular sub-region of an image is often more common than processing complete images. The vast majority of NPPI's image-processing primitives allow for processing of such sub regions also referred to as regions-of-interest or ROIs.

All primitives supporting ROI processing are marked by a "R" in their name suffix. In most cases the ROI is passed as a single `NppiSize` struct, which provides the width and height of the ROI. This raises the question how the primitive knows where in the image this rectangle of (width, height) is located. The "start pixel" of the ROI is implicitly given by the image-data pointer. I.e. instead of explicitly passing a pixel coordinate for the upper-left corner (lowest memory address), the user simply offsets the image-data pointers to point to the first pixel of the ROI.

In practice this means that for an image (`pSrc`, `nSrcStep`) and the start-pixel of the ROI being at location (`x`, `y`), one would pass

```
pSrcOffset = pSrc + y * nSrcStep + x * PixelSize;
```

as the image-data source to the primitive. `PixelSize` is typically computed as

```
PixelSize = NumberOfColorChannels * sizeof(PixelDataType).
```

E.g. for a primitive like `nppiSet_16s_C4R()` we would have

- `NumberOfColorChannels == 4;`
- `sizeof(Npp16s) == 2;`
- and thus `PixelSize = 4 * 2 = 8;`

4.3.1 ROI Related Error Codes

All NPPI primitives operating on ROIs of image data validate the ROI size and image's step size. Failed validation results in one of the following error codes being returned and the primitive not being executed:

- `NPP_SIZE_ERROR` is returned if either the ROI width or ROI height are negative.
- `NPP_STEP_ERROR` is returned if the ROI width exceeds the image's line step. In mathematical terms $(\text{widthROI} * \text{PixelSize}) > \text{nLinStep}$ indicates an error.

4.4 Masked Operation

Some primitive support masked operation. An "M" in the suffix of those variants indicates masked operation. Primitives supporting masked operation consume an additional input image provided via a [Mask-Image Pointer](#) and [Mask-Image Line Step](#). The mask image is interpreted by these primitives as a boolean image. The values of type `Npp8u` are interpreted as boolean values where a values of 0 indicates false, any non-zero values true.

Unless otherwise indicated the operation is only performed on pixels where its spatially corresponding mask pixel is true (non-zero). E.g. a masked copy operation would only copy those pixels in the ROI that have corresponding non-zero mask pixels.

4.5 Channel-of-Interest API

Some primitives allow restricting operations to a single channel of interest within a multi-channel image. These primitives are suffixed with the letter "C" (after the channel information, e.g. `nppiCopy_8u_C3CR(...)`). The channel-of-interest is generally selected by offsetting the image-data pointer to point directly to the channel- of-interest rather than the base of the first pixel in the ROI. Some primitives also explicitly specify the selected channel number and pass it via an integer, e.g. `nppiMean_StdDev_8u_C3CR(...)`.

4.5.1 Select-Channel Source-Image Pointer

This is a pointer to the channel-of-interest within the first pixel of the source image. E.g. if `pSrc` is the pointer to the first pixel inside the ROI of a three channel image. Using the appropriate select-channel copy primitive one could copy the second channel of this source image into the first channel of a destination image given by `pDst` by offsetting the pointer by one:

```
nppiCopy_8u_C3CR(pSrc + 1, nSrcStep, pDst, nDstStep, oSizeROI);
```

4.5.2 Select-Channel Source-Image

Some primitives allow the user to select the channel-of-interest by specifying the channel number (`nCOI`). This approach is typically used in the image statistical functions. For example,

```
nppiMean_StdDev_8u_C3CR(pSrc, nSrcStep, oSizeROI, nCOI, pDeviceBuffer, pMean, pStdDev );
```

The channel-of-interest number can be either 1, 2, or 3.

4.5.3 Select-Channel Destination-Image Pointer

This is a pointer to the channel-of-interest within the first pixel of the destination image. E.g. if `pDst` is the pointer to the first pixel inside the ROI of a three channel image. Using the appropriate select-channel

copy primitive one could copy data into the second channel of this destination image from the first channel of a source image given by pSrc by offsetting the destination pointer by one:

```
nppiCopy_8u_C3CR(pSrc, nSrcStep, pDst + 1, nDstStep, oSizeROI);
```

4.6 Source-Image Sampling

A large number of NPP image-processing functions consume at least one source image and produce an output image (e.g. `nppiAddC_8u_C1RSfs()` or `nppiFilterBox_8u_C1R()`). All NPP functions falling into this category also operate on ROIs (see [Region-of-Interest \(ROI\)](#)) which for these functions should be considered to describe the destination ROI. In other words the ROI describes a rectangular region in the destination image and all pixels inside of this region are being written by the function in question.

In order to use such functions successfully it is important to understand how the user defined destination ROI affects which pixels in the input image(s) are being read by the algorithms. To simplify the discussion of ROI propagation (i.e. given a destination ROI, what are the ROIs in the source(s)), it makes sense to distinguish two major cases:

1. Point-Wise Operations: These are primitives like `nppiAddC_8u_C1RSfs()`. Each output pixel requires exactly one input pixel to be read.
2. Neighborhood Operations: These are primitives like `nppiFilterBox_8u_C1R()`, which require a group of pixels from the source image(s) to be read in order to produce a single output.

4.6.1 Point-Wise Operations

As mentioned above, point-wise operations consume a single pixel from the input image (or a single pixel from each input image, if the operation in question has more than one input image) in order to produce a single output pixel.

4.6.2 Neighborhood Operations

In the case of neighborhood operations a number of input pixels (a "neighborhood" of pixels) is read in the input image (or images) in order to compute a single output pixel. All of the functions for `image_filtering_functions` and `image_morphological_operations` are neighborhood operations.

Most of these functions have parameters that affect the size and relative location of the neighborhood: a mask-size structure and an anchor-point structure. Both parameters are described in more detail in the next subsections.

4.6.2.1 Mask-Size Parameter

Many NPP neighborhood operations allow the user to specify the size of the neighborhood via a parameter usually named `oMaskSize` of type `NppiSize`. In those cases the neighborhood of pixels read from the source(s) is exactly the size of the mask. Assuming the mask is anchored at location (0, 0) (see [Anchor-Point Parameter](#) below) and has a size of (w, h), i.e.

```
assert(oMaskSize.w == w);
assert(oMaskSize.h == h);
assert(oAnchor.x == 0);
assert(oAnchor.y == 0);
```

a neighborhood operation would read the following source pixels in order to compute destination pixel $D_{i,j}$:

$$\begin{array}{cccc}
 S_{i,j} & S_{i,j+1} & \cdots & S_{i,j+w-1} \\
 S_{i+1,j} & S_{i+1,j+1} & \cdots & S_{i+1,j+w-1} \\
 \vdots & \vdots & \ddots & \vdots \\
 S_{i+h-1,j} & S_{i+h-1,j+1} & \cdots & S_{i+h-1,j+w-1}
 \end{array}$$

4.6.2.2 Anchor-Point Parameter

Many NPP primitives performing neighborhood operations allow the user to specify the relative location of the neighborhood via a parameter usually named `oAnchor` of type [NppiPoint](#). Using the anchor a developer can choose the position of the mask (see [Mask-Size Parameter](#)) relative to current pixel index.

Using the same example as in [Mask-Size Parameter](#), but this time with an anchor position of (a, b):

```

assert(oMaskSize.w == w);
assert(oMaskSize.h == h);
assert(oAnchor.x == a);
assert(oAnchor.y == b);

```

the following pixels from the source image would be read:

$$\begin{array}{cccc}
 S_{i-a,j-b} & S_{i-a,j-b+1} & \cdots & S_{i-a,j-b+w-1} \\
 S_{i-a+1,j-b} & S_{i-a+1,j-b+1} & \cdots & S_{i-a+1,j-b+w-1} \\
 \vdots & \vdots & \ddots & \vdots \\
 S_{i-a+h-1,j-b} & S_{i-a+h-1,j-b+1} & \cdots & S_{i-a+h-1,j-b+w-1}
 \end{array}$$

4.6.2.3 Sampling Beyond Image Boundaries

NPP primitives in general and NPP neighborhood operations in particular require that all pixel locations read and written are valid and within the boundaries of the respective images. Sampling outside of the defined image data regions results in undefined behavior and may lead to system instability.

This poses a problem in practice: when processing full-size images one cannot choose the destination ROI to be the same size as the source image. Because neighborhood operations read pixels from an enlarged source ROI, the destination ROI must be shrunk so that the expanded source ROI does not exceed the source image's size.

For cases where this "shrinking" of the destination image size is unacceptable, NPP provides a set of border-expanding Copy primitives. E.g. `nppiCopyConstBorder_8u_C1R()`, `nppiCopyReplicateBorder_8u_C1R()` and `nppiCopyWrapBorder_8u_C1R()`. The user can use these primitives to "expand" the source image's size using one of the three expansion modes. The expanded image can then be safely passed to a neighborhood operation producing a full-size result.

Chapter 5

Module Index

5.1 Modules

Here is a list of all modules:

NPP Core	27
NPP Type Definitions and Constants	31
Basic NPP Data Types	46
Geometry Transforms	50
ResizeSqrPixel	52
Resize	74
Remap	86
Rotate	108
Mirror	117
Affine Transforms	134
Perspective Transform	184

Chapter 6

Data Structure Index

6.1 Data Structures

Here are the data structures with brief descriptions:

NPP_ALIGN_16 (Complex Number This struct represents a long long complex number)	231
NPP_ALIGN_8 (Complex Number This struct represents an unsigned int complex number) . .	233
NppiHaarBuffer	235
NppiHaarClassifier_32f	236
NppiPoint (2D Point)	237
NppiRect (2D Rectangle This struct contains position and size information of a rectangle in two space)	238
NppiSize (2D Size This struct typically represents the size of a a rectangular region in two space)	239
NppLibraryVersion	240

Chapter 7

Module Documentation

7.1 NPP Core

Basic functions for library management, in particular library version and device property query functions.

Functions

- const [NppLibraryVersion](#) * [nppGetLibVersion](#) (void)
Get the NPP library version.
- [NppGpuComputeCapability](#) [nppGetGpuComputeCapability](#) (void)
What CUDA compute model is supported by the active CUDA device?
- int [nppGetGpuNumSMs](#) (void)
Get the number of Streaming Multiprocessors (SM) on the active CUDA device.
- int [nppGetMaxThreadsPerBlock](#) (void)
Get the maximum number of threads per block on the active CUDA device.
- int [nppGetMaxThreadsPerSM](#) (void)
Get the maximum number of threads per SM for the active GPU.
- int [nppGetGpuDeviceProperties](#) (int *pMaxThreadsPerSM, int *pMaxThreadsPerBlock, int *pNumberOfSMs)
Get the maximum number of threads per SM, maximum threads per block, and number of SMs for the active GPU.
- const char * [nppGetGpuName](#) (void)
Get the name of the active CUDA device.
- cudaStream_t [nppGetStream](#) (void)
Get the NPP CUDA stream.
- unsigned int [nppGetStreamNumSMs](#) (void)
Get the number of SMs on the device associated with the current NPP CUDA stream.

- unsigned int `nppGetStreamMaxThreadsPerSM` (void)
Get the maximum number of threads per SM on the device associated with the current NPP CUDA stream.
- void `nppSetStream` (cudaStream_t hStream)
Set the NPP CUDA stream.

7.1.1 Detailed Description

Basic functions for library management, in particular library version and device property query functions.

7.1.2 Function Documentation

7.1.2.1 NppGpuComputeCapability nppGetGpuComputeCapability (void)

What CUDA compute model is supported by the active CUDA device?

Before trying to call any NPP functions, the user should make a call this function to ensure that the current machine has a CUDA capable device.

Returns:

An enum value representing if a CUDA capable device was found and what level of compute capabilities it supports.

7.1.2.2 int nppGetGpuDeviceProperties (int * pMaxThreadsPerSM, int * pMaxThreadsPerBlock, int * pNumberOfSMs)

Get the maximum number of threads per SM, maximum threads per block, and number of SMs for the active GPU.

Returns:

cudaSuccess for success, -1 for failure

7.1.2.3 const char* nppGetGpuName (void)

Get the name of the active CUDA device.

Returns:

Name string of the active graphics-card/compute device in a system.

7.1.2.4 int nppGetGpuNumSMs (void)

Get the number of Streaming Multiprocessors (SM) on the active CUDA device.

Returns:

Number of SMs of the default CUDA device.

7.1.2.5 const NppLibraryVersion* nppGetLibVersion (void)

Get the NPP library version.

Returns:

A struct containing separate values for major and minor revision and build number.

7.1.2.6 int nppGetMaxThreadsPerBlock (void)

Get the maximum number of threads per block on the active CUDA device.

Returns:

Maximum number of threads per block on the active CUDA device.

7.1.2.7 int nppGetMaxThreadsPerSM (void)

Get the maximum number of threads per SM for the active GPU.

Returns:

Maximum number of threads per SM for the active GPU

7.1.2.8 cudaStream_t nppGetStream (void)

Get the NPP CUDA stream.

NPP enables concurrent device tasks via a global stream state variable. The NPP stream by default is set to stream 0, i.e. non-concurrent mode. A user can set the NPP stream to any valid CUDA stream. All CUDA commands issued by NPP (e.g. kernels launched by the NPP library) are then issued to that NPP stream.

7.1.2.9 unsigned int nppGetStreamMaxThreadsPerSM (void)

Get the maximum number of threads per SM on the device associated with the current NPP CUDA stream.

NPP enables concurrent device tasks via a global stream state variable. The NPP stream by default is set to stream 0, i.e. non-concurrent mode. A user can set the NPP stream to any valid CUDA stream. All CUDA commands issued by NPP (e.g. kernels launched by the NPP library) are then issued to that NPP stream. This call avoids a cudaGetDeviceProperties() call.

7.1.2.10 unsigned int nppGetStreamNumSMs (void)

Get the number of SMs on the device associated with the current NPP CUDA stream.

NPP enables concurrent device tasks via a global stream state variable. The NPP stream by default is set to stream 0, i.e. non-concurrent mode. A user can set the NPP stream to any valid CUDA stream. All CUDA commands issued by NPP (e.g. kernels launched by the NPP library) are then issued to that NPP stream. This call avoids a cudaGetDeviceProperties() call.

7.1.2.11 void nppSetStream (cudaStream_t *hStream*)

Set the NPP CUDA stream.

See also:

[nppGetStream\(\)](#)

7.2 NPP Type Definitions and Constants

Data Structures

- struct [NppLibraryVersion](#)
- struct [NppiPoint](#)
2D Point
- struct [NppiSize](#)
2D Size This struct typically represents the size of a rectangular region in two space.
- struct [NppiRect](#)
2D Rectangle This struct contains position and size information of a rectangle in two space.
- struct [NppiHaarClassifier_32f](#)
- struct [NppiHaarBuffer](#)

Modules

- [Basic NPP Data Types](#)

Defines

- #define [NPP_MIN_8U](#) (0)
Minimum 8-bit unsigned integer.
- #define [NPP_MAX_8U](#) (255)
Maximum 8-bit unsigned integer.
- #define [NPP_MIN_16U](#) (0)
Minimum 16-bit unsigned integer.
- #define [NPP_MAX_16U](#) (65535)
Maximum 16-bit unsigned integer.
- #define [NPP_MIN_32U](#) (0)
Minimum 32-bit unsigned integer.
- #define [NPP_MAX_32U](#) (4294967295U)
Maximum 32-bit unsigned integer.
- #define [NPP_MIN_64U](#) (0)
Minimum 64-bit unsigned integer.
- #define [NPP_MAX_64U](#) (18446744073709551615ULL)
Maximum 64-bit unsigned integer.
- #define [NPP_MIN_8S](#) (-127 - 1)
Minimum 8-bit signed integer.

- #define `NPP_MAX_8S` (127)
Maximum 8-bit signed integer.
- #define `NPP_MIN_16S` (-32767 - 1)
Minimum 16-bit signed integer.
- #define `NPP_MAX_16S` (32767)
Maximum 16-bit signed integer.
- #define `NPP_MIN_32S` (-2147483647 - 1)
Minimum 32-bit signed integer.
- #define `NPP_MAX_32S` (2147483647)
Maximum 32-bit signed integer.
- #define `NPP_MAX_64S` (9223372036854775807LL)
Maximum 64-bit signed integer.
- #define `NPP_MIN_64S` (-9223372036854775807LL - 1)
Minimum 64-bit signed integer.
- #define `NPP_MINABS_32F` (1.175494351e-38f)
Smallest positive 32-bit floating point value.
- #define `NPP_MAXABS_32F` (3.402823466e+38f)
Largest positive 32-bit floating point value.
- #define `NPP_MINABS_64F` (2.2250738585072014e-308)
Smallest positive 64-bit floating point value.
- #define `NPP_MAXABS_64F` (1.7976931348623158e+308)
Largest positive 64-bit floating point value.

Enumerations

- enum `NppiInterpolationMode` {
`NPPI_INTER_UNDEFINED` = 0,
`NPPI_INTER_NN` = 1,
`NPPI_INTER_LINEAR` = 2,
`NPPI_INTER_CUBIC` = 4,
`NPPI_INTER_CUBIC2P_BSPLINE`,
`NPPI_INTER_CUBIC2P_CATMULLROM`,
`NPPI_INTER_CUBIC2P_B05C03`,
`NPPI_INTER_SUPER` = 8,
`NPPI_INTER_LANCZOS` = 16,
`NPPI_INTER_LANCZOS3_ADVANCED` = 17,
`NPPI_SMOOTH_EDGE` = (1 << 31) }

Filtering methods.

- enum `NppiBayerGridPosition` {
`NPPI_BAYER_BGGR` = 0,
`NPPI_BAYER_RGGB` = 1,
`NPPI_BAYER_GBRG` = 2,
`NPPI_BAYER_GRBG` = 3 }

Bayer Grid Position Registration.

- enum `NppiMaskSize` {
`NPP_MASK_SIZE_1_X_3`,
`NPP_MASK_SIZE_1_X_5`,
`NPP_MASK_SIZE_3_X_1` = 100,
`NPP_MASK_SIZE_5_X_1`,
`NPP_MASK_SIZE_3_X_3` = 200,
`NPP_MASK_SIZE_5_X_5`,
`NPP_MASK_SIZE_7_X_7` = 400,
`NPP_MASK_SIZE_9_X_9` = 500,
`NPP_MASK_SIZE_11_X_11` = 600,
`NPP_MASK_SIZE_13_X_13` = 700,
`NPP_MASK_SIZE_15_X_15` = 800 }

Fixed filter-kernel sizes.

- enum `NppiDifferentialKernel` {
`NPP_FILTER_SOBEL`,
`NPP_FILTER_SCHARR` }

Differential Filter types.

- enum `NppStatus` {
`NPP_NOT_SUPPORTED_MODE_ERROR` = -9999,
`NPP_INVALID_HOST_POINTER_ERROR` = -1032,
`NPP_INVALID_DEVICE_POINTER_ERROR` = -1031,
`NPP_LUT_PALETTE_BITSIZE_ERROR` = -1030,
`NPP_ZC_MODE_NOT_SUPPORTED_ERROR` = -1028,
`NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY` = -1027,
`NPP_TEXTURE_BIND_ERROR` = -1024,
`NPP_WRONG_INTERSECTION_ROI_ERROR` = -1020,
`NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR` = -1006,
`NPP_MEMFREE_ERROR` = -1005,
`NPP_MEMSET_ERROR` = -1004,
`NPP_MEMCPY_ERROR` = -1003,
`NPP_ALIGNMENT_ERROR` = -1002,
`NPP_CUDA_KERNEL_EXECUTION_ERROR` = -1000,

NPP_ROUND_MODE_NOT_SUPPORTED_ERROR = -213,
NPP_QUALITY_INDEX_ERROR = -210,
NPP_RESIZE_NO_OPERATION_ERROR = -201,
NPP_OVERFLOW_ERROR = -109,
NPP_NOT_EVEN_STEP_ERROR = -108,
NPP_HISTOGRAM_NUMBER_OF_LEVELS_ERROR = -107,
NPP_LUT_NUMBER_OF_LEVELS_ERROR = -106,
NPP_CORRUPTED_DATA_ERROR = -61,
NPP_CHANNEL_ORDER_ERROR = -60,
NPP_ZERO_MASK_VALUE_ERROR = -59,
NPP_QUADRANGLE_ERROR = -58,
NPP_RECTANGLE_ERROR = -57,
NPP_COEFFICIENT_ERROR = -56,
NPP_NUMBER_OF_CHANNELS_ERROR = -53,
NPP_COI_ERROR = -52,
NPP_DIVISOR_ERROR = -51,
NPP_CHANNEL_ERROR = -47,
NPP_STRIDE_ERROR = -37,
NPP_ANCHOR_ERROR = -34,
NPP_MASK_SIZE_ERROR = -33,
NPP_RESIZE_FACTOR_ERROR = -23,
NPP_INTERPOLATION_ERROR = -22,
NPP_MIRROR_FLIP_ERROR = -21,
NPP_MOMENT_00_ZERO_ERROR = -20,
NPP_THRESHOLD_NEGATIVE_LEVEL_ERROR = -19,
NPP_THRESHOLD_ERROR = -18,
NPP_CONTEXT_MATCH_ERROR = -17,
NPP_FFT_FLAG_ERROR = -16,
NPP_FFT_ORDER_ERROR = -15,
NPP_STEP_ERROR = -14,
NPP_SCALE_RANGE_ERROR = -13,
NPP_DATA_TYPE_ERROR = -12,
NPP_OUT_OFF_RANGE_ERROR = -11,
NPP_DIVIDE_BY_ZERO_ERROR = -10,
NPP_MEMORY_ALLOCATION_ERR = -9,
NPP_NULL_POINTER_ERROR = -8,
NPP_RANGE_ERROR = -7,
NPP_SIZE_ERROR = -6,
NPP_BAD_ARGUMENT_ERROR = -5,
NPP_NO_MEMORY_ERROR = -4,
NPP_NOT_IMPLEMENTED_ERROR = -3,

```
NPP_ERROR = -2,  
NPP_ERROR_RESERVED = -1,  
NPP_NO_ERROR = 0,  
NPP_SUCCESS = NPP_NO_ERROR,  
NPP_NO_OPERATION_WARNING = 1,  
NPP_DIVIDE_BY_ZERO_WARNING = 6,  
NPP_AFFINE_QUAD_INCORRECT_WARNING = 28,  
NPP_WRONG_INTERSECTION_ROI_WARNING = 29,  
NPP_WRONG_INTERSECTION_QUAD_WARNING = 30,  
NPP_DOUBLE_SIZE_WARNING = 35,  
NPP_MISALIGNED_DST_ROI_WARNING = 10000 }
```

Error Status Codes.

- enum NppGpuComputeCapability {
NPP_CUDA_UNKNOWN_VERSION = -1,
NPP_CUDA_NOT_CAPABLE = 0,
NPP_CUDA_1_0 = 100,
NPP_CUDA_1_1 = 110,
NPP_CUDA_1_2 = 120,
NPP_CUDA_1_3 = 130,
NPP_CUDA_2_0 = 200,
NPP_CUDA_2_1 = 210,
NPP_CUDA_3_0 = 300,
NPP_CUDA_3_2 = 320,
NPP_CUDA_3_5 = 350,
NPP_CUDA_3_7 = 370,
NPP_CUDA_5_0 = 500,
NPP_CUDA_5_2 = 520,
NPP_CUDA_5_3 = 530,
NPP_CUDA_6_0 = 600 }
- enum NppiAxis {
NPP_HORIZONTAL_AXIS,
NPP_VERTICAL_AXIS,
NPP_BOTH_AXIS }
- enum NppCmpOp {
NPP_CMP_LESS,
NPP_CMP_LESS_EQ,
NPP_CMP_EQ,
NPP_CMP_GREATER_EQ,
NPP_CMP_GREATER }

- enum `NppRoundMode` {
`NPP_RND_NEAR`,
`NPP_ROUND_NEAREST_TIES_TO_EVEN` = `NPP_RND_NEAR`,
`NPP_RND_FINANCIAL`,
`NPP_ROUND_NEAREST_TIES_AWAY_FROM_ZERO` = `NPP_RND_FINANCIAL`,
`NPP_RND_ZERO`,
`NPP_ROUND_TOWARD_ZERO` = `NPP_RND_ZERO` }

Rounding Modes.

- enum `NppiBorderType` {
`NPP_BORDER_UNDEFINED` = 0,
`NPP_BORDER_NONE` = `NPP_BORDER_UNDEFINED`,
`NPP_BORDER_CONSTANT` = 1,
`NPP_BORDER_REPLICATE` = 2,
`NPP_BORDER_WRAP` = 3,
`NPP_BORDER_MIRROR` = 4 }
- enum `NppHintAlgorithm` {
`NPP_ALG_HINT_NONE`,
`NPP_ALG_HINT_FAST`,
`NPP_ALG_HINT_ACCURATE` }
- enum `NppiAlphaOp` {
`NPPI_OP_ALPHA_OVER`,
`NPPI_OP_ALPHA_IN`,
`NPPI_OP_ALPHA_OUT`,
`NPPI_OP_ALPHA_ATOP`,
`NPPI_OP_ALPHA_XOR`,
`NPPI_OP_ALPHA_PLUS`,
`NPPI_OP_ALPHA_OVER_PREMUL`,
`NPPI_OP_ALPHA_IN_PREMUL`,
`NPPI_OP_ALPHA_OUT_PREMUL`,
`NPPI_OP_ALPHA_ATOP_PREMUL`,
`NPPI_OP_ALPHA_XOR_PREMUL`,
`NPPI_OP_ALPHA_PLUS_PREMUL`,
`NPPI_OP_ALPHA_PREMUL` }
- enum `NppsZCType` {
`nppZCR`,
`nppZCXor`,
`nppZCC` }
- enum `NppiHuffmanTableType` {
`nppiDCTable`,
`nppiACTable` }

- enum `NppiNorm` {
 `nppiNormInf` = 0,
 `nppiNormL1` = 1,
 `nppiNormL2` = 2 }

7.2.1 Define Documentation

7.2.1.1 #define `NPP_MAX_16S` (32767)

Maximum 16-bit signed integer.

7.2.1.2 #define `NPP_MAX_16U` (65535)

Maximum 16-bit unsigned integer.

7.2.1.3 #define `NPP_MAX_32S` (2147483647)

Maximum 32-bit signed integer.

7.2.1.4 #define `NPP_MAX_32U` (4294967295U)

Maximum 32-bit unsigned integer.

7.2.1.5 #define `NPP_MAX_64S` (9223372036854775807LL)

Maximum 64-bit signed integer.

7.2.1.6 #define `NPP_MAX_64U` (18446744073709551615ULL)

Maximum 64-bit unsigned integer.

7.2.1.7 #define `NPP_MAX_8S` (127)

Maximum 8-bit signed integer.

7.2.1.8 #define `NPP_MAX_8U` (255)

Maximum 8-bit unsigned integer.

7.2.1.9 #define `NPP_MAXABS_32F` (3.402823466e+38f)

Largest positive 32-bit floating point value.

7.2.1.10 #define `NPP_MAXABS_64F` (1.7976931348623158e+308)

Largest positive 64-bit floating point value.

7.2.1.11 #define NPP_MIN_16S (-32767 - 1)

Minimum 16-bit signed integer.

7.2.1.12 #define NPP_MIN_16U (0)

Minimum 16-bit unsigned integer.

7.2.1.13 #define NPP_MIN_32S (-2147483647 - 1)

Minimum 32-bit signed integer.

7.2.1.14 #define NPP_MIN_32U (0)

Minimum 32-bit unsigned integer.

7.2.1.15 #define NPP_MIN_64S (-9223372036854775807LL - 1)

Minimum 64-bit signed integer.

7.2.1.16 #define NPP_MIN_64U (0)

Minimum 64-bit unsigned integer.

7.2.1.17 #define NPP_MIN_8S (-127 - 1)

Minimum 8-bit signed integer.

7.2.1.18 #define NPP_MIN_8U (0)

Minimum 8-bit unsigned integer.

7.2.1.19 #define NPP_MINABS_32F (1.175494351e-38f)

Smallest positive 32-bit floating point value.

7.2.1.20 #define NPP_MINABS_64F (2.2250738585072014e-308)

Smallest positive 64-bit floating point value.

7.2.2 Enumeration Type Documentation**7.2.2.1 enum NppCmpOp**

Enumerator:

NPP_CMP_LESS

NPP_CMP_LESS_EQ
NPP_CMP_EQ
NPP_CMP_GREATER_EQ
NPP_CMP_GREATER

7.2.2.2 enum NppGpuComputeCapability

Enumerator:

NPP_CUDA_UNKNOWN_VERSION Indicates that the compute-capability query failed.
NPP_CUDA_NOT_CAPABLE Indicates that no CUDA capable device was found.
NPP_CUDA_1_0 Indicates that CUDA 1.0 capable device is machine's default device.
NPP_CUDA_1_1 Indicates that CUDA 1.1 capable device is machine's default device.
NPP_CUDA_1_2 Indicates that CUDA 1.2 capable device is machine's default device.
NPP_CUDA_1_3 Indicates that CUDA 1.3 capable device is machine's default device.
NPP_CUDA_2_0 Indicates that CUDA 2.0 capable device is machine's default device.
NPP_CUDA_2_1 Indicates that CUDA 2.1 capable device is machine's default device.
NPP_CUDA_3_0 Indicates that CUDA 3.0 capable device is machine's default device.
NPP_CUDA_3_2 Indicates that CUDA 3.2 capable device is machine's default device.
NPP_CUDA_3_5 Indicates that CUDA 3.5 capable device is machine's default device.
NPP_CUDA_3_7 Indicates that CUDA 3.7 capable device is machine's default device.
NPP_CUDA_5_0 Indicates that CUDA 5.0 capable device is machine's default device.
NPP_CUDA_5_2 Indicates that CUDA 5.2 capable device is machine's default device.
NPP_CUDA_5_3 Indicates that CUDA 5.3 capable device is machine's default device.
NPP_CUDA_6_0 Indicates that CUDA 6.0 or better is machine's default device.

7.2.2.3 enum NppHintAlgorithm

Enumerator:

NPP_ALG_HINT_NONE
NPP_ALG_HINT_FAST
NPP_ALG_HINT_ACCURATE

7.2.2.4 enum NppiAlphaOp

Enumerator:

NPPI_OP_ALPHA_OVER
NPPI_OP_ALPHA_IN
NPPI_OP_ALPHA_OUT
NPPI_OP_ALPHA_ATOP
NPPI_OP_ALPHA_XOR

NPPI_OP_ALPHA_PLUS
NPPI_OP_ALPHA_OVER_PREMUL
NPPI_OP_ALPHA_IN_PREMUL
NPPI_OP_ALPHA_OUT_PREMUL
NPPI_OP_ALPHA_ATOP_PREMUL
NPPI_OP_ALPHA_XOR_PREMUL
NPPI_OP_ALPHA_PLUS_PREMUL
NPPI_OP_ALPHA_PREMUL

7.2.2.5 enum NppiAxis

Enumerator:

NPP_HORIZONTAL_AXIS
NPP_VERTICAL_AXIS
NPP_BOTH_AXIS

7.2.2.6 enum NppiBayerGridPosition

Bayer Grid Position Registration.

Enumerator:

NPPI_BAYER_BGGR Default registration position.
NPPI_BAYER_RGGB
NPPI_BAYER_GBRG
NPPI_BAYER_GRBG

7.2.2.7 enum NppiBorderType

Enumerator:

NPP_BORDER_UNDEFINED
NPP_BORDER_NONE
NPP_BORDER_CONSTANT
NPP_BORDER_REPLICATE
NPP_BORDER_WRAP
NPP_BORDER_MIRROR

7.2.2.8 enum NppiDifferentialKernel

Differential Filter types.

Enumerator:

NPP_FILTER_SOBEL
NPP_FILTER_SCHARR

7.2.2.9 enum NppiHuffmanTableType

Enumerator:

nppiDCTable DC Table.

nppiACTable AC Table.

7.2.2.10 enum NppiInterpolationMode

Filtering methods.

Enumerator:

NPPI_INTER_UNDEFINED

NPPI_INTER_NN Nearest neighbor filtering.

NPPI_INTER_LINEAR Linear interpolation.

NPPI_INTER_CUBIC Cubic interpolation.

NPPI_INTER_CUBIC2P_BSPLINE Two-parameter cubic filter (B=1, C=0).

NPPI_INTER_CUBIC2P_CATMULLROM Two-parameter cubic filter (B=0, C=1/2).

NPPI_INTER_CUBIC2P_B05C03 Two-parameter cubic filter (B=1/2, C=3/10).

NPPI_INTER_SUPER Super sampling.

NPPI_INTER_LANCZOS Lanczos filtering.

NPPI_INTER_LANCZOS3_ADVANCED Generic Lanczos filtering with order 3.

NPPI_SMOOTH_EDGE Smooth edge filtering.

7.2.2.11 enum NppiMaskSize

Fixed filter-kernel sizes.

Enumerator:

NPP_MASK_SIZE_1_X_3

NPP_MASK_SIZE_1_X_5

NPP_MASK_SIZE_3_X_1

NPP_MASK_SIZE_5_X_1

NPP_MASK_SIZE_3_X_3

NPP_MASK_SIZE_5_X_5

NPP_MASK_SIZE_7_X_7

NPP_MASK_SIZE_9_X_9

NPP_MASK_SIZE_11_X_11

NPP_MASK_SIZE_13_X_13

NPP_MASK_SIZE_15_X_15

7.2.2.12 enum NppiNorm

Enumerator:

- nppiNormInf* maximum
- nppiNormL1* sum
- nppiNormL2* square root of sum of squares

7.2.2.13 enum NppRoundMode

Rounding Modes.

The enumerated rounding modes are used by a large number of NPP primitives to allow the user to specify the method by which fractional values are converted to integer values. Also see [Rounding Modes](#).

For NPP release 5.5 new names for the three rounding modes are introduced that are based on the naming conventions for rounding modes set forth in the IEEE-754 floating-point standard. Developers are encouraged to use the new, longer names to be future proof as the legacy names will be deprecated in subsequent NPP releases.

Enumerator:

NPP_RND_NEAR Round to the nearest even integer.

All fractional numbers are rounded to their nearest integer. The ambiguous cases (i.e. $\langle \text{integer} \rangle.5$) are rounded to the closest even integer. E.g.

- `roundNear(0.5) = 0`
- `roundNear(0.6) = 1`
- `roundNear(1.5) = 2`
- `roundNear(-1.5) = -2`

NPP_ROUND_NEAREST_TIES_TO_EVEN Alias name for [NPP_RND_NEAR](#).

NPP_RND_FINANCIAL Round according to financial rule.

All fractional numbers are rounded to their nearest integer. The ambiguous cases (i.e. $\langle \text{integer} \rangle.5$) are rounded away from zero. E.g.

- `roundFinancial(0.4) = 0`
- `roundFinancial(0.5) = 1`
- `roundFinancial(-1.5) = -2`

NPP_ROUND_NEAREST_TIES_AWAY_FROM_ZERO Alias name for [NPP_RND_FINANCIAL](#).

NPP_RND_ZERO Round towards zero (truncation).

All fractional numbers of the form $\langle \text{integer} \rangle.\langle \text{decimals} \rangle$ are truncated to $\langle \text{integer} \rangle$.

- `roundZero(1.5) = 1`
- `roundZero(1.9) = 1`
- `roundZero(-2.5) = -2`

NPP_ROUND_TOWARD_ZERO Alias name for [NPP_RND_ZERO](#).

7.2.2.14 enum NppStatus

Error Status Codes.

Almost all NPP function return error-status information using these return codes. Negative return codes indicate errors, positive return codes indicate warnings, a return code of 0 indicates success.

Enumerator:

NPP_NOT_SUPPORTED_MODE_ERROR

NPP_INVALID_HOST_POINTER_ERROR

NPP_INVALID_DEVICE_POINTER_ERROR

NPP_LUT_PALETTE_BITSIZE_ERROR

NPP_ZC_MODE_NOT_SUPPORTED_ERROR ZeroCrossing mode not supported.

NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY

NPP_TEXTURE_BIND_ERROR

NPP_WRONG_INTERSECTION_ROI_ERROR

NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR

NPP_MEMFREE_ERROR

NPP_MEMSET_ERROR

NPP_MEMCPY_ERROR

NPP_ALIGNMENT_ERROR

NPP_CUDA_KERNEL_EXECUTION_ERROR

NPP_ROUND_MODE_NOT_SUPPORTED_ERROR Unsupported round mode.

NPP_QUALITY_INDEX_ERROR Image pixels are constant for quality index.

NPP_RESIZE_NO_OPERATION_ERROR One of the output image dimensions is less than 1 pixel.

NPP_OVERFLOW_ERROR Number overflows the upper or lower limit of the data type.

NPP_NOT_EVEN_STEP_ERROR Step value is not pixel multiple.

NPP_HISTOGRAM_NUMBER_OF_LEVELS_ERROR Number of levels for histogram is less than 2.

NPP_LUT_NUMBER_OF_LEVELS_ERROR Number of levels for LUT is less than 2.

NPP_CORRUPTED_DATA_ERROR Processed data is corrupted.

NPP_CHANNEL_ORDER_ERROR Wrong order of the destination channels.

NPP_ZERO_MASK_VALUE_ERROR All values of the mask are zero.

NPP_QUADRANGLE_ERROR The quadrangle is nonconvex or degenerates into triangle, line or point.

NPP_RECTANGLE_ERROR Size of the rectangle region is less than or equal to 1.

NPP_COEFFICIENT_ERROR Unallowable values of the transformation coefficients.

NPP_NUMBER_OF_CHANNELS_ERROR Bad or unsupported number of channels.

NPP_COI_ERROR Channel of interest is not 1, 2, or 3.

NPP_DIVISOR_ERROR Divisor is equal to zero.

NPP_CHANNEL_ERROR Illegal channel index.

NPP_STRIDE_ERROR Stride is less than the row length.

NPP_ANCHOR_ERROR Anchor point is outside mask.

NPP_MASK_SIZE_ERROR Lower bound is larger than upper bound.

NPP_RESIZE_FACTOR_ERROR

NPP_INTERPOLATION_ERROR

NPP_MIRROR_FLIP_ERROR

NPP_MOMENT_00_ZERO_ERROR

NPP_THRESHOLD_NEGATIVE_LEVEL_ERROR

NPP_THRESHOLD_ERROR

NPP_CONTEXT_MATCH_ERROR

NPP_FFT_FLAG_ERROR

NPP_FFT_ORDER_ERROR

NPP_STEP_ERROR Step is less or equal zero.

NPP_SCALE_RANGE_ERROR

NPP_DATA_TYPE_ERROR

NPP_OUT_OFF_RANGE_ERROR

NPP_DIVIDE_BY_ZERO_ERROR

NPP_MEMORY_ALLOCATION_ERR

NPP_NULL_POINTER_ERROR

NPP_RANGE_ERROR

NPP_SIZE_ERROR

NPP_BAD_ARGUMENT_ERROR

NPP_NO_MEMORY_ERROR

NPP_NOT_IMPLEMENTED_ERROR

NPP_ERROR

NPP_ERROR_RESERVED

NPP_NO_ERROR Error free operation.

NPP_SUCCESS Successful operation (same as ***NPP_NO_ERROR***).

NPP_NO_OPERATION_WARNING Indicates that no operation was performed.

NPP_DIVIDE_BY_ZERO_WARNING Divisor is zero however does not terminate the execution.

NPP_AFFINE_QUAD_INCORRECT_WARNING Indicates that the quadrangle passed to one of affine warping functions doesn't have necessary properties.
First 3 vertices are used, the fourth vertex discarded.

NPP_WRONG_INTERSECTION_ROI_WARNING The given ROI has no intersection with either the source or destination ROI.
Thus no operation was performed.

NPP_WRONG_INTERSECTION_QUAD_WARNING The given quadrangle has no intersection with either the source or destination ROI.
Thus no operation was performed.

NPP_DOUBLE_SIZE_WARNING Image size isn't multiple of two.
Indicates that in case of 422/411/420 sampling the ROI width/height was modified for proper processing.

NPP_MISALIGNED_DST_ROI_WARNING Speed reduction due to uncoalesced memory accesses warning.

7.2.2.15 enum NppsZCType**Enumerator:**

nppZCR sign change

nppZCXor sign change XOR

nppZCC sign change count_0

7.3 Basic NPP Data Types

Data Structures

- struct [NPP_ALIGN_8](#)
Complex Number This struct represents an unsigned int complex number.
- struct [NPP_ALIGN_16](#)
Complex Number This struct represents a long long complex number.

Typedefs

- typedef unsigned char [Npp8u](#)
8-bit unsigned chars
- typedef signed char [Npp8s](#)
8-bit signed chars
- typedef unsigned short [Npp16u](#)
16-bit unsigned integers
- typedef short [Npp16s](#)
16-bit signed integers
- typedef unsigned int [Npp32u](#)
32-bit unsigned integers
- typedef int [Npp32s](#)
32-bit signed integers
- typedef unsigned long long [Npp64u](#)
64-bit unsigned integers
- typedef long long [Npp64s](#)
64-bit signed integers
- typedef float [Npp32f](#)
32-bit (IEEE) floating-point numbers
- typedef double [Npp64f](#)
64-bit floating-point numbers
- typedef struct [NPP_ALIGN_8](#) [Npp32uc](#)
Complex Number This struct represents an unsigned int complex number.
- typedef struct [NPP_ALIGN_8](#) [Npp32sc](#)
Complex Number This struct represents a signed int complex number.

- typedef struct [NPP_ALIGN_8 Npp32fc](#)
Complex Number This struct represents a single floating-point complex number.
- typedef struct [NPP_ALIGN_16 Npp64sc](#)
Complex Number This struct represents a long long complex number.
- typedef struct [NPP_ALIGN_16 Npp64fc](#)
Complex Number This struct represents a double floating-point complex number.

Functions

- struct [__align__](#) (2)
Complex Number This struct represents an unsigned char complex number.
- struct [__align__](#) (4)
Complex Number This struct represents an unsigned short complex number.

Variables

- [Npp8uc](#)
- [Npp16uc](#)
- [Npp16sc](#)

7.3.1 Typedef Documentation

7.3.1.1 typedef short Npp16s

16-bit signed integers

7.3.1.2 typedef unsigned short Npp16u

16-bit unsigned integers

7.3.1.3 typedef float Npp32f

32-bit (IEEE) floating-point numbers

7.3.1.4 typedef struct NPP_ALIGN_8 Npp32fc

Complex Number This struct represents a single floating-point complex number.

7.3.1.5 typedef int Npp32s

32-bit signed integers

7.3.1.6 typedef struct NPP_ALIGN_8 Npp32sc

Complex Number This struct represents a signed int complex number.

7.3.1.7 typedef unsigned int Npp32u

32-bit unsigned integers

7.3.1.8 typedef struct NPP_ALIGN_8 Npp32uc

Complex Number This struct represents an unsigned int complex number.

7.3.1.9 typedef double Npp64f

64-bit floating-point numbers

7.3.1.10 typedef struct NPP_ALIGN_16 Npp64fc

Complex Number This struct represents a double floating-point complex number.

7.3.1.11 typedef long long Npp64s

64-bit signed integers

7.3.1.12 typedef struct NPP_ALIGN_16 Npp64sc

Complex Number This struct represents a long long complex number.

7.3.1.13 typedef unsigned long long Npp64u

64-bit unsigned integers

7.3.1.14 typedef signed char Npp8s

8-bit signed chars

7.3.1.15 typedef unsigned char Npp8u

8-bit unsigned chars

7.3.2 Function Documentation**7.3.2.1 struct __align__ (4) [read]**

Complex Number This struct represents an unsigned short complex number.

Complex Number This struct represents a short complex number.

< Real part

< Imaginary part

< Real part

< Imaginary part

7.3.2.2 `struct __align__(2) [read]`

Complex Number This struct represents an unsigned char complex number.

< Real part

< Imaginary part

7.3.3 Variable Documentation

7.3.3.1 `Npp16sc`

7.3.3.2 `Npp16uc`

7.3.3.3 `Npp8uc`

7.4 Geometry Transforms

Routines manipulating an image's geometry.

Modules

- [ResizeSqrPixel](#)

ResizeSqrPixel supports the following interpolation modes:

- [Resize](#)

This function has been deprecated.

- [Remap](#)

Remap supports the following interpolation modes:

- [Rotate](#)

Rotates an image around the origin (0,0) and then shifts it.

- [Mirror](#)
- [Affine Transforms](#)
- [Perspective Transform](#)

7.4.1 Detailed Description

Routines manipulating an image's geometry.

These functions can be found in either the nppi or nppig libraries. Linking to only the sub-libraries that you use can significantly save link time, application load time, and CUDA runtime startup time when using dynamic libraries.

7.4.2 Geometric Transform API Specifics

This section covers some of the unique API features common to the geometric transform primitives.

7.4.2.1 Geometric Transforms and ROIs

Geometric transforms operate on source and destination ROIs. The way these ROIs affect the processing of pixels differs from other (non geometric) image-processing primitives: Only pixels in the intersection of the destination ROI and the transformed source ROI are being processed.

The typical processing proceeds as follows:

1. Transform the rectangular source ROI (given in source image coordinates) into the destination image space. This yields a quadrilateral.
2. Write only pixels in the intersection of the transformed source ROI and the destination ROI.

7.4.2.2 Pixel Interpolation

The majority of image geometry transform operation need to perform a resampling of the source image as source and destination pixels are not coincident.

NPP supports the following pixel interpolation modes (in order from fastest to slowest and lowest to highest quality):

- nearest neighbor
- linear interpolation
- cubic convolution
- supersampling
- interpolation using Lanczos window function

7.5 ResizeSqrPixel

ResizeSqrPixel supports the following interpolation modes:.

GetResizeRect

Returns [NppiRect](#) which represents the offset and size of the destination rectangle that would be generated by resizing the source [NppiRect](#) by the requested scale factors and shifts.

- [NppStatus](#) [nppiGetResizeRect](#) ([NppiRect](#) oSrcROI, [NppiRect](#) *pDstRect, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

ResizeSqrPixel

Resizes images.

- [NppStatus](#) [nppiResizeSqrPixel_8u_C1R](#) (const [Npp8u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 8-bit unsigned image resize.
- [NppStatus](#) [nppiResizeSqrPixel_8u_C3R](#) (const [Npp8u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 8-bit unsigned image resize.
- [NppStatus](#) [nppiResizeSqrPixel_8u_C4R](#) (const [Npp8u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 8-bit unsigned image resize.
- [NppStatus](#) [nppiResizeSqrPixel_8u_AC4R](#) (const [Npp8u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 8-bit unsigned image resize not affecting alpha.
- [NppStatus](#) [nppiResizeSqrPixel_8u_P3R](#) (const [Npp8u](#) *const pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst[3], int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 8-bit unsigned planar image resize.
- [NppStatus](#) [nppiResizeSqrPixel_8u_P4R](#) (const [Npp8u](#) *const pSrc[4], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp8u](#) *pDst[4], int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 8-bit unsigned planar image resize.
- [NppStatus](#) [nppiResizeSqrPixel_16u_C1R](#) (const [Npp16u](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, [Npp16u](#) *pDst, int nDstStep, [NppiRect](#) oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 16-bit unsigned image resize.

- `NppStatus nppiResizeSqrPixel_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 16-bit unsigned image resize.
- `NppStatus nppiResizeSqrPixel_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit unsigned image resize.
- `NppStatus nppiResizeSqrPixel_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit unsigned image resize not affecting alpha.
- `NppStatus nppiResizeSqrPixel_16u_P3R` (const `Npp16u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[3], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 16-bit unsigned planar image resize.
- `NppStatus nppiResizeSqrPixel_16u_P4R` (const `Npp16u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[4], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit unsigned planar image resize.
- `NppStatus nppiResizeSqrPixel_16s_C1R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 16-bit signed image resize.
- `NppStatus nppiResizeSqrPixel_16s_C3R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 16-bit signed image resize.
- `NppStatus nppiResizeSqrPixel_16s_C4R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit signed image resize.
- `NppStatus nppiResizeSqrPixel_16s_AC4R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit signed image resize not affecting alpha.
- `NppStatus nppiResizeSqrPixel_16s_P3R` (const `Npp16s` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst[3], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 16-bit signed planar image resize.

- `NppStatus nppiResizeSqrPixel_16s_P4R` (const `Npp16s` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16s` *pDst[4], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 16-bit signed planar image resize.
- `NppStatus nppiResizeSqrPixel_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 32-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 32-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 32-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 32-bit floating point image resize not affecting alpha.
- `NppStatus nppiResizeSqrPixel_32f_P3R` (const `Npp32f` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[3], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 32-bit floating point planar image resize.
- `NppStatus nppiResizeSqrPixel_32f_P4R` (const `Npp32f` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[4], int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 32-bit floating point planar image resize.
- `NppStatus nppiResizeSqrPixel_64f_C1R` (const `Npp64f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
1 channel 64-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_64f_C3R` (const `Npp64f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 64-bit floating point image resize.
- `NppStatus nppiResizeSqrPixel_64f_C4R` (const `Npp64f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f` *pDst, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 64-bit floating point image resize.

- `NppStatus nppiResizeSqrPixel_64f_AC4R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 64-bit floating point image resize not affecting alpha.
- `NppStatus nppiResizeSqrPixel_64f_P3R` (const `Npp64f *const pSrc[3]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst[3]`, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
3 channel 64-bit floating point planar image resize.
- `NppStatus nppiResizeSqrPixel_64f_P4R` (const `Npp64f *const pSrc[4]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst[4]`, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)
4 channel 64-bit floating point planar image resize.
- `NppStatus nppiResizeAdvancedGetBufferHostSize_8u_C1R` (`NppiSize` oSrcROI, `NppiSize` oDstROI, int *hpBufferSize, int eInterpolationMode)
Buffer size for `nppiResizeSqrPixel_8u_C1R_Advanced`.
- `NppStatus nppiResizeSqrPixel_8u_C1R_Advanced` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, double nXFactor, double nYFactor, `Npp8u *pBuffer`, int eInterpolationMode)
1 channel 8-bit unsigned image resize.

7.5.1 Detailed Description

ResizeSqrPixel supports the following interpolation modes:

```

NPPI_INTER_NN
NPPI_INTER_LINEAR
NPPI_INTER_CUBIC
NPPI_INTER_CUBIC2P_BSPLINE
NPPI_INTER_CUBIC2P_CATMULLROM
NPPI_INTER_CUBIC2P_B05C03
NPPI_INTER_SUPER
NPPI_INTER_LANZOS

```

ResizeSqrPixel attempts to choose source pixels that would approximately represent the center of the destination pixels. It does so by using the following scaling formula to select source pixels for interpolation:

```

nAdjustedXFactor = 1.0 / nXFactor;
nAdjustedYFactor = 1.0 / nYFactor;
nAdjustedXShift = nXShift * nAdjustedXFactor + ((1.0 - nAdjustedXFactor) * 0.5);
nAdjustedYShift = nYShift * nAdjustedYFactor + ((1.0 - nAdjustedYFactor) * 0.5);
nSrcX = nAdjustedXFactor * nDstX - nAdjustedXShift;
nSrcY = nAdjustedYFactor * nDstY - nAdjustedYShift;

```

In the ResizeSqrPixel functions below source image clip checking is handled as follows:

If the source pixel fractional x and y coordinates are greater than or equal to oSizeROI.x and less than oSizeROI.x + oSizeROI.width and greater than or equal to oSizeROI.y and less than oSizeROI.y + oSizeROI.height then the source pixel is considered to be within the source image clip rectangle and the source image is sampled. Otherwise the source image is not sampled and a destination pixel is not written to the destination image.

7.5.2 Error Codes

The resize primitives return the following error codes:

- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) indicates an error condition if srcROIrect has no intersection with the source image.
- [NPP_RESIZE_NO_OPERATION_ERROR](#) if either destination ROI width or height is less than 1 pixel.
- [NPP_RESIZE_FACTOR_ERROR](#) Indicates an error condition if either nXFactor or nYFactor is less than or equal to zero.
- [NPP_INTERPOLATION_ERROR](#) if eInterpolation has an illegal value.
- [NPP_SIZE_ERROR](#) if source size width or height is less than 2 pixels.

7.5.3 Function Documentation

7.5.3.1 NppStatus nppiGetResizeRect (NppiRect oSrcROI, NppiRect * pDstRect, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

Parameters:

oSrcROI Region of interest in the source image.

pDstRect User supplied host memory pointer to an [NppiRect](#) structure that will be filled in by this function with the region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.2 NppStatus nppiResizeAdvancedGetBufferHostSize_8u_C1R (NppiSize oSrcROI, NppiSize oDstROI, int * hpBufferSize, int eInterpolationMode)

Buffer size for [nppiResizeSqrPixel_8u_C1R_Advanced](#).

Parameters:

oSrcROI Region-of-Interest (ROI).

oDstROI Region-of-Interest (ROI).

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*: [Scratch Buffer and Host Pointer](#).

eInterpolationMode The type of eInterpolation to perform resampling. Currently only supports NPPI_INTER_LANCZOS3_Advanced.

Returns:

NPP_NULL_POINTER_ERROR if hpBufferSize is 0 (NULL), [ROI Related Error Codes](#).

7.5.3.3 NppStatus nppiResizeSqrPixel_16s_AC4R (const Npp16s * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16s * *pDst*, int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

4 channel 16-bit signed image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.4 NppStatus nppiResizeSqrPixel_16s_C1R (const Npp16s * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16s * *pDst*, int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

1 channel 16-bit signed image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.5 NppStatus nppiResizeSqrPixel_16s_C3R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16s * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

3 channel 16-bit signed image resize.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.6 NppStatus nppiResizeSqrPixel_16s_C4R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16s * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

4 channel 16-bit signed image resize.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.7 NppStatus nppiResizeSqrPixel_16s_P3R (**const Npp16s *const pSrc[3]**, **NppiSize oSrcSize**, **int nSrcStep**, **NppiRect oSrcROI**, **Npp16s *pDst[3]**, **int nDstStep**, **NppiRect oDstROI**, **double nXFactor**, **double nYFactor**, **double nXShift**, **double nYShift**, **int eInterpolation**)

3 channel 16-bit signed planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.8 NppStatus nppiResizeSqrPixel_16s_P4R (**const Npp16s *const pSrc[4]**, **NppiSize oSrcSize**, **int nSrcStep**, **NppiRect oSrcROI**, **Npp16s *pDst[4]**, **int nDstStep**, **NppiRect oDstROI**, **double nXFactor**, **double nYFactor**, **double nXShift**, **double nYShift**, **int eInterpolation**)

4 channel 16-bit signed planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.9 NppStatus nppiResizeSqrPixel_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

4 channel 16-bit unsigned image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.10 NppStatus nppiResizeSqrPixel_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

1 channel 16-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.11 `NppStatus nppiResizeSqrPixel_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 16-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.12 `NppStatus nppiResizeSqrPixel_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 16-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.13 `NppStatus nppiResizeSqrPixel_16u_P3R (const Npp16u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u *pDst[3], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 16-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
nXShift Source pixel shift in x-direction.
nYShift Source pixel shift in y-direction.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.14 `NppStatus nppiResizeSqrPixel_16u_P4R (const Npp16u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u *pDst[4], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 16-bit unsigned planar image resize.

Parameters:

- pSrc* [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.15 `NppStatus nppiResizeSqrPixel_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 32-bit floating point image resize not affecting alpha.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.16 NppStatus nppiResizeSqrPixel_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

1 channel 32-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.17 NppStatus nppiResizeSqrPixel_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

3 channel 32-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.18 NppStatus nppiResizeSqrPixel_32f_C4R (const Npp32f * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32f * *pDst*, int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

4 channel 32-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.19 NppStatus nppiResizeSqrPixel_32f_P3R (const Npp32f *const *pSrc*[3], NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32f * *pDst*[3], int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

3 channel 32-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.20 NppStatus nppiResizeSqrPixel_32f_P4R (const Npp32f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f *pDst[4], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

4 channel 32-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.21 NppStatus nppiResizeSqrPixel_64f_AC4R (const Npp64f *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f *pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

4 channel 64-bit floating point image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.22 NppStatus nppiResizeSqrPixel_64f_C1R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

1 channel 64-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.23 NppStatus nppiResizeSqrPixel_64f_C3R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

3 channel 64-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.24 NppStatus nppiResizeSqrPixel_64f_C4R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

4 channel 64-bit floating point image resize.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.25 NppStatus nppiResizeSqrPixel_64f_P3R (const Npp64f *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst[3], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

3 channel 64-bit floating point planar image resize.

Parameters:

- pSrc* [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.26 `NppStatus nppiResizeSqrPixel_64f_P4R (const Npp64f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f *pDst[4], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 64-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.27 `NppStatus nppiResizeSqrPixel_8u_AC4R (const Npp8u *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 8-bit unsigned image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.28 NppStatus nppiResizeSqrPixel_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)

1 channel 8-bit unsigned image resize.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- nXShift* Source pixel shift in x-direction.
- nYShift* Source pixel shift in y-direction.
- eInterpolation* The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.29 NppStatus nppiResizeSqrPixel_8u_C1R_Advanced (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, Npp8u * pBuffer, int eInterpolationMode)

1 channel 8-bit unsigned image resize.

This primitive matches the behavior of GraphicsMagick++.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstROI* Region of interest in the destination image.
- nXFactor* Factor by which x dimension is changed.
- nYFactor* Factor by which y dimension is changed.
- pBuffer* Device buffer that is used during calculations.
- eInterpolationMode* The type of eInterpolation to perform resampling. Currently only supports NPPI_INTER_LANCZOS3_Advanced.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.30 NppStatus nppiResizeSqrPixel_8u_C3R (const Npp8u * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp8u * *pDst*, int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

3 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.31 NppStatus nppiResizeSqrPixel_8u_C4R (const Npp8u * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp8u * *pDst*, int *nDstStep*, NppiRect *oDstROI*, double *nXFactor*, double *nYFactor*, double *nXShift*, double *nYShift*, int *eInterpolation*)

4 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.32 `NppStatus nppiResizeSqrPixel_8u_P3R (const Npp8u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst[3], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

3 channel 8-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.5.3.33 `NppStatus nppiResizeSqrPixel_8u_P4R (const Npp8u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst[4], int nDstStep, NppiRect oDstROI, double nXFactor, double nYFactor, double nXShift, double nYShift, int eInterpolation)`

4 channel 8-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

nXShift Source pixel shift in x-direction.

nYShift Source pixel shift in y-direction.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6 Resize

This function has been deprecated.

Resize

Resizes images.

- `NppStatus nppiResize_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
1 channel 8-bit unsigned image resize.
- `NppStatus nppiResize_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
3 channel 8-bit unsigned image resize.
- `NppStatus nppiResize_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
4 channel 8-bit unsigned image resize.
- `NppStatus nppiResize_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
4 channel 8-bit unsigned image resize not affecting alpha.
- `NppStatus nppiResize_8u_P3R` (const `Npp8u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst[3], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
3 channel 8-bit unsigned planar image resize.
- `NppStatus nppiResize_8u_P4R` (const `Npp8u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst[4], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
4 channel 8-bit unsigned planar image resize.
- `NppStatus nppiResize_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
1 channel 16-bit unsigned image resize.
- `NppStatus nppiResize_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)
3 channel 16-bit unsigned image resize.
- `NppStatus nppiResize_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned image resize.

- `NppStatus nppiResize_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned image resize not affecting alpha.

- `NppStatus nppiResize_16u_P3R` (const `Npp16u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[3], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

3 channel 16-bit unsigned planar image resize.

- `NppStatus nppiResize_16u_P4R` (const `Npp16u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[4], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned planar image resize.

- `NppStatus nppiResize_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

1 channel 32-bit floating point image resize.

- `NppStatus nppiResize_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

3 channel 32-bit floating point image resize.

- `NppStatus nppiResize_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 32-bit floating point image resize.

- `NppStatus nppiResize_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 32-bit floating point image resize not affecting alpha.

- `NppStatus nppiResize_32f_P3R` (const `Npp32f` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[3], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

3 channel 32-bit floating point planar image resize.

- `NppStatus nppiResize_32f_P4R` (const `Npp32f` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[4], int nDstStep, `NppiSize` dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 32-bit floating point planar image resize.

7.6.1 Detailed Description

This function has been deprecated.

ResizeSqrPixel provides the same functionality and more.

Resize supports the following interpolation modes:

```
NPPI_INTER_NN
NPPI_INTER_LINEAR
NPPI_INTER_CUBIC
NPPI_INTER_SUPER
NPPI_INTER_LANCZOS
```

Resize uses the following scaling formula to select source pixels for interpolation:

```
scaledSrcSize.width = nXFactor * srcRectROI.width;
scaledSrcSize.height = nYFactor * srcRectROI.height;
nAdjustedXFactor = (srcRectROI.width - 1) / (scaledSrcSize.width - 1);
nAdjustedYFactor = (srcRectROI.height - 1) / (scaledSrcSize.height - 1);
nSrcX = nAdjustedXFactor * nDstX;
nSrcY = nAdjustedYFactor * nDstY;
```

In the Resize functions below source image clip checking is handled as follows:

If the source pixel fractional x and y coordinates are greater than or equal to oSizeROI.x and less than oSizeROI.x + oSizeROI.width and greater than or equal to oSizeROI.y and less than oSizeROI.y + oSizeROI.height then the source pixel is considered to be within the source image clip rectangle and the source image is sampled. Otherwise the source image is not sampled and a destination pixel is not written to the destination image.

7.6.2 Error Codes

The resize primitives return the following error codes:

- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) indicates an error condition if srcROIRect has no intersection with the source image.
- [NPP_RESIZE_NO_OPERATION_ERROR](#) if either destination ROI width or height is less than 1 pixel.
- [NPP_RESIZE_FACTOR_ERROR](#) Indicates an error condition if either nXFactor or nYFactor is less than or equal to zero.
- [NPP_INTERPOLATION_ERROR](#) if eInterpolation has an illegal value.
- [NPP_SIZE_ERROR](#) if source size width or height is less than 2 pixels.

7.6.3 Function Documentation

7.6.3.1 NppStatus nppiResize_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned image resize not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.2 **NppStatus nppiResize_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)**

1 channel 16-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.3 **NppStatus nppiResize_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)**

3 channel 16-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.4 NppStatus nppiResize_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.5 NppStatus nppiResize_16u_P3R (const Npp16u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

3 channel 16-bit unsigned planar image resize.

Parameters:

pSrc Source-Planar-Image Pointer Array (host memory array containing device memory image plane pointers).
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst Destination-Planar-Image Pointer Array (host memory array containing device memory image plane pointers).

nDstStep Destination-Image Line Step.

dstROISize Size in pixels of the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.6 NppStatus nppiResize_16u_P4R (const Npp16u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u *pDst[4], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 16-bit unsigned planar image resize.

Parameters:

pSrc Source-Planar-Image Pointer Array (host memory array containing device memory image plane pointers).

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst Destination-Planar-Image Pointer Array (host memory array containing device memory image plane pointers).

nDstStep Destination-Image Line Step.

dstROISize Size in pixels of the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.7 NppStatus nppiResize_32f_AC4R (const Npp32f *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f *pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 32-bit floating point image resize not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.8 `NppStatus nppiResize_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

1 channel 32-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.9 `NppStatus nppiResize_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

3 channel 32-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.10 `NppStatus nppiResize_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 32-bit floating point image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.11 `NppStatus nppiResize_32f_P3R (const Npp32f *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

3 channel 32-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of `eInterpolation` to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.12 `NppStatus nppiResize_32f_P4R (const Npp32f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f *pDst[4], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 32-bit floating point planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of `eInterpolation` to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.13 `NppStatus nppiResize_8u_AC4R (const Npp8u *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 8-bit unsigned image resize not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.14 `NppStatus nppiResize_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

1 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.15 `NppStatus nppiResize_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

3 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.16 `NppStatus nppiResize_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

4 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstROISize Size in pixels of the destination image.
nXFactor Factor by which x dimension is changed.
nYFactor Factor by which y dimension is changed.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.17 `NppStatus nppiResize_8u_P3R (const Npp8u * const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)`

3 channel 8-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).
nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.6.3.18 NppStatus nppiResize_8u_P4R (const Npp8u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiSize dstROISize, double nXFactor, double nYFactor, int eInterpolation)

4 channel 8-bit unsigned planar image resize.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pDst [Destination-Planar-Image Pointer Array](#) (host memory array containing device memory image plane pointers).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image.

nXFactor Factor by which x dimension is changed.

nYFactor Factor by which y dimension is changed.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7 Remap

Remap supports the following interpolation modes:

Remap

Remaps images.

- `NppStatus nppiRemap_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
1 channel 8-bit unsigned image remap.
- `NppStatus nppiRemap_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
3 channel 8-bit unsigned image remap.
- `NppStatus nppiRemap_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
4 channel 8-bit unsigned image remap.
- `NppStatus nppiRemap_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
4 channel 8-bit unsigned image remap not affecting alpha.
- `NppStatus nppiRemap_8u_P3R` (const `Npp8u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst[3], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
3 channel 8-bit unsigned planar image remap.
- `NppStatus nppiRemap_8u_P4R` (const `Npp8u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp8u` *pDst[4], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
4 channel 8-bit unsigned planar image remap.
- `NppStatus nppiRemap_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
1 channel 16-bit unsigned image remap.
- `NppStatus nppiRemap_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)
3 channel 16-bit unsigned image remap.
- `NppStatus nppiRemap_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit unsigned image remap.

- `NppStatus nppiRemap_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit unsigned image remap not affecting alpha.

- `NppStatus nppiRemap_16u_P3R` (const `Npp16u` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst[3], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

3 channel 16-bit unsigned planar image remap.

- `NppStatus nppiRemap_16u_P4R` (const `Npp16u` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16u` *pDst[4], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit unsigned planar image remap.

- `NppStatus nppiRemap_16s_C1R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

1 channel 16-bit signed image remap.

- `NppStatus nppiRemap_16s_C3R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

3 channel 16-bit signed image remap.

- `NppStatus nppiRemap_16s_C4R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit signed image remap.

- `NppStatus nppiRemap_16s_AC4R` (const `Npp16s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit signed image remap not affecting alpha.

- `NppStatus nppiRemap_16s_P3R` (const `Npp16s` *const pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst[3], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

3 channel 16-bit signed planar image remap.

- `NppStatus nppiRemap_16s_P4R` (const `Npp16s` *const pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp16s` *pDst[4], int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

4 channel 16-bit signed planar image remap.

- `NppStatus nppiRemap_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const `Npp32f` *pXMap, int nXMapStep, const `Npp32f` *pYMap, int nYMapStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oDstSizeROI, int eInterpolation)

1 channel 32-bit floating point image remap.

- [NppStatus nppiRemap_32f_C3R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp32f](#) *pXMap, int nXMapStep, const [Npp32f](#) *pYMap, int nYMapStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
3 channel 32-bit floating point image remap.
- [NppStatus nppiRemap_32f_C4R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp32f](#) *pXMap, int nXMapStep, const [Npp32f](#) *pYMap, int nYMapStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
4 channel 32-bit floating point image remap.
- [NppStatus nppiRemap_32f_AC4R](#) (const [Npp32f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp32f](#) *pXMap, int nXMapStep, const [Npp32f](#) *pYMap, int nYMapStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
4 channel 32-bit floating point image remap not affecting alpha.
- [NppStatus nppiRemap_32f_P3R](#) (const [Npp32f](#) *const pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp32f](#) *pXMap, int nXMapStep, const [Npp32f](#) *pYMap, int nYMapStep, [Npp32f](#) *pDst[3], int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
3 channel 32-bit floating point planar image remap.
- [NppStatus nppiRemap_32f_P4R](#) (const [Npp32f](#) *const pSrc[4], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp32f](#) *pXMap, int nXMapStep, const [Npp32f](#) *pYMap, int nYMapStep, [Npp32f](#) *pDst[4], int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
4 channel 32-bit floating point planar image remap.
- [NppStatus nppiRemap_64f_C1R](#) (const [Npp64f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp64f](#) *pXMap, int nXMapStep, const [Npp64f](#) *pYMap, int nYMapStep, [Npp64f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
1 channel 64-bit floating point image remap.
- [NppStatus nppiRemap_64f_C3R](#) (const [Npp64f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp64f](#) *pXMap, int nXMapStep, const [Npp64f](#) *pYMap, int nYMapStep, [Npp64f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
3 channel 64-bit floating point image remap.
- [NppStatus nppiRemap_64f_C4R](#) (const [Npp64f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp64f](#) *pXMap, int nXMapStep, const [Npp64f](#) *pYMap, int nYMapStep, [Npp64f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
4 channel 64-bit floating point image remap.
- [NppStatus nppiRemap_64f_AC4R](#) (const [Npp64f](#) *pSrc, [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp64f](#) *pXMap, int nXMapStep, const [Npp64f](#) *pYMap, int nYMapStep, [Npp64f](#) *pDst, int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
4 channel 64-bit floating point image remap not affecting alpha.
- [NppStatus nppiRemap_64f_P3R](#) (const [Npp64f](#) *const pSrc[3], [NppiSize](#) oSrcSize, int nSrcStep, [NppiRect](#) oSrcROI, const [Npp64f](#) *pXMap, int nXMapStep, const [Npp64f](#) *pYMap, int nYMapStep, [Npp64f](#) *pDst[3], int nDstStep, [NppiSize](#) oDstSizeROI, int eInterpolation)
3 channel 64-bit floating point planar image remap.

- `NppStatus nppiRemap_64f_P4R` (const `Npp64f` *const `pSrc`[4], `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const `Npp64f` *`pXMap`, int `nXMapStep`, const `Npp64f` *`pYMap`, int `nYMapStep`, `Npp64f` *`pDst`[4], int `nDstStep`, `NppiSize` `oDstSizeROI`, int `eInterpolation`)

4 channel 64-bit floating point planar image remap.

7.7.1 Detailed Description

Remap supports the following interpolation modes:

NPPI_INTER_NN NPPI_INTER_LINEAR NPPI_INTER_CUBIC NPPI_INTER_CUBIC2P_BSPLINE
NPPI_INTER_CUBIC2P_CATMULLROM NPPI_INTER_CUBIC2P_B05C03 NPPI_INTER_
LANCZOS

Remap chooses source pixels using pixel coordinates explicitly supplied in two 2D device memory image arrays pointed to by the `pXMap` and `pYMap` pointers. The `pXMap` array contains the X coordinated and the `pYMap` array contains the Y coordinate of the corresponding source image pixel to use as input. These coordinates are in floating point format so fraction pixel positions can be used. The coordinates of the source pixel to sample are determined as follows:

$$nSrcX = pxMap[nDstX, nDstY] \quad nSrcY = pyMap[nDstX, nDstY]$$

In the Remap functions below source image clip checking is handled as follows:

If the source pixel fractional `x` and `y` coordinates are greater than or equal to `oSizeROI.x` and less than `oSizeROI.x + oSizeROI.width` and greater than or equal to `oSizeROI.y` and less than `oSizeROI.y + oSizeROI.height` then the source pixel is considered to be within the source image clip rectangle and the source image is sampled. Otherwise the source image is not sampled and a destination pixel is not written to the destination image.

7.7.2 Error Codes

The remap primitives return the following error codes:

- `NPP_WRONG_INTERSECTION_ROI_ERROR` indicates an error condition if `srcROIRect` has no intersection with the source image.
- `NPP_INTERPOLATION_ERROR` if `eInterpolation` has an illegal value.

7.7.3 Function Documentation

7.7.3.1 `NppStatus nppiRemap_16s_AC4R` (const `Npp16s` *`pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const `Npp32f` *`pXMap`, int `nXMapStep`, const `Npp32f` *`pYMap`, int `nYMapStep`, `Npp16s` *`pDst`, int `nDstStep`, `NppiSize` `oDstSizeROI`, int `eInterpolation`)

4 channel 16-bit signed image remap not affecting alpha.

Parameters:

`pSrc` Source-Image Pointer.

`nSrcStep` Source-Image Line Step.

`oSrcSize` Size in pixels of the source image.

`oSrcROI` Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.2 NppStatus nppiRemap_16s_C1R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

1 channel 16-bit signed image remap.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.3 NppStatus nppiRemap_16s_C3R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

3 channel 16-bit signed image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.4 NppStatus nppiRemap_16s_C4R (const Npp16s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16s * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

4 channel 16-bit signed image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.5 `NppStatus nppiRemap_16s_P3R (const Npp16s *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16s * pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 16-bit signed planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Planar-Image Pointer Array](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.6 `NppStatus nppiRemap_16s_P4R (const Npp16s *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16s * pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 16-bit signed planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.7 `NppStatus nppiRemap_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 16-bit unsigned image remap not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.8 NppStatus nppiRemap_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

1 channel 16-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.9 NppStatus nppiRemap_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp16u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

3 channel 16-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.10 `NppStatus nppiRemap_16u_C4R (const Npp16u *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp16u *pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 16-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.11 `NppStatus nppiRemap_16u_P3R (const Npp16u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp16u *pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 16-bit unsigned planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.12 `NppStatus nppiRemap_16u_P4R (const Npp16u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp16u *pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 16-bit unsigned planar image remap.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.13 NppStatus nppiRemap_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

4 channel 32-bit floating point image remap not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.14 NppStatus nppiRemap_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

1 channel 32-bit floating point image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.
eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.15 `NppStatus nppiRemap_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 32-bit floating point image remap.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.
nXMapStep pXMap image array line step in bytes.
pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
nYMapStep pYMap image array line step in bytes.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstSizeROI Region of interest size in the destination image.
eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.16 `NppStatus nppiRemap_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp32f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 32-bit floating point image remap.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.
pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
nYMapStep pYMap image array line step in bytes.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstSizeROI Region of interest size in the destination image.
eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.17 `NppStatus nppiRemap_32f_P3R (const Npp32f *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp32f *pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 32-bit floating point planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.
nXMapStep pXMap image array line step in bytes.
pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
nYMapStep pYMap image array line step in bytes.
pDst [Destination-Planar-Image Pointer Array](#).
nDstStep [Destination-Image Line Step](#).
oDstSizeROI Region of interest size in the destination image.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.18 `NppStatus nppiRemap_32f_P4R (const Npp32f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp32f *pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 32-bit floating point planar image remap.

Parameters:

- pSrc* [Source-Planar-Image Pointer Array](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pXMap* Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.
- nXMapStep* pXMap image array line step in bytes.
- pYMap* Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
- nYMapStep* pYMap image array line step in bytes.
- pDst* [Destination-Planar-Image Pointer Array](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstSizeROI* Region of interest size in the destination image.
- eInterpolation* The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.19 `NppStatus nppiRemap_64f_AC4R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f * pXMap, int nXMapStep, const Npp64f * pYMap, int nYMapStep, Npp64f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 64-bit floating point image remap not affecting alpha.

Parameters:

- pSrc* [Source-Image Pointer](#).
- nSrcStep* [Source-Image Line Step](#).
- oSrcSize* Size in pixels of the source image.
- oSrcROI* Region of interest in the source image.
- pXMap* Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.
- nXMapStep* pXMap image array line step in bytes.
- pYMap* Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
- nYMapStep* pYMap image array line step in bytes.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oDstSizeROI* Region of interest size in the destination image.
- eInterpolation* The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.20 NppStatus nppiRemap_64f_C1R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f * pXMap, int nXMapStep, const Npp64f * pYMap, int nYMapStep, Npp64f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

1 channel 64-bit floating point image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.21 NppStatus nppiRemap_64f_C3R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f * pXMap, int nXMapStep, const Npp64f * pYMap, int nYMapStep, Npp64f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)

3 channel 64-bit floating point image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.22 `NppStatus nppiRemap_64f_C4R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f * pXMap, int nXMapStep, const Npp64f * pYMap, int nYMapStep, Npp64f * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 64-bit floating point image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.23 `NppStatus nppiRemap_64f_P3R (const Npp64f *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f * pXMap, int nXMapStep, const Npp64f * pYMap, int nYMapStep, Npp64f * pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 64-bit floating point planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.24 `NppStatus nppiRemap_64f_P4R (const Npp64f *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp64f *pXMap, int nXMapStep, const Npp64f *pYMap, int nYMapStep, Npp64f *pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 64-bit floating point planar image remap.

Parameters:

pSrc Source-Planar-Image Pointer Array.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst Destination-Planar-Image Pointer Array.

nDstStep Destination-Image Line Step.

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.25 `NppStatus nppiRemap_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 8-bit unsigned image remap not affecting alpha.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of interpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.26 `NppStatus nppiRemap_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

1 channel 8-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.27 `NppStatus nppiRemap_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 8-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.28 `NppStatus nppiRemap_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f * pXMap, int nXMapStep, const Npp32f * pYMap, int nYMapStep, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 8-bit unsigned image remap.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.
pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
nYMapStep pYMap image array line step in bytes.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstSizeROI Region of interest size in the destination image.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.29 `NppStatus nppiRemap_8u_P3R (const Npp8u *const pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp8u *pDst[3], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

3 channel 8-bit unsigned planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image.
oSrcROI Region of interest in the source image.
pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.
nXMapStep pXMap image array line step in bytes.
pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.
nYMapStep pYMap image array line step in bytes.
pDst [Destination-Planar-Image Pointer Array](#).
nDstStep [Destination-Image Line Step](#).
oDstSizeROI Region of interest size in the destination image.
eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.7.3.30 `NppStatus nppiRemap_8u_P4R (const Npp8u *const pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const Npp32f *pXMap, int nXMapStep, const Npp32f *pYMap, int nYMapStep, Npp8u *pDst[4], int nDstStep, NppiSize oDstSizeROI, int eInterpolation)`

4 channel 8-bit unsigned planar image remap.

Parameters:

pSrc [Source-Planar-Image Pointer Array](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image.

oSrcROI Region of interest in the source image.

pXMap Device memory pointer to 2D image array of X coordinate values to be used when sampling source image.

nXMapStep pXMap image array line step in bytes.

pYMap Device memory pointer to 2D image array of Y coordinate values to be used when sampling source image.

nYMapStep pYMap image array line step in bytes.

pDst [Destination-Planar-Image Pointer Array](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Region of interest size in the destination image.

eInterpolation The type of eInterpolation to perform resampling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Error Codes](#)

7.8 Rotate

Rotates an image around the origin (0,0) and then shifts it.

Utility Functions

- `NppStatus nppiGetRotateQuad` (`NppiRect` oSrcROI, double aQuad[4][2], double nAngle, double nShiftX, double nShiftY)
Compute shape of rotated image.
- `NppStatus nppiGetRotateBound` (`NppiRect` oSrcROI, double aBoundingBox[2][2], double nAngle, double nShiftX, double nShiftY)
Compute bounding-box of rotated image.

Rotate

- `NppStatus nppiRotate_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
8-bit unsigned image rotate.
- `NppStatus nppiRotate_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
3 channel 8-bit unsigned image rotate.
- `NppStatus nppiRotate_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
4 channel 8-bit unsigned image rotate.
- `NppStatus nppiRotate_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
4 channel 8-bit unsigned image rotate ignoring alpha channel.
- `NppStatus nppiRotate_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
16-bit unsigned image rotate.
- `NppStatus nppiRotate_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)
3 channel 16-bit unsigned image rotate.
- `NppStatus nppiRotate_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 16-bit unsigned image rotate.

- `NppStatus nppiRotate_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u *pDst`, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 16-bit unsigned image rotate ignoring alpha channel.

- `NppStatus nppiRotate_32f_C1R` (const `Npp32f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst`, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

32-bit float image rotate.

- `NppStatus nppiRotate_32f_C3R` (const `Npp32f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst`, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

3 channel 32-bit float image rotate.

- `NppStatus nppiRotate_32f_C4R` (const `Npp32f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst`, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 32-bit float image rotate.

- `NppStatus nppiRotate_32f_AC4R` (const `Npp32f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst`, int nDstStep, `NppiRect` oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 32-bit float image rotate ignoring alpha channel.

7.8.1 Detailed Description

Rotates an image around the origin (0,0) and then shifts it.

7.8.2 Rotate Error Codes

- `NPP_INTERPOLATION_ERROR` if eInterpolation has an illegal value.
- `NPP_RECTANGLE_ERROR` Indicates an error condition if width or height of the intersection of the oSrcROI and source image is less than or equal to 1.
- `NPP_WRONG_INTERSECTION_ROI_ERROR` indicates an error condition if srcROIrect has no intersection with the source image.
- `NPP_WRONG_INTERSECTION_QUAD_WARNING` indicates a warning that no operation is performed if the transformed source ROI does not intersect the destination ROI.

7.8.3 Function Documentation

7.8.3.1 `NppStatus nppiGetRotateBound` (`NppiRect oSrcROI`, `double aBoundingBox[2][2]`, `double nAngle`, `double nShiftX`, `double nShiftY`)

Compute bounding-box of rotated image.

Parameters:

- oSrcROI* Region-of-interest of the source image.
- aBoundingBox* Two 2D points representing the bounding-box of the rotated image. All four points from `nppiGetRotateQuad` are contained inside the axis-aligned rectangle spanned by the two points of this bounding box.
- nAngle* The rotation angle.
- nShiftX* Post-rotation shift in x-direction.
- nShiftY* Post-rotation shift in y-direction.

Returns:

[ROI Related Error Codes.](#)

7.8.3.2 `NppStatus nppiGetRotateQuad (NppiRect oSrcROI, double aQuad[4][2], double nAngle, double nShiftX, double nShiftY)`

Compute shape of rotated image.

Parameters:

- oSrcROI* Region-of-interest of the source image.
- aQuad* Array of 2D points. These points are the locations of the corners of the rotated ROI.
- nAngle* The rotation nAngle.
- nShiftX* Post-rotation shift in x-direction
- nShiftY* Post-rotation shift in y-direction

Returns:

[ROI Related Error Codes.](#)

7.8.3.3 `NppStatus nppiRotate_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

4 channel 16-bit unsigned image rotate ignoring alpha channel.

Parameters:

- pSrc* [Source-Image Pointer.](#)
- nSrcStep* [Source-Image Line Step.](#)
- oSrcSize* Size in pixels of the source image
- oSrcROI* Region of interest in the source image.
- pDst* [Destination-Image Pointer.](#)
- nDstStep* [Destination-Image Line Step.](#)
- oDstROI* Region of interest in the destination image.
- nAngle* The angle of rotation in degrees.
- nShiftX* Shift along horizontal axis

nShiftY Shift along vertical axis

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.4 `NppStatus nppiRotate_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

16-bit unsigned image rotate.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.

nShiftX Shift along horizontal axis

nShiftY Shift along vertical axis

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.5 `NppStatus nppiRotate_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

3 channel 16-bit unsigned image rotate.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.

nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.6 NppStatus nppiRotate_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 16-bit unsigned image rotate.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.7 NppStatus nppiRotate_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 32-bit float image rotate ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.8 `NppStatus nppiRotate_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

32-bit float image rotate.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.9 `NppStatus nppiRotate_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

3 channel 32-bit float image rotate.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).

oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.10 NppStatus nppiRotate_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 32-bit float image rotate.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.11 NppStatus nppiRotate_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)

4 channel 8-bit unsigned image rotate ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst [Destination-Image Pointer](#).

nDstStep Destination-Image Line Step.

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.

nShiftX Shift along horizontal axis

nShiftY Shift along vertical axis

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.12 `NppStatus nppiRotate_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

8-bit unsigned image rotate.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Region of interest in the destination image.

nAngle The angle of rotation in degrees.

nShiftX Shift along horizontal axis

nShiftY Shift along vertical axis

eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.13 `NppStatus nppiRotate_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

3 channel 8-bit unsigned image rotate.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSrcSize Size in pixels of the source image

oSrcROI Region of interest in the source image.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.8.3.14 `NppStatus nppiRotate_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, double nAngle, double nShiftX, double nShiftY, int eInterpolation)`

4 channel 8-bit unsigned image rotate.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSize Size in pixels of the source image
oSrcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Region of interest in the destination image.
nAngle The angle of rotation in degrees.
nShiftX Shift along horizontal axis
nShiftY Shift along vertical axis
eInterpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Rotate Error Codes](#)

7.9 Mirror

Mirror

Mirrors images horizontally, vertically and diagonally.

- `NppStatus nppiMirror_8u_C1R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
1 channel 8-bit unsigned image mirror.
- `NppStatus nppiMirror_8u_C1IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
1 channel 8-bit unsigned in place image mirror.
- `NppStatus nppiMirror_8u_C3R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
3 channel 8-bit unsigned image mirror.
- `NppStatus nppiMirror_8u_C3IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
3 channel 8-bit unsigned in place image mirror.
- `NppStatus nppiMirror_8u_C4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
4 channel 8-bit unsigned image mirror.
- `NppStatus nppiMirror_8u_C4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
4 channel 8-bit unsigned in place image mirror.
- `NppStatus nppiMirror_8u_AC4R` (const `Npp8u *pSrc`, int `nSrcStep`, `Npp8u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
4 channel 8-bit unsigned image mirror not affecting alpha.
- `NppStatus nppiMirror_8u_AC4IR` (`Npp8u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
4 channel 8-bit unsigned in place image mirror not affecting alpha.
- `NppStatus nppiMirror_16u_C1R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
1 channel 16-bit unsigned image mirror.
- `NppStatus nppiMirror_16u_C1IR` (`Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
1 channel 16-bit unsigned in place image mirror.
- `NppStatus nppiMirror_16u_C3R` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize` `oROI`, `NppiAxis` `flip`)
3 channel 16-bit unsigned image mirror.

- `NppStatus nppiMirror_16u_C3IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
3 channel 16-bit unsigned in place image mirror.
- `NppStatus nppiMirror_16u_C4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 16-bit unsigned image mirror.
- `NppStatus nppiMirror_16u_C4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 16-bit unsigned in place image mirror.
- `NppStatus nppiMirror_16u_AC4R` (`const Npp16u *pSrc`, `int nSrcStep`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 16-bit unsigned image mirror not affecting alpha.
- `NppStatus nppiMirror_16u_AC4IR` (`Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 16-bit unsigned in place image mirror not affecting alpha.
- `NppStatus nppiMirror_16s_C1R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
1 channel 16-bit signed image mirror.
- `NppStatus nppiMirror_16s_C1IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
1 channel 16-bit signed in place image mirror.
- `NppStatus nppiMirror_16s_C3R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
3 channel 16-bit signed image mirror.
- `NppStatus nppiMirror_16s_C3IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
3 channel 16-bit signed in place image mirror.
- `NppStatus nppiMirror_16s_C4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 16-bit signed image mirror.
- `NppStatus nppiMirror_16s_C4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 16-bit signed in place image mirror.
- `NppStatus nppiMirror_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 16-bit signed image mirror not affecting alpha.
- `NppStatus nppiMirror_16s_AC4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 16-bit signed in place image mirror not affecting alpha.

- `NppStatus nppiMirror_32s_C1R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
1 channel 32-bit image mirror.
- `NppStatus nppiMirror_32s_C1IR` (`Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
1 channel 32-bit signed in place image mirror.
- `NppStatus nppiMirror_32s_C3R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
3 channel 32-bit image mirror.
- `NppStatus nppiMirror_32s_C3IR` (`Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
3 channel 32-bit signed in place image mirror.
- `NppStatus nppiMirror_32s_C4R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 32-bit image mirror.
- `NppStatus nppiMirror_32s_C4IR` (`Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 32-bit signed in place image mirror.
- `NppStatus nppiMirror_32s_AC4R` (const `Npp32s *pSrc`, int `nSrcStep`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 32-bit image mirror not affecting alpha.
- `NppStatus nppiMirror_32s_AC4IR` (`Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
4 channel 32-bit signed in place image mirror not affecting alpha.
- `NppStatus nppiMirror_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
1 channel 32-bit float image mirror.
- `NppStatus nppiMirror_32f_C1IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
1 channel 32-bit float in place image mirror.
- `NppStatus nppiMirror_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oROI`, `NppiAxis flip`)
3 channel 32-bit float image mirror.
- `NppStatus nppiMirror_32f_C3IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)
3 channel 32-bit float in place image mirror.
- `NppStatus nppiMirror_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 32-bit float image mirror.

- `NppStatus nppiMirror_32f_C4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 32-bit float in place image mirror.

- `NppStatus nppiMirror_32f_AC4R` (`const Npp32f *pSrc`, `int nSrcStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 32-bit float image mirror not affecting alpha.

- `NppStatus nppiMirror_32f_AC4IR` (`Npp32f *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 32-bit float in place image mirror not affecting alpha.

7.9.1 Detailed Description

7.9.2 Mirror Error Codes

- `NPP_MIRROR_FLIP_ERR` if flip has an illegal value.

7.9.3 Function Documentation

7.9.3.1 `NppStatus nppiMirror_16s_AC4IR` (`Npp16s *pSrcDst`, `int nSrcDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 16-bit signed in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.2 `NppStatus nppiMirror_16s_AC4R` (`const Npp16s *pSrc`, `int nSrcStep`, `Npp16s *pDst`, `int nDstStep`, `NppiSize oROI`, `NppiAxis flip`)

4 channel 16-bit signed image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.3 NppStatus nppiMirror_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

1 channel 16-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.4 NppStatus nppiMirror_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

1 channel 16-bit signed image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.5 NppStatus nppiMirror_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

3 channel 16-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.6 NppStatus nppiMirror_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 16-bit signed image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.7 NppStatus nppiMirror_16s_C4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.8 NppStatus nppiMirror_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit signed image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Mirror Error Codes

7.9.3.9 NppStatus nppiMirror_16u_AC4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit unsigned in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Mirror Error Codes

7.9.3.10 NppStatus nppiMirror_16u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit unsigned image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Mirror Error Codes

7.9.3.11 NppStatus nppiMirror_16u_C1IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

1 channel 16-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.12 NppStatus nppiMirror_16u_C1R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

1 channel 16-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.13 NppStatus nppiMirror_16u_C3IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

3 channel 16-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.14 NppStatus nppiMirror_16u_C3R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 16-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.15 NppStatus nppiMirror_16u_C4IR (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.16 NppStatus nppiMirror_16u_C4R (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 16-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.17 **NppStatus nppiMirror_32f_AC4IR** (**Npp32f * pSrcDst**, **int nSrcDstStep**, **NppiSize oROI**, **NppiAxis flip**)

4 channel 32-bit float in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.18 **NppStatus nppiMirror_32f_AC4R** (**const Npp32f * pSrc**, **int nSrcStep**, **Npp32f * pDst**, **int nDstStep**, **NppiSize oROI**, **NppiAxis flip**)

4 channel 32-bit float image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.19 **NppStatus nppiMirror_32f_C1IR** (**Npp32f * pSrcDst**, **int nSrcDstStep**, **NppiSize oROI**, **NppiAxis flip**)

1 channel 32-bit float in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.20 NppStatus nppiMirror_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

1 channel 32-bit float image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.21 NppStatus nppiMirror_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

3 channel 32-bit float in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.22 NppStatus nppiMirror_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 32-bit float image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.23 **NppStatus nppiMirror_32f_C4IR** (**Npp32f * pSrcDst**, **int nSrcDstStep**, **NppiSize oROI**, **NppiAxis flip**)

4 channel 32-bit float in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.24 **NppStatus nppiMirror_32f_C4R** (**const Npp32f * pSrc**, **int nSrcStep**, **Npp32f * pDst**, **int nDstStep**, **NppiSize oROI**, **NppiAxis flip**)

4 channel 32-bit float image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.25 **NppStatus nppiMirror_32s_AC4IR** (**Npp32s * pSrcDst**, **int nSrcDstStep**, **NppiSize oROI**, **NppiAxis flip**)

4 channel 32-bit signed in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.26 NppStatus nppiMirror_32s_AC4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 32-bit image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.27 NppStatus nppiMirror_32s_C1IR (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

1 channel 32-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.28 NppStatus nppiMirror_32s_C1R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

1 channel 32-bit image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.29 NppStatus nppiMirror_32s_C3IR (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

3 channel 32-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.30 NppStatus nppiMirror_32s_C3R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 32-bit image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.31 NppStatus nppiMirror_32s_C4IR (Npp32s * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 32-bit signed in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.32 NppStatus nppiMirror_32s_C4R (const Npp32s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 32-bit image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.33 NppStatus nppiMirror_8u_AC4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 8-bit unsigned in place image mirror not affecting alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.34 NppStatus nppiMirror_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 8-bit unsigned image mirror not affecting alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.35 `NppStatus nppiMirror_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)`

1 channel 8-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.36 `NppStatus nppiMirror_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)`

1 channel 8-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.37 `NppStatus nppiMirror_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)`

3 channel 8-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.38 NppStatus nppiMirror_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

3 channel 8-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.39 NppStatus nppiMirror_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oROI, NppiAxis flip)

4 channel 8-bit unsigned in place image mirror.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.9.3.40 NppStatus nppiMirror_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)

4 channel 8-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Mirror Error Codes](#)

7.10 Affine Transforms

Utility Functions

- `NppStatus nppiGetAffineTransform (NppiRect oSrcROI, const double aQuad[4][2], double aCoeffs[2][3])`
Computes affine transform coefficients based on source ROI and destination quadrilateral.
- `NppStatus nppiGetAffineQuad (NppiRect oSrcROI, double aQuad[4][2], const double aCoeffs[2][3])`
Compute shape of transformed image.
- `NppStatus nppiGetAffineBound (NppiRect oSrcROI, double aBound[2][2], const double aCoeffs[2][3])`
Compute bounding-box of transformed image.

Affine Transform

Transforms (warps) an image based on an affine transform.

The affine transform is given as a 2×3 matrix C . A pixel location (x, y) in the source image is mapped to the location (x', y') in the destination image. The destination image coordinates are computed as follows:

$$x' = c_{00} * x + c_{01} * y + c_{02} \quad y' = c_{10} * x + c_{11} * y + c_{12} \quad C = \begin{bmatrix} c_{00} & c_{01} & c_{02} \\ c_{10} & c_{11} & c_{12} \end{bmatrix}$$

Affine transforms can be understood as a linear transformation (traditional matrix multiplication) and a shift operation. The 2×2 matrix

$$L = \begin{bmatrix} c_{00} & c_{01} \\ c_{10} & c_{11} \end{bmatrix}$$

represents the linear transform portion of the affine transformation. The vector

$$v = \begin{pmatrix} c_{02} \\ c_{12} \end{pmatrix}$$

represents the post-transform shift, i.e. after the pixel location is transformed by L it is translated by v .

- `NppStatus nppiWarpAffine_8u_C1R (const Npp8u *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`
Single-channel 8-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_8u_C3R (const Npp8u *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`
Three-channel 8-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_8u_C4R (const Npp8u *pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u *pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`
Four-channel 8-bit unsigned affine warp.

- `NppStatus nppiWarpAffine_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 8-bit unsigned affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst[3]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel planar 8-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst[4]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel planar 8-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_C1R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Single-channel 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_C3R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_C4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 16-bit unsigned affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_16u_P3R` (const `Npp16u *pSrc[3]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst[3]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel planar 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_16u_P4R` (const `Npp16u *pSrc[4]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst[4]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel planar 16-bit unsigned affine warp.
- `NppStatus nppiWarpAffine_32s_C1R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Single-channel 32-bit signed affine warp.

- `NppStatus nppiWarpAffine_32s_C3R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel 32-bit signed affine warp.
- `NppStatus nppiWarpAffine_32s_C4R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 32-bit signed affine warp.
- `NppStatus nppiWarpAffine_32s_AC4R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 32-bit signed affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_32s_P3R` (const `Npp32s *pSrc[3]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst[3]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel planar 32-bit signed affine warp.
- `NppStatus nppiWarpAffine_32s_P4R` (const `Npp32s *pSrc[4]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32s *pDst[4]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel planar 32-bit signed affine warp.
- `NppStatus nppiWarpAffine_32f_C1R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Single-channel 32-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_32f_C3R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel 32-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_32f_C4R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 32-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_32f_AC4R` (const `Npp32f *pSrc`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Four-channel 32-bit floating-point affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize` `oSrcSize`, `int` `nSrcStep`, `NppiRect` `oSrcROI`, `Npp32f *pDst[3]`, `int` `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, `int` `eInterpolation`)

Three-channel planar 32-bit floating-point affine warp.

- `NppStatus nppiWarpAffine_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst[4]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel planar 32-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_C1R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Single-channel 64-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_C3R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Three-channel 64-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_C4R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 64-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_AC4R` (const `Npp64f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 64-bit floating-point affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffine_64f_P3R` (const `Npp64f *aSrc[3]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *aDst[3]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Three-channel planar 64-bit floating-point affine warp.
- `NppStatus nppiWarpAffine_64f_P4R` (const `Npp64f *aSrc[4]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp64f *aDst[4]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel planar 64-bit floating-point affine warp.

Backwards Affine Transform

Transforms (warps) an image based on an affine transform.

The affine transform is given as a 2×3 matrix C . A pixel location (x, y) in the source image is mapped to the location (x', y') in the destination image. The destination image coordinates fulfill the following properties:

$$x = c_{00} * x' + c_{01} * y' + c_{02} \quad y = c_{10} * x' + c_{11} * y' + c_{12} \quad C = \begin{bmatrix} c_{00} & c_{01} & c_{02} \\ c_{10} & c_{11} & c_{12} \end{bmatrix}$$

In other words, given matrix C the source image's shape is transformed to the destination image using the inverse matrix C^{-1} :

$$M = C^{-1} = \begin{bmatrix} m_{00} & m_{01} & m_{02} \\ m_{10} & m_{11} & m_{12} \end{bmatrix} \quad x' = m_{00} * x + m_{01} * y + m_{02} \quad y' = m_{10} * x + m_{11} * y + m_{12}$$

- `NppStatus nppiWarpAffineBack_8u_C1R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Single-channel 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_8u_C3R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Three-channel 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_8u_C4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer backwards affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffineBack_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Three-channel planar 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp8u *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel planar 8-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_C1R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Single-channel 16-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_C3R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Three-channel 16-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_C4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aCoeffs[2][3]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer backwards affine warp, ignoring alpha channel.

- `NppStatus nppiWarpAffineBack_16u_P3R` (const `Npp16u` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel planar 16-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_16u_P4R` (const `Npp16u` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp16u` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel planar 16-bit unsigned integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_32s_C1R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 32-bit signed integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_32s_C3R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel 32-bit signed integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 32-bit signed integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 32-bit signed integer backwards affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffineBack_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel planar 32-bit signed integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel planar 32-bit signed integer backwards affine warp.
- `NppStatus nppiWarpAffineBack_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 32-bit floating-point backwards affine warp.
- `NppStatus nppiWarpAffineBack_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel 32-bit floating-point backwards affine warp.

- `NppStatus nppiWarpAffineBack_32f_C4R` (const `Npp32f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 32-bit floating-point backwards affine warp.
- `NppStatus nppiWarpAffineBack_32f_AC4R` (const `Npp32f *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel 32-bit floating-point backwards affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffineBack_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst[3]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Three-channel planar 32-bit floating-point backwards affine warp.
- `NppStatus nppiWarpAffineBack_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f *pDst[4]`, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[2][3], int eInterpolation)
Four-channel planar 32-bit floating-point backwards affine warp.

Quad-Based Affine Transform

Transforms (warps) an image based on an affine transform.

The affine transform is computed such that it maps a quadrilateral in source image space to a quadrilateral in destination image space.

An affine transform is fully determined by the mapping of 3 discrete points. The following primitives compute an affine transformation matrix that maps the first three corners of the source quad are mapped to the first three vertices of the destination image quad. If the fourth vertices do not match the transform, an `NPP_AFFINE_QUAD_INCORRECT_WARNING` is returned by the primitive.

- `NppStatus nppiWarpAffineQuad_8u_C1R` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Single-channel 32-bit floating-point quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_8u_C3R` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel 8-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_8u_C4R` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 8-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u *pDst`, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 8-bit unsigned integer quad-based affine warp, ignoring alpha channel.

- `NppStatus nppiWarpAffineQuad_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel planar 8-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel planar 8-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_16u_C1R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Single-channel 16-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_16u_C3R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel 16-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_16u_C4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer quad-based affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffineQuad_16u_P3R` (const `Npp16u *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel planar 16-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_16u_P4R` (const `Npp16u *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel planar 16-bit unsigned integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32s_C1R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp32s *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Single-channel 32-bit signed integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32s_C3R` (const `Npp32s *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp32s *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel 32-bit signed integer quad-based affine warp.

- `NppStatus nppiWarpAffineQuad_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit signed integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit signed integer quad-based affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffineQuad_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel planar 32-bit signed integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel planar 32-bit signed integer quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Single-channel 32-bit floating-point quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel 32-bit floating-point quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit floating-point quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit floating-point quad-based affine warp, ignoring alpha channel.
- `NppStatus nppiWarpAffineQuad_32f_P3R` (const `Npp32f` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel planar 32-bit floating-point quad-based affine warp.
- `NppStatus nppiWarpAffineQuad_32f_P4R` (const `Npp32f` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel planar 32-bit floating-point quad-based affine warp.

7.10.1 Detailed Description

7.10.2 Affine Transform Error Codes

- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1
- `NPP_WRONG_INTERSECTION_ROI_ERROR` Indicates an error condition if `oSrcROI` has no intersection with the source image
- `NPP_INTERPOLATION_ERROR` Indicates an error condition if interpolation has an illegal value
- `NPP_COEFF_ERROR` Indicates an error condition if coefficient values are invalid
- `NPP_WRONG_INTERSECTION_QUAD_WARNING` Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI

7.10.3 Function Documentation

7.10.3.1 `NppStatus nppiGetAffineBound (NppiRect oSrcROI, double aBound[2][2], const double aCoeffs[2][3])`

Compute bounding-box of transformed image.

The method effectively computes the bounding box (axis aligned rectangle) of the transformed source ROI (see [nppiGetAffineQuad\(\)](#)).

Parameters:

- oSrcROI* The source ROI.
- aBound* The resulting bounding box.
- aCoeffs* The affine transform coefficients.

Returns:

Error codes:

- `NPP_SIZE_ERROR` Indicates an error condition if any image dimension has zero or negative value
- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1
- `NPP_COEFF_ERROR` Indicates an error condition if coefficient values are invalid

7.10.3.2 `NppStatus nppiGetAffineQuad (NppiRect oSrcROI, double aQuad[4][2], const double aCoeffs[2][3])`

Compute shape of transformed image.

This method computes the quadrilateral in the destination image that the source ROI is transformed into by the affine transformation expressed by the coefficients array (`aCoeffs`).

Parameters:

- oSrcROI* The source ROI.

aQuad The resulting destination quadrangle.

aCoeffs The affine transform coefficients.

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *oSrcROI* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.10.3.3 NppStatus nppiGetAffineTransform (NppiRect *oSrcROI*, const double *aQuad*[4][2], double *aCoeffs*[2][3])

Computes affine transform coefficients based on source ROI and destination quadrilateral.

The function computes the coefficients of an affine transformation that maps the given source ROI (axis aligned rectangle with integer coordinates) to a quadrilateral in the destination image.

An affine transform in 2D is fully determined by the mapping of just three vertices. This function's API allows for passing a complete quadrilateral effectively making the problem overdetermined. What this means in practice is, that for certain quadrilaterals it is not possible to find an affine transform that would map all four corners of the source ROI to the four vertices of that quadrilateral.

The function circumvents this problem by only looking at the first three vertices of the destination image quadrilateral to determine the affine transformation's coefficients. If the destination quadrilateral is indeed one that cannot be mapped using an affine transformation the function informs the user of this situation by returning a [NPP_AFFINE_QUAD_INCORRECT_WARNING](#).

Parameters:

oSrcROI The source ROI. This rectangle needs to be at least one pixel wide and high. If either width or height are less than one an [NPP_RECT_ERROR](#) is returned.

aQuad The destination quadrilateral.

aCoeffs The resulting affine transform coefficients.

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *oSrcROI* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_AFFINE_QUAD_INCORRECT_WARNING](#) Indicates a warning when quad does not conform to the transform properties. Fourth vertex is ignored, internally computed coordinates are used instead

7.10.3.4 NppStatus nppiWarpAffine_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 16-bit unsigned affine warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.5 NppStatus nppiWarpAffine_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 16-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.6 NppStatus nppiWarpAffine_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel 16-bit unsigned affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.7 NppStatus nppiWarpAffine_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 16-bit unsigned affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.8 `NppStatus nppiWarpAffine_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 16-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.9 `NppStatus nppiWarpAffine_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 16-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.10 NppStatus nppiWarpAffine_32f_AC4R (const Npp32f * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32f * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Four-channel 32-bit floating-point affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.11 NppStatus nppiWarpAffine_32f_C1R (const Npp32f * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32f * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Single-channel 32-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.12 `NppStatus nppiWarpAffine_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 32-bit floating-point affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.13 `NppStatus nppiWarpAffine_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit floating-point affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.14 `NppStatus nppiWarpAffine_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 32-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.15 `NppStatus nppiWarpAffine_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 32-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.16 NppStatus nppiWarpAffine_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 32-bit signed affine warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.17 NppStatus nppiWarpAffine_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 32-bit signed affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.18 NppStatus nppiWarpAffine_32s_C3R (*const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation*)

Three-channel 32-bit signed affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.19 NppStatus nppiWarpAffine_32s_C4R (*const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation*)

Four-channel 32-bit signed affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.20 `NppStatus nppiWarpAffine_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 32-bit signed affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.21 `NppStatus nppiWarpAffine_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 32-bit signed affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.22 NppStatus nppiWarpAffine_64f_AC4R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 64-bit floating-point affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.23 NppStatus nppiWarpAffine_64f_C1R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 64-bit floating-point affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.24 `NppStatus nppiWarpAffine_64f_C3R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 64-bit floating-point affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.25 `NppStatus nppiWarpAffine_64f_C4R (const Npp64f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 64-bit floating-point affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.26 `NppStatus nppiWarpAffine_64f_P3R (const Npp64f * aSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * aDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 64-bit floating-point affine warp.

Parameters:

aSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.27 `NppStatus nppiWarpAffine_64f_P4R (const Npp64f * aSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp64f * aDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 64-bit floating-point affine warp.

Parameters:

aSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.28 `NppStatus nppiWarpAffine_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 8-bit unsigned affine warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.29 `NppStatus nppiWarpAffine_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 8-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.30 `NppStatus nppiWarpAffine_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 8-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.31 `NppStatus nppiWarpAffine_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 8-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.32 `NppStatus nppiWarpAffine_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 8-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.33 `NppStatus nppiWarpAffine_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 8-bit unsigned affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.34 NppStatus nppiWarpAffineBack_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 16-bit unsigned integer backwards affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.35 NppStatus nppiWarpAffineBack_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Single-channel 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.36 `NppStatus nppiWarpAffineBack_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.37 `NppStatus nppiWarpAffineBack_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.38 NppStatus nppiWarpAffineBack_16u_P3R (const Npp16u * *pSrc*[3], NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16u * *pDst*[3], int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Three-channel planar 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.39 NppStatus nppiWarpAffineBack_16u_P4R (const Npp16u * *pSrc*[4], NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp16u * *pDst*[4], int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Four-channel planar 16-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.40 `NppStatus nppiWarpAffineBack_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit floating-point backwards affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.41 `NppStatus nppiWarpAffineBack_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 32-bit floating-point backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.42 NppStatus nppiWarpAffineBack_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Three-channel 32-bit floating-point backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.43 NppStatus nppiWarpAffineBack_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)

Four-channel 32-bit floating-point backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.44 `NppStatus nppiWarpAffineBack_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 32-bit floating-point backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.45 `NppStatus nppiWarpAffineBack_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 32-bit floating-point backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.46 NppStatus nppiWarpAffineBack_32s_AC4R (const Npp32s * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32s * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Four-channel 32-bit signed integer backwards affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.47 NppStatus nppiWarpAffineBack_32s_C1R (const Npp32s * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32s * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Single-channel 32-bit signed integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.48 `NppStatus nppiWarpAffineBack_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel 32-bit signed integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.49 `NppStatus nppiWarpAffineBack_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 32-bit signed integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.50 `NppStatus nppiWarpAffineBack_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 32-bit signed integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.51 `NppStatus nppiWarpAffineBack_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 32-bit signed integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.52 `NppStatus nppiWarpAffineBack_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel 8-bit unsigned integer backwards affine warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.53 `NppStatus nppiWarpAffineBack_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Single-channel 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.54 NppStatus nppiWarpAffineBack_8u_C3R (const Npp8u * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp8u * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Three-channel 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.55 NppStatus nppiWarpAffineBack_8u_C4R (const Npp8u * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp8u * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[2][3], int *eInterpolation*)

Four-channel 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.56 `NppStatus nppiWarpAffineBack_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Three-channel planar 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.57 `NppStatus nppiWarpAffineBack_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[2][3], int eInterpolation)`

Four-channel planar 8-bit unsigned integer backwards affine warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Affine transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.58 `NppStatus nppiWarpAffineQuad_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 16-bit unsigned integer quad-based affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.59 `NppStatus nppiWarpAffineQuad_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.60 `NppStatus nppiWarpAffineQuad_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.61 `NppStatus nppiWarpAffineQuad_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.62 `NppStatus nppiWarpAffineQuad_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.63 `NppStatus nppiWarpAffineQuad_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 16-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.64 `NppStatus nppiWarpAffineQuad_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit floating-point quad-based affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.65 `NppStatus nppiWarpAffineQuad_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.66 `NppStatus nppiWarpAffineQuad_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.67 `NppStatus nppiWarpAffineQuad_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.68 `NppStatus nppiWarpAffineQuad_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.69 `NppStatus nppiWarpAffineQuad_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.70 `NppStatus nppiWarpAffineQuad_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit signed integer quad-based affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.71 `NppStatus nppiWarpAffineQuad_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.72 `NppStatus nppiWarpAffineQuad_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.73 `NppStatus nppiWarpAffineQuad_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.74 `NppStatus nppiWarpAffineQuad_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.75 `NppStatus nppiWarpAffineQuad_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 32-bit signed integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.76 `NppStatus nppiWarpAffineQuad_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 8-bit unsigned integer quad-based affine warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.77 `NppStatus nppiWarpAffineQuad_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit floating-point quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.78 `NppStatus nppiWarpAffineQuad_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 8-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.79 `NppStatus nppiWarpAffineQuad_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 8-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.80 `NppStatus nppiWarpAffineQuad_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 8-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.10.3.81 `NppStatus nppiWarpAffineQuad_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 8-bit unsigned integer quad-based affine warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Affine Transform Error Codes](#)

7.11 Perspective Transform

Utility Functions

- `NppStatus nppiGetPerspectiveTransform` (`NppiRect` oSrcROI, const double quad[4][2], double aCoeffs[3][3])
Calculates perspective transform coefficients given source rectangular ROI and its destination quadrangle projection.
- `NppStatus nppiGetPerspectiveQuad` (`NppiRect` oSrcROI, double quad[4][2], const double aCoeffs[3][3])
Calculates perspective transform projection of given source rectangular ROI.
- `NppStatus nppiGetPerspectiveBound` (`NppiRect` oSrcROI, double bound[2][2], const double aCoeffs[3][3])
Calculates bounding box of the perspective transform projection of the given source rectangular ROI.

Perspective Transform

Transforms (warps) an image based on a perspective transform.

The perspective transform is given as a 3×3 matrix C . A pixel location (x, y) in the source image is mapped to the location (x', y') in the destination image. The destination image coordinates are computed as follows:

$$x' = \frac{c_{00} * x + c_{01} * y + c_{02}}{c_{20} * x + c_{21} * y + c_{22}} \quad y' = \frac{c_{10} * x + c_{11} * y + c_{12}}{c_{20} * x + c_{21} * y + c_{22}}$$

$$C = \begin{bmatrix} c_{00} & c_{01} & c_{02} \\ c_{10} & c_{11} & c_{12} \\ c_{20} & c_{21} & c_{22} \end{bmatrix}$$

- `NppStatus nppiWarpPerspective_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Single-channel 8-bit unsigned integer perspective warp.
- `NppStatus nppiWarpPerspective_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel 8-bit unsigned integer perspective warp.
- `NppStatus nppiWarpPerspective_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 8-bit unsigned integer perspective warp.
- `NppStatus nppiWarpPerspective_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 8-bit unsigned integer perspective warp, ignoring alpha channel.

- **NppStatus** **nppiWarpPerspective_8u_P3R** (const **Npp8u** *pSrc[3], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst[3], int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 8-bit unsigned integer perspective warp.
- **NppStatus** **nppiWarpPerspective_8u_P4R** (const **Npp8u** *pSrc[4], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp8u** *pDst[4], int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 8-bit unsigned integer perspective warp.
- **NppStatus** **nppiWarpPerspective_16u_C1R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Single-channel 16-bit unsigned integer perspective warp.
- **NppStatus** **nppiWarpPerspective_16u_C3R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel 16-bit unsigned integer perspective warp.
- **NppStatus** **nppiWarpPerspective_16u_C4R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 16-bit unsigned integer perspective warp.
- **NppStatus** **nppiWarpPerspective_16u_AC4R** (const **Npp16u** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 16-bit unsigned integer perspective warp, ignoring alpha channel.
- **NppStatus** **nppiWarpPerspective_16u_P3R** (const **Npp16u** *pSrc[3], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst[3], int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 16-bit unsigned integer perspective warp.
- **NppStatus** **nppiWarpPerspective_16u_P4R** (const **Npp16u** *pSrc[4], **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp16u** *pDst[4], int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 16-bit unsigned integer perspective warp.
- **NppStatus** **nppiWarpPerspective_32s_C1R** (const **Npp32s** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp32s** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Single-channel 32-bit signed integer perspective warp.
- **NppStatus** **nppiWarpPerspective_32s_C3R** (const **Npp32s** *pSrc, **NppiSize** oSrcSize, int nSrcStep, **NppiRect** oSrcROI, **Npp32s** *pDst, int nDstStep, **NppiRect** oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel 32-bit signed integer perspective warp.

- `NppStatus nppiWarpPerspective_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit signed integer perspective warp.
- `NppStatus nppiWarpPerspective_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit signed integer perspective warp, ignoring alpha channel.
- `NppStatus nppiWarpPerspective_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 32-bit signed integer perspective warp.
- `NppStatus nppiWarpPerspective_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 32-bit signed integer perspective warp.
- `NppStatus nppiWarpPerspective_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Single-channel 32-bit floating-point perspective warp.
- `NppStatus nppiWarpPerspective_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel 32-bit floating-point perspective warp.
- `NppStatus nppiWarpPerspective_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit floating-point perspective warp.
- `NppStatus nppiWarpPerspective_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit floating-point perspective warp, ignoring alpha channel.
- `NppStatus nppiWarpPerspective_32f_P3R` (const `Npp32f` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 32-bit floating-point perspective warp.
- `NppStatus nppiWarpPerspective_32f_P4R` (const `Npp32f` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 32-bit floating-point perspective warp.

Backwards Perspective Transform

Transforms (warps) an image based on a perspective transform.

The perspective transform is given as a 3×3 matrix C . A pixel location (x, y) in the source image is mapped to the location (x', y') in the destination image. The destination image coordinates fulfill the following properties:

$$x = \frac{c_{00} * x' + c_{01} * y' + c_{02}}{c_{20} * x' + c_{21} * y' + c_{22}} \quad y = \frac{c_{10} * x' + c_{11} * y' + c_{12}}{c_{20} * x' + c_{21} * y' + c_{22}}$$

$$C = \begin{bmatrix} c_{00} & c_{01} & c_{02} \\ c_{10} & c_{11} & c_{12} \\ c_{20} & c_{21} & c_{22} \end{bmatrix}$$

In other words, given matrix C the source image's shape is transformed to the destination image using the inverse matrix C^{-1} :

$$M = C^{-1} = \begin{bmatrix} m_{00} & m_{01} & m_{02} \\ m_{10} & m_{11} & m_{12} \\ m_{20} & m_{21} & m_{22} \end{bmatrix} \quad x' = \frac{c_{00} * x + c_{01} * y + c_{02}}{c_{20} * x + c_{21} * y + c_{22}} \quad y' = \frac{c_{10} * x + c_{11} * y + c_{12}}{c_{20} * x + c_{21} * y + c_{22}}$$

- `NppStatus nppiWarpPerspectiveBack_8u_C1R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Single-channel 8-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_8u_C3R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Three-channel 8-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_8u_C4R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer backwards perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveBack_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Three-channel planar 8-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp8u *pDst[4]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel planar 8-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_C1R` (const `Npp16u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Single-channel 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_C3R` (const `Npp16u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Three-channel 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_C4R` (const `Npp16u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer backwards perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveBack_16u_P3R` (const `Npp16u *pSrc[3]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst[3]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel planar 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_16u_P4R` (const `Npp16u *pSrc[4]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp16u *pDst[4]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel planar 16-bit unsigned integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_C1R` (const `Npp32s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Single-channel 32-bit signed integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_C3R` (const `Npp32s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Three-channel 32-bit signed integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_C4R` (const `Npp32s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 32-bit signed integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_AC4R` (const `Npp32s *pSrc`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Four-channel 32-bit signed integer backwards perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveBack_32s_P3R` (const `Npp32s *pSrc[3]`, `NppiSize oSrcSize`, int `nSrcStep`, `NppiRect oSrcROI`, `Npp32s *pDst[3]`, int `nDstStep`, `NppiRect oDstROI`, const double `aCoeffs[3][3]`, int `eInterpolation`)

Three-channel planar 32-bit signed integer backwards perspective warp.

- `NppStatus nppiWarpPerspectiveBack_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32s` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 32-bit signed integer backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Single-channel 32-bit floating-point backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel 32-bit floating-point backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit floating-point backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel 32-bit floating-point backwards perspective warp, ignoring alpha channel.
- `NppStatus nppiWarpPerspectiveBack_32f_P3R` (const `Npp32f` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Three-channel planar 32-bit floating-point backwards perspective warp.
- `NppStatus nppiWarpPerspectiveBack_32f_P4R` (const `Npp32f` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, `Npp32f` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aCoeffs[3][3], int eInterpolation)
Four-channel planar 32-bit floating-point backwards perspective warp.

Quad-Based Perspective Transform

Transforms (warps) an image based on an perspective transform.

The perspective transform is computed such that it maps a quadrilateral in source image space to a quadrilateral in destination image space.

- `NppStatus nppiWarpPerspectiveQuad_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Single-channel 8-bit unsigned integer quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel 8-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_8u_C4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_8u_AC4R` (const `Npp8u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 8-bit unsigned integer quad-based perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveQuad_8u_P3R` (const `Npp8u *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel planar 8-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_8u_P4R` (const `Npp8u *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp8u *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel planar 8-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_C1R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Single-channel 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_C3R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_C4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_AC4R` (const `Npp16u *pSrc`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel 16-bit unsigned integer quad-based perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveQuad_16u_P3R` (const `Npp16u *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel planar 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_16u_P4R` (const `Npp16u *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp16u *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel planar 16-bit unsigned integer quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_32s_C1R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Single-channel 32-bit signed integer quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_32s_C3R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel 32-bit signed integer quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit signed integer quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit signed integer quad-based perspective warp, ignoring alpha channel.
- `NppStatus nppiWarpPerspectiveQuad_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst[3], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel planar 32-bit signed integer quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32s` *pDst[4], int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel planar 32-bit signed integer quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Single-channel 32-bit floating-point quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Three-channel 32-bit floating-point quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit floating-point quad-based perspective warp.
- `NppStatus nppiWarpPerspectiveQuad_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` oSrcSize, int nSrcStep, `NppiRect` oSrcROI, const double aSrcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` oDstROI, const double aDstQuad[4][2], int eInterpolation)
Four-channel 32-bit floating-point quad-based perspective warp, ignoring alpha channel.

- `NppStatus nppiWarpPerspectiveQuad_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp32f *pDst[3]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Three-channel planar 32-bit floating-point quad-based perspective warp.

- `NppStatus nppiWarpPerspectiveQuad_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize` `oSrcSize`, int `nSrcStep`, `NppiRect` `oSrcROI`, const double `aSrcQuad[4][2]`, `Npp32f *pDst[4]`, int `nDstStep`, `NppiRect` `oDstROI`, const double `aDstQuad[4][2]`, int `eInterpolation`)

Four-channel planar 32-bit floating-point quad-based perspective warp.

7.11.1 Detailed Description

7.11.2 Perspective Transform Error Codes

- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1
- `NPP_WRONG_INTERSECTION_ROI_ERROR` Indicates an error condition if `oSrcROI` has no intersection with the source image
- `NPP_INTERPOLATION_ERROR` Indicates an error condition if interpolation has an illegal value
- `NPP_COEFF_ERROR` Indicates an error condition if coefficient values are invalid
- `NPP_WRONG_INTERSECTION_QUAD_WARNING` Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI

7.11.3 Function Documentation

7.11.3.1 `NppStatus nppiGetPerspectiveBound` (`NppiRect oSrcROI`, double `bound[2][2]`, const double `aCoeffs[3][3]`)

Calculates bounding box of the perspective transform projection of the given source rectangular ROI.

Parameters:

oSrcROI Source ROI

bound Bounding box of the transformed source ROI

aCoeffs Perspective transform coefficients

Returns:

Error codes:

- `NPP_SIZE_ERROR` Indicates an error condition if any image dimension has zero or negative value
- `NPP_RECT_ERROR` Indicates an error condition if width or height of the intersection of the `oSrcROI` and source image is less than or equal to 1
- `NPP_COEFF_ERROR` Indicates an error condition if coefficient values are invalid

7.11.3.2 NppStatus nppiGetPerspectiveQuad (NppiRect oSrcROI, double quad[4][2], const double aCoeffs[3][3])

Calculates perspective transform projection of given source rectangular ROI.

Parameters:

oSrcROI Source ROI
quad Destination quadrangle
aCoeffs Perspective transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *oSrcROI* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.11.3.3 NppStatus nppiGetPerspectiveTransform (NppiRect oSrcROI, const double quad[4][2], double aCoeffs[3][3])

Calculates perspective transform coefficients given source rectangular ROI and its destination quadrangle projection.

Parameters:

oSrcROI Source ROI
quad Destination quadrangle
aCoeffs Perspective transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *oSrcROI* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.11.3.4 NppStatus nppiWarpPerspective_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel 16-bit unsigned integer perspective warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels
nSrcStep [Source-Image Line Step](#).
oSrcROI Source ROI
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.5 `NppStatus nppiWarpPerspective_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 16-bit unsigned integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).
oSrcSize Size of source image in pixels
nSrcStep [Source-Image Line Step](#).
oSrcROI Source ROI
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.6 `NppStatus nppiWarpPerspective_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 16-bit unsigned integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).
oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.7 `NppStatus nppiWarpPerspective_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 16-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.8 `NppStatus nppiWarpPerspective_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 16-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Perspective Transform Error Codes

7.11.3.9 `NppStatus nppiWarpPerspective_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 16-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.
oSrcSize Size of source image in pixels
nSrcStep Source-Image Line Step.
oSrcROI Source ROI
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oDstROI Destination ROI
aCoeffs Perspective transform coefficients
eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

Image Data Related Error Codes, ROI Related Error Codes, Perspective Transform Error Codes

7.11.3.10 `NppStatus nppiWarpPerspective_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit floating-point perspective warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.
oSrcSize Size of source image in pixels
nSrcStep Source-Image Line Step.
oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.11 `NppStatus nppiWarpPerspective_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 32-bit floating-point perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.12 `NppStatus nppiWarpPerspective_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 32-bit floating-point perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.13 `NppStatus nppiWarpPerspective_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit floating-point perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.14 `NppStatus nppiWarpPerspective_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 32-bit floating-point perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.15 NppStatus nppiWarpPerspective_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel planar 32-bit floating-point perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.16 NppStatus nppiWarpPerspective_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel 32-bit signed integer perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.17 `NppStatus nppiWarpPerspective_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.18 `NppStatus nppiWarpPerspective_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.19 `NppStatus nppiWarpPerspective_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.20 `NppStatus nppiWarpPerspective_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.21 NppStatus nppiWarpPerspective_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel planar 32-bit signed integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.22 NppStatus nppiWarpPerspective_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel 8-bit unsigned integer perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.23 `NppStatus nppiWarpPerspective_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 8-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.24 `NppStatus nppiWarpPerspective_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 8-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.25 NppStatus nppiWarpPerspective_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel 8-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.26 NppStatus nppiWarpPerspective_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Three-channel planar 8-bit unsigned integer perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.27 `NppStatus nppiWarpPerspective_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 8-bit unsigned integer perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.28 `NppStatus nppiWarpPerspectiveBack_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 16-bit unsigned integer backwards perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.29 NppStatus nppiWarpPerspectiveBack_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Single-channel 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.30 NppStatus nppiWarpPerspectiveBack_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Three-channel 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.31 `NppStatus nppiWarpPerspectiveBack_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.32 `NppStatus nppiWarpPerspectiveBack_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.33 NppStatus nppiWarpPerspectiveBack_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel planar 16-bit unsigned integer backwards perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.34 NppStatus nppiWarpPerspectiveBack_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel 32-bit floating-point backwards perspective warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.335 NppStatus nppiWarpPerspectiveBack_32f_C1R (const Npp32f * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32f * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[3][3], int *eInterpolation*)

Single-channel 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.336 NppStatus nppiWarpPerspectiveBack_32f_C3R (const Npp32f * *pSrc*, NppiSize *oSrcSize*, int *nSrcStep*, NppiRect *oSrcROI*, Npp32f * *pDst*, int *nDstStep*, NppiRect *oDstROI*, const double *aCoeffs*[3][3], int *eInterpolation*)

Three-channel 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.37 `NppStatus nppiWarpPerspectiveBack_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.38 `NppStatus nppiWarpPerspectiveBack_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 32-bit floating-point backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.39 `NppStatus nppiWarpPerspectiveBack_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 32-bit floating-point backwards perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.40 `NppStatus nppiWarpPerspectiveBack_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 32-bit signed integer backwards perspective warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.41 NppStatus nppiWarpPerspectiveBack_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Single-channel 32-bit signed integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.42 NppStatus nppiWarpPerspectiveBack_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Three-channel 32-bit signed integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.43 NppStatus nppiWarpPerspectiveBack_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Four-channel 32-bit signed integer backwards perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.44 NppStatus nppiWarpPerspectiveBack_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)

Three-channel planar 32-bit signed integer backwards perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.45 `NppStatus nppiWarpPerspectiveBack_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 32-bit signed integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.46 `NppStatus nppiWarpPerspectiveBack_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 8-bit unsigned integer backwards perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.47 `NppStatus nppiWarpPerspectiveBack_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Single-channel 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.48 `NppStatus nppiWarpPerspectiveBack_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.49 `NppStatus nppiWarpPerspectiveBack_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.50 `NppStatus nppiWarpPerspectiveBack_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Three-channel planar 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.51 `NppStatus nppiWarpPerspectiveBack_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aCoeffs[3][3], int eInterpolation)`

Four-channel planar 8-bit unsigned integer backwards perspective warp.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aCoeffs Perspective transform coefficients

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.52 `NppStatus nppiWarpPerspectiveQuad_16u_AC4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 16-bit unsigned integer quad-based perspective warp, ignoring alpha channel.

Parameters:

pSrc Source-Image Pointer.

oSrcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

oSrcROI Source ROI

aSrcQuad Source quad.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.53 NppStatus nppiWarpPerspectiveQuad_16u_C1R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)

Single-channel 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.54 NppStatus nppiWarpPerspectiveQuad_16u_C3R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)

Three-channel 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.55 `NppStatus nppiWarpPerspectiveQuad_16u_C4R (const Npp16u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.56 `NppStatus nppiWarpPerspectiveQuad_16u_P3R (const Npp16u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.57 `NppStatus nppiWarpPerspectiveQuad_16u_P4R (const Npp16u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp16u * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 16-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.58 `NppStatus nppiWarpPerspectiveQuad_32f_AC4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit floating-point quad-based perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.59 `NppStatus nppiWarpPerspectiveQuad_32f_C1R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.60 `NppStatus nppiWarpPerspectiveQuad_32f_C3R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.61 `NppStatus nppiWarpPerspectiveQuad_32f_C4R (const Npp32f * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.62 `NppStatus nppiWarpPerspectiveQuad_32f_P3R (const Npp32f * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.63 `NppStatus nppiWarpPerspectiveQuad_32f_P4R (const Npp32f * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32f * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 32-bit floating-point quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.64 `NppStatus nppiWarpPerspectiveQuad_32s_AC4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit signed integer quad-based perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.65 `NppStatus nppiWarpPerspectiveQuad_32s_C1R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.66 `NppStatus nppiWarpPerspectiveQuad_32s_C3R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.67 `NppStatus nppiWarpPerspectiveQuad_32s_C4R (const Npp32s * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.68 `NppStatus nppiWarpPerspectiveQuad_32s_P3R (const Npp32s * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.69 `NppStatus nppiWarpPerspectiveQuad_32s_P4R (const Npp32s * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp32s * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 32-bit signed integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.70 `NppStatus nppiWarpPerspectiveQuad_8u_AC4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 8-bit unsigned integer quad-based perspective warp, ignoring alpha channel.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.71 `NppStatus nppiWarpPerspectiveQuad_8u_C1R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Single-channel 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.72 `NppStatus nppiWarpPerspectiveQuad_8u_C3R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.73 `NppStatus nppiWarpPerspectiveQuad_8u_C4R (const Npp8u * pSrc, NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.74 `NppStatus nppiWarpPerspectiveQuad_8u_P3R (const Npp8u * pSrc[3], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst[3], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Three-channel planar 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

7.11.3.75 `NppStatus nppiWarpPerspectiveQuad_8u_P4R (const Npp8u * pSrc[4], NppiSize oSrcSize, int nSrcStep, NppiRect oSrcROI, const double aSrcQuad[4][2], Npp8u * pDst[4], int nDstStep, NppiRect oDstROI, const double aDstQuad[4][2], int eInterpolation)`

Four-channel planar 8-bit unsigned integer quad-based perspective warp.

Parameters:

pSrc [Source-Image Pointer](#).

oSrcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

oSrcROI Source ROI

aSrcQuad Source quad.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstROI Destination ROI

aDstQuad Destination quad.

eInterpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), [Perspective Transform Error Codes](#)

Chapter 8

Data Structure Documentation

8.1 NPP_ALIGN_16 Struct Reference

Complex Number This struct represents a long long complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp64s re](#)
Real part.
- [Npp64s im](#)
Imaginary part.
- [Npp64f re](#)
Real part.
- [Npp64f im](#)
Imaginary part.

8.1.1 Detailed Description

Complex Number This struct represents a long long complex number.

Complex Number This struct represents a double floating-point complex number.

8.1.2 Field Documentation

8.1.2.1 Npp64f NPP_ALIGN_16::im

Imaginary part.

8.1.2.2 Npp64s NPP_ALIGN_16::im

Imaginary part.

8.1.2.3 Npp64f NPP_ALIGN_16::re

Real part.

8.1.2.4 Npp64s NPP_ALIGN_16::re

Real part.

The documentation for this struct was generated from the following file:

- C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h

8.2 NPP_ALIGN_8 Struct Reference

Complex Number This struct represents an unsigned int complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp32u re](#)
Real part.
- [Npp32u im](#)
Imaginary part.
- [Npp32s re](#)
Real part.
- [Npp32s im](#)
Imaginary part.
- [Npp32f re](#)
Real part.
- [Npp32f im](#)
Imaginary part.

8.2.1 Detailed Description

Complex Number This struct represents an unsigned int complex number.

Complex Number This struct represents a single floating-point complex number.

Complex Number This struct represents a signed int complex number.

8.2.2 Field Documentation

8.2.2.1 Npp32f NPP_ALIGN_8::im

Imaginary part.

8.2.2.2 Npp32s NPP_ALIGN_8::im

Imaginary part.

8.2.2.3 Npp32u NPP_ALIGN_8::im

Imaginary part.

8.2.2.4 Npp32f NPP_ALIGN_8::re

Real part.

8.2.2.5 Npp32s NPP_ALIGN_8::re

Real part.

8.2.2.6 Npp32u NPP_ALIGN_8::re

Real part.

The documentation for this struct was generated from the following file:

- C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h

8.3 NppiHaarBuffer Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int `haarBufferSize`
size of the buffer
- `Npp32s * haarBuffer`
buffer

8.3.1 Field Documentation

8.3.1.1 `Npp32s* NppiHaarBuffer::haarBuffer`

buffer

8.3.1.2 `int NppiHaarBuffer::haarBufferSize`

size of the buffer

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.4 NppiHaarClassifier_32f Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int `numClassifiers`
number of classifiers
- `Npp32s * classifiers`
packed classifier data 40 bytes each
- `size_t classifierStep`
- `NppiSize classifierSize`
- `Npp32s * counterDevice`

8.4.1 Field Documentation

8.4.1.1 `Npp32s* NppiHaarClassifier_32f::classifiers`

packed classifier data 40 bytes each

8.4.1.2 `NppiSize NppiHaarClassifier_32f::classifierSize`

8.4.1.3 `size_t NppiHaarClassifier_32f::classifierStep`

8.4.1.4 `Npp32s* NppiHaarClassifier_32f::counterDevice`

8.4.1.5 `int NppiHaarClassifier_32f::numClassifiers`

number of classifiers

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.5 NppiPoint Struct Reference

2D Point

```
#include <nppdefs.h>
```

Data Fields

- `int x`
x-coordinate.
- `int y`
y-coordinate.

8.5.1 Detailed Description

2D Point

8.5.2 Field Documentation

8.5.2.1 `int NppiPoint::x`

x-coordinate.

8.5.2.2 `int NppiPoint::y`

y-coordinate.

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.6 NppiRect Struct Reference

2D Rectangle This struct contains position and size information of a rectangle in two space.

```
#include <nppdefs.h>
```

Data Fields

- `int x`
x-coordinate of upper left corner (lowest memory address).
- `int y`
y-coordinate of upper left corner (lowest memory address).
- `int width`
Rectangle width.
- `int height`
Rectangle height.

8.6.1 Detailed Description

2D Rectangle This struct contains position and size information of a rectangle in two space.

The rectangle's position is usually signified by the coordinate of its upper-left corner.

8.6.2 Field Documentation

8.6.2.1 `int NppiRect::height`

Rectangle height.

8.6.2.2 `int NppiRect::width`

Rectangle width.

8.6.2.3 `int NppiRect::x`

x-coordinate of upper left corner (lowest memory address).

8.6.2.4 `int NppiRect::y`

y-coordinate of upper left corner (lowest memory address).

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.7 NppiSize Struct Reference

2D Size This struct typically represents the size of a rectangular region in two space.

```
#include <nppdefs.h>
```

Data Fields

- `int width`
Rectangle width.
- `int height`
Rectangle height.

8.7.1 Detailed Description

2D Size This struct typically represents the size of a rectangular region in two space.

8.7.2 Field Documentation

8.7.2.1 `int NppiSize::height`

Rectangle height.

8.7.2.2 `int NppiSize::width`

Rectangle width.

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.8 NppLibraryVersion Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int [major](#)
Major version number.
- int [minor](#)
Minor version number.
- int [build](#)
Build number.

8.8.1 Field Documentation

8.8.1.1 int NppLibraryVersion::build

Build number.

This reflects the nightly build this release was made from.

8.8.1.2 int NppLibraryVersion::major

Major version number.

8.8.1.3 int NppLibraryVersion::minor

Minor version number.

The documentation for this struct was generated from the following file:

- C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h

Index

- `__align__`
 - `npp_basic_types`, 48, 49
- Affine Transforms, 134
- Basic NPP Data Types, 46
- build
 - `NppLibraryVersion`, 240
- classifiers
 - `NppiHaarClassifier_32f`, 236
- classifierSize
 - `NppiHaarClassifier_32f`, 236
- classifierStep
 - `NppiHaarClassifier_32f`, 236
- core_npp
 - `nppGetGpuComputeCapability`, 28
 - `nppGetGpuDeviceProperties`, 28
 - `nppGetGpuName`, 28
 - `nppGetGpuNumSMs`, 28
 - `nppGetLibVersion`, 28
 - `nppGetMaxThreadsPerBlock`, 29
 - `nppGetMaxThreadsPerSM`, 29
 - `nppGetStream`, 29
 - `nppGetStreamMaxThreadsPerSM`, 29
 - `nppGetStreamNumSMs`, 29
 - `nppSetStream`, 29
- counterDevice
 - `NppiHaarClassifier_32f`, 236
- Geometry Transforms, 50
- haarBuffer
 - `NppiHaarBuffer`, 235
- haarBufferSize
 - `NppiHaarBuffer`, 235
- height
 - `NppiRect`, 238
 - `NppiSize`, 239
- im
 - `NPP_ALIGN_16`, 231
 - `NPP_ALIGN_8`, 233
- image_affine_transform
 - `nppiGetAffineBound`, 143
 - `nppiGetAffineQuad`, 143
 - `nppiGetAffineTransform`, 144
 - `nppiWarpAffine_16u_AC4R`, 144
 - `nppiWarpAffine_16u_C1R`, 145
 - `nppiWarpAffine_16u_C3R`, 145
 - `nppiWarpAffine_16u_C4R`, 146
 - `nppiWarpAffine_16u_P3R`, 146
 - `nppiWarpAffine_16u_P4R`, 147
 - `nppiWarpAffine_32f_AC4R`, 147
 - `nppiWarpAffine_32f_C1R`, 148
 - `nppiWarpAffine_32f_C3R`, 148
 - `nppiWarpAffine_32f_C4R`, 149
 - `nppiWarpAffine_32f_P3R`, 149
 - `nppiWarpAffine_32f_P4R`, 150
 - `nppiWarpAffine_32s_AC4R`, 150
 - `nppiWarpAffine_32s_C1R`, 151
 - `nppiWarpAffine_32s_C3R`, 151
 - `nppiWarpAffine_32s_C4R`, 152
 - `nppiWarpAffine_32s_P3R`, 152
 - `nppiWarpAffine_32s_P4R`, 153
 - `nppiWarpAffine_64f_AC4R`, 153
 - `nppiWarpAffine_64f_C1R`, 154
 - `nppiWarpAffine_64f_C3R`, 154
 - `nppiWarpAffine_64f_C4R`, 155
 - `nppiWarpAffine_64f_P3R`, 155
 - `nppiWarpAffine_64f_P4R`, 156
 - `nppiWarpAffine_8u_AC4R`, 156
 - `nppiWarpAffine_8u_C1R`, 157
 - `nppiWarpAffine_8u_C3R`, 157
 - `nppiWarpAffine_8u_C4R`, 158
 - `nppiWarpAffine_8u_P3R`, 158
 - `nppiWarpAffine_8u_P4R`, 159
 - `nppiWarpAffineBack_16u_AC4R`, 159
 - `nppiWarpAffineBack_16u_C1R`, 160
 - `nppiWarpAffineBack_16u_C3R`, 160
 - `nppiWarpAffineBack_16u_C4R`, 161
 - `nppiWarpAffineBack_16u_P3R`, 161
 - `nppiWarpAffineBack_16u_P4R`, 162
 - `nppiWarpAffineBack_32f_AC4R`, 162
 - `nppiWarpAffineBack_32f_C1R`, 163
 - `nppiWarpAffineBack_32f_C3R`, 163
 - `nppiWarpAffineBack_32f_C4R`, 164
 - `nppiWarpAffineBack_32f_P3R`, 164
 - `nppiWarpAffineBack_32f_P4R`, 165
 - `nppiWarpAffineBack_32s_AC4R`, 165
 - `nppiWarpAffineBack_32s_C1R`, 166

- nppiWarpAffineBack_32s_C3R, 166
- nppiWarpAffineBack_32s_C4R, 167
- nppiWarpAffineBack_32s_P3R, 167
- nppiWarpAffineBack_32s_P4R, 168
- nppiWarpAffineBack_8u_AC4R, 168
- nppiWarpAffineBack_8u_C1R, 169
- nppiWarpAffineBack_8u_C3R, 169
- nppiWarpAffineBack_8u_C4R, 170
- nppiWarpAffineBack_8u_P3R, 170
- nppiWarpAffineBack_8u_P4R, 171
- nppiWarpAffineQuad_16u_AC4R, 171
- nppiWarpAffineQuad_16u_C1R, 172
- nppiWarpAffineQuad_16u_C3R, 172
- nppiWarpAffineQuad_16u_C4R, 173
- nppiWarpAffineQuad_16u_P3R, 173
- nppiWarpAffineQuad_16u_P4R, 174
- nppiWarpAffineQuad_32f_AC4R, 174
- nppiWarpAffineQuad_32f_C1R, 175
- nppiWarpAffineQuad_32f_C3R, 175
- nppiWarpAffineQuad_32f_C4R, 176
- nppiWarpAffineQuad_32f_P3R, 176
- nppiWarpAffineQuad_32f_P4R, 177
- nppiWarpAffineQuad_32s_AC4R, 177
- nppiWarpAffineQuad_32s_C1R, 178
- nppiWarpAffineQuad_32s_C3R, 178
- nppiWarpAffineQuad_32s_C4R, 179
- nppiWarpAffineQuad_32s_P3R, 179
- nppiWarpAffineQuad_32s_P4R, 180
- nppiWarpAffineQuad_8u_AC4R, 180
- nppiWarpAffineQuad_8u_C1R, 181
- nppiWarpAffineQuad_8u_C3R, 181
- nppiWarpAffineQuad_8u_C4R, 182
- nppiWarpAffineQuad_8u_P3R, 182
- nppiWarpAffineQuad_8u_P4R, 183
- image_mirror
 - nppiMirror_16s_AC4IR, 120
 - nppiMirror_16s_AC4R, 120
 - nppiMirror_16s_C1IR, 121
 - nppiMirror_16s_C1R, 121
 - nppiMirror_16s_C3IR, 121
 - nppiMirror_16s_C3R, 122
 - nppiMirror_16s_C4IR, 122
 - nppiMirror_16s_C4R, 122
 - nppiMirror_16u_AC4IR, 123
 - nppiMirror_16u_AC4R, 123
 - nppiMirror_16u_C1IR, 123
 - nppiMirror_16u_C1R, 124
 - nppiMirror_16u_C3IR, 124
 - nppiMirror_16u_C3R, 124
 - nppiMirror_16u_C4IR, 125
 - nppiMirror_16u_C4R, 125
 - nppiMirror_32f_AC4IR, 125
 - nppiMirror_32f_AC4R, 126
 - nppiMirror_32f_C1IR, 126
 - nppiMirror_32f_C1R, 126
 - nppiMirror_32f_C3IR, 127
 - nppiMirror_32f_C3R, 127
 - nppiMirror_32f_C4IR, 127
 - nppiMirror_32f_C4R, 128
 - nppiMirror_32s_AC4IR, 128
 - nppiMirror_32s_AC4R, 128
 - nppiMirror_32s_C1IR, 129
 - nppiMirror_32s_C1R, 129
 - nppiMirror_32s_C3IR, 129
 - nppiMirror_32s_C3R, 130
 - nppiMirror_32s_C4IR, 130
 - nppiMirror_32s_C4R, 130
 - nppiMirror_8u_AC4IR, 131
 - nppiMirror_8u_AC4R, 131
 - nppiMirror_8u_C1IR, 131
 - nppiMirror_8u_C1R, 132
 - nppiMirror_8u_C3IR, 132
 - nppiMirror_8u_C3R, 132
 - nppiMirror_8u_C4IR, 133
 - nppiMirror_8u_C4R, 133
- image_perspective_transforms
 - nppiGetPerspectiveBound, 192
 - nppiGetPerspectiveQuad, 192
 - nppiGetPerspectiveTransform, 193
 - nppiWarpPerspective_16u_AC4R, 193
 - nppiWarpPerspective_16u_C1R, 194
 - nppiWarpPerspective_16u_C3R, 194
 - nppiWarpPerspective_16u_C4R, 195
 - nppiWarpPerspective_16u_P3R, 195
 - nppiWarpPerspective_16u_P4R, 196
 - nppiWarpPerspective_32f_AC4R, 196
 - nppiWarpPerspective_32f_C1R, 197
 - nppiWarpPerspective_32f_C3R, 197
 - nppiWarpPerspective_32f_C4R, 198
 - nppiWarpPerspective_32f_P3R, 198
 - nppiWarpPerspective_32f_P4R, 199
 - nppiWarpPerspective_32s_AC4R, 199
 - nppiWarpPerspective_32s_C1R, 200
 - nppiWarpPerspective_32s_C3R, 200
 - nppiWarpPerspective_32s_C4R, 201
 - nppiWarpPerspective_32s_P3R, 201
 - nppiWarpPerspective_32s_P4R, 201
 - nppiWarpPerspective_8u_AC4R, 202
 - nppiWarpPerspective_8u_C1R, 202
 - nppiWarpPerspective_8u_C3R, 203
 - nppiWarpPerspective_8u_C4R, 203
 - nppiWarpPerspective_8u_P3R, 204
 - nppiWarpPerspective_8u_P4R, 204
 - nppiWarpPerspectiveBack_16u_AC4R, 205
 - nppiWarpPerspectiveBack_16u_C1R, 205
 - nppiWarpPerspectiveBack_16u_C3R, 206
 - nppiWarpPerspectiveBack_16u_C4R, 206
 - nppiWarpPerspectiveBack_16u_P3R, 207

- nppiWarpPerspectiveBack_16u_P4R, 207
- nppiWarpPerspectiveBack_32f_AC4R, 208
- nppiWarpPerspectiveBack_32f_C1R, 208
- nppiWarpPerspectiveBack_32f_C3R, 209
- nppiWarpPerspectiveBack_32f_C4R, 209
- nppiWarpPerspectiveBack_32f_P3R, 210
- nppiWarpPerspectiveBack_32f_P4R, 210
- nppiWarpPerspectiveBack_32s_AC4R, 211
- nppiWarpPerspectiveBack_32s_C1R, 211
- nppiWarpPerspectiveBack_32s_C3R, 212
- nppiWarpPerspectiveBack_32s_C4R, 212
- nppiWarpPerspectiveBack_32s_P3R, 213
- nppiWarpPerspectiveBack_32s_P4R, 213
- nppiWarpPerspectiveBack_8u_AC4R, 214
- nppiWarpPerspectiveBack_8u_C1R, 214
- nppiWarpPerspectiveBack_8u_C3R, 215
- nppiWarpPerspectiveBack_8u_C4R, 215
- nppiWarpPerspectiveBack_8u_P3R, 216
- nppiWarpPerspectiveBack_8u_P4R, 216
- nppiWarpPerspectiveQuad_16u_AC4R, 217
- nppiWarpPerspectiveQuad_16u_C1R, 217
- nppiWarpPerspectiveQuad_16u_C3R, 218
- nppiWarpPerspectiveQuad_16u_C4R, 218
- nppiWarpPerspectiveQuad_16u_P3R, 219
- nppiWarpPerspectiveQuad_16u_P4R, 219
- nppiWarpPerspectiveQuad_32f_AC4R, 220
- nppiWarpPerspectiveQuad_32f_C1R, 220
- nppiWarpPerspectiveQuad_32f_C3R, 221
- nppiWarpPerspectiveQuad_32f_C4R, 221
- nppiWarpPerspectiveQuad_32f_P3R, 222
- nppiWarpPerspectiveQuad_32f_P4R, 222
- nppiWarpPerspectiveQuad_32s_AC4R, 223
- nppiWarpPerspectiveQuad_32s_C1R, 223
- nppiWarpPerspectiveQuad_32s_C3R, 224
- nppiWarpPerspectiveQuad_32s_C4R, 224
- nppiWarpPerspectiveQuad_32s_P3R, 225
- nppiWarpPerspectiveQuad_32s_P4R, 225
- nppiWarpPerspectiveQuad_8u_AC4R, 226
- nppiWarpPerspectiveQuad_8u_C1R, 226
- nppiWarpPerspectiveQuad_8u_C3R, 227
- nppiWarpPerspectiveQuad_8u_C4R, 227
- nppiWarpPerspectiveQuad_8u_P3R, 228
- nppiWarpPerspectiveQuad_8u_P4R, 228
- image_remap
 - nppiRemap_16s_AC4R, 89
 - nppiRemap_16s_C1R, 90
 - nppiRemap_16s_C3R, 90
 - nppiRemap_16s_C4R, 91
 - nppiRemap_16s_P3R, 92
 - nppiRemap_16s_P4R, 92
 - nppiRemap_16u_AC4R, 93
 - nppiRemap_16u_C1R, 93
 - nppiRemap_16u_C3R, 94
 - nppiRemap_16u_C4R, 95
 - nppiRemap_16u_P3R, 95
 - nppiRemap_16u_P4R, 96
 - nppiRemap_32f_AC4R, 96
 - nppiRemap_32f_C1R, 97
 - nppiRemap_32f_C3R, 98
 - nppiRemap_32f_C4R, 98
 - nppiRemap_32f_P3R, 99
 - nppiRemap_32f_P4R, 99
 - nppiRemap_64f_AC4R, 100
 - nppiRemap_64f_C1R, 100
 - nppiRemap_64f_C3R, 101
 - nppiRemap_64f_C4R, 102
 - nppiRemap_64f_P3R, 102
 - nppiRemap_64f_P4R, 103
 - nppiRemap_8u_AC4R, 103
 - nppiRemap_8u_C1R, 104
 - nppiRemap_8u_C3R, 105
 - nppiRemap_8u_C4R, 105
 - nppiRemap_8u_P3R, 106
 - nppiRemap_8u_P4R, 106
- image_resize
 - nppiResize_16u_AC4R, 76
 - nppiResize_16u_C1R, 77
 - nppiResize_16u_C3R, 77
 - nppiResize_16u_C4R, 78
 - nppiResize_16u_P3R, 78
 - nppiResize_16u_P4R, 79
 - nppiResize_32f_AC4R, 79
 - nppiResize_32f_C1R, 80
 - nppiResize_32f_C3R, 80
 - nppiResize_32f_C4R, 81
 - nppiResize_32f_P3R, 81
 - nppiResize_32f_P4R, 82
 - nppiResize_8u_AC4R, 82
 - nppiResize_8u_C1R, 83
 - nppiResize_8u_C3R, 83
 - nppiResize_8u_C4R, 84
 - nppiResize_8u_P3R, 84
 - nppiResize_8u_P4R, 85
- image_resize_square_pixel
 - nppiGetResizeRect, 56
 - nppiResizeAdvancedGetBufferHostSize_8u_C1R, 56
 - nppiResizeSqrPixel_16s_AC4R, 56
 - nppiResizeSqrPixel_16s_C1R, 57
 - nppiResizeSqrPixel_16s_C3R, 57
 - nppiResizeSqrPixel_16s_C4R, 58
 - nppiResizeSqrPixel_16s_P3R, 58
 - nppiResizeSqrPixel_16s_P4R, 59
 - nppiResizeSqrPixel_16u_AC4R, 60
 - nppiResizeSqrPixel_16u_C1R, 60
 - nppiResizeSqrPixel_16u_C3R, 61
 - nppiResizeSqrPixel_16u_C4R, 61
 - nppiResizeSqrPixel_16u_P3R, 62

- nppiResizeSqrPixel_16u_P4R, 62
- nppiResizeSqrPixel_32f_AC4R, 63
- nppiResizeSqrPixel_32f_C1R, 63
- nppiResizeSqrPixel_32f_C3R, 64
- nppiResizeSqrPixel_32f_C4R, 64
- nppiResizeSqrPixel_32f_P3R, 65
- nppiResizeSqrPixel_32f_P4R, 65
- nppiResizeSqrPixel_64f_AC4R, 66
- nppiResizeSqrPixel_64f_C1R, 66
- nppiResizeSqrPixel_64f_C3R, 67
- nppiResizeSqrPixel_64f_C4R, 67
- nppiResizeSqrPixel_64f_P3R, 68
- nppiResizeSqrPixel_64f_P4R, 68
- nppiResizeSqrPixel_8u_AC4R, 69
- nppiResizeSqrPixel_8u_C1R, 69
- nppiResizeSqrPixel_8u_C1R_Advanced, 70
- nppiResizeSqrPixel_8u_C3R, 70
- nppiResizeSqrPixel_8u_C4R, 71
- nppiResizeSqrPixel_8u_P3R, 71
- nppiResizeSqrPixel_8u_P4R, 72
- image_rotate
 - nppiGetRotateBound, 109
 - nppiGetRotateQuad, 110
 - nppiRotate_16u_AC4R, 110
 - nppiRotate_16u_C1R, 111
 - nppiRotate_16u_C3R, 111
 - nppiRotate_16u_C4R, 112
 - nppiRotate_32f_AC4R, 112
 - nppiRotate_32f_C1R, 113
 - nppiRotate_32f_C3R, 113
 - nppiRotate_32f_C4R, 114
 - nppiRotate_8u_AC4R, 114
 - nppiRotate_8u_C1R, 115
 - nppiRotate_8u_C3R, 115
 - nppiRotate_8u_C4R, 116
- major
 - NppLibraryVersion, 240
- minor
 - NppLibraryVersion, 240
- Mirror, 117
- NPP Core, 27
- NPP Type Definitions and Constants, 31
- Npp16s
 - npp_basic_types, 47
- Npp16sc
 - npp_basic_types, 49
- Npp16u
 - npp_basic_types, 47
- Npp16uc
 - npp_basic_types, 49
- Npp32f
 - npp_basic_types, 47
- Npp32fc
 - npp_basic_types, 47
- Npp32s
 - npp_basic_types, 47
- Npp32sc
 - npp_basic_types, 47
- Npp32u
 - npp_basic_types, 48
- Npp32uc
 - npp_basic_types, 48
- Npp64f
 - npp_basic_types, 48
- Npp64fc
 - npp_basic_types, 48
- Npp64s
 - npp_basic_types, 48
- Npp64sc
 - npp_basic_types, 48
- Npp64u
 - npp_basic_types, 48
- Npp8s
 - npp_basic_types, 48
- Npp8u
 - npp_basic_types, 48
- Npp8uc
 - npp_basic_types, 49
- NPP_AFFINE_QUAD_INCORRECT_WARNING
 - typedefs_npp, 44
- NPP_ALG_HINT_ACCURATE
 - typedefs_npp, 39
- NPP_ALG_HINT_FAST
 - typedefs_npp, 39
- NPP_ALG_HINT_NONE
 - typedefs_npp, 39
- NPP_ALIGNMENT_ERROR
 - typedefs_npp, 43
- NPP_ANCHOR_ERROR
 - typedefs_npp, 43
- NPP_BAD_ARGUMENT_ERROR
 - typedefs_npp, 44
- NPP_BORDER_CONSTANT
 - typedefs_npp, 40
- NPP_BORDER_MIRROR
 - typedefs_npp, 40
- NPP_BORDER_NONE
 - typedefs_npp, 40
- NPP_BORDER_REPLICATE
 - typedefs_npp, 40
- NPP_BORDER_UNDEFINED
 - typedefs_npp, 40
- NPP_BORDER_WRAP
 - typedefs_npp, 40
- NPP_BOTH_AXIS
 - typedefs_npp, 40

- NPP_CHANNEL_ERROR
typedefs_npp, 43
- NPP_CHANNEL_ORDER_ERROR
typedefs_npp, 43
- NPP_CMP_EQ
typedefs_npp, 39
- NPP_CMP_GREATER
typedefs_npp, 39
- NPP_CMP_GREATER_EQ
typedefs_npp, 39
- NPP_CMP_LESS
typedefs_npp, 38
- NPP_CMP_LESS_EQ
typedefs_npp, 38
- NPP_COEFFICIENT_ERROR
typedefs_npp, 43
- NPP_COI_ERROR
typedefs_npp, 43
- NPP_CONTEXT_MATCH_ERROR
typedefs_npp, 44
- NPP_CORRUPTED_DATA_ERROR
typedefs_npp, 43
- NPP_CUDA_1_0
typedefs_npp, 39
- NPP_CUDA_1_1
typedefs_npp, 39
- NPP_CUDA_1_2
typedefs_npp, 39
- NPP_CUDA_1_3
typedefs_npp, 39
- NPP_CUDA_2_0
typedefs_npp, 39
- NPP_CUDA_2_1
typedefs_npp, 39
- NPP_CUDA_3_0
typedefs_npp, 39
- NPP_CUDA_3_2
typedefs_npp, 39
- NPP_CUDA_3_5
typedefs_npp, 39
- NPP_CUDA_3_7
typedefs_npp, 39
- NPP_CUDA_5_0
typedefs_npp, 39
- NPP_CUDA_5_2
typedefs_npp, 39
- NPP_CUDA_5_3
typedefs_npp, 39
- NPP_CUDA_6_0
typedefs_npp, 39
- NPP_CUDA_KERNEL_EXECUTION_ERROR
typedefs_npp, 43
- NPP_CUDA_NOT_CAPABLE
typedefs_npp, 39
- NPP_CUDA_UNKNOWN_VERSION
typedefs_npp, 39
- NPP_DATA_TYPE_ERROR
typedefs_npp, 44
- NPP_DIVIDE_BY_ZERO_ERROR
typedefs_npp, 44
- NPP_DIVIDE_BY_ZERO_WARNING
typedefs_npp, 44
- NPP_DIVISOR_ERROR
typedefs_npp, 43
- NPP_DOUBLE_SIZE_WARNING
typedefs_npp, 44
- NPP_ERROR
typedefs_npp, 44
- NPP_ERROR_RESERVED
typedefs_npp, 44
- NPP_FFT_FLAG_ERROR
typedefs_npp, 44
- NPP_FFT_ORDER_ERROR
typedefs_npp, 44
- NPP_FILTER_SCHARR
typedefs_npp, 40
- NPP_FILTER_SOBEL
typedefs_npp, 40
- NPP_HAAR_CLASSIFIER_PIXEL_MATCH_-
ERROR
typedefs_npp, 43
- NPP_HISTOGRAM_NUMBER_OF_LEVELS_-
ERROR
typedefs_npp, 43
- NPP_HORIZONTAL_AXIS
typedefs_npp, 40
- NPP_INTERPOLATION_ERROR
typedefs_npp, 44
- NPP_INVALID_DEVICE_POINTER_ERROR
typedefs_npp, 43
- NPP_INVALID_HOST_POINTER_ERROR
typedefs_npp, 43
- NPP_LUT_NUMBER_OF_LEVELS_ERROR
typedefs_npp, 43
- NPP_LUT_PALETTE_BITSIZE_ERROR
typedefs_npp, 43
- NPP_MASK_SIZE_11_X_11
typedefs_npp, 41
- NPP_MASK_SIZE_13_X_13
typedefs_npp, 41
- NPP_MASK_SIZE_15_X_15
typedefs_npp, 41
- NPP_MASK_SIZE_1_X_3
typedefs_npp, 41
- NPP_MASK_SIZE_1_X_5
typedefs_npp, 41
- NPP_MASK_SIZE_3_X_1
typedefs_npp, 41

- NPP_MASK_SIZE_3_X_3
typedefs_npp, 41
- NPP_MASK_SIZE_5_X_1
typedefs_npp, 41
- NPP_MASK_SIZE_5_X_5
typedefs_npp, 41
- NPP_MASK_SIZE_7_X_7
typedefs_npp, 41
- NPP_MASK_SIZE_9_X_9
typedefs_npp, 41
- NPP_MASK_SIZE_ERROR
typedefs_npp, 43
- NPP_MEMCPY_ERROR
typedefs_npp, 43
- NPP_MEMFREE_ERROR
typedefs_npp, 43
- NPP_MEMORY_ALLOCATION_ERR
typedefs_npp, 44
- NPP_MEMSET_ERROR
typedefs_npp, 43
- NPP_MIRROR_FLIP_ERROR
typedefs_npp, 44
- NPP_MISALIGNED_DST_ROI_WARNING
typedefs_npp, 44
- NPP_MOMENT_00_ZERO_ERROR
typedefs_npp, 44
- NPP_NO_ERROR
typedefs_npp, 44
- NPP_NO_MEMORY_ERROR
typedefs_npp, 44
- NPP_NO_OPERATION_WARNING
typedefs_npp, 44
- NPP_NOT_EVEN_STEP_ERROR
typedefs_npp, 43
- NPP_NOT_IMPLEMENTED_ERROR
typedefs_npp, 44
- NPP_NOT_SUFFICIENT_COMPUTE_-
CAPABILITY
typedefs_npp, 43
- NPP_NOT_SUPPORTED_MODE_ERROR
typedefs_npp, 43
- NPP_NULL_POINTER_ERROR
typedefs_npp, 44
- NPP_NUMBER_OF_CHANNELS_ERROR
typedefs_npp, 43
- NPP_OUT_OFF_RANGE_ERROR
typedefs_npp, 44
- NPP_OVERFLOW_ERROR
typedefs_npp, 43
- NPP_QUADRANGLE_ERROR
typedefs_npp, 43
- NPP_QUALITY_INDEX_ERROR
typedefs_npp, 43
- NPP_RANGE_ERROR
typedefs_npp, 44
- NPP_RECTANGLE_ERROR
typedefs_npp, 43
- NPP_RESIZE_FACTOR_ERROR
typedefs_npp, 44
- NPP_RESIZE_NO_OPERATION_ERROR
typedefs_npp, 43
- NPP_RND_FINANCIAL
typedefs_npp, 42
- NPP_RND_NEAR
typedefs_npp, 42
- NPP_RND_ZERO
typedefs_npp, 42
- NPP_ROUND_MODE_NOT_SUPPORTED_-
ERROR
typedefs_npp, 43
- NPP_ROUND_NEAREST_TIES_AWAY_-
FROM_ZERO
typedefs_npp, 42
- NPP_ROUND_NEAREST_TIES_TO_EVEN
typedefs_npp, 42
- NPP_ROUND_TOWARD_ZERO
typedefs_npp, 42
- NPP_SCALE_RANGE_ERROR
typedefs_npp, 44
- NPP_SIZE_ERROR
typedefs_npp, 44
- NPP_STEP_ERROR
typedefs_npp, 44
- NPP_STRIDE_ERROR
typedefs_npp, 43
- NPP_SUCCESS
typedefs_npp, 44
- NPP_TEXTURE_BIND_ERROR
typedefs_npp, 43
- NPP_THRESHOLD_ERROR
typedefs_npp, 44
- NPP_THRESHOLD_NEGATIVE_LEVEL_-
ERROR
typedefs_npp, 44
- NPP_VERTICAL_AXIS
typedefs_npp, 40
- NPP_WRONG_INTERSECTION_QUAD_-
WARNING
typedefs_npp, 44
- NPP_WRONG_INTERSECTION_ROI_ERROR
typedefs_npp, 43
- NPP_WRONG_INTERSECTION_ROI_-
WARNING
typedefs_npp, 44
- NPP_ZC_MODE_NOT_SUPPORTED_ERROR
typedefs_npp, 43
- NPP_ZERO_MASK_VALUE_ERROR
typedefs_npp, 43

- NPP_ALIGN_16, 231
 - im, 231
 - re, 232
- NPP_ALIGN_8, 233
 - im, 233
 - re, 233, 234
- npp_basic_types
 - __align__, 48, 49
 - Npp16s, 47
 - Npp16sc, 49
 - Npp16u, 47
 - Npp16uc, 49
 - Npp32f, 47
 - Npp32fc, 47
 - Npp32s, 47
 - Npp32sc, 47
 - Npp32u, 48
 - Npp32uc, 48
 - Npp64f, 48
 - Npp64fc, 48
 - Npp64s, 48
 - Npp64sc, 48
 - Npp64u, 48
 - Npp8s, 48
 - Npp8u, 48
 - Npp8uc, 49
- NPP_MAX_16S
 - typedefs_npp, 37
- NPP_MAX_16U
 - typedefs_npp, 37
- NPP_MAX_32S
 - typedefs_npp, 37
- NPP_MAX_32U
 - typedefs_npp, 37
- NPP_MAX_64S
 - typedefs_npp, 37
- NPP_MAX_64U
 - typedefs_npp, 37
- NPP_MAX_8S
 - typedefs_npp, 37
- NPP_MAX_8U
 - typedefs_npp, 37
- NPP_MAXABS_32F
 - typedefs_npp, 37
- NPP_MAXABS_64F
 - typedefs_npp, 37
- NPP_MIN_16S
 - typedefs_npp, 37
- NPP_MIN_16U
 - typedefs_npp, 38
- NPP_MIN_32S
 - typedefs_npp, 38
- NPP_MIN_32U
 - typedefs_npp, 38
- NPP_MIN_64S
 - typedefs_npp, 38
- NPP_MIN_64U
 - typedefs_npp, 38
- NPP_MIN_8S
 - typedefs_npp, 38
- NPP_MIN_8U
 - typedefs_npp, 38
- NPP_MINABS_32F
 - typedefs_npp, 38
- NPP_MINABS_64F
 - typedefs_npp, 38
- NppCmpOp
 - typedefs_npp, 38
- nppGetGpuComputeCapability
 - core_npp, 28
- nppGetGpuDeviceProperties
 - core_npp, 28
- nppGetGpuName
 - core_npp, 28
- nppGetGpuNumSMs
 - core_npp, 28
- nppGetLibVersion
 - core_npp, 28
- nppGetMaxThreadsPerBlock
 - core_npp, 29
- nppGetMaxThreadsPerSM
 - core_npp, 29
- nppGetStream
 - core_npp, 29
- nppGetStreamMaxThreadsPerSM
 - core_npp, 29
- nppGetStreamNumSMs
 - core_npp, 29
- NppGpuComputeCapability
 - typedefs_npp, 39
- NppHintAlgorithm
 - typedefs_npp, 39
- NPPI_BAYER_BGGR
 - typedefs_npp, 40
- NPPI_BAYER_GBRG
 - typedefs_npp, 40
- NPPI_BAYER_GRBG
 - typedefs_npp, 40
- NPPI_BAYER_RGGB
 - typedefs_npp, 40
- NPPI_INTER_CUBIC
 - typedefs_npp, 41
- NPPI_INTER_CUBIC2P_B05C03
 - typedefs_npp, 41
- NPPI_INTER_CUBIC2P_BSPLINE
 - typedefs_npp, 41
- NPPI_INTER_CUBIC2P_CATMULLROM
 - typedefs_npp, 41

- NPPI_INTER_LANCZOS
 - typedefs_npp, 41
- NPPI_INTER_LANCZOS3_ADVANCED
 - typedefs_npp, 41
- NPPI_INTER_LINEAR
 - typedefs_npp, 41
- NPPI_INTER_NN
 - typedefs_npp, 41
- NPPI_INTER_SUPER
 - typedefs_npp, 41
- NPPI_INTER_UNDEFINED
 - typedefs_npp, 41
- NPPI_OP_ALPHA_ATOP
 - typedefs_npp, 39
- NPPI_OP_ALPHA_ATOP_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_IN
 - typedefs_npp, 39
- NPPI_OP_ALPHA_IN_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_OUT
 - typedefs_npp, 39
- NPPI_OP_ALPHA_OUT_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_OVER
 - typedefs_npp, 39
- NPPI_OP_ALPHA_OVER_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_PLUS
 - typedefs_npp, 39
- NPPI_OP_ALPHA_PLUS_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_XOR
 - typedefs_npp, 39
- NPPI_OP_ALPHA_XOR_PREMUL
 - typedefs_npp, 40
- NPPI_SMOOTH_EDGE
 - typedefs_npp, 41
- nppiACTable
 - typedefs_npp, 41
- NppiAlphaOp
 - typedefs_npp, 39
- NppiAxis
 - typedefs_npp, 40
- NppiBayerGridPosition
 - typedefs_npp, 40
- NppiBorderType
 - typedefs_npp, 40
- nppiDCTable
 - typedefs_npp, 41
- NppiDifferentialKernel
 - typedefs_npp, 40
- nppiGetAffineBound
 - image_affine_transform, 143
- nppiGetAffineQuad
 - image_affine_transform, 143
- nppiGetAffineTransform
 - image_affine_transform, 144
- nppiGetPerspectiveBound
 - image_perspective_transforms, 192
- nppiGetPerspectiveQuad
 - image_perspective_transforms, 192
- nppiGetPerspectiveTransform
 - image_perspective_transforms, 193
- nppiGetResizeRect
 - image_resize_square_pixel, 56
- nppiGetRotateBound
 - image_rotate, 109
- nppiGetRotateQuad
 - image_rotate, 110
- NppiHaarBuffer, 235
 - haarBuffer, 235
 - haarBufferSize, 235
- NppiHaarClassifier_32f, 236
 - classifiers, 236
 - classifierSize, 236
 - classifierStep, 236
 - counterDevice, 236
 - numClassifiers, 236
- NppiHuffmanTableType
 - typedefs_npp, 40
- NppiInterpolationMode
 - typedefs_npp, 41
- NppiMaskSize
 - typedefs_npp, 41
- nppiMirror_16s_AC4IR
 - image_mirror, 120
- nppiMirror_16s_AC4R
 - image_mirror, 120
- nppiMirror_16s_C1IR
 - image_mirror, 121
- nppiMirror_16s_C1R
 - image_mirror, 121
- nppiMirror_16s_C3IR
 - image_mirror, 121
- nppiMirror_16s_C3R
 - image_mirror, 122
- nppiMirror_16s_C4IR
 - image_mirror, 122
- nppiMirror_16s_C4R
 - image_mirror, 122
- nppiMirror_16u_AC4IR
 - image_mirror, 123
- nppiMirror_16u_AC4R
 - image_mirror, 123
- nppiMirror_16u_C1IR

- image_mirror, 123
- nppiMirror_16u_C1R
 - image_mirror, 124
- nppiMirror_16u_C3IR
 - image_mirror, 124
- nppiMirror_16u_C3R
 - image_mirror, 124
- nppiMirror_16u_C4IR
 - image_mirror, 125
- nppiMirror_16u_C4R
 - image_mirror, 125
- nppiMirror_32f_AC4IR
 - image_mirror, 125
- nppiMirror_32f_AC4R
 - image_mirror, 126
- nppiMirror_32f_C1IR
 - image_mirror, 126
- nppiMirror_32f_C1R
 - image_mirror, 126
- nppiMirror_32f_C3IR
 - image_mirror, 127
- nppiMirror_32f_C3R
 - image_mirror, 127
- nppiMirror_32f_C4IR
 - image_mirror, 127
- nppiMirror_32f_C4R
 - image_mirror, 128
- nppiMirror_32s_AC4IR
 - image_mirror, 128
- nppiMirror_32s_AC4R
 - image_mirror, 128
- nppiMirror_32s_C1IR
 - image_mirror, 129
- nppiMirror_32s_C1R
 - image_mirror, 129
- nppiMirror_32s_C3IR
 - image_mirror, 129
- nppiMirror_32s_C3R
 - image_mirror, 130
- nppiMirror_32s_C4IR
 - image_mirror, 130
- nppiMirror_32s_C4R
 - image_mirror, 130
- nppiMirror_8u_AC4IR
 - image_mirror, 131
- nppiMirror_8u_AC4R
 - image_mirror, 131
- nppiMirror_8u_C1IR
 - image_mirror, 131
- nppiMirror_8u_C1R
 - image_mirror, 132
- nppiMirror_8u_C3IR
 - image_mirror, 132
- nppiMirror_8u_C3R
 - image_mirror, 132
- nppiMirror_8u_C4IR
 - image_mirror, 133
- nppiMirror_8u_C4R
 - image_mirror, 133
- NppiNorm
 - typedefs_npp, 41
- nppiNormInf
 - typedefs_npp, 42
- nppiNormL1
 - typedefs_npp, 42
- nppiNormL2
 - typedefs_npp, 42
- NppiPoint, 237
 - x, 237
 - y, 237
- NppiRect, 238
 - height, 238
 - width, 238
 - x, 238
 - y, 238
- nppiRemap_16s_AC4R
 - image_remap, 89
- nppiRemap_16s_C1R
 - image_remap, 90
- nppiRemap_16s_C3R
 - image_remap, 90
- nppiRemap_16s_C4R
 - image_remap, 91
- nppiRemap_16s_P3R
 - image_remap, 92
- nppiRemap_16s_P4R
 - image_remap, 92
- nppiRemap_16u_AC4R
 - image_remap, 93
- nppiRemap_16u_C1R
 - image_remap, 93
- nppiRemap_16u_C3R
 - image_remap, 94
- nppiRemap_16u_C4R
 - image_remap, 95
- nppiRemap_16u_P3R
 - image_remap, 95
- nppiRemap_16u_P4R
 - image_remap, 96
- nppiRemap_32f_AC4R
 - image_remap, 96
- nppiRemap_32f_C1R
 - image_remap, 97
- nppiRemap_32f_C3R
 - image_remap, 98
- nppiRemap_32f_C4R
 - image_remap, 98
- nppiRemap_32f_P3R

- image_remap, 99
- nppiRemap_32f_P4R
 - image_remap, 99
- nppiRemap_64f_AC4R
 - image_remap, 100
- nppiRemap_64f_C1R
 - image_remap, 100
- nppiRemap_64f_C3R
 - image_remap, 101
- nppiRemap_64f_C4R
 - image_remap, 102
- nppiRemap_64f_P3R
 - image_remap, 102
- nppiRemap_64f_P4R
 - image_remap, 103
- nppiRemap_8u_AC4R
 - image_remap, 103
- nppiRemap_8u_C1R
 - image_remap, 104
- nppiRemap_8u_C3R
 - image_remap, 105
- nppiRemap_8u_C4R
 - image_remap, 105
- nppiRemap_8u_P3R
 - image_remap, 106
- nppiRemap_8u_P4R
 - image_remap, 106
- nppiResize_16u_AC4R
 - image_resize, 76
- nppiResize_16u_C1R
 - image_resize, 77
- nppiResize_16u_C3R
 - image_resize, 77
- nppiResize_16u_C4R
 - image_resize, 78
- nppiResize_16u_P3R
 - image_resize, 78
- nppiResize_16u_P4R
 - image_resize, 79
- nppiResize_32f_AC4R
 - image_resize, 79
- nppiResize_32f_C1R
 - image_resize, 80
- nppiResize_32f_C3R
 - image_resize, 80
- nppiResize_32f_C4R
 - image_resize, 81
- nppiResize_32f_P3R
 - image_resize, 81
- nppiResize_32f_P4R
 - image_resize, 82
- nppiResize_8u_AC4R
 - image_resize, 82
- nppiResize_8u_C1R
 - image_resize, 83
- nppiResize_8u_C3R
 - image_resize, 83
- nppiResize_8u_C4R
 - image_resize, 84
- nppiResize_8u_P3R
 - image_resize, 84
- nppiResize_8u_P4R
 - image_resize, 85
- nppiResizeAdvancedGetBufferHostSize_8u_C1R
 - image_resize_square_pixel, 56
- nppiResizeSqrPixel_16s_AC4R
 - image_resize_square_pixel, 56
- nppiResizeSqrPixel_16s_C1R
 - image_resize_square_pixel, 57
- nppiResizeSqrPixel_16s_C3R
 - image_resize_square_pixel, 57
- nppiResizeSqrPixel_16s_C4R
 - image_resize_square_pixel, 58
- nppiResizeSqrPixel_16s_P3R
 - image_resize_square_pixel, 58
- nppiResizeSqrPixel_16s_P4R
 - image_resize_square_pixel, 59
- nppiResizeSqrPixel_16u_AC4R
 - image_resize_square_pixel, 60
- nppiResizeSqrPixel_16u_C1R
 - image_resize_square_pixel, 60
- nppiResizeSqrPixel_16u_C3R
 - image_resize_square_pixel, 61
- nppiResizeSqrPixel_16u_C4R
 - image_resize_square_pixel, 61
- nppiResizeSqrPixel_16u_P3R
 - image_resize_square_pixel, 62
- nppiResizeSqrPixel_16u_P4R
 - image_resize_square_pixel, 62
- nppiResizeSqrPixel_32f_AC4R
 - image_resize_square_pixel, 63
- nppiResizeSqrPixel_32f_C1R
 - image_resize_square_pixel, 63
- nppiResizeSqrPixel_32f_C3R
 - image_resize_square_pixel, 64
- nppiResizeSqrPixel_32f_C4R
 - image_resize_square_pixel, 64
- nppiResizeSqrPixel_32f_P3R
 - image_resize_square_pixel, 65
- nppiResizeSqrPixel_32f_P4R
 - image_resize_square_pixel, 65
- nppiResizeSqrPixel_64f_AC4R
 - image_resize_square_pixel, 66
- nppiResizeSqrPixel_64f_C1R
 - image_resize_square_pixel, 66
- nppiResizeSqrPixel_64f_C3R
 - image_resize_square_pixel, 67
- nppiResizeSqrPixel_64f_C4R
 - image_resize_square_pixel, 67

- image_resize_square_pixel, 67
- nppiResizeSqrPixel_64f_P3R
 - image_resize_square_pixel, 68
- nppiResizeSqrPixel_64f_P4R
 - image_resize_square_pixel, 68
- nppiResizeSqrPixel_8u_AC4R
 - image_resize_square_pixel, 69
- nppiResizeSqrPixel_8u_C1R
 - image_resize_square_pixel, 69
- nppiResizeSqrPixel_8u_C1R_Advanced
 - image_resize_square_pixel, 70
- nppiResizeSqrPixel_8u_C3R
 - image_resize_square_pixel, 70
- nppiResizeSqrPixel_8u_C4R
 - image_resize_square_pixel, 71
- nppiResizeSqrPixel_8u_P3R
 - image_resize_square_pixel, 71
- nppiResizeSqrPixel_8u_P4R
 - image_resize_square_pixel, 72
- nppiRotate_16u_AC4R
 - image_rotate, 110
- nppiRotate_16u_C1R
 - image_rotate, 111
- nppiRotate_16u_C3R
 - image_rotate, 111
- nppiRotate_16u_C4R
 - image_rotate, 112
- nppiRotate_32f_AC4R
 - image_rotate, 112
- nppiRotate_32f_C1R
 - image_rotate, 113
- nppiRotate_32f_C3R
 - image_rotate, 113
- nppiRotate_32f_C4R
 - image_rotate, 114
- nppiRotate_8u_AC4R
 - image_rotate, 114
- nppiRotate_8u_C1R
 - image_rotate, 115
- nppiRotate_8u_C3R
 - image_rotate, 115
- nppiRotate_8u_C4R
 - image_rotate, 116
- NppiSize, 239
 - height, 239
 - width, 239
- nppiWarpAffine_16u_AC4R
 - image_affine_transform, 144
- nppiWarpAffine_16u_C1R
 - image_affine_transform, 145
- nppiWarpAffine_16u_C3R
 - image_affine_transform, 145
- nppiWarpAffine_16u_C4R
 - image_affine_transform, 146
- nppiWarpAffine_16u_P3R
 - image_affine_transform, 146
- nppiWarpAffine_16u_P4R
 - image_affine_transform, 147
- nppiWarpAffine_32f_AC4R
 - image_affine_transform, 147
- nppiWarpAffine_32f_C1R
 - image_affine_transform, 148
- nppiWarpAffine_32f_C3R
 - image_affine_transform, 148
- nppiWarpAffine_32f_C4R
 - image_affine_transform, 149
- nppiWarpAffine_32f_P3R
 - image_affine_transform, 149
- nppiWarpAffine_32f_P4R
 - image_affine_transform, 150
- nppiWarpAffine_32s_AC4R
 - image_affine_transform, 150
- nppiWarpAffine_32s_C1R
 - image_affine_transform, 151
- nppiWarpAffine_32s_C3R
 - image_affine_transform, 151
- nppiWarpAffine_32s_C4R
 - image_affine_transform, 152
- nppiWarpAffine_32s_P3R
 - image_affine_transform, 152
- nppiWarpAffine_32s_P4R
 - image_affine_transform, 153
- nppiWarpAffine_64f_AC4R
 - image_affine_transform, 153
- nppiWarpAffine_64f_C1R
 - image_affine_transform, 154
- nppiWarpAffine_64f_C3R
 - image_affine_transform, 154
- nppiWarpAffine_64f_C4R
 - image_affine_transform, 155
- nppiWarpAffine_64f_P3R
 - image_affine_transform, 155
- nppiWarpAffine_64f_P4R
 - image_affine_transform, 156
- nppiWarpAffine_8u_AC4R
 - image_affine_transform, 156
- nppiWarpAffine_8u_C1R
 - image_affine_transform, 157
- nppiWarpAffine_8u_C3R
 - image_affine_transform, 157
- nppiWarpAffine_8u_C4R
 - image_affine_transform, 158
- nppiWarpAffine_8u_P3R
 - image_affine_transform, 158
- nppiWarpAffine_8u_P4R
 - image_affine_transform, 159
- nppiWarpAffineBack_16u_AC4R
 - image_affine_transform, 159

- nppiWarpAffineBack_16u_C1R
image_affine_transform, 160
- nppiWarpAffineBack_16u_C3R
image_affine_transform, 160
- nppiWarpAffineBack_16u_C4R
image_affine_transform, 161
- nppiWarpAffineBack_16u_P3R
image_affine_transform, 161
- nppiWarpAffineBack_16u_P4R
image_affine_transform, 162
- nppiWarpAffineBack_32f_AC4R
image_affine_transform, 162
- nppiWarpAffineBack_32f_C1R
image_affine_transform, 163
- nppiWarpAffineBack_32f_C3R
image_affine_transform, 163
- nppiWarpAffineBack_32f_C4R
image_affine_transform, 164
- nppiWarpAffineBack_32f_P3R
image_affine_transform, 164
- nppiWarpAffineBack_32f_P4R
image_affine_transform, 165
- nppiWarpAffineBack_32s_AC4R
image_affine_transform, 165
- nppiWarpAffineBack_32s_C1R
image_affine_transform, 166
- nppiWarpAffineBack_32s_C3R
image_affine_transform, 166
- nppiWarpAffineBack_32s_C4R
image_affine_transform, 167
- nppiWarpAffineBack_32s_P3R
image_affine_transform, 167
- nppiWarpAffineBack_32s_P4R
image_affine_transform, 168
- nppiWarpAffineBack_8u_AC4R
image_affine_transform, 168
- nppiWarpAffineBack_8u_C1R
image_affine_transform, 169
- nppiWarpAffineBack_8u_C3R
image_affine_transform, 169
- nppiWarpAffineBack_8u_C4R
image_affine_transform, 170
- nppiWarpAffineBack_8u_P3R
image_affine_transform, 170
- nppiWarpAffineBack_8u_P4R
image_affine_transform, 171
- nppiWarpAffineQuad_16u_AC4R
image_affine_transform, 171
- nppiWarpAffineQuad_16u_C1R
image_affine_transform, 172
- nppiWarpAffineQuad_16u_C3R
image_affine_transform, 172
- nppiWarpAffineQuad_16u_C4R
image_affine_transform, 173
- nppiWarpAffineQuad_16u_P3R
image_affine_transform, 173
- nppiWarpAffineQuad_16u_P4R
image_affine_transform, 174
- nppiWarpAffineQuad_32f_AC4R
image_affine_transform, 174
- nppiWarpAffineQuad_32f_C1R
image_affine_transform, 175
- nppiWarpAffineQuad_32f_C3R
image_affine_transform, 175
- nppiWarpAffineQuad_32f_C4R
image_affine_transform, 176
- nppiWarpAffineQuad_32f_P3R
image_affine_transform, 176
- nppiWarpAffineQuad_32f_P4R
image_affine_transform, 177
- nppiWarpAffineQuad_32s_AC4R
image_affine_transform, 177
- nppiWarpAffineQuad_32s_C1R
image_affine_transform, 178
- nppiWarpAffineQuad_32s_C3R
image_affine_transform, 178
- nppiWarpAffineQuad_32s_C4R
image_affine_transform, 179
- nppiWarpAffineQuad_32s_P3R
image_affine_transform, 179
- nppiWarpAffineQuad_32s_P4R
image_affine_transform, 180
- nppiWarpAffineQuad_8u_AC4R
image_affine_transform, 180
- nppiWarpAffineQuad_8u_C1R
image_affine_transform, 181
- nppiWarpAffineQuad_8u_C3R
image_affine_transform, 181
- nppiWarpAffineQuad_8u_C4R
image_affine_transform, 182
- nppiWarpAffineQuad_8u_P3R
image_affine_transform, 182
- nppiWarpAffineQuad_8u_P4R
image_affine_transform, 183
- nppiWarpPerspective_16u_AC4R
image_perspective_transforms, 193
- nppiWarpPerspective_16u_C1R
image_perspective_transforms, 194
- nppiWarpPerspective_16u_C3R
image_perspective_transforms, 194
- nppiWarpPerspective_16u_C4R
image_perspective_transforms, 195
- nppiWarpPerspective_16u_P3R
image_perspective_transforms, 195
- nppiWarpPerspective_16u_P4R
image_perspective_transforms, 196
- nppiWarpPerspective_32f_AC4R
image_perspective_transforms, 196

- nppiWarpPerspective_32f_C1R
 - image_perspective_transforms, 197
- nppiWarpPerspective_32f_C3R
 - image_perspective_transforms, 197
- nppiWarpPerspective_32f_C4R
 - image_perspective_transforms, 198
- nppiWarpPerspective_32f_P3R
 - image_perspective_transforms, 198
- nppiWarpPerspective_32f_P4R
 - image_perspective_transforms, 199
- nppiWarpPerspective_32s_AC4R
 - image_perspective_transforms, 199
- nppiWarpPerspective_32s_C1R
 - image_perspective_transforms, 200
- nppiWarpPerspective_32s_C3R
 - image_perspective_transforms, 200
- nppiWarpPerspective_32s_C4R
 - image_perspective_transforms, 201
- nppiWarpPerspective_32s_P3R
 - image_perspective_transforms, 201
- nppiWarpPerspective_32s_P4R
 - image_perspective_transforms, 201
- nppiWarpPerspective_8u_AC4R
 - image_perspective_transforms, 202
- nppiWarpPerspective_8u_C1R
 - image_perspective_transforms, 202
- nppiWarpPerspective_8u_C3R
 - image_perspective_transforms, 203
- nppiWarpPerspective_8u_C4R
 - image_perspective_transforms, 203
- nppiWarpPerspective_8u_P3R
 - image_perspective_transforms, 204
- nppiWarpPerspective_8u_P4R
 - image_perspective_transforms, 204
- nppiWarpPerspectiveBack_16u_AC4R
 - image_perspective_transforms, 205
- nppiWarpPerspectiveBack_16u_C1R
 - image_perspective_transforms, 205
- nppiWarpPerspectiveBack_16u_C3R
 - image_perspective_transforms, 206
- nppiWarpPerspectiveBack_16u_C4R
 - image_perspective_transforms, 206
- nppiWarpPerspectiveBack_16u_P3R
 - image_perspective_transforms, 207
- nppiWarpPerspectiveBack_16u_P4R
 - image_perspective_transforms, 207
- nppiWarpPerspectiveBack_32f_AC4R
 - image_perspective_transforms, 208
- nppiWarpPerspectiveBack_32f_C1R
 - image_perspective_transforms, 208
- nppiWarpPerspectiveBack_32f_C3R
 - image_perspective_transforms, 209
- nppiWarpPerspectiveBack_32f_C4R
 - image_perspective_transforms, 209
- nppiWarpPerspectiveBack_32f_P3R
 - image_perspective_transforms, 210
- nppiWarpPerspectiveBack_32f_P4R
 - image_perspective_transforms, 210
- nppiWarpPerspectiveBack_32s_AC4R
 - image_perspective_transforms, 211
- nppiWarpPerspectiveBack_32s_C1R
 - image_perspective_transforms, 211
- nppiWarpPerspectiveBack_32s_C3R
 - image_perspective_transforms, 212
- nppiWarpPerspectiveBack_32s_C4R
 - image_perspective_transforms, 212
- nppiWarpPerspectiveBack_32s_P3R
 - image_perspective_transforms, 213
- nppiWarpPerspectiveBack_32s_P4R
 - image_perspective_transforms, 213
- nppiWarpPerspectiveBack_8u_AC4R
 - image_perspective_transforms, 214
- nppiWarpPerspectiveBack_8u_C1R
 - image_perspective_transforms, 214
- nppiWarpPerspectiveBack_8u_C3R
 - image_perspective_transforms, 215
- nppiWarpPerspectiveBack_8u_C4R
 - image_perspective_transforms, 215
- nppiWarpPerspectiveBack_8u_P3R
 - image_perspective_transforms, 216
- nppiWarpPerspectiveBack_8u_P4R
 - image_perspective_transforms, 216
- nppiWarpPerspectiveQuad_16u_AC4R
 - image_perspective_transforms, 217
- nppiWarpPerspectiveQuad_16u_C1R
 - image_perspective_transforms, 217
- nppiWarpPerspectiveQuad_16u_C3R
 - image_perspective_transforms, 218
- nppiWarpPerspectiveQuad_16u_C4R
 - image_perspective_transforms, 218
- nppiWarpPerspectiveQuad_16u_P3R
 - image_perspective_transforms, 219
- nppiWarpPerspectiveQuad_16u_P4R
 - image_perspective_transforms, 219
- nppiWarpPerspectiveQuad_32f_AC4R
 - image_perspective_transforms, 220
- nppiWarpPerspectiveQuad_32f_C1R
 - image_perspective_transforms, 220
- nppiWarpPerspectiveQuad_32f_C3R
 - image_perspective_transforms, 221
- nppiWarpPerspectiveQuad_32f_C4R
 - image_perspective_transforms, 221
- nppiWarpPerspectiveQuad_32f_P3R
 - image_perspective_transforms, 222
- nppiWarpPerspectiveQuad_32f_P4R
 - image_perspective_transforms, 222
- nppiWarpPerspectiveQuad_32s_AC4R
 - image_perspective_transforms, 223

- nppiWarpPerspectiveQuad_32s_C1R
 - image_perspective_transforms, 223
- nppiWarpPerspectiveQuad_32s_C3R
 - image_perspective_transforms, 224
- nppiWarpPerspectiveQuad_32s_C4R
 - image_perspective_transforms, 224
- nppiWarpPerspectiveQuad_32s_P3R
 - image_perspective_transforms, 225
- nppiWarpPerspectiveQuad_32s_P4R
 - image_perspective_transforms, 225
- nppiWarpPerspectiveQuad_8u_AC4R
 - image_perspective_transforms, 226
- nppiWarpPerspectiveQuad_8u_C1R
 - image_perspective_transforms, 226
- nppiWarpPerspectiveQuad_8u_C3R
 - image_perspective_transforms, 227
- nppiWarpPerspectiveQuad_8u_C4R
 - image_perspective_transforms, 227
- nppiWarpPerspectiveQuad_8u_P3R
 - image_perspective_transforms, 228
- nppiWarpPerspectiveQuad_8u_P4R
 - image_perspective_transforms, 228
- NppLibraryVersion, 240
 - build, 240
 - major, 240
 - minor, 240
- NppRoundMode
 - typedefs_npp, 42
- nppSetStream
 - core_npp, 29
- NppStatus
 - typedefs_npp, 42
- NppsZCType
 - typedefs_npp, 44
- nppZCC
 - typedefs_npp, 45
- nppZCR
 - typedefs_npp, 45
- nppZCxor
 - typedefs_npp, 45
- numClassifiers
 - NppiHaarClassifier_32f, 236
- Perspective Transform, 184
- re
 - NPP_ALIGN_16, 232
 - NPP_ALIGN_8, 233, 234
- Remap, 86
- Resize, 74
- ResizeSqrPixel, 52
- Rotate, 108
- typedefs_npp
 - NPP_AFFINE_QUAD_INCORRECT_WARNING, 44
 - NPP_ALG_HINT_ACCURATE, 39
 - NPP_ALG_HINT_FAST, 39
 - NPP_ALG_HINT_NONE, 39
 - NPP_ALIGNMENT_ERROR, 43
 - NPP_ANCHOR_ERROR, 43
 - NPP_BAD_ARGUMENT_ERROR, 44
 - NPP_BORDER_CONSTANT, 40
 - NPP_BORDER_MIRROR, 40
 - NPP_BORDER_NONE, 40
 - NPP_BORDER_REPLICATE, 40
 - NPP_BORDER_UNDEFINED, 40
 - NPP_BORDER_WRAP, 40
 - NPP_BOTH_AXIS, 40
 - NPP_CHANNEL_ERROR, 43
 - NPP_CHANNEL_ORDER_ERROR, 43
 - NPP_CMP_EQ, 39
 - NPP_CMP_GREATER, 39
 - NPP_CMP_GREATER_EQ, 39
 - NPP_CMP_LESS, 38
 - NPP_CMP_LESS_EQ, 38
 - NPP_COEFFICIENT_ERROR, 43
 - NPP_COI_ERROR, 43
 - NPP_CONTEXT_MATCH_ERROR, 44
 - NPP_CORRUPTED_DATA_ERROR, 43
 - NPP_CUDA_1_0, 39
 - NPP_CUDA_1_1, 39
 - NPP_CUDA_1_2, 39
 - NPP_CUDA_1_3, 39
 - NPP_CUDA_2_0, 39
 - NPP_CUDA_2_1, 39
 - NPP_CUDA_3_0, 39
 - NPP_CUDA_3_2, 39
 - NPP_CUDA_3_5, 39
 - NPP_CUDA_3_7, 39
 - NPP_CUDA_5_0, 39
 - NPP_CUDA_5_2, 39
 - NPP_CUDA_5_3, 39
 - NPP_CUDA_6_0, 39
 - NPP_CUDA_KERNEL_EXECUTION_ERROR, 43
 - NPP_CUDA_NOT_CAPABLE, 39
 - NPP_CUDA_UNKNOWN_VERSION, 39
 - NPP_DATA_TYPE_ERROR, 44
 - NPP_DIVIDE_BY_ZERO_ERROR, 44
 - NPP_DIVIDE_BY_ZERO_WARNING, 44
 - NPP_DIVISOR_ERROR, 43
 - NPP_DOUBLE_SIZE_WARNING, 44
 - NPP_ERROR, 44
 - NPP_ERROR_RESERVED, 44
 - NPP_FFT_FLAG_ERROR, 44
 - NPP_FFT_ORDER_ERROR, 44
 - NPP_FILTER_SCHARR, 40

- NPP_FILTER_SOBEL, 40
- NPP_HAAR_CLASSIFIER_PIXEL_-
MATCH_ERROR, 43
- NPP_HISTOGRAM_NUMBER_OF_-
LEVELS_ERROR, 43
- NPP_HORIZONTAL_AXIS, 40
- NPP_INTERPOLATION_ERROR, 44
- NPP_INVALID_DEVICE_POINTER_-
ERROR, 43
- NPP_INVALID_HOST_POINTER_ERROR,
43
- NPP_LUT_NUMBER_OF_LEVELS_-
ERROR, 43
- NPP_LUT_PALETTE_BITSIZE_ERROR, 43
- NPP_MASK_SIZE_11_X_11, 41
- NPP_MASK_SIZE_13_X_13, 41
- NPP_MASK_SIZE_15_X_15, 41
- NPP_MASK_SIZE_1_X_3, 41
- NPP_MASK_SIZE_1_X_5, 41
- NPP_MASK_SIZE_3_X_1, 41
- NPP_MASK_SIZE_3_X_3, 41
- NPP_MASK_SIZE_5_X_1, 41
- NPP_MASK_SIZE_5_X_5, 41
- NPP_MASK_SIZE_7_X_7, 41
- NPP_MASK_SIZE_9_X_9, 41
- NPP_MASK_SIZE_ERROR, 43
- NPP_MEMCPY_ERROR, 43
- NPP_MEMFREE_ERROR, 43
- NPP_MEMORY_ALLOCATION_ERR, 44
- NPP_MEMSET_ERROR, 43
- NPP_MIRROR_FLIP_ERROR, 44
- NPP_MISALIGNED_DST_ROI_WARNING,
44
- NPP_MOMENT_00_ZERO_ERROR, 44
- NPP_NO_ERROR, 44
- NPP_NO_MEMORY_ERROR, 44
- NPP_NO_OPERATION_WARNING, 44
- NPP_NOT_EVEN_STEP_ERROR, 43
- NPP_NOT_IMPLEMENTED_ERROR, 44
- NPP_NOT_SUFFICIENT_COMPUTE_-
CAPABILITY, 43
- NPP_NOT_SUPPORTED_MODE_ERROR,
43
- NPP_NULL_POINTER_ERROR, 44
- NPP_NUMBER_OF_CHANNELS_ERROR,
43
- NPP_OUT_OFF_RANGE_ERROR, 44
- NPP_OVERFLOW_ERROR, 43
- NPP_QUADRANGLE_ERROR, 43
- NPP_QUALITY_INDEX_ERROR, 43
- NPP_RANGE_ERROR, 44
- NPP_RECTANGLE_ERROR, 43
- NPP_RESIZE_FACTOR_ERROR, 44
- NPP_RESIZE_NO_OPERATION_ERROR,
43
- NPP_RND_FINANCIAL, 42
- NPP_RND_NEAR, 42
- NPP_RND_ZERO, 42
- NPP_ROUND_MODE_NOT_-
SUPPORTED_ERROR, 43
- NPP_ROUND_NEAREST_TIES_AWAY_-
FROM_ZERO, 42
- NPP_ROUND_NEAREST_TIES_TO_EVEN,
42
- NPP_ROUND_TOWARD_ZERO, 42
- NPP_SCALE_RANGE_ERROR, 44
- NPP_SIZE_ERROR, 44
- NPP_STEP_ERROR, 44
- NPP_STRIDE_ERROR, 43
- NPP_SUCCESS, 44
- NPP_TEXTURE_BIND_ERROR, 43
- NPP_THRESHOLD_ERROR, 44
- NPP_THRESHOLD_NEGATIVE_LEVEL_-
ERROR, 44
- NPP_VERTICAL_AXIS, 40
- NPP_WRONG_INTERSECTION_QUAD_-
WARNING, 44
- NPP_WRONG_INTERSECTION_ROI_-
ERROR, 43
- NPP_WRONG_INTERSECTION_ROI_-
WARNING, 44
- NPP_ZC_MODE_NOT_SUPPORTED_-
ERROR, 43
- NPP_ZERO_MASK_VALUE_ERROR, 43
- NPPI_BAYER_BGGR, 40
- NPPI_BAYER_GBRG, 40
- NPPI_BAYER_GRBG, 40
- NPPI_BAYER_RGGG, 40
- NPPI_INTER_CUBIC, 41
- NPPI_INTER_CUBIC2P_B05C03, 41
- NPPI_INTER_CUBIC2P_BSPLINE, 41
- NPPI_INTER_CUBIC2P_CATMULLROM,
41
- NPPI_INTER_LANCZOS, 41
- NPPI_INTER_LANCZOS3_ADVANCED, 41
- NPPI_INTER_LINEAR, 41
- NPPI_INTER_NN, 41
- NPPI_INTER_SUPER, 41
- NPPI_INTER_UNDEFINED, 41
- NPPI_OP_ALPHA_ATOP, 39
- NPPI_OP_ALPHA_ATOP_PREMUL, 40
- NPPI_OP_ALPHA_IN, 39
- NPPI_OP_ALPHA_IN_PREMUL, 40
- NPPI_OP_ALPHA_OUT, 39
- NPPI_OP_ALPHA_OUT_PREMUL, 40
- NPPI_OP_ALPHA_OVER, 39
- NPPI_OP_ALPHA_OVER_PREMUL, 40

- NPPI_OP_ALPHA_PLUS, 39
- NPPI_OP_ALPHA_PLUS_PREMUL, 40
- NPPI_OP_ALPHA_PREMUL, 40
- NPPI_OP_ALPHA_XOR, 39
- NPPI_OP_ALPHA_XOR_PREMUL, 40
- NPPI_SMOOTH_EDGE, 41
- nppiACTable, 41
- nppiDCTable, 41
- nppiNormInf, 42
- nppiNormL1, 42
- nppiNormL2, 42
- nppZCC, 45
- nppZCR, 45
- nppZCxor, 45
- typedefs_npp
 - NPP_MAX_16S, 37
 - NPP_MAX_16U, 37
 - NPP_MAX_32S, 37
 - NPP_MAX_32U, 37
 - NPP_MAX_64S, 37
 - NPP_MAX_64U, 37
 - NPP_MAX_8S, 37
 - NPP_MAX_8U, 37
 - NPP_MAXABS_32F, 37
 - NPP_MAXABS_64F, 37
 - NPP_MIN_16S, 37
 - NPP_MIN_16U, 38
 - NPP_MIN_32S, 38
 - NPP_MIN_32U, 38
 - NPP_MIN_64S, 38
 - NPP_MIN_64U, 38
 - NPP_MIN_8S, 38
 - NPP_MIN_8U, 38
 - NPP_MINABS_32F, 38
 - NPP_MINABS_64F, 38
 - NppCmpOp, 38
 - NppGpuComputeCapability, 39
 - NppHintAlgorithm, 39
 - NppiAlphaOp, 39
 - NppiAxis, 40
 - NppiBayerGridPosition, 40
 - NppiBorderType, 40
 - NppiDifferentialKernel, 40
 - NppiHuffmanTableType, 40
 - NppiInterpolationMode, 41
 - NppiMaskSize, 41
 - NppiNorm, 41
 - NppRoundMode, 42
 - NppStatus, 42
 - NppsZCType, 44
- width
 - NppiRect, 238
 - NppiSize, 239

- x
 - NppiPoint, 237
 - NppiRect, 238
- y
 - NppiPoint, 237
 - NppiRect, 238