



PGI<sup>®</sup> Server  
PGI<sup>®</sup> Workstation  
Release Notes  
Release 2010

**The Portland Group<sup>®</sup>**

While every precaution has been taken in the preparation of this document, The Portland Group® (PGI®), a wholly-owned subsidiary of STMicroelectronics, Inc., makes no warranty for the use of its products and assumes no responsibility for any errors that may appear, or for damages resulting from the use of the information contained herein. The Portland Group retains the right to make changes to this information at any time, without notice. The software described in this document is distributed under license from STMicroelectronics and/or The Portland Group and may be used or copied only in accordance with the terms of the license agreement ("EULA").

PGI Workstation, PGI Server, PGI Accelerator, PGF95, PGF90, PGFORTRAN, and PGI Unified Binary are trademarks; and PGI, PGHPE, PGF77, PGCC, PGC++, PGI Visual Fortran, PVE, PGI CDK, Cluster Development Kit, PGPROF, PGDBG, and The Portland Group are registered trademarks of The Portland Group Incorporated.

No part of this document may be reproduced or transmitted in any form or by any means, for any purpose other than the purchaser's or the end user's personal use without the express written permission of STMicroelectronics and/or The Portland Group.

**PGI® Server PGI® Workstation Release Notes**  
Copyright © 2010 The Portland Group® and STMicroelectronics, Inc.  
All rights reserved.

Printed in the United States of America

First Printing: Release 2010, version 10.0, November 2009

Second Printing: Release 2010, version 10.1, January 2010

Third Printing: Release 2010, version 10.2, February 2010

Fourth Printing: Release 2010, version 10.3, March 2010

Fifth Printing: Release 2010, version 10.4, April 2010

Sixth Printing: Release 2010, version 10.5, May 2010

Seventh Printing: Release 2010, version 10.6, June 2010

Eighth Printing: Release 2010, version 10.8, August 2010

Ninth Printing: Release 2010, version 10.9, September 2010

Technical support: [trs@pgroup.com](mailto:trs@pgroup.com)

Sales: [sales@pgroup.com](mailto:sales@pgroup.com)

Web: [www.pgroup.com](http://www.pgroup.com)

# Contents

<b>1. Release Overview</b> .....	1
PGI Workstation and PGI Server .....	1
Licensing Terminology .....	1
Workstation and Server Comparison .....	1
Product Overview .....	2
Terms and Definitions .....	2
Supported Platforms .....	3
<b>2. New or Modified Features</b> .....	5
What's New in PGI Release 2010 .....	5
10.9 Additions .....	5
10.8 Additions .....	5
10.6 Additions .....	6
10.5 Additions .....	7
10.4 Additions .....	8
10.3 Additions .....	9
2010 Additions Prior to 10.3 .....	10
Getting Started .....	11
Using -fast, -fastsse, and Other Performance-Enhancing Options .....	11
New or Modified Compiler Options .....	12
C++ Compilation Requirements .....	14
Fortran Enhancements .....	14
Enhanced Fortran Interoperability with C .....	14
New or Modified Fortran Statements .....	15
New or Modified Fortran Intrinsic Functions .....	15
New Fortran Intrinsic Modules .....	16
Fortran I/O Enhancements .....	19
New or Modified Runtime Library Routines .....	19
New or Modified Tools Support .....	19
New or Modified PVF Samples .....	20
Library Interfaces .....	20
<b>3. PGI Workstation 2010</b> .....	21

PGI Workstation 2010 for Linux .....	21
Java Runtime Environment (JRE) .....	21
PGI Workstation 2010 for Windows .....	21
PGI Workstation 2010 for Mac OS X .....	21
<b>4. PGI Accelerator .....</b>	<b>23</b>
Components .....	23
Availability .....	23
User-directed Accelerator Programming .....	23
Features Not Covered or Implemented .....	24
System Requirements .....	24
Supported Processors and GPUs .....	24
Installation and Licensing .....	24
Running an Accelerator Program .....	24
PGI Accelerator Compilers Runtime Libraries .....	24
Environment Variables .....	25
Applicable Command Line Options .....	26
PGI Unified Binary for Accelerators .....	27
Profiling Accelerator Kernels .....	28
Supported Intrinsic .....	28
<b>5. Distribution and Deployment .....</b>	<b>29</b>
Application Deployment and Redistributables .....	29
PGI Redistributables .....	29
Linux Redistributables .....	30
Microsoft Redistributables .....	30
<b>6. The PGI Windows CDK .....</b>	<b>31</b>
Build MPI Applications with MSMPI .....	31
Using MSMPI libraries .....	31
Generate MPI Profile Data .....	31
Debug MSMPI Applications with PGDBG .....	32
Bash Shell Example .....	32
DOS Shell Example .....	33
<b>7. Troubleshooting Tips and Known Limitations .....</b>	<b>35</b>
General Issues .....	35
Platform-specific Issues .....	36
Linux .....	36
Apple Mac OS X .....	36
Windows .....	36
PGDBG-related Issues .....	37
PGPROF-related Issues .....	37
CUDA Fortran Toolkit Issues .....	38
Corrections .....	38
<b>8. Contact Information .....</b>	<b>39</b>

# Chapter 1. Release Overview

Welcome to Release 2010 of *PGI Workstation* and *PGI Server*, a set of Fortran, C, and C++ compilers and development tools for 32-bit and 64-bit x86-compatible processor-based workstations and servers running versions of the Linux, Windows, and Mac OS operating systems.

These release notes apply to all workstation-class and server-class compiler products from The Portland Group.

This document describes changes between previous releases and Release 2010 of the PGI compilers, as well as late-breaking information not included in the current printing of the PGI User's Guide.

## PGI Workstation and PGI Server

The PGI Workstation and PGI Server include exactly the same software. The difference in the two is the manner in which the user gets a license to run the software.

## Licensing Terminology

The PGI compilers and tools are license-managed. It is useful to have common terminology. These two terms are often confused, so they are clarified here:

- **License** - a legal agreement between ST and PGI end-users, to which users assent upon installation of any PGI product. The terms of the License are kept up-to-date in documents on [pgroup.com](http://pgroup.com) and in the \$PGI/<platform>/<rel\_number> directory of every PGI SW installation.
- **License keys** - ASCII text strings that enable use of the PGI software and are intended to enforce the terms of the License. License keys are generated by each PGI end-user on [pgroup.com](http://pgroup.com) using a unique hostid and are typically stored in a file called `license.dat` that is accessible to the systems for which the PGI software is licensed at a given site.

## Workstation and Server Comparison

- All workstation-class compilers and tools products from The Portland Group, such as PGI Fortran Workstation, are subsets of the PGI Workstation Complete product. These workstation-class products provide a node-locked single-user license, meaning one user at a time can compile on the one system on which the PGI Workstation compilers and tools are installed. The product and license server are on the same local machine.

- PGI Server products are offered in configurations identical to the workstation-class products, but provide network-floating multi-user licenses. This means that two or more users can use the PGI compilers and tools concurrently on any compatible system networked to the system on which the PGI Server compilers are installed. There can be multiple installations on machines connected to the server and the users can use the product concurrently, provided they are issued a license key.

## Product Overview

Release 2010 of *PGI Workstation* and *PGI Server* includes the following components:

- PGFORTRAN native OpenMP and auto-parallelizing Fortran 90/95/2003 compiler.
- PGF77 native OpenMP and auto-parallelizing FORTRAN 77 compiler.
- PGHPF data parallel High Performance Fortran compiler.

### Note

---

PGHPF is supported only on Linux platforms.

- PGCC native OpenMP and auto-parallelizing ANSI C99 and K&R C compiler.
- PGC++ native OpenMP and auto-parallelizing ANSI C++ compiler.
- PGPROF MPI, OpenMP, and multi-thread graphical profiler.
- PGDBG MPI, OpenMP, and multi-thread graphical debugger.
- MPICH MPI libraries, version 1.2.7, for both 32-bit and 64-bit development environments (Linux only).

### Note

---

64-bit linux86-64 MPI messages are limited to <2GB size each.

- Online documentation in PDF, HTML and man page formats.
- A UNIX-like shell environment for Win32 and Win64 platforms.

Depending on the product configuration you purchased, you may not have licensed all of the above components.

The MPI profiler and debugger included with PGI Workstation are limited to processes on a single node. PGI Workstation can be installed on a single computer, and that computer can be used to develop, debug, and profile MPI applications. The PGI CDK Cluster Development Kit supports general development on clusters.

## Terms and Definitions

These release notes contain a number of terms and definitions with which you may or may not be familiar. If you encounter a term in these notes with which you are not familiar, please refer to the online glossary at

[www.pgroup.com/support/definitions.htm](http://www.pgroup.com/support/definitions.htm)

These two terms are used throughout the documentation to reflect groups of processors:

- AMD64 – a 64-bit processor from AMD designed to be binary compatible with 32-bit x86 processors, and incorporating new features such as additional registers and 64-bit addressing support for improved performance and greatly increased memory range. This term includes the AMD™ Athlon64™, AMD Opteron™, AMD Turion™, AMD Barcelona, AMD Shanghai, and AMD Istanbul processors.
- Intel 64 – a 64-bit IA32 processor with Extended Memory 64-bit Technology extensions designed to be binary compatible with AMD64 processors. This includes Intel Pentium 4, Intel Xeon, Intel Core 2, Intel Penryn, and Intel Core i7 (Nehalem) processors.

## Supported Platforms

There are six platforms supported by the PGI Workstation and PGI Server compilers and tools:

- *32-bit Linux* - supported on *32-bit Linux operating systems* running on either a 32-bit *x86* compatible or an *x64* compatible processor.
- *64-bit/32-bit Linux* – includes all features and capabilities of the 32-bit Linux version, and is also supported on *64-bit Linux operating systems* running an *x64* compatible processor.
- *32-bit Windows* – supported on *32-bit Windows operating systems* running on either a 32-bit *x86* compatible or an *x64* compatible processor.
- *64-bit/32-bit Windows* – includes all features and capabilities of the 32-bit Windows version, and is also supported on *64-bit Windows operating systems* running an *x64* compatible processor.
- *32-bit Apple Mac OS X* – supported on 32-bit Apple Mac operating systems running on either a 32-bit or 64-bit Intel-based Mac system.
- *64-bit Apple Mac OS X* – supported on 64-bit Apple Mac operating systems running on a 64-bit Intel-based Mac system.



# Chapter 2. New or Modified Features

This chapter provides information about the new or modified features of Release 2010 of the PGI compilers and tools as compared to prior releases.

## What's New in PGI Release 2010

### 10.9 Additions

- Updated the version of **MPICH2** used in the CDK `q| .+/.m..`
- Additional **PGI Visual Fortran** features in 10.9 include a new property page that facilitates building and linking against specific libraries, such as **Intel's Math Kernel Library**, **AMD's Core Math Library**, or **Rogue Wave's IMSL numerical library**.

### 10.8 Additions

- Additional **Fortran 2003 features** in 10.8 include:
  - **Associate Construct** - associates a name either with a variable or with the value of an expression for the duration of a block. When the block is executed, the `associate-name` remains associated with the variable or retains the value specified, taking its type, type parameters, and rank from the association.

For more information and an example, refer to Chapter 3 of the PGI User's Guide.

- **Sourced Allocation** for polymorphic types (no unlimited polymorphics) - uses the `source=` clause in the `allocate` statement to take the type, type parameters, and values from another variable or expression instead of allocating explicitly specified types and type parameters. The allocated variable has the same dynamic type, parameters, and value as the source variable.

```
subroutine example(x)
  class(t), allocate :: a
  class(t)           :: x
  allocate(a, source=x)
```

- **PGI Accelerator x64+GPU** native Fortran 95/03 and C99 compilers, and **PGI CUDA Fortran** now support the CUDA 3.1 Toolkit. This CUDA 3.1 Toolkit is an update to the CUDA 3.0 Toolkit, so CUDA 3.0 Toolkit is no longer shipped with the PGI compilers and tools, though you may leave it on your system if it exists from a previous installation.

Due to changes in the CUDA 3.1 API, CUDA Fortran host programs should be recompiled, as the PGI 10.8 CUDA Fortran runtime libraries are not compatible with previous CUDA Fortran releases.

- Additional **PGI Visual Fortran features** in 10.8 include a property that supports specifying the CUDA 3.1 toolkit. When `Enable CUDA Fortran` is set to `Yes`, you can now use the `Fortran|Language|CUDA Fortran Toolkit` property to specify version 3.1 of the CUDA toolkit as the one targeted by the compilers. You can also access this version of the toolkit from the `Fortran|Target Accelerators|NVIDIA: CUDA Toolkit` property.

## 10.6 Additions

- Additional **Fortran 2003 features** in 10.6 include:
  - deferred type-bound procedures - procedures that are defined for the purpose of defining a base type for a future extension.
  - `NON_OVERRIDABLE` attribute - specifies that the type-bound procedure cannot be overridden during type extension.
  - `PRIVATE` statement for type-bound procedures - specifies the accessibility of the type-bound procedure. The accessibility of components within the derived types is separate from the accessibility of the type-bound procedures. By default, a type-bound procedure is `PUBLIC`, unless a `PRIVATE` statement is in the type's procedure section or it is explicitly declared to be `PRIVATE`.
  - `PRIVATE` and `PUBLIC` attributes - determine where the type-bound procedures can be referenced. The default is `PUBLIC`, which allows the procedures to be referenced anywhere in the program having that type of variable. If the procedure is `PRIVATE`, it can only be referenced from within the module in which it is defined.

Mixed component accessibility allows some components of a type to be `PRIVATE` while others are `PUBLIC`. The `PRIVATE` attribute sets the default accessibility of the component, but can be overridden or confirmed in the component definition.

- `ASYNCHRONOUS` statement and attribute - warn the compiler that incorrect results might occur for optimizations involving movement of code across wait statements, or statements that cause wait operations.
- `ABSTRACT` and `DEFERRED` - are placeholders. When `abstract` is specified, the compiler warns if any variable is declared of that type. When `deferred` is specified for a procedure, the compiler warns if the procedure is not overridden.
- The IEEE standard intrinsic module `ieee_features` supports specification of essential IEEE features. It provides access to one derived type and a collection of named constants of this type that affect the manner in which code is compiled in the scoping units.
- Enhancements to I/O that include the following. For more details on these features, refer to [“Fortran I/O Enhancements,” on page 19](#).
  - I/O Decimal specifier - Ability to use a comma instead of a decimal point in input and output. Support for this feature is through the `DECIMAL=scalar_char` clause or through use of the `dp` and `dc` descriptors.

- I/O Encoding specifier - Ability to specify input/output encoding using the `encoding=` specifier on the `OPEN` or `INQUIRE` statements.
- Intrinsic functions `max`, `min`, `maxloc`, `minloc`, `maxval`, and `minval` now accept arguments of type `character`.
- Statements `allocate` and `deallocate` now accept an `errmsg=` clause. The clause takes a scalar default character string variable. This variable is assigned an explanatory message if an error condition occurs.
- The `allocate` statement now accepts the `source=` clause. Instead of allocating a variable with an explicitly specified type and type parameter, it is now possible to take the type, type parameters, and value from another variable or expression.

Specifying a polymorphic variable for the `source=` clause is not yet supported.

- **PGI Accelerator x64+GPU native Fortran 95/03 and C99 compilers, and PGI CUDA Fortran** now support the following CUDA built-in functions: **`synctreads_count`**, **`synctreads_and`**, **`synctreads_or`**, **`threadfence`**, **`threadfence_block`**, **`threadfence_system`**, **`ballot`**. In addition, CUDA Fortran device code now supports the functions **`popcnt()`**, **`poppar()`**, and **`leadz()`**.
- **PGPROF** now supports PGI Accelerator model and CUDA Fortran profiling.
- Additional **PGI Visual Fortran features** in 10.6 include:
  - **Support for Visual Studio 2010.** PGI Visual Fortran is completely integrated with Microsoft's recent release of Visual Studio 2010.
  - Three additional **PVF Samples** are available:

```
gpu/AccelPM_Matmul
gpu/CUDAFor_Matmul
interlanguage/vcmain_calling_pvf.dll
```

For more detailed information on these samples, refer to [“New or Modified PVF Samples,”](#) on [page 20](#).

## 10.5 Additions

- Additional **Fortran 2003 features** in 10.5 include:
  - Type-bound procedures - procedures that are invoked through an object and the actual procedure executed depends on the dynamic type of the object.
  - `PASS` and `NOPASS` attributes - allow the procedure to specify to which argument, if any, the invoking object is passed. For example, `pass(x)` passes it to dummy argument `x`, while `nopass` indicates not to pass it at all.
- **PGI Accelerator x64+GPU native Fortran 95/03 and C99 compilers, and PGI CUDA Fortran** now support the runtime library routine **`acc_get_device_num`** which returns the number of the device being used to execute an accelerator region. For a complete list of supported routines, refer to [“PGI Accelerator Compilers Runtime Libraries”](#).

- **Accelerator Profiling:** If you are profiling a program that uses the PGI Accelerator Model or PGI CUDA Fortran, **pgcollect** automatically collects information about accelerator performance and includes that information in the profile output for the program.

### Note

---

Inclusion of the accelerator performance information in the program's profile output occurs for both time-based sampling and, on Linux, for event-based sampling.

On some Linux systems, initialization of the CUDA driver for accelerator hardware that is in a power-save state can take a significant amount of time. You can avoid this delay in one of these ways:

- Run the `pgcudainit` program in the background, which keeps the GPU powered on and significantly reduces initialization time for subsequent programs. For more information on this approach, refer to Chapter 7 of the *PGI User's Guide*.
- Use the **pgcollect** option `-accinit` to eliminate much of the initialization overhead and to provide a more accurate profile.

```
pgcollect -time -accinit myaccelprog
```

- **PGI Visual Fortran** enhancements including: **Enhanced Variable Rollover, Watch and Quick Watch** support. Fortran-specific support for user-defined type members and array elements is improved in this release.

## 10.4 Additions

- **PGI Accelerator x64+GPU native Fortran 95/03 and C99 compilers, and PGI CUDA Fortran** now support CUDA 3.0 Toolkit and compute capability 2.0.
- To specify **CUDA compute capability 2.0**, use one of the following options:

In the Accelerator: `-ta=nvidia:cc20`

---

In CUDA Fortran: `-Mcuda=cc20`

- To specify the version of the **CUDA toolkit** that is targeted by compilers, use one of the following options:

In the Accelerator:

In the Accelerator:

---

For CUDA toolkit 3.0 `-ta=nvidia:cuda3.0` or  
`-ta=nvidia:3.0`

---

For CUDA toolkit 2.3 `-ta=nvidia:cuda2.3` or  
`-ta=nvidia:2.3`

---

## For CUDA Fortran:

---

For CUDA toolkit 3.0	<code>-Mcuda=cuda3.0</code> or <code>-Mcuda=3.0</code>
----------------------	---

---

For CUDA toolkit 2.3	<code>-Mcuda=cuda2.3</code> or <code>-Mcuda=2.3</code>
----------------------	---

---

**Note**


---

Compiling with the CUDA 3.0 toolkits generates binaries that may not work on machines with a 2.3 CUDA driver. For more information, refer to [“CUDA Fortran Toolkit Issues,”](#) on page 38.

- A **wait for kernel** option, `-ta=nvidia:[no]wait`, is available when targeting NVIDIA Accelerator; the user can specify whether to wait for the kernel to finish before continuing in the host program. The default is to wait.
- Added support for **fused multiply-add instructions in CUDA Fortran**. The user can now control the generation of fused multiply-add instructions in both the Accelerator and with CUDA Fortran. In addition to the existing `-ta=nvidia:nofma` option already available for the Accelerator, PGI 10.4 and higher support the equivalent option in CUDA Fortran: `-Mcuda=nofma`.
- Added ability to **use fast math library in CUDA Fortran**. The user can now specify to use routines from the fast math library. In addition to the existing `-ta=nvidia:fastmath` option available for the Accelerator, PGI 10.4 and higher support the equivalent option in CUDA Fortran: `-Mcuda=fastmath`.
- Added support in CUDA Fortran for using **allocatable device arrays in modules** which contain global subroutines, accessible from both the host code which uses the module, and the device code contained within the module.

### 10.3 Additions

- **Enhanced compute capabilities with CUDA in 10.3:**

The default compute capabilities target both compute capability 1.0 and 1.3. Further, beginning with 10.3, the user can specify multiple compute capabilities to be targeted.

For example, to target all four compute capabilities 1.0, 1.1, 1.2, and 1.3, use these options on the command line:

```
-Mcuda=cc10, -Mcuda=cc11, -Mcuda=cc12, -Mcuda=cc13
```

or

```
-Mcuda=cc10,cc11,cc12,cc13
```

- Additional **Fortran 2003 features** in 10.3 include:
  - Abstract interfaces
  - `IS_IOSTAT_END`, `IS_IOSTAT_EOR`, and `NEW_LINE` intrinsics
  - Object-oriented features including classes, type extensions (non-polymorphic), polymorphic entities, typed allocation, inheritance association, as well as `EXTENDS_TYPE_OF` and `SAME_TYPE_AS` intrinsics.

- New and modified statements, including: WAIT statement; blank, pad, and pos specifiers for the READ statement; delim and pos specifiers for the WRITE statement; and pending and pos specifiers for the INQUIRE statement

For more information on these features, refer to [“Fortran Enhancements,”](#) on page 14.

## 2010 Additions Prior to 10.3

- **PGI Accelerator x64+GPU native Fortran 95/03 and C99 compilers** support the full PGI Accelerator programming model v1.0 standard for directive-based GPU programming and optimization as well as several features from the v1.1 standard.
  - Supported on Linux, MacOS, and Windows
  - Device-resident data using the UPDATE directive
  - COMPLEX and DOUBLE COMPLEX data, Fortran derived types, C structs
  - Automatic GPU-side loop unrolling
  - Support for Accelerator regions nested within OpenMP parallel regions
- **PGI CUDA Fortran extensions** supported in the PGI 2010 Fortran 95/03 compiler enable explicit CUDA GPU programming
  - Declare variables in CUDA GPU device, constant or shared memory
  - Dynamically allocate page-locked pinned host memory, CUDA device main memory, constant memory and shared memory
  - Move data between host and GPU with Fortran assignment statements
  - Declare explicit CUDA grids/thread-blocks to launch GPU compute kernels
  - Support for CUDA Runtime API functions and features
  - Additional options for CUDA Fortran, such as `-Mcuda=keepgpu`, which keeps the generated GPU code for CUDA Fortran.
  - Efficient host-side emulation for easy CUDA Fortran debugging
- **Fortran 2003 incremental features** including: namelist I/O on internal files, IMPORT, pointer reshaping, procedure pointers and statement, iso\_c\_binding intrinsic module, c\_associated, c\_f\_pointer, c\_f\_procpointer, enum, move\_alloc(), iso\_fortran\_env module, optional kind to intrinsics, allocatable scalars, volatile attribute and statement, pass and nopass attributes, bind(c), value, command\_argument\_count, get\_command, get\_command\_argument, get\_environment\_variable, ieee\_exceptions module, and ieee\_arithmetic module.
- **PGC++/ PGCC (2010 C++)** new features and enhancements include:
  - The latest EDG release 4.1, with enhanced GNU and Microsoft compatibility
  - `extern` inline support by default: Multiple copies of inline functions in an executable are now removed.
  - Extended internal tables for better support of large codes, including improved BOOST support.

- C++ `-mp` thread safe exception handling.
- **Expanded Operating Systems Support** including RHEL 5, Fedora 11, SLES 11, SuSE 11.1, Ubuntu 9, Windows 7 and MacOS Snow Leopard
- **Compiler optimizations and enhancements** including:
  - OpenMP support for up to 256 cores
  - AVX code generation
  - Partial redundancy elimination
  - Executable size improvements
- **PGI Visual Fortran** enhancements including:
  - Supports launching and debugging of MSMPI programs on Windows clusters from within Visual Studio
  - Full support for the PGI Accelerator programming model
  - Support for PGI CUDA Fortran on NVIDIA CUDA-enabled GPUs
  - Includes the standalone PGPROF performance profiler with CCFF support.
  - Easier access to products through an improved Start menu entry.
  - Easier access to commands through additional Property page selections.
- **Updated Documentation** including the *PGI Users Guide*, *PGI Tools Guide*, and *PGI Fortran Reference*.

## Getting Started

By default, the PGI 2010 compilers generate code that is optimized for the type of processor on which compilation is performed, the compilation host. If you are unfamiliar with the PGI compilers and tools, a good option to use by default is `-fast` or `-fastsse`.

### Using `-fast`, `-fastsse`, and Other Performance-Enhancing Options

These aggregate options incorporate a generally optimal set of flags for targets that support SSE capability. These options incorporate optimization options to enable use of vector streaming SIMD instructions for 64-bit targets. They enable vectorization with SSE instructions, cache alignment, and flushz.

#### Note

---

The contents of the `-fast` and `-fastsse` options are host-dependent.

`-fast` and `-fastsse` typically include these options:

<code>-O2</code>	Specifies a code optimization level of 2.
<code>-Munroll=c:1</code>	Unrolls loops, executing multiple instances of the original loop during each iteration.

<code>-Mnoframe</code>	Indicates to not generate code to set up a stack frame. <b>Note.</b> With this option, a stack trace does not work.
<code>-Mlre</code>	Indicates loop-carried redundancy elimination
<code>-Mpre</code>	Indicates partial redundancy elimination

`-fast` for 64-bit targets and `-fastsse` for both 32- and 64-bit targets also typically include:

<code>-Mvect=sse</code>	Generates SSE instructions.
<code>-Mscalarsse</code>	Generates scalar SSE code with xmm registers; implies <code>-Mflushz</code> .
<code>-Mcache_align</code>	Aligns long objects on cache-line boundaries <b>Note.</b> On 32-bit systems, if one file is compiled with the <code>-Mcache_align</code> option, all files should be compiled with it. This is not true on 64-bit systems.
<code>-Mflushz</code>	Sets SSE to flush-to-zero mode.
<code>-M[no]vect</code>	Controls automatic vector pipelining.

## Note

---

For best performance on processors that support SSE instructions, use the PGFORTRAN compiler, even for FORTRAN 77 code, and the `-fastsse` option.

In addition to `-fast` and `-fastsse`, the `-Mipa=fast` option for inter-procedural analysis and optimization can improve performance. You may also be able to obtain further performance improvements by experimenting with the individual `-Mpgflag` options detailed in the PGI User's Guide, such as `-Mvect`, `-Munroll`, `-Minline`, `-Mconcur`, `-Mphi`/`-Mpfo` and so on. However, increased speeds using these options are typically application- and system-dependent. It is important to time your application carefully when using these options to ensure no performance degradations occur.

## New or Modified Compiler Options

Unknown options are treated as errors instead of warnings. This feature means it is a compiler error to pass switches that are not known to the compiler; however, you can use the switch `-noswitcherror` to issue warnings instead of errors for unknown switches.

The following compiler options have been added or modified in PGI 2010:

- `-m32` indicates to use the 32-bit compiler for the default processor type.
- `-m64` indicates to use the 64-bit compiler for the default processor type.
- `-ta=nvidia(,nvidia_suboptions),host` is a switch associated with the PGI Accelerator compilers. `-ta` defines the target architecture.

In release 2010, the `nvidia_suboptions` include:

<code>analysis</code>	Perform loop analysis only; do not generate GPU code.
<code>cc10, cc11, cc12, cc13, cc20</code>	Generate code for compute capability 1.0, 1.1, 1.2, 1.3, or 2.0 respectively.

<code>cuda2.3</code> or <code>2.3</code>	Specify the CUDA 2.3 version of the toolkit.
<code>cuda3.0</code> or <code>3.0</code>	Specify the CUDA 3.0 version of the toolkit.
<code>cuda3.1</code> or <code>3.1</code>	Specify the CUDA 3.1 version of the toolkit.
<code>fastmath</code>	Use routines from the fast math library.
<code>keepbin</code>	Keep the binary (.bin) files.
<code>keepgpu</code>	Keep the kernel source (.gpu) files.
<code>keepptx</code>	Keep the portable assembly (.ptx) file for the GPU code.
<code>maxregcount:n</code>	Specify the maximum number of registers to use on the GPU. Leaving this blank indicates no limit.
<code>mul24</code>	Use 24-bit multiplication for subscripting.
<code>nofma</code>	Do not generate fused multiply-add instructions.
<code>time</code>	Link in a limited-profiling library.
<code>[no]wait</code>	[Do not] Wait for each kernel to finish before continuing in the host program. The default is wait.

- `-Mautoinline` has new suboptions:

<code>levels:n</code>	Instructs the compiler to perform $n$ levels of inlining. The default number of levels is 10.
<code>maxsize:n</code>	Instructs the compiler not to inline functions of size $> n$ . The default size is 100.
<code>totalsize:n</code>	Instructs the compiler not to stop inlining when the size equals $n$ . The default size is 800.

- New options `-pre` and `-Mnopro` exist to enable/disable partial redundancy elimination.
- New options `-Meh_frame` and `-Mnoeh_frame` instruct the linker to keep eh\_frame call frame sections in the executable.

## Note

---

The `eh_frame` option is available only on newer Linux systems that supply the system unwind libraries.

- A new option `--gnu_version <num>` exists that sets the GNU C++ compatibility version. (C++ only)
- A new option `--microsoft_version <num>` exists that sets the Microsoft C++ compatibility version. (C++ only)
- A new option `-Mcuda` tells the compiler to enable CUDA Fortran. In release 2010, `-Mcuda` has these suboptions:

<code>cc10, cc11, cc12, cc13, cc20</code>	Generate code for compute capability 1.0, 1.1, 1.2, 1.3, or 2.0 respectively.
<code>cuda2.3</code> or <code>2.3</code>	Specify the CUDA 2.3 version of the toolkit.

<code>cuda3.0</code> or <code>3.0</code>	Specify the CUDA 3.0 version of the toolkit.
<code>cuda3.1</code> or <code>3.1</code>	Specify the CUDA 3.1 version of the toolkit.
<code>emu</code>	Enable CUDA Fortran emulation mode.
<code>fastmath</code>	Use routines from the fast math library.
<code>keepbin</code>	Keep the generated binary (.bin) file for CUDA Fortran.
<code>keepgpu</code>	Keep the generated GPU code (.gpu) for CUDA Fortran.
<code>keepptx</code>	Keep the portable assembly (.ptx) file for the GPU code.
<code>maxregcount:n</code>	Specify the maximum number of registers to use on the GPU. Leaving this blank indicates no limit.
<code>nofma</code>	Do not generate fused multiply-add instructions.

## C++ Compilation Requirements

### Note

---

We break object code compatibility in this release for C++.

All C++ source files and libraries that were built with PGI 9.0 or prior releases must be recompiled to link with 10.1 or higher object files.

## Fortran Enhancements

The following sections describe enhancements to Fortran related to interoperability with C, statements, assignments, intrinsics, modules, array-related allocation, and I/O operations.

### Enhanced Fortran Interoperability with C

Fortran 2003 provides a mechanism for interoperating with C. Any entity involved must have equivalent declarations made in both C and Fortran. In this release, PGI has expanded Fortran interoperability with C by adding these components:

- Enumerators – a set of integer constants. The kind of enumerator corresponds to the integer type that C would choose for the same set of constants.
- `c_f_pointer` – a subroutine that assigns the C pointer target, `cptr`, to the Fortran pointer, `fptr`, and optionally specifies its shape, `shape`. The syntax is:

```
c_f_pointer (cptr, fptr [,shape])
```

- `c_f_procpointer` – a subroutine that associates the C pointer target, `cptr`, with the target of a C function pointer. The syntax is:

```
c_f_procpointer (cptr, fptr)
```

- `c_associated` – a subroutine that determines the status of the C pointer target, `cptr1`, or determines if one `C_PTR`, `cptr1` is associated with a target `C_PTR`, `cptr2`. The syntax is:

```
c_associated (cptr1[,cptr2])
```

For more information on these components, refer to Chapter 9, *Interoperability with C* of the *PGI Fortran Reference*.

## New or Modified Fortran Statements

The following Fortran statements are new. For complete descriptions, refer to chapter 3, *Fortran Statements* of the *PGI Fortran Reference*.

### ASSOCIATE

Associates a name either with a variable or with the value of an expression for the duration of a block. When the block is executed, the `associate-name` remains associated with the variable or retains the value specified, taking its type, type parameters, and rank from the association.

### ASYNCHRONOUS

Indicates to the compiler that incorrect results might occur for optimizations involving movement of code across wait statements, or statements that cause wait operations.

### WAIT

Performs a wait operation for specified pending asynchronous data transfer operations.

The following Fortran statements are enhanced in this release:

### ALLOCATE

New specifiers of `ERRMSG` and `SOURCE` are now available.

### INQUIRE

New specifiers of `PENDING` and `POS` are now available.

### READ

New specifiers of `ASYNCHRONOUS`, `BLANK`, `DECIMAL`, `PAD`, and `POS` are now available.

### WRITE

New specifiers of `ASYNCHRONOUS`, `DECIMAL`, `DELIM` and `POS` are now available.

## New or Modified Fortran Intrinsic Functions

An intrinsic is a function available in a given language whose implementation is handled specifically by the compiler. Since the compiler has an intimate knowledge of the intrinsic function, it can better integrate it and optimize it for the situation. In this release, PGI implemented the following intrinsics. For detailed information about these intrinsics, refer to the chapter 6, *Intrinsics* of the *PGI Fortran Reference*.

### EXTENDS\_TYPE\_OF(A,B)

Determines whether the dynamic type of A is an extension type of the dynamic type of B. Returns either true or false.

### GET\_COMMAND\_ARGUMENT(NUMBER [, VALUE, LENGTH, STATUS])

Returns the specified command line argument of the command that invoked the program.

### GET\_COMMAND([COMMAND, LENGTH, STATUS])

Returns the entire command line that was used to invoke the program.

GET\_ENVIRONMENT\_VARIABLE (NAME [,VALUE, LENGTH, STATUS, TRIM\_NAME])

Returns the value of the specified environment variable.

IS\_IOSTAT\_END(STAT)

Tests whether a variable has the value of the I/O status: “end of file”; returns either true or false.

IS\_IOSTAT\_EOR(STAT)

Tests whether a variable has the value of the I/O status: “end of record”; returns either true or false.

NEW\_LINE(A)

Returns the newline character.

SAME\_TYPE\_AS(A,B)

Determines whether the dynamic type of A is the same as the dynamic type of B. Returns either true or false.

## New Fortran Intrinsic Modules

PGI 2010 now supports the Fortran intrinsic modules `ieee_arithmetic`, `ieee_exceptions`, and `ieee_features`.

### IEEE\_ARITHMETIC

The `ieee_arithmetic` intrinsic module provides access to two derived types, named constants of these types, and a collection of generic procedures.

This module behaves as if it contained a `use` statement for the module `ieee_exceptions`, so all the features of `ieee_exceptions` are included.

#### Note

---

For specific information on these types, functions, and subroutines, refer to the *PGI Fortran Reference*.

### Defined Elemental Operators

- `==`

For two values of one of the derived types, this operator returns true if the values are the same; false, otherwise.

- `/=`

For two values of one of the derived types, this operator returns true if the values are different; false, otherwise.

### Derived Types

- `ieee_class_type` - Identifies a class of floating point values.
- `ieee_round_type` - Identifies a particular round mode.

The following table shows the values that each of these class types can take:

This derived type...	Takes these values...
ieee_class_type	ieee_signaling_nan ieee_quiet_nan ieee_negative_inf ieee_negative_normal ieee_negative_denormal ieee_negative_zero ieee_postive_zero ieee_postive_denormal ieee_postive_normal ieee_postive_inf ieee_other_value (Fortran 2003 only)
ieee_round_type	ieee_nearest ieee_to_zero ieee_up ieee_down

### Note

For specific information on these values refer to the *PGI Fortran Reference*.

### Inquiry Functions

ieee_support_datatype([x])	ieee_support_rounding (round_value[,x])
ieee_support_denormal([x])	ieee_support_sqrt([x])
ieee_support_divide([x])	ieee_support_standard ([x])
ieee_support_inf([x])	ieee_support_underflow_control ([x]) Fortran 2003 only
ieee_support_nan([x])	

### Elemental Functions

ieee_class(x)	ieee_next_after(x,y)
ieee_copy_sign(x,y)	ieee_rem(x,y)
ieee_is_finite(x)	ieee_rint(x,y)
ieee_is_nan(x)	ieee_scaln(x,i)
ieee_is_negative(x)	ieee_unordered(x,y)
ieee_is_normal(x)	ieee_value(x,class)
ieee_is_logb(x)	ieee_support_datatype

### Non-Elemental Subroutines

```

ieee_get_rounding_mode(round_value)
ieee_get_underflow_mode(gradual)
ieee_set_rounding_mode(round_value)
ieee_gst_underflow_mode(gradual)

```

### Transformational Function

```

ieee_selected_real_kind([p] [,r])

```

For more information on these intrinsic modules, and on the derived types, functions, and subroutines to which they provide access, refer to the *Intrinsics Modules* section of the *PGI Fortran Reference*.

## IEEE\_EXCEPTIONS

The `ieee_exceptions` intrinsic module specifies accessibility of overflow and divide-by-zero flags as well as determines the level of support for other exceptions. This module provides access to two derived types, named constants of these types, and a collection of generic procedures.

### Derived Types

`ieee_flag_type` - Identifies a particular exception flag.  
`ieee_status_type` - Saves the current floating-point status.

### Inquiry Functions

`ieee_support_flag(flag [,x])`  
`ieee_support_halting(flag)`

### Subroutines for Flags and Halting Modes

`ieee_get_flag(flag, flag_value)`  
`ieee_get_halting_mode(flag, halting)`  
`ieee_set_flag(flag, flag_value)`  
`ieee_set_halting_mode(flag, halting)`

### Subroutines for Floating-Point Status

`ieee_get_status(status_value)`  
`ieee_set_status(status_value)`

For more information on this intrinsic module and the derived types, functions, and subroutines to which it provides access, refer to the *Intrinsics Modules* section of the *PGI Fortran Reference*.

## IEEE\_FEATURES

The `ieee_features` intrinsic module supports specification of essential IEEE features. It provides access to one derived type and a collection of named constants of this type.

### Derived Type

`ieee_features_type` - Identifies a particular feature and may only take values that are those of named constants defined in the module.

### Named Constants

<code>ieee_datatype</code>	<code>ieee_invalid_flag</code>
<code>ieee_denormal</code>	<code>ieee_nan</code>
<code>ieee_divide</code>	<code>ieee_rounding</code>
<code>ieee_halting</code>	<code>ieee_sqrt</code>
<code>ieee_inexact_flag</code>	<code>ieee_underflow_flag</code>
<code>ieee_inf</code>	

For more information on this intrinsic module and the derived types, functions, and subroutines to which it provides access, refer to the *Intrinsics Modules* section of the *PGI Fortran Reference*.

## Fortran I/O Enhancements

PGI 2010 implements these enhancements related to Input and Output:

- Ability to use a comma instead of a decimal point in input and output. Support for this feature is through the `DECIMAL=scalar_char` clause or through use of the `dp` and `dc` descriptors.
- The `DECIMAL=scalar_char` clause is available for `OPEN`, `READ`, and `WRITE` statements, where `scalar_char` is a scalar character expression which takes the value 'point' or 'comma'. When the edit mode is *point*, decimal points appear in both input and output. When the edit mode is *comma*, commas rather than decimal points appear in both input and output.

For `OPEN` statements, this value specifies the default decimal edit mode for the unit. For `READ/WRITE` statements, this decimal edit mode is the default mode only for the duration of that `READ/WRITE` statement.

- The `dc` and `dp` descriptors, representing decimal comma and decimal point edit modes, respectively, are valid in format processing, such as in a `FORMAT` statement. The specific edit mode takes effect immediately when encountered in formatting, and stays in effect until either another descriptor is encountered or until the end of the current I/O statement.
- Ability to specify input/output encoding using the `encoding=` specifier on the `OPEN` statement. Further, the use of this specifier with the `INQUIRE` statement returns the encoding of the file:

`UTF-8` specifies the file is connected for UTF-8 I/O or that the processor can detect this format in some way.

`UNKNOWN` specifies the processor cannot detect the format.

A processor-dependent value indicates the file is in another known format, such as

`UTF-16LE`.

## New or Modified Runtime Library Routines

PGI 2010 supports new runtime library routines associated with the PGI Accelerator compilers. For more information, refer to “[PGI Accelerator Compilers Runtime Libraries](#),” on page 24.

## New or Modified Tools Support

The PGI Tools Guide describes the tools in detail as well as explains the new features highlighted in this section.

PGPROF graphical MPI/OpenMP/multi-thread performance analysis and tuning profiler has these enhancements in this release:

- PGI Accelerator and CUDA Fortran GPU-side performance statistics
- New data collection mechanism via `pgcollect` enables profiling without re-compiling or any special software co-installation requirements for OProfile. You can use `pgcollect` in standalone mode for time-based sampling using only PGI software – both on Linux and on Mac OS X 10.5 (Leopard).

- Support for profiling of code in shared object files – on Linux.  
Dynamic libraries are not yet supported on Mac OS X.
- Updated GUI for easier navigation with tabbed access to multiple source files and improved drill-down to assembly code
- Support for profiling of binaries compiled by non-PGI compilers.
- Uniform cross-platform performance profiling without re-compiling or any special software privileges on Linux, MacOS and Windows
- Updated graphical user interface

## New or Modified PVF Samples

Additional **PVF Samples** are available from the PVF installation directory, typically in a directory called `Samples`:

```
$(VSInstallDir)\PGI Visual Fortran\Samples\
```

In the `gpu` subdirectory of the `Samples` directory, you find these new sample programs which require a PGI Accelerator License to compile and a GPU to run.

`AccelPM_Matmul`

Uses directives from the PGI Accelerator Programming Model to offload a `matmul` computation to a GPU.

`CUDAFor_Matmul`

Uses CUDA Fortran to offload a `matmul` computation to a GPU.

In the `interlanguage` subdirectory of the `Samples` directory, you find this new sample program which requires that Visual C++ be installed to build and run:

`vcmain_calling_pvfdll`

Calls a routine in a PVF DLL from a main program compiled by VC++.

For a complete list of sample projects available in PVF, refer to Chapter 1 of the PVF User's Guide.

## Library Interfaces

PGI provides access to a number of libraries that export C interfaces by using Fortran modules. These libraries and functions are described in Chapter 8 of the *PGI User's Guide*.

# Chapter 3. PGI Workstation 2010

This chapter describes the updates and changes to PGI Workstation 2010 that are specific to Linux, Windows, and Mac OS X, such as using the module load command on Linux.

## PGI Workstation 2010 for Linux

### Java Runtime Environment (JRE)

Although the PGI installation on Linux includes a 32-bit version of the Java Runtime Environment (JRE), sufficient 32-bit X Windows support must be available on the system for the JRE and the PGI software that depends on it to function properly. On some systems, notably recent releases of Fedora Core, these libraries are not part of the standard installation.

The required X Windows support generally includes these libraries:

libXau	libXdmcp	libxcb
libX11	libXext	

## PGI Workstation 2010 for Windows

PGI Workstation 2010 for Windows supports most of the features of the 32- and 64-bit versions for linux86 and linux86-64 environments.

PGI Workstation 2010 for Windows, during the point-and-click installation, now supports automatic license generation from [www.pgroup.com](http://www.pgroup.com), and license server setup. In addition, an improved Start menu entry allows easier access for launching command shells and PGI tools, as well as easier access to licensing and documentation.

## PGI Workstation 2010 for Mac OS X

PGI Workstation 2010 for Mac OS X supports most of the features of the 32- and 64-bit versions for linux86 and linux86-64 environments. Except where noted in these release notes or the user manuals, the PGI compilers and tools on Mac OS X function identically to their Linux counterparts.



# Chapter 4. PGI Accelerator

An accelerator is a special-purpose co-processor attached to a CPU and to which the CPU can offload data and executable kernels to perform compute-intensive calculations. This chapter describes the new PGI Accelerator compilers, including the collection of compiler directives used to specify regions of code in Fortran and C programs that can be offloaded from a host CPU to an attached accelerator.

## Note

---

For more information and more details about the PGI Accelerator compilers, the programming model, directives, and how to run an accelerator program, refer to Chapter 7, *Using an Accelerator* and Chapter 18, *PGI Accelerator Compilers Reference*, in the *PGI User's Guide*.

## Components

The PGI Accelerator compiler technology includes the following components:

- PGFORTRAN auto-parallelizing accelerator-enabled Fortran 95/2003 compiler
- PGCC auto-parallelizing accelerator-enabled ANSI C99 and K&R C compiler.
- NVIDIA CUDA Toolkit components
- A simple command-line tool to detect whether the system has an appropriate GPU or accelerator card.

No accelerator-enabled debugger is included with this release.

## Availability

The PGI 2010 Fortran & C Accelerator compilers are available only on x86 processor-based workstations and servers with an attached NVIDIA CUDA-enabled GeForce, Quadro, Tesla, or Fermi card. These compilers target all platforms that PGI supports except 64-bit Mac OS X. For a list of supported GPUs, refer to the Accelerator Installation and Supported Platforms list in the latest *PGI Installation Guide*.

## User-directed Accelerator Programming

In user-directed accelerator programming the user specifies the regions of a host program to be targeted for offloading to an accelerator device. The bulk of a user's program, as well as regions containing constructs

that are not supported on the targeted accelerator, are executed on the host. This chapter concentrates on specification of loops and regions of code to be offloaded to an accelerator.

## Features Not Covered or Implemented

Currently the PGI Accelerator compilers do not include features for automatic detection and offloading of regions of code to an accelerator by a compiler or other tool. While future versions of the PGI compilers may allow for automatic offloading, multiple accelerators of the same type, or multiple accelerators of different types, these features are not currently supported.

## System Requirements

To use the PGI Accelerator compiler features, you must install the NVIDIA CUDA component: NVIDIA Driver.

You may download this driver from the NVIDIA website at [www.nvidia.com/cuda](http://www.nvidia.com/cuda). These are not PGI products, and are licensed and supported by NVIDIA.

## Supported Processors and GPUs

This PGI Accelerator compiler release supports all AMD64 and Intel 64 host processors supported by Release 2010 or higher of the PGI compilers and tools. Further, you can use the `-tp <target>` flag as documented in that release.

You can also use the `-ta=nvidia` flag to enable the accelerator directives and target the NVIDIA GPU. You can then use the generated code on any system with CUDA installed that has a CUDA-enabled GeForce, Quadro, Tesla, or Fermi card.

For more information on these flags as they relate to accelerator technology, refer to the PGI User's Guide. For a complete list of supported GPUs, refer to the NVIDIA website at:

[www.nvidia.com/object/cuda\\_learn\\_products.html](http://www.nvidia.com/object/cuda_learn_products.html)

## Installation and Licensing

The PGI Accelerator compilers require a separate license key in addition to a normal PGI Workstation, Server, or CDK license key. For specific information related to installation, refer to the *PGI Workstation Installation Guide*.

## Running an Accelerator Program

Launch a program that has accelerator directives and that was compiled and linked with the `-ta=nvidia` flag in the same way you would launch the program if it had been compiled without the `-ta=nvidia` flag. For more specific information, refer to Chapter 7 in the *PGI User's Guide*.

## PGI Accelerator Compilers Runtime Libraries

PGI Accelerator Compilers provide user-callable functions and library routines that are available for use by programmers to query the accelerator features and to control behavior of accelerator-enabled programs at runtime. In Fortran, none of the PGI Accelerator compilers runtime library routines may be called from a PURE or ELEMENTAL procedure.

To access accelerator libraries, you must link an accelerator program with the same `-ta` flag used when compiling.

There are runtime library files for C and for Fortran.

- **C Runtime Library Files** - In C, prototypes for the runtime library routines are available in a header file named `accel.h`. All the library routines are extern functions with “C” linkage. This file defines:
  - The prototypes of all routines in this section.
  - Any data types used in those prototypes, including an enumeration type to describe types of accelerators.
- **Fortran Runtime Library Files** - In Fortran, interface declarations are provided in a Fortran include file named `accel_lib.h` and in a Fortran module named `accel_lib`. These files define:
  - Interfaces for all routines in this section.
  - Integer parameters to define integer kinds for arguments to those routines.
  - Integer parameters to describe types of accelerators.

The integer parameter `accel_version` has a value `yyyymm`, where `yyyy` and `mm` are the year and month designations of the version of the Accelerator programming model supported. This value matches the value of the preprocessor variable `_ACCEL`.

The following list briefly describes the PGI Accelerator compilers runtime library routines that PGI currently supports. For a complete description of these routines, refer to the *PGI Accelerator Runtime Routines* section of the *PGI User's Guide*.

- **acc\_get\_device** - returns the type of accelerator device being used.
- **acc\_get\_device\_num** - returns the number of the device being used to execute an accelerator region.
- **acc\_get\_num\_devices** - returns the number of accelerator devices of the given type attached to the host.
- **acc\_init** - connects to and initializes the accelerator device and allocates control structures in the accelerator library.
- **acc\_set\_device** - tells the runtime which type of device to use when executing an accelerator compute region.
- **acc\_set\_device\_num** - tells the runtime which device of the given type to use among those that are attached.
- **acc\_shutdown** - tells the runtime to shutdown the connection to the given accelerator device, and free up any runtime resources.

## Environment Variables

PGI supports environment variables that modify the behavior of accelerator regions. This section defines the user-settable environment variables used to control behavior of accelerator-enabled programs at execution. These environment variables must comply with these rules:

- The names of the environment variables must be upper case.

- The values assigned environment variables are case insensitive and may have leading and trailing white space.
- The behavior is implementation-defined if the values of the environment variables change after the program has started, even if the program itself modifies the values.

The following list briefly describes the PGI Accelerator environment variables that PGI supports. For more information on these variables, refer to the PGI User's Guide.

- `ACC_DEVICE` - controls which accelerator device to use when executing PGI Unified Binary for accelerators. The value of this environment variable may be the string `NVIDIA` or `HOST`.
- `ACC_DEVICE_NUM` - controls the default device number to use when executing accelerator regions. The value of this environment variable must be a nonnegative integer between zero and the number of devices attached to the host.
- `ACC_NOTIFY` - when set to a non-negative integer, indicates to print a message for each kernel launched on the device.

## Applicable Command Line Options

There are command line options that apply specifically when working with accelerators.

- `-tp` - use this option to specify the target host processor architecture.
- `-Minfo` or `-Minfo=accel` - use either format of this option to see messages about the success or failure of the compiler in translating the accelerator region into GPU kernels.
- `-ta=nvidia(,nvidia_suboptions),host` - enables recognition of the `!$ACC` directives in Fortran, and `#pragma acc` directives in C. [C, Fortran only]

where:

- **nvidia** - Select NVIDIA accelerator target. This option has the following `nvidia`-suboptions:

<code>analysis</code>	Perform loop analysis only; do not generate GPU code.
<code>cc10, cc11, cc12, cc13, cc20</code>	Generate code for compute capability 1.0, 1.1, 1.2, 1.3, or 2.0 respectively.
<code>cuda2.3</code> or <code>2.3</code>	Specify the CUDA 2.3 version of the toolkit.
<code>cuda3.0</code> or <code>3.0</code>	Specify the CUDA 3.0 version of the toolkit.
<code>cuda3.1</code> or <code>3.1</code>	Specify the CUDA 3.1 version of the toolkit.
<code>fastmath</code>	Use routines from the fast math library.
<code>keepbin</code>	Keep the binary ( <code>.bin</code> ) files.
<code>keepgpu</code>	Keep the kernel source ( <code>.gpu</code> ) files.
<code>keepptx</code>	Keep the portable assembly ( <code>.ptx</code> ) file for the GPU code.
<code>maxregcount:n</code>	Specify the maximum number of registers to use on the GPU. Leaving this blank indicates no limit.
<code>mul24</code>	Use 24-bit multiplication for subscripting.

<code>nofma</code>	Do not generate fused multiply-add instructions.
<code>time</code>	Link in a limited-profiling library.
<code>[no]wait</code>	[Do not] Wait for each kernel to finish before continuing in the host program. the default is wait.

- **host** - Select the host as the target; when used in combination with the `nvidia` option, this option generates PGI Unified Binary Code.

The compiler automatically invokes the necessary CUDA software tools to create the kernel code and embeds the kernels in the Linux object file.

To access accelerator libraries, you must link an accelerator program with the same `-ta` flag used when compiling the program.

## PGI Unified Binary for Accelerators

PGI compilers support the PGI Unified Binary feature to generate executables with functions optimized for different host processors, all packed into a single binary. This release extends the PGI Unified Binary technology for accelerators. Specifically, you can generate a single binary that includes two versions of functions:

- one version is optimized for the accelerator.
- one version runs on the host processor when the accelerator is not available or when you want to compare host to accelerator execution.

To enable this feature, use the extended `-ta` flag: `-ta=nvidia,host`

This flag tells the compiler to generate two versions of functions that have valid accelerator regions.

If you use the `-minfo` flag, you get messages similar to the following during compilation:

```
s1:
 12, PGI Unified Binary version for -tp=barcelona-64 -ta=host
 18, Generated an alternate loop for the inner loop
    Generated vector sse code for inner loop
    Generated 1 prefetch instructions for this loop
s1:
 12, PGI Unified Binary version for -tp=barcelona-64 -ta=nvidia
 15, Generating copy(b(:,2:90))
    Generating copyin(a(:,2:90))
 16, Loop is parallelizable
 18, Loop is parallelizable
    Parallelization requires privatization of array t(2:90)
    Accelerator kernel generated
 16, !$acc do parallel
 18, !$acc do parallel, vector(256) Using register for t
```

The PGI Unified Binary message shows that two versions of the subprogram `s1` were generated:

- one for no accelerator (`-ta=host`)
- one for the NVIDIA GPU (`-ta=nvidia`)

At run time, the program tries to load the NVIDIA CUDA dynamic libraries and test for the presence of a GPU. If the libraries are not available or no GPU is found, the program runs the host version.

You can also set an environment variable to tell the program to run on the NVIDIA GPU. To do this, set `ACC_DEVICE` to the value `NVIDIA` or `nvidia`. Any other value of the environment variable causes the program to use the host version.

The only supported `-ta` targets for this release are `nvidia` and `host`.

## Profiling Accelerator Kernels

This release supports the command line option:

```
-ta=nvidia,time
```

The `time` suboption links in a timer library, which collects and prints out simple timing information about the accelerator regions and generated kernels. For a specific example of accelerator kernel timing data, refer to *Chapter 7* in the *PGI User's Guide*.

## Supported Intrinsic

PGI Accelerator compilers support Fortran and C intrinsics. For complete descriptions of these intrinsics, refer to the "*Supported Intrinsic*" section of the *Using an Accelerator* chapter of the *PGI User's Guide*. PGI plans to support additional intrinsics in future releases.

# Chapter 5. Distribution and Deployment

Once you have successfully built, debugged and tuned your application, you may want to distribute it to users who need to run it on a variety of systems. This chapter addresses how to effectively distribute applications built using PGI compilers and tools. The application must be installed in such a way that it executes accurately on a system other than the one on which it was built, and which may be configured differently.

## Application Deployment and Redistributables

Programs built with PGI compilers may depend on run-time library files. These library files must be distributed with such programs to enable them to execute on systems where the PGI compilers are not installed. There are PGI redistributable files for all platforms. On Windows, PGI also supplies Microsoft redistributable files.

### PGI Redistributables

The PGI 2010 release includes these directories:

```
$PGI/linux86/10.9/REDIST  
$PGI/linux86/10.9/REDIST-RLR  
$PGI/linux86-64/10.9/REDIST  
$PGI/linux86-64/10.9/REDIST-RLR  
$PGI/win32/10.9/REDIST  
$PGI/win32/10.9/REDIST-RLR  
$PGI/win64/10.9/REDIST  
$PGI/win64/10.9/REDIST-RLR  
$PGI/osx86/10.9/REDIST-RLR
```

These directories contain all of the PGI Linux runtime library shared object files or Windows dynamically linked libraries that can be re-distributed by PGI 2010 licensees under the terms of the PGI End-user License Agreement (EULA). For reference, a text-form copy of the PGI EULA is included in the 2010 directory.

## Linux Redistributables

The Linux REDIST directories contain the PGI runtime library shared objects for all supported targets. This enables users of the PGI compilers to create packages of executables and PGI runtime libraries that will execute successfully on almost any PGI-supported target system, subject to these requirements:

- End-users of the executable have properly initialized their environment
- Users have set LD\_LIBRARY\_PATH to use the relevant version of the PGI shared objects.

## Microsoft Redistributables

The PGI products on Windows include Microsoft Open Tools. The Microsoft Open Tools directory contains a subdirectory named "redist". PGI 2010 licensees may redistribute the files contained in this directory in accordance with the terms of the PGI End-User License Agreement.

Microsoft supplies installation packages, `vcredist_x86.exe` and `vcredist_x64.exe`, containing these runtime files. These files are available in the `redist` directory.

# Chapter 6. The PGI Windows CDK

If you have a PGI Windows CDK (Cluster Development Kit) license, then your PGI software includes support for working with Microsoft Compute Cluster Server and MSMPI. Specifically, this software includes support for these things:

- Building MPI applications with MSMPI
- Using PGPROF to do MPI profiling of MSMPI applications
- Using PGDBG to do MPI debugging of MSMPI applications

This chapter provides information on these tasks.

## Build MPI Applications with MSMPI

### Note

---

For the options `-Mprof=msmpi` and `-Mmpi=msmpi` to work properly, the `CCP_HOME` environment variable must be set. This variable is typically set when the Microsoft Compute Cluster SDK is installed.

## Using MSMPI libraries

To build an application using the MSMPI libraries, use the option `-Mmpi=msmpi`. This option inserts options into the compile and link lines to pick up the MSMPI headers and libraries.

## Generate MPI Profile Data

To build an application that generates MPI profile data, use the `-Mprof=msmpi` option. This option performs MPICH-style profiling for Microsoft MSMPI. For Microsoft Compute Cluster Server only, using this option implies `-Mmpi=msmpi`.

The profile data generated by running an application built with the option `-Mprof=msmpi` contains information about the number of sends and receives, as well as the number of bytes sent and received, correlated with the source location associated with the sends and receives. You must use `-Mprof=msmpi` in conjunction with either the option `-Mprof=func` or `-Mprof=lines`.

When invoked using this type of profile data, PGPROF automatically displays MPI statistics.



## DOS Shell Example

Suppose you wanted to debug the following job invoked in a DOS shell:

```
DOS> job submit /numprocessors:4 /workdir:\\cce-head\d\srt
      /stdout:sendrecv.out mpiexec sendrecv.exe
```

You use this command:

```
$ pgdbg -pgserv "-mpi:c:\Program Files\Microsoft Compute Cluster Pack\Bin\job.cmd"
      submit /numprocessors:4 /workdir:\\cce-head\d\srt
      /stdout:sendrecv.out mpiexec sendrecv.exe
```



# Chapter 7. Troubleshooting Tips and Known Limitations

This chapter contains information about known limitations, documentation errors, and corrections that have occurred to PGI Server and Workstation.

The frequently asked questions (FAQ) section of the [pgroup.com](http://www.pgroup.com) web page provides more up-to-date information about the state of the current release. The location is:

<http://www.pgroup.com/support/index.htm>

## General Issues

Most issues in this section are related to specific uses of compiler options and suboptions.

- Object and module files created using PGI Workstation 2010 compilers are incompatible with object files from PGI Workstation 5.x and prior releases.
- Object files compiled with `-Mipa` using PGI Workstation 6.1 and prior releases must be recompiled with PGI Workstation 2010.
- The `-i8` option can make programs incompatible with the bundled ACML library. Visit [developer.amd.com](http://developer.amd.com) to check for compatible libraries.
- The `-i8` option can make programs incompatible with MPI and ACML; use of any `INTEGER*8` array size argument can cause failures with these libraries.
- Using `-Mipa=vestigial` in combination with `-Mipa=libopt` with PGCC, you may encounter unresolved references at link time. This problem is due to the erroneous removal of functions by the vestigial sub-option to `-Mipa`. You can work around this problem by listing specific sub-options to `-Mipa`, not including `vestigial`.
- OpenMP programs compiled using `-mp` and run on multiple processors of a SuSE 9.0 system can run very slowly. These same executables deliver the expected performance and speed-up on similar hardware running SuSE 9.1 and above.

## Platform-specific Issues

### Linux

The following are known issues on Linux:

- If you experience poor performance in the PGDBG or PGPROF GUI, try upgrading the X library `libxcb` to the latest version. The version number varies depending on your distribution. You can obtain a patch from your Linux distributor.
- Programs that incorporate object files compiled using `-mmodel=medium` cannot be statically linked. This is a limitation of the `linux86-64` environment, not a limitation of the PGI compilers and tools.

### Apple Mac OS X

The following are known issues on Apple Mac OS X:

#### Note

---

Tiger is no longer supported

- On Apple Mac OS platform, the PGI Workstation 2010 compilers do not support static linking of user binaries. For compatibility with future Apple updates, the compilers support dynamic linking of user binaries.
- Using `-Mprof=func` or `-Mprof=lines` is not supported.
- To begin an OpenMPI debugging session with PGDBG on Mac OS X 10.5, use the following steps:
  1. Invoke the debugger using the full pathname of the executable. For example, you might use a command similar to this one:
 

```
pgdbg -mpi:mpirun -np 4 /home/user1/a.out
```
  2. Set a breakpoint on `main`.
  3. Continue to the breakpoint.
  4. Begin your debugging session.

### Windows

The following are known issues on Windows:

- On Windows, the version of `vi` included in Cygwin can have problems when the `SHELL` variable is defined to something it does not expect. In this case, the following messages appear when `vi` is invoked:

```
E79: Cannot expand wildcards Hit ENTER or type command to continue
```

To workaroud this problem, set `SHELL` to refer to a shell in the cygwin bin directory, e.g. `/bin/bash`.

- On Windows, runtime libraries built for debugging (e.g. `msvcrt` and `libcmt`) are not included with PGI Workstation. When a program is linked with `-g`, for debugging, the standard non-debug versions of

both the PGI runtime libraries and the Microsoft runtime libraries are always used. This limitation does not affect debugging of application code.

The following are known issues on Windows and PGDBG:

- In PGDBG on the Windows platform, use the forward slash (/) character to delimit directory names in file path names.

### Note

---

This requirement does not apply to the PGDBG debug command or to target executable names on the command line, although this convention will work with those commands.

- In PGDBG on the Windows platform, Windows times out stepi/nexti operations when single stepping over blocked system calls. For more information on the workaround for this issue, refer to the online FAQs at [www.pgroup.com/support/tools.htm](http://www.pgroup.com/support/tools.htm).

The following are known issues on Windows and PGPROF:

- Do not use `-Mprof` with PGI Workstation runtime library DLLs. To build an executable for profiling, use the static libraries. When the compiler option `-Bdynamic` is not used, the static libraries are the default.

## PGDBG-related Issues

The following are known issues on PGDBG:

- Before PGDBG can set a breakpoint in code contained in a shared library, `.so` or `.dll`, the shared library must be loaded.
- Due to problems in PGDBG in shared library load recognition on Fedora Core 6 or RHEL5, breakpoints in processes other than the process with rank 0 may be ignored when debugging MPICH-1 applications when the loading of shared libraries to randomized addresses is enabled.
- Debugging of unified binaries, that is, programs built with the `-tp=x64` option, is not fully supported. The names of some subprograms are modified in the creation of the unified binary, and PGDBG does not translate these names back to the names used in the application source code. For detailed information on how to debug a unified binary, see [www.pgroup.com/support/tools.htm](http://www.pgroup.com/support/tools.htm).

## PGPROF-related Issues

The following are known issues on PGDBG:

- Using `-Mprof=func`, `-mmodel=medium` and `-mp` together on any of the PGI compilers can result in segmentation faults by the generated executable. These options should not be used together.
- Programs compiled and linked for gprof-style performance profiling using `-pg` can result in segmentation faults on system running version 2.6.4 Linux kernels.
- Times reported for multi-threaded sample-based profiles, that is, profiling invoked with `-pg` or `-Mprof=time` options, are for the master thread only. PGI-style instrumentation profiling with `-`

`Mprof={lines | func}` or hardware counter-based profiling using `-Mprof=hwcts` or `pgcollect` must be used to obtain profile data on individual threads.

## CUDA Fortran Toolkit Issues

### Note

---

You can compile with the CUDA 3.1 toolkit, either by adding the `-ta=nvidia:cuda3.1` option to the command line or by adding `set CUDAVERSION=3.1` to the `siterc` file. Using Cuda 3.1 generates binaries that may not work on machines with a 2.3 CUDA driver.

`pgaccelinfo` prints the driver version as the first line of output.

For a 2.3 driver: `CUDA Driver Version 2030`

For a 3.0 driver: `CUDA Driver Version 3000`

For a 3.1 driver: `CUDA Driver Version 3010`

## Corrections

A number of problems have been corrected in the PGI 2010 release. Refer to [www.pgroup.com/support/release\\_tprs.htm](http://www.pgroup.com/support/release_tprs.htm) for a complete and up-to-date table of technical problem reports, TPRs, fixed in recent releases of the PGI compilers and tools. This table contains a summary description of each problem as well as the release in which it was fixed.

# Chapter 8. Contact Information

You can contact The Portland Group at:

The Portland Group  
STMicroelectronics, Inc.  
Two Centerpointe Drive  
Lake Oswego, OR 97035 USA

The PGI User Forum is monitored by members of the PGI engineering and support teams as well as other PGI customers. The forum newsgroups may contain answers to commonly asked questions. Log in to the PGI website to access the forum:

[www.pgroup.com/userforum/index.php](http://www.pgroup.com/userforum/index.php)

Or contact us electronically using any of the following means:

Fax	+1-503-682-2637
Sales	<a href="mailto:sales@pgroup.com">sales@pgroup.com</a>
Support	<a href="mailto:trs@pgroup.com">trs@pgroup.com</a>
WWW	<a href="http://www.pgroup.com">www.pgroup.com</a>

All technical support is by email or submissions using an online form at [www.pgroup.com/support](http://www.pgroup.com/support). Phone support is not currently available.

Many questions and problems can be resolved at our frequently asked questions (FAQ) site at [www.pgroup.com/support/faq.htm](http://www.pgroup.com/support/faq.htm).

PGI documentation is available at [www.pgroup.com/resources/docs.htm](http://www.pgroup.com/resources/docs.htm) or in your local copy of the documentation in the release directory [doc/index.htm](http://doc/index.htm).

