



800Gbps XDR (200G-PAM4) Transceivers, Copper Cables, and Fiber Parts List

Table of contents

Where to Find More LinkX Documentation	10
Document Revision History	12

Overview

800Gb/s XDR Twin-port OSFP and OSFP Transceivers and Fiber Part Numbers based on 200G-PAM4 Modulation for InfiniBand

The XDR InfiniBand four-channel 200G-PAM4 cable and transceiver product line consists of linear active copper cables (LACC), single-mode transceivers and optical fiber cables.

- 2x800G-to-2x800G links for switch-to-switch
- 2x800G-to-two 400G links to ConnectX-8 (PCIe and mezzanine cards)
- 2x800G-to-four 200G links to ConnectX-8 (PCIe and mezzanine cards)

Note

Important notes:




- The same single mode, straight and 1:2 splitter crossover fiber cables are used for both XDR and NDR/400GbE.
- New OSFP metal connector terminologies: IHS and RHS.
- Integrated Heat Sink (IHS) integrates the cooling fins into the **transceiver** plug tops for extra cooling (aka finned top).
 - Two IHS versions:
 - Open-top IHS (exposed cooling fins)
 - Closed-top IHS (fins have a metal plate on top for extra cooling)
 - IHS transceivers or copper cables are **only** used in air-cooled switches (Q3400, Q3200) – everything else uses RHS.
- Riding Heat Sink (RHS) on top of ConnectX-8 card **cage** is called RHS, but the name applies to the OSFP plug (aka flat top).
 - RHS devices are used in ConnectX-8 cages for B300, GB300, ConnectX-8 PCIe cards, and liquid cooled switches.

- Twin-port OSFP RHS connectors also may be referred to as “-FLT” in the legacy part numbers.
 - Note, there are tiny fins on the MPO end of the transceiver – this is still RHS device.
- Twin-port OSFP transceivers must use the **same fiber type** (straight or splitter) in **both optical ports** and not one of each.
- Not used for XDR:
 - **QSFP112 devices**, plug used in ConnectX-7/QSFP112 and BlueField-3/QSFP112 DPUs. QSFP112 is only for 100G-PAM4.
 - **Multimode transceivers**, active optical cables (AOC). (Lasers not available yet)
 - **Direct attach copper (DAC) cables** (too short at 200G-PAM4)
- 200G-PAM4-based transceivers cannot downshift to 100G-PAM4 or 50G-PAM4.
- IHS and RHS transceivers or copper cables contain the same internals and can be linked to each other.
- 1.6Tb/s refers to the transceiver electrical end. May also be called 2x800G or 1,600G.
- 2x800G refers to the dual 800G, 4-channel optical ports.
- Linear active copper cables (LACC) are passive direct attach copper (DAC) copper cables with a linear amplifier IC to boost the signal and extend cable length. Called active copper cables (ACC) in NDR generation.
- Active electric cables (AEC) are DAC cables with DSP ICs inside for switch-to-switch links replacing LACC 1.6T-1.6T LACCs.
- Q3200 XDR, InfiniBand switch supports 36 twin-port OSFP, IHS, 1.6Tb/s cables and transceivers. It consists of two Quantum-3 switch ICs inside the chassis that operate independently. The Q3200 supports backwards compatibility to the NDR (4x100G-

PAM4) product line of DAC, LACC copper cables, multimode transceivers and AOCs, and single mode transceivers.

- Q3400 XDR InfiniBand switch supports 72 twin-port OSFP, IHS, 1.6Tb/s cables and transceivers. It consists of four Quantum-3 switch ICs inside the chassis that operate together.
 - It supports “selected” backwards compatibility parts to the NDR product line of cables and transceivers.
 - Q3400 can only link to ConnectX-7, ConnectX-8 PCIe cards – not NDR switches or B300, GB300 mezzanine cards.
 - Q3400 does not support 1:2 port splitting the 4-channel MPO-12/APC ports. Q3200 does.
- 1:2 and 1:4 LACC splitters in the Q3400 can only link to the ConnectX-8 PCIe card – not switches, Iris8 mezzanine card in B300, GB300. They can link to all cards and switches in the Q3200 switch.

1.6T to 1.6T, 800G and AEC, LACC and Transceiver Summary



Parts List

Tip

- Click on the green bold underlined part numbers to open the Product Specifications for that specific product.
- See also the [user guide](#) and [configuration map](#) for configuring these transceivers in DGXs, switches, network adapters, and DPUs.

2x800G Twin-port OSFP IHS and RHS Transceivers 500m, 2km for Switch-to-Switch Ap							
Name	Form Factor	Configuration	Reach, Power	Part Number (link to product spec)	NVIDIA SKU	Crossover Cables Type-B	No
2x800G 2xDR4 Single mode	Twin-port OSFP RHS 2x MPO-12/APC optical connectors	8x200G-PAM4 electrical to Dual 4x200G-PAM4 optical Parallel	500m 33.5W	 MMS4A00-XM OSFP-IHS for air-cooled switches	980-9IAH1-00XM00 980-9IAH0-00XM00	 Multimode Straight cables MFP7E30-Nxxx (xx = 01-to-100 meters) or	IH RH lin ot Ea lin 8C tra M XM 1: fik or us Q: sw
				 OSFP-RHS for liquid-cooled switches		 Single mode 1:2 Splitter cables (xx=01-to-50m)	
2x800G 2xFR4	Twin-port OSFP IHS	4x200G-PAM4 electrical	2km 33.5W	 MMS4A50-XM	980-9IAS0-00XM00		2x or ea

2x800G Twin-port OSFP IHS and RHS Transceivers 500m, 2km for Switch-to-Switch Ap

Single mode	2x LC optical connector	to 4x200G-PAM4 optical Serial Multiplexed		OSFP-IHS For air-cooled switches only		2x LC fiber cables not supplied by NVIDIA. Two LC fiber cables per transceiver.	800G transceivers supplied by NVIDIA. LC cables per transceiver.
--------------------	-------------------------	---	--	---------------------------------------	--	---	--

800G Single-Port Transceivers 500m for ConnectX-8 Embedded Mezzanine and PCIe Cards Adapters

Name	Form Factor	Configuration	Reach, Power	Part Number (link to product spec)	NVIDIA SKU	Figure	Notes
800G DR4 Single mode	Single port MPO-12/APC optical connector	4x200G-PAM4 electrical to 4x200G-PAM4 optical Parallel	500m 18W	 MMS4A20-XM800 OSFP-RHS	980-9IAT0-00XM00		Links to 2x800G IHS or RHS transceiver Used in B100, GB300, ConnectX-8 PCIe and mezzanine cards.

Name	Configuration	Part Number (link to product spec) (one fiber)	Reach (m)	NVIDIA SKU
Straight Fiber Cables Type-B Crossover MPO-12/APC	4 channels to 4-channels Parallel	MFP7E30-N003 MFP7E30-N005 MFP7E30-N007 MFP7E30-N010 MFP7E30-N015 MFP7E30-N020 MFP7E30-N030 MFP7E30-N050	3 5 7 10 15 20 30 50	980-9I55A-00N003 980-9I55B-00N005 980-9I58C-00N007 980-9I58D-00N010 980-9I58E-00N015 980-9I58F-00N020 980-9I58G-00N030 980-9I58H-00N050

		N060MFP7E30- N070MFP7E30- N100MFP7E30- N150		
1:2 Splitter Fiber Cables MPO-12/APC	4 channels to Dual 2-channel Parallel	MFP7E40-N003 MFP7E40-N005 MFP7E40-N007MFP7E40- N010MFP7E40- N015MFP7E40- N020MFP7E40- N030MFP7E40- N050	3 5 71015203050	980-9I58K-00NC 980-9I58L-00NC 980-9I58M-00N 00N010980-9I5 00N015980-9I5 00N020980-9I5 00N030980-9I5

Notes (for table above):

- Part numbers refer to one fiber only. **Order two per twin-port OSFP transceiver.**
- 2x800Gb/s transceivers used with 1:2 fiber splitters result in four 400Gb/s transceivers ends.
- 400Gb/s transceivers based on 200G-PAM4 are not offered. Use 800G transceivers with fiber 2-channel split ends.
- Twin-port transceivers can only use either 2 straight or 2 splitter fiber cables; not one of each.
- LC Duplex fibers and MPO-12/APC fibers beyond listed 50- or 150-meter reaches are not offered.
- These are the same fiber cables used with NDR/400GbE.
- MPO-12/APC cables use 8-fibers; 4 fibers are not used.

2x800G (1.6T) Active Electric Cables (AEC) Copper Switch-to-Switch (PVC mesh sheath)

Name	Form Factor	Configuration	Reach (m)	Part Number (link to product spec)	NVIDIA SKU	Specs	Active Electric Cables (AEC)
------	-------------	---------------	-----------	------------------------------------	------------	-------	------------------------------

2x800G (1.6T) Active Electric Cables (AEC) Copper Switch-to-Switch (PVC mesh sheath)

2x800G AEC IHS	OSFP-IHS to OSFP-IHS	8x 200G-PAM4 to 8x 200G-PAM4	1 1.5 22.53	MCA4K50-X001 MCA4K50-X01A MCA4K50-X002 MCA4K50-X02A MCA4K50-X003	980-9IAM5-00X001 980-9IAM5-00X01A 980-9IAM3-00X002 980-9IAM3-00X02A 980-9IAM3-00X003	26 AWG 27W	
-----------------------	----------------------	------------------------------	-------------------	---	--	---------------	---

2x800G (1.6T) Linear Active Copper Cables (LACC) 1:1, 1:2 and 1:4 Splitters (PVC mesh sheath)

Name	Form Factor	Channels	Reach (m)	Part Number (link to product spec)	NVIDIA SKU	Specs	Linear Copper Cable
2x800G 2x 800G 1:2 Splitter	OSFP-IHS to OSFP-RHS	8x 200G-PAM4 to Dual 4x 200G-PAM4	1 1.5 22.5	MCA7K10-X001 MCA7K10-X01A MCA7K10-X002 MCA7K10-X02A	980-9IAO5-00X001 980-9IAO5-00X01A 980-9IAO5-00X002 980-9IAO5-00X02A	26 AWG 4.3W 8-ch end <0.1W split end	
2x800G 4x 400G 1:4 Splitter	OSFP-IHS to OSFP-RHS	8x 200G-PAM4 to Quad 2x 200G-PAM4	1 1.5 22.5	MCA7K20-X001 MCA7K20-X01A MCA7K20-X002 MCA7K20-X02A	980-9IAQ5-00X001 980-9IAQ5-00X01A 980-9IAQ5-00X002 980-9IAQ5-00X02A	26 AWG 4.3W 8-ch end <0.1W split end	

Notes (for table above):

- AEC contains DSP ICs in each end at 27 Watts; 22 Watts typical.
- LACC contain linear amplifiers in 1.6T end at 4.3 Watts and <0.1 Watts in split end.

- 1:2 and 1:4 LACC splitters in the Q3400 can only link to the ConnectX-8 PCIe card -- not switches, Iris8 mezzanine card in B300, GB300. They can link to all cards and switches in the Q3200 switch.

Page updated: October 20, 2025

Where to Find More LinkX Documentation

This parts list is to be used in conjunction with other documents located in folders in docs.nvidia.com/networking/ > Networking Interconnect.

This site is where the following LinkX cables and transceivers documents are provided.

LinkX Overview Documents:	<p>Review of parts, important notes, and configuration details for linking to NVIDIA switches and adapters</p> <ul style="list-style-type: none">• LinkX Cables and Transceivers Guide to Key Technologies• LinkX User Guide for 400Gb/s 100G-PAM4 OSFP & QSFP112-based Cables and Transceivers
Configuration Maps:	<p>Picture and part number-based PowerPoint® slides for configuration with NVIDIA switches, network adapters, and DGX GPU systems with NVIDIA cables and transceivers</p> <ul style="list-style-type: none">• Configuration Maps
Parts Lists:	<p>Tables summarize by speed, form factor, connector, power, reach, etc. and hyperlinks to individual products specs</p> <ul style="list-style-type: none">• 400Gb/s (100G-PAM4) Transceivers and Fiber Parts List• 400GbE and 200Gb/s (50G-PAM4) and 100Gb/s (25G NRZ) Cables and Transceivers Parts List using QSFP-DD, QSFP56, QSFP28, SFP28• 800Gb/s XDR (200G-PAM4) Transceivers, Copper Cables and Fiber Parts List (this document)
Product Specifications:	<p>10-to-16-page detailed hardware datasheets with physical, thermal, electrical, and optical specifications for each product</p> <ul style="list-style-type: none">• docs.nvidia.com/networking/ > Networking Interconnect > <i>select speed and type</i>

Additional Docs:

- [NVIDIA Cable Management Guidelines and FAQ](#)
- [NVIDIA Interconnect Structured Cabling Requirements for InfiniBand NDR/XDR and 400/800G ETH Solutions](#)

Document Revision History

Version	Date	Changes
1.2	November 2025	Initial release

Notice

This document is provided for information purposes only and shall not be regarded as a warranty of a certain functionality, condition, or quality of a product. NVIDIA Corporation (“NVIDIA”) makes no representations or warranties, expressed or implied, as to the accuracy or completeness of the information contained in this document and assumes no responsibility for any errors contained herein. NVIDIA shall have no liability for the consequences or use of such information or for any infringement of patents or other rights of third parties that may result from its use. This document is not a commitment to develop, release, or deliver any Material (defined below), code, or functionality.

NVIDIA reserves the right to make corrections, modifications, enhancements, improvements, and any other changes to this document, at any time without notice.

Customer should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

NVIDIA products are sold subject to the NVIDIA standard terms and conditions of sale supplied at the time of order acknowledgement, unless otherwise agreed in an individual sales agreement signed by authorized representatives of NVIDIA and customer (“Terms of Sale”). NVIDIA hereby expressly objects to applying any customer general terms and conditions with regards to the purchase of the NVIDIA product referenced in this document. No contractual obligations are formed either directly or indirectly by this document.

NVIDIA products are not designed, authorized, or warranted to be suitable for use in medical, military, aircraft, space, or life support equipment, nor in applications where failure or malfunction of the NVIDIA product can reasonably be expected to result in personal injury, death, or property or environmental damage. NVIDIA accepts no liability for inclusion and/or use of NVIDIA products in such equipment or applications and therefore such inclusion and/or use is at customer’s own risk.

NVIDIA makes no representation or warranty that products based on this document will be suitable for any specified use. Testing of all parameters of each product is not necessarily performed by NVIDIA. It is customer’s sole responsibility to evaluate and determine the applicability of any information contained in this document, ensure the product is suitable and fit for the application planned by customer, and perform the necessary testing for the application in order to avoid a default of the application or the product. Weaknesses in customer’s product designs may affect the quality and reliability of the NVIDIA product and may result in additional or different conditions and/or requirements beyond those contained in this document. NVIDIA accepts no liability related to any default, damage, costs, or problem which may be based on or attributable to: (i) the use of the NVIDIA product in any manner that is contrary to this document or (ii) customer product designs.

No license, either expressed or implied, is granted under any NVIDIA patent right, copyright, or other NVIDIA intellectual property right under this document. Information published by NVIDIA regarding third-party products or services does not constitute a license from NVIDIA to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property rights of the third party, or a license from NVIDIA under the patents or other intellectual property rights of NVIDIA.

Reproduction of information in this document is permissible only if approved in advance by NVIDIA in writing, reproduced without alteration and in full compliance with all applicable export laws and regulations, and accompanied by all associated conditions, limitations, and notices.

THIS DOCUMENT AND ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, “MATERIALS”) ARE BEING PROVIDED “AS IS.” NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE. TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL NVIDIA BE LIABLE FOR ANY DAMAGES, INCLUDING WITHOUT LIMITATION ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF

ANY USE OF THIS DOCUMENT, EVEN IF NVIDIA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Notwithstanding any damages that customer might incur for any reason whatsoever, NVIDIA's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms of Sale for the product.

Trademarks

NVIDIA and the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

© Copyright 2025, NVIDIA. PDF Generated on 11/18/2025