



NVIDIA UFM-SDN Appliance Command Reference Guide v4.14.1

Table of Contents

- Using Command Line Interface 32**
 - CLI Modes 32
 - Syntax Conventions 33
 - Prompt and Response Conventions 33
 - Getting Help 34
 - Using "no" Command Form..... 35
 - CLI Pipeline Operator Commands 37
 - CLI Filtration Options "include" and "exclude" 37
 - CLI Monitoring Option "watch" 38
 - CLI "json-print" Option 39
 - CLI Shortcuts..... 39
 - Users, Roles and Capabilities 41
- System Management..... 43**
 - Network Interfaces 43
 - Interface 44
 - interface 44
 - ip address 45
 - alias ip address..... 45
 - mtu..... 46

duplex	47
speed	48
dhcp.....	49
zeroconf	50
shutdown	50
comment	51
show interfaces	52
ipv6 enable	53
ipv6 address	54
ipv6 dhcp client enable	55
ipv6 dhcp client renew.....	56
Hostname	56
hostname.....	56
ip name-server	57
ip domain-list.....	58
{ip ipv6} host	58
{ip ipv6} map-hostname	59
show hosts	60
Routing	61
{ip ipv6} default-gateway	61
show {ip ipv6} default-gateway	62

{ip ipv6} route.....	63
show {ip ipv6} route.....	64
Network to Media Resolution (ARP & NDP).....	64
arp	65
show arp.....	65
ipv6 neighbor	66
clear ipv6 neighbors	67
show ipv6 neighbors	68
DHCP	69
ip dhcp.....	69
show {ip ipv6} dhcp	70
ipv6 dhcp primary-intf	71
ipv6 dhcp stateless	72
IP Diagnostic Tools	73
ping ping6.....	73
tracert	74
tcpdump.....	76
Network Bonding.....	77
bond.....	77
interface	78
show bonds.....	79

NTP, Clock and Time Zones	80
clock set.....	80
clock timezone	81
ntp	82
ntpdate	83
show clock	83
show ntp.....	84
Software Management	85
image boot.....	85
boot next.....	86
image delete.....	87
image fetch	87
image install	88
image move.....	90
image option.....	90
show bootvar	91
show images	92
Configuration Management.....	93
Saving a Configuration File.....	93
Loading a Configuration File	94
Restoring Factory Default Configuration	94

Managing Configuration Files	95
BIN Configuration Files.....	95
Text Configuration Files.....	96
Configuration Management Commands.....	97
File Transfer	98
ftp-server enable	98
show ftp-server	98
File System.....	99
File System Commands.....	99
Configuration File.....	110
configuration audit	110
configuration copy	111
configuration delete.....	111
configuration fetch	112
configuration jump-start	113
configuration merge.....	114
configuration move	115
configuration new	116
configuration switch-to	117
configuration text fetch	118
configuration text file.....	119

configuration text generate.....	120
configuration upload	121
configuration write	121
write	122
show configuration	123
show running-config.....	125
Local and Remote Logging.....	127
logging local	127
logging local override	128
logging <syslog-ip-address>.....	129
logging receive	130
logging format.....	131
logging fields	132
logging level	133
logging files delete	134
logging files rotation	134
logging files upload.....	135
show logging	136
show log	137
User Management and AAA	139
User Accounts.....	139

username	139
show usernames	140
show users	141
show whoami	142
AAA Methods	143
aaa accounting	143
aaa authentication login default	144
aaa authorization map	145
show aaa	146
RADIUS	147
radius-server	147
radius-server host	148
show radius	149
TACACS+	150
tacacs-server	150
tacacs-server host	151
show tacacs	152
LDAP	153
ldap base-dn	153
ldap {bind-dn bind-password}	154
ldap {group-attribute group-dn}	154

ldap host	155
ldap login-attribute.....	156
ldap port	157
ldap referrals	157
ldap scope.....	158
ldap ssl	159
ldap timeout.....	160
ldap version.....	161
show ldap	161
Security.....	163
ip filter enable	163
ip filter chain	163
show ip filter	164
Firmware Management.....	165
firmware install	165
show firmware.....	166
CLI Session	167
cli clear-history	167
cli default	168
cli session	169
show cli.....	170

Banner	171
banner login	171
banner motd	172
show banner	173
SSH	174
ssh server enable	174
ssh server host-key	174
ssh server listen	175
ssh server min-version	176
ssh server ports	177
ssh server x11-forwarding	177
ssh client global	178
ssh client user	179
slogin.....	180
show ssh client	181
show ssh server.....	182
Remote Login	183
telnet-server enable.....	183
show telnet-server.....	184
Web Server	184
web auto-logout.....	184

web enable	185
web http	186
web httpd listen	187
web https	187
web sessions	188
web proxy auth.....	189
web proxy host	190
show web.....	191
SNMP	192
snmp-server community	192
snmp-server contact.....	193
snmp-server listen	194
snmp-server location	194
snmp-server port.....	195
snmp-server traps.....	196
snmp-server user.....	197
show snmp	198
Scheduled Jobs.....	199
job.....	199
comment	200
command.....	200

enable	201
execute	202
fail-continue	202
name	203
schedule type.....	204
schedule <recurrence-type>	205
show jobs.....	206
Event Notification	207
email autosupport	207
email dead-letter	208
email domain	208
email mailhub	209
email mailhub-port	210
email notify event	210
email notify recipient.....	211
email return-addr	212
email return-host	213
email send-test.....	213
show email	214
Statistics and Alarms	215
stats alarm clear	215

stats alarm enable	216
stats alarm event-repeat	217
stats alarm {rising falling}	218
stats alarm rate-limit	219
stats chd clear.....	220
stats chd enable.....	221
stats chd compute time.....	222
stats sample clear	223
stats sample enable	224
stats sample interval	225
stats clear-all.....	226
stats export	227
show stats alarm	228
show stats chd.....	229
show stats cpu.....	230
show stats sample	231
Chassis Management.....	232
show version	232
show inventory	233
show chassis health.....	234
show memory.....	235

show chassis input power	236
chassis altitude	237
chassis remote-management dhcp	237
chassis remote-management ip.....	238
chassis remote-management ipv6	239
chassis remote-management username	240
show chassis firmware	240
show chassis remote-management.....	241
show chassis altitude	242
show chassis raid.....	243
show chassis raid rebuild-status.....	244
Cryptography (X.509, IPSec)	245
crypto ipsec ike	245
crypto ipsec peer local.....	246
crypto certificate ca-list.....	247
crypto certificate default-cert	248
crypto certificate generation	249
crypto certificate name.....	250
crypto certificate system-self-signed.....	251
show crypto certificate	252
show crypto ipsec	253

Docker Container	255
docker	255
commit	256
remove image	256
exec	257
file fetch	258
image upload	258
file image upload	259
label	260
label-fetch	260
label-upload	261
pull	262
save	262
shutdown	263
start	264
show docker containers	265
show docker images	267
show docker labels	268
show docker ps	268
UFM Commands	270
General	271

ufm start	271
show ufm status.....	271
ufm counters	273
show ufm counters.....	274
License	275
ufm license install	275
ufm license delete.....	276
show ufm license.....	277
UFM Configuration Management.....	278
ufm configuration delete	278
ufm configuration export	278
ufm configuration fetch	279
ufm configuration import.....	280
ufm configuration upload.....	281
Database Management	282
ufm database import	282
ufm database export	282
ufm database delete	283
ufm database upload	284
Data Management.....	285
ufm data backup	285

ufm data delete	285
ufm data fetch	286
ufm data reset	287
ufm data restore	287
ufm data upload	288
High Availability	289
ufm ha configure.....	289
ufm ha configure dual-subnet	290
ufm ha	290
Telemetry	291
telemetry target enable	291
telemetry target import-filter-file	292
telemetry target ip port	293
telemetry target message type	294
telemetry streaming enable.....	294
show telemetry.....	295
show telemetry target	296
ufm low-frequency-telemetry enable	297
show ufm low-frequency-telemetry	297
UFM Multi-site Portal	298
ufm multi-site enable	298

ufm multi-site interval	299
ufm multi-site port	300
ufm multi-site server	300
ufm multi-site site-name	301
ufm multi-site username password	302
show ufm multi-site	302
UFM External Subnet Manager	303
ufm safe-stop	303
ufm external-sm trust	304
ufm external-sm register	305
show ufm external-sm	306
show ufm external-sm status	306
UFM Process Commands	307
ufm process health start	307
ufm process model start	308
ufm process telemetry start	309
ufm process sharp start	310
UFM Firmware Management	311
ufm firmware fetch	311
ufm firmware import	312
ufm firmware delete	312

UFM Running Modes.....	313
ufm mode	313
UFM Logs	314
ufm logging files delete oldest	314
ufm logging files rotation criteria.....	315
ufm logging files rotation max-num.....	316
ufm logging level.....	316
ufm logging syslog	317
ufm logging syslog level.....	318
ufm logging syslog enable	318
ufm logging syslog ufm-events enable.....	319
show ufm console log	320
show ufm console log continuous	321
show ufm console log files	321
show ufm event log.....	322
show ufm event log continuous.....	323
show ufm event log files.....	324
show ufm logging	325
show ufm log	326
show ufmhealth log.....	327
Advanced Subnet Manager Configuration	328

ib sm <hm-action>	328
ib sm <hm-num>	329
ib sm hm-reboots-period	330
ib sm hm-unhealthy-ports-checks enable	331
show ib sm hm-unhealthy-ports	332
ib sm opensm-health-policy-merge	333
ib sm reassign-lids	334
show ib sm reassign-lids	334
UFM Web Client	335
ufm web-client mode	335
ufm web-client client-authentication ca-cert fetch	336
ufm web-client client-authentication associate-user	337
show ufm web-client	337
ufm web-client server-cert hostname	339
ufm web-client server-cert fetch	339
ufm web-client client-authentication cert-refresh enable	340
ufm web-client client-authentication cert-refresh ca-cert	341
ufm web-client client-authentication cert-refresh self-client-cert fetch	341
ufm web-client client-authentication cert-refresh self-client-cert password-file fetch	342
ufm web-client client-authentication cert-refresh server-cert	343
ufm web-client client-authentication cert-refresh run-now	344

ufm ws-address.....	344
show ufm ws-address.....	345
Management Interface Monitoring	346
ufm mgmt-interface monitor enable	346
ufm mgmt-interface monitor interval	346
ufm mgmt-interface	347
show ufm mgmt-interface	348
AHX Monitoring	349
ib managed-switch ahx-monitor enable	349
managed-switch ahx-monitor interval.....	349
ib managed-switch ahx-monitor device	351
show ib managed-switch ahx-monitor	352
UFM Events Forwarder	353
ufm events-forwarder enable	353
ufm events-forwarder server.....	354
show ufm events-forwarder	354
ufm events max-restored	355
ufm events persistency enable	356
show ufm events	356
UFM Virtualization	357
ufm virtualization enable.....	357

ufm virtualization interval	358
show ufm virtualization	358
UFM Agent	359
ufm agent interface	359
show ufm agent	360
Unhealthy Ports	361
ufm unhealthy-ports isolate-high-ber isolation-mode	361
ufm unhealthy-ports isolate-high-ber enable	362
ufm unhealthy-ports switch-ports-threshold	362
ufm high-ber-ports enable-warnings	363
show ufm unhealthy-ports	364
show ufm high-ber-ports	364
ufm network-fast-recovery enable	365
show ufm network-fast-recovery	366
UFM Audit	367
ufm track-conf-changes enable	367
show ufm track-conf-changes	368
UFM Plugin Commands	369
ufm plugin	369
show ufm plugin	370
Fabric Discovery	371

ufm discovered-switch-ip-version	371
InfiniBand Commands	372
InfiniBand Utilities	372
ib ibdiagnet	372
ib ibdiagnet gmp-window	373
show ib ibdiagnet gmp-window	373
ib ibdiagnet smp-window	374
show ib ibdiagnet smp-window	375
ib ibdiagnet upload	375
ib ibdiagpath	376
ib ibdiagpath upload	377
ib perfquery	377
ib ibtracert.....	378
ib ibportstate.....	379
ib smpquery.....	379
ib sminfo	380
ib smpdump.....	381
ib ibqueryerrors	381
ib ibroute.....	382
ib ibrouters	383
ib ibnetdiscover	383

ib ibnetdiscover upload	384
ib ibstat	385
ib ibstatus	385
ib ibnodes	386
ib saquery	387
ib ibhosts	387
ib ibswitches	388
ib iblinkinfo	389
ib vendstat	389
ib ibaddr	390
ib ibping	391
ib ibsysstat	391
ib smparquery	392
OpenSM	393
ib qos	393
ib sm allow-both-pkeys	393
show ib sm allow-both-pkeys	394
ib sm ar-sl-mask	395
show ib sm ar-sl-mask	395
ib sm configuration import	396
show ib sm configuration import	397

ib sm congestion-control	398
show ib sm congestion-control.....	399
ib sm dfp max-cas-on-spine	399
show ib sm dfp max-cas-on-spine	400
ib sm dfp down-up-turns-mode	401
show ib sm dfp down-up-turns-mode	401
ib sm files opensm-dump delete	402
ib sm force-log-flush	403
ib sm force-link-speed	403
ib sm keep-pkey-indexes	404
show ib sm keep-pkey-indexes.....	405
ib sm log-flags.....	405
show ib sm log.....	406
ib sm partition-config-merge	407
ib sm root-guid	408
show ib sm root-guid	408
ib sm routing-engines	409
ib sm routing-threads-num	410
show ib sm routing-threads-num	411
ib sm scatter-ports	411
ib sm smp-window	412

show ib sm smp-window	413
ib sm ufm-events	413
show ib sm ufm-events.....	414
ib sm use-ucast-cache enable.....	415
ib sm virtualization enable	415
ib sm virtualization ignore	416
show ib sm virtualization	417
ib sm virt-max-ports-in-process	417
show ib sm virt-max-ports-in-process	418
ufm multi-port-sm	419
show ufm multi-port-sm	419
ufm sm-static-lid.....	420
show ufm sm-static-lid	421
InfiniBand Router	421
ib router set-num-of-subnets	421
ib router add-interfaces-to-subnet.....	422
ib router remove-interfaces-from-subnet.....	423
ib router add-subnet-to-router	424
ib router remove-subnet-from-router	425
ib router set-ufm-sm-router-support	425
NVIDIA SHARP	426

SHARP Aggregation Manager	427
ib sharp enable	427
ib sharp allocation enable	427
ib sharp job-pkey-on-tree enable	428
ib sharp smx-protocol	429
ib sharp smx-sock-interface	429
ib sharp smx-sock-port	430
ib sharp smx-ucx-interface	431
ib sharp topology-api enable	431
show ib sharp	432
show ib sharp log	433
show ib sharp log continuous	434
show ib sharp log files	434
show ib sharp log matching	435
show ib sharp log not matching	436
SHARP Configuration in OpenSM	436
ib sm sharp enable	436
ib sm sharp ignore	437
show ib sm sharp	438
SHARP API	438
ufm sharp-api event-query-interval	438

ufm sharp-api event-query-retries	439
show ufm sharp-api.....	440
Partition	441
ib partition management defmember	441
show ib partition.....	442
ib partition management mtu-limit <2K 4K>.....	442
Switch Auto-provisioning.....	443
ib managed-switch image ppc fetch	443
ib managed-switch image x86 fetch	444
ib managed-switch configuration global fetch	445
ib managed-switch list fetch.....	446
ib managed-switch settings fetch	446
ib managed-switch settings upload	447
ib managed-switch settings admin-password.....	448
ib managed-switch settings reboot-timeout.....	449
ib managed-switch settings upgrade-both-partitions	450
ib managed-switch auto-provisioning start	450
show ib managed-switch settings	451
show ib managed-switch auto-provisioning status.....	452
show ib managed-switch list	453
Fabric Topology.....	454

ib topo-file generate	454
ib topo-file upload.....	454
ib fabric-split generate	455
ib fabric-split upload	456
ib fabric-split delete	456
SA_Key	457
SAETM.....	457
ib sm sa-enhanced-trust-model.....	457
ib sm sa-etm-max-num-event-subs	458
ib sm sa-etm-max-num-mcast-groups	459
ib sm sa-etm-max-num-services	459
show ib sm sa-enhanced-trust-model.....	460
show ib sm sa-etm-max-num-event-subs.....	461
show ib sm sa-etm-max-num-mcast-groups	461
show ib sm sa-etm-max-num-services	462
UFM Configuration	463
ufm randomize-sa-key	463
show ufm randomize-sa-key.....	463
MKey	464
ufm mkey-per-port	464
show ufm mkey-per-port	465

ufm mkey-global-seed	465
show ufm mkey-global-seed.....	466
ib sm mkey-lease-period.....	467
show ib sm mkey-lease-period.....	467
HCA Commands.....	468
ib hca-smp-window	468
ib hca-vl15-window.....	469
ufm hca-grouping enable	469
show ib hca-smp-window	470
show ib hca-vl15-window	471
show ufm hca-grouping	472
Document Revision History	473

 You can download a PDF version here.

About This Document



NVIDIA Unified Fabric Manager for Software Defined Networks (UFM-SDN) appliance enables data center operators to efficiently provision, monitor and operate large-scale compute and storage data center interconnect infrastructures. UFM eliminates the complexity of fabric management, while also providing deep visibility into traffic and optimizing fabric performance.

This reference guide documents all the commands that can be used to configure the NVIDIA® UFM®-SDN Appliance.

Technical Support

Customers who purchased NVIDIA products directly from NVIDIA are invited to contact us through the following methods:

- E-mail: enterprisesupport@nvidia.com
- Enterprise Support page: <https://www.nvidia.com/en-us/support/enterprise>

Customers who purchased NVIDIA M-1 Global Support Services, please see your contract for details regarding Technical Support.

Customers who purchased NVIDIA products through an NVIDIA-approved reseller should first seek assistance through their reseller.

Document Revision History

For the list of changes made to this document, refer to [Document Revision History](#).

Using Command Line Interface

UFM-SDN Appliance is equipped with an industry-standard command line interface (CLI). The CLI is accessed through SSH or Telnet sessions or directly through the console port on the front panel, if it exists. This page explains how to use the CLI of UFM-SDN Appliance.

CLI Modes


The CLI has the following modes, and each mode makes available a different set of commands for execution. The different CLI configuration modes are:


Mode/Context	Description
standard	When the CLI is launched, it begins in Standard mode. This is the most restrictive mode and only has commands to query a restricted set of state information. Users cannot take any actions that directly affect the system, nor can they change any configuration.
enable	The "enable" command moves the user to Enable mode. This mode offers commands to view all state information and take actions like rebooting the system, but it does not allow any configuration to be changed. Its commands are a superset of those in Standard mode. To return to Standard mode, enter "disable" or "exit".
config	The "configure terminal" command moves the user from Enable mode to Config mode. Config mode is allowed only for user accounts in the "admin" role (or capabilities) - see Users, Roles and Capabilities . This mode has a full unrestricted set of commands to view anything, take any action, or change any configuration. Its commands are a superset of those in Enable mode. To return to Enable mode, enter "exit" or "no configure". Note that moving directly from/to Standard mode to/from Config mode is not possible.
config ufm	Configuration mode for UFM interface. Config ufm mode is allowed only for user accounts in the "admin" role (or capabilities) - see Users, Roles and Capabilities . This mode has a full unrestricted set of commands to view anything, take any action, or change any configuration. Its commands are a superset of those in config mode and enables you to configure UFM-related commands.
config interface management	Configuration mode for management interfaces
Any configuration mode	Several commands such as "show" can be applied within any context

Syntax Conventions

To help you identify the different parts of a CLI command, the following table explains conventions of presenting the syntax of commands.

Syntax Convention	Description	Example
< > Angled brackets	Indicate a value/variable that must be replaced. mtu <value> value - MTU size in MB	<1...65535> or <interface>
[] Square brackets	Enclose optional parameters. However, only one parameter out of the list of parameters listed can be used. The user cannot have a combination of the parameters unless stated otherwise.	[destination-ip destination-port destination-mac]
{ } Braces	Enclose alternatives or variables that are required for the parameter in square brackets.	[mode {active on passive}]
Pipe	Identify mutually exclusive choices.	active on passive

 Do not use the angled or square brackets, vertical bar, or braces in command lines. This guide uses these symbols only to show the different entry types.

 CLI commands and options are in lowercase and are case-sensitive. For example, when you enter the enable command, enter it all in lowercase. It cannot be ENABLE or Enable. Text entries you create are also case-sensitive.

Prompt and Response Conventions

The prompt always begins with the hostname of the system. What follows depends on what command mode the user is in. To demonstrate by example, assuming the machine name is "ufm-sdn-app", the prompts for each of the modes are:

```
ufm-sdn-app > (Standard mode)
ufm-sdn-app # (Enable mode)
ufm-sdn-app (config) # (Config mode)
```

The following session shows how to move between command modes:

```
ufm-sdn-app > (You start in Standard mode)
ufm-sdn-app > enable (Move to Enable mode)
ufm-sdn-app # (You are in Enable mode)
ufm-sdn-app # configure terminal (Move to Config mode)
ufm-sdn-app (config) # (You are in Config mode)
ufm-sdn-app (config) # exit (Exit Config mode)
ufm-sdn-app # (You are back in Enable mode)
ufm-sdn-app # disable (Exit Enable mode)
ufm-sdn-app > (You are back in Standard mode)
```

Commands entered do not print any response and simply show the command prompt after you press <Enter>.

If an error is encountered in executing a command, the response will begin with "%", followed by some text describing the error.

Getting Help

You may request context-sensitive help at any time by pressing "?" on the command line. This will show a list of choices for the word you are on, or a list of top-level commands if you have not typed anything yet.

For example, if you are in Standard mode and you type "?" at the command line, then you will get the following list of available commands.

```
ufm-sdn-app > ?
cli          Configure CLI shell options
enable       Enter enable mode
exit         Log out of the CLI
help         View description of the interactive help system
no           Negate or clear certain configuration options
show         Display system configuration or statistics
slogin       Log into another system securely using ssh
switch       Configure switch on system
```

```
telnet          Log into another system using telnet
terminal       Set terminal parameters
traceroute     Trace the route packets take to a destination
switch >
```

If you type a legal string and then press "?" without a space character before it, then you will either get a description of the command that you have typed so far or the possible command/parameter completions. If you press "?" after a space character and "<cr>" is shown, this means that what you have entered so far is a complete command, and that you may press Enter (carriage return) to execute it.

Try the following to get started:

```
?
show ?
show c?
show clock?
show clock ?
show interfaces ?      (from enable mode)
```

You can also enter "help" to view a description of the interactive help system.

Note also that the CLI supports command and/or parameter tab-completions and their shortened forms. For example, you can enter "en" instead of the "enable" command, or "cli cl" instead of "cli clear-history". In case of ambiguity (more than one completion option is available, that is), then you can hit double tabs to obtain the disambiguation options. Thus, if you are in Enable mode and wish to learn which commands start with the letter "c", type "c" and click twice on the tab key to get the following:

```
ufm-sdn-app # c<tab>
clear      cli      configure
ufm-sdn-app # c
```

This signifies that there are three commands that start with the letter "c": clear, cli and configure.

Using "no" Command Form

Several config commands feature a "no" form whose purpose is to reset a parameter value to its inherited or default value, or to disable a configuration.

The command sequence below performs the following:

1. Displays the current CLI session option.
2. Disables auto-logout.
3. Displays the new CLI session options (auto-logout is disabled).
4. Re-enables auto-logout (after 15 minutes).
5. Displays the final CLI session options (auto-logout is enabled).

```
// 1. Display the current CLI session options
ufm-sdn-app (config) # show cli
CLI current session settings:
Maximum line size: 8192
Terminal width: 157 columns
Terminal length: 60 rows
Terminal type: xterm
Auto-logout: 15 minutes
Paging: enabled
Progress tracking: enabled
Prefix modes: enabled
...
// 2. Disable auto-logout
ufm-sdn-app (config) # no cli session auto-logout
// 3. Display the new CLI session options
ufm-sdn-app (config) # show cli
CLI current session settings:
Maximum line size: 8192
Terminal width: 157 columns
Terminal length: 60 rows
Terminal type: xterm
Auto-logout: disabled
Paging: enabled
Progress tracking: enabled
Prefix modes: enabled
...
// 4. Re-enable auto-logout after 15 minutes
ufm-sdn-app (config) # cli session auto-logout 15
// 5. Display the final CLI session options
ufm-sdn-app (config) # show cli
CLI current session settings:
Maximum line size: 8192
Terminal width: 157 columns
```

```
Terminal length: 60 rows
Terminal type: xterm
Auto-logout: 15 minutes
Paging: enabled
Progress tracking: enabled
Prefix modes: enabled
...
```

CLI Pipeline Operator Commands

CLI Filtration Options "include" and "exclude"

The UFM-SDN appliance CLI supports filtering "show" commands to display lines containing or excluding certain phrases or characters. To filter the outputs of the "show" commands use the following format:

```
ufm-sdn-app (config) # <show command> | {include | exclude} <extended regular expression> [<ignore-case>] [next <lines>] [prev <lines>]
```

The filtering parameters are separated from the show command they filter by a pipe character (i.e. "|"). Quotation marks may be used to include or exclude a string including space, and multiple filters can be used simultaneously. For example:

```
ufm-sdn-app (config) # <show command> | {include <extended regular expression>} [<ignore-case>] [next <lines>] [prev <lines>] | exclude <extended regular expression> [<ignore-case>] [next <lines>] [prev <lines>]]
```

Example for "include":

```
ufm-sdn-app (config) # show clock | include Time
Time:      15:46:54
Time zone: UTC
```

Example for "exclude":

```
ufm-sdn-app (config) # show clock | exclude Time
Date:                2020/08/07
                    (Etc/UTC)
```

CLI Monitoring Option "watch"

Running this command displays a show-command output that is updated at a time interval specified by the "interval" parameter (2 seconds is the default).

```
ufm-sdn-app (config) # <show command> | watch [diff] [interval <1-100 secs>]
```

The "diff" parameter highlights the differences between each iteration of the command.

For example running the command "show power | watch diff interval 1" yields something similar to the following:

```
-----
Module  Device          Sensor  Power   Voltage  Current  Feed  Status
      [Watts] [Watts]  [Amp]
-----
PS1     power-mon        input   85.00   230.00   0.38     AC   OK
PS2     power-mon        -       -       -        -       -   FAIL

Total power used : 85.00 Watts
Total power capacity : 460.00 Watts
Total power available : 375.00 Watts
Maximum consumed power of all turned on modules: 46.00 Watts
```

With the highlighted black blocks indicating the change that has occurred between one iteration of the command from one second to the next.

To exit "watch" mode, press Ctrl+C. The "watch" option may be used in conjunction with the "include" and "exclude" options as follows:

```
ufm-sdn-app (config) # <show command> | {include | exclude} <extended regular expression> | watch [diff] [interval <1-100 secs>]
```

It is possible to count the number of lines in an output of a "show" command by using the following:

```
ufm-sdn-app (config) # <show command> | count
```

For example:

```
ufm-sdn-app (config) # show clock | count  
4
```

CLI "json-print" Option

The UFM-SDN appliance CLI supports printing "show" commands in JSON syntax.

To print the output of the show commands as JSON, use the following format:

```
ufm-sdn-app (config) # <show command> | json-print
```

Running the command displays an output of the show command in JSON syntax structure instead of its regular format. For example:

```
ufm-sdn-app (config) # show ftp-server  
FTP server enabled: no  
ufm-sdn-app (config) # show ftp-server | json-print  
{  
  "FTP server enabled": "no"  
}
```

The "json-print" option cannot be used together with filtering ("include" and "exclude") and/or monitoring ("watch").

CLI Shortcuts

The following table presents the available keyboard shortcuts for the UFM-SDN CLI.

Key Combination	Description
Ctrl-a	Move cursor to beginning of line
Ctrl-b	Move cursor backward one character without deleting
Ctrl-c	Terminate operation
Ctrl-d	If cursor is in the middle of the line, delete one character forward If cursor is at the end of the line, show autocomplete options for current word or word fragment If cursor at an empty line, same as Esc
Ctrl-e	Move cursor to end of line
Ctrl-f	Move cursor forward one character
Ctrl-h	Delete one character backwards from cursor
Ctrl-i	Auto-complete current word (same as TAB)
Ctrl-j	Return carriage (same as ENTER)
Ctrl-k	Delete line after cursor
Ctrl-l	Clear screen and show line at the top of terminal window
Ctrl-m	Return carriage (same as ENTER)
Ctrl-n	Next line (same as DOWN ARROW)
Ctrl-p	Next line (same as UP ARROW)
Ctrl-t	Transpose the two characters on either side of cursor

Key Combination	Description
Ctrl-u	Delete line
Ctrl-w	Delete the last word
Ctrl-y	Retrieve ("yank") last item deleted
Esc b	Move cursor one word backward
Esc c	Capitalizes first letter in word after cursor
Esc d	Delete one word forward from cursor
Esc f	Move one word forward from cursor
Esc l	Change word after cursor to lowercase letters
Esc Ctrl-h	Delete one word backward from cursor
Esc [A	Next line (same as DOWN ARROW)
Esc [B	Next line (same as UP ARROW)
Esc [C	Move forward one character from cursor
Esc [D	Move backward one character from cursor

Users, Roles and Capabilities

The following table describes the predefined users and their roles and capabilities. The roles described below can be assigned to new users and to existing ones as well.

Username	Role and Capability	Description
admin	System Administrator	Can perform all operations allowed to System Administration group for both Appliance Management and UFM Application
ufmsysadmin	UFM System Administrator	Can perform all operations allowed to Fabric Administration group
ufmfabadmin	UFM Fabric Administrator	Can perform all operations allowed to Fabric Operator group users, and can also create, delete, and modify environments and global networks
ufmfaboperator	UFM Fabric Operator	Can perform all operations allowed to Monitoring group users, and can also configure fabric, modify the fabric design, define logical objects, and allocate resources. Fabric Operator group users cannot create, delete or modify environments or global networks.
ufmfabmonitor	UFM Monitoring Only	Can see the fabric configuration, open monitoring sessions, define monitoring templates, and export monitoring data to CSV files
ufmportalmanager	Multi-site Portal Administration	Multi-site Portal Administration group
ufmportaluser	Multi-site Portal Monitoring	Multi-site Portal Monitoring group

System Management

- [Network Interfaces](#)
- [NTP, Clock and Time Zones](#)
- [Software Management](#)
- [Configuration Management](#)
- [Local and Remote Logging](#)
- [User Management and AAA](#)
- [Security](#)
- [Firmware Management](#)
- [CLI Session](#)
- [Banner](#)
- [SSH](#)
- [Remote Login](#)
- [Web Server](#)
- [SNMP](#)
- [Scheduled Jobs](#)
- [Event Notification](#)
- [Statistics and Alarms](#)
- [Chassis Management](#)
- [Cryptography \(X.509, IPSec\)](#)
- [Docker Container](#)

Network Interfaces

- [Interface](#)
- [Hostname](#)
- [Routing](#)
- [Network to Media Resolution \(ARP & NDP\)](#)
- [DHCP](#)
- [IP Diagnostic Tools](#)
- [Network Bonding](#)

Interface

This chapter describes the commands that configure and monitor the network interface.

interface

	<code>interface {eth0 eth1 eth2 eth3 ib0 ib1 bond0}</code> Enters a network interface context.	
Syntax Description	<code>eth0</code>	Management port 0 (out of band)
	<code>eth1</code>	Management port 1 (out of band)
	<code>eth2</code>	Management port 2 (out of band)
	<code>eth3</code>	Management port 3 (out of band)
	<code>ib0</code>	InfiniBand interface 0 (part of bond0)
	<code>ib1</code>	InfiniBand interface 1 (part of bond0)
	<code>bond0</code>	IP-over-IB bonded interface which consist of ib0 and ib1
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # interface eth0 ufmap1 [mgmt-sa] (config interface eth0) #</pre>	
Related Commands	show interfaces	
Notes		

ip address

	ip address <IP address> <netmask> no ip address Sets the IP address and netmask of this interface. The no form of the command clears the IP address and netmask of this interface.	
Syntax Description	IP address	IPv4 address
	netmask	Subnet mask of IP address
Default	0.0.0.0/0	
Configuration Mode	config interface	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config interface eth0) # ip address 10.10.10.10 255.255.255.0</pre>	
Related Commands	interface show interfaces	
Notes	If DHCP is enabled on the specified interface, then the DHCP IP assignment will hold until DHCP is disabled	

alias ip address

	alias <index> ip address < IP address> <netmask> no alias <index> Adds an additional IP address to the specified interface. The secondary address will appear in the output of “show interface” under the data of the primary interface along with the alias. The no form of the command removes the secondary address to the specified interface.
--	---

Syntax Description	alias	A number to be associated with the secondary IP
	IP address	IPv4 address
	netmask	Subnet mask of IP address
Default	N/A	
Configuration Mode	config interface	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config interface eth0) # alias 2 ip address 9.9.9.9 255.255.255.255</pre>	
Related Commands	interface show interfaces	
Notes	<ul style="list-style-type: none"> • If DHCP is enabled on the specified interface, then the DHCP IP assignment will hold until DHCP is disabled • More than one additional IP address can be added to the interface 	

mtu

	mtu <size> no mtu Sets the maximum transmission unit (MTU) size for this interface in bytes. The no form of the command resets the MTU to its default.	
Syntax Description	bytes	Range: 65-1500 [bytes]
Default	N/A	
Configuration Mode	config interface	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config interface eth0) # mtu 1500</pre>
Related Commands	<pre>interface show interfaces <if-name></pre>
Notes	

duplex

	<pre>duplex <duplex> no duplex</pre> <p>Sets the duplex mode of the interface. The no form of the command resets the duplex setting to its default value.</p>	
Syntax Description	duplex	<ul style="list-style-type: none"> • half - half duplex • full - full duplex • auto - auto-duplex sensing (half or full)
Default	auto	
Configuration Mode	config interface	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config interface eth0) # duplex auto</pre>	
Related Commands	<pre>interface show interfaces <if-name></pre>	
Notes	<ul style="list-style-type: none"> • Setting the duplex to “auto” also sets the speed to “auto” • Setting the duplex to “half” or “full” also sets the speed to a manual setting which is determined by querying the interface to find out its current auto-detected state 	

speed

	<code>speed <speed></code> <code>no speed</code> Sets interface speed in Mbps. The no form of the command resets the speed setting to its default value.	
Syntax Description	<code>speed</code>	<ul style="list-style-type: none"> • 10 - 10Mbps • 100 - 100Mbps • 1000 - 1000Mbps • auto - auto-speed sensing (10/100/1000Mbps)
Default	<code>auto</code>	
Configuration Mode	<code>config interface</code>	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config interface eth0) # speed auto</pre>	
Related Commands	<code>interface</code> <code>show interfaces <if-name></code>	
Notes	<ul style="list-style-type: none"> • Setting the speed to “auto” also sets the duplex to “auto” • Setting the speed to 10, 100, or 1000 also sets the duplex to a manual setting which is determined by querying the interface to find out its current auto-detected state 	

dhcp

	dhcp [renew] no dhcp Enables DHCP on the specified interface. The no form of the command disables DHCP on the specified interface.	
Syntax Description	renew	Forces a renewal of the IP address. A restart on the DHCP client for the specified interface will be issued.
Default	Enabled	
Configuration Mode	config interface	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config interface eth0) # dhcp</pre>	
Related Commands	interface show interfaces <if-name> configured	
Notes	<ul style="list-style-type: none"> • When enabling DHCP, the IP address and netmask are received via DHCP hence, the static IP address configuration is ignored • Enabling DHCP disables zeroconf and vice versa • Setting a static IP address and netmask does not disable DHCP. DHCP is disabled by using the “no” form of this command, or by enabling zeroconf. 	

zeroconf

	<code>zeroconf</code> <code>no zeroconf</code> Enables zeroconf on the specified interface. The no form of the command disables the use of zeroconf on the specified interface.
Syntax Description	N/A
Default	Disabled
Configuration Mode	config interface
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config interface eth0) # zeroconf</pre>
Related Commands	<code>interface</code> <code>show interfaces <if-name> configured</code>
Notes	<ul style="list-style-type: none">• Enabling zeroconf randomly chooses a unique link-local IPv4 address from the 169.254.0.0/16 block• This command is an alternative to DHCP• Enabling zeroconf disables DHCP and vice versa

shutdown

	<code>shutdown</code> <code>no shutdown</code> Disables the specified interface. The no form of the command enables the specified interface.
Syntax Description	N/A

Default	Enabled
Configuration Mode	config interface
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config interface eth0) # shutdown</pre>
Related Commands	interface show interfaces <if-name> configured
Notes	

comment

	comment <string> no comment Adds a comment for an interface. The no form of the command removes a comment for an interface.	
Syntax Description	string	A free-form string that has no semantics other than being displayed when interface records are listed
Default	""	
Configuration Mode	config interface	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config interface eth0) # comment my_interface</pre>	
Related Commands	interface show interfaces <if-name>	

Notes	
-------	--

show interfaces

	<p><code>show interfaces <ifname> [configured brief]</code></p> <p>Displays information about the specified interface, configuration status, and counters.</p>	
Syntax Description	ifname	The interface whose data to display (e.g., “eth0”, “eth1”, etc.)
	configured	Displays interface configuration
	brief	Displays interface configuration and status in brief format
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
	4.1.0	Updated output
Example	<pre> ufmap1 [mgmt-sa] (config) # show interfaces eth0 Interface eth0 status: Comment: Admin up: yes Link up: yes DHCP running: yes IP address: 172.30.30.8 Netmask: 255.255.0.0 IPv6 enabled: yes Autoconf enabled: no Autoconf route: yes Autoconf privacy: no DHCPv6 running: no IPv6 addresses: 1 IPv6 address: fe80::a6bf:1ff:fe00:9c20/64 Speed: 1000Mb/s (auto) </pre>	

	<pre>Duplex: full (auto) Interface type: ethernet Interface source: physical MTU: 1500 HW address: A4:BF:01:00:9C:20 RX bytes: 1629833421 TX bytes: 2808005 RX packets: 12981118 TX packets: 51988 RX mcast packets: 26852703 TX discards: 0 RX discards: 0 TX errors: 0 RX errors: 0 TX overruns: 0 RX overruns: 0 TX carrier: 0 RX frame: 0 TX collisions: 0 TX queue len: 1000</pre>
Related Commands	interface <ifname> ip address <IP address> <netmask>
Notes	

ipv6 enable

	<pre>ipv6 enable no ipv6 enable</pre> <p>Enables all IPv6 addressing for this interface. The no form of the command disables all IPv6 addressing for this interface.</p>
Syntax Description	N/A
Default	Disabled
Configuration Mode	config interface management
History	4.1.0

Example	<pre>ufmap1 (config interface eth0)# ipv6 enable</pre>
Related Commands	ipv6 address show interface
Notes	<ul style="list-style-type: none"> • The interface identifier is a 64-bit long modified EUI-64, which is based on the MAC address of the interface. • If IPv6 is enabled on an interface, the system will automatically add a link-local address to the interface. Link-local addresses can only be used to communicate with other hosts on the same link, and packets with link-local addresses are never forwarded by a router. • A link-local address, which may not be removed, is required for proper IPv6 operation. The link-local addresses start with “fe80::”, and are combined with the interface identifier to form the complete address.

ipv6 address

	<pre>ipv6 address {<IPv6 address>/<netmask> autoconfig [default privacy]}</pre> <pre>no ipv6 {<IPv6 address/netmask> autoconfig [default privacy]}</pre> <p>Configures IPv6 address and netmask to this interface, static or autoconfig options are possible. The no form of the command removes the given IPv6 address and netmask or disables the autoconfig options.</p>	
Syntax Description	IPv6 address/netmask	Configures a static IPv6 address and netmask. Format example: 2001:db8:1234::5678/64.
	autoconfig	Enables IPv6 stateless address auto configuration (SLAAC) for this interface. An address will be automatically added to the interface based on an IPv6 prefix learned from router advertisements, combined with an interface identifier.
	autoconfig default	Enables default learning routes. The default route will be discovered automatically, if the autoconfig is enabled.
	autoconfig privacy	Uses privacy extensions for SLAAC to construct the autoconfig address, if the autoconfig is enabled
Default	No IP address available, auto config is enabled	
Configuration Mode	config interface management	
History	4.1.0	

Example	<pre>ufmap1 (config interface eth0)# ipv6 fe80::202:c9ff:fe5e:a5d8/64</pre>
Related Commands	<pre>ipv6 address show interface</pre>
Notes	<ul style="list-style-type: none"> • On a given interface, up to 16 addresses can be configured • For Ethernet, the default interface identifier is a 64-bit long modified EUI-64, which is based on the MAC address of the interface

ipv6 dhcp client enable

	<pre>ipv6 dhcp client enable no ipv6 dhcp client enable</pre> <p>Enables DHCPv6 on this interface. The no form of the command disables DHCPv6 on this interface.</p>
Syntax Description	N/A
Default	Enabled
Configuration Mode	config interface management
History	4.1.0
Example	<pre>ufmap1 (config interface eth0)# ipv6 dhcp client enable</pre>
Related Commands	<pre>ipv6 dhcp client renew show ipv6 dhcp</pre>
Notes	

ipv6 dhcp client renew

	<code>ipv6 dhcp client renew</code> Renews DHCPv6 lease for this interface.
Syntax Description	N/A
Default	N/A
Configuration Mode	config interface management
History	4.1.0
Example	<pre>ufmapl (config interface eth0)# ipv6 dhcp client renew</pre>
Related Commands	<code>ipv6 dhcp client enable</code> <code>show ipv6 dhcp</code>
Notes	

Hostname

hostname

	<code>hostname <hostname></code> <code>no hostname</code> Sets a static system hostname. The no form of the command clears the user-configured hostname.
Syntax Description	<code>hostname</code> String

Default	Default hostname
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # hostname ufmapl-hostname ufmapl-hostname [mgmt-sa] (config) #</pre>
Related Commands	show hosts
Notes	"." is not permitted as a valid character of the hostname.

ip name-server

	<p>ip name-server <IPv4/IPv6 address> no name-server</p> <p>Sets the static name server. The no form of the command clears the name server.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # ip name-server 9.9.9.9</pre>
Related Commands	show hosts
Notes	

ip domain-list

	ip domain-list <domain_name> no ip domain-list Sets the static domain name. The no form of the command clears the domain name.	
Syntax Description	domain_name	String
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # ip domain-list mydomain2.com</pre>	
Related Commands	show hosts	
Notes	<ul style="list-style-type: none"> • A domain name is an identification string that defines a realm of administrative autonomy, authority, or control in the Internet • Domain names are formed by the rules and procedures of the Domain Name System (DNS) 	

{ip | ipv6} host

	{ip ipv6} host <hostname> <ip-address> no {ip ipv6} host <hostname> <ip-address> Sets the static domain name. The no form of the command clears the domain name.	
Syntax Description	hostname	String

	ip-address	IPv4 or IPv6 address
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ip host test-host 1.2.3.4 ufmapl [mgmt-sa] (config) # ipv6 host my-ipv6-host 2001::8f9</pre>	
Related Commands	show hosts	
Notes		

{ip | ipv6} map-hostname

	<pre>{ip ipv6} map-hostname no {ip ipv6} map-hostname</pre> <p>Maps between the currently-configured hostname and the loopback address 127.0.0.1. The no form of the command clears the mapping.</p>
Syntax Description	N/A
Default	IPv4 mapping is enabled by default IPv6 mapping is disabled by default
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # ip map-hostname</pre>

Related Commands	show hosts
Notes	<ul style="list-style-type: none"> • If no mapping is configured, a mapping between the hostname and the IPv4 loopback address 127.0.0.1 will be added • The no form of the command maps the hostname to the IPv6 loopback address if there is no statically configured mapping from the hostname to an IPv6 address (disabled by default) • Static host mappings are preferred over DNS results. As a result, with this option set, you will not be able to look up your hostname on your configured DNS server; but without it set, some problems may arise if your hostname cannot be looked up in DNS.

show hosts

	<p>show hosts</p> <p>Displays hostname, DNS configuration, and static host mappings.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmapl [mgmt-sa] (config) # show hosts Hostname: ufmapl Name servers: 9.9.9.9 configured 10.211.0.121 (DHCP on eth0) Domain names: mydomain2.com configured lab.mydomain.com dynamic (DHCP on eth0) vmlab.mydomain.com dynamic (DHCP on eth0) tok.mydomain.com dynamic (DHCP on eth0) mydomain.com dynamic (DHCP on eth0) </pre>

	<pre> Static IPv4 host mappings: 10.7.144.133 --> ufmapl1 127.0.0.1 --> localhost Static IPv6 host mappings: ::1 --> localhost6 fcfc:fcfc:209:36:a6bf:1ff:fe00:9c20 --> ufmapl1 Automatically map hostname to loopback address: yes Automatically map hostname to IPv6 loopback address: no ufmapl [mgmt-sa] (config) # </pre>
Related Commands	show hosts
Notes	

Routing

{ip | ipv6} default-gateway

	<pre> {ip ipv6} default-gateway {<ip-address> <ifname>} no {ip ipv6} default-gateway </pre> <p>Sets a static default gateway. The no form of the command deletes the default gateway.</p>	
Syntax Description	ip-address	The default gateway IP address
	ifname	Name of the interface interface name (e.g. eth0, eth1).
Default	N/A	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmap1 [mgmt-sa] (config) # ip default-gateway 172.30.0.1</pre>
Related Commands	<pre>show {ip ipv6} default-gateway show {ip ipv6} route</pre>
Notes	<ul style="list-style-type: none"> • The configured default gateway will not be used if DHCP is enabled • In order to configure ipv4 default-gateway use "ip route" command

show {ip | ipv6} default-gateway

	<pre>show {ip ipv6} default-gateway [static]</pre> <p>Displays the default gateway.</p>	
Syntax Description	static	Displays the static configuration of the default gateway
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # show ip default-gateway Active default gateways: 172.30.0.1 (interface: eth0)</pre>	
Related Commands	{ip ipv6} default-gateway	
Notes		

{ip | ipv6} route

	<pre>{ip ipv6} route {<network-prefix> <netmask> <network-prefix>/<masklen>} <next-hop></pre> <pre>no ip route {<network-prefix> <netmask> <network-prefix>/<masklen>} <next-hop></pre> <p>Sets a static route for a given IP. The no form of the command deletes the static route.</p>	
Syntax Description	network-prefix	IPv4 or IPv6 network prefix
	netmask	IPv4 netmask formats are: <ul style="list-style-type: none"> • /24 • 255.255.255.0 IPv6 netmask format is: <ul style="list-style-type: none"> • /48 (as a part of the network prefix)
	nexthop-address	IPv4 or IPv6 address of the next hop router for this route
	ifname	Interface name (e.g. eth0, eth1)
Default	N/A	
Configuration Mode	config	
History	4.1.0	
Example	<pre>ufmapl [mgmt-sa] (config) # ip route 20.20.20.0 255.255.255.0 eth0</pre>	
Related Commands	show ip route	
Notes		

show {ip | ipv6} route

	show {ip ipv6} route [static] Displays the routing table in the system.	
Syntax Description	static	Filters the table with the static route entries
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.1.0	
Example	<pre> ufmapl [mgmt-sa] (config) # show ip route Destination Mask Gateway Interface Source default 0.0.0.0 172.30.0.1 eth0 DHCP 10.10.10.10 255.255.255.255 0.0.0.0 eth0 static 20.10.10.10 255.255.255.255 172.30.0.1 eth0 static 20.20.20.0 255.255.255.0 0.0.0.0 eth0 static 172.30.0.0 255.255.0.0 0.0.0.0 eth0 interface </pre>	
Related Commands	{ip ipv6} route	
Notes		

Network to Media Resolution (ARP & NDP)

IPv4 network use Address Resolution Protocol (ARP) to resolve IP address to MAC address.

arp

	arp <ip-address> <mac-address> no arp <ip-address> <mac-address> Sets a static ARP entry. The no form of the command deletes the static ARP.	
Syntax Description	ip-address	IPv4 address
	mac-address	MAC address
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # arp 172.30.0.1 00:00:5E:00:01:01</pre>	
Related Commands	show ip arp	
Notes		

show arp

	show arp [static] Displays the ARP table.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show arp ARP cache contents IP 172.30.0.1 maps to MAC 00:00:5E:00:01:01 (interface eth0) ufmapl [mgmt-sa] (config) # show arp static Static ARP entries IP 1.1.1.1 maps to MAC 00:01:02:03:04:05</pre>
Related Commands	arp
Notes	

ipv6 neighbor

	<p>ipv6 neighbor <ipv6-address> <ifname> <mac-address> no ipv6 neighbor <ipv6-address> <ifname> <mac-address></p> <p>Adds a static neighbor entry. The no form of the command deletes the static entry.</p>	
Syntax Description	ipv6-address	IPv6 address
	ifname	Management interface (i.e. eth0, eth1)
	mac-address	MAC address
Default	N/A	
Configuration Mode	config	
History	4.1.0	
Example	<pre>ufmapl [mgmt-sa] (config) # ipv6 neighbor 2001:db8:701f::8f9 eth0</pre>	

	00:11:22:33:44:55
Related Commands	show ipv6 neighbor ipv6 route arp clear ipv6 neighbors
Notes	<ul style="list-style-type: none"> • ARP is used only with IPv4. In IPv6 networks, Neighbor Discovery Protocol (NDP) is used similarly. • Use The no form of the command to remove static entries. Dynamic entries can be cleared via the “clear ipv6 neighbors” command.

clear ipv6 neighbors

	clear ipv6 neighbors Clears the dynamic neighbors cache.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.1.0
Example	<pre>ufmap1 [mgmt-sa] (config) # clear ipv6 neighbors</pre>
Related Commands	ipv6 neighbor show ipv6 neighbor arp
Notes	<ul style="list-style-type: none"> • Clearing Neighbor Discovery Protocol (NDP) cache removes only the dynamic entries learned and not the static entries configured • Use the no form of the command to remove static entries

show ipv6 neighbors

	show ipv6 neighbors [static] Displays the Neighbor Discovery Protocol (NDP) table.	
Syntax Description	static	Filters only the table of the static entries
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.1.0	
Example	<pre> ufmap1 [mgmt-sa] (config) # show ipv6 neighbors IPv6 Address Age MAC Address State Interf ----- 2001::2 9428 AA:AA:AA:AA:AA:AA permanent eth0 </pre>	
Related Commands	ipv6 neighbor clear ipv6 neighbor show ipv6	
Notes		

DHCP

ip dhcp

	<pre>ip dhcp {default-gateway yield-to-static hostname <hostname> primary-intf <ifname> send-hostname} no ip dhcp {default-gateway yield-to-static hostname primary-intf send-hostname}</pre> <p>Sets global DHCP configuration. The no form of the command deletes the DHCP configuration.</p>	
Syntax Description	yield-to-static	Does not allow you to install a default gateway from DHCP if there is already a statically configured one
	hostname	Specifies the hostname to be sent during DHCP client negotiation if send-hostname is enabled
	primary-intf	Sets the interface from which a non-interface-specific configuration (resolver and routes) will be accepted via DHCP
	send-hostname	Enables the DHCP client to send a hostname during negotiation
Default	<pre>no ip dhcp yield-to-static no ip dhcp hostname ip dhcp primary-intf eth0 no ip dhcp send-hostname</pre>	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ip dhcp default-gateway yield-to-static</pre>	
Related Commands	<pre>show ip dhcp dhcp [renew]</pre>	
Notes	DHCP is supported for IPv4 networks only	

show {ip | ipv6} dhcp

	<pre>show {ip ipv6} dhcp</pre> <p>Displays the DHCP/DHCPv6 configuration and status.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show ip dhcp ----- Interface DHCP DHCP Valid Enabled Running lease ----- bond0 no no no eth0 yes yes yes eth1 no no no ib0 no no no ib1 no no no lo no no no IPv4 dhcp default gateway yields to static configuration: no DHCP primary interface: Configured: eth0 Active: eth0 DHCP client options: Send Hostname: no Client Hostname: ufmapl (using system hostname)</pre>

Related Commands	ip dhcp dhcp [renew]
Notes	

ipv6 dhcp primary-intf

	ipv6 dhcp primary-intf <if-name> no ipv6 dhcp primary-intf Sets the interface from which non-interface-specific (resolver) configuration is accepted via DHCPv6. The no form of the command resets non-interface-specific (resolver) configuration.	
Syntax Description	if-name	<ul style="list-style-type: none"> • lo • eth0 • eth1
Default	N/A	
Configuration Mode	config	
History	4.1.0	
Example	<pre>ufmapl [mgmt-sa] (config) # ipv6 dhcp primary-intf eth0</pre>	
Related Commands	ipv6 enable ipv6 address show interface <ifname>	
Notes		

ipv6 dhcp stateless

	<pre>ipv6 dhcp stateless no ipv6 dhcp stateless</pre> <p>Enables stateless DHCPv6 requests. The no form of the command disables stateless DHCPv6 requests.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.1.0
Example	<pre>uflmap1 [mgmt-sa] (config) # ipv6 dhcp stateless</pre>
Related Commands	<pre>ipv6 enable ipv6 address show interface <ifname></pre>
Notes	<ul style="list-style-type: none">• This command only gets DNS configuration, not an IPv6 address• The no form of the command requests all information, including an IPv6 address

IP Diagnostic Tools

ping | ping6

	<p>{ping ping6} [-LRUbdnqrVvAa] [-c count] [-i interval] [-w deadline] [-p pattern] [-s packetsize] [-t ttl] [-I interface or address] [-M mtu discovery hint] [-S sndbuf] [-T timestamp option] [-Q tos] [hop1 ...] destination</p> <p>Sends ICMP echo requests to a specified host.</p>	
Syntax Description	Linux Ping options	http://linux.about.com/od/commands/l/blcmdl8_ping.htm
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmap1 [mgmt-sa] (config) # ping 172.30.2.2 PING 172.30.2.2 (172.30.2.2) 56(84) bytes of data. 64 bytes from 172.30.2.2: icmp_seq=1 ttl=64 time=0.703 ms 64 bytes from 172.30.2.2: icmp_seq=2 ttl=64 time=0.187 ms 64 bytes from 172.30.2.2: icmp_seq=3 ttl=64 time=0.166 ms 64 bytes from 172.30.2.2: icmp_seq=4 ttl=64 time=0.161 ms 64 bytes from 172.30.2.2: icmp_seq=5 ttl=64 time=0.153 ms 64 bytes from 172.30.2.2: icmp_seq=6 ttl=64 time=0.144 ms ^C --- 172.30.2.2 ping statistics --- 6 packets transmitted, 6 received, 0% packet loss, time 5004ms rtt min/avg/max/mdev = 0.144/0.252/0.703/0.202 ms </pre>	
Related Commands	tracert/route	
Notes		

traceroutes

	<pre>traceroute [-4dFITUnrAV] [-f first_ttl] [-g gate,...] [-i device] [-m max_ttl] [-N squeries] [-p port] [-t tos] [-l flow_label] [-w waittime] [-q nqueries] [-s src_addr] [-z sendwait] host [packetlen]</pre> <p>Traces the route packets take to a destination.</p>	
Syntax Description	-4	Uses IPv4
	-6	Uses IPv6
	-d	Enables socket level debugging
	-F	Sets DF (do not fragment bit) on
	-I	Uses ICMP ECHO for tracerouting
	-T	Uses TCP SYN for tracerouting
	-U	Uses UDP datagram (default) for tracerouting
	-n	Does not resolve IP addresses to their domain names
	-r	Bypasses the normal routing and send directly to a host on an attached network
	-A	Performs AS path lookups in routing registries and print results directly after the corresponding addresses
	-V	Prints version info and exit
	-f	Starts from the first_ttl hop (instead from 1)
	-g	Routes packets throw the specified gateway (maximum 8 for IPv4 and 127 for IPv6)
	-i	Specifies a network interface to operate with
	-m	Sets the max number of hops--max TTL to be reached (default is 30)
	-N	Sets the number of probes to be tried simultaneously (default is 16)
	-p	Uses destination port. It is an initial value for the UDP destination port (incremented by each probe, default is 33434), for the ICMP seq number (incremented as well, default from 1), and the constant destination port for TCP tries (default is 80)
-t	Sets the TOS (IPv4 type of service) or TC (IPv6 traffic class) value for outgoing packets	
-l	Uses specified flow_label for IPv6 packets	

	-w	Sets the number of seconds to wait for response to a probe (default is 5.0). Non-integer (float point) values allowed too.
	-q	Sets the number of probes per each hop (default is 3)
	-s	Uses source src_addr for outgoing packets
	-z	Sets minimal time interval between probes (default is 0). If the value is more than 10, then it specifies a number in milliseconds, else it is a number of seconds (float point values allowed too).
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # traceroute 192.168.10.70 traceroute to 192.168.10.70 (192.168.10.70), 30 hops max, 40 byte packets 1 172.30.0.1 (172.30.0.1) 3.632 ms 2.849 ms 3.544 ms 2 10.222.128.46 (10.222.128.46) 3.176 ms 3.289 ms 3.656 ms 3 10.158.128.30 (10.158.128.30) 15.331 ms 15.819 ms 16.388 ms 4 10.158.128.65 (10.158.128.65) 20.468 ms 7.893 ms 12.27 ms 5 10.7.34.115 (10.7.34.115) 16.405 ms 11.985 ms 12.264 ms 6 192.168.10.70 (192.168.10.70) 16.377 ms 16.091 ms 20.475 ms </pre>	
Related Commands	ping ping6	
Notes		

tcpdump

	<pre>tcpdump [-aAdeflLnNOpqRStuUvxX] [-c count] [-C file_size] [-E algo:secret] [-F file] [-i interface] [-M secret] [-r file] [-s snaplen] [-T type] [-w file] [-W filecount] [-y datalinktype] [-Z user] [expression]</pre> <p>Invokes standard binary, passing command line parameters straight through. Runs in foreground, printing packets as they arrive, until the user hits Ctrl+C.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmap1 [mgmt-sa] (config) # tcpdump 09:37:38.678812 IP 192.168.10.7.ssh > 192.168.10.1.54155: P 1494624:1494800(176) ack 625 win 90 <nop,nop,timestamp 5842763 858672398> 09:37:38.678860 IP 192.168.10.7.ssh > 192.168.10.1.54155: P 1494800:1495104(304) ack 625 win 90 <nop,nop,timestamp 5842763 858672398> 9141 packets captured 9142 packets received by filter 0 packets dropped by kernel</pre>
Related Commands	
Notes	

Network Bonding

bond

	<code>bond <bonded-if> [mode <string>] [link-mon-time <milliseconds>] [up-delay-time <milliseconds>] [down-delay-time <milliseconds>]</code> <code>no bond <bonded-if></code> Creates the named bonded interface. The no form of the command deletes the named bonded interface.	
Syntax Description	mode	Specifies the type of mode the bonded interface is: <ul style="list-style-type: none"> • balance-rr • backup • balance-xor • balance-xor-layer3+4 • broadcast • link-agg • link-agg-layer3+4 • balance-tlb • balance-alb
	link-mon-time	Specifies the link monitoring frequency (in msec)
	up-delay-time	Specifies the time (in msec) to wait before enabling a slave after a link recovery has been detected
	down-delay-time	Specifies the time (in msec), to wait before disabling a slave after a link failure has been detected for the specified bonded interface
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # bond bond0 mode backup</pre>	

	<pre>ufmapl [mgmt-sa] (config) # bond bond0 link-mon-time 100</pre>
Related Commands	<pre>interface show bonds</pre>
Notes	

interface

	<pre>interface <ifname> bond <bond-if> no interface <ifname> bond <bond-if></pre> <p>Adds the named interface from the specified bonded interface. The no form of the command removes the named interface from the specified bonded interface.</p>	
Syntax Description	<pre>bond</pre>	The bonded interface
Default	N/A	
Configuration Mode	<pre>config</pre>	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # interface ib0 bond bond0</pre>	
Related Commands	<pre>bond show bonds</pre>	
Notes		

show bonds

	<code>show bonds [bonded-if]</code> Displays bonding configuration and status.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmap1 [mgmt-sa] (config) # show bonds Bonded Interface bond0: Enabled: yes Mode: backup Link Monitor Time: 100 Interfaces: ib0 ib1</pre>
Related Commands	<code>bond</code> <code>interface</code>
Notes	

NTP, Clock and Time Zones

clock set

	<code>clock set <hh:mm:ss> [<yyyy/mm/dd>]</code> Sets the time and date.	
Syntax Description	<code>hh:mm:ss</code>	Time
	<code>yyyy/mm/dd</code>	Date
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # clock set 23:23:23 2012/12/15</pre>	
Related Commands	show clock	
Notes	If not specified, the date will be left as is	

clock timezone

	<p>clock timezone [<zone word> [<zone word> [<zone word>] [<zone word>]]]</p> <p>Sets the system time zone. The time zone may be specified in one of three ways:</p> <ul style="list-style-type: none"> • A nearby city whose time zone rules to follow. The system has a large list of cities which can be displayed by the help and completion system. They are organized hierarchically because there are too many of them to display in a flat list. A given city may be required to be specified in two, three, or four words, depending on the city. • An offset from UTC. This will be in the form UTC-offset UTC, UTC-offset UTC+<0-14>, UTC-offset UTC-<1-12>. • UTC (Universal Time, which is almost identical to GMT), and this is the default time zone <p>The no form of the command resets time zone to its default (GMT).</p>	
Syntax Description	zone word	The possible forms this could take include: continent, city, continent, country, city, continent, region, country, city, ocean, and/or island.
Default	GMT	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # clock timezone America North United_States Other New_York</pre>	
Related Commands	show clock	
Notes	If not specified, the date will be left as is	

ntp

	<pre>ntp {disable enable {peer server} <ip-address> [version <number> disable]} no ntp {disable enable {peer server} <ip-address> [disable]}</pre> <p>Configures NTP. The no form of the command negates NTP options.</p>	
Syntax Description	disable	Disables NTP
	enable	Enables NTP
	peer server	Configures an NTP peer or server node
	ip-address	IPv4 address
	version	Specifies the NTP version number of this peer. Possible values are 3 or 4.
Default	NTP is enabled NTP version number is 4	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # no ntp peer 192.168.10.24 disable</pre>	
Related Commands	show ntp	
Notes		

ntpdate

	<code>ntpdate <ip-address></code> Sets the system clock using the specified SNTP server.	
Syntax Description	<code>ip-address</code>	IP address
Default	N/A	
Configuration Mode	<code>config</code>	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # ntpdate 192.168.10.10 15 Dec 17:25:40 ntpdate[15206]: adjust time server 192.168.10.10 offset -0.000092 sec</pre>	
Related Commands	<code>show ntp</code>	
Notes	This is a one-time operation and does not cause the clock to be kept in sync on an ongoing basis. It will generate an error if SNTP is enabled since the socket it requires will already be in use.	

show clock

	<code>show clock</code> Displays the current system time, date and time zone.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show clock Time: 23:23:26 Date: 2012/12/15 Time zone: America North United_States Other New_York</pre>
Related Commands	<pre>clock set clock timezone ntp ntpdate</pre>
Notes	

show ntp

	<pre>show ntp</pre> <p>Displays the current NTP settings.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show ntp NTP is enabled. Clock is unsynchronized. No NTP peers or servers configured.</pre>

Related Commands	ntp ntpdate
Notes	

Software Management

This chapter displays all the relevant commands used to manage the system software image.

image boot

	<code>image boot {location <location-id> next}</code> Specifies the default location where the system should be booted from.	
Syntax Description	location-id	Specifies the default destination location. There can be up to 2 images on the system. Possible values: 1-2.
	next	Sets the boot location to be the next once after the one currently booted from, thus avoiding a cycle through all the available locations
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # image boot location 2</pre>	
Related Commands	show images	
Notes		

boot next

	<p>boot next fallback-reboot enable no boot next fallback-reboot enable</p> <p>Sets the default setting for next boot. Normally, if the system fails to apply the configuration on startup (after attempting upgrades or downgrades, as appropriate), it will reboot to the other partition as a fallback. The no form of the command tells the system not to do that, only for the next boot.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # boot fallback-reboot enable</pre>
Related Commands	show images
Notes	Normally, if the system fails to apply the configuration on startup (after attempting upgrades or downgrades, as appropriate), it will reboot to the other partition as a fallback. The 'no' variant of this command tells the system NOT to do that, ONLY for the next boot. Note that this setting is not persistent, and will go back to enabled automatically after every boot.

image delete

	image delete <image-name> Deletes the specified image file.	
Syntax Description	image-name	Specifies the image name
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # image delete image-ufm_appliance-x86_64- x86_64-20121205-152024.img</pre>	
Related Commands	show images	
Notes		

image fetch

	image fetch <URL> [<filename>] Downloads an image from the specified URL or via SCP.	
Syntax Description	URL	HTTP, HTTPS, FTP, TFTP, SCP and SFTP are supported Example: scp://username[:password]@hostname/path/filename
	filename	Specifies a filename for this image to be stored as locally
Default	N/A	
Configuration Mode	config	

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # image fetch scp:// <username>@192.168.10.125/var/www/html/<image_name> Password ***** 100.0% [#####] #####</pre>
Related Commands	show images
Notes	<ul style="list-style-type: none"> • Please delete the previously available image, prior to fetching the new image • See section "Updating UFM™ SDN Appliance Software" in the Mellanox UFM SDN Appliance User Manual for a full upgrade example

image install

	<pre>image install <image-filename> [location <location-id>] [progress <prog-options>] [verify <ver-options>]</pre> <p>Downloads an image from the specified URL or via SCP.</p>	
Syntax Description	image filename	Specifies the image name
	location-id	Specifies the image destination location
	prog-options	<ul style="list-style-type: none"> • “no-track” overrides CLI default and does not track the installation progress. • “track” overrides CLI default and tracks the installation progress.
	ver-options	<ul style="list-style-type: none"> • “check-sig” requires an image to have either a valid signature or no signature. • “ignore-sig” allows unsigned or invalidly signed images to be installed.

		<ul style="list-style-type: none"> • “require-sig” requires from the installed image to have a valid signature. If a valid signature is not found on the image, the image cannot be installed.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # image install image-ufm_appliance-x86_64- x86_64-20121205-152024.img Step 1 of 4: Verify Image 100.0% [#####] #####] Step 2 of 4: Uncompress Image 100.0% [#####] #####] Step 3 of 4: Create Filesystems 100.0% [#####] #####] Step 4 of 4: Extract Image 100.0% [#####] #####] </pre>	
Related Commands	show images	
Notes	<ul style="list-style-type: none"> • The image cannot be installed on the “active” location (the one which is currently being booted) • On a two-location system, the location is chosen automatically if no location is specified 	

image move

	image move <src image name> <dest image name> Renames the specified image file.	
Syntax Description	src image name	Specifies the old image name
	dest image name	Specifies the new image name
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # image move image1.img image2.img</pre>	
Related Commands	show images	
Notes		

image option

	image options require-sig no image options require-sig Requires from all the installed images a valid signature. The no form of the command does not require a signature. However if one is present, it must be valid.	
Syntax Description	require-sig	Requires images to be signed by a trusted signature
Default	N/A	
Configuration Mode	config	

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # image options require-sig</pre>
Related Commands	show images
Notes	

show bootvar

	<p>show bootvar</p> <p>Displays the installed system images and the boot parameters.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show bootvar Installed images: Partition 1: ufm_appliance UFMAPL_1.1.0.11_UFM_3.8.2.5 2012-12-05 15:20:24 x86_64 Partition 2: ufm_appliance UFMAPL_1.0.5.0_UFM_3.8.0.16 2012-10-24 14:27:53 x86_64 Last boot partition: 1 Next boot partition: 1 Boot manager password is set.</pre>

	<pre>No image install currently in progress. Image signing: trusted signature always required Admin require signed images: yes Settings for next boot only: Fallback reboot on configuration failure: yes (default)</pre>
Related Commands	N/A
Notes	

show images

	<p>show image</p> <p>Displays information about the system images and boot parameters.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show images Images available to be installed: image-ufm_appliance-x86_64-x86_64-20121205-152024.img ufm_appliance UFMAPL_1.1.0.11_UFM_3.8.2.5 2012-12-05 15:20:24 x86_64 Installed images: Partition 1: ufm_appliance UFMAPL_1.1.0.11_UFM_3.8.2.5 2012-12-05 15:20:24 x86_64</pre>

	<pre> Partition 2: ufm_appliance UFMAPL_1.0.5.0_UFM_3.8.0.16 2012-10-24 14:27:53 x86_64 Last boot partition: 1 Next boot partition: 1 Boot manager password is set. No image install currently in progress. Image signing: trusted signature always required Admin require signed images: yes Settings for next boot only: Fallback reboot on configuration failure: yes (default) </pre>
Related Commands	<pre> image boot image delete image fetch image install image move image option boot next </pre>
Notes	

Configuration Management

Saving a Configuration File

To save the current configuration to the active configuration file, you can either use the “configuration write” command (requires running in Config mode) or the “write memory” command (requires running in Enable mode).

- To save the configuration to the active configuration file, run:

```
ufmapl (config) # configuration write
```

- To save the configuration to a user-specified file without making the new file the active configuration file, run:

```
ufmapl (config) # configuration write to myconf no-switch
```

- To save the configuration to a user-specified file and make the new file the active configuration file, run:

```
ufmapl (config) # configuration write to myconf
```

- To display the available configuration files and the active file, run:

```
ufmapl (config) # show configuration files
initial
myconf (active)
ufmapl (config) #
```

Loading a Configuration File

By default, or after a system reset, the system loads the default “initial” configuration file.

To load a different configuration file and make it the active configuration:

```
ufmapl >
ufmapl > enable
ufmapl # configure terminal
ufmapl (config) # configuration ufmpl-to myconfig
ufmapl (config) #
```

Restoring Factory Default Configuration

If system configuration becomes corrupted, it is suggested to restore factory default configuration.

To restore factory default configuration on a single management module system, run:

```
ufmapl (config) # reset factory keep-basic
```

Managing Configuration Files


There are two types of configuration files that can be applied on the host, BIN files (binary) and text-based configuration files.

BIN Configuration Files

BIN configuration files are not human readable. Additionally, these files are encrypted and contain integrity verification preventing them from being edited and used on the host.

To create a new BIN configuration file:

```
ufmapl (config) # configuration new my-filename
```

 A newly created BIN configuration file is always empty and is not created from the running-config.

To upload a BIN configuration file from a host to an external file server:

```
ufmapl (config) # configuration upload my-filename scp://myusername@my-server/path/to/my/<file>
```

To fetch a BIN configuration file:

```
ufmapl (config) # configuration fetch scp://myusername@my-server/path/to/my/<file>
```

To see the available configuration files:

```
ufmapl (config) # show configuration files
```

```
initial (active)
my-filename

Active configuration: initial
Unsaved changes:      no
ufmapl (config) #
```

To load a BIN configuration file:

```
ufmapl (config) # configuration ufmapl-to my-filename
This requires a reboot.
Type 'yes' to confirm: yes
```

⚠ Applying a new BIN configuration file changes the whole host's configuration and requires system reboot which can be performed using the command "reload".

⚠ A binary configuration file uploaded from the host is encrypted and has integrity verification. If the file is modified in any manner, the fetch to the host fails.

Text Configuration Files

Text configuration files are text based and editable. It is similar in form to the output of the command "show running-config expanded".

To create a new text-based configuration file:

```
ufmapl (config) # configuration text generate active running save my-filename
```

⚠ A newly created text configuration file is always created from the running-config.

To apply a text-based configuration file:


```
ufmapl (config) # configuration text file my-filename apply
```

⚠ Applying a text-based configuration file to an existing/running data port configuration may result in unpredictable behavior. It is therefore suggested to first clear the host's configuration by applying a specific configuration file (following the procedure in "BIN Configuration File") or by resetting the host back to factory default.

To upload a text-based configuration file from a host to an external file server:

```
ufmapl (config) # configuration text file my-filename upload scp://root@my-server/root/tmp/my-filename
```

To fetch a text-based configuration file from an external file server to a host:

```
ufmapl (config) # configuration text fetch scp://root@my-server/root/tmp/my-filename
```

To apply a text-based configuration file:

```
ufmapl (config) # configuration text file my-filename apply
```

⚠ When applying a text-based configuration file, the configuration is appended to the host's existing configuration. Only new or changed configuration is added. Reboot is not required.

Configuration Management Commands

- [File Transfer](#)
- [File System](#)
- [Configuration File](#)

File Transfer

ftp-server enable

	<code>ftp-server enable</code> <code>no ftp-server enable</code> Enables the FTP server. The no form of the command disables the FTP server.
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	1.5
Example	<pre>ufmap1 [mgmt-sa] (config) # ftp-server enable</pre>
Related Commands	<code>show ftp-server</code>
Notes	

show ftp-server

	<code>show ftp-server</code> Displays FTP server settings.
Syntax Description	N/A
Default	Disabled

Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show ftp-server FTP server enabled: yes</pre>
Related Commands	ftp-server enable
Notes	

File System

File System Commands

debug generate dump

	<p>debug generate dump</p> <p>Generates a debug dump.e</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # debug generate dump Generated dump sysdump-ufmapl-112104-201140526-091707.tgz</pre>

Related Commands	file debug-dump
Notes	The dump can then be manipulated using the “file debug-dump...” commands

file debug-dump

	file debug-dump {delete {<filename> latest} email {<filename> latest} upload {{<filename> latest} <URL>}} Manipulates debug dump files.	
Syntax Description	filename	The specified file name
	latest	Delete, upload, or e-mail the latest debug dump file to a remote host
	URL	HTTP, HTTPS, FTP, TFTP, SCP and SFTP are supported Example: scp://username[:password]@hostname/path/filename
Default	N/A	
Configuration Mode	config	
History	1.5	
	1.8	Updated delete/email/upload syntax
Example	<pre>ufmapl [mgmt-sa] (config) # file debug-dump email sysdump- ufmapl-112104-20114052-091707.tgz</pre>	
Related Commands		
Notes		

file docker-label delete

	file docker-label delete <filename> Deletes a docker label archive file.	
Syntax Description	filename	The specified file name
Default	N/A	
Configuration Mode	config	
History	4.7.0	
Example	<pre>ufmapl [mgmt-sa] (config) # file docker-label delete dockerfile</pre>	
Related Commands	show files docker-label	
Notes		

file stats

	file stats {delete <filename> move {<source filename> <destination filename>} upload <filename> <URL>} Manipulates statistics report files.	
Syntax Description	delete	Deletes a stats report file
	move	Renames a stats report file
	upload	Uploads a stats report file. HTTP, HTTPS, FTP, TFTP, SCP and SFTP are supported. Example: scp://username[:password]@hostname/path/filename
Default	N/A	
Configuration Mode	config	

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # file stats move memory-1.csv memory-2.csv</pre>
Related Commands	show files stats
Notes	

file tcpdump

	<p>file tcpdump {delete <filename> upload <filename> <URL>}</p> <p>Manipulates tcpdump output files.</p>	
Syntax Description	delete	Deletes the specified tcpdump output file
	upload	<p>Uploads the specified tcpdump output file to the specified URL. HTTP, HTTPS, FTP, TFTP, SCP and SFTP are supported.</p> <p>Example: scp://username[:password]@hostname/path/filename</p>
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # file tcpdump delete my-tcpdump-file.txt</pre>	
Related Commands	<p>show files stats</p> <p>tcpdump</p>	
Notes		

show files debug-dump

	show files debug-dump [<filename>] Displays a list of debug dump files.	
Syntax Description	filename	Displays a summary of the contents of a particular debug dump file
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] # show files debug-dump sysdump-r- ufm237-20210809-211426.tgz ===== System information: Hostname: r-ufm237 Version: ufm_appliance UFMAPL_4.6.0.6_UFM_6.7.0.8 2021-08-08 19:27:47 x86_64 Current time: 2021-08-09 21:14:26 System uptime: 0d 21h 27m 28s ===== ===== Output of 'uname -a': Linux r-ufm237 3.10.0-1127.19.1.el7MELLANOXsmp-x86_64 ufm_appliance UFMAPL_4.6.0.6_UFM_6.7.0.8 #1 2021-08-08 18:45:38 x86_64 x86_64 x86_64 GNU/ Linux ===== </pre>	
Related Commands	file debug-dump	

Notes	
-------	--

show files docker-label

	show files docker-label Displays a list of docker label archive files.	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.7.0	
Example	<pre>ufmapl [mgmt-sa] (config) # show file docker-label ribd.config.zip</pre>	
Related Commands	file docker-label delete	
Notes		

show files stats

	show files stats <filename> Displays a list of statistics report files.	
Syntax Description	filename	Display the contents of a particular statistics report file
Default	N/A	
Configuration Mode	Any configuration mode	

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show files stats memory-201140524-111745.csv</pre>
Related Commands	file stats
Notes	

show files system

	show files system [detail] Displays usage information of the file systems on the system.	
Syntax Description	detail	Displays more detailed information on file-system
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # show files system Statistics for /config filesystem: Space Total 182 MB Space Used 1 MB Space Free 181 MB Space Available 172 MB Space Percent Free 99% Inodes Percent Free 99% Statistics for /var filesystem: Space Total 50529 MB Space Used 1880 MB</pre>	

	<pre> Space Free 48650 MB Space Available 46076 MB Space Percent Free 96% Inodes Percent Free 99% Statistics for /opt/ufm/history filesystem: Space Total 775980 MB Space Used 674 MB Space Free 775306 MB Space Available 735882 MB Space Percent Free 99% Inodes Percent Free 99% Statistics for /opt/ufm/files filesystem: Space Total 50267 MB Space Used 107 MB Space Free 50160 MB Space Available 47600 MB Space Percent Free 99% Inodes Percent Free 99% </pre>
Related Commands	
Notes	

show files tcpdump

	<pre> show files tcpdump Displays a list of statistics report files. </pre>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5

Example	<pre>ufmap1 [mgmt-sa] (config) # show files stats test dump3</pre>
Related Commands	file tcpdump tcpdump
Notes	

reload

	<pre>reload [force halt [noconfirm] noconfirm]</pre> <p>Reboots or shuts down the system.</p>	
Syntax Description	force	Forces an immediate reboot of the system even if the system is busy
	halt	Shuts down the system
	noconfirm	Reboots the system without asking about unsaved changes
Default	1000	
Configuration Mode	config	
History	1.5	
Example	<pre>ufm-ap1 [mgmt-sa] (config) # reload Configuration has been modified; save first? [yes] yes Configuration changes saved. ...</pre>	
Related Commands	reset factory	
Notes		

reset factory

	reset factory [keep-all-config keep-basic only-config] [halt] Clears the system and resets it entirely to its factory state.	
Syntax Description	keep-all-cofig	Preserves all configuration files including licenses. Removes the logs, stats, images, snapshots, history, known hosts. The user is prompted for confirmation before honoring this command, unless confirmation is disabled with the command: "no cli default prompt confirm-reset".
	keep-basic	Preserves licenses in the running configuration file.
	only-config	Removes configuration files only. Logs, stats, images, snapshots, history, and known hosts are preserved.
	halt	The system is halted after this process completes
Default	N/A	
History	4.2.0	
Example	<pre> ufm-apl (config) # reset factory Warning - confirming will cause system reboot. Type 'YES' to confirm reset: YES Resetting and rebooting the system -- please wait... ... </pre>	
Related Commands	reload	
Notes	<ul style="list-style-type: none"> • Effects of parameter "keep-all-cofig": Licenses - not deleted; profile - no change; configuration - unchanged; management IP - unchanged • Effects of parameter "keep-basic": Licenses - not deleted; profile - reset; configuration - reset; management IP - reset • Confirming the command causes system reboot 	

reset factory keep-docker

	<code>reset factory keep-docker</code> Resets all host configuration except for docker configuration.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.2.0
Example	<pre>ufm-apl (config) # reset factory keep-docker</pre>
Related Commands	<code>reset factory</code>
Notes	

configuration new factory keep-docker

	<code>configuration new <filename> factory keep-docker</code> Creates new file with only factory defaults except docker current configuration.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.2.0

Example	<pre>ufm-apl (config) # no configuration new my_file factory keep-docker</pre>
Related Commands	configuration new factory
Notes	

Configuration File

configuration audit

	configuration audit max-changes <number> Chooses settings related to configuration change auditing.	
Syntax Description	max-changes	Set maximum number of audit messages to log per change
Default	1000	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # configuration audit max-changes 100</pre>	
Related Commands	show configuration	
Notes		

configuration copy

	configuration copy <source-name> <dest-name> Copies a configuration file.	
Syntax Description	source-name	Name of source file
	dest-name	Name of destination file. If the file of specified filename does not exist a new file will be created with said filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # configuration copy initial.bak example</pre>	
Related Commands		
Notes	<ul style="list-style-type: none"> • This command does not affect the current running configuration • The active configuration file may not be the target of a copy. However, it may be the source of a copy in which case the original remains active. 	

configuration delete

	configuration delete <filename> Deletes a configuration file.	
Syntax Description	filename	Name of file to delete
Default	N/A	

Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show configuration files example initial initial.bak initial.prev ufmapl [mgmt-sa] (config) # configuration delete example ufmapl [mgmt-sa] (config) # show configuration files initial initial.bak initial.prev</pre>
Related Commands	show configuration
Notes	<ul style="list-style-type: none"> • This command does not affect the current running configuration • The active configuration file may not be deleted

configuration fetch

	configuration fetch <URL or scp or sftp://username:password@hostname[:port]/path/filename > [<name>] Downloads a configuration file from a remote host.	
Syntax Description	name	Configuration filename
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # configuration fetch scp:// root:password@192.168.10.125/tmp/conf1</pre>	
Related Commands	configuration switch-to	

Notes	<ul style="list-style-type: none"> • The downloaded file should not override the active configuration file, using the <name> parameter • If no name is specified for a configuration fetch, it is given the same name as it had on the server • No configuration file may have the name "active"
-------	---

configuration jump-start

	<p>configuration jump-start</p> <p>Runs the initial-configuration wizard.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre> ufmapl [mgmt-sa] (config) # configuration jump-start Mellanox UFM appliance configuration wizard Step 1: Hostname? [ufm-appliance-8990b8] Step 2: Use DHCP on eth0 interface? [yes] Step 3: Enable IPv6? [yes] Step 4: Enable IPv6 autoconfig (SLAAC) on eth0 interface? [no] Step 5: Enable DHCPv6 on eth0 interface? [yes] Step 6: Admin password (Enter to leave unchanged)? Step 7: bond0 IPv4 address and masklen? [192.168.1.234/24] You have entered the following information: 1. Hostname: ufm-appliance-8990b8 2. Use DHCP on eth0 interface: yes 3. Enable IPv6: yes 4. Enable IPv6 autoconfig (SLAAC) on eth0 interface: yes 5. Enable DHCPv6 on eth0 interface? yes </pre>

	<pre> 6. Admin password (Enter to leave unchanged): (unchanged) 7. bond0 IP address and masklen: 192.168.1.234/24 To change an answer, enter the step number to return to. Otherwise hit <enter> to save changes and exit. Choice: Configuration changes saved. UFM is configured as an external SM. </pre>
Related Commands	
Notes	<ul style="list-style-type: none"> • The wizard is automatically invoked whenever the CLI is launched when the active configuration file is fresh (i.e. not modified from its initial contents) • This command invokes the wizard on demand

configuration merge

	<pre> configuration merge <filename> </pre> <p>Merges the “shared configuration” from one configuration file into the running configuration.</p>	
Syntax Description	filename	Name of file from which to merge settings
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # configuration merge new-config-file </pre>	
Related Commands		

Notes	<ul style="list-style-type: none"> • No configuration files are modified during this process • The configuration name must be a non-active configuration file
-------	---

configuration move

	configuration move <source-name> <dest-name> Moves a configuration file.	
Syntax Description	source-name	Old name of file to move
	dest-name	New name for moved file
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # show configuration files example1 initial initial.bak initial.prev ufmapl [mgmt-sa] (config) # configuration move example1 example2 ufmapl [mgmt-sa] (config) # show configuration files example2 initial initial.bak initial.prev </pre>	
Related Commands	show configuration	
Notes	<ul style="list-style-type: none"> • This command does not affect the current running configuration • The active configuration file may not be the target of a move 	

configuration new

	<code>configuration new <filename> [factory [keep-basic] [keep-connect]]</code> Creates a new configuration file under the specified name. The parameters specify what configuration, if any, to carry forward from the current running configuration.	
Syntax Description	filename	Names for new configuration file
	factory	Creates new file with only factory defaults
	keep-basic	Keeps licenses and host keys
	keep-connect	Keeps configuration necessary for connectivity (interfaces, routes, and ARP)
Default	Keeps licenses and host keys	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # show configuration files initial initial.bak initial.prev ufmapl [mgmt-sa] (config) # configuration new example2 ufmapl [mgmt-sa] (config) # show configuration files example2 initial initial.bak initial.prev </pre>	
Related Commands	show configuration	
Notes		

configuration switch-to

	configuration switch-to <filename> [no-reboot] Loads the configuration from the specified file and makes it the active configuration file.	
Syntax Description	no-reboot	Forces configuration change without rebooting the host
Default	N/A	
Configuration Mode	config	
History	4.2.0	
Example	<pre> ufmapl [mgmt-sa] (config) # show configuration files initial (active) newcon initial.prev initial.bak ufmapl [mgmt-sa] (config) # configuration switch-to newcon ufmapl [mgmt-sa] (config) # show configuration files initial newcon (active) initial.prev initial.bak </pre>	
Related Commands	show configuration files	
Notes	<ul style="list-style-type: none"> • The current running configuration is lost and not automatically saved to the previous active configuration file. • When running the command without the "no-reboot" parameter, the user is prompted to OK a reboot. If the answer is "yes", the configuration is replaced and the host is rebooted immediately. 	

configuration text fetch

	configuration text fetch <download-URL> [apply] [discard] [fail-continue] [filename <file>] [verbose] Downloads a text-based configuration file from a remote host.	
Syntax Description	download-URL	Supported types are HTTP, HTTPS, FTP, TFTP, SCP and SFTP Example: scp://username[:password]@hostname/path/filename
	apply	Applies the configuration on the system
	discard	Deletes the configuration text after applying it
	fail-continue	Continues execution of the commands even if some commands fail
	filename	Specifies filename for saving downloaded text file
	verbose	Displays all commands being executed and their output, instead of just those that get errors
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # configuration text fetch example@host.com</pre>	
Related Commands	show configuration files	
Notes		

configuration text file

	<code>configuration text file <filename> {apply [fail-continue] [verbose] delete rename <filename> upload < URL>}</code> Performs operations on text-based configuration files.	
Syntax Description	filename	Specifies the filename
	apply	Applies the configuration on the system
	fail-continue	Continues execution of the commands even if some commands fail
	verbose	Displays all commands being executed and their output, instead of just those that get errors
	delete	Deletes the file
	rename	Renames the file
	upload	Supported types are HTTP, HTTPS, FTP, TFTP, SCP and SFTP Example: scp://username[:password]@hostname/path/filename
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # configuration text file my-config-file delete</pre>	
Related Commands	show configuration files	
Notes		

configuration text generate

	<code>configuration text generate {active {running saved} file <filename> } {save <filename> upload <URL>}</code> Generates a new text-based configuration file from this system's configuration.	
Syntax Description	active	Generates from currently active configuration
	running	Uses running configuration
	saved	Uses saved configuration
	file	Generates from inactive saved configuration
	save	Saves new file to local persistent storage
	upload	Supported types are HTTP, HTTPS, FTP, TFTP, SCP and SFTP Example: scp://username[:password]@hostname/path/filename
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # configuration text generate file initial.prev save example ufmapl [mgmt-sa] (config) # show configuration files initial (active) initial.prev initial.bak Active configuration: initial Unsaved changes: yes </pre>	
Related Commands	show configuration files	
Notes		

configuration upload

	<code>configuration upload {active <name>} <URL></code> Uploads a configuration file to a remote host.	
Syntax Description	active	Upload the active configuration file
	URL	Supported types are HTTP, HTTPS, FTP, TFTP, SCP and SFTP Example: <code>scp://username[:password]@hostname/path/filename</code>
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # configuration upload active scp:// root:password@192.168.10.125/tmp/conf1</pre>	
Related Commands	show configuration files	
Notes	Configuration filename cannot be "active"	

configuration write

	<code>configuration write [local to <filename> [no-switch]]</code> Saves the running configuration to the active configuration file.	
Syntax Description	local	Saves the running configuration locally (same as "write memory local").
	to <filename>	Saves the running configuration to a new file under a different name and makes it the active file.

	no-switch	Saves the running configuration to this file but keep the current one active.
Default	N/A	
Configuration Mode	config	
History	4.2.0	
Example	<pre>ufmapl (config) # configuration write</pre>	
Related Commands	write	
Notes		

write

	<p>write {memory [local] terminal}</p> <p>Saves or displays the running configuration.</p>	
Syntax Description	memory	Saves running configuration to the active configuration file. It is the same as "configuration write".
	local	Saves the running configuration only on the local node. It is the same as "configuration write local".
	terminal	Displays commands to recreate current running configuration. It is the same as "show running-config".
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # write terminal ##</pre>	

	<pre> ## Running database "initial" ## Generated at 20114/05/27 10:05:16 +0000 ## Hostname: ufmapl ## ## ## Network interface configuration ## interface eth0 comment "" interface eth0 create interface eth0 dhcp interface eth0 display interface eth0 duplex auto interface eth0 mtu 1500 no interface eth0 shutdown interface eth0 speed auto no interface eth0 zeroconf ## ## Local user account configuration ## username a** capability admin no username a** disable username a** disable password </pre>
Related Commands	<pre> show running-config configuration write </pre>
Notes	

show configuration

	<pre> show configuration [audit files [<filename>] full running [full] text files] </pre> <p>Displays a list of CLI commands that will bring the state of a fresh system up to match the current persistent state of this system.</p>	
Syntax Description	audit	Displays settings for configuration change auditing

	files	Displays a list of configuration files in persistent storage if no filename is specified. If a filename is specified, it displays the commands to recreate the configuration in that file. In the latter case, only non-default commands are shown, as for the normal “show configuration” command.
	full	Does not exclude commands that set default values
	running	Displays commands to recreate current running configuration. Same as “show configuration” except that it applies to the currently running configuration, rather than the current persisted configuration.
	text files	Displays names of available text-based configuration files
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # show configuration ## ## Active saved database "newcon" ## Generated at 20114/05/25 10:18:52 +0000 ## Hostname: ufmapl-3cc29c ## ## ## Network interface configuration ## interface eth0 comment " " interface eth0 create interface eth0 dhcp interface eth0 display interface eth0 duplex auto interface eth0 mtu 1500 no interface eth0 shutdown interface eth0 speed auto no interface eth0 zeroconf </pre>	
Related Commands	configuration audit configuration delete configuration move configuration new	

Notes	
-------	--

show running-config

	show running-config [full] Displays commands to recreate current running configuration.	
Syntax Description	full	Does not exclude commands that set default values
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre> ufmap1 [mgmt-sa] (config) # show running-config ## ## Running database "initial" ## Generated at 2012/02/28 14:59:02 +0000 ## Hostname: ufmap1-5ea5d8 ## ## ## License keys ## license install LK2- EFM_SX-5M11-5K11-5HGL-0KAL-64QK-8C2Q-60Q3-6C1G-88A1-F5DF- 2K GK-8 license install LK2-RESTRICTED_CMDS-88A0-RFD7-W4CF-Y ## ## Network interface configuration ## interface eth0 create interface eth0 comment "" interface eth0 dhcp </pre>	

```
interface eth0 display
interface eth0 duplex auto
interface eth0 mtu 1500
no interface eth0 shutdown
...
```

Related Commands

show configuration running

Notes

Same as "show configuration running" except that it applies to the currently running configuration rather than the current persisted configuration.

Local and Remote Logging

logging local

	<p>logging local <log-level> no logging local</p> <p>Sets the minimum severity of log messages to be saved in log files on local persistent storage. The no form disables the ability to log messages locally and remotely.</p>	
Syntax Description	log-level	<ul style="list-style-type: none"> • alert - alert notification, action must be taken immediately • crit - critical condition • debug - debug level messages • emerg - system is unusable (emergency) • err - error condition • info - informational condition • none - disables the logging locally and remotely • notice - normal, but significant condition • warning - warning condition
Default	info	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # logging local info</pre>	
Related Commands	<p>show logging logging local override</p>	
Notes	<ul style="list-style-type: none"> • The commands "logging local none" and "no logging local" have the same effect. • Disabling the logging messages will disable all logging: <ul style="list-style-type: none"> • Local logging 	

- Logging messages sent from hosts to be logged in the system
- Remote logging (syslog)

logging local override

	<p>logging local override [class <class> priority <log-level>] no logging local override [class <class> priority <log-level>]</p> <p>Enables class-specific overrides to the local log level. The no form of the command disables all class-specific overrides to the local log level without deleting them from the configuration, but disables them so that the logging level for all classes is determined solely by the global setting.</p>	
Syntax Description	override	Enables class-specific overrides to the local log level
	class	<p>Sets or removes a per-class override on the logging level. All classes which do not have an override set will use the global logging level set with "logging local <log level>". Classes that do have an override will do as the override specifies. If "none" is specified for the log level, MLNX-OS will not log anything from this class.</p> <p>Classes available:</p> <ul style="list-style-type: none"> • iss-modules - protocol stack • mgmt-back - system management back-end • mgmt-core - system management core • mgmt-front - system management front-end • mlx-daemons - management daemons • sx-sdk - switch SDK
	log-level	<ul style="list-style-type: none"> • alert - alert notification, action must be taken immediately • crit - critical condition • debug - debug level messages • emerg - system is unusable (emergency) • err - error condition • info - informational condition • none - disables the logging locally and remotely • notice - normal, but significant condition • warning - warning condition
Default	Override disabled	
Configuration Mode	config	

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # logging local override class mgmt-front priority warning</pre>
Related Commands	show logging logging local
Notes	

logging <syslog-ip-address>

	<p>logging <syslog-ip-address> [trap {<log-level> override class <class> priority <log-level>}] no logging <syslog-ip-address> [trap {<log-level> override class <class> priority <log-level>}]</p> <p>Enables (by setting the IP address) sending logging messages, with ability to filter the logging messages according to their classes. The no form of the command stops sending messages to the remote syslog server.</p>	
Syntax Description	syslog-ip-address	IPv4 address of the remote syslog server
	class	<p>Sets or removes a per-class override on the logging level. All classes which do not have an override set will use the global logging level set with "logging local <log-level>". Classes that do have an override will do as the override specifies. If "none" is specified for the log level, MLNX-OS will not log anything from this class.</p> <p>Classes available:</p> <ul style="list-style-type: none"> • iss-modules - protocol stack • mgmt-back - system management back-end • mgmt-core - system management core • mgmt-front - system management front-end • mlx-daemons - management daemons • sx-sdk - switch SDK
	log-level	<ul style="list-style-type: none"> • alert - alert notification, action must be taken immediately • crit - critical condition • debug - debug level messages • emerg - system is unusable (emergency) • err - error condition

	<ul style="list-style-type: none"> • info - informational condition • none - disables the logging locally and remotely • notice - normal, but significant condition • warning - warning condition
Default	Remote logging is disabled
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # logging local info</pre>
Related Commands	show logging logging local override
Notes	

logging receive

	<p>logging receive no logging receive</p> <p>Enables receiving logging messages from a remote host. The no form of the command disables the option of receiving logging messages from a remote host.</p>
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	1.5

Example	<pre>ufmapl [mgmt-sa] (config) # logging receive</pre>
Related Commands	show logging logging local logging local override
Notes	<ul style="list-style-type: none"> • This does not log to the console TTY port • Inband management should be enabled in order to open a channel from the host to the CPU • If enabled, only log messages matching or exceeding the minimum severity specified with the "logging local" command will be logged, regardless of what is sent from the remote host

logging format

	<pre>logging format {standard welf [fw-name <hostname>]}</pre> <pre>no logging format {standard welf [fw-name <hostname>]}</pre> <p>Sets the format of the logging messages. The no form of the command resets the format to its default.</p>	
Syntax Description	standard	Standard format
	welf	WebTrends Enhanced Log file (WELF) format
	fw-name	Specifies the firewall hostname that should be associated with each message logged in WELF format. If no firewall name is set, the hostname is used by default
Default	Standard	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # logging format standard</pre>	

Related Commands	show logging
Notes	

logging fields

	logging fields seconds {enable fractional-digits <f-digit> whole-digits <w-digit>} no logging fields seconds {enable fractional-digits <f-digit> whole-digits <w-digit>} Specifies whether to include an additional field in each log message that shows the number of seconds since the Epoch or not. The no form of the command disallows including an additional field in each log message that shows the number of seconds since the Epoch.	
Syntax Description	enable	Specifies whether to include an additional field in each log message that shows the number of seconds since the Epoch or not
	fractional-digits	The fractional-digits parameter controls the number of digits to the right of the decimal point. Truncation is done from the right. Possible values: 1, 2, 3, or 6.
	whole-digits	The whole-digits parameter controls the number of digits to the left of the decimal point. Truncation is done from the left. Except for the year, all of these digits are redundant with syslog's own date and time. Possible values: 1, 6, or all.
Default	Disabled	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # logging fields seconds enable ufmapl [mgmt-sa] (config) # logging fields seconds whole-digits 1</pre>	
Related Commands	show logging	

Notes	This is independent of the standard syslog date and time at the beginning of each message in the format of "July 15 18:00:00". Aside from indicating the year at full precision, its main purpose is to provide subsecond precision.
-------	--

logging level

	logging level {cli commands <log-level> audit mgmt <log-level>}	
	Sets the severity level at which CLI commands or the management audit message that the user executes are logged. This includes auditing of both configuration changes and actions.	
Syntax Description	cli commands	Sets the severity level at which CLI commands which the user executes are logged
	audit mgmt	Sets the severity level at which all network management audit messages are logged
	log-level	<ul style="list-style-type: none"> • alert - alert notification, action must be taken immediately • crit - critical condition • debug - debug level messages • emerg - system is unusable (emergency) • err - error condition • info - informational condition • none - disables the logging locally and remotely • notice - normal, but significant condition • warning - warning condition
Default	CLI commands and audit message are set to notice logging level	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # logging level cli commands info</pre>	
Related Commands	show logging	
Notes		

logging files delete

	logging files delete {current oldest [<number-of-files>]}	
	Deletes the current or oldest log files.	
Syntax Description	current	Deletes current log file
	oldest	Deletes oldest log file
	number-of-files	Sets the number of files to be deleted
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # logging files delete current</pre>	
Related Commands	show logging show log files	
Notes		

logging files rotation

	logging files rotation {criteria { frequency <freq> size <size-mb> size-pct <size-percentage>} force max-number <number-of-files>}	
	Sets the rotation criteria of the logging files.	
Syntax Description	frequency	Sets rotation criteria according to time. Possible options: Daily, Weekly, Monthly
	size	Sets rotation criteria according to size in megabytes. Range: 1-9999.

	size-pct	Sets rotation criteria according to size in percentage of the partition where the logging files are kept in. The percentage given is truncated to three decimal points (thousandths of a percent).
	force	Forces an immediate rotation of the log files. This does not affect the schedule of auto-rotation if it was done based on time: the next automatic rotation will still occur at the same time for which it was previously scheduled. Naturally, if the auto-rotation was based on size, this will delay it somewhat as it reduces the size of the active log file to zero.
	max-number	The number of log files will be kept. If the number of log files ever exceeds this number (either at rotation time, or when this setting is lowered), the system will delete as many files as necessary to bring it down to this number, starting with the oldest.
Default	10 files are kept by default with rotation criteria of 5% of the log partition size	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # logging files rotation criteria size-pct 6</pre>	
Related Commands	show logging show log files	
Notes		

logging files upload

	logging files upload {current <file-number>} <url> Uploads a log file to a remote host.	
Syntax Description	current	The current log file. The current log file will have the filename "messages" if you do not specify a new name for it in the upload URL.
	file-number	An archived log file. The archived log file will have the name "messages<n>.gz" (while "n" is the file number) if you do not specify a new name for it in the upload URL. The file will be compressed with gzip.

	url	Uploads URL path. FTP, TFTP, SCP, and SFTP are supported. Example: scp://username[:password]@hostname/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # logging files uplaod 1 scp://admin@scpserver</pre>	
Related Commands	<pre>show logging show log files</pre>	
Notes		

show logging

	<pre>show logging</pre> <p>Displays the logging configurations.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show logging Local logging level: info Override for class mgmt-front: warning Default remote logging level: notice No remote syslog servers configured.</pre>

	<pre> Allow receiving of messages from remote hosts: no Number of archived log files to keep: 10 Log rotation size threshold: 5.000% of partition (43 megabytes) Log format: standard Subsecond timestamp field: enabled Subsecond timestamp precision: 1 whole digit; 3 fractional digits Levels at which messages are logged: CLI commands: info Audit messages: notice </pre>
Related Commands	<pre> logging fields logging files rotation logging level logging local logging receive logging <syslog IP address> </pre>
Notes	

show log

	<pre>show log [continues files [<file-number>]] [[not] matching <reg-exp>]</pre> <p>Displays the log file with optional filter criteria.</p>	
Syntax Description	continues	Displays the last few lines of the current log file and then continues to display new lines as they come in until the user hits Ctrl+C, similar to LINUX "tail" utility
	files	Displays the list of log files
	file-number	Displays an archived log file, where the number may range from 1 up to the number of archived log files available
	[not] matching <reg-exp>	The file is piped through a LINUX "grep" utility to only include lines either matching, or not matching, the provided regular expression
Default	N/A	
Configuration Mode	Any configuration mode	

History	1.5
Example	<pre> ufmapl [mgmt-sa] (config) # show log matching INFO Feb 1 10:57:04 switch clusterd[2659]: [4.193] [clusterd.INFO]: master browse reply: add service 0x20000 mxyzzzy--0002c95ea5d8 _tms_cluster._tcp. local. Feb 1 10:57:04 switch clusterd[2659]: [4.199] [clusterd.INFO]: master resolve reply via browse: name mxyzzzy--0002c95ea5d8 type _tms_cluster._tcp. domain local. addr 172.30.2.2 port 60102 ifindex 1 31072 Feb 1 10:57:07 switch SX[2785]: TID 1208106288: [7.746] [hwd.INFO]: hwd_kernel_interrupt_sim: Entry Feb 1 10:57:07 switch SX[2785]: TID 1208106288: [7.747] [hwd.INFO]: hwd_kernel_interrupt_sim: err=0 Feb 1 10:57:07 switch mgmtd[2599]: [7.748] [mgmtd.INFO]: Handling EVENT request (session 26) Feb 1 10:57:07 switch mgmtd[2599]: [7.749] [mgmtd.INFO]: EVENT: /system/ chassis/events/hw-isr-event Feb 1 10:57:07 switch mgmtd[2599]: [7.750] [mgmtd.INFO]: EVENT: [0] mask = 0 (uint32) Feb 1 10:57:07 switch health[2900]: TID 1208104656: [7.751] [health.INFO]: Received ISR event with mask 0 Feb 1 10:57:07 switch mgmtd[2599]: [7.754] [mgmtd.INFO]: Sending externally: type event session 36 id 1732128 Feb 1 10:57:07 switch mgmtd[2599]: [7.755] [mgmtd.INFO]: Event sent by user i:2785-0-0 has been handled </pre>
Related Commands	<pre> logging fields logging files rotation logging level logging local logging receive logging <syslog IP address> </pre>
Notes	

User Management and AAA

- [User Accounts](#)
- [AAA Methods](#)
- [RADIUS](#)
- [TACACS+](#)
- [LDAP](#)

User Accounts

username

	<p>username <username> [capability <cap> disable [login password] full-name <name> nopassword password [0 7] <password>] no username <username> [capability disable [login password] full-name]</p> <p>Creates a user and sets its capabilities, password and name. The no form of the command deletes the user configuration.</p>	
Syntax Description	username	Specifies a username and creates a user account. New users are created initially with admin privileges but is disabled.
	capability	User capabilities: <ul style="list-style-type: none"> • admin - full administrative capabilities • monitor - read only capabilities and actions, can not change the running configuration
	disable [login password]	<ul style="list-style-type: none"> • Disable - disable this account • Disable login - disable all logins to this account • Disable password - disable login to this account using a local password
	full-name	Full name of the user
	nopassword	The next login of the user will not require password

	0 7	<ul style="list-style-type: none"> • 0 - specifies a login password in cleartext • 7 - specifies a login password in encrypted text
	password	Specifies a password for the user in string form. If [0 7] was not specified then the password is in cleartext.
Default	<p>The following usernames are available by default:</p> <ul style="list-style-type: none"> • admin • monitor • xmladmin • xmluser 	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # username monitor full-name smith</pre>	
Related Commands	<pre>show usernames show users</pre>	
Notes	<ul style="list-style-type: none"> • To enable a user account, set a password on it (or use the "... nopassword" command to enable it with no password required for login) • Removing a user account does not terminate any current sessions that user has open; it just prevents new sessions from being established • Encrypted password is useful for the "show configuration" command, since the cleartext password cannot be recovered after it is set 	

show usernames

	<pre>show usernames</pre> <p>Displays list of users and their capabilities.</p>
--	---

Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmapl [mgmt-sa] (config) # show usernames USERNAME FULL NAME CAPABILITY ACCOUNT STATUS USERID System Administrator admin Password set admin System Administrator admin Password set monitor smith monitor Password set xmladmin XML Admin User admin No password required xmluser XML Monitor User monitor No password required </pre>
Related Commands	username show users
Notes	

show users

	show users [history]	
	Displays logged in users and related information such as idle time and what host they have connected from.	
Syntax Description	history	Displays current and historical sessions
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	

Example	<pre> ufmapl [mgmt-sa] (config) # show users USERNAME FULL NAME LINE HOST IDLE admin System Administrator pts/0 172.22.237.174 0d0h34m4s admin System Administrator pts/1 172.30.0.127 1d3h30m49s admin System Administrator pts/3 172.22.237.34 0d0h0m0s ufmapl [mgmt-sa] (config) # show users history admin pts/3 172.22.237.34 Wed Feb 1 11:56 still logged in admin pts/3 172.22.237.34 Wed Feb 1 11:42 - 11:46 (00:04) wtmp begins Wed Feb 1 11:38:10 2012 </pre>
Related Commands	<pre> username show usernames </pre>
Notes	

show whoami

	<pre> show whoami </pre> <p>Displays username and capabilities of user currently logged in.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmapl [mgmt-sa] (config) # show whoami Current user: admin Capabilities: admin </pre>

Related Commands	username show usernames show users
Notes	

AAA Methods

aaa accounting

	aaa accounting changes default {<time-frame> stop-only} tacacs+ no aaa accounting changes default {<time-frame> stop-only} tacacs+ Enables logging of system changes to a AAA accounting server. The no form of the command disables the accounting.	
Syntax Description	stop-only	Sends a stop accounting notice at the end of requested user process
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # aaa accounting changes default stop-only tacacs+</pre>	
Related Commands	show aaa	
Notes	<ul style="list-style-type: none"> • TACACS+ is presently the only accounting service method supported • Change accounting covers both configuration changes and system actions that are visible under audit logging, however this feature operates independently of audit logging, so it is unaffected by the "logging level audit mgmt" or "configuration audit" commands 	

- Configured TACACS+ servers are contacted in the order in which they appear in the configuration until one accepts the accounting data, or the server list is exhausted
- Despite the name of the "stop-only" keyword, which indicates that this feature logs a TACACS+ accounting "stop" message, and in contrast to configuration change accounting, which happens after configuration database changes, system actions are logged when the action is started, not when the action has completed

aaa authentication login default

	aaa authentication login default <auth method> [<auth method> [<auth method> [<auth method> [<auth method>]]]] no aaa authentication login Sets a sequence of authentication methods. Up to four methods can be configured. The no form of the command resets the configuration to its default.	
Syntax Description	auth-method	Possible values: <ul style="list-style-type: none"> • local • radius • tacacs+ • ldap
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # aaa authentication login default local radius tacacs+ ldap</pre>	
Related Commands	show aaa	
Notes	The order in which the methods are specified is the order in which the authentication is attempted. It is required that "local" is one of the methods selected. It is recommended that "local" be listed first to avoid potential problems logging in to local accounts in the face of network or remote server issues.	

aaa authorization map

	<p>aaa authorization map [default-user <username> order <policy>] no aaa authorization map [default-user order]</p> <p>Sets the mapping permissions of a user in case a remote authentication is done. The no form of the command resets the attributes to default.</p>	
Syntax Description	username	Specifies what local account the authenticated user will be logged on as when a user is authenticated (via RADIUS or TACACS+) and does not have a local account. If the username is local, this mapping is ignored.
	policy	<p>Sets the user mapping behavior when authenticating users via RADIUS or TACACS+ to one of three choices. The order determines how the remote user mapping behaves. If the authenticated username is valid locally, no mapping is performed. The setting has the following three possible behaviors:</p> <ul style="list-style-type: none"> • remote-first - If a local-user mapping attribute is returned and it is a valid local username, it maps the authenticated user to the local user specified in the attribute. Otherwise, it uses the user specified by the default-user command. • remote-only - Maps a remote authenticated user if the authentication server sends a local-user mapping attribute. If the attribute does not specify a valid local user, no further mapping is tried. • local-only - Maps all remote users to the user specified by the "aaa authorization map default-user <user name>" command. Any vendor attributes received by an authentication server are ignored.
Default	<p>Default user: admin Map order: remote-first</p>	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # aaa authorization map default-user admin</pre>	
Related Commands	show aaa username	
Notes	<p>If, for example, the user is locally defined to have admin permission, but in a remote server such as RADIUS the user is authenticated as monitor and the order is remote-first, then the user will be given monitor permissions.</p>	

show aaa

	<code>show aaa</code> Displays the AAA configuration.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show aaa AAA authorization: Default User: admin Map Order: remote-first Authentication method(s): local Accounting method(s): tacacs+</pre>
Related Commands	<code>aaa accounting</code> <code>aaa authentication</code> <code>aaa authorization</code> <code>show aaa</code> <code>show usernames</code> <code>username</code>
Notes	

RADIUS

radius-server

	<code>radius-server {key <secret> retransmit <retries> timeout <seconds>}</code> <code>no radius-server {key retransmit timeout}</code> Sets global RADIUS server attributes. The no form of the command resets the attributes to their default values.	
Syntax Description	key	Sets a secret key (shared hidden text string), known to the system and to the RADIUS server
	retransmit	Number of retries (0-5) before exhausting from the authentication
	timeout	Timeout in seconds between each retry (1-60)
Default	3 seconds, 1 retry	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # radius-server retransmit 3</pre>	
Related Commands	aaa authorization radius-server host show radius	
Notes	Each RADIUS server can override those global parameters using the command "radius-server host"	

radius-server host

	<p>radius-server host <ip-address> {enable auth-port <port> key <secret> retransmit <retries> timeout <seconds>} no radius-server host <ip-address> {enable auth-port }</p> <p>Configures RADIUS server attributes. The no form of the command resets the attributes to their default values and deletes the RADIUS server.</p>	
Syntax Description	ip-address	RADIUS server IP address
	enable	Administrative enable of the RADIUS server
	auth-port	RADIUS server UDP port number
	key	Sets a secret key (shared hidden text string) known to the system and to the RADIUS server
	retransmit	Number of retries (0-5) before exhausting from the authentication
	timeout	Timeout in seconds between each retry (1-60)
Default	3 seconds, 1 retry Default UDP port is 1812	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # radius-server host 40.40.40.40</pre>	
Related Commands	aaa authorization radius-server show radius	
Notes	<ul style="list-style-type: none"> • RADIUS servers are tried in the order they are configured • If you do not specify a parameter for this configured RADIUS server, the configuration will be taken from the global RADIUS server configuration. Refer to "radius-server" command. 	

show radius

	<code>show radius</code> Displays RADIUS configurations.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show radius RADIUS defaults: Key: 3333 Timeout: 3 Retransmit: 1 RADIUS servers: 40.40.40.40:1812 Enabled: yes Key: 3333 (default) Timeout: 3 (default) Retransmit: 1 (default)</pre>
Related Commands	<code>aaa authorization</code> <code>radius-server</code> <code>radius-server host</code>
Notes	

TACACS+

tacacs-server

	<code>tacacs-server {key <secret> retransmit <retries> timeout <seconds>}</code> <code>no tacacs-server {key retransmit timeout}</code> Sets global TACACS+ server attributes. The no form of the command resets the attributes to default values.	
Syntax Description	key	Set a secret key (shared hidden text string) known to the system and to the TACACS+ server
	retransmit	Number of retries (0-5) before exhausting from the authentication
	timeout	Timeout in seconds between each retry (1-60)
Default	3 seconds, 1 retry	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # tacacs-server retransmit 3</pre>	
Related Commands	aaa authorization show radius show tacacs tacacs-server host	
Notes	Each TACACS+ server can override those global parameters using the command "tacacs-server host"	

tacacs-server host

	<p>tacacs-server host <ip-address> {enable auth-port <port> auth-type <type> key <secret> retransmit <retries> timeout <seconds>}</p> <p>no tacacs-server host <ip-address> {enable auth-port}</p> <p>Configures TACACS+ server attributes. The no form of the command resets the attributes to their default values and deletes the TACACS+ server.</p>	
Syntax Description	ip-address	TACACS+ server IP address
	enable	Administrative enable for the TACACS+ server
	auth-port	TACACS+ server UDP port number
	key	Set a secret key (shared hidden text string) known to the system and to the TACACS+ server
	retransmit	Number of retries (0-5) before exhausting from the authentication
	timeout	Timeout in seconds between each retry (1-60)
Default	<p>3 seconds, 1 retry Default TCP port is 49 Default auth-type is PAP</p>	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # tacacs-server host 40.40.40.40</pre>	
Related Commands	<p>aaa authorization show tacacs tacacs-server</p>	
Notes	<ul style="list-style-type: none"> TACACS+ servers are tried in the order they are configured A PAP auth-type similar to an ASCII login, except that the username and password arrive at the network access server in a PAP protocol packet instead of being typed in by the user, so the user is not prompted 	

- If the user does not specify a parameter for this configured TACACS+ server, the configuration will be taken from the global TACACS+ server configuration. Refer to "tacacs-server" command.

show tacacs

	<p>show tacacs</p> <p>Displays TACACS+ configurations.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmap1 [mgmt-sa] (config) # show tacacs TACACS+ defaults: Key: 3333 Timeout: 3 Retransmit: 1 TACACS+ servers: 40.40.40.40:49 Enabled: yes Auth-type: PAP Key: 3333 (default) Timeout: 3 (default) Retransmit: 1 (default) </pre>
Related Commands	<p>aaa authorization</p> <p>tacacs-server</p> <p>tacacs-server host</p>
Notes	

LDAP

ldap base-dn

	ldap base-dn <string> no ldap base-dn Sets the base distinguished name (location) of the user information in the schema of the LDAP server. The no form of the command resets the attribute to its default values.	
Syntax Description	string	A case-sensitive string that specifies the location in the LDAP hierarchy where the server should begin searching when it receives an authorization request. For example: "ou=users,dc=example,dc=com", with no spaces. Where: <ul style="list-style-type: none">• ou - organizational unit• dc - domain component• cn - common name• sn - surname
Default	ou=users,dc=example,dc=com	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # ldap base-dn ou=department,dc=example,dc=com</pre>	
Related Commands	show ldap	
Notes		

ldap {bind-dn | bind-password}

	ldap {bind-dn bind-password} <string> no ldap {bind-dn bind-password}	
	Gives the distinguished name or password to bind to on the LDAP server. This can be left empty for anonymous login (the default). The no form of the command resets the attribute to its default values.	
Syntax Description	string	A case-sensitive string that specifies distinguished name or password to bind to on the LDAP server
Default	""	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ldap bind-dn my-dn ufmapl [mgmt-sa] (config) # ldap bind-password my-password</pre>	
Related Commands	show ldap	
Notes	For anonymous login, bind-dn and bind-password should be empty strings ""	

ldap {group-attribute | group-dn}

	ldap {group-attribute {<group-att> member uniqueMember} group-dn <group-dn>} no ldap {group-attribute group-dn}	
	Sets the distinguished name or attribute name of a group on the LDAP server. The no form of the command resets the attribute to its default values.	
Syntax Description	group-attribute	Specifies a custom attribute name
	member	groupOfNames or group membership attribute

	uniqueMember	groupOfUniqueNames membership attribute
	group-dn	DN of group required for authorization
Default	group-att: member group-dn: ""	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ldap group-attribute member ufmapl [mgmt-sa] (config) # ldap group-dn my-group-dn</pre>	
Related Commands	show ldap	
Notes	<ul style="list-style-type: none"> The user's distinguished name must be listed as one of the values of this attribute or the user will not be authorized to log in. After login authentication, if the group-dn is set, a user must be a member of this group or the user will not be authorized to log in. If the group is not set ("" - the default) no authorization checks are done. 	

Ldap host

	ldap host <ip-address> [order <number> last] no ldap host <ip-address>	
	Adds an LDAP server to the set of servers used for authentication. The no form of the command deletes the LDAP host.	
Syntax Description	ip-address	IP address
	number	The order of the LDAP server
	last	The LDAP server will be added in the last location
Default	N/A	
Configuration Mode	config	

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # ldap host 10.10.10.10</pre>
Related Commands	show aaa show ldap
Notes	<ul style="list-style-type: none"> • The system will select the LDAP host to try according to its order • New servers are by default added at the end of the list of servers

ldap login-attribute

	ldap login-attribute {<string> uid sAMAccountName} no ldap login-attribute Sets the attribute name which contains the login name of the user. The no form of the command resets this attribute to its default.	
Syntax Description	string	Custom attribute name
	uid	LDAP login name is taken from the user login username
	sAMAccountName	SAM Account name, active directory login name
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ldap login-attribute uid</pre>	
Related Commands	show aaa show ldap	

Notes	
-------	--

ldap port

	ldap port <port> no ldap port Sets the TCP port on the LDAP server to connect to for authentication. The no form of the command resets this attribute to its default value.	
Syntax Description	port	TCP port number
Default	389	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ldap port 1111</pre>	
Related Commands	show aaa show ldap	
Notes		

ldap referrals

	ldap referrals no ldap referrals Enables LDAP referrals. The no form of the command disables LDAP referrals.
--	---

Syntax Description	N/A
Default	Enabled
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # no ldap referrals</pre>
Related Commands	show aaa show ldap
Notes	Referral is the process by which an LDAP server, instead of returning a result, will return a referral (a reference) to another LDAP server which may contain further information.

Ldap scope

	ldap scope <scope> no ldap scope Specifies the extent of the search in the LDAP hierarchy that the server should make when it receives an authorization request. The no form of the command resets the attribute to its default value.	
Syntax Description	scope	<ul style="list-style-type: none"> • one-level - searches the immediate children of the base dn • subtree - searches at the base DN and all its children
Default	subtree	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # ldap scope subtree</pre>
Related Commands	<pre>show aaa show ldap</pre>
Notes	

ldap ssl

	<pre>ldap ssl {cert-verify mode <mode> port <port-number>} no ldap ssl {cert-verify mode port}</pre> <p>Sets SSL parameter for LDAP. The no form of the command resets the attribute to its default value.</p>	
Syntax Description	cert-verify	Enables verification of SSL/TLS server certificates. This may be required if the server's certificate is self-signed, or does not match the name of the server.
	mode	<p>Sets the security mode for connections to the LDAP server.</p> <ul style="list-style-type: none"> • none - requests no encryption for the LDAP connection • ssl - the SSL-port configuration is used, an SSL connection is made before LDAP requests are sent (LDAP over SSL) • tls - the normal LDAP port is used, an LDAP connection is initiated, and then TLS is started on this existing connection
	port	Sets the port on the LDAP server to connect to for authentication when the SSL security mode is enabled (LDAP over SSL)
Default	<pre>cert-verify is enabled mode is none (LDAP SSL is not activated) port-number is 636</pre>	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # ldap ssl mode ssl</pre>
Related Commands	show aaa show ldap
Notes	<ul style="list-style-type: none"> • If available, the TLS mode is recommended, as it is standardized, and may also be of higher security • The port number is used only for SSL mode. If the mode is TLS, the LDAP port number will be used.

Ldap timeout

	<pre>ldap {timeout-bind timeout-search} <seconds> no ldap {timeout-bind timeout-search}</pre> <p>Sets a global communication timeout in seconds for all LDAP servers to specify the extent of the search in the LDAP hierarchy that the server should make when it receives an authorization request. The no form of the command resets the attribute to its default value.</p>	
Syntax Description	timeout-bind	Sets the global LDAP bind timeout for all LDAP servers
	timeout-search	Sets the global LDAP search timeout for all LDAP servers
	seconds	Range: 1-60
Default	5 seconds	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ldap timeout-bind 10</pre>	
Related Commands	show aaa show ldap	

Notes	
-------	--

ldap version

	ldap version <version> no ldap version Sets the LDAP version. The no form of the command resets the attribute to its default value.	
Syntax Description	version	Sets the LDAP version. Possible values: 2 or 3.
Default	3	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ldap version 3</pre>	
Related Commands	show aaa show ldap	
Notes		

show ldap

	show ldap Displays LDAP configurations.
Syntax Description	N/A
Default	N/A

Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmapl [mgmt-sa] (config) # show ldap User base DN : ou=department,dc=example,dc=com User search scope : subtree Login attribute : uid Bind DN : my-dn Bind password : my-password Group base DN : my-group-dn Group attribute : member LDAP version : 3 Referrals : no Server port : 1111 Search Timeout : 5 Bind Timeout : 10 SSL mode : none Server SSL port : 636 (not active) SSL cert verify : yes LDAP servers: 1: 10.10.10.10 2: 10.10.10.12 </pre>
Related Commands	<pre> show aaa show ldap </pre>
Notes	

Security

ip filter enable

	<code>ip filter enable</code> <code>no ip filter enable</code> Enables IP filtering. The no form of the command disables IP filtering.
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # no ip filter enable</pre>
Related Commands	<code>show ip filter</code>
Notes	

ip filter chain

	<code>ip filter chain [FORWARD <clear> <policy> <rule> INPUT <clear> <policy> <rule> OUTPUT <clear> <policy> <rule>]</code> <code>no ip filter chain</code> Sets the policy, as a default target, for a specified chain. The no form of the command resets the policy to its default.
--	--

Syntax Description	clear	Delete all rules from this chain
	policy	Specify default policy for this chain
	rule	Add or modify an IP filtering rule
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ip filter chain FORWARD clear</pre>	
Related Commands	show ip filter	
Notes		

show ip filter

	show ip filter [all configured] Displays IP filtering configuration or status.	
Syntax Description	all	Displays IP filtering state (including unconfigured rules)
	configured	Displays IP filtering configuration
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # show ip filter Packet filtering for IPv4: DISABLED</pre>	

	<pre>Active IPv4 filtering rules (omitting any not from configuration): Chain 'INPUT' No rules. Policy: ACCEPT Chain 'OUTPUT' No rules. Policy: ACCEPT Chain 'FORWARD' No rules. Policy: ACCEPT</pre>
Related Commands	<pre>ip filter chain ip filter enable</pre>
Notes	

Firmware Management

firmware install

	<pre>firmware install</pre> <p>Installs the updated HCA firmware supplied in the software image.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5

Example	<pre>ufmapl [mgmt-sa] (config) # firmware install</pre>
Related Commands	show firmware
Notes	Running this command requires system reboot.

show firmware

	<p>show firmware</p> <p>Displays the HCA firmware information.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show firmware Installed firmware version: 2.11.500 Running firmware version: 2.11.500 Image available for installation: 2.11.500</pre>
Related Commands	firmware install
Notes	

CLI Session

This chapter displays all the relevant commands used to manage CLI session terminal.

cli clear-history

	<code>cli clear-history</code> Clears the command history of the current user.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # cli clear-history</pre>
Related Commands	
Notes	

cli default

	<p>cli default {auto-logout <minutes> paging enable prefix-modes {enable show-config} progress enable prompt {confirm-reload confirm-reset confirm-unsaved empty-password}</p> <p>no cli default {auto-logout paging enable prefix-modes {enable show-config} progress enable prompt {confirm-reload confirm-reset confirm-unsaved empty-password}</p> <p>Configures default CLI options for all future sessions. The no form of the command deletes or disables the default CLI options.</p>	
Syntax Description	minutes	Configures keyboard inactivity timeout for automatic logout. Range: 0-35791. Setting the value to 0 or using the no form of the command disables the auto-logout.
	paging enable	Enables text viewing one screen at a time
	prefix-modes {enable show-config}	Configures the prefix modes feature of CLI. <ul style="list-style-type: none"> • "prefix-modes enable" enables prefix modes for current and all future sessions • "prefix-modes show-config" uses prefix modes in "show configuration" output for current and all future sessions
	progress enable	Enables progress updates
	prompt confirm-reload	Prompts for confirmation before rebooting
	prompt confirm-reset	Prompts for confirmation before resetting to factory state
	prompt confirm-unsaved	Confirms whether or not to save unsaved changes before rebooting
	prompt empty-password	Prompts for a password if none is specified in a pseudo-URL for SCP
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # cli default prefix-modes enable</pre>	
Related Commands	show cli	

Notes	
-------	--

cli session

	<pre>cli session {auto-logout <minutes> paging enable prefix-modes {enable show-config} progress enable terminal {length <size> resize type <terminal-type> width} x-display full <display>} no cli session {auto-logout paging enable prefix-modes {enable show-config} progress enable terminal type x-display}</pre> <p>Configures default CLI options for all future sessions. The no form of the command deletes or disables the CLI sessions.</p>	
Syntax Description	minutes	Configures keyboard inactivity timeout for automatic logout. Range: 0-35791. Setting the value to 0 or using the no form of the command disables the auto logout.
	paging enable	Enables text viewing one screen at a time
	prefix-modes enable show-config	Configures the prefix modes feature of CLI. “prefix-modes enable” enables prefix modes for current and all future sessions “prefix-modes show-config” uses prefix modes in “show configuration” output for current and all future sessions
	progress enable	Enables progress updates
	terminal length	Sets the number of lines for the current terminal. Range: 5-999.
	terminal resize	Resizes the CLI terminal settings (to match the actual terminal window)
	terminal-type	Sets the terminal type. Valid options: ansi, console, dumb, linux, unknown, vt52, vt100, vt102, vt220, vt320, xterm.
	terminal width	Sets the width of the terminal in characters. Range: 34-999.
	x-display full <display>	Specifies the display as a raw string (e.g localhost:0.0)
Default	N/A	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # cli session auto-logout</pre>
Related Commands	show terminal
Notes	

show cli

	<p>show cli</p> <p>Displays the CLI configuration and status.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show cli CLI current session settings: Maximum line size: 8192 Terminal width: 171 columns Terminal length: 38 rows Terminal type: xterm X display setting: (none) Auto-logout: disabled Paging: enabled Progress tracking: enabled Prefix modes: disabled CLI defaults for future sessions:</pre>

	<pre> Auto-logout: disabled Paging: enabled Progress tracking: enabled Prefix modes: enabled (and use in 'show configuration') Settings for both this session and future ones: Show hidden config: yes Confirm losing changes: yes Confirm reboot/shutdown: no Confirm factory reset: yes Prompt on empty password: yes </pre>
Related Commands	cli default
Notes	

Banner

banner login

	<pre> banner login <string> no banner login </pre> <p>Sets the CLI welcome banner message. The no form of the command resets the system login banner to its default.</p>	
Syntax Description	string	Text banner
Default	"Mellanox MLNX-OS UFM Appliance Management"	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # banner login example</pre>
Related Commands	show banner
Notes	The banner's content changes in case of different system issues

banner motd

	banner motd <string> no banner motd Sets the contents of the /etc/motd file. The no form of the command resets the system Message of the Day banner.	
Syntax Description	string	Text banner
Default	"Mellanox Switch"	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # banner motd Testing</pre>	
Related Commands	show banner	
Notes	If more than one word is used (there is a space) quotation marks should be added (i.e. "xxxx xxxx")	

show banner

	<code>show banner</code> Displays configured banners.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show banner Banners: MOTD: Mellanox UFM Appliance Login: Mellanox MLNX-OS UFM Appliance Management</pre>
Related Commands	<code>banner login</code> <code>banner motd</code>
Notes	

SSH

ssh server enable

	ssh server enable no ssh server enable Enables the SSH server. The no form of the command disables the SSH server.
Syntax Description	N/A
Default	Enabled
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # ssh server enable</pre>
Related Commands	show ssh server
Notes	Disabling SSH server does not terminate existing SSH sessions, it only prevents new ones from being established.

ssh server host-key

	ssh server host-key {<key type> {private-key <private-key> public-key <public-key>} generate} Manipulates host keys for SSH.	
Syntax Description	key-type	<ul style="list-style-type: none">rsa1 - RSAv1

		<ul style="list-style-type: none"> rsa2 - RSAv2 dsa2 - DSAv2
	private-key	Sets new private-key for the host keys of the specified type
	public-key	Sets new public-key for the host keys of the specified type
	generate	Generates new RSA and DSA host keys for SSH
Default	SSH keys are locally generated	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmap1 [mgmt-sa] (config) # ssh server host-key dsa2 private-key Key: ***** Confirm: ***** </pre>	
Related Commands	show ssh server	
Notes		

ssh server listen

	ssh server listen {enable interface <inf>} no ssh server listen {enable interface <inf>} Enables the listen interface restricted list for SSH. If enabled, and at least one non-DHCP interface is specified in the list, the SSH connections are only accepted on those specified interfaces. The no form of the command disables the listen interface restricted list for SSH. When disabled, SSH connections are not accepted on any interface.	
Syntax Description	enable	Enables SSH interface restrictions on access to this system
	interface	Adds interface to SSH server access restriction list Possible values: {lo eth0}

Default	SSH listen is enabled
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # ssh server listen enable</pre>
Related Commands	show ssh server
Notes	

ssh server min-version

	ssh server min-version <version> no ssh server min-version Sets the minimum version of the SSH protocol that the server supports. The no form of the command resets the minimum version of SSH protocol supported.	
Syntax Description	version	Values: 1 or 2
Default	2	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ssh server min-version 2</pre>	
Related Commands	show ssh server	
Notes		

ssh server ports

	ssh server ports {<port1> [<port2>...]}	
	Specifies which ports the SSH server listens on.	
Syntax Description	port	Port number in [1...65535]
Default	22	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # ssh server ports 22</pre>	
Related Commands	show ssh server	
Notes	<ul style="list-style-type: none"> • Multiple ports can be specified by repeating the <port> parameter • The command will remove any previous ports if not listed in the command 	

ssh server x11-forwarding

	ssh server x11-forwarding enable no ssh server x11-forwarding enable
	Enables X11 forwarding on the SSH server. The no form of the command disables X11 forwarding.
Syntax Description	N/A
Default	Disabled
Configuration Mode	config

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # ssh server x11-forwarding enable</pre>
Related Commands	show ssh server
Notes	

ssh client global

	<code>ssh client global {host-key-check <policy>} known-host <known-host-entry>}</code> <code>no ssh client global {host-key-check known-host localhost}</code> Configures global SSH client settings. The no form of the command negates global SSH client settings.	
Syntax Description	host-key-check	Sets SSH client configuration to control how host key checking is performed. This parameter may be set in 3 ways. <ul style="list-style-type: none"> • If set to "no" it always permits connection, and accepts any new or changed host keys without checking • If set to "ask" it prompts user to accept new host keys, but does not permit a connection if there was already a known host entry that does not match the one presented by the host • If set to "yes" it only permits connection if a matching host key is already in the known hosts file
	known-host	Adds an entry to the global known-hosts configuration file. The entry consists of "<IP> <key-type> <key>".
Default	host-key-check - ask, no keys are configured by default	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmap1 [mgmt-sa] (config) # ssh client global host-key-check no</pre>
Related Commands	show ssh client
Notes	

ssh client user

	<pre>ssh client user <username> {authorized-key sshv2 <public key> identity <key type> {generate private-key [<private key>] public-key [<public key>]} known-host <known host> remove} no ssh client user admin {authorized-key sshv2 <public key ID> identity <key type>}</pre> <p>Adds an entry to the global known-hosts configuration file, either by generating new key, or by adding manually a public or private key. The no form of the command removes a public key from the specified user's authorized key list, or changes the key type.</p>	
Syntax Description	username	The specified user must be a valid account on the system. Possible values: admin, monitor, xmladmin, and xmluser.
	authorized-key sshv2	Adds the specified key to the list of authorized SSHv2 RSA or DSA public keys for this user account. These keys can be used to log into the user's account.
	identity	Sets certain SSH client identity settings for a user, dsa2 or rsa2
	generate	Generates SSH client identity keys for specified user
	private-key	Sets private key SSH client identity settings for the user
	public-key	Sets public key SSH client identity settings for the user
	known-host	Removes host from user's known host file
Default	No keys	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # ssh client user admin known-host 172.30.1.116 remove</pre>
Related Commands	show ssh client
Notes	If a key is being pasted from a cut buffer and was displayed with a paging program, it is likely that newline characters have been inserted, even if the output was not long enough to require paging. One can specify "no cli session paging enable" before running the "show" command to prevent the newlines from being inserted.

slogin

	slogin [<slogin options>] <hostname> Invokes the SSH client. The user is returned to the CLI when SSH finishes.	
Syntax Description	slogin options	usage: slogin [-1246AaCfGkNnqsTtVvXxY] [-b bind_address] [-c cipher_spec] [-D port] [-e escape_char] [-F configfile] [-i identity_file] [-L port:host:hostport] [-l login_name] [-m mac_spec] [-o option] [-p port] [-R port:host:hostport] [user@]hostname [command]
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # slogin 192.168.10.70 The authenticity of host '192.168.10.70 (192.168.10.70)' can't be established. RSA key fingerprint is 2e:ad:2d:23:45:4e:47:e0:2c:ae:8c:34:f0:1a:88:cb. Are you sure you want to continue connecting (yes/no)? yes Warning: Permanently added '192.168.10.70' (RSA) to the list of known hosts.</pre>	

	<pre>Mellanox MLNX-OS Switch Management Last login: Sat Feb 28 22:55:17 2009 from 10.208.0.121 Mellanox Switch</pre>
Related Commands	
Notes	

show ssh client

	<pre>show ssh client Displays the client configuration of the SSH server.</pre>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show ssh client SSH client Strict Hostkey Checking: ask SSH Global Known Hosts: Entry 1: 72.30.2.2 Finger Print: 1e:b7:8b:ec:ab:35:98:be:6b:d6:12:c2:18:72:12:d6 No SSH user identities configured. No SSH authorized keys configured.</pre>

Related Commands	ssh client global ssh client user
Notes	

show ssh server

	show ssh server Displays SSH server configuration.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmap1 [mgmt-sa] (config) # show ssh server SSH server configuration: SSH server enabled: yes Minimum protocol version: 2 X11 forwarding enabled: no SSH server ports: 22 Interface listen enabled: yes No Listen Interfaces. Host Key Finger Prints: RSA v1 host key: a0:63:db:96:e2:95:5a:5a:fd:a8:d0:f4:ab:e3:5f:f8 RSA v2 host key: 1e:b7:8b:ec:ab:35:98:be:6b:d6:12:c2:18:72:12:d6 DSA v2 host key: 7c:4a:f7:72:51:67:b5:0b:cd:a2:d2:b9:f3:be:3e:68 </pre>
Related Commands	ssh server

Notes	
-------	--

Remote Login

telnet-server enable

	<p>telnet-server enable no telnet-server enable</p> <p>Enables the telnet server. The no form of the command disables the telnet server.</p>
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	1.5
Example	<pre>ufmap1 [mgmt-sa] (config) # telnet-server enable</pre>
Related Commands	show telnet-server
Notes	

show telnet-server

	<code>show telnet-server</code> Displays telnet server settings.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmap1 [mgmt-sa] (config) # show telnet-server Telnet server enabled: yes</pre>
Related Commands	telnet-server
Notes	

Web Server

web auto-logout

	<code>web auto-logout <number-of-minutes></code> <code>no web auto-logout</code> Configures length of user inactivity before auto-logout of a web session. The no form of the command disables the web auto-logout (web sessions will never logged out due to inactivity).
--	---

Syntax Description	number-of-minutes	The length of user inactivity in minutes. 0 disables the inactivity timer (same as a "no web auto-logout" command).
Default	60 minutes	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # web auto-logout 60</pre>	
Related Commands	show web	
Notes	The no form of the command does not automatically log users out due to inactivity.	

web enable

	<pre>web enable no web enable</pre> <p>Enables the web-based management console. The no form of the command disables the web-based management console.</p>
Syntax Description	N/A
Default	Enabled
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # web enable</pre>
Related Commands	show web

Notes	
-------	--

web http

	<pre>web http {enable redirect} no web http {enable redirect}</pre> <p>Configures HTTP access to the web-based management console. The no form of the command negates HTTP settings for the web-based management console.</p>	
Syntax Description	enable	Enable HTTP access to the web-based management console
	redirect	Enables redirection to HTTPS
Default	<p>HTTP is enabled HTTP TCP port is 80 HTTP redirect to HTTPS is disabled</p>	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # web http enable</pre>	
Related Commands	show web	
Notes	If HTTP access is enabled, this specifies whether a redirect from the HTTP port to the HTTPS port should be issued to mandate secure HTTPS access.	

web httpd listen

	<pre>web httpd listen {enable interface <ifName>} no web httpd listen {enable interface <ifName>}</pre> <p>Enables the listen interface restricted list for HTTP and HTTPS. The no form of the command disables the HTTP server listen ability.</p>	
Syntax Description	enable	Enable HTTP access to the web-based management console
	interface	Adds interface to Web server access restriction list (i.e. eth0, eth1)
Default	Listening is enabled All interfaces are permitted	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # web httpd enable</pre>	
Related Commands	show web	
Notes	If enabled, and if at least one of the interfaces listed is eligible to be a listen interface, then HTTP/HTTPS requests will only be accepted on those interfaces. Otherwise, HTTP/HTTPS requests are accepted on any interface.	

web https

	<pre>web https {certificate {default-cert name <name> regenerate} enable ssl} no web https {certificate enable ssl}</pre> <p>Configure HTTPS access to the web-based management console. The no form of the command disables the HTTPS server listen ability.</p>	
--	---	--

Syntax Description	certificate	Configure the certificate to use for HTTPS connections <ul style="list-style-type: none"> • default-cert - Configure HTTPS to use the configured default certificate • name - Configure the named certificate to be used for HTTPS connections • regenerate - Regenerate the system default certificate for HTTPS connections
	enable	Enable HTTPS access o the web-based management console
	ssl	Configure SSL/TLS settings for HTTPS
Default	HTTPS is enabled Default port is 443	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # web https enable</pre>	
Related Commands	show web web enable	
Notes		

web sessions

	web session {renewal <minutes> timeout <minutes>} no web session {renewal timeout} Configures session settings. The no form of the command resets session settings to default.	
Syntax Description	renewal	Configures time before expiration to renew a session
	timeout	Configures time after which a session expires

Default	timeout - 2.5 hours renewal - 30 min
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # web sessions renewal 30</pre>
Related Commands	show web
Notes	

web proxy auth

	<pre>web proxy auth {authtype <type> basic [password <password> username <username>]}</pre> <pre>no web proxy auth {authtype basic {password username } }</pre> <p>Configures authentication settings for web proxy authentication. The no form of the command resets the attributes to their default values.</p>	
Syntax Description	type	Configures the type of authentication to use with web proxy. Possible values: <ul style="list-style-type: none"> • basic - HTTP basic authentication • none - No authentication
	basic	Configures HTTP basic authentication settings for proxy
	password	A password used for HTTP basic authentication with the web proxy
	username	A username used for HTTP basic authentication with the web proxy
Default	Web proxy is disabled	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # web proxy auth authtype basic ufmapl [mgmt-sa] (config) # web proxy auth basic username web-user ufmapl [mgmt-sa] (config) # web proxy auth basic password web-password</pre>
Related Commands	<pre>show web web proxy host</pre>
Notes	

web proxy host

	<pre>web proxy host <ip-address> [port <port-number>] no web proxy</pre> <p>Adds and enables a proxy to be used for any HTTP or FTP downloads. The no form of the command disables the web proxy.</p>	
Syntax Description	ip-address	IPv4 address
	port	Sets the web proxy default port
Default	1080	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # web proxy host 10.10.10.10 port 1080</pre>	
Related Commands	<pre>show web web proxy auth</pre>	
Notes		

show web

	<code>show web</code> Displays the web configuration.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show web Web User Interface: Web interface enabled: yes Web caching enabled: no HTTP enabled: no HTTP redirect to HTTPS: no HTTPS enabled: yes HTTPS ssl-ciphers: TLS1.2 HTTPS ssl-renegotiation: no HTTPS ssl-secure-cookie: yes HTTPS certificate name: default-cert Listen enabled: yes Listen interfaces: No interface configured. Inactivity timeout: 5 min Session timeout: 10 min Session renewal: 5 min Web file transfer proxy: Proxy enabled: no Web file transfer certificate authority:</pre>

	<pre>HTTPS server cert verify: yes HTTPS supplemental CA list: default-ca-list</pre>
Related Commands	
Notes	

SNMP

The commands in this section are used to manage the SNMP server. UFM SNMP settings must be modified in the configuration file using the "ufm configuration export/import" commands.

snmp-server community

	<pre>snmp-server community <community> [ro rw] no snmp-server community <community></pre> <p>Sets a community name for either read-only or read-write SNMP requests. The no form of the command sets the community string to default.</p>	
Syntax Description	community	Community name
	ro	Sets the read-only community string
	rw	Sets the read-write community string
Default	Read-only community: "public" Read-write community: ""	
Configuration Mode	config	
History	1.5	
Example	<pre>switch[mgmt-sa] (config) # snmp-server community private rw</pre>	

Related Commands	show snmp
Notes	<ul style="list-style-type: none"> • If neither the "ro" or the "rw" parameters are specified, the read-only community is set as the default community • If the read-only community is specified, only queries can be performed • If the read-write community is specified, both queries and sets can be performed

snmp-server contact

	snmp-server contact <contact-name> no snmp-server contact Sets a value for the sysContact variable in MIB-II. The no form of the command resets the parameter to its default value.	
Syntax Description	contact-name	Contact name
Default	""	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # snmp-server contact my-name</pre>	
Related Commands	show snmp	
Notes		

snmp-server listen

	<code>snmp-server listen {enable interface <ifName>}</code> <code>no snmp-server listen {enable interface <ifName>}</code>	
	<p>Configures SNMP server interface access restrictions. The no form of the command disables the listen interface restricted list for SNMP server.</p>	
Syntax Description	enable	Enables SNMP interface restrictions on access to this system
	interface	Adds an interface to the "listen" list for SNMP server. For example: "eth0", "eth1".
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # snmp listen enable</pre>	
Related Commands	show snmp	
Notes	If enabled, and if at least one of the interfaces listed is eligible to be a listen interface, then SNMP requests will only be accepted on those interfaces. Otherwise, SNMP requests are accepted on any interface.	

snmp-server location

	<code>snmp-server location <system-location></code> <code>no snmp-server location</code>	
	<p>Sets a value for the sysLocation variable in MIB-II. The no form of the command clears the contents of the sysLocation variable.</p>	
Syntax Description	system-location	string

Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # snmp-server location lab</pre>
Related Commands	show snmp
Notes	

snmp-server port

	<p>snmp-server port <port> no snmp-server port</p> <p>Sets the UDP listening port for the SNMP agent. The no form of the command resets the parameter to its default value.</p>
Syntax Description	N/A
Default	161
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # snmp-server port 1000</pre>
Related Commands	show snmp
Notes	

snmp-server traps

	<pre>snmp-server traps {community <community> event <event name> port <port> send-test} no snmp-server traps {community event <event name> port}</pre> <p>Configures hosts to which to send SNMP traps. The no form of the commands removes a host from which SNMP traps should be sent.</p>	
Syntax Description	community	Sets the default community for traps sent to hosts which do not have a custom community string set
	event	Specifies which events will be sent as traps
	port	Sets the default port to which traps are sent
	send-test	Sends a test trap
Default	Community: public All traps are enabled Port: 162	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # snmp-server community public</pre>	
Related Commands	<pre>show snmp show snmp events</pre>	
Notes	<ul style="list-style-type: none"> • This setting is only meaningful if traps are enabled, though the list of hosts may still be edited if traps are disabled • Refer to Mellanox MIB file for the list of supported traps 	

snmp-server user

	<p>snmp-server user {admin <username>} v3 {[encrypted] auth <hash-type> <password> [priv <privacy-type> [<password>]] capability <cap> enable <sets> prompt auth <hash-type> [priv <privacy-type>]}</p> <p>no snmp-server user {admin <username>} v3 {[encrypted] auth <hash-type> <password> [priv <privacy-type> [<password>]] capability <cap> enable <sets> prompt auth <hash-type> [priv <privacy-type>]}</p> <p>Specifies an existing username, or a new one to be added. The no form of the command disables access via SNMP v3 for the specified user.</p>	
Syntax Description	v3	Configures SNMPv3 users
	auth	Configures SNMPv3 security parameters, specifying passwords in plaintext on the command line. Note that passwords are always stored encrypted.
	capability	Sets capability level for SET requests
	enable	Enables SNMPv3 access for this user
	encrypted	Configures SNMPv3 security parameters, specifying passwords in encrypted form
	prompt	Configures SNMPv3 security parameters, specifying passwords securely in follow-up prompts, rather than on the command line
Default	No SNMPv3 users defined	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # snmp-server user admin v3 enable</pre>	
Related Commands	show snmp user	
Notes		

show snmp

	<p>show snmp [engineID events user]</p> <p>Displays SNMP-server configuration and status.</p>	
Syntax Description	engineID	SNMP Engine ID
	events	SNMP events
	user	SNMP users
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # show snmp SNMP enabled : yes SNMP port : 161 System contact : www.mellanox.com System location: Read-only community: public Read-write community: private Interface listen enabled: yes Listen Interfaces: No Listen Interfaces. </pre>	
Related Commands		
Notes		

Scheduled Jobs

Use the commands in this section to manage and schedule the execution of jobs.

job

	<code>job <job-id></code> <code>no job <job-id></code> Creates a job. The no form of the command deletes the job.	
Syntax Description	<code>job-id</code>	An integer
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # job 100 ufmapl [mgmt-sa] (config job 100) #</pre>	
Related Commands	show jobs	
Notes	Job state is lost on reboot.	

comment

	<code>comment <comment></code> <code>no comment</code> Adds a comment to the job. The no form of the command deletes the comment.	
Syntax Description	<code>comment</code>	String
Default	""	
Configuration Mode	config job	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config job 100) # comment example_comment</pre>	
Related Commands	show jobs	
Notes		

command

	<code>command <sequence #> <command></code> <code>no command <sequence #></code> Adds a CLI command to the job. The no form of the command deletes the command from the job.	
Syntax Description	sequence #	An integer that controls the order the command is executed relative to other commands in this job. The commands are executed in an ascending order.
	command	CLI command

Default	N/A
Configuration Mode	config job
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config job 100) # command 10 "show power"</pre>
Related Commands	show jobs
Notes	<ul style="list-style-type: none"> • The command must be defined with quotation marks ("") • The command must be added as it was executed from the "config" mode. For example, in order to change the interface description you need to add the command: "interface <type> <number> description my-description".

enable

	<p>enable no enable</p> <p>Enables the specified job. The no form of the command disables the specified job.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config job
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config job 100) # enable</pre>
Related Commands	show jobs

Notes	If a job is disabled, it will not be executed automatically according to its schedule; nor can it be executed manually.
-------	---

execute

	execute Forces an immediate execution of the job.
Syntax Description	N/A
Default	N/A
Configuration Mode	config job
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config job 100) # execute</pre>
Related Commands	show jobs
Notes	<ul style="list-style-type: none"> The job timer (if set) is not canceled and the job state is not changed (i.e. the time of the next automatic execution is not affected) The job will not be run if not currently enabled

fail-continue

	fail-continue no fail-continue Continues the job execution regardless of any job failures. The no form of the command returns fail-continue to its default.
--	--

Syntax Description	N/A
Default	A job will halt execution as soon as any of its commands fails
Configuration Mode	config job
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config job 100) # fail-continue</pre>
Related Commands	show jobs
Notes	

name

	name <job-name> no name Configures a name for this job. The no form of the command resets the name to its default.	
Syntax Description	job-name	String defining a name for the job
Default	""	
Configuration Mode	config job	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config job 100) # name my-job</pre>	
Related Commands	show jobs	
Notes		

schedule type

	<p>schedule type <recurrence-type> no schedule type</p> <p>Sets the type of schedule the job will automatically execute on. The no form of the command resets the schedule type to its default.</p>	
Syntax Description	recurrence-type	<p>The available schedule types are:</p> <ul style="list-style-type: none"> • daily - the job is executed every day at a specified time • weekly - the job is executed on a weekly basis • monthly - the job is executed every month on a specified day of the month • once - the job is executed once at a single specified date and time • periodic - the job is executed on a specified fixed time interval starting from a fixed point in time
Default	once	
Configuration Mode	config job	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config job 100) # schedule type once</pre>	
Related Commands	show jobs	
Notes	A schedule type is essentially a structure for specifying one or more future dates and times for a job to execute.	

schedule <recurrence-type>

	<p>schedule <recurrence-type> <interval-and-date> no schedule</p> <p>Sets the type of schedule the job will automatically execute on. The no form of the command resets the schedule type to its default.</p>	
Syntax Description	recurrence-type	<p>The available schedule types are:</p> <ul style="list-style-type: none"> • daily - the job is executed every day at a specified time • weekly - the job is executed on a weekly basis • monthly - the job is executed every month on a specified day of the month • once - the job is executed once at a single specified date and time • periodic - the job is executed on a specified fixed time interval starting from a fixed point in time
	interval-and-date	Interval and date per recurrence type
Default	once	
Configuration Mode	config job	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config job 100) # schedule monthly interval 10</pre>	
Related Commands	show jobs	
Notes	A schedule type is essentially a structure for specifying one or more future dates and times for a job to execute.	

show jobs

	show jobs [<job-id>] Displays configuration and state (including results of last execution, if any exist) of all jobs, or of one job if a job ID is specified.	
Syntax Description	job-id	Job ID
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # show jobs 10 Job 10: Status: inactive Enabled: yes Continue on failure: no Schedule Type: once Time and date: 1970/01/01 00:00:00 +0000 Last Exec Time: Thu 2012/04/05 13:11:42 +0000 Next Exec Time: N/A Commands: Command 10: show power Last Output: ===== Module Status ===== PS1 OK PS2 NOT PRESENT </pre>	
Related Commands		
Notes		

Event Notification

email autosupport

	email autosupport {enable event <event-name>} no email autosupport enable Enables the support of the email notification and specifies which events will be sent as email notifications. The no form of the command disables sending of email notifications globally or per event.	
Syntax Description	enable	Enables the sending of email to vendor autosupport when certain failures occur
	event	Specifies events for which to send autosupport notification emails
Default	Email autosupport is disabled	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # email autosupport enable</pre>	
Related Commands	show email	
Notes	Refer to "show email event" for the full event list	

email dead-letter

	email dead-letter {cleanup max-age <duration> enable} no email dead-letter Configures settings for saving undeliverable emails. The no form of the command disables sending of emails to vendor auto-support upon certain failures.	
Syntax Description	cleanup max-age	Example: “5d4h3m2s” for 5 days, 4 hours, 3 minutes, 2 seconds
	enable	Saves dead-letter files for undeliverable emails
Default	Save dead letter is enabled The default duration is 14 days	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # email dead-letter enable</pre>	
Related Commands	show email	
Notes		

email domain

	email domain <hostname-or-ip-address> no email domain Sets the domain name from which the emails will appear to come from (provided that the return address is not already fully-qualified). This is used in conjunction with the system hostname to form the full name of the host from which the email appears to come. The no form of the command clears email domain override.	
--	---	--

Syntax Description	hostname-or-ip-address	Hostname or IP address
Default	No email domain	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # email domain mellanox</pre>	
Related Commands	show email	
Notes		

email mailhub

	<p>email mailhub <hostname-or-ip-address> no email mailhub</p> <p>Sets the mail relay to be used to send notification emails. The no form of the command clears the mail relay to be used to send notification emails.</p>	
Syntax Description	hostname-or-ip-address	Hostname or IP address
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # email mailhub 10.0.8.11</pre>	
Related Commands	show email [events]	
Notes		

email mailhub-port

	email mailhub-port <port> no email mailhub-port Sets the mail relay port to be used to send notification emails. The no form of the command resets the port to its default.	
Syntax Description	port	Port number
Default	25	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # email mailhub-port 125</pre>	
Related Commands	show email	
Notes		

email notify event

	email notify event <event-name> no email notify event <event-name> Enables sending email notifications for the specified event type. The no form of the command disables sending email notifications for the specified event type.	
Syntax Description	event-name	Example event names would include "process-crash" and "cpu-util-high"
Default	No events are enabled	
Configuration Mode	config	

History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # email notify event process-crash</pre>
Related Commands	show email events
Notes	This does not affect auto-support emails. Auto-support can be disabled overall, but if it is enabled, all auto-support events are sent as emails.

email notify recipient

	<p>email notify recipient <email-addr> [class {info failure} detail] no email notify recipient <email-addr> [class {info failure} detail]</p> <p>Adds an email address from the list of addresses to which to send email notifications of events. The no form of the command removes an email address from the list of addresses to which to send email notifications of events.</p>	
Syntax Description	email-addr	Example event names would include "process-crash" and "cpu-util-high"
	class	Specifies which types of events are sent to this recipient
	info	Sends informational events to this recipient
	failure	Sends failure events to this recipient
	detail	Sends detailed event emails to this recipient
Default	No recipients are added	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # email notify recipient user2@autosupport.mellanox.com</pre>	

Related Commands	show email
Notes	

email return-addr

	<p>email return-addr <username> no email domain</p> <p>Sets the username or fully-qualified return address from which email notifications are sent.</p> <ul style="list-style-type: none"> • If the string provided contains an “@” character, it is considered to be fully-qualified and used as-is. • Otherwise, it is considered to be just the username, and we append “@<hostname>.<domain>”. The default is “do-not-reply”, but this can be changed to “admin” or whatnot in case something along the line does not like fictitious addresses. <p>The no form of the command resets this attribute to its default.</p>	
Syntax Description	username	Username
Default	do-not-reply	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # email return-addr user1</pre>	
Related Commands	show email	
Notes		

email return-host

	email return-host no email return-host Includes the hostname in the return address for emails. The no form of the command does not include the hostname in the return address for emails.
Syntax Description	N/A
Default	No return host
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # no email return-host</pre>
Related Commands	show email
Notes	This only takes effect if the return address does not contain an "@" character.

email send-test

	email send-test Sends test-email to all configured event and failure recipients.
Syntax Description	N/A
Default	No return host
Configuration Mode	config
History	1.5

Example	<pre>ufmapl [mgmt-sa] (config) # email autosupport enable</pre>
Related Commands	show email [events]
Notes	

show email

	show email [events] Shows email configuration or events for which email should be sent upon.	
Syntax Description	events	Displays event list
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # show email Mail hub: Mail hub port: 25 Domain override: Return address: do-not-reply Include hostname in return address: yes Current reply address: host@localdomain Security mode: tls-none Verify server cert: yes Supplemental CA list: default-ca-list Dead letter settings:</pre>	

	<pre> Save dead.letter files: yes Dead letter max age: 14 days Email notification recipients: No recipients configured. Autosupport emails Enabled: no Recipient: autosupport@autosupport.mellanox.com Mail hub: autosupport.mellanox.com Security mode: tls-none Verify server cert: yes Supplemental CA list: default-ca-list </pre>
Related Commands	
Notes	

Statistics and Alarms

stats alarm clear

	<pre>stats alarm <alarm-id> clear</pre> <p>Clears alarm state.</p>	
Syntax Description	alarm-id	<p>Alarms supported by the system, for example:</p> <ul style="list-style-type: none"> • cpu_util_indiv - average CPU utilization too high: percent utilization • disk_io - operating system disk I/O per second too high: kilobytes per second • fs_mnt - free filesystem space too low: percent of disk space free • intf_util - network utilization too high: bytes per second • memory_pct_used - too much memory in use: percent of physical memory used • paging - paging activity too high: page faults • temperature - temperature is too high: degrees
Default	N/A	

Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # stats alarm cpu_util_indiv clear</pre>
Related Commands	show stats alarm
Notes	

stats alarm enable

	<pre>stats alarm <alarm-id> enable no stats alarm <alarm-id> enable</pre> <p>Enables the alarm. The no form of the command disables the alarm. Notifications will not be received.</p>	
Syntax Description	alarm-id	<p>Alarms supported by the system, for example:</p> <ul style="list-style-type: none"> • cpu_util_indiv - average CPU utilization too high: percent utilization • disk_io - operating system disk I/O per second too high: kilobytes per second • fs_mnt - free filesystem space too low: percent of disk space free • intf_util - network utilization too high: bytes per second • memory_pct_used - too much memory in use: percent of physical memory used • paging - paging activity too high: page faults • temperature - temperature is too high: degrees
Default	The default is different per alarm ID	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # stats alarm cpu_util_indiv enable</pre>	

Related Commands	show stats alarm
Notes	

stats alarm event-repeat

	<pre>stats alarm <alarm-id> event-repeat {single while-not-cleared} no stats alarm <alarm-id> event-repeat</pre> <p>Configures repetition of events from this alarm.</p>	
Syntax Description	alarm-id	<p>Alarms supported by the system, for example:</p> <ul style="list-style-type: none"> • cpu_util_indiv - average CPU utilization too high: percent utilization • disk_io - operating system disk I/O per second too high: kilobytes per second • fs_mnt - free filesystem space too low: percent of disk space free • intf_util - network utilization too high: bytes per second • memory_pct_used - too much memory in use: percent of physical memory used • paging - paging activity too high: page faults • temperature - temperature is too high: degrees
	single	Does not repeat events: only sends one event whenever the alarm changes state
	while-not-cleared	Repeats error events until the alarm clears
Default	Single	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # stats alarm cpu_util_indiv event-repeat single</pre>	
Related Commands	show stats alarm	
Notes		

stats alarm {rising | falling}

	stats alarm <alarm-id> {rising falling} {clear-threshold error-threshold} <threshold-value> Configure alarms thresholds.	
Syntax Description	alarm-id	Alarms supported by the system, for example: <ul style="list-style-type: none"> • cpu_util_indiv - average CPU utilization too high: percent utilization • disk_io - operating system disk I/O per second too high: kilobytes per second • fs_mnt - free filesystem space too low: percent of disk space free • intf_util - network utilization too high: bytes per second • memory_pct_used - too much memory in use: percent of physical memory used • paging - paging activity too high: page faults • temperature - temperature is too high: degrees
	rising	Configures alarm for when the statistic rises too high
	falling	Configures alarm for when the statistic falls too low
	error-threshold	Sets threshold to trigger falling or rising alarm
	clear-threshold	Sets threshold to clear falling or rising alarm
	threshold-value	Threshold value, different per alarm
Default	Default is different per alarm ID	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # stats alarm cpu_util_indiv falling clear- threshold 10</pre>	
Related Commands	show stats alarm	
Notes	Not all alarms support all four thresholds.	

stats alarm rate-limit

	<code>stats alarm <alarm-id> rate-limit {count <count-type> <count> reset window <window-type> <duration>}</code> Configures alarms rate limit.	
Syntax Description	alarm-id	Alarms supported by the system, for example: <ul style="list-style-type: none"> • cpu_util_indiv - average CPU utilization too high: percent utilization • disk_io - operating system disk I/O per second too high: kilobytes per second • fs_mnt - free filesystem space too low: percent of disk space free • intf_util - network utilization too high: bytes per second • memory_pct_used - too much memory in use: percent of physical memory used • paging - paging activity too high: page faults • temperature - temperature is too high: degrees
	count-type	Long medium, or short count (number of alarms)
	reset	Set the count and window durations to default values for this alarm
	window-type	Long medium, or short count, in seconds
Default	Short window: 5 alarms in 1 hour Medium window: 20 alarms in 1 day Long window: 50 alarms in 7 days	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-sa] (config) # stats alarm paging rate-limit window long 2000</pre>	
Related Commands	show stats alarm	
Notes		

stats chd clear

	<p>stats chd <chd-id> clear</p> <p>Clears CHD counters.</p>	
Syntax Description	chd-id	<p>CHD supported by the system, for example:</p> <ul style="list-style-type: none"> • cpu_util - CPU utilization: percentage of time spent • cpu_util_ave - CPU utilization average: percentage of time spent • cpu_util_day - CPU utilization average: percentage of time spent • disk_device_io_hour - storage device I/O read/write statistics for the last hour: bytes • disk_io - operating system aggregate disk I/O average: KB/sec • eth_day • eth_hour • fs_mnt_day - filesystem system usage average: bytes • fs_mnt_month - filesystem system usage average: bytes • fs_mnt_week - filesystem system usage average: bytes • ib_day • ib_hour • intf_day - network interface statistics aggregation: bytes • intf_hour - network interface statistics (same as "interface" sample) • intf_util - aggregate network utilization across all interfaces • memory_day - average physical memory usage: bytes • memory_pct - average physical memory usage • paging - paging activity: page faults • paging_day - paging activity: page faults
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # stats chd memory_day clear</pre>	
Related Commands	show stats chd	

Notes	
-------	--

stats chd enable

	stats chd <chd-id> enable no stats chd <chd-id> enable Enables the CHD. The no form of the command disables the CHD.	
Syntax Description	chd-id	CHD supported by the system, for example: <ul style="list-style-type: none"> • cpu_util - CPU utilization: percentage of time spent • cpu_util_ave - CPU utilization average: percentage of time spent • cpu_util_day - CPU utilization average: percentage of time spent • disk_device_io_hour - storage device I/O read/write statistics for the last hour: bytes • disk_io - operating system aggregate disk I/O average: KB/sec • eth_day • eth_hour • fs_mnt_day - filesystem system usage average: bytes • fs_mnt_month - filesystem system usage average: bytes • fs_mnt_week - filesystem system usage average: bytes • ib_day • ib_hour • intf_day - network interface statistics aggregation: bytes • intf_hour - network interface statistics (same as “interface” sample) • intf_util - aggregate network utilization across all interfaces • memory_day - average physical memory usage: bytes • memory_pct - average physical memory usage • paging - paging activity: page faults • paging_day - paging activity: page faults
Default	Enabled	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # stats chd memory_day enable</pre>
Related Commands	show stats chd
Notes	

stats chd compute time

	<p>stats chd <chd-id> compute time {interval range} <time></p> <p>Sets parameters for when this CHD is computed.</p>	
Syntax Description	chd-id	<p>CHD supported by the system, for example:</p> <ul style="list-style-type: none"> • cpu_util - CPU utilization: percentage of time spent • cpu_util_ave - CPU utilization average: percentage of time spent • cpu_util_day - CPU utilization average: percentage of time spent • disk_device_io_hour - storage device I/O read/write statistics for the last hour: bytes • disk_io - operating system aggregate disk I/O average: KB/sec • eth_day • eth_hour • fs_mnt_day - filesystem system usage average: bytes • fs_mnt_month - filesystem system usage average: bytes • fs_mnt_week - filesystem system usage average: bytes • ib_day • ib_hour • intf_day - network interface statistics aggregation: bytes • intf_hour - network interface statistics (same as "interface" sample) • intf_util - aggregate network utilization across all interfaces • memory_day - average physical memory usage: bytes • memory_pct - average physical memory usage • paging - paging activity: page faults • paging_day - paging activity: page faults
	interval	Specifies calculation interval (how often to do a new calculation) in number of seconds

	range	Specifies calculation range, in number of seconds
	time	Number of seconds
Default	Different per CHD	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # stats chd memory_day compute time interval 120</pre>	
Related Commands	show stats chd	
Notes		

stats sample clear

	stats sample <sample-id> clear Clears sample history.	
Syntax Description	sample-id	Possible sample IDs are: <ul style="list-style-type: none"> • congested • cpu_util - CPU utilization: milliseconds of time spent • disk_device_io - storage device I/O statistics • disk_io - operating system aggregate disk I/O: KB/sec • eth • fan - fan speed • fs_mnt_bytes - filesystem usage: bytes • fs_mnt_inodes - filesystem usage: inodes • ib • interface - network interface statistics • intf_util - network interface utilization: bytes • memory - system memory utilization: bytes • paging - paging activity: page faults

		<ul style="list-style-type: none"> • power - power supply usage • power-consumption • temperature - modules temperature
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # stats sample temperature clear</pre>	
Related Commands	show stats sample	
Notes		

stats sample enable

	<pre>stats sample <sample-id> enable no states sample <sample-id> enable</pre> <p>Enables the sample. The no form of the command disables the sample.</p>	
Syntax Description	sample-id	<p>Possible sample IDs are:</p> <ul style="list-style-type: none"> • congested • cpu_util - CPU utilization: milliseconds of time spent • disk_device_io - storage device I/O statistics • disk_io - operating system aggregate disk I/O: KB/sec • eth • fan - fan speed • fs_mnt_bytes - filesystem usage: bytes • fs_mnt_inodes - filesystem usage: inodes • ib • interface - network interface statistics • intf_util - network interface utilization: bytes

		<ul style="list-style-type: none"> • memory - system memory utilization: bytes • paging - paging activity: page faults • power - power supply usage • power-consumption • temperature - modules temperature
Default	Enabled	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # stats sample temperature enable</pre>	
Related Commands	show stats sample	
Notes		

stats sample interval

	<p>stats sample <sample-id> interval <time></p> <p>Sets the amount of time between samples for the specified group of sample data.</p>	
Syntax Description	sample-id	<p>Possible sample IDs are:</p> <ul style="list-style-type: none"> • congested • cpu_util - CPU utilization: milliseconds of time spent • disk_device_io - storage device I/O statistics • disk_io - operating system aggregate disk I/O: KB/sec • eth • fan - fan speed • fs_mnt_bytes - filesystem usage: bytes • fs_mnt_inodes - filesystem usage: inodes • ib • interface - network interface statistics • intf_util - network interface utilization: bytes

		<ul style="list-style-type: none"> • memory - system memory utilization: bytes • paging - paging activity: page faults • power - power supply usage • power-consumption • temperature - modules temperature
	time	Number of seconds
Default	Different per sample	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # stats sample temperature interval 1</pre>	
Related Commands	show stats sample	
Notes		

stats clear-all

	<p>stats clear all</p> <p>Clears data for all samples, CHDs, and status for all alarms.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # stats clear-all</pre>

Related Commands	show stats sample
Notes	

stats export

	<code>stats export <format> <report-name> [{after before} <yyyy/mm/dd> <hh:mm:ss>] [filename <filename>]</code> Exports statistics to a file.	
Syntax Description	format	Currently the only supported value for <format> is "csv" (comma-separated value)
	report-name	Determines dataset to be exported. Possible report names are: <ul style="list-style-type: none"> • memory - memory utilization • paging - paging I/O • cpu_util - CPU utilization
	after before	Only includes stats collected after or before a specific time
	yyyy/mm/dd	Date must be between 1970/01/01 and 2038/01/19
	hh:mm:ss	Time must be between 00:00:00 and 03:14:07 UTC and is treated as local time
	filename	Specifies filename to give new report. If a filename is specified, the stats will be exported to a file of that name; otherwise a name will be chosen automatically and will contain the name of the report and the time and date of the export. Any automatically-chosen name will be given a .csv extension.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # stats export csv memory filename mellanoxexample before 2000/08/14 15:59:50 after 2000/08/14 15:01:50 Generated report file: mellanoxexample.csv </pre>	

Related Commands	show files stats
Notes	

show stats alarm

	show stats alarm [<alarm-id> [rate-limit]] Displays status of all alarms or the specified alarm.	
Syntax Description	alarm-id	<ul style="list-style-type: none"> • cpu_util_indiv - average CPU utilization too high: percent utilization • disk_io - operating system disk I/O per second too high: kilobytes per second • fs_mnt - free filesystem space too low: percent of disk space free • intf_util - network utilization too high: bytes per second • memory_pct_used - too much memory in use: percent of physical memory used • paging - paging activity too high: page faults • temperature - temperature is too high: degrees
	rate-limit	Displays rate limit parameters
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre> ufmapl [mgmt-sa] (config) # show stats alarm Alarm cpu_util_indiv (Average CPU utilization too high): ok Alarm disk_io (Operating System Disk I/O per second too high): (disabled) Alarm fs_mnt (Free filesystem space too low): ok Alarm intf_util (Network utilization too high): (disabled) Alarm memory_pct_used (Too much memory in use): (disabled) Alarm paging (Paging activity too high): ok Alarm temperature (Temperature is too high): ok </pre>	

Related Commands	stats alarm
Notes	

show stats chd

	<p>show stats chd [<chd-id>]</p> <p>Displays configuration of all statistics CHDs.</p>	
Syntax Description	chd-id	<ul style="list-style-type: none"> • cpu_util - CPU utilization: percentage of time spent • cpu_util_ave - CPU utilization average: percentage of time spent • cpu_util_day - CPU utilization average: percentage of time spent • disk_device_io_hour - storage device I/O read/write statistics for the last hour: bytes • disk_io - operating system aggregate disk I/O average: KB/sec • eth_day • eth_hour • fs_mnt_day - filesystem system usage average: bytes • fs_mnt_month - filesystem system usage average: bytes • fs_mnt_week - filesystem system usage average: bytes • ib_day • ib_hour • intf_day - network interface statistics aggregation: bytes • intf_hour - network interface statistics (same as "interface" sample) • intf_util - aggregate network utilization across all interfaces • memory_day - average physical memory usage: bytes • memory_pct - average physical memory usage • paging - paging activity: page faults • paging_day - paging activity: page faults
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	

Example	<pre>ufmap1 [mgmt-sa] (config) # show stats chd disk_device_io_hour CHD "disk_device_io_hour" (Storage device I/O read/write statistics for the last hour: bytes): Enabled: yes Source dataset: sample "disk_device_io" Computation basis: data points Interval: 1 data point(s) Range: 1 data point(s)</pre>
Related Commands	stats chd
Notes	

show stats cpu

	<pre>show stats cpu</pre> <p>Displays some basic stats about CPU utilization:</p> <ul style="list-style-type: none"> • the current level • the peak over the past hour • the average over the past hour
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmap1 [mgmt-sa] (config) # show stats cpu</pre>

	<pre> CPU 0 Utilization: 6% Peak Utilization Last Hour: 16% at 2012/02/28 08:47:32 Avg. Utilization Last Hour: 8% </pre>
Related Commands	
Notes	

show stats sample

	<pre>show stats sample [<sample-id>]</pre> <p>Displays sampling interval for all samples, or the specified one.</p>	
Syntax Description	sample-id	<ul style="list-style-type: none"> • congested • cpu_util - CPU utilization: milliseconds of time spent • disk_device_io - storage device I/O statistics • disk_io - operating system aggregate disk I/O: KB/sec • eth • fan - fan speed • fs_mnt_bytes - filesystem usage: bytes • fs_mnt_inodes - filesystem usage: inodes • ib • interface - network interface statistics • intf_util - network interface utilization: bytes • memory - system memory utilization: bytes • paging - paging activity: page faults • power - power supply usage • power-consumption • temperature - modules temperature
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # show stats sample fan Sample "fan" (Fan speed): Enabled: yes Sampling interval: 1 minute 11 seconds</pre>
Related Commands	stats sample
Notes	

Chassis Management

show version

	show version [concise] Displays version information for the currently running system image.	
Syntax Description	concise	Fits output onto one line
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # show version Product name: ufm_appliance Product release: UFMAPL_1.5.0.14_UFM_4.0.0.19 Build ID: #1-dev Build date: 2013-03-03 16:39:17 Target arch: x86_64</pre>	

	<pre> Target hw: x86_64 Built by: root@r-build01 Version summary: ufm_appliance UFMAPL_1.5.0.14_UFM_4.0.0.19 2013-03-03 16:39:17 x86_64 Product model: x86 Host ID: c194d089f00c System serial num: F6qnuuhLcxjG System UUID: 435a85f4-22cc-e111-a4eb-001e6754a51b Uptime: 1d 1h 48m 43.424s CPU load averages: 0.00 / 0.00 / 0.00 Number of CPUs: 24 System memory: 1441 MB used / 30700 MB free / 32141 MB total Swap: 0 MB used / 1506 MB free / 1506 MB total </pre>
Related Commands	
Notes	

show inventory

	<pre> show inventory Displays system inventory. </pre>	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
	4.3.0	Updated output

<p>Example</p>	<pre> ufmapl [mgmt-sa] (config) # show inventory Inventory refresh. Please wait... ===== Module Type Part number Serial Number ===== BOARD S2600GZ G11481-352 QSGR22800436 PS1 DPS-750XB A MUA90-PF E98791D1229075650 PS2 DPS-750XB A MUA90-PF E98791D1229075651 DRIVE1 SATA (931.012 GB) MUA90-HD WD- WCAW33617160WDC DRIVE2 SATA (931.012 GB) MUA90-HD WD- WCAW34670985WDC HCA ConnectX-6 MCX653106A-HDAT MT1234U01297 </pre>
<p>Related Commands</p>	
<p>Notes</p>	

show chassis health

	<p>show chassis health</p> <p>Displays chassis health status.</p>
<p>Syntax Description</p>	<p>N/A</p>
<p>Default</p>	<p>N/A</p>
<p>Configuration Mode</p>	<p>Any configuration mode</p>

History	1.6
Example	<pre>ufmapl [mgmt-sa] (config) # show inventory Inventory refresh. Please wait... ===== Module Type Part number Serial Number ===== BOARD S2600GZ G11481-352 QSGR22800436 PS1 DPS-750XB A MUA90-PF E98791D1229075650 PS2 DPS-750XB A MUA90-PF E98791D1229075651 DRIVE1 SATA (931.012 GB) MUA90-HD WD-WCAW33617160WDC DRIVE2 SATA (931.012 GB) MUA90-HD WD-WCAW34670985WDC HCA ConnectX-6 MCX653106A-HDAT MT1234U01297</pre>
Related Commands	
Notes	

show memory

	<p>show memory</p> <p>Displays memory status.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show memory Total Used Free Used+B/C Free-B/C</pre>

	<pre> Physical 2027 MB 761 MB 1266 MB 1214 MB 813 MB Swap 0 MB 0 MB 0 MB Physical Memory Borrowed for System Buffers and Cache: Buffers: 0 MB Cache: 452 MB Total Buffers/Cache: 452 MB </pre>
Related Commands	
Notes	

show chassis input power

	<pre> show chassis input power Displays chassis input power information. </pre>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre> ufmapl [mgmt-sa] (config) # show chassis input power Refreshing input power information. Please wait... Input Power Supply 1 0 Watts Input Power Supply 2 116 Watts </pre>
Related Commands	
Notes	

chassis altitude

	chassis altitude <elevation> Updates the chassis altitude.	
Syntax Description	elevation	Possible chassis altitude values are: <ul style="list-style-type: none"> • 300: 300m or less • 900: 301m - 900m • 1500: 901m - 1500m • 3000: Higher than 1500m
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # chassis altitude 300</pre>	
Related Commands		
Notes		

chassis remote-management dhcp

	chassis remote-management dhcp Updates chassis remote-management interface to DHCP
Syntax Description	N/A
Default	N/A

Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # chassis remote-management dhcp</pre>
Related Commands	
Notes	

chassis remote-management ip

	<p>chassis remote-management ip {address <ip> <netmask> default-gateway <ipv4-address>}</p> <p>Updates chassis remote-management IP address.</p>	
Syntax Description	address	Configures IP address and netmask for remote-management
	default-gateway	Configures a default route for chassis remote management
Default	N/A	
Configuration Mode	config	
History	1.5	
	4.5.0	Added "default-gateway" parameter
Example	<pre>ufmapl [mgmt-sa] (config) # chassis remote-management up address 10.10.10.10 /30</pre>	
Related Commands		
Notes		

chassis remote-management ipv6

	<p>chassis remote-management ipv6 [enable dhcp autoconfig address <ipv6-address> <prefix len 0-128> default-gateway <ipv6-address>]</p> <p>Updates IPv6 support for chassis remote management.</p>	
Syntax Description	enable	Enables IPv6 support for chassis remote management interface
	dhcp	Sets the chassis remote management interface from which non-interface-specific (resolver) configuration is accepted via DHCPv6
	autoconfig	Enables IPv6 stateless address auto configuration (SLAAC) for the chassis remote management interface
	address	Configures a static IPv6 address and prefix length
	default-gateway	Sets a static default gateway for the chassis remote management interface
Default	N/A	
Configuration Mode	config	
History	4.1.0	
Example	<pre>ufmapl [mgmt-sa] (config) # chassis remote-management ipv6 dhcp</pre>	
Related Commands	show chassis remote-management ip	
Notes		

chassis remote-management username

	<code>chassis remote-management username <username> <password></code> Configures the remote-management username and password.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmap1 [mgmt-sa] (config) # chassis remote-management username ufm-test Str0nGP4sS</pre>
Related Commands	
Notes	

show chassis firmware

	<code>show chassis firmware</code> Displays the BIOS package information.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5

Example	<pre>ufmapl [mgmt-sa] (config) # show chassis firmware Running chassis image: SE5C600.86B.01.06.0002</pre>
Related Commands	
Notes	

show chassis remote-management

	<pre>show chassis remote-management {ip username}</pre> <p>Shows the remote management IP address and username.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # show chassis remote-management ip LAN Configuration Settings: ----- LAN Channel Selected: 3 LAN Alert Destination Index Selected: None. LAN Alert Configuration will not be displayed. IP Address Source: DHCP DHCP Host Name: UFMAPL-00:1E:67:49:CF:BD LAN Failover Mode: DISABLE BMC Host IP Address: 172.30.11.214 Subnet Mask: 255.255.0.0</pre>

	<pre> Gateway IP Address: 172.30.0.1 Gateway MAC Address: 00-00-00-00-00-00 Backup Gateway IP Address: 0.0.0.0 Backup Gateway MAC Address: 00-00-00-00-00-00 Community String: public Gratuitous ARP Enable: DISABLE Gratuitous ARP Interval (milliseconds): 0 BMC ARP Response Enable: ENABLE IPV6 Configuration Settings: ----- IPV6 Status: DISABLE IPV6 IP Address Source: STATIC IPV6 Prefix Length: 64 IPV6 IP Address: 000:000:000:000:000:000:000:000 IPV6 Default Gateway: 000:000:000:000:000:000:000:000 </pre>
Related Commands	chassis remote-management
Notes	

show chassis altitude

	<pre> show chassis altitude Displays chassis altitude setup. </pre>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmapl [mgmt-sa] (config) # show chassis altitude </pre>

	<pre> Altitude ===== Current Value : 301m - 900m ----- Possible Values ----- 300 : 300m or less 900 : 301m - 900m 1500 : 901m - 1500m 3000 : Higher than 1500m </pre>
Related Commands	chassis altitude
Notes	

show chassis raid

	<pre> show chassis raid Displays the status of the RAID configuration. </pre>	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
	4.3	Updated output
Example	<pre> ufmap1 [mgmt-sa] (config) # show chassis raid RAID state: Optimal DRIVE1 state: Online,SpunUp DRIVE2 state: Online,SpunUp </pre>	

Related Commands	
Notes	

show chassis raid rebuild-status

	show chassis raid rebuild-status [drive1 drive2] Displays the status of “rebuilding” process for the selected drive.	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.5	
	4.3	Updated “HDD” to “drive”
Example	<pre> ufmap1 [mgmt-sa] (config) # show chassis rebuild-status drive1 Rebuild progress of physical drivers.... Enclosure: Slot Percent Complete Time Elps --:00 #*****35%***** Press <ESC> key to quit.... </pre>	
Related Commands		
Notes		

Cryptography (X.509, IPSec)

crypto ipsec ike

	crypto ipsec ike {clear sa [peer {any <ipv4v6-address>} local <ip-address>] restart} Manage the IKE (ISAKMP) process or database state.	
Syntax Description	clear	Clears IKE (ISAKMP) peering state
	sa	Clears IKE generated ISAKMP and IPSec security associations (remote peers are affected)
	peer	Clears security associations for the specified IKE peer (remote peers are affected). <ul style="list-style-type: none"> all - clears security associations for all IKE peerings with a specific local address (remote peers are affected) IPv4 or IPv6 address - clears security associations for specific IKE peering with a specific local address (remote peers are affected)
	local	Clear security associations for the specified/all IKE peering (remote peer is affected)
	restart	Restarts the IKE (ISAKMP) daemon (clears all IKE state, peers may be affected)
Default	N/A	
Configuration Mode	config	
History	1.1.0	
Example	<pre>ufmap1 [mgmt-sa] (config) # crypto ipsec ike restart</pre>	
Related Commands		
Notes		

crypto ipsec peer local

	<pre>crypto ipsec peer <ipv4v6-address> local <ipv4v6-address> {enable keying {ike [auth {hmac-md5 hmac-sha1 hmac-sha256 null} dh-group disable encrypt exchange-mode lifetime local-identity mode peer-identity pfs-group preshared-key prompt-preshared-key transform-set] manual [auth disable encrypt local-spi mode remote-spi]}}</pre> <p>Configures ipsec in the system.</p>	
Syntax Description	enable	Enables IPsec peering
	ike	<p>Configures IPsec peering using IKE ISAKMP to manage SA keys.</p> <ul style="list-style-type: none"> • auth - configures the authentication algorithm for IPsec peering • dh-group - configures the phase1 Diffie-Hellman group proposed for secure IKE key exchange • disable - configures this IPsec peering administratively disabled • encrypt - configures the encryption algorithm for IPsec peering • exchange-mode - configures the IKE key exchange mode to propose for peering • lifetime - configures the SA lifetime to propose for this IPsec peering • local-identity - configures the ISAKMP payload identification value to send as local endpoint's identity • mode - configures the peering mode for this IPsec peering • peer-identity - configures the identification value to match against the peer's ISAKMP payload identification • pfs-group - configures the phase2 PFS (Perfect Forward Secrecy) group to propose for Diffie-Hellman exchange for this IPsec peering • preshared-key - configures the IKE pre-shared key for the IPsec peering • prompt-preshared-key - prompts for the pre-shared key, rather than entering it on the command line • transform-set - configures transform proposal parameters
	keying	<p>Configures key management for this IPsec peering:</p> <ul style="list-style-type: none"> • auth - configures the authentication algorithm for this IPsec peering • disable - configures this IPsec peering administratively disabled

		<ul style="list-style-type: none"> • encrypt - configures the encryption algorithm for this IPSec peering • local-spi - configures the local SPI for this manual IPSec peering • mode - configures the peering mode for this IPSec peering • remote-spi - configures the remote SPI for this manual IPSec peering
	manual	Configures IPSec peering using manual keys
Default	N/A	
Configuration Mode	config	
History	1.1.0	
Example	<pre>ufmap1 [mgmt-sa] (config) # crypto ipsec peer 10.10.10.10 local 10.7.34.139 enable</pre>	
Related Commands		
Notes		

crypto certificate ca-list

	<pre>crypto certificate ca-list [default-ca-list {name {<CA list name> system-self-signed}}] no crypto certificate ca-list [default-ca-list {name {<cert-name> system-self-signed}}]</pre> <p>Adds the specified CA certificate to the default CA certificate list. The no form of the command removes the certificate from the default CA certificate list.</p>	
Syntax Description	cert-name	Name of the certificate
Default	N/A	
Configuration Mode	config	
History	1.1.0	

Example	<pre>ufmapl [mgmt-sa] (config) # crypto certificate ca-list default-ca-list name test</pre>
Related Commands	
Notes	<ul style="list-style-type: none"> • Two certificates with the same subject and issuer fields cannot both be placed onto the CA list • The no form of the command does not delete the certificate from the certificate database • Unless specified otherwise, applications that use CA certificates will still consult the well-known certificate bundle before looking at the default-ca-list

crypto certificate default-cert

	<pre>crypto certificate default-cert [{name {<cert-name> system-self-signed}}] no crypto certificate default-cert [{name {<cert-name> system-self-signed}}</pre> <p>Designates the named certificate as the global default certificate role for authentication of this system to clients. The no form of the command reverts the default-cert name to "system-self-signed" (the "cert-name" value is optional and ignored).</p>	
Syntax Description	cert-name	Name of the certificate
Default	N/A	
Configuration Mode	config	
History	1.1.0	
Example	<pre>ufmapl [mgmt-sa] (config) # crypto certificate default-cert name test</pre>	
Related Commands		
Notes	<ul style="list-style-type: none"> • A certificate must already be defined before it can be configured in the default-cert role 	

- If the named default-cert is deleted from the database, the default-cert automatically becomes reconfigured to the factory default, the "system-self-signed" certificate

crypto certificate generation

	crypto certificate generation {default {country-code days-valid email-addr key-size-bits locality org-unit organization state-or-prov}}	
	Configures default values for certificate generation.	
Syntax Description	country-code	Configures the default certificate value for country code with a two-alphanumeric-character code or - for none
	days-valid	Configures the default certificate valid days. Default: 365 days.
	email-addr	Configures the default certificate value for email address
	key-size-bits	Configures the default certificate value for private key size. (Private key length in bits - at least 1024, but 2048 is strongly recommended.)
	locality	Configures the default certificate value for locality
	org-unit	Configures the default certificate value for organizational unit
	organization	Configures the default certificate value for the organization name
	state-or-prov	Configures the default certificate value for state or province
Default	N/A	
Configuration Mode	config	
History	1.1.0	
Example	<pre>ufmapl [mgmt-sa] (config) # crypto certificate generation default days-valid</pre>	
Related Commands		
Notes		

crypto certificate name

	<p>crypto certificate name {<name> system-self-signed} {comment <new comment> generate self-signed [comment <cert-comment> common-name <domain> country-code <code> days-valid <days> email-addr <address> key-size-bits <bits> locality <name> org-unit <name> organization <name> serial-num <number> state-or-prov <name>]} private-key pem <PEM string> prompt-private-key public-cert [comment <comment string> pem <PEM string>] regenerate days-valid <days> rename <new name>} no crypto certificate name <cert-name></p> <p>Configures default values for certificate generation. The no form of the command clears/deletes certain certificate settings.</p>		
Syntax Description	cert-name	Unique name by which the certificate is identified	
	comment	Specifies a certificate comment	
	generate self-signed	Generates certificates. This option has the following parameters which may be entered sequentially in any order: <ul style="list-style-type: none"> • comment - specifies a certificate comment (free string) • common-name- specifies the common name of the issuer and subject (e.g. a domain name) • country-code - specifies the country codwo-alphanumeric-character country code, or “-” for none) • days-valid - specifies the number of days the certificate is valid • email-addr - specifies the email address • key-size-bits - specifies the size of the private key in bits (private key length in bits - at least 1024 but 2048 is strongly recommended) • locality - specifies the locality name • org-unit - specifies the organizational unit name • organization - specifies the organization name • serial-num - specifies the serial number for the certificate (a lower-case hexadecimal serial number prefixed with “0x”) • state-or-prov - specifies the state or province name 	
	private-key pem	Specifies certificate contents in PEM format	
	prompt-private-key	Prompts for certificate private key with secure echo	
	public-cert	Installs a certificate	

	regenerate	Regenerates the named certificate using configured certificate generation default values for the specified validity period
	rename	Renames the certificate
Default	N/A	
Configuration Mode	config	
History	1.1.0	
Example	<pre>ufmapl [mgmt-sa] (config) # crypto certificate name system-self-signed generate self-signed key-size-bits 2048</pre>	
Related Commands		
Notes		

crypto certificate system-self-signed

	crypto certificate system-self-signed regenerate [days-valid <days>] Configures default values for certificate generation.	
Syntax Description	days-valid	Specifies the number of days the certificate is valid
Default	N/A	
Configuration Mode	config	
History	1.1.0	
Example	<pre>ufmapl [mgmt-sa] (config) # crypto certificate system-self-signed regenerate days-valid 3</pre>	

Related Commands	
Notes	

show crypto certificate

	show crypto certificate [detail public-pem default-cert [detail public-pem] [name <cert-name> [detail public-pem] ca-list [default-ca-list]] Displays information about all certificates in the certificate database.	
Syntax Description	ca-list	Specifies the number of days the certificate is valid
	default-ca-list	Displays information about the currently configured default certificates of the CA list
	default-cert	Displays information about the currently configured default certificate
	detail	Displays all attributes related to the certificate
	name	Displays information about the certificate specified
	public-pem	Displays the uninterpreted public certificate as a PEM formatted data string
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.1.0	
Example	<pre> ufmapl [mgmt-sa] (config) # show crypto certificate Certificate with name 'system-self-signed' (default-cert) Comment: system-generated self-signed certificate Private Key: present Serial Number: 0x546c935511bcafc21ac0e8249fbe0844 SHA-1 Fingerprint: fe6df38dd26801971cb2d44f62dbe492b6063c5f Validity: Starts: 2012/12/02 13:45:05 </pre>	

	<pre> Expires: 2013/12/02 13:45:05 Subject: Common Name: IBM-DEV-Bay4 Country: IS State or Province: Locality: Organization: Organizational Unit: E-mail Address: Issuer: Common Name: IBM-DEV-Bay4 Country: IS State or Province: Locality: Organization: Organizational Unit: E-mail Address: </pre>
Related Commands	
Notes	

show crypto ipsec

	<pre> show crypto ipsec [brief configured ike policy sa] Displays information ipsec configuration. </pre>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.1.0

Example	<pre> ufmapl [mgmt-sa] (config) # show crypto ipsec IPSec Summary ----- Crypto IKE is using pluto (Openswan) daemon. Daemon process state is stopped. No IPSec peers configured. IPSec IKE Peering State ----- Crypto IKE is using pluto (Openswan) daemon. Daemon process state is stopped. No active IPSec IKE peers. IPSec Policy State ----- No active IPSec policies. IPSec Security Association State ----- No active IPSec security associations. </pre>
Related Commands	
Notes	

Docker Container

docker

	<code>docker</code> <code>no docker</code> Enables dockers then enters docker configuration context. The no form of the command disables dockers, removes configuration, and deletes all containers and docker images.
Syntax Description	N/A
Default	N/A
Configuration Mode	<code>config</code>
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # docker ufm [mgmt-sa] (config docker) #</pre>
Related Commands	
Notes	

commit

	<code>commit <container-name> <image-name> <image-version></code> Creates a new image from a running container.	
Syntax Description	<code>container-name</code>	Name of the running container to commit (limited to 180 characters)
	<code>image-name</code>	Name of the new image to be created
	<code>image-version</code>	Version of the new image to be created
Default	N/A	
Configuration Mode	config docker	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # commit mycontainer test latest</pre>	
Related Commands	docker	
Notes		

remove image

	<code>remove image <image-name> <image-version></code> Removes an image from the Linux docker service.	
Syntax Description	<code>image-name</code>	Name of the new image to be deleted
	<code>image-version</code>	Version of the new image to be deleted
Default	N/A	

Configuration Mode	config docker
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config docker) # remove image test latest</pre>
Related Commands	docker
Notes	

exec

	<p><code>exec <container-name> <program-executable></code></p> <p>Executes a program within a running container.</p>	
Syntax Description	container-name	Name of the running container to commit (limited to 180 characters)
	program-executable	Linux command
Default	N/A	
Configuration Mode	config docker	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # exec mycontainer "ls -la"</pre>	
Related Commands	docker	
Notes		

file fetch

	<p>file fetch <url></p> <p>Download a docker file from a remote host or a USB device.</p>	
Syntax Description	url	FTP, TFTP, SCP and SFTP are supported (e.g. scp://username[:password]@hostname-or-ip/path/ filename)
Default	N/A	
Configuration Mode	config docker	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # file fetch scp://root:*****@ufm/tmp/ test.txt telemetry.1.config</pre>	
Related Commands	docker	
Notes		

image upload

	<p>image upload <filename> <upload_url></p> <p>Uploads an image file to a remote host.</p>	
Syntax Description	filename	Name of file
	upload_url	FTP, TFTP, SCP and SFTP are supported (e.g. scp:// username[:password]@hostname-or-ip/path/ filename)
Default	N/A	

Configuration Mode	config docker
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config docker) # image upload centos.img.gz scp:// username:password@10.10.10.10/var/www/html/<image_name></pre>
Related Commands	docker
Notes	

file image upload

	file image upload <filename> <upload_url> Uploads a file to a remote host.	
Syntax Description	filename	Name of file
	upload_url	FTP, TFTP, SCP and SFTP are supported (e.g. scp://username[:password]@hostname-or-ip/path/filename)
Default	N/A	
Configuration Mode	config docker	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # file image upload centos.img.gz scp://username:password@10.10.10.10/var/www/html/<image_name></pre>	
Related Commands	docker	
Notes		

label

	<code>label <label-name></code> <code>no label <label-name></code> Creates a label which can be used as a shared storage between containers. The no form of the command removes the label.	
Syntax Description	label-name	Name of label
Default	N/A	
Configuration Mode	config docker	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # label new_label</pre>	
Related Commands	docker	
Notes		

label-fetch

	<code>label-fetch <url></code> Downloads label output files from a remote host or USB device.	
Syntax Description	url	FTP, TFTP, SCP and SFTP are supported (e.g. scp://username[:password]@hostname-or-ip/path/ filename)
Default	N/A	
Configuration Mode	config docker	

History	4.3.0
Example	<pre>ufm [mgmt-sa] (config docker) # label-fetch scp://root:*****@r-ufm208/ tmp/telemetry.1.config.zip telemetry.1.config 100.0% [#####]</pre>
Related Commands	docker
Notes	

label-upload

	label-upload <url> Uploads label output files to a remote host or USB device.	
Syntax Description	url	FTP, TFTP, SCP and SFTP are supported (e.g. scp://username[:password]@hostname-or-ip/path/filename)
Default	N/A	
Configuration Mode	config docker	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # label-upload telemetry.1.config scp:// root:*****@r-ufm208/tmp</pre>	
Related Commands	docker	
Notes		

pull

	<code>pull <image-name>[:<version>]</code> Pulls a docker image from a docker repository.	
Syntax Description	<code>image-name</code>	Image name Format: Name:Version If only "Name" is provided, "version" defaults to latest
Default	N/A	
Configuration Mode	<code>config docker</code>	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # pull test Using default tag: latest latest: Pulling from library/test 45a2e645736c: Pull complete Digest: sha256:c577af3197aacedf79c5a204cd7f493c8e07ffbce7f88f7600bf19c688c38799 Status: Downloaded newer image for test:latest</pre>	
Related Commands	<code>docker</code>	
Notes		

save

	<code>save <image-name> <image-version> <filename></code> Saves an image to a TAR archive.
--	---

Syntax Description	image-name	Name of image
	image-version	Version of image
	filename	Name of file in which to save image
Default	N/A	
Configuration Mode	config docker	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # save busybox latest my_image Saving and compressing image: busybox version: latest this could take a while...</pre>	
Related Commands	docker docker load	
Notes	After the file is created, the filename gets appended a *.gz suffix.	

shutdown

	shutdown no shutdown Stops all docker containers, and deletes all non-auto containers. The no form of the command enables the docker Linux service and runs all configured auto-start containers.
Syntax Description	N/A
Default	N/A
Configuration Mode	config docker
History	4.3.0

Example	<pre>ufm [mgmt-sa] (config docker) # no shutdown</pre>
Related Commands	docker
Notes	After the file is created, the filename gets appended a *.gz suffix.

start

	<pre>start <image-name> <image-version> <container-name> <starting-point> [privileged {network events-forwarder ufm-licenses}] [cpus <max-cpu-resources>] [memory <max-memory>] [usb-mount] [label <label-name>] [cmd <command>] no start <container-name></pre> <p>Starts a new container from an image. The no form of the command stops a running docker container (and removes the container if it is not persistent).</p>	
Syntax Description	image-name	Name of the new image to start
	image-version	Version of the image to start
	container-name	Name of the running container to commit (limited to 180 characters)
	starting-point	<ul style="list-style-type: none"> init - persistent, start the container after boot, when system initialization is done now - start the container now, this is not persistent now-and-init - starts the container now and after boot, when system configuration is done
	privileged	<ul style="list-style-type: none"> network - adds network privileges to the container (--privilege flag) events-forwarder - adds required mounts to use events forwarder ufm-licenses - adds required mounts to use license file
	cpus	Sets how much of the available CPU resources a container can use (e.g. "cpus 1.5" guarantees at most one and a half of the available CPUs for the container)

	memory	Sets the maximum amount of memory the container can use in MB. The minimum amount of memory to configure is 4MB.
	usb-mount	Enables USB mount to the docker container
	label	Creates one or two labels to use as a shared storage between containers
	cmd	Executes specified command inside the docker
Default	N/A	
Configuration Mode	config docker	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config docker) # start centos latest test now Starting docker container. Please wait (this can take a minute)... switch (config) # docker start imagename latestver containername init cpus 0.2 memory 25</pre>	
Related Commands	docker	
Notes	Only one of the privileged options (i.e. events-forwarder, ufm-licenses) can be used	

show docker containers

	<pre>show docker containers <container-name></pre> <p>Displays set parameters on containers already running, and containers planned to run in the future.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode

History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # show docker containers cont_example: image : busybox version : latest status : running start point : data-path-ready cpu limit : 0.2 memory limit: 10m labels : - privileges : network, sdk usb mount : enabled another_container: image : busybox version : latest status : - start point : init cpu limit : 0.2 memory limit: 10m labels : my_label privileges : network, sdk usb mount : disabled ufm [mgmt-sa] (config) # show docker containers cont_example cont_example: image : busybox version : latest status : running start point : data-path-ready cpu limit : 0.2 memory limit: 10m labels : - privileges : network, sdk usb mount : enabled</pre>

Related Commands	
Notes	<ul style="list-style-type: none"> • If a container is already started, the status field displays its current status • If a container is configured to run on the next boot, the start point field displays when it will start • If there is a mismatch between the configuration of a running container and its next-boot configuration, two entries for the container are shown with both of the configurations

show docker images

	<p>show docker images</p> <p>Display docker images.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre> ufm [mgmt-sa] (config) # show docker images ----- Image Version Created Size ----- ubuntu latest Less than a secon 117MB d ago ubuntu-sdk v1 41 seconds ago 215MB </pre>
Related Commands	
Notes	

show docker labels

	show docker labels Displays docker labels.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # show docker labels Storage label : label_name1 configured containers list : cont_name2 active containers list : cont_name1 Storage label : label_name2</pre>
Related Commands	
Notes	

show docker ps

	show docker ps Display docker containers.
Syntax Description	N/A
Default	N/A

Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # show docker ps ----- Container Image:Version Created Status ----- my_ubuntu_app ubuntu:latest 56 seconds ago Up 50 seconds</pre>
Related Commands	
Notes	

UFM Commands

- [General](#)
- [License](#)
- [UFM Configuration Management](#)
- [Database Management](#)
- [Data Management](#)
- [High Availability](#)
- [Telemetry](#)
- [UFM Multi-site Portal](#)
- [UFM External Subnet Manager](#)
- [UFM Process Commands](#)
- [UFM Firmware Management](#)
- [UFM Running Modes](#)
- [UFM Logs](#)
- [Advanced Subnet Manager Configuration](#)
- [UFM Web Client](#)
- [Management Interface Monitoring](#)
- [AHX Monitoring](#)
- [UFM Events Forwarder](#)
- [UFM Virtualization](#)
- [UFM Agent](#)
- [Unhealthy Ports](#)
- [UFM Audit](#)
- [UFM Plugin Commands](#)
- [Fabric Discovery](#)

General

ufm start

	<code>ufm start</code> <code>no ufm start</code> Starts UFM. The no form of the command stops UFM.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) # ufm start</pre>
Related Commands	<code>show ufm status</code>
Notes	

show ufm status

	<code>show ufm status</code> Displays the status of UFM. The outcome of the command varies according to the working mode.
Syntax Description	N/A

Default	N/A	
Configuration Mode	config	
History	1.5	
	1.6	Updated output
	1.7	Updated output
	4.4.0	Updated output
	4.5.0	Updated output
	4.7.0	Updated output
Example	<pre> r-ufm237 [mgmt-ha-active] (config) # show ufm status UFM mode: Management Local - r-ufm237 (10.209.36.86) ===== UFM Running SM Running Telemetry Running Health Running UnhealthyPorts Running DailyReport Running SHArP N/A DRBD Running Primary DRBD State ConnectionState = Connected - DiskState = UpToDate Heartbeat Running (Master) HA Interface eth0 (connected to 10.209.36.89) Mgmt. Interface eth0 (up) ===== UFM mode: Management Peer - r-ufm238 (10.209.36.89) ===== UFM Stopped SM Stopped Telemetry Stopped Health Stopped </pre>	

	<pre> UnhealthyPorts Stopped DailyReport N/A SHArP N/A DRBD Running Secondary DRBD State ConnectionState = Connected - DiskState = UpToDate Heartbeat Running (Slave) HA Interface eth0 (connected to 10.209.36.86) Mgmt. Interface eth0 (up) ===== Virtual IP - 10.209.36.199 ===== High Availability Status: OK ===== r-ufm237 [mgmt-ha-active] (config) # </pre>
Related Commands	ufm start
Notes	<ul style="list-style-type: none"> • The output example above is taken from a high-availability setup • If working in HA mode, you will receive information on the HA status and virtual IP • The status for events forwarder is displayed only if the feature is enabled <p>The process status can be one of the below:</p> <ul style="list-style-type: none"> • Running - the process is running • Stopped - the process is not running • N/A - the process status is not applicable (e.g. NVIDIA SHARP is disabled, status on the standby node, etc...)

ufm counters

	ufm counters [ext-ports-only interval <sec> <never> max-files <number> upload <filename> <upload URL>]	
	Configures the settings of UFM counters.	
Syntax Description	ext-ports-only	Configures settings for UFM ext ports only

	interval	Configures settings for UFM counters interval. The settings can be: <ul style="list-style-type: none"> • sec - number of seconds 30 - 3600 • never - disable settings for UFM counters interval
	max-files	Configures the UFM counters maximum number of files (0-72)
	upload	Uploads the UFM counters file to a remote host or a USB device. <ul style="list-style-type: none"> • filename: UFM counters filename • Upload URL: The URL path from where the counters file can be uploaded. http, https, ftp, tftp, scp, sftp and usb are supported. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>ufm [mgmt-sa] (config) # ufm counters max-files 25</pre>	
Related Commands	show ufm counters	
Notes		

show ufm counters

	show ufm counters Displays UFM counters settings.
Syntax Description	N/A
Default	N/A
Configuration Mode	config

History	1.6
Example	<pre>ufmapl [mgmt-sa] (config) # show ufm counters counters interval = never max files = 5 ext ports only = disable</pre>
Related Commands	ufm counters
Notes	

License

ufm license install

	ufm license install <url> Installs a UFM license file from a remote host or a USB device.	
Syntax Description	url	http, https, ftp, tftp, scp, sftp and usb are supported. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm license install ftp://admin@192.168.11.1/ home/admin/licenses/volt-ufm-advanced.lic</pre>	

Related Commands	ufm license delete show ufm license
Notes	<ul style="list-style-type: none"> • The license format must be as follow: volt_*.lic • Duplicate license are not permitted. You must delete the previous license before installing the new one.

ufm license delete

	ufm license delete <filename> Deletes a UFM license file from the hard drive.	
Syntax Description	filename	UFM license filename
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm license delete volt-ufm-advanced.lic</pre>	
Related Commands	ufm license install show ufm license	
Notes		

show ufm license

	<p>show ufm license</p> <p>Displays UFM license information.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmapl [mgmt-sa] (config) # show ufm license ----- Customer ID SN swName Type MAC Address Exp. Date Limit Functionality Status ----- 495760397 123456778 UFM Evaluation NA 2090-11-21 1024 Advanced Valid ----- </pre>
Related Commands	<p>ufm license install</p> <p>ufm license delete</p>
Notes	

UFM Configuration Management

ufm configuration delete

	ufm configuration delete <zip-file> Deletes a configuration zip file from the hard drive.	
Syntax Description	zip-file	Zip filename to delete
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm configuration delete ufm- config-20121128-180857.zip</pre>	
Related Commands	ufm configuration upload ufm configuration import ufm configuration export ufm configuration fetch	
Notes		

ufm configuration export

	ufm configuration export [<zip-file>] Exports UFM configuration to a file (a zip archive).
--	---

Syntax Description	zip-file	UFM configuration of exporting the zip file
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm configuration export</pre>	
Related Commands	ufm configuration upload ufm configuration import ufm configuration delete ufm configuration fetch	
Notes	If no zip file is provided, a zip archive is created with the name: ufm-config-<date>-<time>.zip (e.g. ufm-config-20130327-153314.zip)	

ufm configuration fetch

	ufm configuration fetch <url> Downloads UFM configuration files from a remote host or a USB device.	
Syntax Description	url	The URL path from where the configuration file can be downloaded. http, https, ftp, tftp, scp, sftp and usb are supported. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # ufm configuration fetch usb:/ufmapp/ufmconf1.zip</pre>
Related Commands	<pre>ufm configuration upload ufm configuration import ufm configuration export ufm configuration delete</pre>
Notes	

ufm configuration import

	<pre>ufm configuration import <zip-file> [upgrade]</pre> <p>Imports UFM configuration from a file (a zip archive).</p>	
Syntax Description	zip-file	Zip filename from which to import
	upgrade	Imports UFM-SDN Appliance configuration from a previous version and upgrades it to the latest one
Default	N/A	
Configuration Mode	config	
History	1.5	
	1.6	Added the “upgrade” parameter
Example	<pre>ufmapl [mgmt-sa] (config) # ufm configuration import ufm-config-20121128-180857.zip</pre>	
Related Commands	<pre>ufm configuration upload ufm configuration export</pre>	

	ufm configuration delete ufm configuration fetch
Notes	

ufm configuration upload

	ufm configuration upload <filename> <url> Uploads UFM configuration to a remote host or a USB device (a zip archive).	
Syntax Description	filename	The UFM configuration of uploading the file name
	url	The URL path from where the configuration file can be uploaded. Supported formats: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm configuration upload ufm- config-20121128-180857.zip scp://mlnx:123456@172.30.3.201/tmp</pre>	
Related Commands	ufm configuration export ufm configuration import ufm configuration delete	
Notes		

Database Management

ufm database import

	ufm database import [<zip-file>] Imports UFM database files.	
Syntax Description	zip-file	Imported UFM database zip file
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm database import ufm- db-20130328-125141.zip</pre>	
Related Commands	ufm database delete ufm database upload	
Notes	<ul style="list-style-type: none">• If the "zip-file" parameter is not provided, a zip archive is created with the name: ufm-db-<date>-<time>.zip (e.g. ufm-db-20130328-125141.zip)• UFM must be stopped before running this command	

ufm database export

	ufm database export [<zip-file>] Exports UFM database (to a zip archive).	
--	--	--

Syntax Description	zip-file	Zipfile to export
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm database export</pre>	
Related Commands	ufm database delete ufm database upload	
Notes	If the "zip-file" parameter is not provided, a zip archive is created with the name: ufm-db-<date>-<time>.zip (e.g. ufm-db-20130328-125141.zip)	

ufm database delete

	ufm database delete <zip-file> Deletes a UFM database archive from the hard drive.	
Syntax Description	zip-file	Zipfile to delete
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm database delete ufm- database-180857.zip</pre>	

Related Commands	ufm database export ufm database upload
Notes	

ufm database upload

	ufm database upload <zip-file> <url> Uploads UFM database to a remote host or a USB device (a zip archive).	
Syntax Description	zip-file	Zipfile to delete
	url	The UFM database of uploading of the URL path. Formats: ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm database upload ufm- database-180857.zip scp://mlnx:1234Kb@172.30.3.201/tmp</pre>	
Related Commands	ufm database export ufm database delete	
Notes		

Data Management

ufm data backup

	<code>ufm data backup [<backup-file>][with-telemetry]</code> Backs up UFM data files.	
Syntax Description	<code>backup file</code>	Backup file name to be generated
	<code>with-telemetry</code>	Backup UFM historical telemetry
Default	N/A	
Configuration Mode	config	
History	4.6.0	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm data backup ufm-backup.zip</pre>	
Related Commands		
Notes		

ufm data delete

	<code>ufm data delete <zip file></code> Deletes a UFM data archive from the hard drive.
--	--

Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.6.0
Example	<pre>ufmapl [mgmt-sa] (config) # ufm data delete ufm-backup-20210716-122851.zip</pre>
Related Commands	
Notes	

ufm data fetch

	ufm data fetch <URL> Deletes a UFM data archive from the hard drive.	
Syntax Description	URL	Supported formats: http, https, ftp, tftp, scp, sftp and usb. (e.g., scp://username[:password]@hostname/path/filename , usb:/path/filename)
Default	N/A	
Configuration Mode	config	
History	4.6.0	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm data fetch scp://mlnx:1234Kb@172.30.3.201/tmp</pre>	
Related Commands		

Notes	
-------	--

ufm data reset

	<p>ufm data reset</p> <p>Resets the UFM data (both the configuration and the database data).</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapi [mgmt-sa] (config) # ufm data reset</pre>
Related Commands	
Notes	

ufm data restore

	<p>ufm data restore <zip file></p> <p>Restores UFM data files.</p>
Syntax Description	N/A
Default	N/A

Configuration Mode	config
History	4.6.0
Example	<pre>ufmapl [mgmt-sa] (config) # ufm data restore ufm-backup-20210716-122851.zip</pre>
Related Commands	
Notes	

ufm data upload

	<p><code>ufm data upload <zip file> <URL></code></p> <p>Uploads UFM data files to a remote host or a USB device.</p>	
Syntax Description	URL	Supported formats: http, https, ftp, tftp, scp, sftp and usb. (e.g., scp://username[:password]@hostname/path/filename , usb:/path/filename)
Default	N/A	
Configuration Mode	config	
History	4.6.0	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm data upload ufm-backup-20210716-130311.zip scp://mlnx:1234Kb@172.30.3.201/tmp</pre>	
Related Commands		
Notes		

High Availability

ufm ha configure

	<code>ufm ha [ipv6] configure <peer-ip> <virtual-ip> [interface]</code> <code>no ufm ha</code> Applies HA configuration. The no form of the command reverts the appliance to a standalone configuration.	
Syntax Description	peer-ip	Management IP address of peer machine
	virtual-ip	Virtual IP used for accessing the active (master) machine
	interface	Sets the working interface. The interface can be eth0...eth3, if no interface is assigned, eth0 is assumed to be the chosen interface.
Default	N/A	
Configuration Mode	config	
History	1.5	
	1.6	Added the "interface" parameter
Example	<pre> ufmapl [mgmt-sa] (config) # ufm ha configure 172.30.30.24 172.30.30.100 Please enter admin password for peer machine: ***** Configuring high availability, please wait... High availability is now configured. Please wait a few minutes for UFM machines to synchronize the configuration partition (DRBD). Please make sure all local UFM users on both machines have the same capabilities and passwords. </pre>	
Related Commands		
Notes		

ufm ha configure dual-subnet

	<code>ufm ha [ipv6] configure dual-subnet <local-ip> <peer-ip> <interface></code> <code>no ufm ha dual-subnet</code> Applies HA configuration for dual-subnet. The no form of the command reverts the appliance to a standalone configuration.	
Syntax Description	local-ip	Management IP address of the local machine
	peer-ip	Management IP address of peer machine
	interface	Sets the working interface. The interface can be eth0...eth3, if no interface is assigned, eth0 is assumed to be the chosen interface.
Default	N/A	
Configuration Mode	config	
History	4.1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm ha ipv6 configure dual-subnet fcfc:fcfc:209:36:21e:67ff:fe49:ce2a fcfc:fcfc:209:32:21e:67ff:fe4f:483a eth1</pre>	
Related Commands		
Notes		

ufm ha

	<code>ufm ha [failover takeover]</code> Performs High Availability failover/takeover operations.
--	---

Syntax Description	failover	Failover can be performed only on master (active) machine
	takeover	Takeover can be performed only on slave (standby) machine
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm ha takeover</pre>	
Related Commands		
Notes		

Telemetry

telemetry target enable

	<pre>telemetry target <target-name> enable no telemetry target <target-name> enable</pre> <p>Configures the target collector for the telemetry data. The no form of the command removes target collector configuration.</p>
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	4.5.0

Example	<pre>ufmapl [mgmt-sa] (config) # telemetry target example-target enable</pre>
Related Commands	<pre>show telemetry show telemetry target</pre>
Notes	

telemetry target import-filter-file

	<pre>telemetry target <target-name> import-filter-file {counters fields} <download-url> no telemetry target <target-name> import-filter-file</pre> <p>Imports filter file for the target collector. The no form of the command disables filter file.</p>	
Syntax Description	counters	Specifies counters file
	fields	Specifies fields file
	download-url	Supported protocols: http, https, ftp, tftp, scp, sftp, and usb. For example: scp://username[:password]@hostname/path/filename, usb:/path/filename
Default	N/A	
Configuration Mode	config	
History	4.5.0	
Example	<pre>ufmapl [mgmt-sa] (config) # telemetry target ufm-enterprise import- filter-file counters scp://user:password@host/tmp/aaa</pre>	

Related Commands	telemetry target enable show telemetry show telemetry target
Notes	If configuration exists for the specified target, then rerunning the command will overwrite the existing configuration.

telemetry target ip port

	telemetry target <target-name> ip <ipv4-address> port <port-id> [message-type {custom standard}] Configures IP address and port number to use for communication with telemetry target.	
Syntax Description	ip	IPv4 address of the target
	port	Port number of the target
	message-type	Supported types: <ul style="list-style-type: none"> extended custom
Default	N/A	
Configuration Mode	config	
History	4.5.0	
Example	<pre>ufmapl [mgmt-sa] (config) # telemetry target ufm-enterprise ip 10.10.10.10 port 443 message-type standard</pre>	
Related Commands	telemetry target enable show telemetry show telemetry target	
Notes	If configuration exists for the specified target, then rerunning the command will overwrite the existing configuration.	

telemetry target message type

	<code>telemetry target <target-name> message type {custom standard}</code> Configures telemetry target message type.
Syntax Description	N/A
Default	standard
Configuration Mode	config
History	4.5.0
Example	<pre>ufmapl [mgmt-sa] (config) # telemetry target ufm-enterprise message-type extended</pre>
Related Commands	<code>show telemetry</code> <code>show telemetry target</code>
Notes	

telemetry streaming enable

	<code>telemetry streaming enable</code> <code>no telemetry streaming enable</code> Enables telemetry streaming. The no form of the command disables telemetry streaming
Syntax Description	N/A
Default	Disabled

Configuration Mode	config
History	4.5.0
Example	<pre>ufmapl [mgmt-sa] (config) # telemetry streaming enable</pre>
Related Commands	show telemetry
Notes	

show telemetry

	<p>show telemetry</p> <p>Displays telemetry target settings.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.5.0
Example	<pre>ufmapl [mgmt-sa] (config) # show telemetry Enabled: Yes Telemetry Targets: Name: ufm-enterprise Enabled: Yes Host: 127.0.0.1 Port: 25225 Message Type: Standard</pre>

	<pre>Counters filter file: Yes Fields filter file: Yes</pre>
Related Commands	telemetry target enable
Notes	

show telemetry target

	<p>show telemetry target</p> <p>Displays telemetry settings for specific target.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.5.0
Example	<pre>ufmapl [mgmt-sa] (config) # show telemetry target ufm-enterprise Enabled: Yes Name: ufm-enterprise Enabled: Yes Host: 127.0.0.1 Port: 25225 Message Type: Standard Counters filter file: Yes Fields filter file: Yes</pre>
Related Commands	telemetry target enable
Notes	

ufm low-frequency-telemetry enable

	<code>ufm low-frequency-telemetry enable</code> <code>no ufm low-frequency-telemetry enable</code> Enables UFM low frequency telemetry. The no form of the command disables UFM low frequency telemetry.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.10.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm low-frequency-telemetry enable</pre>
Related Commands	<code>show ufm low-frequency-telemetry</code>
Notes	

show ufm low-frequency-telemetry

	<code>show ufm low-frequency-telemetry</code> Displays UFM low frequency telemetry settings.
Syntax Description	N/A
Default	N/A

Configuration Mode	Any configuration mode
History	4.10.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm low-frequency-telemetry Low Frequency Telemetry: No</pre>
Related Commands	ufm low-frequency-telemetry enable
Notes	

UFM Multi-site Portal

ufm multi-site enable

	ufm multi-site enable no ufm multi-site enable Enables UFM multi-site. The no form of the command disables UFM multi-site.
Syntax Description	N/A
Default	Disable
Configuration Mode	config
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # ufm multi-site enable</pre>

Related Commands	show ufm multi-site
Notes	

ufm multi-site interval

	ufm multi-site interval <time> no ufm multi-site interval Configures multi-site refresh interval. The no form of the command resets this parameter to its default value.	
Syntax Description	time	60-300 seconds
Default	60	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # ufm multi-site interval 100</pre>	
Related Commands	show ufm multi-site	
Notes		

ufm multi-site port

	<code>ufm multi-site port <port-id></code> <code>no ufm multi-site port</code> Configures the port for the multi-site user. The no form of the command resets this parameter to its default value.	
Syntax Description	port-id	ID of port to use
Default	443	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # ufm multi-site port 100</pre>	
Related Commands	show ufm multi-site	
Notes		

ufm multi-site server

	<code>ufm multi-site server {ip <ipv4-address> ipv6 <ipv6-address> hostname <name>}</code> <code>no ufm multi-site server {ip ipv6 hostname}</code> Configures multi-site server characteristics. The no form of the command clears configurations.	
Syntax Description	ip	Configures IPv4 address for server
	ipv6	Configures IPv6 address for server
	hostname	Configures hostname for server

Default	N/A
Configuration Mode	config
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # ufm multi-site server ipv6 ::1</pre>
Related Commands	show ufm multi-site
Notes	

ufm multi-site site-name

	ufm multi-site site-name <site-name> no ufm multi-site site-name Sets name for multi-site portal. The no form of the command clears name for the multi-site portal.	
Syntax Description	site-name	Name of site
Default	N/A	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # ufm multi-site site-name test_site</pre>	
Related Commands	show ufm multi-site	
Notes		

ufm multi-site username password

	<code>ufm multi-site username <name> password</code> <code>no ufm multi-site username [password]</code> Configures value for username. The no form of the command deletes multi-site user.	
Syntax Description	name	Username
	password	Configures the login password for the multi-site portal user
Default	Default password: 123456	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # ufm multi-site username root password Please enter multi site password:*****</pre>	
Related Commands	show ufm multi-site	
Notes		

show ufm multi-site

	<code>show ufm multi-site</code> Displays UFM multi-site configuration.
Syntax Description	N/A
Default	N/A

Configuration Mode	Any configuration mode
History	4.5.0
Example	<pre>ufm [mgmt-sa] (config) # show ufm multi-site Enabled: Yes Site name: Server: Port: 443 Protocol: https Interval: 60</pre>
Related Commands	
Notes	

UFM External Subnet Manager

ufm safe-stop

	<p>ufm safe-stop</p> <p>Stops UFM after remote UFM-SM take mastership.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	<p>mgmt-allow-sm-sa</p> <p>mgmt-allow-sm-ha-active</p>
History	1.5

Example	<pre>ufmapl [mgmt-allow-sm-ha-active](config) # ufm safe-stop</pre>
Related Commands	
Notes	

ufm external-sm trust

	<pre>ufm external-sm trust {ip <IPv4> ipv6 <IPv6>} no ufm external-sm trust {ip <IPv4> ipv6 <IPv6>}</pre> <p>Creates a trust relationship when in HA mode between the standby and the external SM machines. The no form of the command breaks a trust relationship between the standby and the external SM machines.</p>	
Syntax Description	ip	IPv4 address used to access the external SM machine
	ipv6	IPv6 address used to access the external SM machine
Default	N/A	
Configuration Mode	<pre>mgmt-allow-sm-sa mgmt-allow-sm-ha-active</pre>	
History	1.5	
	4.2.0	Added "ip" and "ipv6" parameters
Example	<pre>ufmapl [ha-standby] (config) # ufm external-sm trust ip 172.30.30.20</pre>	
Related Commands	<pre>show ufm external-sm show ufm external-sm status</pre>	
Notes	This command is available on the standby machine only.	

ufm external-sm register

	<code>ufm external-sm register {ip <ipv4> ipv6 <ipv6>}</code> <code>no ufm external-sm register {ip <ipv4> ipv6 <ipv6>}</code> Registers the external SM machine. The no form of the command unregisters the external SM machine.	
Syntax Description	ip	IPv4 address used to access the external SM machine
	ipv6	IPv6 address used to access the external SM machine
Default	N/A	
Configuration Mode	<code>mgmt-allow-sm-sa</code> <code>mgmt-allow-sm-ha-active</code>	
History	1.5	
	4.2.0	Added "ip" and "ipv6" parameters
Example	<pre>ufmapl [mgmt-sa] (config) # ufm external-sm register ip 10.30.30.101 Please enter admin password for external SM machine: ***** Configuring external SM, please wait... Note: when working in HA configuration, you must create trust between the standby machine and the external-SM machine by running the "ufm external-sm trust" command on the standby machine.</pre>	
Related Commands	<code>show ufm external-sm</code> <code>show ufm external-sm status</code>	
Notes		

show ufm external-sm

	show ufm external-sm Displays UFM external SM machines.
Syntax Description	N/A
Default	N/A
Configuration Mode	mgmt-allow-sm-sa mgmt-allow-sm-ha-active
History	1.5
Example	<pre>ufmapl [mgmt-allow-sm-sa] (config) # show ufm external-sm 10.30.30.101</pre>
Related Commands	show ufm external-sm status ufm external-sm trust ufm external-sm register
Notes	

show ufm external-sm status

	show ufm external-sm status Displays UFM external SM machines status.
Syntax Description	N/A
Default	N/A

Configuration Mode	mgmt-allow-sm-sa mgmt-allow-sm-ha-active
History	1.5
Example	<pre>ufmapl [mgmt-allow-sm-sa] (config) # show ufm external-sm status 10.30.30.19 0 ok Synchronized on: Sun Mar 10 11:26:22 GMT-2 2013 10.30.30.20 0 ok Synchronized on: Sun Mar 10 11:26:23 GMT-2 2013</pre>
Related Commands	show ufm external-sm ufm external-sm trust ufm external-sm register
Notes	

UFM Process Commands

ufm process health start

	ufm process health start ufm process health restart no ufm process health start Starts/restarts the UFM health process. The no form of the command stops the UFM health process.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5

Example	<pre>ufmapl [mgmt-sa] (config) # ufm process health start</pre>
Related Commands	show ufm status
Notes	

ufm process model start

	<p>ufm process model start ufm process model restart no ufm process model start</p> <p>Starts/restarts the UFM ModelMain process. The no form of the command stops the UFM ModelMain process.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-sa] (config) # ufm process model start</pre>
Related Commands	show ufm status
Notes	When stopping the UFM ModelMain process, the UFM health is also stopped in order not to start the UFM ModelMain process.

ufm process telemetry start

	<p>ufm process telemetry start ufm process telemetry restart no ufm process telemetry start</p> <p>Starts/restarts UFM telemetry process. The no form of the command stops UFM telemetry process.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.10.0
Example	<pre>ufmap1 [mgmt-sa] (config) # ufm process telemetry start</pre>
Related Commands	show ufm status
Notes	When stopping the UFM telemetry process, the UFM health is also stopped in order not to start the UFM telemetry process.

ufm process sharp start

	<p>ufm process sharp start ufm process sharp restart no ufm process sharp start</p> <p>Starts/restarts the NVIDIA SHARP Aggregation Manager process. The no form of the command stops the NVIDIA SHARP Aggregation Manager process.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.10.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ufm process sharp start</pre>
Related Commands	show ufm status
Notes	When stopping the SHARP AM process, the UFM health is also stopped in order not to start the SHARP AM process.

UFM Firmware Management

ufm firmware fetch

	ufm firmware fetch <URL> Downloads firmware archive ZIP file from a remote host or a USB device	
Syntax Description	URL	HTTP, HTTPS, FTP, TFTP, SCP, SFTP and USB are supported
	Example	scp://username[:password]@hostname/path/
	File name	usb:/path/filename
Default	N/A	
Configuration Mode	config	
History		
Example	<pre>Ufmap1 [mgmt-ha-active] (config) # ufm firmware fetch scp:// root@10.0.1.11/tmp/switch-fw.zip</pre>	
Related Commands	ufm firmware delete ufm firmware import	
Notes	Refer to In-Band Firmware Upgrade	

ufm firmware import

	ufm firmware import <zip-file> Imports switch FW from a firmware archive ZIP file.	
Syntax Description	zip-file	ZIP file from which to import the switch firmware
Default	N/A	
Configuration Mode	config	
History		
Example	<pre>Ufmap1 [mgmt-ha-active] (config) # ufm firmware import switch-fw.zip</pre>	
Related Commands	ufm firmware fetch ufm firmware delete	
Notes		

ufm firmware delete

	ufm firmware delete <zip-file> Deletes a firmware archive ZIP file from the hard drive	
Syntax Description	zip-file	ZIP file to delete

Default	N/A
Configuration Mode	config
History	
Example	<pre>Ufmapl [mgmt-ha-active] (config) # ufm firmware delete switch-fw.zip</pre>
Related Commands	<pre>ufm firmware fetch ufm firmware import</pre>
Notes	

UFM Running Modes

ufm mode

	<pre>ufm mode [mgmt mgmt-allow-sm mon remote-mon sm-only]</pre> <p>Changes the UFM working mode.</p>	
Syntax Description	mgmt	Changes UFM mode to management
	mgmt-allow-sm	Changes UFM mode to management allow-other-sm
	mon	Changes UFM mode to monitoring
	remote-mon	Changes UFM mode to remote monitoring only
	sm-only	Changes UFM mode to sm-only

Default	N/A	
Configuration Mode	config	
History	1.5	
	1.7	Added remote-mon mode
Example	<pre>ufmapl [mgmt-sa] (config) # ufm mode mgmt-allow-sm</pre>	
Related Commands		
Notes		

UFM Logs

ufm logging files delete oldest

	ufm logging files delete oldest {console event opensm sharp ufm ufmhealth} [<number>] Deletes log files.	
Syntax Description	console	Delete the oldest console log files
	event	Delete the oldest event log files
	opensm	Delete the oldest OpenSM log files
	sharp	Delete the oldest NVIDIA® Scalable Hierarchical Aggregation and Reduction Protocol (SHARP)™ log files
	ufm	Delete the oldest UFM log files
	ufmhealth	Delete the oldest UFM health log files
	number	Specifies the number of log files to delete

Default	If no number is specified, the command deletes the oldest log file only
Configuration Mode	config
History	4.6.0
Example	<pre>ufmapl [mgmt-sa] (config) # ufm logging files delete console 3</pre>
Related Commands	show ufm logging
Notes	

ufm logging files rotation criteria

	ufm logging files rotation criteria {frequency daily size <size-in-megabytes>}	
	Sets how the system decides when to rotate UFM log files.	
Syntax Description	frequency daily	Rotates log files once per day at midnight
	size	Rotates log files when they pass a size threshold
Default	100 MB	
Configuration Mode	config	
History	4.6.0	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm logging files rotation criteria size 100</pre>	
Related Commands	show ufm logging	
Notes		

ufm logging files rotation max-num

	ufm logging files rotation max-num <number> Specifies the maximum number of old log files to maintain.	
Syntax Description	number	Range: 1-999999
Default	10	
Configuration Mode	config	
History	4.6.0	
Example	<pre>ufmap1 [mgmt-sa] (config) # ufm logging files rotation criteria size 13</pre>	
Related Commands	show ufm logging	
Notes		

ufm logging level

	ufm logging level <log-level> Sets the severity level of certain log messages.	
Syntax Description	log-level	<ul style="list-style-type: none"> • CRITICAL - critical conditions • DEBUG - debug-level messages • ERROR - error conditions • INFO - informational messages • WARNING - warning conditions
Default	WARNING	

Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-sa] (config) # ufm logging level WARNING</pre>
Related Commands	
Notes	

ufm logging syslog

	ufm logging syslog <host:port> no ufm logging syslog Sends UFM logs to a remote syslog server. The no form of the command sends UFM logs to the local syslog server.	
Syntax Description	port	Remote syslog hostname and port
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm logging syslog 172.30.36.120:514 This change will take effect after UFM restart.</pre>	
Related Commands		
Notes	This change takes effect after UFM restart.	

ufm logging syslog level

	ufm logging syslog level <log-level> Sets the severity level of certain log messages.	
Syntax Description	log-level	<ul style="list-style-type: none"> • CRITICAL - critical conditions • DEBUG - debug-level messages • ERROR - error conditions • INFO - informational messages • WARNING - warning conditions
Default	WARNING	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm logging syslog level WARNING This change will take effect after UFM restart.</pre>	
Related Commands		
Notes	This change takes effect after UFM restart.	

ufm logging syslog enable

	ufm logging syslog enable no ufm logging syslog enable Enable sending UFM logs to syslog. The no form of the command disables sending UFM logs to syslog.
--	--

Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-sa] (config) # ufm logging syslog enable This change will take effect after UFM restart.</pre>
Related Commands	
Notes	This change takes effect after UFM restart.

ufm logging syslog ufm-events enable

	<pre>ufm logging syslog ufm-events enable no ufm logging syslog ufm-events enable</pre> <p>Send UFM event log messages to a syslog server. The no form disables the ability to log UFM event messages to syslog locally and remotely.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-sa] (config) # ufm logging syslog ufm-events enable This change will take effect after UFM restart.</pre>

Related Commands	
Notes	This change takes effect after UFM restart.

show ufm console log

	show ufm console log [matching <regex> not matching <regex>] Displays current console event log file in a scrollable pager.	
Syntax Description	matching	Displays new console log messages that match a given regular expression
	not matching	Displays new console log messages that do not match a given regular expression
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.6.0	
Example	<pre> ufmapl [mgmt-sa] (config) # show ufm console log 2021-07-20 13:34:49.090 ufm INIT Prometheus Client: Request time = 0.005601406097412109, Total Processing time = 0.011138916015625 2021-07-20 13:34:49.092 ufm INIT handled device stats. (10) 3887.93 devices/sec. (18) 6998.28 ports/sec, queue: 9 2021-07-20 13:35:19.115 ufm INIT Telemetry packet: size: 0.043 MB, transfer rate: 7.684 MB/sec 2021-07-20 13:35:19.120 ufm INIT Prometheus Client: Request time = 0.0056459903717041016, Total Processing time = 0.010822296142578125 ... </pre>	
Related Commands		
Notes		

show ufm console log continuous

	show ufm console log continuous [matching <regex> not matching <regex>] Displays new event log messages as they arrive.	
Syntax Description	matching	Displays new console log messages that match a given regular expression
	not matching	Displays new console log messages that do not match a given regular expression
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.6.0	
Example	<pre> ufmapl [mgmt-sa] (config) # show ufm console log continuous matching CRITICAL 2021-07-20 09:40:33.825 eventlog CRITICAL 2021-07-20 09:40:33.825 [10] [394] CRITICAL [Module_Status] Switch [default(6) / Switch: switch-system / NA / NA] [dev_id: 0002c903005dd830]: Module PS 2 on switch-system(10.10.10.10) status is fatal 2021-07-20 10:36:23.962 eventlog CRITICAL 2021-07-20 10:36:23.961 [40] [518] CRITICAL [Maintenance] Grid [Grid]: Process periodic_report_runner is down. </pre>	
Related Commands	show ufm console log	
Notes		

show ufm console log files

	show ufm console log files [<file-number> [matching <regex> not matching <regex>]] Lists all archived log files available.
--	---

Syntax Description	file-number	Displays the selected archived event log file
	matching	Displays entries from the selected log file that match a given regular expression
	not matching	Displays entries from the selected log file that do not match a given regular expression
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.6.0	
Example	<pre> ufmapl [mgmt-sa] (config) # show ufm console log files 1 matching INFO 2021-07-20 11:47:43.231 rest_api INFO user: ufmsystem, url: (http:// 11.1.1.11:8000/app/events/external_event), method: (POST) 2021-07-20 11:50:43.437 rest_api INFO user: ufmsystem, url: (http:// 11.1.1.11:8000/app/events/external_event), method: (POST) 2021-07-20 11:53:43.642 rest_api INFO user: ufmsystem, url: (http:// 11.1.1.11:8000/app/events/external_event), method: (POST) 2021-07-20 11:56:43.862 rest_api INFO user: ufmsystem, url: (http:// 11.1.1.11:8000/app/events/external_event), method: (POST) </pre>	
Related Commands	show ufm console log	
Notes		

show ufm event log

	show ufm event log [matching <regex> not matching <regex>] Displays current event log file in a scrollable pager.	
Syntax Description	matching	Displays new event log messages that match a given regular expression
	not matching	Displays new event log messages that do not match a given regular expression
Default	N/A	

Configuration Mode	Any configuration mode
History	4.6.0
Example	<pre>ufmap1 [mgmt-sa] (config) # show ufm event log matching INFO 2021-07-20 09:35:31.551 [1] [352] INFO [Logical_Model] Grid [Grid]: Network management is added 2021-07-20 09:35:34.454 [3] [604] INFO [Maintenance] Grid [Grid]: Fabric Analysis Report succeeded 2021-07-20 09:40:31.957 [5] [604] INFO [Maintenance] Grid [Grid]: Fabric Analysis Report succeeded ...</pre>
Related Commands	
Notes	

show ufm event log continuous

	show ufm event log continuous [matching <regex> not matching <regex>] Displays new event log messages as they arrive.	
Syntax Description	matching	Displays new event log messages that match a given regular expression
	not matching	Displays new event log messages that do not match a given regular expression
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.6.0	
Example	<pre>ufmap1 [mgmt-sa] (config) # show ufm event log continuous not matching INFO</pre>	

	<pre>2021-07-20 09:38:33.192 [4] [406] WARNING [Communication_Error] Grid [Grid]: Failed to get sysinfo for switch 0002c903005dd830 2021-07-20 09:40:33.825 [10] [394] CRITICAL [Module_Status] Switch [default(6) / Switch: switch-system / NA / NA] [dev_id: 0002c903005dd830]: Module PS 2 on switch-system(10.10.10.10) status is fatal 2021-07-20 10:36:23.961 [40] [518] CRITICAL [Maintenance] Grid [Grid]: Process periodic_report_runner is down.</pre>
Related Commands	show ufm console event log
Notes	

show ufm event log files

	<pre>show ufm event log files [-<file-number> [matching <regex> not matching <regex>]]</pre> <p>Lists all archived log files available.</p>	
Syntax Description	file-number	Displays the selected archived event log file
	matching	Displays entries from the selected log file that match a given regular expression
	not matching	Displays entries from the selected log file that do not match a given regular expression
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.6.0	
Example	<pre>ufmapl [mgmt-sa] (config) # show ufm event log files</pre>	
Related Commands	show ufm event log	
Notes		

show ufm logging

	show ufm logging Displays logging configuration.	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.6	
	4.6.0	Updated command output
Example	<pre> ufmapl [mgmt-sa] (config) # show ufm logging Number of archived log files to keep: 10 Log rotation size threshold: 100 megabytes Ufm-log level: WARNING Syslog: Enabled: No Server: Local Level: WARNING Ufm-log enabled: No Ufm-events enabled: No </pre>	
Related Commands		
Notes		

show ufm log

	show ufm log [continuous files matching not] Displays UFM event log.	
Syntax Description	continuous	Displays new event log messages as they arrive
	files	Displays archived log files
	matching	Displays event logs that match a given regular expression
	not	Displays event logs that do not meet certain criteria
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.6	
Example	<pre> ufmapl [mgmt-sa] (config) # show ufm log 2013-09-03 14:34:00.407 ufm INIT Request Polling Delta Fabric 2013-09-03 14:34:30.411 ufm INIT Request Polling Delta Fabric 2013-09-03 14:35:00.413 ufm INIT Request Polling Delta Fabric 2013-09-03 14:35:30.416 ufm INIT Request Polling Delta Fabric 2013-09-03 14:36:00.419 ufm INIT Request Polling Delta Fabric 2013-09-03 14:36:06.016 ufm ACTION user ufmsystem called triggerExternalEvent with params : <ws.UFM_services_types.ExternalEvent_Holder instance at 0x6ffe440> 2013-09-03 14:36:30.423 ufm INIT Request Polling Delta Fabric 2013-09-03 14:37:00.426 ufm INIT Request Polling Delta Fabric 2013-09-03 14:37:30.428 ufm INIT Request Polling Delta Fabric 2013-09-03 14:38:00.431 ufm INIT Request Polling Delta Fabric 2013-09-03 14:38:02.175 ufm WARNING Failed to parse host response from host 172.30.105.153 message type 10 2013-09-03 14:38:02.193 ufm WARNING Failed to parse host response from host 172.30.11.161 message type 10 2013-09-03 14:38:02.489 ufm WARNING Failed to parse host response from host 172.30.112.23 message type 10 </pre>	


	<pre>2013-09-03 14:38:02.723 ufm WARNING Failed to parse host response from host 172.30.112.24 message type 10 2013-09-03 14:38:02.768 ufm WARNING Failed to parse host response from host 172.30.49.89 message type 10 2013-09-03 14:38:30.435 ufm INIT Request Polling Delta Fabric</pre>
Related Commands	
Notes	

show ufmhealth log

	<pre>show ufmhealth log [continuous files matching not]</pre> <p>Displays UFM health event log.</p>	
Syntax Description	continuous	Displays new event log messages as they arrive
	files	Displays archived log files
	matching	Displays event logs that match a given regular expression
	not	Displays event logs that do not meet certain criteria
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.6	
Example	<pre>ufmapl [mgmt-sa] (config) # show ufmhealth log 2013-09-03 14:36:30.423 ufm INIT Request Polling Delta Fabric 2013-09-03 14:37:00.426 ufm INIT Request Polling Delta Fabric 2013-09-03 14:37:30.428 ufm INIT Request Polling Delta Fabric 2013-09-03 14:38:00.431 ufm INIT Request Polling Delta Fabric 2013-09-03 14:38:02.175 ufm WARNING Failed to parse host response from host 172.30.105.153 message type 10</pre>	

	2013-09-03 14:38:02.193 ufm WARNING Failed to parse host response from host 172.30.11.161 message type 10
Related Commands	
Notes	

Advanced Subnet Manager Configuration

 The UFM must be restarted for this configuration to take effect.

ib sm <hm-action>

	ib sm <hm-action> <value> Enables unhealthy ports configuration. The value parameter can be set to report, ignore or isolate the action.	
Syntax Description	hm-ca-flapping-action	Unhealthy Ports flapping condition options. Default: report.
	hm-ca-illegal-action	Unhealthy ports illegal condition options. Default: report.
	hm-ca-manual-action	Unhealthy ports manual condition options. Default: report.
	hm-ca-noisy-action	Unhealthy Ports Noisy condition options. Default: report.
	hm-ca-reboot-action	CA/RTR unhealthy Ports Reboot condition options. Default: report.
	hm-ca-seterr-action	Unhealthy Ports SetErr condition options. Default: ignore.
	hm-ca-unresponsive-action	CA/RTR Unresponsive Action. Default: report.
	hm-sw-flapping-action	Switch flapping action. Default: report.
	hm-sw-illegal-action	Switch illegal action. Default: report.

	hm-sw-manual-action	Switch manual action. Default: no_discover.
	hm-sw-noisy-action	Switch noisy action. Default: report.
	hm-sw-reboot-action	Switch unhealthy Ports Reboot condition options. Default: report.
	hm-sw-seterr-action	Switch seterr action. Default: ignore.
	hm-sw-unresponsive-action	Switch unresponsive action. Default: report.
Default	See Syntax Description	
Configuration Mode	config	
History	1.7	
Example	<pre>ufmap1 [mgmt-sa] (config) # ib sm hm-ca-flapping-action ignore</pre>	
Related Commands	show ib sm hm-unhealthy-ports	
Notes		

ib sm <hm-num>

	<p>ib sm <hm-num> <value></p> <p>Enables unhealthy ports configuration. The options are report, ignore or isolate the action.</p>	
Syntax Description	hm-num-flapping-sweeps	The number of sweeps in which the link was flapping. Default: 5.
	hm-num-flapping-sweeps-window	The number of sweeps of which any port exceeding hm_num_flapping_sweeps is declared unhealthy. Default: 10.
	hm-num-illegal	Number of illegal SMPs a port may return to be declared unhealthy. Default: 1.
	hm-num-no-resp-sweeps	The number of sweeps that had that port unresponsive. Default: 5.

	hm-num-no-resp-sweeps-window	The number of sweeps of which any port exceeding. Default: 7.
	hm-num-reboots	Number of reboots in period to declare a node as unhealthy. Default: 10.
	hm-num-set-err-sweeps	The number of sweeps that had that port report back an error for a Set. Default: 5.
	hm-num-set-err-sweeps-window	The number of sweeps of which any port exceeding hm_num_set_err_sweeps is declared unhealthy. Default: 7.
	hm-num-traps	Number of traps received in period to declare the port as unhealthy. Default: 250.
	hm-num-traps-period	The period for counting number of received traps in seconds. Default: 60.
Default	See Syntax Description	
Configuration Mode	config	
History	1.7	
Example	<pre>ufmapl [mgmt-sa] (config) # ib sm hm-num-flapping-action 5</pre>	
Related Commands	show ib sm hm-unhealthy-ports	
Notes		

ib sm hm-reboots-period

	ib sm hm-reboots-period <time>	
	Number of reboots in period to declare a node as unhealthy.	
Syntax Description	time	Range: 60-86400 seconds
Default	900	
Configuration Mode	config	

History	1.7
Example	<pre>ufmapl [mgmt-sa] (config) # ib sm hm-reboots-period 60</pre>
Related Commands	show ib sm hm-unhealthy-ports
Notes	

ib sm hm-unhealthy-ports-checks enable

	<p>ib sm hm-unhealthy-ports-checks enable</p> <p>Enables unhealthy ports configuration.</p>
Syntax Description	N/A
Default	Enabled
Configuration Mode	config
History	1.7
Example	<pre>ufmapl [mgmt-sa] (config) # ib sm hm-unhealthy-ports-checks enable</pre>
Related Commands	show ib sm hm-unhealthy-ports
Notes	

show ib sm hm-unhealthy-ports

	<code>show ib sm hm-unhealthy-ports</code> Displays unhealthy ports configuration.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.7
Example	<pre>ufmap1 [mgmt-sa] (config) # show ib sm hm-unhealthy-ports hm_unhealthy_ports_checks enable hm_ca_reboot_action report hm_sw_reboot_action report hm_num_reboots 10 hm_reboots_period_secs 900 hm_ca_unresponsive_action report hm_sw_unresponsive_action report hm_num_no_resp_sweeps 5 hm_num_no_resp_sweeps_window 7 hm_ca_noisy_action report hm_sw_noisy_action report hm_num_traps 250 hm_num_traps_period_secs 60 hm_ca_seterr_action ignore hm_sw_seterr_action ignore hm_num_set_err_sweeps 5 hm_num_set_err_sweeps_window 7 hm_ca_flapping_action report hm_sw_flapping_action report hm_num_flapping_sweeps 5 hm_num_flapping_sweeps_window 10 hm_ca_illegal_action report hm_sw_illegal_action report</pre>

	<pre> hm_num_illegal 1 hm_ca_manual_action report </pre>
Related Commands	
Notes	

ib sm opensm-health-policy-merge

	<p>ib sm opensm-health-policy-merge</p> <p>Merges the opensm-health-policy.conf.user_ext. To use after importing the specific file or importing all configuration files.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.7
Example	<pre> ufmapl [mgmt-ha-active] (config) # ib sm opensm-health-policy-merge </pre>
Related Commands	
Notes	SM must be running for this command to work.

ib sm reassign-lids

	<code>ib sm reassign-lids</code> <code>no ib sm reassign-lids</code> Enables SM ability to reassign active LIDs. The no form of the command disables SM ability to reassign LIDs
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.6.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm reassign-lids</pre>
Related Commands	<code>show ib sm reassign-lids</code>
Notes	

show ib sm reassign-lids

	<code>show ib sm reassign-lids</code> Displays SM LID reassignment policy.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any command mode
History	4.6.0

Example	<pre>ufmapl [mgmt-ha-active] (config) # show ib sm reassign-lids disable</pre>
Related Commands	
Notes	

UFM Web Client

ufm web-client mode

	<pre>ufm web-client mode <http https https-client-authentication></pre> <p>Configures Access mode to the UFM web clients.</p>	
Syntax Description	http	HTTP access
	https	HTTPS access
	https-client-authentication	HTTPS access with client authentication
Default	http	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client mode https- client-authen</pre>	

Related Commands	show ufm web-client ufm web-client client-authentication ufm web-client associate-user
Notes	The new mode is applied upon UFM start.

ufm web-client client-authentication ca-cert fetch

	ufm web-client client-authentication ca-cert fetch <download-url> no ufm web-client client-authentication ca-cert fetch <download-url> Downloads a root/intermediate certificates file from a remote host or a USB device. The no form of the command deletes the root/intermediate certificate file from the hard disk.	
Syntax Description	download-url	The URL path from where the image file can be downloaded. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client client-authentication certificate fetch scp://root@10.10.32.12/tmp/ca-intermediate.crt</pre>	
Related Commands	show ufm web-client ufm web-client mode ufm web-client associate-user	
Notes		

ufm web-client client-authentication associate-user

	ufm web-client client-authentication associate-user <san> <username> no ufm web-client client-authentication associate-user <san> <username> Associates client certificate subject alternative name with a UFM user. The no form of the command disassociates client certificate subject alternative name from a UFM user.	
Syntax Description	san	Client certificate subject alternative name
	username	UFM username
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client associate-user ufm.mellanoxhpc.net ufmsysadmin</pre>	
Related Commands	show ufm web-client ufm web-client mode ufm web-client client-authentication	
Notes		

show ufm web-client

	show ufm web-client Displays UFM web client settings.
Syntax Description	N/A

Default	N/A
Configuration Mode	Any configuration mode
History	1.5
Example	<pre> ufmapl [mgmt-ha-active] (config) # show ufm web-client Mode: HTTPS Client authentication: Yes Bootstrap certificate file: Present CA certificate file: Present Server certificate file: Present Server certificate hostname: ufm.mellanoxhpc.net User Associations: SAN: ufm.mellanoxhpc.net User: ufmsysadmin Certificate Auto-refresh: Enabled: Yes CA certificate URL: https://mellanox.com/cacert Server certificate URL: https://mellanox.com/servercerts Server certificate thumbprint: 2268BDD79DF7FD9C818EB97F315AE0F35D223A15 Last checked: 2019-04-20 20:57:21 Last update: 2019-04-20 20:57:21 </pre>
Related Commands	<pre> ufm web-client mode ufm web-client client-authentication ufm web-client associate-user </pre>
Notes	

ufm web-client server-cert hostname

	<p>ufm web-client server-cert hostname <hostname> no ufm web-client server-cert hostname <hostname></p> <p>Sets the hostname used to access the UFM web client. The no form of the command deletes the server certificate hostname used to access the UFM web client.</p>	
Syntax Description	hostname	Hostname used to access the UFM web client
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client server-cert hostname ufm.mellanoxhpc.net</pre>	
Related Commands	show ufm web-client	
Notes	Multiple hostnames may be configured.	

ufm web-client server-cert fetch

	<p>ufm web-client server-cert fetch <download-url> no ufm web-client server-cert fetch <download-url></p> <p>Downloads a server certificate file from a remote host or a USB device. The no form of the command deletes the server certificate file from the hard disk.</p>	
Syntax Description	download-url	The URL path from where the image file can be downloaded. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.

Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client server-cert fetch scp://admin@192.168.1.10/tmp/certs/server.pfx</pre>
Related Commands	show ufm web-client
Notes	

ufm web-client client-authentication cert-refresh enable

	<p>ufm web-client client-authentication cert-refresh enable no ufm web-client client-authentication cert-refresh enable</p> <p>Enables UFM web client certificates auto-refresh. The no form of the command disables the feature.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client client-authentication cert-refresh enable</pre>
Related Commands	show ufm web-client
Notes	

ufm web-client client-authentication cert-refresh ca-cert

	<p>ufm web-client client-authentication cert-refresh ca-cert <download-url> no ufm web-client client-authentication cert-refresh ca-cert <download-url></p> <p>Sets the download URL for root/intermediate certificate. The no form of the command clears the root/intermediate certificate auto-refresh settings.</p>	
Syntax Description	download-url	Download URL for root/intermediate certificate
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client client-authentication cert- refresh ca-cert "https://mellanox.com/cacerts"</pre>	
Related Commands	show ufm web-client	
Notes		

ufm web-client client-authentication cert-refresh self-client-cert fetch

	<p>ufm web-client client-authentication cert-refresh self-client-cert fetch <download-url> <password> no ufm web-client client-authentication cert-refresh self-client-cert fetch <download-url> <password></p> <p>Downloads a bootstrap certificate file from a remote host or a USB device. The no form on the command deletes the bootstrap certificate file from the hard disk.</p>	
Syntax Description	download-url	http, https, ftp, tftp, scp, sftp and usb are supported. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.

	password	Bootstrap certificate password
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ufm web-client client-authentication cert- refresh self-client-cert fetch scp://admin@192.168.1.10/tmp/certs/bootstrap.pfx "UMm6gF8bGR81+yUScXpVEnr8Q4t4Svccy6UkHK8oolv1GF1wyreTHjdsWBcIUYH1TRgQt2yguvDs4wr cRIbGGQ=="</pre>	
Related Commands	show ufm web-client ufm web-client client-authentication cert-refresh self-client-cert password-file fetch	
Notes		

ufm web-client client-authentication cert-refresh self-client-cert password-file fetch

	ufm web-client client-authentication cert-refresh self-client-cert password-file fetch <download-uri> no ufm web-client client-authentication cert-refresh self-client-cert password-file fetch <download-uri> Fetches a bootstrap certificate password file (containing a password to be used to open a bootstrap certificate) rather than having to supply a cleartext password while fetching the bootstrap certificate. The no form on the command deletes the bootstrap certificate password file from the hard disk.	
Syntax Description	download-uri	http, https, ftp, tftp, scp, sftp and usb are supported. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	4.3.0	

Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client client-authentication cert- refresh self-client-cert password-file fetch scp://admin@192.168.1.10/tmp/certs/ bootstrap.txt</pre>
Related Commands	<pre>show ufm web-client ufm web-client client-authentication cert-refresh self-client-cert fetch</pre>
Notes	

ufm web-client client-authentication cert-refresh server-cert

	<pre>ufm web-client client-authentication cert-refresh server-cert <url> <thumbprint> no ufm web-client client-authentication cert-refresh server-cert <url> <thumbprint></pre> <p>Sets the download URL for server and bootstrap certificates. The no form of the command clears the server and bootstrap certificates auto-refresh settings.</p>	
Syntax Description	url	http, https, ftp, tftp, scp, sftp and usb are supported. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
	thumbprint	Server certificate thumbprint
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client client-authentication cert-refresh server-cert "https://mellanox.com/servercerts" 2268BDD79DF7FD9C818EB97F315AE0F35D223A15</pre>	
Related Commands	show ufm web-client	

Notes	
-------	--

ufm web-client client-authentication cert-refresh run-now

	ufm web-client client-authentication cert-refresh run-now Refreshes the server and root/intermediate certificates manually.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm web-client client-authentication cert-refresh run-now</pre>
Related Commands	show ufm web-client
Notes	

ufm ws-address

	ufm ws-address <address> Sets the web server external address.
Syntax Description	N/A
Default	N/A
Configuration Mode	config

History	1.6
Example	<pre>ufmapl [mgmt-sa] (config) # ufm ws-address 172.10.30.16</pre>
Related Commands	show ufm ws-address
Notes	

show ufm ws-address

	<p>show ufm ws-address <address></p> <p>Displays the web server external address.</p>	
Syntax Description	address	Web server external address
Default	N/A	
Configuration Mode	Any configuration mode	
History	1.6	
Example	<pre>ufmapl [mgmt-sa] (config) # show ufm ws-address Web server external address: UNDEFINED</pre>	
Related Commands	ufm ws-address	
Notes		

Management Interface Monitoring

ufm mgmt-interface monitor enable

	<code>ufm mgmt-interface monitor enable</code> <code>no ufm mgmt-interface monitor enable</code> Enables monitoring of the management interface. The no form of the command disables monitoring of the management interface.
Syntax Description	N/A
Default	http
Configuration Mode	config
History	4.1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm mgmt-interface monitor enable</pre>
Related Commands	<code>ufm mgmt-interface monitor interval</code> <code>ufm mgmt-interface</code> <code>show ufm mgmt-interface</code>
Notes	

ufm mgmt-interface monitor interval

	<code>ufm mgmt-interface monitor interval <time></code> Configures the management interface monitoring interval.
--	---

Syntax Description	time	The management interface monitoring interval. Range: 5-180 seconds.
Default	10 seconds	
Configuration Mode	config	
History	4.1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm mgmt-interface monitor interval 15</pre>	
Related Commands	ufm mgmt-interface monitor enable ufm mgmt-interface show ufm mgmt-interface	
Notes		

ufm mgmt-interface

	ufm mgmt-interface <interface> Configures the management interface to be monitored.	
Syntax Description	interface	Management interface to be monitored (e.g. eth0, eth1)
Default	eth0	
Configuration Mode	config	
History	4.1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm mgmt-interface eth0</pre>	

Related Commands	ufm mgmt-interface monitor enable ufm mgmt-interface monitor interval show ufm mgmt-interface
Notes	The interface is set automatically when invoking the command "ufm ha configure".

show ufm mgmt-interface

	show ufm mgmt-interface Displays the management interface settings.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm mgmt-interface Management interface monitoring: Interface name: eth0 Enabled: Yes Monitoring interval: 10 seconds</pre>
Related Commands	ufm mgmt-interface monitor enable ufm mgmt-interface monitor interval ufm mgmt-interface
Notes	

AHX Monitoring

ib managed-switch ahx-monitor enable

	<pre>ib managed-switch ahx-monitor enable no ib managed-switch ahx-monitor enable</pre> <p>Enables AHX monitoring. The no form of the command disables AHX monitoring.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.2
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib managed-switch ahx-monitor enable</pre>
Related Commands	<pre>show ib managed-switch ahx-monitor</pre>
Notes	

managed-switch ahx-monitor interval

	<pre>ib managed-switch ahx-monitor interval <time> no ib managed-switch ahx-monitor interval</pre> <p>Configures AHX monitoring interval. The no form of the command resets the AHX monitoring interval to default.</p>
--	---

Syntax Description	time	Monitoring interval values: 1m - 1 minute 5m - 5 minutes 10m - 10 minutes 15m - 15 minutes 20m - 20 minutes 30m - 30 minutes 1h - 1 hour 2h - 2 hours 3h - 3 hours 4h - 4 hours 6h - 6 hours 8h - 8 hours 12h - 12 hours 24h - 24 hours
Default	1m	
Configuration Mode	config	
History	4.2	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib managed-switch ahx-monitor interval 10m</pre>	
Related Commands	show ib managed-switch ahx-monitor	
Notes		

ib managed-switch ahx-monitor device

	ib managed-switch ahx-monitor device <switch-name> <ip ipv6> <primary-ip-address> <secondary-ip-address> [<AHX alternative switch name>] no ib managed-switch ahx-monitor device <switch-name>	
	Adds AHX device to monitoring. The no form of the command removes AHX device from monitoring.	
Syntax Description	switch-name	AHX switch name
	alternative-switch-name	AHX alternative switch name
	ip ipv6	Sets IPv4/IPv6 addresses for this device
	primary-ip-address	AHX primary IP address
	secondary-ip-address	AHX secondary IP address
Default		
Configuration Mode	config	
History	4.2	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib managed-switch ahx-monitor device ahx_switch01 ip 10.10.10.10 10.10.10.11</pre>	
Related Commands	show ib managed-switch ahx-monitor	
Notes		

show ib managed-switch ahx-monitor

	<pre>show ib managed-switch ahx-monitor</pre> <p>Displays AHX monitoring settings.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.2
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ib managed-switch ahx-monitor AHX Monitoring: Enabled : Yes Interval: 10m AHX Devices: Switch name : ahx_switch01 Primary IP address : 10.1.1.11 Secondary IP address: 10.1.2.11</pre>
Related Commands	<pre>ib managed-switch ahx-monitor enable managed-switch ahx-monitor interval ib managed-switch ahx-monitor device</pre>
Notes	

UFM Events Forwarder

ufm events-forwarder enable

	<code>ufm events-forwarder enable</code> <code>no ufm events-forwarder enable</code> Enables events-forwarder. The no form of the command disables events-forwarder.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.4.0
Example	<pre>ufmapl [mgmt-sa] (config) # ufm events-forwarder enable</pre>
Related Commands	<code>ufm events-forwarder server</code> <code>show ufm events-forwarder</code>
Notes	

ufm events-forwarder server

	<pre>ufm events-forwarder server ip <ip-address> port <number> no ufm events-forwarder server</pre> <p>Configures server IP and port for events forwarder service. The no form of the command deletes server configuration.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.4.0
Example	<pre>ufmapl [mgmt-sa] (config) # ufm events-forwarder server ip 2.2.2.2 port 300</pre>
Related Commands	<pre>ufm events-forwarder enable show ufm events-forwarder</pre>
Notes	This configuration can be done only if UFM is stopped

show ufm events-forwarder

	<pre>show ufm events-forwarder</pre> <p>Displays UFM events-forwarder status.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config

History	4.4.0
Example	<pre>ufmapl [mgmt-sa] (config) # show ufm events-forwarder Enabled: Yes Server: 2.2.2.2 Port: 300</pre>
Related Commands	<pre>ufm events-forwarder enable ufm events-forwarder server</pre>
Notes	

ufm events max-restored

	<pre>ufm events max-restored <1-1000></pre> <p>Restores max UFM events.</p>	
Syntax Description	max-restored-value	Maximum number of restored events
Default	50	
Configuration Mode	config	
History	4.8.0	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm events max-restored 70</pre>	
Related Commands	<pre>ufm events persistency enable show ufm events</pre>	
Notes		

ufm events persistency enable

	<code>ufm events persistency enable</code> <code>no ufm persistency enable</code> Enables events persistency The no form of the command disables UFM persistency
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	4.8.0
Example	<pre>ufmapl [mgmt-sa] (config) # ufm events persistency enable</pre>
Related Commands	<code>show ufm events</code> <code>ufm events max-restored</code>
Notes	

show ufm events

	<code>show ufm events</code> Displays UFM events
Syntax Description	N/A
Default	N/A
Configuration Mode	config

History	4.8.0
Example	<pre>ufmapl [mgmt-sa] (config) # show ufm events Events persistency: No Max restored: 50</pre>
Related Commands	<pre>ufm events persistency enable ufm events max-restored</pre>
Notes	

UFM Virtualization

ufm virtualization enable

	<pre>ufm virtualization enable no ufm virtualization enable</pre> <p>Enables discovery of all the virtual ports in the fabric. The no form of the command disables discovery of virtual ports in the fabric.</p>
Syntax Description	N/A
Default	Disable
Configuration Mode	config
History	4.5.0
Example	<pre>ufm [mgmt-sa] (config) # ufm virtualization enable</pre>

Related Commands	ufm virtualization interval
Notes	

ufm virtualization interval

	ufm virtualization interval <seconds> no ufm virtualization interval Sets the virtual ports discovery interval. The no form of the command resets this parameter to its default.	
Syntax Description	seconds	Range: 5-86400 seconds
Default	60	
Configuration Mode	config	
History	4.5.0	
Example	<pre>ufm [mgmt-sa] (config) # ufm virtualization interval 300</pre>	
Related Commands	ufm virtualization enable	
Notes		

show ufm virtualization

	show ufm virtualization Displays UFM virtualization settings.
--	--

Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.5.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm virtualization Enabled : No</pre>
Related Commands	ufm virtualization enable
Notes	

UFM Agent

ufm agent interface

	<pre>ufm agent interface {eth0 eth1} no ufm agent interface {eth0 eth1}</pre> <p>Sets UFM agent interface. The no form of the command removes the settings for UFM agent interface.</p>	
Syntax Description	eth0	Adds/removes UFM agent interface to eth0
	eth1	Adds/removes UFM agent interface to eth1
Default	N/A	
Configuration Mode	config	
History	1.6	

Example	<pre>ufmapl [mgmt-sa] (config interface eth0) # ufm agent interface eth1</pre>
Related Commands	
Notes	

show ufm agent

	<p>show ufm agent</p> <p>Displays the configured settings for UFM agent.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre>ufmapl [mgmt-sa] (config) # show ufm agent interface eth0</pre>
Related Commands	ufm agent
Notes	

Unhealthy Ports

ufm unhealthy-ports isolate-high-ber isolation-mode

	ufm unhealthy-ports isolate-high-ber isolation-mode <mode> Configure high BER ports isolation mode.	
Syntax Description	mode	<ul style="list-style-type: none">• all - isolates switch-to-switch and switch-to-host unhealthy high-BER ports• switch-switch - isolates switch-to-switch unhealthy high-BER ports• switch-host - isolates switch-to-host unhealthy high-BER ports
Default	switch-switch	
Configuration Mode	config	
History	4.7.0	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm high-ber-ports isolate-high-ber isolation-mode switch-switch</pre>	
Related Commands	show ufm unhealthy-ports ufm unhealthy-ports isolate-high-ber enable	
Notes		

ufm unhealthy-ports isolate-high-ber enable

	ufm unhealthy-ports isolate-high-ber enable no ufm unhealthy-ports isolate-high-ber enable Enable automatically marking high-BER ports as unhealthy. The no form of the command stops automatically marking high-BER ports as unhealthy.	
Syntax Description	N/A	
Default	Disabled	
Configuration Mode	config	
History	4.6.0	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm unhealthy-ports isolate-high-ber enable</pre>	
Related Commands	show ufm unhealthy-ports	
Notes	Please stop UFM before performing attempting to change the event query interval value.	

ufm unhealthy-ports switch-ports-threshold

	ufm unhealthy-ports switch-ports-threshold <threshold> Configure the unhealthy switch ports event threshold	
Syntax Description	threshold	0-99 percent
Default	20%	
Configuration Mode	config	
History	4.12.0	

Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm unhealthy-ports switch-ports-threshold 30</pre>
Related Commands	show ufm unhealthy-ports
Notes	

ufm high-ber-ports enable-warnings

	<pre>ufm high-ber-ports enable-warnings no ufm high-ber-ports enable-warnings</pre> <p>Enables high BER ports warnings. The no form of the command disables the UFM high BER ports warnings.</p>
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	4.7.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm high-ber-ports enable-warnings</pre>
Related Commands	show ufm high-ber-ports
Notes	

show ufm unhealthy-ports

	show ufm unhealthy-ports Displays UFM unhealthy ports settings.	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.6.0	
	4.7.0	Updated output
Example	<pre> ufmapl [mgmt-ha-active] (config) # show ufm unhealthy-ports Enabled: No Isolation Mode: switch-switch Switch Ports Event Threshold: 20 percent </pre>	
Related Commands	ufm unhealthy-ports isolate-high-ber enable ufm unhealthy-ports isolate-high-ber isolation-mode	
Notes		

show ufm high-ber-ports

	show ufm high-ber-ports Displays high BER ports configuration.
Syntax Description	N/A
Default	N/A

Configuration Mode	Any configuration mode
History	4.7.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm high-ber-ports Enable Warnings: No</pre>
Related Commands	ufm high-ber-ports enable-warnings
Notes	

ufm network-fast-recovery enable

	ufm network-fast-recovery enable no ufm network-fast-recovery enable Enables UFM network fast recovery. The no form of the command disables UFM network fast recovery.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.12.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm network-fast-recovery enable</pre>
Related Commands	show ufm network-fast-recovery
Notes	

show ufm network-fast-recovery

	<code>show ufm network-fast-recovery</code> Displays UFM network fast recovery settings.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.12.0
Example	<pre>ufm-ap1 [mgmt-ha-active] (config) # show ufm network-fast-recovery Network Fast Recovery: No</pre>
Related Commands	<code>ufm network-fast-recovery enable</code>
Notes	

UFM Audit

ufm track-conf-changes enable

	ufm track-conf-changes enable no ufm track-conf-changes enable Enables UFM configuration changes tracking The no form of the command disables UFM configuration changes tracking	
Syntax Description	N/A	
Default	Enabled	
Configuration Mode	config	
History	4.8	First Release
	4.9	Modified command names as follows: <ul style="list-style-type: none">• From "ufm track-sm-conf-change enable" to "ufm track-conf-changes enable"• From "no ufm track-sm-conf-change enable" to "no ufm track-conf-changes enable"
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ufm track-conf-changes enable</pre>	
Related Commands	show ufm track-conf-changes	
Notes		

show ufm track-conf-changes

	show ufm track-conf-changes Displays UFM configuration changes tracking settings	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	config	
History	4.8	First release
	4.9	Modified command name from "show ufm track-sm-conf-change" to "show ufm track-conf-changes"
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm Track UFM configuration changes: No</pre>	
Related Commands	ufm track-conf-changes enable no ufm track-conf-changes enable	
Notes		

UFM Plugin Commands

ufm plugin

	<pre>ufm plugin <plugin-name> {add [tag <tag name>] enable remove} no ufm plugin <plugin-name> enable</pre> <p>Add UFM plugin manages UFM plugin. The no form of the command disables UFM plugin.</p>	
Syntax Description	add	Adds UFM plugin
	enable	Enables UFM plugin
	remove	Removes UFM plugin
Default	N/A	
Configuration Mode	config	
History	4.7	
Example	<pre>ufmapl [mgmt-sa] (config) # ufm plugin ndt add tag 1.0.0-3</pre>	
Related Commands	show ufm plugin	
Notes	<ul style="list-style-type: none"> • The plugin can be added, removed, enabled or disabled while UFM is running. • The plugin will be started upon UFM startup. • Disabling the plugin will only stop it. • Removing the plugin also clears all its folders and files (including conflagration and logs). 	

show ufm plugin

	<p>show ufm plugin</p> <p>Displays UFM plugin</p>
Syntax Description	N/A
Default	enabled
Configuration Mode	config
History	4.7
Example	<pre> ufmapl [mgmt-ha-active] (config) # show ufm plugin Plugin ndt: Enabled: Yes Plugin tag: latest Shared volumes: /opt/ufm/files/log:/log,/dev:/host_dev Httpd port: 8980 State: stop Plugin rest-rdma: Enabled: Yes Plugin tag: 1.0.0-5 Shared volumes: /opt/ufm/files/periodicIbdiagnet:/opt/ufm/files/ periodicIbdiagnet,/opt/ufm/files/log:/opt/ufm/files/log,/opt/ufm/files/ conf:/opt/ufm/files/conf Httpd port: NA State: stop </pre>
Related Commands	ufm plugin add, ufm plugin remove, ufm plugin enable, no ufm plugin enable
Notes	

Fabric Discovery

ufm discovered-switch-ip-version

	ufm discovered-switch-ip-version <ipv4/ipv6> show ufm discovered-switch-ip-version Sets the UFM discovered switch IP version (IPv4 or IPv6). Displays UFM discovered switch IP version.	
Syntax Description	ipv4	Discover switch IPv4 address
	ipv6	Discover switch IPv6 address
Default	IPv4	
Configuration Mode	config	
History	4.10.0	
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm discovered-switch-ip-version Discovered Switch IP Version: IPv4</pre>	
Related Commands		
Notes		

InfiniBand Commands

- [InfiniBand Utilities](#)
- [OpenSM](#)
- [InfiniBand Router](#)
- [NVIDIA SHARP](#)
- [Partition](#)
- [Switch Auto-provisioning](#)
- [Fabric Topology](#)
- [SA Key](#)
- [MKey](#)
- [HCA Commands](#)

InfiniBand Utilities

ib ibdiagnet

	Dib ibdiagnet [<ibdiagnet-options>] Scans the fabric using directed route packets and extracts all the available information regarding its connectivity and devices.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib ibdiagnet</pre>
Related Commands	

Notes	<ul style="list-style-type: none"> For further information on the command, please run "ib ibdiagnet --help". Running this command with the "upload" parameter uploads the last execution of the command.
-------	--

ib ibdiagnet gmp-window

	ib ibdiagnet gmp-window <value> no ib ibdiagnet gmp-window Set the maximum number of GMPs sent in parallel. The no form of the command resets the parameter to its default.	
Syntax Description	value	Range: 0-16384
Default	128	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # ib ibdiagnet gmp-window 10</pre>	
Related Commands	show ib ibdiagnet gmp-window	
Notes		

show ib ibdiagnet gmp-window

	show ib ibdiagnet gmp-window Displays the maximum number of GMPs sent in parallel.
Syntax Description	N/A

Default	N/A
Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # show ib ibdiagnet gmp-window 10</pre>
Related Commands	ib ibdiagnet gmp-window
Notes	

ib ibdiagnet smp-window

	ib ibdiagnet smp-window <value> no ib ibdiagnet smp-window Sets the maximum number of SMPs sent in parallel. The no form of the command resets the parameter to its default.	
Syntax Description	value	Range: 0-256
Default	8	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # ib ibdiagnet smp-window 10</pre>	
Related Commands	show ib ibdiagnet smp-window	
Notes		

show ib ibdiagnet smp-window

	show ib ibdiagnet smp-window Displays the maximum number of SMPs sent in parallel.	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	Any configuration mode	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # show ib ibdiagnet smp-window 10</pre>	
Related Commands	ib ibdiagnet smp-window	
Notes		

ib ibdiagnet upload

	ib ibdiagnet upload <upload-url> Uploads ibdiagnet output files to a remote host or a USB device.	
Syntax Description	upload-url	Formats supported: ftp, tftp, scp, sftp and usb. For example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-sa] (config) # ib ibdiagnet upload scp://root@10.10.1.11/tmp</pre>
Related Commands	
Notes	Prior to running this command, you must run the "ib ibdiagnet" command. For further information on the command, please run: "ib ibdiagnet --help".

ib ibdiagpath

	<p>ib ibdiagpath <ibdiagpath-options></p> <p>Scans the fabric using directed route packets and extracts all the available information regarding its connectivity and devices.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	<ul style="list-style-type: none"> • For further information on the command, please run "ib ibdiagpath --help". • Running this command with the "upload" parameter uploads the last execution of the command.

ib ibdiagpath upload

	ib ibdiagpath upload <upload-url> Uploads ibdiagpath output files to a remote host or a USB device.	
Syntax Description	upload-url	Formats supported: ftp, tftp, scp, sftp and usb. For example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ib ibdiagpath upload scp://root@10.10.1.11/tmp</pre>	
Related Commands		
Notes	Prior to running this command, you must run the command "ib ibdiagpath". For further information on the command, please run "ib ibdiagpath --help".	

ib perfquery

	ib perfquery <perfquery-options> Dumps (and optionally clears) the performance counters of the destination port (including error counters).
Syntax Description	N/A
Default	N/A
Configuration Mode	config

History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib perfquery --help".

ib ibtracert

	<p>ib ibtracert <ibtracert-options></p> <p>Displays unicast or multicast route from source to destination.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibtracert --help".

ib ibportstate

	<code>ib ibportstate <ibportstate-options></code> Gets the logical and physical port states of an InfiniBand port or disables or enables the port (only on a switch).
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibportstate --help".

ib smpquery

	<code>ib smpquery <smpquery-options></code> Enables a basic subset of standard SMP queries including the following: node info, node description, switch info, port info. Fields are displayed in human readable format.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5

Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib smpquery --help".

ib sminfo

	<pre>ib sminfo <sminfo-options></pre> <p>Queries the SMInfo attribute on a node.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib sminfo --help".

ib smpdump

	<code>ib smpdump <smpdump-options></code> A general purpose SMP utility which gets SM attributes from a specified SMA. The result is dumped in hex by default.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib smpdump --help".

ib ibqueryerrors

	<code>ib ibqueryerrors <ibqueryerrors-options></code> Queries and reports non-zero IB port counters.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5

Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibqueryerrors --help".

ib ibroute

	<pre>ib ibroute <ibroute-options></pre> <p>Displays unicast and multicast forwarding tables of the switches.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibroute --help".

ib ibrouters

	ib ibrouters <ibrouters-options> Shows InfiniBand router nodes in topology.	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	config	
History	3.0	
Example	<pre> ufm [mgmt-sa] (config) # ib routers Rt : 0xe41d2d030048dbf8 ports 3 "MFO;mlnx-switch15:MSB7780/RT" Rt : 0xe41d2d030048dc18 ports 3 "MFO;mlnx-switch18:MSB7780/RT" </pre>	
Related Commands		
Notes	For further information on the command, please run "ib ibrouters --help".	

ib ibnetdiscover

	ib ibnetdiscover [matching <expression> [count]] Assists to match more ibnetdiscover information.	
Syntax Description	matching	A matching expression in a form of a string to ease the information search
	count	The number of times the matching expression appears
Default	N/A	

Configuration Mode	config	
History	1.5	
	1.6	Updated the command's format and added new parameters
Example	<pre>ufmapl [mgmt-sa] (config) # ib ibnetdiscover</pre>	
Related Commands		
Notes	For further information on the command, please run "ib ibnetdiscover --help".	

ib ibnetdiscover upload

	ib ibnetdiscover upload <upload-url> Upload ibnetdiscover output file to a remote host or a USB device.	
Syntax Description	upload-url	Supported formats: ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-sa] (config) # ib ibnetdiscover upload scp://root@10.10.1.11/tmp</pre>	
Related Commands		
Notes	<ul style="list-style-type: none"> For further information on the command, please run "ib ibnetdiscover --help". Running this command with the "upload" parameter uploads the last execution of the command. 	

ib ibstat

	<code>ib ibstat <ibstat options></code> Shows the host adapters status.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibstat --help"

ib ibstatus

	<code>ib ibstatus <ibstatus-options></code> Queries basic status of InfiniBand device(s).
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5

Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibstatus --help"

ib ibnodes

	<p>ib ibnodes <ibnodes-options></p> <p>Scans the net or uses existing net topology file and lists all nodes.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibnodes --help"

ib saquery

	<code>ib saquery <saquery-options></code> Queries InfiniBand subnet administration attributes.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib saquery --help"

ib ibhosts

	<code>ib ibhosts [matching <expression> [count]]</code> Scans the net or uses existing net topology file and lists all hosts.	
Syntax Description	matching	A matching expression in a form of a string to ease the information search
	count	The number of times the matching expression appears
Default	N/A	
Configuration Mode	config	

History	1.5	
	1.6	Updated the command's format and added new parameters
Example	<pre>ufm [mgmt-sa] (config) #</pre>	
Related Commands		
Notes	For further information on the command, please run "ib ibhosts --help"	

ib ibswitches

	ib ibswitches [matching <expression> [count]] Scans the net or uses existing net topology file and lists all switches.	
Syntax Description	matching	A matching expression in a form of a string to ease the information search
	count	The number of times the matching expression appears
Default	N/A	
Configuration Mode	config	
History	1.5	
	1.6	Updated the command's format and added new parameters
Example	<pre>ufm [mgmt-sa] (config) #</pre>	
Related Commands		
Notes	For further information on the command, please run "ib ibswitches --help"	

ib iblinkinfo

	<code>ib iblinkinfo [<iblinkinfo-options>] [matching <expression>] [count]</code> Reports link info for each port in an IB fabric, node by node. Optionally, iblinkinfo can do partial scans and limit its output to parts of a fabric.	
Syntax Description	matching	A matching expression in a form of a string to ease the information search
	count	The number of times the matching expression appears
Default	N/A	
Configuration Mode	config	
History	1.5	
	1.6	Updated the command's format and added new parameters
Example	<pre>ufm [mgmt-sa] (config) #</pre>	
Related Commands		
Notes	For further information on the command, please run "ib iblinkinfo --help"	

ib vendstat

	<code>ib vendstat <vendstat-options></code> Uses vendor specific MADs to access beyond the IB spec vendor specific functionality.
Syntax Description	N/A
Default	N/A

Configuration Mode	config
History	1.5
Example	<pre>ufm [mgmt-sa] (config) #</pre>
Related Commands	
Notes	For further information on the command, please run "ib vendstat --help"

ib ibaddr

	<p><code>ib ibaddr <ibaddr options></code></p> <p>Shows the LID range and default GID of the target.</p>
Syntax Description	N/A
Default	The local port.
Configuration Mode	config
History	4.10.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib ibaddr GID fe80::c42:a103:74:f88e LID start 0x4 end 0x4</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibaddr --help"

ib ibping

	<code>ib ibping <ibping options></code> Uses vendor MADs to validate connectivity between InfiniBand nodes. On exit, (IP) ping-like output is shown.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.10.0
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ib ibping -c 3 5 --- (Lid 5) ibping statistics --- 3 packets transmitted, 0 received, 100% packet loss, time 3000 ms rtt min/avg/max = 0.000/0.000/0.000 ms</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibping --help"

ib ibsysstat

	<code>ib ibsysstat <ibsysstat options></code> Obtains basic information for the specific node which may be remote. This information includes: hostname, CPUs, memory utilization.
Syntax Description	N/A

Default	N/A
Configuration Mode	config
History	4.10.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib ibsysstat 5 sysstat ping succeeded</pre>
Related Commands	
Notes	For further information on the command, please run "ib ibsysstat --help"

ib smparquery

	<code>ib smparquery <smparquery options></code> Queries adaptive-routing related settings from a particular switch.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.10.0
Example	<pre>ufmapl [mgmt-ha-active] (config) # smparquery argrouptable 3 1</pre>
Related Commands	
Notes	For further information on the command, please run "ib smparquery --help"

OpenSM

ib qos

	ib qos [enable] Manages advanced SM QoS options.	
Syntax Description	enable	Enables advanced QoS management on this node
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmapl [mgmt-ha-active] (config) #</pre>	
Related Commands		
Notes		

ib sm allow-both-pkeys

	ib sm allow-both-pkeys no ib sm allow-both-pkeys Enables having both a full and limited membership on the same partition. The no form of the command disables having both full and limited memberships on the same partition.
Syntax Description	N/A

Default	Disabled
Configuration Mode	config
History	2.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm allow-both-pkeys</pre>
Related Commands	show ib sm allow-both-pkey ib partition management defmember
Notes	

show ib sm allow-both-pkeys

	show ib sm allow-both-pkeys Displays if both full and limited memberships on the same partition are enabled or not.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	2.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ib sm allow-both-pkeys disable</pre>
Related Commands	ib sm allow-both-pkeys
Notes	

ib sm ar-sl-mask

	ib sm ar-sl-mask <mask> no ib sm ar-sl-mask Configures the adaptive routing SL mask. The no form of the command rests the mask value to default.	
Syntax Description	mask	Range: 0x0000-0xffff
Default	0xffff	
Configuration Mode	config	
History	4.2.0	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sm ar-sl-mask 0xfffe</pre>	
Related Commands	show ib sm ar-sl-mask	
Notes		

show ib sm ar-sl-mask

	show ib sm ar-sl-mask Displays the adaptive routing SL mask.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.2.0

Example	<pre>UFM-APL [mgmt-ha-active] (config) # show ib sm ar-sl-mask 0xffff</pre>
Related Commands	ib sm ar-sl-mask
Notes	

ib sm configuration import

	<p>[no] ib sm configuration import [cn-guid congestion-control fts port-search-ordering guid-routing-order lid-matrix-dump prefix-routes held-back-sw opensm-health-policy-user-ext rch-policy hop-weights per-module-logging root-guid ids-guid partition-config-user-ext pgrp-policy sa-db io-guid port-prof-ignore topo-policy] <url></p> <p>Imports the Subnet Manager configuration. The no form of the command deletes the imported configuration files.</p>	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	config	
History	1.6	
	4.3.0	Added congestion-control parameter
Example	<pre>ufmapl [mgmt-ha-active] (config) #</pre>	
Related Commands	show ib sm configuration import	
Notes		

show ib sm configuration import

	<p>show ib sm configuration import</p> <p>Displays imported subnet manager configuration files.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre> ufmapl [mgmt-ha-active] (config) # show ib sm configuration import port_prof_ignore_file ----- hop_weights_file ----- port_search_ordering_file ----- mc_roots_file ----- lid_matrix_dump_file ----- lfts_file ----- root_guid_file ----- pgrp_policy_file ----- topo_policy_file ----- rch_policy_file ----- held_back_sw_file ----- cn_guid_file ----- io_guid_file ----- ids_guid_file ----- guid_routing_order_file ----- sa_db_file ----- per_module_logging_file ----- congestion_control_policy_file imported prefix_routes_file ----- router_policy_file ----- verbose_bypass_policy_file ----- sa_db_dump_file ----- subnet_lst_file ----- </pre>

	<pre>virt_dump_file ----- health-policy.conf.user_ext imported partitions.conf.user_ext imported</pre>
Related Commands	ib sm configuration import
Notes	

ib sm congestion-control

	<pre>ib sm congestion-control {enable ignore} no ib sm congestion-control enable</pre> <p>Configure congestion control. The no form of the command disables congestion control configuration.</p>	
Syntax Description	enable	Enables congestion control
	ignore	Ignores congestion control configuration
Default	Disabled	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # ib sm congestion-control enable</pre>	
Related Commands	show ib sm congestion-control	
Notes		

show ib sm congestion-control

	<p>show ib sm congestion-control</p> <p>Displays congestion control configuration.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # show ib sm congestion-control ignore</pre>
Related Commands	ib sm congestion-control
Notes	

ib sm dfp max-cas-on-spine

	<p>ib sm dfp max-cas-on-spine <int></p> <p>no ib sm dfp max-cas-on-spine</p> <p>Configures maximum number of CAs on the switch before it is considered a spine instead of leaf. The no form of the command resets the parameter to its default.</p>	
Syntax Description	int	Range: 1-126
Default	2	
Configuration Mode	config	

History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # ib sm dfp max-cas-on-spine 20</pre>
Related Commands	show ib sm dfp max-cas-on-spine
Notes	

show ib sm dfp max-cas-on-spine

	<p>show ib sm dfp max-cas-on-spine</p> <p>Displays maximum number of CAs on the switch before it is considered a spine instead of leaf.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # show ib sm dfp max-cas-on-spine 20</pre>
Related Commands	ib sm dfp max-cas-on-spine
Notes	

ib sm dfp down-up-turns-mode

	<code>ib sm dfp down-up-turns-mode {allow-in-intermediate-groups allow-turns-through-intermediate-spine disable}</code> Configures whether to allow turns through intermediate spine.
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # ib sm dfp down-up-turns-mode allow-in-intermediate-groups</pre>
Related Commands	<code>show ib sm dfp down-up-turns-mode</code>
Notes	

show ib sm dfp down-up-turns-mode

	<code>show ib sm dfp down-up-turns-mode</code> Displays mode of taking down up-turns in intermediate groups with DF+ routing engine.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.3.0

Example	<pre>ufm [mgmt-sa] (config) # show ib sm dfp down-up-turns-mode allow down up turns in intermediate groups</pre>
Related Commands	ib sm dfp down-up-turns-mode
Notes	

ib sm files opensm-dump delete

	<p>ib sm files opensm-dump delete</p> <p>Deletes OpenSM dump files.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.6.0
Example	<pre>ufm [mgmt-sa] (config) # ib sm files opensm-dump delete</pre>
Related Commands	
Notes	

ib sm force-log-flush

	ib sm force-log-flush [enable] Forces log flush after every write.	
Syntax Description	enable	Enables force log flush after every write
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ib sm force-log-flush enable</pre>	
Related Commands		
Notes		

ib sm force-link-speed

	ib sm force-link-speed Sets SM behavior for port speed on switch ports.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.6

Example	<pre>ufmapl [mgmt-ha-active] (config) #</pre>
Related Commands	
Notes	

ib sm keep-pkey-indexes

	<p>ib sm keep-pkey-indexes no ib sm keep-pkey-indexes</p> <p>Preserves PKey indexes belonging to the historical PKeys configured on the port when generating PKey tables for a certain port. The no form of the command calculates PKey indexes belonging to the historical PKeys configured on the port.</p>
Syntax Description	N/A
Default	Enabled
Configuration Mode	config
History	2.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # no ib sm keep-pkey-indexes</pre>
Related Commands	<p>show ib sm keep-pkey-indexes ib sm allow-both-pkeys</p>
Notes	

show ib sm keep-pkey-indexes

	<p>show ib sm keep-pkey-indexes</p> <p>Displays whether PKey indexes belonging to the historical PKeys configured on the port are preserved or not.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	2.6
Example	<pre>ufmap1 [mgmt-ha-active] (config) # show ib sm keep-pkey-indexes enable</pre>
Related Commands	ib sm keep-pkey-indexes
Notes	

ib sm log-flags

	<p>ib sm log-flags [all debug error frames funcs info none routing verbose]</p> <p>Configures all log-files.</p>	
Syntax Description	all	Error info verbose debug funcs frames routing
	debug	Logs diagnostic messages, high volume
	error	Logs error messages
	frames	Logs all SMP and GMP frames

	funcs	Logs function entry/exit, very high volume
	info	Logs basic messages, low volume
	none	Turns off all logging flags
	routing	Logs FDB routing information
	verbose	Logs interesting stuff, moderate volume
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmapl [mgmt-ha-active] (config) #</pre>	
Related Commands		
Notes		

show ib sm log

	show ib sm log [continuous files matching not]	
	Displays ib sm log event.	
Syntax Description	continuous	Displays new event log messages as they arrive
	files	Displays archived log files
	matching	Displays event logs that match a given regular expression
	not	Displays event logs that do not meet certain criteria
Default	N/A	
Configuration Mode	Any configuration mode	

History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) #</pre>
Related Commands	
Notes	

ib sm partition-config-merge

	<p>ib sm partition-config-merge Merges the partitions.conf.user_ext into the partitions.conf and starts the heavy sweep on the SM. To use after importing the specific file or importing all configuration files.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	2.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm partition-config-merge</pre>
Related Commands	ib sm configuration import partition-config-user-ext
Notes	The SM must be running for this command to work.

ib sm root-guid

	ib sm root-guid <guid> no ib sm root-guid <guid> Adds a root GUID for the SM. The no form of the command removes the GUID from the SM.	
Syntax Description	guid	The root GUID number in hexadecimal notation For example: 0x0002c903006ad830
Default	N/A	
Configuration Mode	config	
History	2.6	
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ib sm root-guid 0x0002c903006ad830</pre>	
Related Commands	show ib sm root-guid	
Notes	The list of root GUIDs are relevant when the routing algorithm is up-down or fat-tree.	

show ib sm root-guid

	show ib sm root-guid Displays all configured root GUIDs for the SM.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode

History	2.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ib sm root-guid 0x0002c903006ad830 0x0002c903006ae120 0x0002c903006af520</pre>
Related Commands	ib sm root-guid
Notes	

ib sm routing-engines

	ib sm routing-engines [dfsssp dor file ftree minhop torus-2QoS updn chain pqft] Sets the routing engine of the SM. Multiple routing engines can be specified separated by a space so that specific ordering of routing algorithms is tried if earlier routing engines fail.	
Syntax Description	dfsssp	Includes 'dfsssp' (EXPERIMENTAL) engine in selection of routing engines
	dor	Includes 'dor' engine in selection of routing engines
	file	Includes 'file' engine in selection of routing engines
	ftree	Includes 'ftree' engine in selection of routing engines
	minhop	Includes 'minhop' engine in selection of routing engines
	none	No routing engines specified; use SM default(s)
	sssp	Includes 'sssp' (EXPERIMENTAL) engine in selection of routing engines
	torus-2QoS	Includes 'torus-2QoS' engine in selection of routing engines
	updn	Includes 'updn' engine in selection of routing engines
	chain	Includes 'chain' engine in selection of routing engines
	pqft	

Default	N/A
Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) #</pre>
Related Commands	
Notes	

ib sm routing-threads-num

	ib sm routing-threads-num <int> no ib sm routing-threads-num Configures number of CPUs to use for parallel calculations. The no form of the command resets the parameter to its default.	
Syntax Description	int	Range: 1-8
Default	1	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufm [mgmt-sa] (config) # ib sm routing-threads-num 5</pre>	
Related Commands	show ib sm routing-threads-num	
Notes		

show ib sm routing-threads-num

	<code>show ib sm routing-threads-num</code> Displays number of CPUs configured to use for parallel calculations.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # show ib sm routing-threads-num 5</pre>
Related Commands	<code>ib sm routing-threads-num</code>
Notes	

ib sm scatter-ports

	<code>ib sm scatter-ports</code> Assigns ports in a random order instead of round-robin.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.6

Example	<pre>ufmapl [mgmt-ha-active] (config) #</pre>
Related Commands	
Notes	

ib sm smp-window

	ib sm smp-window <value> no ib sm smp-window Sets the maximum number of SMPs sent in parallel. The no form of the command resets this parameter to its default.	
Syntax Description	value	0-256
Default	8	
Configuration Mode	config	
History	2.6	
Example	<pre>UFM-APL (config) # ib sm smp-window 10</pre>	
Related Commands	show ib sm smp-windows	
Notes		

show ib sm smp-window

	<p>show ib sm smp-window</p> <p>Displays the maximum number of SMPs sent in parallel.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	2.6
Example	<pre> UFM-APL (config) # show ib sm smp-window 10 </pre>
Related Commands	ib sm smp-window
Notes	

ib sm ufm-events

	<p>ib sm ufm-events {all security}</p> <p>no ib sm ufm-events</p> <p>Configures which traps the SM sends to the UFM. The no form of the command configures that no traps are sent to the UFM (i.e. "none").</p>	
Syntax Description	all	Sends all traps to the UFM
	security	Sends security traps to the UFM only
Default	0xffff	

Configuration Mode	config
History	4.2.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sm ufm-events security</pre>
Related Commands	show ib sm ufm-events
Notes	

show ib sm ufm-events

	<p>show ib sm ufm-events</p> <p>Displays the types of traps configured to be sent to the UFM by the SM.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.2.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # show ib sm ufm-events Determines which Subnet Manager traps will be sent to UFM: security</pre>
Related Commands	ib sm ufm-events
Notes	

ib sm use-ucast-cache enable

	<code>ib sm use-ucast-cache enable</code> Allows SM to use cached routine data (LMC=0 only).
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) #</pre>
Related Commands	
Notes	

ib sm virtualization enable

	<code>ib sm virtualization enable</code> <code>no ib sm virtualization enable</code> Enables virtualization on all supported ports (default). The no form of the command disables virtualization on all supporting ports.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	2.6

Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sm virtualization enable</pre>
Related Commands	show ib sm virtualization
Notes	It is not possible to modify the virtualization support in case OpenSM or UFM are running.

ib sm virtualization ignore

	<pre>ib sm virtualization ignore</pre> <p>No virtualization support.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	2.6
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sm virtualization ignore</pre>
Related Commands	show ib sm virtualization
Notes	It is not possible to modify the virtualization support in case OpenSM or UFM are running.

show ib sm virtualization

	show ib sm virtualization Displays virtualization support.	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	config	
History	2.6	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # show ib sm virtualization ignore</pre>	
Related Commands	ib sm virtualization enable ib sm virtualization ignore	
Notes		

ib sm virt-max-ports-in-process

	ib sm virt-max-ports-in-process <value> no ib sm virt-max-ports-in-process Sets the maximum number of ports to be processed simultaneously. The no form of the command resets this parameter to its default.	
Syntax Description	value	Range: 1-65535
Default	64	
Configuration Mode	config	

History	2.6
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sm virt-max-ports-in-process 20</pre>
Related Commands	show ib sm virt-max-ports-in-process
Notes	

show ib sm virt-max-ports-in-process

	<p>show ib sm virt-max-ports-in-process</p> <p>Displays the maximum number of ports to be processed simultaneously.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	2.6
Example	<pre>UFM-APL (config) # show ib sm virt-max-ports-in-process 20</pre>
Related Commands	ib sm virt-max-ports-in-process
Notes	

ufm multi-port-sm

	<code>ufm multi-port-sm enable</code> <code>ufm multi-port-sm ha-enable</code> <code>no ufm multi-port-sm enable</code> Enables configuring OpenSM with multiple GUIDs. The no form of the command disables configuring OpenSM with multiple GUIDs.
Syntax Description	<code>enable</code> - enables configuring OpenSM with multiple GUIDs <code>ha-enable</code> - enables multi-port SM with high availability
Default	Disabled
Configuration Mode	config
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # ufm multi-port-sm enable</pre>
Related Commands	<code>show ufm multi-port-sm</code>
Notes	

show ufm multi-port-sm

	<code>show ufm multi-port-sm</code> Displays whether configuring OpenSM with multiple GUIDs is enabled.
Syntax Description	N/A
Default	N/A

Configuration Mode	Any configuration mode
History	4.3.0
Example	<pre>ufm [mgmt-sa] (config) # show ufm multi-port-sm Enable</pre>
Related Commands	ufm multi-port-sm enable
Notes	

ufm sm-static-lid

	<p>ufm sm-static-lid <1-49151> no ufm sm-static-lid</p> <p>Sets a static SM LID to be used by the SM. The no form of the command resets the static SM LID to default.</p>
Syntax Description	N/A
Default	Assigned by the SM
Configuration Mode	config
History	4.5.0
Example	<pre>ufm [mgmt-sa] (config) # ufm sm-static-lid 20</pre>
Related Commands	show ufm sm-static-lid
Notes	

show ufm sm-static-lid

	show ufm sm-static-lid Displays the static SM LID.	
Syntax Description	N/A	
Default	Assigned by the SM	
Configuration Mode	Any configuration mode	
History	4.5.0	
Example	<pre>ufm [mgmt-sa] (config) # show ufm sm-static-lid Static SM LID: 20</pre>	
Related Commands	ufm sm-static-lid	
Notes		

InfiniBand Router

ib router set-num-of-subnets

	ib router set-num-of-subnets <command-options> Configures system profile to InfiniBand, allowing multiple switch IDs.	
Syntax Description	hostname	IB router hostname or IP address
	username	IP router username

	password	IB router user password
	num-of-subnets	Specified number of subnets (AKA SWIDs) to be initialized by the system. Range: 2-6.
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib router set-num-of-subnets -- hostname 10.10.1.12 --username admin --password admin --num-of-subnets 6</pre>	
Related Commands		
Notes	As a result of running this command, reboot is performed and all configuration is removed.	

ib router add-interfaces-to-subnet

	ib router add-interfaces-to-subnet <command-options> Maps an interface to a subnet and enables it.	
Syntax Description	hostname	IB router hostname or IP address
	username	IP router username
	password	IB router user password
	interface interface-range	Single IB interface or range of IB interfaces. Single IB interface: 1/<interface> Range of IB interfaces: 1/<interface>-1/<interface>
	subnet	Name of IB subnet (i.e. SWID): infiniband-default, infiniband-1...infiniband-5
Default	N/A	
Configuration Mode	config	

History	1.6
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib router add-interfaces-to-subnet --hostname 10.10.1.12 --username admin --password admin --interface 1/1-1/6 --subnet infiniband-1</pre>
Related Commands	
Notes	

ib router remove-interfaces-from-subnet

	ib router remove-interfaces-from-subnet <command-options> Unmaps an interface from a subnet after it has been disabled.	
Syntax Description	hostname	IB router hostname or IP address
	username	IP router username
	password	IB router user password
	interface interface-range	Single IB interface or range of IB interfaces. Single IB interface: 1/<interface> Range of IB interfaces: 1/<interface>-1/<interface>
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib router remove-interfaces-from- subnet --hostname 10.10.1.12 --username admin --password admin -- interface 1/6</pre>	

Related Commands	
Notes	

ib router add-subnet-to-router

	ib router add-subnet-to-router <command-options> Creates routing on IB subnet interface and enables routing on that interface.	
Syntax Description	hostname	IB router hostname or IP address
	username	IP router username
	password	IB router user password
	subnet	Name of IB subnet (i.e. SWID): infiniband-default, infiniband-1...infiniband-5
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre> UFM-APL [mgmt-ha-active] (config) # ib router add-subnet-to-router -- hostname 10.10.1.12 --username admin --password admin --subnet infiniband-3 </pre>	
Related Commands		
Notes	As a result of running his command, the set of commands that allow control of IB router functionality will be enabled.	

ib router remove-subnet-from-router

	ib router remove-subnet-from-router <command-options> Destroys routing on IB subnet interface after routing on that interface has been disabled.	
Syntax Description	hostname	IB router hostname or IP address
	username	IP router username
	password	IB router user password
	subnet	Name of IB subnet (i.e. SWID): infiniband-default, infiniband-1...infiniband-5
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib router remove-subnet-from-router --hostname 10.10.1.12 --username admin --password admin --subnet infiniband-default</pre>	
Related Commands		
Notes		

ib router set-ufm-sm-router-support

	ib router set-ufm-sm-router-support <command-options> Configures OpenSM with IB subnet prefix.	
--	--	--

Syntax Description	-c <subnet prefix>]	Configure new IB subnet prefix. Should be followed by new IB router subnet prefix value.
	-r	Reset to default
	-h	Show help
Default	N/A	
Configuration Mode	config	
History	1.6	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib router set-ufm-sm-router-support -c 0xfec0000000001234</pre>	
Related Commands		
Notes	<ul style="list-style-type: none"> • -c <subnet prefix> is used for updating OpenSM configuration file with new subnet prefix and forces OpenSM to re-read configuration • -r is used for resetting OpenSM configuration to default value and canceling IB routing 	

NVIDIA SHARP

- [SHARP Aggregation Manager](#)
- [SHARP Configuration in OpenSM](#)
- [SHARP API](#)

SHARP Aggregation Manager

ib sharp enable

	<code>ib sharp enable</code> <code>no ib sharp enable</code> Enables NVIDIA® Scalable Hierarchical Aggregation and Reduction Protocol (SHARP)™. The no form of the command disables NVIDIA SHARP.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.6
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sharp enable</pre>
Related Commands	<code>show ib sharp</code>
Notes	

ib sharp allocation enable

	<code>ib sharp allocation enable</code> <code>no ib sharp allocation enable</code> Enables NVIDIA SHARP allocation reservation. The no form of the command disables NVIDIA SHARP allocation reservation.
--	--

Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.3.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sharp allocation enable</pre>
Related Commands	show ib sharp
Notes	

ib sharp job-pkey-on-tree enable

	<p>ib sharp job-pkey-on-tree enable no ib sharp job-pkey-on-tree enable</p> <p>Enable setting job PKEY on the aggregation tree allocated for the job. The no form of the command disables setting job PKEY on the aggregation tree allocated for the job.</p>
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	4.5.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sharp job-pkey-on-tree enable</pre>
Related Commands	show ib sharp
Notes	

ib sharp smx-protocol

	<pre>ib sharp smx-protocol {sockets ucx} no ib sharp smx-protocol</pre> <p>Configures network protocol to be used by SMX. The no form of the command resets this parameter to its default value.</p>
Syntax Description	N/A
Default	sockets
Configuration Mode	config
History	4.3.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sharp smx-protocol ucx</pre>
Related Commands	show ib sharp
Notes	

ib sharp smx-sock-interface

	<pre>ib sharp smx-sock-interface {eth0 eth1} no ib sharp smx-sock-interface</pre> <p>Sets the socket interface to be used by SMX. The no form of the command resets this parameter to its default value.</p>
Syntax Description	N/A
Default	The first interface found in UP state is used
Configuration Mode	config

History	1.6	First release
	4.5.0	Updated command from <code>ib sharp interface</code> to <code>ib sharp smx-sock-interface</code>
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sharp smx-sock-interface eth0</pre>	
Related Commands	show ib sharp	
Notes		

ib sharp smx-sock-port

	<pre>ib sharp smx-sock-port <1-65535> no ib sharp smx-sock-port</pre> <p>Sets the socket port to be used by SM The no form of the command resets this parameter to its default value.</p>	
Syntax Description	N/A	
Default	6126	
Configuration Mode	config	
History	1.6	First release
	4.5.0	Updated command from <code>ib sharp port</code> to <code>ib sharp smx-sock-port</code>
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sharp smx-sock-interface 636</pre>	
Related Commands	show ib sharp	
Notes		

ib sharp smx-ucx-interface

	<pre>ib sharp smx-ucx-interface {ib0 ib1} no ib sharp smx-ucx-interface</pre> <p>Sets the UCX interface to be used by SMX. The no form of the command resets this parameter to its default value.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.5.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sharp smx-ucx-interface ib0</pre>
Related Commands	show ib sharp
Notes	

ib sharp topology-api enable

	<pre>ib sharp topology-api enable no ib sharp topology-api enable</pre> <p>Enables the SHARP topology API. The no form of the command disables NVIDIA SHARP topology API.</p>
Syntax Description	N/A
Default	Disabled
Configuration Mode	config

History	4.5.1
Example	<pre>ufm-apl [mgmt-ha-active] (config) # ib sharp topology-api enable</pre>
Related Commands	show ib sharp
Notes	

show ib sharp

	<p>show ib sharp</p> <p>Displays the configuration of NVIDIA SHARP Aggregation Manager.</p>	
Syntax Description	N/A	
Default	N/A	
Configuration Mode	config	
History	1.6	
	4.3.0	Updated output
	4.5.0	Updated output
	4.5.1	Updated output
Example	<pre>ufm-apl [mgmt-ha-active] (config) # show ib sharp SHArP Aggregation Manager: Enabled: No Allocation: No SMX socket interface: default SMX UCX interface: default</pre>	

	<pre> SMX socket port: 6126 SMX protocol: sockets Job PKEY on tree: No Topology API: No </pre>
Related Commands	
Notes	

show ib sharp log

	<pre> show ib sharp log </pre> <p>Displays NVIDIA SHARP log file in a scrollable pager.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.6.0
Example	<pre> ufm-apl [mgmt-ha-active] (config) # show ib sharp log </pre>
Related Commands	
Notes	

show ib sharp log continuous

	<code>show ib sharp log continuous</code> Displays new NVIDIA SHARP log messages as they happen.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.6.0
Example	<pre>ufm-apl [mgmt-ha-active] (config) # show ib sharp log continuous</pre>
Related Commands	
Notes	

show ib sharp log files

	<code>show ib sharp log files</code> Displays archived log files.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.6.0

Example	<pre>ufm-apl [mgmt-ha-active] (config) # show ib sharp log files</pre>
Related Commands	
Notes	

show ib sharp log matching

	<p><code>show ib sharp log matching <reg-exp></code></p> <p>Display NVIDIA SHARP logs that match a given regular expression.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.6.0
Example	<pre>ufm-apl [mgmt-ha-active] (config) # show ib sharp log matching error</pre>
Related Commands	
Notes	

show ib sharp log not matching

	<code>show ib sharp log not matching <reg-exp></code> Display NVIDIA SHARP logs that do not match a given regular expression.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.6.0
Example	<pre>ufm-apl [mgmt-ha-active] (config) # show ib sharp log not matching error</pre>
Related Commands	
Notes	

SHARP Configuration in OpenSM

ib sm sharp enable

	<code>ib sm sharp enable</code> <code>no ib sm sharp enable</code> Enables NVIDIA® Scalable Hierarchical Aggregation and Reduction Protocol (SHARP)™ on all supporting switches. The no form disables NVIDIA SHARP on all supporting switches.
Syntax Description	N/A
Default	N/A

Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm sharp enable</pre>
Related Commands	show ib sm sharp
Notes	It is not possible to modify the NVIDIA SHARP support parameter in case OpenSM is running.

ib sm sharp ignore

	<p>ib sm sharp ignore</p> <p>No NVIDIA SHARP support. This command does not change the current switch configuration. If NVIDIA SHARP is enabled on the switch, it will remain enabled. If it is disabled on the switch, it will remain disabled.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.6
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib sm sharp ignore</pre>
Related Commands	show ib sm sharp
Notes	It is not possible to modify the NVIDIA SHARP support parameter in case OpenSM is running.

show ib sm sharp

	<code>show ib sm sharp</code> Displays NVIDIA SHARP support.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre>UFM-APL [mgmt-ha-active] (config) # show ib sm sharp ignore</pre>
Related Commands	<code>ib sm sharp enable</code> <code>ib sm sharp ignore</code>
Notes	

SHARP API

ufm sharp-api event-query-interval

	<code>ufm sharp-api event-query-interval <value></code> <code>no ufm sharp-api event-query-interval</code> Configure SHARP API event query interval in seconds. The no form of the command resets this value to its default.
--	---

Syntax Description	value	Range: 1-1000 seconds
Default	5 seconds	
Configuration Mode	config	
History	4.6.0	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ufm sharp-api event-query- interval 10</pre>	
Related Commands	show ufm sharp-api	
Notes	Please stop UFM before performing attempting to change the event query interval value.	

ufm sharp-api event-query-retries

	ufm sharp-api event-query-retries <value> no ufm sharp-api event-query-retries Configure SHARP API event query retries. The no form of the command resets this value to its default.	
Syntax Description	value	Range: 1-1000
Default	3	
Configuration Mode	config	
History	4.6.0	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ufm sharp-api event-query- retries 11</pre>	
Related Commands	show ufm sharp-api	

Notes	Please stop UFM before performing attempting to change the event query interval value.
-------	--

show ufm sharp-api

	<p>show ufm sharp-api</p> <p>Displays UFM SHARP API settings</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.6.0
Example	<pre> UFM-APL [mgmt-ha-active] (config) # show ufm sharp-api Event query retries : 3 Event query interval : 5 </pre>
Related Commands	<p>ufm sharp-api event-query-interval</p> <p>ufm sharp-api event-query-retries</p>
Notes	

Partition

ib partition management defmember

	ib partition management defmember <type> no ib partition management defmember Sets the default membership for the management IB partition (default PKEY). The no form of the command resets the parameter to its default value.	
Syntax Description	type	<ul style="list-style-type: none"> • full - full membership • limited - limited membership • both - both full and limited membership
Default	Full membership	
Configuration Mode	config	
History	1.6	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib partition management defmember limited</pre>	
Related Commands	show ib partition	
Notes	<ul style="list-style-type: none"> • The defmember setting controls the ability of end nodes to communicate over the management partition • It is not possible to modify the defmember in case OpenSM or UFM are running 	

show ib partition

	<p>show ib partition</p> <p>Displays partition information.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre>UFM-APL [mgmt-ha-active] (config) # show ib partition management: Default membership: full MTU limit: 2KB</pre>
Related Commands	ib partition management defmember
Notes	N/A

ib partition management mtu-limit <2K|4K>

	<p>ib partition management mtu-limit <2K 4K></p> <p>no ib partition management mtu-limit <2K 4K></p> <p>Sets the MTU limit for the default partition. The no form of the command reset the MTU limit for the default partition to default.</p>	
Syntax Description	mtu-limit	2K 4K

Default	
Configuration Mode	config
History	4.12.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # no ib partition management mtu-limit 4K</pre>
Related Commands	N/A
Notes	N/A

Switch Auto-provisioning

ib managed-switch image ppc fetch

	<p>ib managed-switch image ppc fetch <download-url> no ib managed-switch image ppc</p> <p>Downloads a PPC switch image file from a remote host or a USB device. The no form deletes the PPC switch image file from the hard disk.</p>	
Syntax Description	download-url	The URL path from where the image file can be downloaded. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/ filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmap1 [mgmt-ha-active] (config) # ib managed-switch image ppc fetch scp:// root@10.10.32.12/tmp/image-PPC_M460EX-3.6.3130.img Password (if required): ***** 100.0%[#####]</pre>
Related Commands	
Notes	<ul style="list-style-type: none"> • If the downloaded image file is invalid (not an image file/has wrong architecture), it will be deleted from the hard disk. • The last file downloaded will always overwrite the existing file.

ib managed-switch image x86 fetch

	<p>ib managed-switch image x86 fetch <download-url> no ib managed-switch image x86</p> <p>Downloads a x86 switch image file from a remote host or a USB device. The no form deletes the x86 switch image file from the hard disk.</p>	
Syntax Description	download-url	The URL path from where the image file can be downloaded. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/ filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ib managed-switch image x86 fetch scp:// root@10.10.32.12/tmp/image-X86_64-3.6.3130.img Password (if required): ***** 100.0%[#####]</pre>	

Related Commands	
Notes	<ul style="list-style-type: none"> • If the downloaded image file is invalid (not an image file/has wrong architecture), it will be deleted from the hard disk. • The last file downloaded will always overwrite the existing file.

ib managed-switch configuration global fetch

	<p>ib managed-switch configuration global fetch <download-url> no ib managed-switch configuration global</p> <p>Downloads a global switch configuration file from a remote host or a USB device. The no form deletes the global switch configuration file from the hard disk.</p>	
Syntax Description	download-url	The URL path from where the image file can be downloaded. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ib managed-switch configuration global fetch scp://root@10.10.32.12/tmp/global_running_config.txt Password (if required): ***** 100.0%[#####]</pre>	
Related Commands		
Notes	The last file downloaded will always overwrite the existing file.	

ib managed-switch list fetch

	ib managed-switch list fetch <download-url> no ib managed-switch list Downloads a switch list file from a remote host or a USB device. The no form deletes the switch list file from the hard disk.	
Syntax Description	download-url	The URL path from where the image file can be downloaded. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre> ufmap1 [mgmt-ha-active] (config) # ib managed-switch list fetch scp:// root@10.10.32.12/tmp/switch_ips.txt Password (if required): ***** 100.0%[#####] </pre>	
Related Commands		
Notes	The last file downloaded will always overwrite the existing file.	

ib managed-switch settings fetch

	ib managed-switch settings fetch <download-url> Downloads a switch-auto-provisioning-settings file from a remote host or a USB device.	
--	---	--

Syntax Description	download-url	The URL path from where the image file can be downloaded. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ib managed-switch settings fetch scp:// root@10.10.32.12/tmp/switch_auto_provisioning.ini Password (if required): ***** 100.0%[#####]</pre>	
Related Commands		
Notes	The last file downloaded will always overwrite the existing file.	

ib managed-switch settings upload

	ib managed-switch settings upload <upload-url> Uploads the switch-auto-provisioning-settings file to a remote host or a USB device.	
Syntax Description	upload-url	The URL path from where the image file can be uploaded. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	1.5	

Example	<pre>ufmapl [mgmt-ha-active] (config) # ib managed-switch settings upload scp:// root@10.10.32.12/tmp/switch_auto_provisioning.ini Password (if required): *****</pre>
Related Commands	
Notes	

ib managed-switch settings admin-password

	<p>ib managed-switch settings admin-password <password> no ib managed-switch settings admin-password</p> <p>Sets the admin password to use with switch auto provisioning. The no form resets the admin password used for switch auto provisioning to its default.</p>	
Syntax Description	password	The admin password to use with switch auto provisioning
Default	admin	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib managed-switch settings admin- password Password: ***** Confirm: ***** ufmapl [mgmt-ha-active] (config) #</pre>	
Related Commands		

Notes	The password argument can either be provided as a clear text, or as encrypted text.
-------	---

ib managed-switch settings reboot-timeout

	ib managed-switch settings reboot-timeout <time> no ib managed-switch settings reboot-timeout Sets the reboot timeout to use with switch auto-provisioning. The no form of the command restores to default.	
Syntax Description	time	Switch reboot timeout. Range: 10-180 minutes.
Default	30	
Configuration Mode	config	
History	1.5	
Example	<pre>ufmap1 [mgmt-ha-active] (config) # ib managed-switch settings reboot- timeout 60</pre>	
Related Commands	show ib managed-switch settings	
Notes		

ib managed-switch settings upgrade-both-partitions

	<code>ib managed-switch settings upgrade-both-partitions</code> <code>no ib managed-switch settings upgrade-both-partitions</code> Upgrades both boot partitions as part of switch auto-provisioning. The no form of the command upgrades only one boot partition.
Syntax Description	N/A
Default	<code>upgrade-both-partitions</code>
Configuration Mode	<code>config</code>
History	1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib managed-switch settings upgrade-both-partitions</pre>
Related Commands	<code>show ib managed-switch settings</code>
Notes	

ib managed-switch auto-provisioning start

	<code>ib managed-switch auto-provisioning start</code> <code>no ib managed-switch auto-provisioning start</code> Starts the switch auto provisioning process. The no form stops the switch auto provisioning process.
Syntax Description	N/A
Default	N/A

Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib managed-switch auto-provisioning start</pre>
Related Commands	
Notes	

show ib managed-switch settings

	<p><code>show ib managed-switch settings</code></p> <p>Displays the switch auto provisioning settings.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ib managed-switch settings Switch List: Loaded Software Image X86: 3.6.3130 Software Image PPC: 3.6.3130 Global Configuration File: Loaded SNMP Community: mlnxpublic</pre>

	<pre> Admin Password: Default Password set Reboot Timeout 30 Upgrade Both Boot Partitions Yes </pre>
Related Commands	
Notes	

show ib managed-switch auto-provisioning status

	<pre> show ib managed-switch auto-provisioning status </pre> <p>Displays switch auto provisioning status and progress.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre> ufmap1 [mgmt-ha-active] (config) # show ib managed-switch auto-provisioning status Started: 2017-03-15 08:00:30 UTC Status: Completed IP Address TAG SW Upgrade Configuration ----- - 10.10.37.84 MT1452X05493 Updated Updated 10.10.37.85 leaf01 Up-to-Date Not-Required </pre>
Related Commands	

Notes	
-------	--

show ib managed-switch list

	<p>show ib managed-switch list</p> <p>Displays the content of the switch list file.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.5
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ib managed-switch list 10.10.37.84 10.10.37.85,leaf01</pre>
Related Commands	
Notes	

Fabric Topology

ib topo-file generate

	ib topo-file generate Generates a fabric topology file and if relevant, generates IBNL files.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib topo-file generate</pre>
Related Commands	ib topo-file upload
Notes	

ib topo-file upload

	ib topo-file upload <upload-url> Uploads the fabric topology file to a remote host or a USB device.	
Syntax Description	upload-url	Upload URL. Supported protocols: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	

Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib topo-file upload scp:// root@192.168.1.100/tmp Password (if required): *****</pre>
Related Commands	ib topo-file generate
Notes	The fabric topology file name is fabric.topo.

ib fabric-split generate

	ib fabric-split generate <num-of-groups> [refresh-topology] Generates an archive file containing ibdiagnet scope files.	
Syntax Description	num-of-groups	Number of groups for fabric division. Range: 2-10.
	refresh-topology	Re-discover the IB fabric before division
Default	N/A	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib fabric-split generate 3</pre>	
Related Commands	ib fabric-split upload	
Notes		

ib fabric-split upload

	ib fabric-split upload <upload-url> Uploads the fabric split archive file to a remote host or a USB device.	
Syntax Description	upload-url	Upload URL. Formats supported: http, https, ftp, tftp, scp, sftp and usb. Example: scp://username[:password]@hostname/path/filename, usb:/path/filename.
Default	N/A	
Configuration Mode	config	
History	4.3.0	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib fabric-split upload scp:// root@10.10.1.11/tmp</pre>	
Related Commands	ib fabric-split generate	
Notes		

ib fabric-split delete

	ib fabric-split delete Deletes a fabric split archive file from the drive.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	4.3.0

Example	<pre>ufmapl [mgmt-ha-active] (config) # ib fabric-split delete</pre>
Related Commands	ib fabric-split generate
Notes	

SA_Key

- [SAETM](#)
- [UFM Configuration](#)

SAETM

ib sm sa-enhanced-trust-model

	<pre>ib sm sa-enhanced-trust-model no ib sm sa-enhanced-trust-model</pre> <p>Enables the SA Enhanced Trust Model (SAETM). The no form of the command disables the SAETM.</p>
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	1.6

Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm sa-enhanced-trust-model</pre>
Related Commands	<code>show ib sm sa-enhanced-trust-model</code>
Notes	

ib sm sa-etm-max-num-event-subs

	<code>ib sm sa-etm-max-num-event-subs <event-subscriptions></code> <code>no ib sm sa-etm-max-num-event-subs</code> Sets the SAETM maximum number of event subscriptions. The no form of the command resets to the default value.	
Syntax Description	event-subscriptions	SAETM maximum number of event subscriptions. Range: 1-4294967295; 0=unlimited.
Default	32	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm sa-etm-max-num-event-subs 64</pre>	
Related Commands	<code>show ib sm sa-etm-max-num-event-subs</code>	
Notes		

ib sm sa-etm-max-num-mcast-groups

	ib sm sa-etm-max-num-mcast-groups <multicast-groups> no ib sm sa-etm-max-num-mcast-groups Sets the SAETM maximum number of multicast groups. The no form of the command resets to the default value.	
Syntax Description	multicast-groups	SAETM maximum number of multicast groups. Range: 1-4294967295; 0=unlimited.
Default	128	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm sa-etm-max-num-mcast-groups 256</pre>	
Related Commands	show ib sm sa-etm-max-num-mcast-groups	
Notes		

ib sm sa-etm-max-num-services

	ib sm sa-etm-max-num-services <number-of-services> no ib sm sa-etm-max-num-services Sets the SAETM maximum number of services. The no form of the command resets to the default value.	
Syntax Description	number-of-services	SAETM maximum number of services Range: 1-4294967295; 0=unlimited.
Default	32	

Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm sa-etm-max-num-services 64</pre>
Related Commands	show ib sm sa-etm-max-num-services
Notes	

show ib sm sa-enhanced-trust-model

	<pre>show ib sm sa-enhanced-trust-model</pre> <p>Displays the SA enhanced trust model (SAETM) state.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ib sm sa-enhanced-trust-model disable</pre>
Related Commands	ib sm sa-enhanced-trust-model
Notes	

show ib sm sa-etm-max-num-event-subs

	<code>show ib sm sa-etm-max-num-event-subs</code> Displays the SAETM maximum number of event subscriptions.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre>ufmap1 [mgmt-ha-active] (config) # show ib sm sa-etm-max-num-event-subs 32</pre>
Related Commands	<code>ib sm sa-etm-max-num-event-subs</code>
Notes	

show ib sm sa-etm-max-num-mcast-groups

	<code>show ib sm sa-etm-max-num-mcast-groups</code> Displays the SAETM maximum number of multicast groups.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6

Example	<pre>ufmap1 [mgmt-ha-active] (config) # show ib sm sa-etm-max-num-mcast-groups 128</pre>
Related Commands	<code>ib sm sa-etm-max-num-mcast-groups</code>
Notes	

show ib sm sa-etm-max-num-services

	<code>show ib sm sa-etm-max-num-services</code> Displays the SAETM maximum number of services.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre>ufmap1 [mgmt-ha-active] (config) # show ib sm sa-etm-max-num-services 32</pre>
Related Commands	<code>ib sm sa-etm-max-num-services</code>
Notes	

UFM Configuration

ufm randomize-sa-key

	<code>ufm randomize-sa-key</code> <code>no ufm randomize-sa-key</code> Enables SA key randomization. The no form disables the SA key randomization.
Syntax Description	N/A
Default	N/A
Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm randomize-sa-key</pre>
Related Commands	<code>show ufm randomize-sa-key</code>
Notes	

show ufm randomize-sa-key

	<code>show ufm randomize-sa-key</code> Displays the state of the SA key randomization (Enabled/Disabled).
Syntax Description	N/A
Default	N/A

Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm randomize-sa-key disable</pre>
Related Commands	ufm randomize-sa-key
Notes	

MKey

ufm mkey-per-port

	ufm mkey-per-port no ufm mkey-per-port Enables MKey per port enforcement. The no form of the command disables the feature.
Syntax Description	N/A
Default	Disabled
Configuration Mode	config
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm mkey-per-port</pre>

Related Commands	show ufm mkey-per-port
Notes	

show ufm mkey-per-port

	<pre>show ufm mkey-per-port</pre> <p>Displays MKey per port enforcement state.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm mkey-per-port disable</pre>
Related Commands	ufm mkey-per-port
Notes	

ufm mkey-global-seed

	<pre>ufm mkey-global-seed <seed> no ufm mkey-global-seed</pre> <p>Sets the seed for the global MKey used by SM. The no form of the command resets the seed for the global MKey to the default value.</p>
--	--

Syntax Description	seed	Global MKey used by SM. Format: 64-bit hexadecimal. Example: 0x000000000a12c30.
Default	0x0000000000000000	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ufm mkey-global-seed 0x000000000a12c30</pre>	
Related Commands	show ufm mkey-global-seed	
Notes		

show ufm mkey-global-seed

	<pre>show ufm mkey-global-seed</pre> <p>Displays the seed for the global MKey used by SM.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6
Example	<pre>ufmapl [mgmt-ha-active] (config) # show ufm mkey-global-seed 0x0000000000000000</pre>
Related Commands	ufm mkey-global-seed
Notes	

ib sm mkey-lease-period

	<code>ib sm mkey-lease-period <time></code> <code>no ib sm mkey-lease-period</code> Sets the lease period used when MKey is non-zero. The no form on the command resets the MKey lease period to the default value.	
Syntax Description	time	Lease period used when MKey is non-zero. Range: 1-65535 seconds; 0=unlimited.
Default	60 seconds	
Configuration Mode	config	
History	1.6	
Example	<pre>ufmapl [mgmt-ha-active] (config) # ib sm mkey-lease-period 90</pre>	
Related Commands	show ib sm mkey-lease-period	
Notes		

show ib sm mkey-lease-period

	<code>show ib sm mkey-lease-period</code> Displays the MKey lease period.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	1.6

Example	<pre>ufmapl [mgmt-ha-active] (config) # show ib sm mkey-lease-period 90</pre>
Related Commands	ib sm mkey-lease-period
Notes	

HCA Commands

ib hca-smp-window

	ib hca-smp-window <value> no ib hca-smp-window Sets the maximum number of SMPs sent in HCA. The no form of the command resets this parameter to its default.	
Syntax Description	value	Range: 0-256
Default	128	
Configuration Mode	config	
History	4.4.0	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib hca-smp-window 128</pre>	
Related Commands	show ib hca-smp-window	
Notes	UFM system must be rebooted to apply the new configuration	

ib hca-vl15-window

	ib hca-vl15-window <value> no ib hca-vl15-window Sets the HCA VL15 port receive buffer size. The no form of the command resets this parameter to its default.	
Syntax Description	value	1,2,4,8,16,32,64,128
Default	1	
Configuration Mode	config	
History	4.4.0	
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ib hca-vl15-window 1</pre>	
Related Commands	show ib hca-vl15-window	
Notes	UFM system must be rebooted to apply the new configuration	

ufm hca-grouping enable

	ufm hca-grouping enable no ufm hca-grouping enable Enables HCA grouping. The no form of the command disables HCA grouping.	
Syntax Description	N/A	
Default	Disabled	

Configuration Mode	config
History	4.5.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # ufm hca-grouping enable WARNING. Enabling multi-NIC grouping will cause reset of your fabric network configuration (PKEY and QoS configuration). You will have to redefine your network PKEYs and QoS configuration (PKEY->GUIDs and QoS->GUIDs association) after applying the script. Are you sure you wish to proceed? [yes/no] yes</pre>
Related Commands	show ufm hca-grouping
Notes	To use this capability, it is recommended for users to use this command after performing software upgrade.

show ib hca-smp-window

	<pre>show ib hca-smp-window</pre> <p>Displays the configured maximum number of SMPs sent in HCA.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.4.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # show ib hca-smp-window Running configuration: 128 User configuration: 256 Please reload machine to load new configurations.</pre>

Related Commands	ib hca-smp-window
Notes	The example shows an instance where the system has not been rebooted after implementing new configuration

show ib hca-vl15-window

	<p>show ib hca-vl15-window</p> <p>Displays the configured HCA VL15 port receive buffer size.</p>
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.4.0
Example	<pre> UFM-APL [mgmt-ha-active] (config) # show ib hca-vl15-window Running configuration: 1 User configuration: 64 Please reload machine to load new configurations. </pre>
Related Commands	ib hca-vl15-window
Notes	The example shows an instance where the system has not been rebooted after implementing new configuration

show ufm hca-grouping

	<code>show ufm hca-grouping</code> Displays UFM HCA grouping configuration.
Syntax Description	N/A
Default	N/A
Configuration Mode	Any configuration mode
History	4.5.0
Example	<pre>UFM-APL [mgmt-ha-active] (config) # show ufm hca-grouping HCA grouping: Yes</pre>
Related Commands	<code>ufm hca-grouping enable</code>
Notes	

Document Revision History

Revision and	Date	Description
4.14.1	Dec 11, 2023	No changes
4.14.0	Nov 5, 2023	No changes
4.13.1	Aug 31, 2023	No changes
4.13.0	Aug 10, 2023	No changes
4.12.1	May 18, 2023	No changes
4.12.0	May 8, 2023	Updated: <ul style="list-style-type: none"> • show ib partition Added: <ul style="list-style-type: none"> • ib partition management mtu-limit <2K 4K> • ufm network-fast-recovery enable • show ufm network-fast-recovery
4.11.1	Feb 19, 2023	No changes
4.11.0	Feb 6, 2023	Added ufm unhealthy-ports switch-ports-threshold Updated example in show ufm unhealthy-ports
4.10.1	Dec, 2022	Added UFM Firmware Management
4.10.0	Oct, 2022	Added: <ul style="list-style-type: none"> • ufm process telemetry start • ufm process telemetry restart • no ufm process telemetry start • ufm process health restart • ufm process model restart • ufm process sharp restart • ib ibaddr • ib ibping • ib ibsysstat

Revision and	Date	Description
		<ul style="list-style-type: none"> • ib smparquery • ufm low-frequency-telemetry enable • no ufm low-frequency-telemetry enable • show ufm low-frequency-telemetry • ufm discovered-switch-ip-version • show ufm discovered-switch-ip-version
4.9.0	Jul, 2022	<p>Updated:</p> <ul style="list-style-type: none"> • Command ufm track-conf-changes enable • Command show ufm track-conf-changes
4.8.0	Apr, 2022	<p>Added:</p> <ul style="list-style-type: none"> • Command show ufm events • Command ufm events max-restored • Command ufm events persistency enable • Command no ufm events persistency enable • Command ufm track-conf-changes enable • Command show ufm track-conf-changes <p>Updated:</p> <ul style="list-style-type: none"> • Command ufm data backup • Command ufm multi-port-sm
4.7.0	Dec 3, 2021	<p>Added:</p> <ul style="list-style-type: none"> • Command file docker-label delete • Command ufm unhealthy-ports isolate-high-ber isolation-mode • Command show files docker-label • Command ufm high-ber-ports enable-warnings • Command show ufm high-ber-ports • Page UFM Plugin Commands <p>Updated:</p> <ul style="list-style-type: none"> • All commands under Telemetry • Command show ufm status output • Command show ufm unhealthy-ports • Command ib managed-switch ahx-monitor device

Revision and	Date	Description
		<ul style="list-style-type: none">• Command show ufm virtualization• Command ufm plugin• Command show ufm plugin

Notice

This document is provided for information purposes only and shall not be regarded as a warranty of a certain functionality, condition, or quality of a product. Neither NVIDIA Corporation nor any of its direct or indirect subsidiaries and affiliates (collectively: "NVIDIA") make any representations or warranties, expressed or implied, as to the accuracy or completeness of the information contained in this document and assumes no responsibility for any errors contained herein. NVIDIA shall have no liability for the consequences or use of such information or for any infringement of patents or other rights of third parties that may result from its use. This document is not a commitment to develop, release, or deliver any Material (defined below), code, or functionality.

NVIDIA reserves the right to make corrections, modifications, enhancements, improvements, and any other changes to this document, at any time without notice. Customer should obtain the latest relevant information before placing orders and should verify that such information is current and complete. NVIDIA products are sold subject to the NVIDIA standard terms and conditions of sale supplied at the time of order acknowledgement, unless otherwise agreed in an individual sales agreement signed by authorized representatives of NVIDIA and customer ("Terms of Sale"). NVIDIA hereby expressly objects to applying any customer general terms and conditions with regards to the purchase of the NVIDIA product referenced in this document. No contractual obligations are formed either directly or indirectly by this document.

NVIDIA products are not designed, authorized, or warranted to be suitable for use in medical, military, aircraft, space, or life support equipment, nor in applications where failure or malfunction of the NVIDIA product can reasonably be expected to result in personal injury, death, or property or environmental damage. NVIDIA accepts no liability for inclusion and/or use of NVIDIA products in such equipment or applications and therefore such inclusion and/or use is at customer's own risk.

NVIDIA makes no representation or warranty that products based on this document will be suitable for any specified use. Testing of all parameters of each product is not necessarily performed by NVIDIA. It is customer's sole responsibility to evaluate and determine the applicability of any information contained in this document, ensure the product is suitable and fit for the application planned by customer, and perform the necessary testing for the application in order to avoid a default of the application or the product. Weaknesses in customer's product designs may affect the quality and reliability of the NVIDIA product and may result in additional or different conditions and/or requirements beyond those contained in this document. NVIDIA accepts no liability related to any default, damage, costs, or problem which may be based on or attributable to: (i) the use of the NVIDIA product in any manner that is contrary to this document or (ii) customer product designs.

No license, either expressed or implied, is granted under any NVIDIA patent right, copyright, or other NVIDIA intellectual property right under this document. Information published by NVIDIA regarding third-party products or services does not constitute a license from NVIDIA to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property rights of the third party, or a license from NVIDIA under the patents or other intellectual property rights of NVIDIA.

Reproduction of information in this document is permissible only if approved in advance by NVIDIA in writing, reproduced without alteration and in full compliance with all applicable export laws and regulations, and accompanied by all associated conditions, limitations, and notices.

THIS DOCUMENT AND ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE. TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL NVIDIA BE LIABLE FOR ANY DAMAGES, INCLUDING WITHOUT LIMITATION ANY DIRECT,



INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF ANY USE OF THIS DOCUMENT, EVEN IF NVIDIA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Notwithstanding any damages that customer might incur for any reason whatsoever, NVIDIA's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms of Sale for the product.

Trademarks

NVIDIA, the NVIDIA logo, and Mellanox are trademarks and/or registered trademarks of NVIDIA Corporation and/or Mellanox Technologies Ltd. in the U.S. and in other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

© 2023 NVIDIA Corporation & affiliates. All Rights Reserved.

